

Documented Code for datatool v3.4

Nicola L. C. Talbot

<http://www.dickimaw-books.com/>

2025-04-03

1 Introduction

This is the documented code for the `datatool` bundle. See `datatool-user.pdf` for the main user manual.

2 `datatool-base.sty`

This package provides all the basic commands needed by various packages in the `datatool` bundle. The `datatool` package was first released in 2007. The \LaTeX kernel has changed significantly since then. I've started switching over to using $\text{\LaTeX}3$, but it's still in a hybrid state. I have too many large packages and not enough time to do a complete rewrite.

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```
\DeclareRelease{v2.32}{2019-09-27}{datatool-base-2019-09-27.sty}  
\DeclareCurrentRelease{v3.4}{2025-04-03}
```

Declare package:

```
\ProvidesPackage{datatool-base}[2025/04/03 v3.4 (NLCT)]
```

Required packages:

```
\RequirePackage{etoolbox}  
\RequirePackage{amsmath}  
\RequirePackage{xfor}  
\RequirePackage{ifthen}
```

`tracklang` now loaded as from v3.0. Ideally it needs to be v1.6.3+ but doesn't matter so much if no localisation support requested.

```
\RequirePackage{tracklang}[2022/12/13]
```

Removed `substr.sty`.

2.1 Package Options

Version 3.0 has switched to L^AT_EX3 key=value interface.

`\ifdtlverbose` Switch to govern verbose mode.

```
\newif\ifdtlverbose
```

`\if@dtl@utf8` Switch to determine UTF-8 setting. Deprecated.

```
\expandafter\newif\csname if@dtl@utf8\endcsname
```

`\TrackLangEncodingName` Check for `\TrackLangEncodingName`. This is used to input the appropriate encoding file, if available. If this command isn't available then it's likely that an old version of `tracklang` is installed.

```
\ExplSyntaxOn
\cs_if_exist:NF \TrackLangEncodingName
{
  \cs_if_exist:NTF \inputencodingname
  { \tl_set:NN \TrackLangEncodingName \inputencodingname }
  { \tl_set:Nn \TrackLangEncodingName { utf8 } }
}
```

Are we using a Unicode engine? (Affects regular expression matches with `x{<hex>}` for sort handler functions.)

```
\bool_lazy_any:nTF
{
  { \sys_if_engine luatex_p: }
  { \sys_if_engine xetex_p: }
  { \sys_if_engine uptex_p: }
}
{
  \cs_set_eq:NN \datatool_if_unicode_engine:TF \use_i:n
  \cs_set_eq:NN \datatool_if_unicode_engine:T \use_n
  \cs_set_eq:NN \datatool_if_unicode_engine:F \use_none:n
}
{
  \cs_set_eq:NN \datatool_if_unicode_engine:TF \use_ii:n
  \cs_set_eq:NN \datatool_if_unicode_engine:T \use_none:n
  \cs_set_eq:NN \datatool_if_unicode_engine:F \use_n
}
}
```

`\@dtl@mathprocessor` As from v3.0, the default processor is lua if `\direct lua` is defined or l3fp otherwise.

```
\ifdef\directlua
{\providecommand*\@dtl@mathprocessor}{lua}}
{\providecommand*\@dtl@mathprocessor}{l3fp}}
```

Determine whether or not to load locale support. This command will either expand to its argument or ignore it.

```
\newcommand\datatool@load@locales[1]{#1}
```

List of locales to track (in addition to any that might already be tracked):

```
\clist_new:N \l__datatool_extra_locales_clist
```

When to purify sort values:

```
\bool_new:N \l__datatool_initial_purify_early_bool
```

```
\bool_set_true:N \l__datatool_initial_purify_early_bool
```

List of types to reformat if auto-reformat settings are on:

```
\seq_new:N \l__datatool_auto_reformat_types_seq
```

```
\seq_set_from_clist:Nn \l__datatool_auto_reformat_types_seq  
{ integer , decimal , si , currency , datetime , date , time }
```

Append to sequence:

```
\cs_new:Nn \__datatool_auto_reformat_types_do:n
```

```
{  
  \tl_if_eq:nnTF { #1 } { integer }  
  {  
    \seq_put_right:Nn \l__datatool_auto_reformat_types_seq  
      { #1 }  
  }  
  {  
    \tl_if_eq:nnTF { #1 } { decimal }  
    {  
      \seq_put_right:Nn \l__datatool_auto_reformat_types_seq  
        { #1 }  
    }  
  }  
  {  
    \tl_if_eq:nnTF { #1 } { si }  
    {  
      \seq_put_right:Nn \l__datatool_auto_reformat_types_seq  
        { #1 }  
    }  
  }  
  {  
    \tl_if_eq:nnTF { #1 } { datetime }  
    {  
      \seq_put_right:Nn \l__datatool_auto_reformat_types_seq  
        { #1 }  
    }  
  }  
  {  
    \tl_if_eq:nnTF { #1 } { date }  
    {  
      \seq_put_right:Nn \l__datatool_auto_reformat_types_seq  
        { #1 }  
    }  
  }  
  {  
    \tl_if_eq:nnTF { #1 } { time }  
    {  
      \seq_put_right:Nn \l__datatool_auto_reformat_types_seq  
        { #1 }  
    }  
  }  
}
```



```

    }
    }
    { \prg_return_false: }
  }
}
{ \prg_return_false: }
}

```

Similarly, but data type under consideration is in \@dtl@datatype:

```

\prg_new_conditional:Npnn \__datatool_if_auto_reformat_on:
{ T, F, TF }
{
  \int_case:nnF { \@dtl@datatype }
  {
    { \c_datatool_integer_int }
    {
      \seq_if_in:NnTF
      \l__datatool_auto_reformat_types_seq
      { integer }
      {
        \bool_if:NTF \l__datatool_reformat_numeric_bool
        { \prg_return_true: }
        { \prg_return_false: }
      }
      { \prg_return_false: }
    }
  }
  { \c_datatool_decimal_int }
  {
    \seq_if_in:NnTF
    \l__datatool_auto_reformat_types_seq
    { decimal }
    {
      \bool_if:NTF \l__datatool_reformat_numeric_bool
      { \prg_return_true: }
      { \prg_return_false: }
    }
    { \prg_return_false: }
  }
}
{ \c_datatool_currency_int }
{
  \seq_if_in:NnTF
  \l__datatool_auto_reformat_types_seq
  { currency }
  {
    \bool_if:NTF \l__datatool_reformat_numeric_bool
    { \prg_return_true: }
    { \prg_return_false: }
  }
  { \prg_return_false: }
}
}

```

```

{ \c_datatool_datetime_int }
{
  \seq_if_in:NnTF
    \l__datatool_auto_reformat_types_seq
    { datetime }
    {
      \bool_if:NTF \l__datatool_reformat_datetime_bool
        { \prg_return_true: }
        { \prg_return_false: }
    }
    { \prg_return_false: }
}
}
{ \c_datatool_date_int }
{
  \seq_if_in:NnTF
    \l__datatool_auto_reformat_types_seq
    { date }
    {
      \bool_if:NTF \l__datatool_reformat_datetime_bool
        { \prg_return_true: }
        { \prg_return_false: }
    }
    { \prg_return_false: }
}
}
{ \c_datatool_time_int }
{
  \seq_if_in:NnTF
    \l__datatool_auto_reformat_types_seq
    { time }
    {
      \bool_if:NTF \l__datatool_reformat_datetime_bool
        { \prg_return_true: }
        { \prg_return_false: }
    }
    { \prg_return_false: }
}
}
}
{ \prg_return_false: }
}

```

Option definitions. Note that all packages in the datatool bundle now all use the same option group.

```

\keys_define:nn { datatool }
{
  verbose .legacy_if_set:n = dtlverbose,
  utf8 .legacy_if_set:n = @dtl@utf8,
  math .choices:nn = { fp, pgfmath, l3fp, lua }
                    { \tl_set_eq:NN \@dtl@mathprocessor \l_keys_choice_tl },
  math .usage:n = load,
  lang-warn .choice: ,
}

```

```

lang-warn / true .code:n =
{
  \cs_set_eq:NN \datatool_locale_warn:nn \PackageWarning
},
lang-warn / false .code:n =
{
  \PackageInfo
  {datatool-base}
  {
    localisation ~ warnings ~ switched ~
    off ~ (including ~ tracklang ~ warnings)
  }
  \cs_set_eq:NN \datatool_locale_warn:nn \use_none:nn
  \TrackLangShowWarningsfalse
},
lang-warn .default:n = true ,
lang-warn .initial:n = true ,
lang-warn .usage:n = load ,
nolocale .code:n =
{
  \cs_set_eq:NN \datatool@load@locales \use_none:n
  \clist_clear:N \l__datatool_extra_locales_clist
},
nolocale .value_forbidden:n = true,
nolocale .usage:n = load,
locales .code:n =
{
  \cs_set_eq:NN \datatool@load@locales \use:n
  \clist_set:Nn \l__datatool_extra_locales_clist { #1 }
},
locales .usage:n = load,

```

Synonym:

```

lang .code:n =
{
  \cs_set_eq:NN \datatool@load@locales \use:n
  \clist_set:Nn \l__datatool_extra_locales_clist { #1 }
},
lang .usage:n = load,
lists .code:n = { \keys_set:nn { datatool / lists } { #1 } },
initial-purify .choice:,
initial-purify / early .code:n =
{ \bool_set_true:N \l__datatool_initial_purify_early_bool },
initial-purify / late .code:n =
{ \bool_set_false:N \l__datatool_initial_purify_early_bool },
auto-reformat-types .code:n =
{
  \seq_clear:N \l__datatool_auto_reformat_types_seq
  \exp_args:Ne \clist_map_function:nN { #1 }
  \__datatool_auto_reformat_types_do:n
}

```

```

    } ,
    compare .code:n = { \keys_set:nn { datatool / compare } { #1 } },
    datetime .code:n = { \keys_set:nn { datatool / datetime } { #1 } },
    numeric .code:n = { \keys_set:nn { datatool / numeric } { #1 } },
}

```

Numeric options (new to v3.0).

Should numeric values be reformatted after parsing?

```
\bool_new:N \l__datatool_reformat_numeric_bool
```

```
\bool_set_false:N \l__datatool_reformat_numeric_bool
```

\DTLscinum Used with auto-reformat for scientific notation.

```
\IfPackageLoadedTF { siunitx }
```

```
{
  \newcommand \DTLscinum [ 1 ] { \num { #1 } }
}
```

```
{
  \newcommand \DTLscinum [ 1 ] { #1 }
  \AddToHook
  { package / siunitx / after }
  {
    \renewcommand \DTLscinum [ 1 ] { \num { #1 } }
  }
}
```

Should region files override the default number chars?

```
\bool_new:N \l_datatool_region_set_numberchars_bool
```

```
\bool_set_true:N \l_datatool_region_set_numberchars_bool
```

Should region files override the default currency?

```
\bool_new:N \l_datatool_region_set_currency_bool
```

```
\bool_set_true:N \l_datatool_region_set_currency_bool
```

\lcurrencyymbolprefixfmt

```
\newcommand{\datatoolcurrencyymbolprefixfmt}[1]{#1}
```

\DTLcurrCodeOrSymOrChar

```
\newcommand{\DTLcurrCodeOrSymOrChar}[3]{#2}
```

```
\keys_define:nn { datatool / numeric }
```

```
{
  auto-reformat .bool_set:N = \l__datatool_reformat_numeric_bool ,

```

This will also switch off any region number chars. Value needs to be in the form $\{\langle grp-char \rangle\}\{\langle decimal-char \rangle\}$

```
set-number-chars .code:n =
```

```
{
  \DTLsetnumberchars #1
  \bool_set_false:N \l_datatool_region_set_numberchars_bool
} ,
```

Should the region set the number group and decimal characters:

```

region-number-chars .choice: ,
region-number-chars / true .code:n =
{
  \bool_set_true:N \l_datatool_region_set_numberchars_bool
  \tl_if_empty:NF \l_datatool_current_region_tl
  {
    \cs_if_exist_use:cF
    { datatool \l_datatool_current_region_tl SetNumberChars }
    {
      \PackageWarning { datatool-base }
      {
        No ~ numberchars ~ hook ~ found ~ for ~ region ~
        ` \l_datatool_current_region_tl '
      }
    }
  }
},
region-number-chars / false .code:n =
{
  \bool_set_false:N \l_datatool_region_set_numberchars_bool
},
region-number-chars .default:n = true ,

```

Currency must already have been defined. This will also switch off any region currency.

```

set-currency .code:n =
{
  \tl_if_exist:cTF { dtl@curr@ \tl_to_str:n { #1 } @sym }
  {
    \tl_set:Ne \@dtl@currency { \exp_not:c { DTLcurr #1 } }
    \tl_set:Ne \DTLCurrencyCode { #1 }
    \tl_set:Ne \DTLfmtcurrency
    { \exp_not:c { dtl@curr@ #1 @fmt } }
    \bool_false:N \l_datatool_region_set_currency_bool
  }
  {
    \PackageError { datatool-base }
    {
      Currency ~ ` #1 ' ~ has ~ not ~ been ~ defined
    }
    {
      Currency ~ must ~ first ~ be ~ defined ~ with ~
      \tl_to_str:N \DTLdefcurrency
    }
  }
},
region-currency .choice: ,
region-currency / true .code:n =
{
  \bool_set_true:N \l_datatool_region_set_currency_bool
}

```

```

\tl_if_empty:NF \l_datatool_current_region_tl
{
  \cs_if_exist_use:cF
  { datatool \l_datatool_current_region_tl SetCurrency }
  {
    \PackageWarning { datatool-base }
    {
      No ~ currency ~ hook ~ found ~ for ~ region ~
      ` \l_datatool_current_region_tl '
    }
  }
}
},
region-currency / false .code:n =
{
  \bool_set_false:N \l_datatool_region_set_currency_bool
},
region-currency .default:n = true ,

```

Convenient method of redefining formatting command used by region files, but will only have an effect if the region uses it.

```

region-currency-prefix .choice: ,
region-currency-prefix / normal .code:n =
{
  \cs_set_eq:NN \datatoolcurrencysymbolprefixfmt \use:n
},
region-currency-prefix / smallcaps .code:n =
{
  \renewcommand \datatoolcurrencysymbolprefixfmt [ 1 ]
  {
    \exp_args:Ne \textsc { \text_lowercase:n { ##1 } }
  }
},
region-currency-prefix / smaller .code:n =
{
  \renewcommand \datatoolcurrencysymbolprefixfmt [ 1 ]
  {
    \textsmaller { ##1 }
  }
},

```

Redefine \DTLcurrCodeOrSymOrChar:

```

currency-symbol-style .choice:,
currency-symbol-style / iso .code:n =
{
  \cs_set_eq:NN \DTLcurrCodeOrSymOrChar \use_i:nnn
},
currency-symbol-style / symbol .code:n =
{
  \cs_set_eq:NN \DTLcurrCodeOrSymOrChar \use_ii:nnn
},

```

```

currency-symbol-style / string .code:n =
{
  \cs_set_eq:NN \DTLcurrCodeOrSymOrChar \use_iii:nnn
},
}

```

Date/time options (new to v3.0).

Should date/time values be parsed?

```

\bool_new:N \l__datatool_parse_datetime_bool
\bool_set_false:N \l__datatool_parse_datetime_bool

```

The next two conditionals are only relevant if the above is true. Should date/time values be parsed for ISO format?

```

\bool_new:N \l__datatool_parse_datetime_iso_bool
\bool_set_true:N \l__datatool_parse_datetime_iso_bool

```

Should date/time values be parsed for regional format? This will require the appropriate regional support.

```

\bool_new:N \l__datatool_parse_datetime_regional_bool
\bool_set_true:N \l__datatool_parse_datetime_regional_bool

```

Should parsed date/time values be reformatted?

```

\bool_new:N \l__datatool_reformat_datetime_bool
\bool_set_false:N \l__datatool_reformat_datetime_bool

```

```

\DTLCurrentLocaleFormatDate{<YYYY>}{<MM>}{<DD>}{<DOW>}

```

LCurrentLocaleFormatDate

Localisation support should redefine this.

```

\newcommand \DTLCurrentLocaleFormatDate [4]
{
  \datatool_default_date_fmt:nnnn { #1 } { #2 } { #3 } { #4 }
}

\cs_new_nopar:Nn \datatool_default_date_fmt:nnnn
{
  \cs_if_exist:NTF \DTMdisplaydate
  {
    \tl_if_empty:nTF { #4 }
    {
      \DTMdisplaydate { #1 } { #2 } { #3 } { -1 }
    }
    {
      \DTMdisplaydate { #1 } { #2 } { #3 } { #4 }
    }
  }
  {
    \datatool_date_iso_fmt:nnnn { #1 } { #2 } { #3 } { #4 }
  }
}

```

\DataToolDateFmt

\DataToolDateFmt{<YYYY>}{<MM>}{<DD>}{<DOW>}

```
\newcommand \DataToolDateFmt [4]
{
  \DTLCurrentLocaleFormatDate { #1 } { #2 } { #3 } { #4 }
}

The following has a fourth argument for consistency.
\cs_new_nopar:Nn \datatool_date_iso_fmt:nnnn
{
  \datatool_date_iso_fmt:nnn { #1 } { #2 } { #3 }
}
\cs_new_nopar:Nn \datatool_date_iso_fmt:nnn
{
  \int_eval:n { #1 }
  - \datatool_two_digits:n { #2 }
  - \datatool_two_digits:n { #3 }
}
```

Localisation support should redefine this.

\DTLCurrentLocaleFormatDate{<hh>}{<mm>}{<ss>}

```
\newcommand \DTLCurrentLocaleFormatTime [3]
{
  \datatool_default_time_fmt:nnn { #1 } { #2 } { #3 }
}

\cs_new_nopar:Nn \datatool_default_time_fmt:nnn
{
  \cs_if_exist:NTF \DTMdisplaytime
  {
    \tl_if_empty:nTF { #3 }
    {
      \DTMdisplaytime { #1 } { #2 } { 0 }
    }
    {
      \DTMdisplaytime { #1 } { #2 } { #3 }
    }
  }
  {
    \datatool_time_iso_fmt:nnn { #1 } { #2 } { #3 }
  }
}
```

\DataToolTimeFmt

\DataToolTimeFmt{<hh>}{<mm>}{<ss>}

```

\newcommand \DataToolTimeFmt [3]
{
  \DTLCurrentLocaleFormatTime { #1 } { #2 } { #3 }
}

\cs_new_nopar:Nn \datatool_time_iso_fmt:nnn
{
  \datatool_two_digits:n { #1 }
  \c_colon_str
  \datatool_two_digits:n { #2 }
  \tl_if_empty:nF { #3 }
  {
    \c_colon_str
    \datatool_two_digits:n { #3 }
  }
}

```

\DTLCurrentLocaleFormatTimeZone{<TZh>}{<TZm>}

rentLocaleFormatTimeZone

```

\newcommand \DTLCurrentLocaleFormatTimeZone [2]
{
  \datatool_default_timezone_fmt:nn { #1 } { #2 }
}

\cs_new:Nn \datatool_default_timezone_fmt:nn
{
  \cs_if_exist:NTF \DTMdisplayzone
  {
    \DTMdisplayzone { #1 } { #2 }
  }
  {
    \datatool_timezone_iso_fmt:nn { #1 } { #2 }
  }
}

```

\DataToolTimeZoneFmt{<TZh>}{<TZm>}

\DataToolTimeZoneFmt

```

\newcommand \DataToolTimeZoneFmt [2]
{
  \DTLCurrentLocaleFormatTimeZone { #1 } { #2 }
}

\cs_new_nopar:Nn \datatool_timezone_iso_fmt:nn
{
  \datatool_signed_two_digits:n { #1 }
  \c_colon_str
  \datatool_two_digits:n { #2 }
}

```

entLocaleTimeStampFmtSep Localisation files may redefine this.

```
\newcommand \DTLCurrentLocaleTimeStampFmtSep { ~ }
```

\DataToolTimeStampFmtSep Separator used in \datatool_default_timestamp_fmt:nnnnnnn between the date and time. Defaults to a space.

```
\newcommand \DataToolTimeStampFmtSep
{
  \DTLCurrentLocaleTimeStampFmtSep
}
```

```
\DataToolDateTimeFmt{<date-args>}{<time-args>}
{<time-zone-args>}
```

\DataToolDateTimeFmt

The *<date-args>* argument may either be empty or in the form `{<YYYY>}{<MM>}{<DD>}{<DOW>}` appropriate for `\DataToolDateFmt`. The *<time-args>* argument may either be empty or in the form `{<hh>}{<mm>}{<ss>}` appropriate for `\DataToolTimeFmt`. The *<time-zone-args>* argument may either be empty or in the form `{<TZh>}{<TZm>}` appropriate for `\DataToolTimeZoneFmt`.

```
\newcommand* \DataToolDateTimeFmt [3]
{
  \tl_if_empty:nTF { #1 }
  {
```

No date arguments.

```
  \tl_if_empty:nF { #2 }
  {
```

Time arguments provided. (There should be three.)

```
    \DataToolTimeFmt #2
  }
  \tl_if_empty:nF { #3 }
  {
```

Time zone arguments provided. (There should be two.)

```
    \DataToolTimeZoneFmt #3
  }
}
```

Date arguments provided. (There should be four.)

```
  \tl_if_empty:nTF { #2 }
  {
```

No time arguments provided.

```
    \DataToolDateFmt #1
  }
}
```

Time arguments provided. (There should be three.)

```
\tl_if_empty:nTF { #3 }  
{
```

No time zone arguments provided.

```
\DataToolTimeStampNoZoneFmt #1 #2  
}  
{
```

Time zone arguments provided. (There should be two.)

```
\DataToolTimeStampWithZoneFmt #1 #2 #3  
}  
}  
}
```

```
\DataToolTimeStampWithZoneFmt{<YYYY>}{<MM>}{<DD>}  
{<DOW>}  
{<hh>}{<mm>}{<ss>}
```

ToolTimeStampWithZoneFmt

```
\newcommand \DataToolTimeStampWithZoneFmt [9]  
{  
  \DTLCurrentLocaleFormatTimeStampWithZone  
  { #1 } { #2 } { #3 } { #4 } { #5 } { #6 } { #7 } { #8 } { #9 }  
}
```

```
\DataToolTimeStampNoZoneFmt{<YYYY>}{<MM>}{<DD>}{<DOW>}  
{<hh>}{<mm>}{<ss>}
```

taToolTimeStampNoZoneFmt

```
\newcommand \DataToolTimeStampNoZoneFmt [7]  
{  
  \DTLCurrentLocaleFormatTimeStampNoZone  
  { #1 } { #2 } { #3 } { #4 } { #5 } { #6 } { #7 }  
}  
  
\cs_new_nopar:Nn \datatool_default_timestamp_fmt:nnnnnn  
{  
  \cs_if_exist:NTF \DTMdisplay  
  {
```

The `datetime2` style will need to have the zone suppressed with `showzone=false` (if supported by the current style).

```
\tl_if_empty:nTF { #4 }  
{  
  \DTMdisplay
```

```

        { #1 } { #2 } { #3 } { -1 }
        { #5 } { #6 } { #7 }
        { 0 } { 0 }
    }
    {
        \DTMdisplay
        { #1 } { #2 } { #3 } { #4 }
        { #5 } { #6 } { #7 }
        { 0 } { 0 }
    }
}
{
    \datatool_default_date_fmt:nnnn
    { #1 } { #2 } { #3 } { #4 }
    \DataToolTimeStampFmtSep
    \datatool_default_time_fmt:nnn
    { #5 } { #6 } { #7 }
}
}
\cs_new_nopar:Nn \datatool_default_timestamp_fmt:nnnnnnnn
{
    \cs_if_exist:NTF \DTMdisplay
    {
        \tl_if_empty:nTF { #4 }
        {
            \DTMdisplay
            { #1 } { #2 } { #3 } { -1 }
            { #5 } { #6 } { #7 }
            { #8 } { #9 }
        }
        {
            \DTMdisplay
            { #1 } { #2 } { #3 } { #4 }
            { #5 } { #6 } { #7 }
            { #8 } { #9 }
        }
    }
}
{
    \datatool_default_timestamp_fmt:nnnnnnn
    { #1 } { #2 } { #3 } { #4 }
    { #5 } { #6 } { #7 }
    \datatool_default_timezone_fmt:nn
    { #8 } { #9 }
}
}
\cs_new_nopar:Nn \datatool_timestamp_iso_fmt:nnnnnnn
{
    \datatool_date_iso_fmt:nnnn { #1 } { #2 } { #3 } { #4 }
}
T

```

```

\datatool_time_iso_fmt:nnn { #5 } { #6 } { #7 }
}
\cs_new_nopar:Nn \datatool_timestamp_iso_fmt:nnnnnnnnn
{
\datatool_timestamp_iso_fmt:nnnnnnn
{ #1 } { #2 } { #3 } { #4 }
{ #5 } { #6 } { #7 }
\datatool_timezone_iso_fmt:nn { #8 } { #9 }
}

```

```

\DTLCurrentLocaleFormatTimeStampWithZone{<YYYY>}
{<MM>}{<DD>}{<DOW>}
{<hh>}{<mm>}{<ss>}{<tzh>}{<tzm>}

```

eFormatTimeStampWithZone

Localisation support should redefine this.

```

\newcommand \DTLCurrentLocaleFormatTimeStampWithZone [9]
{
\datatool_default_timestamp_fmt:nnnnnnnnn
{ #1 } { #2 } { #3 } { #4 } { #5 } { #6 } { #7 } { #8 } { #9 }
}

```

```

\DTLCurrentLocaleFormatTimeStampNoZone{<YYYY>}{<MM>}
{<DD>}{<DOW>}
{<hh>}{<mm>}{<ss>}

```

aLeFormatTimeStampNoZone

Localisation support should redefine this.

```

\newcommand \DTLCurrentLocaleFormatTimeStampNoZone [7]
{
\datatool_default_timestamp_fmt:nnnnnnn
{ #1 } { #2 } { #3 } { #4 } { #5 } { #6 } { #7 }
}

\keys_define:nn { datatool / datetime }
{
parse .choice:,
parse / false .code:n =
{
\bool_set_false:N \l__datatool_parse_datetime_bool
} ,
parse / true .code:n =
{
\bool_set_true:N \l__datatool_parse_datetime_bool
} ,
parse / parse-only .code:n =
{
\bool_set_true:N \l__datatool_parse_datetime_bool
}
}

```

```

    \bool_set_false:N \l__datatool_reformat_datetime_bool
  } ,
parse / auto-reformat .code:n =
{
  \bool_set_true:N \l__datatool_parse_datetime_bool
  \bool_set_true:N \l__datatool_reformat_datetime_bool
} ,
parse / iso-only .code:n =
{
  \bool_set_true:N \l__datatool_parse_datetime_bool
  \bool_set_true:N \l__datatool_parse_datetime_iso_bool
  \bool_set_false:N \l__datatool_parse_datetime_regional_bool
} ,
parse / region-only .code:n =
{
  \bool_set_true:N \l__datatool_parse_datetime_bool
  \bool_set_false:N \l__datatool_parse_datetime_iso_bool
  \bool_set_true:N \l__datatool_parse_datetime_regional_bool
} ,
parse / iso + region .code:n =
{
  \bool_set_true:N \l__datatool_parse_datetime_bool
  \bool_set_true:N \l__datatool_parse_datetime_iso_bool
  \bool_set_true:N \l__datatool_parse_datetime_regional_bool
} ,
parse .default:n = true ,
auto-reformat .choice: ,
auto-reformat / false .code:n =
{
  \bool_set_false:N \l__datatool_reformat_datetime_bool
} ,
auto-reformat / true .code:n =
{
  \bool_set_true:N \l__datatool_reformat_datetime_bool
} ,
auto-reformat / region .code:n =
{
  \bool_set_true:N \l__datatool_reformat_datetime_bool
  \renewcommand \DataToolDateFmt [ 4 ]
  {
    \DTLCurrentLocaleFormatDate { ##1 } { ##2 } { ##3 } { ##4 }
  }
  \renewcommand \DataToolTimeFmt [ 3 ]
  {
    \DTLCurrentLocaleFormatTime { ##1 } { ##2 } { ##3 }
  }
  \renewcommand \DataToolTimeZoneFmt [ 2 ]
  {
    \DTLCurrentLocaleFormatTimeZone { ##1 } { ##2 }
  }
}

```

```

\renewcommand \DataToolTimeStampWithZoneFmt [ 9 ]
{
  \DTLCurrentLocaleFormatTimeStampWithZone
  { ##1 } { ##2 } { ##3 } { ##4 }
  { ##5 } { ##6 } { ##7 }
  { ##8 } { ##9 }
}
\renewcommand \DataToolTimeStampNoZoneFmt [ 7 ]
{
  \DTLCurrentLocaleFormatTimeStampNoZone
  { ##1 } { ##2 } { ##3 } { ##4 }
  { ##5 } { ##6 } { ##7 }
}
\renewcommand \DataToolTimeStampFmtSep
{
  \DTLCurrentLocaleTimeStampFmtSep
}
} ,
auto-reformat / iso .code:n =
{
  \bool_set_true:N \__datatool_reformat_datetime_bool
  \renewcommand \DataToolDateFmt [ 4 ]
  {
    \datatool_date_iso_fmt:nnnn
    { ##1 } { ##2 } { ##3 } { ##4 }
  }
  \renewcommand \DataToolTimeFmt [ 3 ]
  {
    \datatool_time_iso_fmt:nnn
    { ##1 } { ##2 } { ##3 }
  }
  \renewcommand \DataToolTimeZoneFmt [ 2 ]
  {
    \datatool_timezone_iso_fmt:nn
    { ##1 } { ##2 }
  }
  \renewcommand \DataToolTimeStampWithZoneFmt [ 9 ]
  {
    \datatool_timestamp_iso_fmt:nnnnnnnn
    { ##1 } { ##2 } { ##3 } { ##4 }
    { ##5 } { ##6 } { ##7 }
    { ##8 } { ##9 }
  }
  \renewcommand \DataToolTimeStampNoZoneFmt [ 7 ]
  {
    \datatool_timestamp_iso_fmt:nnnnnn
    { ##1 } { ##2 } { ##3 } { ##4 }
    { ##5 } { ##6 } { ##7 }
  }
} ,

```

```

auto-reformat / datetime2 .code:n =
{
  \cs_if_exist:NTF \DTLdisplay
  {
    \bool_set_true:N \l_datatool_reformat_datetime_bool
    \renewcommand \DataToolDateFmt [ 4 ]
    {
      \tl_if_empty:nTF { ##4 }
      {
        \DTMdisplaydate { ##1 } { ##2 } { ##3 } { -1 }
      }
      {
        \DTMdisplaydate { ##1 } { ##2 } { ##3 } { ##4 }
      }
    }
  }
  \renewcommand \DataToolTimeFmt [ 3 ]
  {
    \tl_if_empty:nTF { ##3 }
    {
      \DTMdisplaytime { ##1 } { ##2 } { 0 }
    }
    {
      \DTMdisplaytime { ##1 } { ##2 } { ##3 }
    }
  }
  \renewcommand \DataToolTimeZoneFmt [ 2 ]
  {
    \DTMdisplayzone { ##1 } { ##2 }
  }
  \renewcommand \DataToolTimeStampWithZoneFmt [ 9 ]
  {
    \tl_if_empty:nTF { ##4 }
    {
      \DTMdisplay
      { ##1 } { ##2 } { ##3 } { -1 }
      { ##5 } { ##6 } { ##7 }
      { ##8 } { ##9 }
    }
    {
      \DTMdisplay
      { ##1 } { ##2 } { ##3 } { ##4 }
      { ##5 } { ##6 } { ##7 }
      { ##8 } { ##9 }
    }
  }
  \renewcommand \DataToolTimeStampNoZoneFmt [ 7 ]
  {
    \tl_if_empty:nTF { ##4 }
    {
      \DTMdisplay

```

```

        { ##1 } { ##2 } { ##3 } {-1 }
        { ##5 } { ##6 } { ##7 }
        { 0 } { 0 }
    }
    {
    \DTMdisplay
    { ##1 } { ##2 } { ##3 } { ##4 }
    { ##5 } { ##6 } { ##7 }
    { 0 } { 0 }
    }
}
}
{
\PackageError { datatool-base }
{
    Option ~ datetime ~ = ~ { ~ auto-reformat ~ = ~ datetime2 ~ } ~
    requires ~ datetime2 ~ package
}
{
    You ~ need ~ to ~ load ~ datetime2.sty ~ before ~ you ~
    set ~ this ~ option
}
}
} ,
auto-reformat .default:n = false ,
}

```

List options (new to v3.0).

If true, trim leading and trailing space around elements in the list-related commands below. Note the default changes the behaviour as from v3.0.

`\bool_new:N \l_datatool_list_trim_bool`

Reverse sort CSV lists:

`\bool_new:N \l_datatool_sort_reverse_bool`

Preprocess to create datum elements when sorting CSV lists:

`\bool_new:N \l_datatool_sort_datum_bool`

`\DTLlistand` Use either `\DTLlandname` or `\&` in lists. (No difference if no language support provided.)

`\bool_new:N \l_datatool_list_and_bool`

`\bool_set_true:N \l_datatool_list_and_bool`

`\newcommand \DTLlistand`

```

{
    \bool_if:NTF \l_datatool_list_and_bool
    { \DTLlandname }
    { \& }
}

```

`\ifDTLlistskipempty` If true, skip empty elements in the list-related commands below.

```

\newif\ifDTLlistskipempty
\DTLlistskipemptytrue

\keys_define:nn { datatool / lists }
{
  skip-empty .legacy_if_set:n = DTLlistskipempty ,
  trim .bool_set:N = \l_datatool_list_trim_bool ,
  trim .initial:n = true ,
  sort-reverse .bool_set:N = \l_datatool_sort_reverse_bool ,
  sort-reverse .initial:n = false ,
  sort-datum .bool_set:N = \l_datatool_sort_datum_bool ,
  sort-datum .initial:n = false ,
  and .choice: ,
  and / word .code:n =
  {
    \bool_true:N \l_datatool_list_and_bool
  } ,
  and / symbol .code:n =
  {
    \bool_false:N \l_datatool_list_and_bool
  } ,
}

```

String comparison options.

`\ifdtlcompareskipcs` If true, `\dtlcompare` should skip control sequences.

```

\newif\ifdtlcompareskipcs
\dtlcompareskipcsfalse

  If the following boolean is true, \dtlcompare should expand control sequences.
\bool_new:N \l_datatool_compare_expand_cs_bool
\keys_define:nn { datatool / compare }
{
  expand-cs .bool_set:N = \l_datatool_compare_expand_cs_bool,
  skip-cs .legacy_if_set:n = dtlcompareskipcs,
}

```

`\DTLsetup` Provide user interface command to set options later.

```

\DeclareDocumentCommand \DTLsetup { m }
{ \keys_set:nn { datatool } { #1 } }

```

Use `\DTLsetLocaleOptions` for options provided by localisation files.

```

\ExplSyntaxOff

```

Process options:

```

\ProcessKeyOptions[datatool]

```

Load file dealing with numerical processes. As from version 3.0, these are in def files not packages.

```

\InputIfFileExists

```

```

{datatool-\@dtl@mathprocessor.def}
{}
{
  \InputIfFileExists
  {datatool-l3fp.def}
  {
    \PackageError{datatool}
    {%
      Missing file `datatool-\@dtl@mathprocessor.def'
      for math=\@dtl@mathprocessor. Falling back on
      math=l3fp
    }
    {%
      Check that your TeX distribution contains the file
      `datatool-\@dtl@mathprocessor.def'
    }
  }
}
{
  \PackageError{datatool}
  {%
    Missing file `datatool-\@dtl@mathprocessor.def'
    for math=\@dtl@mathprocessor. No math commands
    available!
  }
  {%
    Something is wrong with the datatool installation
  }
}
}
}

```

2.2 Utilities

`\dtl@message{message string}`

`\dtl@message`

Displays message only if the verbose option is set.

```

\newcommand*{\dtl@message}[1]{%
  \ifdtlverbose\typeout{#1}\fi
}

```

`\@dtl@toks`

`\newtoks\@dtl@toks`

`\@dtl@tmpcount` Define temporary count register

`\newcount\@dtl@tmpcount`

`\dtl@tmplength` Define temporary length register. TODO: rename `\l__datatool_tmp_dim?`

`\newlength\dtl@tmplength`

Provide a way of measuring the height of text with problematic commands locally disabled:

```
\ExplSyntaxOn
\cs_new:Nn \datatool_measure_height:Nn
{
  NB \settoheight automatically scopes the content.
  \settoheight #1 { \l_datatool_measure_hook_tl #2 }
}
\cs_new:Nn \datatool_measure_width:Nn
{
  \settowidth #1 { \l_datatool_measure_hook_tl #2 }
}
\cs_new:Nn \datatool_measure_depth:Nn
{
  \settodepth #1 { \l_datatool_measure_hook_tl #2 }
}
```

```
\datatool_measure:NNNn <wd-dim> <ht-dim>
<dp-dim> {<text>}
```

Measure all dimensions.

```
\cs_new:Nn \datatool_measure:NNNn
{
  \hbox_set:Nn \l__datatool_measure_box
  { \l_datatool_measure_hook_tl #4 }
  \dim_set:Nn #1 { \box_wd:N \l__datatool_measure_box }
  \dim_set:Nn #2 { \box_ht:N \l__datatool_measure_box }
  \dim_set:Nn #3 { \box_dp:N \l__datatool_measure_box }
}
```

```
\datatool_measure_ht_plus_dp:Nn <dim> {<text>}
```

Measure the height plus depth.

```
\cs_new:Nn \datatool_measure_ht_plus_dp:Nn
{
  \hbox_set:Nn \l__datatool_measure_box
  { \l_datatool_measure_hook_tl #2 }
  \dim_set:Nn #1
  {
    \box_ht:N \l__datatool_measure_box
    + \box_dp:N \l__datatool_measure_box
  }
}
\box_new:N \l__datatool_measure_box
```

Hook:

```
\tl_new:N \l_datatool_measure_hook_tl
```

```

\tl_set:Nn \l_datatool_measure_hook_tl
{
  \cs_set_eq:NN \label \use_none:n
  \cs_set_eq:NN \ref \use_none:n
  \cs_set_eq:NN \pageref \use_none:n
  \cs_set_eq:NN \refstepcounter \__datatool_local_stepcounter:n
  \cs_set_eq:NN \stepcounter \__datatool_local_stepcounter:n
  \cs_set_eq:NN \hypertarget \use_ii:nn
  \cs_set_eq:NN \hyperlink \use_ii:nn
}

```

Local step counter for use in the above. This doesn't trigger an error if the counter is undefined nor does it reset dependent counter.

```

\cs_new:Nn \__datatool_local_stepcounter:n
{
  \int_if_exist:cT { c@ #1 } { \int_incr:c { c@ #1 } }
}

```

Swap values in integer variables:

```

\cs_new:Nn \datatool_swap_ints:NN
{
  \exp_args:Nee \__datatool_swap_ints:nnNN
  { \int_use:N #1 } { \int_use:N #2 } #1 #2
}
\cs_new:Nn \__datatool_swap_ints:nnNN
{
  \int_set:Nn #3 { #2 }
  \int_set:Nn #4 { #1 }
}

```

`\dtlifintopenbetween{<num>}{<min>}{<max>}{<true part>}{<false part>}`

`\dtlifintopenbetween`

If the values may be decimal, use `\dtlifnumopenbetween` instead.

Version 3.0 rewritten to use L^AT_EX3 commands. This means it can now fully expand.

```

\newcommand{\dtlifintopenbetween}[5]{%
  \bool_lazy_and:nnTF
  { \int_compare_p:nNn { #1 } > { #2 } }
  { \int_compare_p:nNn { #1 } < { #3 } }
  { #4 } { #5 }
}

```

`\dtlifintclosedbetween{<num>}{<min>}{<max>}{<true part>}{<false part>}`

`\dtlifintclosedbetween`

If the values may be decimal, use `\dtlifnumclosedbetween` instead.

Version 3.0 rewritten to use L^AT_EX3 commands. This means it can now fully expand. It's simpler to perform the reverse test (if outside the range).

```
\newcommand{\dtlifintclosedbetween}[5]{%
  \bool_lazy_or:nnTF
    { \int_compare_p:nNn { #1 } < { #2 } }
    { \int_compare_p:nNn { #1 } > { #3 } }
  { #5 } { #4 }
}
```

This is mainly for formatting time zone hours with a required leading sign:

```
\cs_new:Nn \datatool_signed_two_digits:n
{
  \int_compare:nNnTF { #1 } < { \c_zero_int }
  {
    - \datatool_two_digits:e { \int_abs:n { #1 } }
  }
  {
    + \datatool_two_digits:n { #1 }
  }
}
```

Expanding first reduces computations if the argument is an expression rather than just a number.

```
\cs_generate_variant:Nn \datatool_signed_two_digits:n { e, V }
```

Argument an integer variable:

```
\cs_new:Nn \datatool_signed_two_digits:N
{
  \int_compare:nNnTF { #1 } < { \c_zero_int }
  {
    - \datatool_two_digits:e { \int_abs:n { #1 } }
  }
  {
    + \datatool_two_digits:N #1
  }
}
```

Similar but omit sign for positive numbers. Note that `\two@digits` can discard a following space since it uses `\number`. This is avoided here by using `\int_eval:n`.

```
\cs_new:Nn \datatool_two_digits:n
{
  \int_compare:nNnTF { #1 } < { \c_zero_int }
  {
    - \datatool_two_digits:e { \int_abs:n { #1 } }
  }
  {
    \int_compare:nNnT { #1 } < { 10 } { 0 }
    \int_eval:n { #1 }
  }
}
\cs_generate_variant:Nn \datatool_two_digits:n { e, V }
```

Argument an integer variable:

```
\cs_new:Nn \datatool_two_digits:N
{
  \int_compare:nNnTF { #1 } < { \c_zero_int }
  {
    - \datatool_two_digits:e { \int_abs:n { #1 } }
  }
  {
    \int_compare:nNnT { #1 } < { 10 } { 0 }
    \int_use:N #1
  }
}
```

`\dtlpadleadingzeros{<num-digits>}{<value>}`

`\dtlpadleadingzeros`

Pad leading zeros. This is designed for sorting numbers by character code (and so needs to be expandable). Zero-padding helps place them in numeric order. The `<num-digits>` argument should be between 1 and 6.

```
\newcommand{\dtlpadleadingzeros}[2]{
  \fp_compare:nNnTF { #2 } < { \c_zero_fp }
  { \dtlpadleadingzerosminus } { \dtlpadleadingzerosplus }
  \__datatool_int_leading_zeros:ee
  { \int_eval:n { #1 } }
  { \fp_to_int:n { floor ( abs ( #2 ) ) } }
  \fp_to_decimal:n { abs ( #2 ) }
}
```

`\dtlpadleadingzerosminus`

```
\newcommand{\dtlpadleadingzerosminus}{-}
```

`\dtlpadleadingzerosplus`

```
\newcommand{\dtlpadleadingzerosplus}{+}
```

```
\cs_new:Nn \__datatool_int_leading_zeros:nn
{
  \bool_lazy_and:nnTF
  { \int_compare_p:nNn { #1 } > { \c_one_int } }
  { \int_compare_p:nNn { #2 } < { 10 } }
  { \prg_replicate:nn { #1 - \c_one_int } { 0 } }
  {
    \bool_lazy_and:nnTF
    { \int_compare_p:nNn { #1 } > { 2 } }
    { \int_compare_p:nNn { #2 } < { 100 } }
    { \prg_replicate:nn { #1 - 2 } { 0 } }
    {
      \bool_lazy_and:nnTF
      { \int_compare_p:nNn { #1 } > { 3 } }
      { \int_compare_p:nNn { #2 } < { 1000 } }
    }
  }
}
```



```

{
  \tl_set:Nn #3 { #1 }
  \tl_set:Nn #4 { #2 }
}

```

2.2.1 General List Utilities

`\@dtl@assigntmpseq` Assign `__datatool_tmp_seq` taking into account the trim spaces and skip empty elements settings. The argument may be a single token (a command whose definition is a comma-separated list), in which case it will be expanded once, or the argument should be a comma-separated list. Any nested use will need to be scoped.

```

\newcommand{\@dtl@assigntmpseq}[1]{
  \tl_if_single_token:nTF { #1 }
  {
    \exp_args:No \__datatool_create_tmp_list:n { #1 }
  }
  {
    \__datatool_create_tmp_list:n { #1 }
  }
}
\cs_new:Nn \__datatool_create_tmp_list:n
{
  \bool_if:NTF \__datatool_list_trim_bool
  {
    \seq_set_from_clist:Nn \__datatool_tmp_seq { #1 }
  }
  {
    \seq_set_split_keep_spaces:Nnn \__datatool_tmp_seq { , } { #1 }
  }
  \ifDTLlistskipempty
  \seq_remove_all:Nn \__datatool_tmp_seq {}
  \fi
}

```

```

\DTLifinlist{<element>}{<list>}{<true part>}{<false
part>}

```

`\DTLifinlist`

If *<element>* is contained in the comma-separated list given by *<list>*, then do *<true part>* otherwise do false part. The *<list>* may be a command whose definition is a comma-separated list. Rewritten in v3.0 to use L^AT_EX3. This is fractionally slower than the old definition but more reliable.

```

\newcommand*{\DTLifinlist}[4]{
  \@dtl@assigntmpseq{#2}
  \seq_if_in:NnTF \__datatool_tmp_seq { #1 } { #3 } { #4 }
}

```

`\DTLlistelement`

`\DTLlistelement{<list>}{<idx>}`

Does the `<idx>`th element in the list. The index should start from 1 for the first element.

```
\newrobustcmd{\DTLlistelement}[2]{%
  \@dtl@assigntmpseq{#1}
  \seq_item:Nn \l_datatool_tmp_seq { #2 }
}
```

`\DTLfetchlistelement`

`\DTLfetchlistelement{<list>}{<idx>}{<cs>}`

Fetches the `<idx>`th element in the list and stores in `<cs>`. The index should start from 1 for the first element.

```
\newrobustcmd{\DTLfetchlistelement}[3]{%
  \@dtl@assigntmpseq{#1}
  \tl_set:Nx #3 { \seq_item:Nn \l_datatool_tmp_seq { #2 } }
}
```

`\DTLnumitemsinlist`

`\DTLnumitemsinlist{<list>}{<cmd>}`

Counts number of elements in list and stores result in control sequence `<cmd>`.

```
\newrobustcmd{\DTLnumitemsinlist}[2]{%
  \@dtl@assigntmpseq{#1}
  \tl_set:Nx #2 { \seq_count:N \l_datatool_tmp_seq }
}
```

`DefaultLocaleWordHandler`

```
\newcommand{\DTLDefaultLocaleWordHandler}[1]{%
  \DTLCurrentLocaleWordHandler{#1}%
  \appto#1{\datatoolctrlboundary}%
}
```

`CurrentLocaleWordHandler`

```
\newcommand{\DTLCurrentLocaleWordHandler}[1]{}
```

```
\ExplSyntaxOff
```

The original sorting algorithm required a comparison command. This isn't a problem for a simple case-sensitive character code sort, but it's less efficient if the sort value needs to be obtained by processing the original value. If this is done by the comparison command, then it has to be done every time a comparison is made (for both values). It's more efficient to process the sort values first and then sort, but this means keeping track of the original value.

Provide a convenient way of locally redefining commands while obtaining the sort value.

`\dtlSortWordCommands`

```
\newcommand*{\dtlSortWordCommands}{%  
  \begingroup\makeatletter  
  \dtl@SortWordCommands  
}
```

`\dtl@SortWordCommands`

```
\newcommand{\dtl@SortWordCommands}[1]{%  
  \gappto\dtl@SortWordCommands@hook{#1}%  
  \endgroup  
}
```

`\datatoolasciistart` Does nothing but influences sorting.

```
\newcommand{\datatoolasciistart}{}
```

`\datatoolasciend` Does nothing but influences sorting.

```
\newcommand{\datatoolasciend}{}
```

`\datatoolctrlboundary` Does nothing but influences sorting.

```
\newcommand{\datatoolctrlboundary}{}
```

`\dtltextorsort`

```
\newcommand{\dtltextorsort}[2]{#1}
```

`\dtl@SortWordCommands@hook`

```
\begingroup  
\ExplSyntaxOn  
\char_set_catcode_other:n {0}  
\char_set_catcode_other:n {28}  
\char_set_catcode_other:n {29}  
\char_set_catcode_other:n {30}  
\char_set_catcode_other:n {31}  
\char_set_catcode_other:n {127}  
\ExplSyntaxOff  
\gdef\dtl@SortWordCommands@hook{%  
  \def\datatoolasciistart{^^@}%  
  \def\datatoolpersoncomma{^^1c}%  
  \def\datatoolplacecomma{^^1d}%  
  \def\datatoolsubjectcomma{^^1e}%  
  \def\datatoolparenstart{^^1f}%  
  \def\datatoolctrlboundary{^^1f}%  
  \def\datatoolparen{\datatoolctrlboundary\@gobble}%  
  \def\datatoolasciend{^^7f}%  
  \let\nobreakspace\space  
  \let\ \space  
  \edef\${\expandafter\@gobble\string\}$%  
  \edef\_ {\expandafter\@gobble\string\_}%  
  \edef\# {\expandafter\@gobble\string\#}%  
  \edef\% {\expandafter\@gobble\string\}%
```

```

\edef\&\expandafter\@gobble\string\&}%
\let\dtl\textsort\@secondoftwo
\def\TeX{TeX}%
\def\LaTeX{LaTeX}%
\datatoolSetCurrencySort
}
\endgroup

```

```
\ExplSyntaxOn
```

Apply basic sort pre-processing (no locale):

```

\cs_new:Nn \datatool_sort_preprocess:Nn
{
  \datatool_sort_preprocess:NnN #1 { #2 }
  \l_datatool_sort_to_lowercase_bool
}

```

Version 3.2: added variant that takes boolean final argument to determine whether or not to convert to lower case.

```

\cs_new:Nn \datatool_sort_preprocess:NnN
{
  \group_begin:
  \dtl@SortWordCommands@hook
  \bool_if:NTF #3
  {
    \datatool_sort_handler_preprocess:Nn #1 { \text_lowercase:n { #2 } }
  }
  {
    \datatool_sort_handler_preprocess:Nn #1 { #2 }
  }
  \exp_args:NNNe
  \group_end:
  \tl_set:Nn #1 { \exp_args:NV \text_purify:n #1 }
}

```

```
\DTLsortwordlist{<clist-var>}{<handler-cs>}
```

\DTLsortwordlist

The first argument is a macro containing the list. The second argument is a handler macro for converting the original value into a byte sequence, which needs to have the form `\cs {<original>}{<tl>}`, where `<original>` is the original value and `<tl>` is a token list in which to store the byte sequence.

```

\seq_new:N \l__datatool_wordlist_seq
\tl_new:N \l__datatool_word_tl
\NewDocumentCommand \DTLsortwordlist { m m }
{
  \datatool_sortwordlist:NNN #1 #2 \__datatool_append_sorteditem:w
}

```

Syntax: `<clist-var> <handler-cs> <append-cs>`

The `<append-cs>` function is used after sorting to append the sort markup to a token list register with each item in the form `__datatool_sorted:nnn {<actual>}{<sort value>}{<letter group>}`. The `<append-cs>` function should have the syntax `<sort value>\q_mark<actual>\q_stop <tl var>`

```
\cs_new:Nn \datatool_sortwordlist:NNN
{
  \__datatool_sortword_list:NN #1 #2
  \__datatool_finish_sortword_list:NN #1 #3
}
```

Syntax: `<clist-var> <handler-cs>`

```
\cs_new:Nn \__datatool_sortword_list:NN
{
```

Scope to localise the effect of the hook.

```
\group_begin:
\dtl@SortWordCommands@hook
\seq_clear:N \l__datatool_wordlist_seq
```

Convert clist to temporary sequence variable, according to the current settings.

```
\exp_args:No \__datatool_create_tmp_list:n { #1 }
\__datatool_sortword_seq:NN \l__datatool_tmp_seq #2
\exp_args:No
  \__datatool_start_sortword_list:n
  { \l__datatool_wordlist_seq }
}
```

Alternative function if list is already in a sequence. Syntax: `<seq-var> <handler-cs>`

```
\cs_new:Nn \datatool_sortwordseq:NN
{
  \datatool_sortwordseq:NNN #1 #2 \__datatool_append_sorted_seq_item:w
}
```

Syntax: `<seq-var> <handler-cs> <append-cs>`

```
\cs_new:Nn \datatool_sortwordseq:NNN
{
  \__datatool_sortword_seqlist:NN #1 #2
  \__datatool_finish_sortword_seq:NN #1 #3
}
```

Syntax: `<seq-var> <handler-cs>`

```
\cs_new:Nn \__datatool_sortword_seqlist:NN
{
```

Scope to localise the effect of the hook.

```
\group_begin:
\dtl@SortWordCommands@hook
\seq_clear:N \l__datatool_wordlist_seq
\__datatool_sortword_seq:NN #1 #2
\exp_args:No
  \__datatool_start_sortword_list:n
  { \l__datatool_wordlist_seq }
}
```

Syntax: $\langle seq-var \rangle$ $\langle handler-cs \rangle$ Inner workings.

```
\cs_new:Nn \__datatool_sortword_seq:NN
{
  \seq_map_inline:Nn #1
  {
    \bool_if:NTF \l__datatool_sort_datum_bool
    {
      \DTLparse \l__datatool_tmpa_tl { ##1 }
      \tl_set:No \l__datatool_word_tl { ##1 }
      #2 { ##1 } { \l__datatool_word_tl }
      \exp_args:Noo \__datatool_sortword_append:nn
      { \l__datatool_word_tl }
      { \l__datatool_tmpa_tl }
    }
    {
      \tl_set:Nn \l__datatool_word_tl { ##1 }
      #2 { ##1 } { \l__datatool_word_tl }
      \exp_args:No \__datatool_sortword_append:nn
      { \l__datatool_word_tl } { ##1 }
    }
  }
}
```

End group to cancel effect of sort hook. This allows the original definitions to be used by the fallback function.

```
\cs_new:Nn \__datatool_start_sortword_list:n
{
  \group_end:
  \tl_set:Nn \l__datatool_wordlist_seq { #1 }
  \seq_sort:Nn \l__datatool_wordlist_seq
  {
    \__datatool_compare_sortitem:w ##1 ##2
  }
}
```

Add sort element to sequence.

```
\cs_new:Nn \__datatool_sortword_append:nn
{
  \seq_put_right:Nn \l__datatool_wordlist_seq
  { #1 \q_mark #2 \q_stop }
}
```

Comparator used by `\DTLsortwordlist`

```
\__datatool_compare_sortitem:w
\sort1\q_mark \actual1\q_stop
\sort2\q_mark \actual2\q_stop
```

```
\cs_new:Npn \__datatool_compare_sortitem:w
#1\q_mark#2\q_stop#3\q_mark#4\q_stop
```

```

{
  \__datatool_compare_sortitem:nnnn
  { #1 } { #2 } { #3 } { #4 }
  \int_compare:nNnTF
    { \dtl@sortresult } < { \c_zero_int }
    {
      \sort_return_same:
    }
    {
      \int_compare:nNnTF
        { \dtl@sortresult } > { \c_zero_int }
        {
          \sort_return_swapped:
        }
        {
          \bool_if:NTF \l__datatool_sort_reverse_bool
          {
            \__datatool_fallback_action:nnnn { #4 } { #2 }
            { \sort_return_swapped: }
            { \sort_return_same: }
          }
          {
            \__datatool_fallback_action:nnnn { #2 } { #4 }
            { \sort_return_swapped: }
            { \sort_return_same: }
          }
        }
      }
    }
}

```

Syntax: {<sort A>}{<actual A>}{<sort B>}{<actual B>} If the actual values are in the datum format, a numeric comparison can be used if the datum format indicates the original value was identified as numeric.

```

\cs_new:Nn \__datatool_compare_sortitem:nnnn
{
  \tl_clear:N \l__datatool_tmpc_tl
  \tl_clear:N \l__datatool_tmpd_tl
  \int_set_eq:NN \@dtl@datatype \c_datatool_string_int
  \tl_if_head_eq_meaning:nNTF { #2 } \__datatool_datum:nnnn
  {
    \__datatool_get_datum:w #2 \q_nil \q_stop
    \int_set_eq:NN
      \l__datatool_tmp_datatype_int
      \@dtl@datatype
    \tl_set:No \l__datatool_tmpc_tl
      { \datatool_datum_currency:Nnnnn #2 }
  }
  {
    \datatool_if_null:nT { #2 }
    {

```

```

        \int_set_eq:NN
        \l_datatool_tmp_datatype_int
        \c_datatool_unknown_int
    }
}
\tl_if_head_eq_meaning:nNTF { #4 } \__datatool_datum:nnnn
{
    \__datatool_get_datum:w #4 \q_nil \q_stop
    \tl_set:No \l__datatool_tmpd_tl
    { \datatool_datum_currency:Nnnnn #4 }
}
{
    \datatool_if_null:nT { #4 }
    {
        \int_set_eq:NN
        \@dtl@datatype
        \c_datatool_unknown_int
    }
}

```

If they have different currency symbols, treat them as strings.

```

\tl_if_eq:NNF \l__datatool_tmpe_tl \l__datatool_tmpd_tl
{
    \int_set_eq:NN
    \l__datatool_tmp_datatype_int \c_datatool_string_int
    \int_set_eq:NN
    \@dtl@datatype \c_datatool_string_int
}
\int_compare:nNnTF
{ \l__datatool_tmp_datatype_int }
=
{ \c_datatool_unknown_int }
{

```

The first value has an unknown type.

```

    \int_compare:nNnTF
    { \@dtl@datatype } > { \c_datatool_string_int }
    {

```

The first value has an unknown type. The second is numeric, so treat the first as zero.

```

    \__datatool_numcmp:Nnn \dtl@sortresult
    { 0 }
    { \datatool_datum_value:Nnnnn #4 }
}
{

```

The first value has an unknown type. If the second is not numeric so use a string comparison.

```

    \__datatool_strcmp:Nnn \dtl@sortresult { #1 } { #3 }
}
}
{

```

The first value has a known type.

```
\int_case:nnF { \@dtl@datatype }  
{  
  { \c_datatool_unknown_int }  
  }
```

The first value is known. The second is unknown.

```
\int_compare:nNnTF  
  { \l__datatool_tmp_datatype_int }  
  >  
  { \c_datatool_string_int }  
{
```

The first value is numeric. The second is unknown so treat as 0.

```
\__datatool_numcmp:Nnn \dtl@sortresult  
  { \datatool_datum_value:Nnnnn #2 }  
  { 0 }  
}  
{
```

The first value is not numeric. The second is unknown so use a string comparison.

```
\__datatool_strcmp:Nnn \dtl@sortresult { #1 } { #3 }  
}  
{ \c_datatool_string_int }  
{
```

The first value is known. The second is a string. Use a string comparison

```
\__datatool_strcmp:Nnn \dtl@sortresult { #1 } { #3 }  
}  
{
```

The first value is known. The second is numeric.

```
\int_compare:nNnTF  
  { \l__datatool_tmp_datatype_int }  
  >  
  { \c_datatool_string_int }  
{
```

Both values are numeric.

```
\__datatool_numcmp:Nnn \dtl@sortresult  
  { \datatool_datum_value:Nnnnn #2 }  
  { \datatool_datum_value:Nnnnn #4 }  
}  
{
```

The first value is a string. The second is numeric. Use a string comparison.

```
\__datatool_strcmp:Nnn \dtl@sortresult { #1 } { #3 }  
}  
}
```

```

\bool_if:NT \l__datatool_sort_reverse_bool
{
  \int_compare:nNnTF
  { \dtl@sortresult } < { \c_zero_int }
  {
    \int_set:Nn \dtl@sortresult { \c_one_int }
  }
  {
    \int_set:Nn \dtl@sortresult { - \dtl@sortresult }
  }
}
}

```

Finish off after sorting. The first argument is the clist in which to store the sorted values. The second argument is the function that extracts the required information and appends it to the clist.

```

\cs_new:Nn \__datatool_finish_sortword_list:NN
{
  \clist_clear:N #1
  \seq_map_inline:Nn \l__datatool_wordlist_seq
  {

```

The argument ##1 should be in the form $\langle sort \rangle \backslash q_mark \langle actual \rangle \backslash q_stop \{ \langle tl \rangle \}$

```

#2 ##1 #1
}
}

```

Similarly, but for a sequence variable.

```

\cs_new:Nn \__datatool_finish_sortword_seq:NN
{
  \seq_clear:N #1
  \seq_map_inline:Nn \l__datatool_wordlist_seq
  {

```

The argument ##1 should be in the form $\langle sort \rangle \backslash q_mark \langle actual \rangle \backslash q_stop \{ \langle tl \rangle \}$

```

#2 ##1 #1
}
}

```

This is similar to the datum marker but allows the sort value and initial letter (which may be required for letter groups) to be available. The three arguments are: original item, sort string, letter group.

```

\cs_new:Nn \__datatool_sorted:nnn { \exp_not:n { #1 } }

```

Unlike the datum markers, these are more likely to be passed directly (for example, in the argument of `\do`) so the `\sort marker` is expected to be in the form `__datatool_sorted:nnn{<actual>}{<sort>}{<letter>}`. If using `\@for` to iterate over the list then the loop control sequence will need to be expanded first.

```
\DTLsortedactual{<sort marker>}
```

`\DTLsortedactual`

The original item.

```
\newcommand{\DTLsortedactual} [1] { \use_ii:nnnn #1 }
```

```
\DTLsortedvalue{<sort marker>}
```

`\DTLsortedvalue`

The sort value.

```
\newcommand{\DTLsortedvalue} [1] { \use_iii:nnnn #1 }
```

```
\DTLsortedletter{<sort marker>}
```

`\DTLsortedletter`

The letter group.

```
\newcommand{\DTLsortedletter} [1] { \use_iv:nnnn #1 }
```

```
\__datatool_append_sorteditem:w
<sort>\q_mark <actual>\q_stop <clist_var>
```

```
\cs_new:Npn \__datatool_append_sorteditem:w
#1 \q_mark #2 \q_stop #3
{
  \tl_clear:N \l__datatool_tmpa_tl
  \DTLassignlettergroup { #2 } { #1 } { \l__datatool_tmpa_tl }
  \clist_put_right:Nx #3
  { \exp_not:N \__datatool_sorted:nnn
    { \exp_not:n { #2 } } { \exp_not:n { #1 } }
    { \exp_not:o { \l__datatool_tmpa_tl } }
  }
}
\cs_new:Npn \__datatool_append_sorted_seq_item:w
#1 \q_mark #2 \q_stop #3
{
```

```

\l_clear:N \l_datatool_tmpa_tl
\DTLassignlettergroup { #2 } { #1 } { \l_datatool_tmpa_tl }
\seq_put_right:Nx #3
  { \exp_not:N \__datatool_sorted:nnn
    { \exp_not:n { #2 } } { \exp_not:n { #1 } }
    { \exp_not:o { \l_datatool_tmpa_tl } }
  }
}

```

`\DTLassignlettergroup{<actual>}{<sort value>}{<tl>}`

\DTLassignlettergroup

Obtains the letter group from the sort value.

```

\newcommand{\DTLassignlettergroup} [3]
{
  \@dtl@datatype = \c_datatool_string_int
  \tl_if_head_eq_meaning:nNT { #1 } \__datatool_datum:nnnn
  {
    \__datatool_get_datum:w #1 \q_nil \q_stop
  }
  \int_case:nn { \@dtl@datatype }
  {
    { \c_datatool_string_int }
    {
      \DTLCurrentLocaleGetGroupString { #1 } { #2 } #3
      \exp_args:NV \datatool_get_first_grapheme:nN #3 #3
      \exp_args:NV \datatool_if_letter:nTF #3
      {
        \exp_args:NV \DTLCurrentLocaleGetInitialLetter #3 { #3 }
        \DTLPreProcessLetterGroup { #3 }
        \tl_set:Nx #3 { \exp_not:N \dtllettergroup { #3 } }
      }
      {
        \DTLPreProcessNonLetterGroup { #3 }
        \tl_set:Nx #3 { \exp_not:N \dtlnonlettergroup { #3 } }
      }
    }
  }
  { \c_datatool_integer_int }
  {
    \DTLPreProcessIntegerGroup
    { \l__datatool_datum_value_tl } { #1 }
    \tl_set:Nx #3
    { \exp_not:N \dtlnumbergroup { \l__datatool_datum_value_tl } }
  }
  { \c_datatool_decimal_int }
  {
    \DTLPreProcessDecimalGroup
    { \l__datatool_datum_value_tl } { #1 }
    \tl_set:Nx #3

```

```

    { \exp_not:N \dtlnumbergroup { \l__datatool_datum_value_tl } }
  }
{ \c_datatool_currency_int }
{
  \DTLPreProcessCurrencyGroup
  { \l__datatool_datum_currency_tl }
  { \l__datatool_datum_value_tl }
  { #1 }
  \tl_set:Nx #3
  {
    \exp_not:N \dtlcurrencygroup
    { \exp_not:o { \l__datatool_datum_currency_tl } }
    { \l__datatool_datum_value_tl }
  }
}
{ \c_datatool_datetime_int }
{
  \DTLPreProcessDateTimeGroup
  { \l__datatool_datum_value_tl } { #1 }
  \tl_set:Nx #3
  { \exp_not:N \dtldatetimegroup { \l__datatool_datum_value_tl } }
}
{ \c_datatool_date_int }
{
  \DTLPreProcessDateGroup
  { \l__datatool_datum_value_tl } { #1 }
  \tl_set:Nx #3
  { \exp_not:N \dtldategroup { \l__datatool_datum_value_tl } }
}
{ \c_datatool_time_int }
{
  \DTLPreProcessTimeGroup
  { \l__datatool_datum_value_tl } { #1 }
  \tl_set:Nx #3
  { \exp_not:N \dtltimegroup { \l__datatool_datum_value_tl } }
}
}
}
}

```

`\DTLCurrentLocaleGetGroupString{<actual>}{<sort value>}{<tl>}`

rentLocaleGetGroupString

May consist of more than one character. This determines whether to use the sort or actual value to obtain the letter group. The returned value may be truncated as only the initial part is of interest.

```

\newcommand{\DTLCurrentLocaleGetGroupString}[3]
{
  \tl_set:Nn #3 { #1 }
}

```

}

`\DTLPreProcessLetterGroup` Hook to pre-process letter group. The argument is a token list variable containing the current value.

```
\newcommand{\DTLPreProcessLetterGroup}[1]{}
```

`\PreProcessNonLetterGroup` Hook to pre-process non-letter group. The argument is a token list variable containing the current value.

```
\newcommand{\DTLPreProcessNonLetterGroup}[1]{}
```

`\TLPreProcessIntegerGroup` Hook to pre-process integer number group. The first argument is a token list variable containing the current value. The second argument is the actual value. The hook may adjust the token list variable.

```
\newcommand{\DTLPreProcessIntegerGroup}[2]{}
```

`\TLPreProcessDecimalGroup` Hook to pre-process decimal number group. The first argument is a token list variable containing the current value. The second argument is the actual value. The hook may adjust the token list variable.

```
\newcommand{\DTLPreProcessDecimalGroup}[2]{}
```

```
\DTLPreProcessCurrencyGroup{<sym tl var>}{<num tl var>}{<actual>}
```

`\LPreProcessCurrencyGroup`

Hook to pre-process currency number group. The `<num tl var>` is a token list variable containing the current numeric value. The `<sym tl var>` is a token list variable containing the currency symbol. The `<actual>` argument is the actual value. The hook may adjust the token list variable.

```
\newcommand{\DTLPreProcessCurrencyGroup}[3]{}
```

`\LPreProcessDateTimeGroup` Hook to pre-process datetime group. The first argument is a token list variable containing the current value. The second argument is the actual value. The hook may adjust the token list variable.

```
\newcommand{\DTLPreProcessDateTimeGroup}[2]{}
```

`\DTLPreProcessDateGroup` Hook to pre-process date group. The first argument is a token list variable containing the current value. The second argument is the actual value. The hook may adjust the token list variable.

```
\newcommand{\DTLPreProcessDateGroup}[2]{}
```

`\DTLPreProcessTimeGroup` Hook to pre-process time group. The first argument is a token list variable containing the current value. The second argument is the actual value. The hook may adjust the token list variable.

```
\newcommand{\DTLPreProcessTimeGroup}[2]{}
```

`\dtllettergroup`

```
\newcommand{\dtllettergroup}[1]{ \text_titlecase_first:n { #1 } }
```

```

\dtlnonlettergroup
\newcommand{\dtlnonlettergroup}[1]{\detokenize{#1}}

\dtlnumbergroup
\newcommand{\dtlnumbergroup}[1]{#1}

\dtlcurrencygroup
\newcommand{\dtlcurrencygroup}[2]{#1}

\dtldatetimegroup
\newcommand{\dtldatetimegroup}[1]{#1}

\dtldategroup
\newcommand{\dtldategroup}[1]{#1}

\dtltimegroup
\newcommand{\dtltimegroup}[1]{#1}

```

```

\dtlfallbackaction{<val1>}{<val2>}{<swap code>}{<no
swap code>}

```

```

\dtlfallbackaction
Used when two sort values are identical. This uses the original values for comparison.
\newcommand{\dtlfallbackaction}[4]{
  \DTLifstringgt { #1 } { #2 } { #3 } { #4 }
}
\cs_new:Nn \__datatool_fallback_action:nnnn
{
  \dtlfallbackaction { #1 } { #2 } { #3 } { #4 }
}

```

Word sort doesn't discard spaces or punctuation. So the first word of a compound word or phrase will come before a longer word that happens to have the other word at the start. This means that, for example, "sea lion" will come before "seal" because the space character comes before the character "l". This isn't exactly the same as a character sort as the localisation handler may convert the token list to series of bytes that alters the ordering.

Letter sort is only really concerned with alphanumerics (letters and digits). Spaces and punctuation aren't considered relevant to order. Commands will be expanded first, then stripped after the locale handler has been applied. This will ensure that any accent commands, such as `\'e`, will be converted to UTF-8 before the locale handler is applied.

```

\cs_new:Nn \datatool_sort_handler_preprocess:Nn
{
  \protected@edef #1 { #2 }
}

```

Handlers should set this to true if the sort value is converted to lowercase and false otherwise.

```
\bool_new:N \l_datatool_sort_to_lowercase_bool  
\bool_set_true:N \l_datatool_sort_to_lowercase_bool
```

```
\DTLsortwordhandler{<original>}{<cs>}
```

\DTLsortwordhandler

```
\newcommand{\DTLsortwordhandler}[2]{  
  \bool_set_true:N \l_datatool_sort_to_lowercase_bool  
  \datatool_sort_handler_preprocess:Nn  
    #2 { #1 }  
  \DTLDefaultLocaleWordHandler { #2 }
```

v3.1: Case change has been moved from pre-process to here:

```
  \tl_set:Nc #2 { \text_lowercase:n { \text_purify:n { #2 } } }  
}
```

```
\DTLsortwordcasehandler{<original>}{<cs>}
```

\DTLsortwordcasehandler

Case-sensitive handler.

```
\newcommand{\DTLsortwordcasehandler}[2]{  
  \bool_set_false:N \l_datatool_sort_to_lowercase_bool  
  \datatool_sort_handler_preprocess:Nn  
    #2 { #1 }  
  \DTLDefaultLocaleWordHandler { #2 }  
  \tl_set:Nc #2 { \text_purify:n { #2 } }  
}
```

Regular expression for content that should be stripped for letter sort.

```
\regex_new:N \l_datatool_letter_regex  
\regex_set:Nn \l_datatool_letter_regex { [\-[:space:]] }
```

```
\DTLsortletterhandler{<original>}{<cs>}
```

\DTLsortletterhandler

Hyphens and spaces are discarded from the sort value.

```
\newcommand{\DTLsortletterhandler}[2]{  
  \bool_set_true:N \l_datatool_sort_to_lowercase_bool  
  \datatool_sort_handler_preprocess:Nn  
    #2 { #1 }  
  \regex_replace_all:NnN \l_datatool_letter_regex {} #2  
  \DTLDefaultLocaleWordHandler { #2 }
```

v3.1: Case change has been moved from pre-process to here:

```
  \tl_set:Nc #2 { \text_lowercase:n { \text_purify:n { #2 } } }  
}
```

DTLsortlettercasehandler

`\DTLsortlettercasehandler{<original>}{<cs>}`

Case-sensitive handler.

```

\newcommand{\DTLsortlettercasehandler}[2]{
  \bool_set_false:N \l_datatool_sort_to_lowercase_bool
  \datatool_sort_handler_preprocess:Nn
    #2 { #1 }
  \regex_replace_all:NnN \l_datatool_letter_regex {} #2
  \DTLDefaultLocaleWordHandler { #2 }
  \tl_set:Nc #2 { \text_purify:n { #2 } }
}

```

\dtlsortlist

`\dtlsortlist{<list-cs>}{<criteria cmd>}`

Sorts the given comma-separated list according to the *<criteria>* command, which must take three arguments.

```

\newcommand{\dtlsortlist}[2]{%
  \exp_args:No \__datatool_create_tmp_list:n { #1 }
  \seq_set_eq:NN \__datatool_wordlist_seq \l_datatool_tmp_seq
  \seq_sort:Nn \__datatool_wordlist_seq
  {
    \bool_if:NTF \l__datatool_sort_reverse_bool
    {
      #2 { \dtl@sortresult } { ##2 } { ##1 }
    }
    {
      #2 { \dtl@sortresult } { ##1 } { ##2 }
    }
  }
  \ifnum\dtl@sortresult > 0\relax
  \sort_return_swapped:
  \else
  \sort_return_same:
  \fi
}
\tl_clear:N #1
\seq_map_inline:Nn \l__datatool_wordlist_seq
{
  \tl_if_empty:NF #1
  {
    \tl_put_right:Nn #1 { , }
  }
  \tl_if_in:nnTF { ##1 } { , }
  {
    \tl_put_right:Nn #1 { { ##1 } }
  }
  {
    \tl_put_right:Nn #1 { ##1 }
  }
}

```

```

    }
  }
}

```

```

\dtlinsertinto{<element>}{<sorted-list>}{<criteria
cmd>}

```

\dtlinsertinto

Globally inserts *<element>* into the sorted list *<sorted-list>* according to the criteria given by *<criteria cmd>*, which should be a command that takes three arguments $\{\langle reg \rangle\} \{\langle A \rangle\} \{\langle B \rangle\}$, where *<reg>* is a count register in which to store the result, *<A>* is the first element and ** is the second element to compare.

```

\newrobustcmd{\dtlinsertinto}[3]{%
  \exp_args:No \__datatool_create_tmp_list:n { #2 }
  \seq_set_eq:NN \l__datatool_wordlist_seq \l__datatool_tmp_seq
  \tl_gclear:N #2
  \@dtl@insertdonefalse
  \seq_map_inline:Nn \l__datatool_wordlist_seq
  {
    \tl_if_empty:NF #2
    {
      \tl_gput_right:Nn #2 { , }
    }
    \if@dtl@insertdone
    \else
      #3 { \dtl@sortresult } { ##1 } { #1 }
      \ifnum\dtl@sortresult > 0\relax
        \@dtl@insertdonetrue
        \tl_if_in:nnTF { #1 } { , }
        {
          \tl_gput_right:Nn #2 { { #1 } , }
        }
        {
          \tl_gput_right:Nn #2 { #1 , }
        }
      \fi
    \fi
    \tl_if_in:nnTF { ##1 } { , }
    {
      \tl_gput_right:Nn #2 { { ##1 } }
    }
    {
      \tl_gput_right:Nn #2 { ##1 }
    }
  }
  \if@dtl@insertdone
  \else
    \tl_if_empty:NF #2
    {

```

```

        \tl_gput_right:Nn #2 { , }
      }
    \tl_if_in:nnTF { #1 } { , }
    {
      \tl_gput_right:Nn #2 { { #1 } }
    }
    {
      \tl_gput_right:Nn #2 { #1 }
    }
  \fi
}

```

```

\edtlinsertinto{<element>}{<sorted-list>}{<criteria
cmd>}

```

\edtlinsertinto

First expands *<element>* before inserting into the list.

```

\newcommand*{\edtlinsertinto}[3]{%
  \exp_args:Nx \dtlinsertinto {#1} {#2} {#3}%
}
\ExplSyntaxOff

```

\if@dtl@insertdone Define conditional to indicate whether the new entry has been inserted into the sorted list.

```

\newif\if@dtl@insertdone

```

\dtl@sortresult Define \dtl@sortresult to be set by comparison macro. TODO: replace with L3 int var? (NB used by glossaries.sty)

```

\newcount\dtl@sortresult
\ExplSyntaxOn

```

```

\DTLshufflelist<clist-var>

```

\DTLshufflelist

Shuffle a comma-separated list. This just converts the list to a sequence and shuffles that using `seq_shuffle:N` and then converts that back to a comma-separated list.

```

\NewDocumentCommand \DTLshufflelist { m }
{

```

Convert *clist* to temporary sequence variable, according to the current settings.

```

  \group_begin:
  \exp_args:No \__datatool_create_tmp_list:n { #1 }
  \seq_shuffle:N \l__datatool_tmp_seq
  \clist_clear:N \l__datatool_tmp_clist
  \seq_map_inline:Nn \l__datatool_tmp_seq
  {
    \clist_put_right:Nn \l__datatool_tmp_clist { ##1 }
  }

```

```

    }
    \exp_args:NNNV
    \group_end:
    \tl_set:Nn #1 \l__datatool_tmp_clist
  }
  \ExplSyntaxOff

```

This next command is based on the list iteration exercise given at <http://www.dickimaw-books.com/latex/admin/html/foreachtips.shtml#oxfordcomma>. It's designed to format a comma-separated list using `\DTLlistformatsep` between each item except for the last. The separator for the last pair is `\DTLlistformatlastsep` if the list only contains two items or `\DTLlistformatoxford\DTLlistformatlastsep` if the list contains three or more items. Each item is formatted according to `\DTLlistformatitem`.

```
\DTLlistformatsep
```

```
\newcommand*\DTLlistformatsep}{, }
```

```
\DTLlistformatoxford
```

```
\newcommand*\DTLlistformatoxford}{}
```

```
\DTLlandname
```

```
\ifdef\andname
{\newcommand*\DTLlandname}{\andname}}
{\newcommand*\DTLlandname}{\&}}
```

```
\DTLlistformatlastsep
```

```
\newcommand*\DTLlistformatlastsep}{ \DTLlistand\space}
```

```
\DTLlistformatitem
```

```
\newcommand*\DTLlistformatitem}[1]{#1}
```

```
\@dtl@formatlist@handler
```

```
\newcommand*\@dtl@formatlist@handler}[1]{%
  \@dtl@formatlist@itemsep
  \@dtl@formatlist@lastitem
  \renewcommand{\@dtl@formatlist@lastitem}{%
    \renewcommand{\@dtl@formatlist@itemsep}{%
      \DTLlistformatsep
      \renewcommand*\@dtl@formatlist@prelastitemsep}{%
        \DTLlistformatoxford}}%
    \renewcommand{\@dtl@formatlist@prelastitem}{%
      \@dtl@formatlist@prelastitemsep
      \DTLlistformatlastsep}%
    \DTLlistformatitem{#1}%
  }%
}%
```

`\DTLformatlist` Formats the comma-separated list supplied in its argument. The unstarred version adds grouping.

```
\newrobustcmd*{\DTLformatlist}{%
  \@ifstar{\s@dtlformatlist}{\@dtlformatlist}%
}
```

`\s@dtlformatlist` Starred version of `\DTLformatlist` doesn't add grouping.

```
\ExplSyntaxOn
\newcommand*{\s@dtlformatlist}[1]{%
  \def\dtl@formatlist@itemsep{ }%
  \def\dtl@formatlist@lastitem{}%
  \def\dtl@formatlist@prelastitem{}%
  \def\dtl@formatlist@prelastitemsep{ }%
  \@dtl@assigntmpseq{#1}%
  \seq_map_function:NN \l__datatool_tmp_seq \dtl@formatlist@handler
  \dtl@formatlist@prelastitem\dtl@formatlist@lastitem
}
\ExplSyntaxOff
```

`\@dtlformatlist` Unstarred version of `\DTLformatlist` adds grouping.

```
\newcommand*{\@dtlformatlist}[1]{\s@dtlformatlist{#1}}
```

2.2.2 General Token Utilities

These commands are for altering the content of token registers. They're mostly used by `datatool` for the internal database structure.

```
\ExplSyntaxOn
```

```
\dtl@toks@gput@right@cx{<toks name>}{<stuff>}
```

`\dtl@toks@gput@right@cx`

Globally appends `stuff` to token register `\<toks name>` Deprecated. TODO remove

```
\newcommand{\dtl@toks@gput@right@cx}[2]{%
  \__datatool_token_register_gput_right:cx #1 { #2 }
}
```

```
\dtl@toks@gconcat@middle@cx{<toks name>}{<before
toks>}{<stuff>}{<after toks>}
```

`\dtl@toks@gconcat@middle@cx`

Globally sets token register `\<toks name>` to the contents of `<before toks>` concatenated with `<stuff>` (expanded) and the contents of `<after toks>` Deprecated. TODO remove

```
\newcommand{\dtl@toks@gconcat@middle@cx}[4]{%
  \__datatool_token_register_gset:cx
  { #1 } { \the #2 #3 \the #4 }
}
```

Use a token register.

```
\cs_new:Nn \__datatool_token_register_use:N
{
  \the #1
}
\cs_generate_variant:Nn
  \__datatool_token_register_use:N { c }
```

Set a token register equal to another.

```
\cs_new:Nn \__datatool_token_register_set_eq:NN
{
  #1 = #2
}
\cs_generate_variant:Nn
  \__datatool_token_register_set_eq:NN
  { cN, Nc, cc }
```

Globally set a token register equal to another.

```
\cs_new:Nn \__datatool_token_register_gset_eq:NN
{
  \global #1 = #2
}
\cs_generate_variant:Nn
  \__datatool_token_register_gset_eq:NN
  { cN, Nc, cc }
```

Set the contents of a token register.

```
\cs_new:Nn \__datatool_token_register_set:Nn
{
  #1 = { #2 }
}
\cs_generate_variant:Nn
  \__datatool_token_register_set:Nn
  { cn, cx, co, cV, No, Nx, NV }
```

Globally set the contents of a token register.

```
\cs_new:Nn \__datatool_token_register_gset:Nn
{
  \global #1 = { #2 }
}
\cs_generate_variant:Nn
  \__datatool_token_register_gset:Nn
  { cn, cx, co, cV, No, Nx }
```

Append content to a token register.

```
\cs_new:Nn \__datatool_token_register_put_right:Nn
{
  \__datatool_token_register_set:No #1
  { \the #1 #2 }
}
\cs_generate_variant:Nn
```

```

    \__datatool_token_register_put_right:Nn
    { cn, cx, co, cV, No, Nx }

```

Globally append content to a token register.

```

\cs_new:Nn \__datatool_token_register_gput_right:Nn
{
  \__datatool_token_register_gset:No #1
  { \the #1 #2 }
}
\cs_generate_variant:Nn
  \__datatool_token_register_gput_right:Nn
  { cn, cx, co, cV, No, Nx }

```

Concatenate the content of two registers with extra stuff in between

```

\cs_new:Nn \__datatool_token_register_concat_middle:NNnN
{
  \__datatool_token_register_set:Nx
  #1 { \the #2 \exp_not:n { #3 } \the #4 }
}
\cs_generate_variant:Nn
  \__datatool_token_register_concat_middle:NNnN
  { cNnN, cNxN, NNxN }

```

Globally concatenate.

```

\cs_new:Nn \__datatool_token_register_gconcat_middle:NNnN
{
  \__datatool_token_register_gset:Nx
  #1 { \the #2 \exp_not:n { #3 } \the #4 }
}
\cs_generate_variant:Nn
  \__datatool_token_register_gconcat_middle:NNnN
  { cNnN, cNxN, NNxN }

```

2.3 Encodings

Load file dealing with non-ASCII characters, but first initialise ASCII defaults. Each character is represented by both a string variable (for use by the sort comparator) and a token list variable (for typesetting, if required). The difference in expansion is more noticeable with input than with native Unicode engines.

Define new variables with default ASCII value.

Regular expression to match apostrophe.

```

\regex_new:N \l_datatool_apos_regex
\regex_set:Nn \l_datatool_apos_regex { \' }

```

Most symbols are currency signs, but mid-point is also added as it's sometimes used as a number separator.

```

\cs_new:Nn \__datatool_new_symbol:nn
{
  \__datatool_new_symbol:nnn { #1 } { #2 } { #2 }
}

```

```

\cs_new:Nn \__datatool_new_symbol:nnn
{
  \tl_new:c { l_datatool_ #1 _tl }
  \tl_set:cn { l_datatool_ #1 _tl } { #2 }
  \str_new:c { l_datatool_ #1 _str }
  \str_set:cn { l_datatool_ #1 _str } { #3 }
}
\cs_generate_variant:Nn \__datatool_new_symbol:nnn { nnV }

```

Regular expression to search for these symbols, which may be used in localisation files.
Only those characters supported by the encoding will be added.

```

\regex_new:N \l_datatool_currency_signs_regex
\regex_set:Nn \l_datatool_currency_signs_regex { \$ }

```

Allow encoding file to change the values.

```

\cs_new:Nn \datatool_set_symbol:nn
{
  \str_set:cn { l_datatool_ #1 _str } { #2 }
  \tl_set:cn { l_datatool_ #1 _tl } { #2 }
}
\cs_generate_variant:Nn \datatool_set_symbol:nn { ne }

```

Designed for inputenc to set by character code:

```

\cs_new:Nn \datatool_set_symbol_from_charcode:nn
{
  \str_set:ce { l_datatool_ #1 _str }
  { \char_generate:nn { #2 } { 12 } }
  \exp_args:Nno \tl_set:co { l_datatool_ #1 _tl }
  { \char_generate:nn { #2 } { 13 } }
}

```

Just for currency signs so that they can be added to the regular expression and list of known currencies:

```

\cs_new:Nn \datatool_set_currency_sign:nn
{
  \datatool_set_symbol:nn { #1 } { #2 }
  \regex_set:Nn \l_datatool_currency_signs_regex
  {
    \ur { l_datatool_currency_signs_regex }
    | \u { l_datatool_ #1 _str }
  }
  \DTLnewcurrencysymbol { #2 }
}
\cs_generate_variant:Nn \datatool_set_currency_sign:nn { ne }
\cs_new:Nn \datatool_set_currency_sign_from_charcode:nn
{
  \datatool_set_symbol_from_charcode:nn { #1 } { #2 }
  \regex_set:Nn \l_datatool_currency_signs_regex
  {
    \ur { l_datatool_currency_signs_regex }
    | \u { l_datatool_ #1 _str }
  }
}

```

```

    }
}

```

These may be redefined by an encoding file, if available. See section 2.3.

```

\__datatool_new_symbol:nn { cent } { c }
\__datatool_new_symbol:nn { pound } { L }
\__datatool_new_symbol:nnV { currency } { \# } \c_hash_str
\__datatool_new_symbol:nn { yen } { Y }
\__datatool_new_symbol:nn { middot } { . }
\__datatool_new_symbol:nn { florin } { f }
\__datatool_new_symbol:nn { baht } { B }
\__datatool_new_symbol:nn { ecu } { CE }
\__datatool_new_symbol:nn { colonsign } { C }
\__datatool_new_symbol:nn { cruzerio } { Cr }
\__datatool_new_symbol:nn { frenchfranc } { F }
\__datatool_new_symbol:nn { lira } { L }
\__datatool_new_symbol:nn { mill } { m }
\__datatool_new_symbol:nn { naira } { N }
\__datatool_new_symbol:nn { peseta } { Pts }
\__datatool_new_symbol:nn { rupee } { Rs }
\__datatool_new_symbol:nn { won } { W }
\__datatool_new_symbol:nn { shekel } { S }
\__datatool_new_symbol:nn { dong } { d }
\__datatool_new_symbol:nn { euro } { E }
\__datatool_new_symbol:nn { kip } { K }
\__datatool_new_symbol:nn { tugrik } { T }
\__datatool_new_symbol:nn { drachma } { Dr }
\__datatool_new_symbol:nn { germanpenny } { p }
\__datatool_new_symbol:nn { peso } { P }
\__datatool_new_symbol:nn { guarani } { G. }
\__datatool_new_symbol:nn { austral } { A }
\__datatool_new_symbol:nn { hryvnia } { S }
\__datatool_new_symbol:nn { cedi } { C }
\__datatool_new_symbol:nn { livretournois } { lt }
\__datatool_new_symbol:nn { spesmiilo } { Sm }
\__datatool_new_symbol:nn { tenge } { T }
\__datatool_new_symbol:nn { indianrupee } { R }
\__datatool_new_symbol:nn { turkishlira } { L }
\__datatool_new_symbol:nn { nordicmark } { M }
\__datatool_new_symbol:nn { manat } { M }
\__datatool_new_symbol:nn { ruble } { R }
\__datatool_new_symbol:nn { lari } { L }
\__datatool_new_symbol:nn { bitcoin } { B }
\__datatool_new_symbol:nn { som } { c }

```

An internal list that stores all known currencies. This sequence variable and `\DTLnewcurrencysymbol` need to be defined before the ldf encoding file is input.

```
\seq_new:N \l__datatool_known_currencies_seq
```

A list of all defined currency labels:

`\seq_new:N \l_datatool_currencies_seq`
 A list of all defined currency labels registered by regions:
`\seq_new:N \l_datatool_regional_currencies_seq`
 Map region to currency code:
`\prop_new:N \l_datatool_regional_currencies_prop`

`\DTLaddcurrency{<symbol>}`

`\DTLnewcurrencysymbol`

Adds *<symbol>* to the list of known currencies

```

\NewDocumentCommand \DTLnewcurrencysymbol { m }
{
  \seq_if_in:NnF \l__datatool_known_currencies_seq { #1 }
  {
    \seq_put_right:Nn \l__datatool_known_currencies_seq { #1 }
  }
}

\ExplSyntaxOff
\InputIfFileExists
{datatool-\TrackLangEncodingName .ldf}
{}
{
  \PackageInfo{datatool-base}
  {Missing file `datatool-\TrackLangEncodingName .ldf'.
   Falling back on US-ASCII for \string\datatool\string_...\string_str commands}
}

```

2.4 Locale Dependent Information

`\ExplSyntaxOn`

`\@dtl@decimal` The current decimal character was stored in `\@dtl@decimal` prior to version 3.0. As from v3.0, there are separate variables for formatting and parsing.

`\tl_new:N __datatool_decimal_tl`

Parsing may either be a token list:

`\tl_new:N __datatool_decimal_parse_tl`

or a regular expression:

`\regex_new:N __datatool_decimal_parse_regex`

`\@dtl@numbergroupchar` The current number group character was stored in `\@dtl@numbergroupchar` prior to version 3.0. As from v3.0, there are separate variables for formatting and parsing.

`\tl_new:N __datatool_numbergroup_tl`

Parsing may either be a token list:

`\tl_new:N __datatool_numbergroup_parse_tl`

or a regular expression:

```
\regex_new:N \__datatool_numbergroup_parse_regex
```

Regular expressions for parsing numeric values. For parsing locale numbers:

```
\regex_new:N \l_datatool_locale_numeric_regex
```

```
\regex_new:N \l_datatool_locale_fractional_regex
```

```
\regex_new:N \l_datatool_locale_fractional_nozero_regex
```

TeX's maximum integer limit is 0x7FFFFFFF so provide a regular expression to capture large integers that would otherwise trigger an error. (For example, a numeric ID or a bare telephone number without parentheses or hyphens could well exceed this value.)

```
\regex_new:N \l_datatool_locale_bigint_regex
```

For splitting standard decimals into number groups (dot for decimal separator and no number groups):

```
\regex_const:Nn \c_datatool_decimal_grps_regex  
{ \A ([+\-])? 0* (\d{1,3}) \. (\d+) \Z }
```

```
\regex_const:Nn \c_datatool_decimal_grps_i_regex  
{ \A ([+\-])? 0* (\d{1,3}) (\d{3}) \. (\d+) \Z }
```

```
\regex_const:Nn \c_datatool_decimal_grps_ii_regex  
{ \A ([+\-])? 0* (\d{1,3}) (\d{3}) (\d{3}) \. (\d+) \Z }
```

```
\regex_const:Nn \c_datatool_decimal_grps_iii_regex  
{ \A ([+\-])? 0* (\d+) (\d{3}) (\d{3}) (\d{3}) \. (\d+) \Z }
```

Similarly for integers:

```
\regex_const:Nn \c_datatool_integer_grps_i_regex  
{ \A ([+\-])? 0* (\d{1,3}) (\d{3}) \Z }
```

```
\regex_const:Nn \c_datatool_integer_grps_ii_regex  
{ \A ([+\-])? 0* (\d{1,3}) (\d{3}) (\d{3}) \Z }
```

```
\regex_const:Nn \c_datatool_integer_grps_iii_regex  
{ \A ([+\-])? 0* (\d+) (\d{3}) (\d{3}) (\d{3}) \Z }
```

```
\regex_const:Nn \c_datatool_integer_no_grps_regex  
{ \A ([+\-])? (\d{1,3}) \Z }
```

Trimming:

```
\regex_const:Nn \c_datatool_numeric_leading_zeros_regex  
{ \A ([+\-])? 0* (\d+ (?: (\.\d+) )? ) \Z }
```

```
\regex_const:Nn \c_datatool_integer_leading_zeros_regex  
{ \A ([+\-])? 0* (\d+ ) \Z }
```

```
\regex_const:Nn \c_datatool_decimal_redundant_zeros_regex  
{ \A ([+\-])? 0* (\d+ \. \d+ ) 0* \Z }
```

```
\regex_const:Nn \c_datatool_decimal_implicit_zero_regex  
{ \A ([+\-])? ( \. \d+ ) 0* \Z }
```

Any unformatted number:

```
\regex_const:Nn \c_datatool_any_numeric_regex
```

```
{ \A ([+\-])? \d* \. ? \d+ ( [eE] [+ \-]? \d+ ) ? \Z }
```

Get fractional part:

```
\cs_new:Nn \datatool_decimal_frac:n  
{
```

```

    \__datatool_decimal_frac:w #1 . 0 . 0 \q_stop
  }
\cs_generate_variant:Nn \datatool_decimal_frac:n { e , o }

```

Internal command:

```

\cs_new:Npn \__datatool_decimal_frac:w #1.#2.#3 \q_stop
{
  \tl_if_head_eq_meaning:nNT { #1 } - { - }
  0 . #2
}

```

Right zero pad or truncate decimals.

```

\cs_new:Npn \__datatool_decimal_places_i:w #1.#2#3\q_stop
{
  #1.#2
}
\cs_new:Npn \__datatool_decimal_places_ii:w #1.#2#3#4\q_stop
{
  #1.#2#3
}
\cs_new:Npn \__datatool_decimal_places_iii:w #1.#2#3#4#5\q_stop
{
  #1.#2#3#4
}
\cs_new:Npn \__datatool_decimal_places_iv:w #1.#2#3#4#5#6\q_stop
{
  #1.#2#3#4#5
}
\cs_new:Npn \__datatool_decimal_places_v:w #1.#2#3#4#5#6#7\q_stop
{
  #1.#2#3#4#5#6
}
\cs_new:Npn \__datatool_decimal_places_vi:w #1.#2#3#4#5#6#7#8\q_stop
{
  #1.#2#3#4#5#6#7
}
\cs_new:Npn \__datatool_decimal_places_vii:w #1.#2#3#4#5#6#7#8#9\q_stop
{
  #1.#2#3#4#5#6#7#8
}

```

NB First check that the number is a decimal. Expand to padded value:

```

\cs_new:Nn \__datatool_decimal_trunc_pad_zeros:nn
{
  \int_case:nnF { #2 }
  {
    { 1 }
    { \__datatool_decimal_places_i:w #1 0 \q_stop }
    { 2 }
    { \__datatool_decimal_places_ii:w #1 00 \q_stop }
    { 3 }
  }
}

```

```

        { \__datatool_decimal_places_iii:w #1 000 \q_stop }
    { 4 }
    { \__datatool_decimal_places_iv:w #1 0000 \q_stop }
    { 5 }
    { \__datatool_decimal_places_v:w #1 00000 \q_stop }
    { 6 }
    { \__datatool_decimal_places_vi:w #1 000000 \q_stop }
}
{
    \__datatool_decimal_places_vii:w #1 0000000 \q_stop
}
}

```

`\DTLsetnumberchars{<number group char>}{<decimal char>}`

`\DTLsetnumberchars`

This sets the decimal character and number group characters.

```

\NewDocumentCommand \DTLsetnumberchars { m m }
{
    \datatool_set_numberchars:nn { #1 } { #2 }
}

```

```

\cs_new:Nn \datatool_set_numberchars:nn
{
    \datatool_set_numberchars:nnnn { #1 } { #2 } { #1 } { #2 }
}
\cs_generate_variant:Nn \datatool_set_numberchars:nn
{ nV , Vn , VV }

```

Syntax: `{<format number group char>}` `{<format decimal char>}` `{<parse number group char>}` `{<parse decimal char>}`

```

\cs_new:Nn \datatool_set_numberchars:nnnn
{
    \tl_set:Nn \__datatool_numbergroup_tl { #1 }
    \tl_set:Nn \__datatool_numbergroup_parse_tl { #3 }
    \tl_set:Nn \__datatool_decimal_tl { #2 }
    \tl_set:Nn \__datatool_decimal_parse_tl { #4 }
}

```

Regular expressions used for parsing.

```

\regex_set:Nn \l_datatool_locale_bigint_regex
{
    \A [+\\-]?\\d* [2-9]
    \\u{\\__datatool_numbergroup_parse_tl}? \\d{3}
    \\u{\\__datatool_numbergroup_parse_tl}? \\d{3}
    \\u{\\__datatool_numbergroup_parse_tl}? \\d{3}
    \\Z
}
\regex_set:Nn \l_datatool_locale_numeric_regex
{

```

```

        \A ([+\-]?\d+)
          (?:\u{__datatool_numbergroup_parse_tl}\d{3})?
          (?:\u{__datatool_numbergroup_parse_tl}\d{3})?
          (?:\u{__datatool_numbergroup_parse_tl}\d{3})?
          (?:\u{__datatool_decimal_parse_tl}\d+)? \Z
      }
\regex_set:Nn \l_datatool_locale_fractional_regex
{
    \A ([+\-]?\d+) \u{__datatool_decimal_parse_tl} (\d+) \Z
}
\regex_set:Nn \l_datatool_locale_fractional_nozero_regex
{
    \A ([+\-]?) \u{__datatool_decimal_parse_tl} (\d+) \Z
}
}
\cs_generate_variant:Nn \datatool_set_numberchars:nnnn
{ VVVV , eeee , VnVn , nnVn }
Set the default.
\DTLsetnumberchars{,}{.}
As above but where a regular expression is needed for parsing.
\cs_new:Nn \datatool_set_numberchars_regex:nnnn
{
    \tl_set:Nn \__datatool_numbergroup_tl { #1 }
    \tl_clear:N \__datatool_numbergroup_parse_tl
    \regex_set:Nn \__datatool_numbergroup_parse_regex { #3 }
    \tl_set:Nn \__datatool_decimal_tl { #2 }
    \tl_clear:N \__datatool_decimal_parse_tl
    \regex_set:Nn \__datatool_decimal_parse_regex { #4 }
}
Regular expressions used for parsing.
\regex_set:Nn \l_datatool_locale_bigint_regex
{
    \A [+\\-]?\d* [2-9]
      \ur{__datatool_numbergroup_parse_regex}? \d{3}
      \ur{__datatool_numbergroup_parse_regex}? \d{3}
      \ur{__datatool_numbergroup_parse_regex}? \d{3}
      \Z
}
\regex_set:Nn \l_datatool_locale_numeric_regex
{
    \A ([+\-]?\d+)
      (?:\ur{__datatool_numbergroup_parse_regex}\d{3})?
      (?:\ur{__datatool_numbergroup_parse_regex}\d{3})?
      (?:\ur{__datatool_numbergroup_parse_regex}\d{3})?
      (?:\ur{__datatool_decimal_parse_regex}\d+)? \Z
}
\regex_set:Nn \l_datatool_locale_fractional_regex
{
    \A ([+\-]?\d+) \ur{__datatool_decimal_parse_regex} (\d+) \Z
}

```

```

    }
    \regex_set:Nn \l_datatool_locale_fractional_nozero_regex
    {
      \A ([+\-]?) \ur{__datatool_decimal_parse_regex} (\d+) \Z
    }
  }
  \cs_generate_variant:Nn \datatool_set_numberchars_regex:nnnn
  { VVnn , Vnnn , nVnn }

```

As above but regex is needed for number group and token list for decimal group when parsing.

```

\cs_new:Nn \datatool_set_numberchars_regex_tl:nnnn
{
  \tl_set:Nn \__datatool_numbergroup_tl { #1 }
  \tl_clear:N \__datatool_numbergroup_parse_tl
  \regex_set:Nn \__datatool_numbergroup_parse_regex { #3 }
  \tl_set:Nn \__datatool_decimal_tl { #2 }
  \tl_set:Nn \__datatool_decimal_parse_tl { #4 }
}

```

Regular expressions used for parsing.

```

\regex_set:Nn \l_datatool_locale_bigint_regex
{
  \A [+\\-]?\\d* [2-9]
  \ur{__datatool_numbergroup_parse_regex}? \\d{3}
  \ur{__datatool_numbergroup_parse_regex}? \\d{3}
  \ur{__datatool_numbergroup_parse_regex}? \\d{3}
  \Z
}
\regex_set:Nn \l_datatool_locale_numeric_regex
{
  \A ([+\-]?\\d+)
  (?:\\ur{__datatool_numbergroup_parse_regex}(\\d{3}))?
  (?:\\ur{__datatool_numbergroup_parse_regex}(\\d{3}))?
  (?:\\ur{__datatool_numbergroup_parse_regex}(\\d{3}))?
  (?:\\u{__datatool_decimal_parse_tl}(\\d+))? \Z
}
\regex_set:Nn \l_datatool_locale_fractional_regex
{
  \A ([+\-]?\\d+) \\u{__datatool_decimal_parse_tl} (\\d+) \Z
}
\regex_set:Nn \l_datatool_locale_fractional_nozero_regex
{
  \A ([+\-]?) \\u{__datatool_decimal_parse_tl} (\\d+) \Z
}
}
\cs_generate_variant:Nn \datatool_set_numberchars_regex_tl:nnnn
{ VVnn , Vnnn , nVnn , nVnV , nnnV }

```

As above but token list is needed for number group and regex for decimal group when parsing.

```

\cs_new:Nn \datatool_set_numberchars_tl_regex:nnnn

```

```

{
  \tl_set:Nn \__datatool_numbergroup_tl { #1 }
  \tl_set:Nn \__datatool_numbergroup_parse_tl { #3 }
  \tl_set:Nn \__datatool_decimal_tl { #2 }
  \tl_clear:N \__datatool_decimal_parse_tl
  \regex_set:Nn \__datatool_decimal_parse_regex { #4 }
}
Regular expressions used for parsing.
\regex_set:Nn \l_datatool_locale_bigint_regex
{
  \A [+\\-]?\\d* [2-9]
  \u{__datatool_numbergroup_parse_tl}? \\d{3}
  \u{__datatool_numbergroup_parse_tl}? \\d{3}
  \u{__datatool_numbergroup_parse_tl}? \\d{3}
  \\Z
}
\regex_set:Nn \l_datatool_locale_numeric_regex
{
  \A ([+\\-]?\\d+)
  (?:\\u{__datatool_numbergroup_parse_tl}\\d{3})?
  (?:\\u{__datatool_numbergroup_parse_tl}\\d{3})?
  (?:\\u{__datatool_numbergroup_parse_tl}\\d{3})?
  (?:\\ur{__datatool_decimal_parse_regex}\\d+)? \\Z
}
\regex_set:Nn \l_datatool_locale_fractional_regex
{
  \A ([+\\-]?\\d+) \\ur{__datatool_decimal_parse_regex} (\\d+) \\Z
}
\regex_set:Nn \l_datatool_locale_fractional_nozero_regex
{
  \A ([+\\-]?) \\ur{__datatool_decimal_parse_regex} (\\d+) \\Z
}
}
\cs_generate_variant:Nn \datatool_set_numberchars_tl_regex:nnnn
{ VVnn , Vnnn , nVnn , VnVn , nnVn }
Convenient shortcut to set thin-space number group:
\datatool_if_unicode_engine:TF
{
  \cs_new:Nn \datatool_set_thinspace_group_decimal_char:n
  {
    \datatool_set_numberchars_regex_tl:nnnn
    { \\ , } { #1 } { \\c{,} | \\s | \\x{2009} } { #1 }
  }
}
{
  \cs_new:Nn \datatool_set_thinspace_group_decimal_char:n
  {
    \datatool_set_numberchars_regex_tl:nnnn
    { \\ , } { #1 } { \\c{,} | \\s | \\x{E2} \\x{80} \\x{89} } { #1 }
  }
}

```

```

}
\cs_generate_variant:Nn \datatool_set_thinspace_group_decimal_char:n { V }
  Similarly for apostrophe:
\datatool_if_unicode_engine:TF
{
  \regex_const:Nn \c_datatool_apostrophe_regex
    { \x{27} | \x{2019} }
}
{
  \regex_const:Nn \c_datatool_apostrophe_regex
    { \x{27} | \x{E2} \x{80} \x{99} }
}
\cs_new:Nn \datatool_set_apos_group_decimal_char:n
{
  \datatool_set_numberchars_regex_tl:nnnn
    { ' } { #1 } { \ur{c_datatool_apostrophe_regex} } { #1 }
}
\cs_generate_variant:Nn \datatool_set_apos_group_decimal_char:n { V }
  Similarly for underscore number group character.
\cs_new:Nn \datatool_set_underscore_group_decimal_char:n
{
  \datatool_set_numberchars_regex_tl:nnnn
    { \_ } { #1 } { \c{\_} | \x{5F} } { #1 }
}
\cs_generate_variant:Nn \datatool_set_underscore_group_decimal_char:n { V }

```

2.4.1 Determining Data Types

The control sequence `__datatool_datum:nnnn` parses its argument to determine the data type of its argument. Each data type is represented by one of the following values: 0 (string), 1 (integer), 2 (decimal), 3 (currency), 4 (datetime), 5 (date), or 6 (time). The unknown data type -1 is used when the data is empty. Numeric values are expected to use the number group and decimal characters currently in effect.

The temporal data types (datetime, date and time) are new to v3.0 and have a numeric value. This is mainly provided for the benefit of `datatooltk` as imported data typically treats date/time data as numeric and it may be useful to retain the numeric value and ISO format. The Julian day number (an integer) is used to represent a date, the Julian time (a decimal between -0.5 and 0.5, where 0 is midday) is used to represent a time, and the Julian date (the sum of the Julian day number and the Julian time) is used to represent a timestamp (datetime).

`\@dtl@datatype` Scratch variable used to represent the data type identifier. This may be replaced with an integer variable at some point.

```
\newcount\@dtl@datatype
```

Scratch variables. Integers:

```
\int_new:N \l__datatool_tmpa_int
```

```
\int_new:N \l__datatool_tmpb_int
\int_new:N \l__datatool_tmpc_int
\int_new:N \l__datatool_tmpd_int
```

Used to count or index items:

```
\int_new:N \l__datatool_count_int
```

Temporary storage of data type identifier:

```
\int_new:N \l__datatool_tmp_datatype_int
```

Token lists (the first one may have already been defined if `datatool` has been loaded):

```
\tl_clear_new:N \l__datatool_tmpa_tl
\tl_new:N \l__datatool_tmpb_tl
\tl_new:N \l__datatool_tmpc_tl
\tl_new:N \l__datatool_tmpd_tl
\tl_new:N \l__datatool_tmp_currency_tl
\tl_new:N \l__datatool_tmp_initial_tl
\tl_new:N \l__datatool_result_tl
\tl_new:N \l__datatool_resulta_tl
\tl_new:N \l__datatool_resultb_tl
\tl_new:N \l__datatool_dialect_tl
```

Floating point:

```
\fp_new:N \l__datatool_tmpa_fp
\fp_new:N \l__datatool_tmpb_fp
\fp_new:N \l__datatool_tmpc_fp
\fp_new:N \l__datatool_tmpd_fp
\fp_new:N \l__datatool_mean_fp
\fp_new:N \l__datatool_total_fp
\fp_new:N \l__datatool_datum_value_fp
```

Dimensions:

```
\dim_new:N \l__datatool_tmpa_dim
\dim_new:N \l__datatool_tmpb_dim
```

Strings:

```
\str_new:N \l__datatool_tmpa_str
\str_new:N \l__datatool_tmpb_str
\str_new:N \l__datatool_tmpc_str
```

Clist.

```
\clist_new:N \l__datatool_tmp_clist
```

Sequences.

```
\seq_new:N \l__datatool_tmp_seq
\seq_new:N \l__datatool_tmpa_seq
\seq_new:N \l__datatool_tmpb_seq
```

The following may also be used by the localisation files, so not a private variable, but still just a scratch variable.

```
\seq_new:N \l__datatool_regex_match_seq
\seq_new:N \l__datatool_timestamp_match_seq
```

Regular expressions

```
\regex_new:N \l__datatool_tmpa_regex  
\regex_new:N \l__datatool_tmpb_regex
```

Data type identifiers.

```
\int_const:Nn \c_datatool_unknown_int {-1}  
\int_const:Nn \c_datatool_string_int {0}  
\int_const:Nn \c_datatool_integer_int {1}  
\int_const:Nn \c_datatool_decimal_int {2}  
\int_const:Nn \c_datatool_currency_int {3}  
\int_const:Nn \c_datatool_datetime_int {4}  
\int_const:Nn \c_datatool_date_int {5}  
\int_const:Nn \c_datatool_time_int {6}
```

Maximum known value. This will be updated if any new types are added in future.

```
\cs_new:Nn \datatool_max_known_type:  
{  
  \c_datatool_time_int  
}
```

`\DTLgetDataTypeName` Get textual name for data type (expandable):

```
\newcommand*{\DTLgetDataTypeName}[1]  
{  
  \int_case:nnF { #1 }  
  {  
    { \c_datatool_unknown_int }  
    { \DTLdatatypeunsetname }  
    { \c_datatool_string_int }  
    { \DTLdatatypestringname }  
    { \c_datatool_integer_int }  
    { \DTLdatatypeintegername }  
    { \c_datatool_decimal_int }  
    { \DTLdatatypedecimalname }  
    { \c_datatool_currency_int }  
    { \DTLdatatypecurrencyname }  
    { \c_datatool_datetime_int }  
    { \DTLdatatypedatetimename }  
    { \c_datatool_date_int }  
    { \DTLdatatypedatename }  
    { \c_datatool_time_int }  
    { \DTLdatatypetimename }  
  }  
  {  
    \DTLdatatypeinvalidname  
  }  
}
```

`\DTLdatatypeunsetname`

```
\newcommand \DTLdatatypeunsetname { unset }
```

```

\DTLdatatypestringname
    \newcommand \DTLdatatypestringname { string }

\DTLdatatypeintegername
    \newcommand \DTLdatatypeintegername { integer }

\DTLdatatypedecimalname
    \newcommand \DTLdatatypedecimalname { decimal }

\DTLdatatypecurrencyname
    \newcommand \DTLdatatypecurrencyname { currency }

\DTLdatatypedatetimetype
    \newcommand \DTLdatatypedatetimetype { date-time }

\DTLdatatypedatename
    \newcommand \DTLdatatypedatename { date }

\DTLdatatypetimetype
    \newcommand \DTLdatatypetimetype { time }

\DTLdatatypeinvalidname
    \newcommand \DTLdatatypeinvalidname { invalid }

```

Test for datum types. The argument should be a number. Test if the number is a recognised type (including “unknown”):

```

\prg_new_conditional:Npnn \datatool_if_valid_datum_type:n #1
  { p, T, F, TF }
  {
    \bool_lazy_or:nnTF
      { \int_compare_p:nNn { #1 } < { \c_datatool_unknown_int } }
      { \int_compare_p:nNn { #1 } > { \datatool_max_known_type: } }
    { \prg_return_false: }
    { \prg_return_true: }
  }

```

Test if the argument is a numeric datum type ID (currency, dates and times are considered numeric, in addition to integers and decimals):

```

\prg_new_conditional:Npnn \datatool_if_numeric_datum_type:n #1
  { p, T, F, TF }
  {
    \bool_lazy_or:nnTF
      { \int_compare_p:nNn { #1 } < { \c_datatool_integer_int } }
      { \int_compare_p:nNn { #1 } > { \c_datatool_time_int } }
    { \prg_return_false: }
    { \prg_return_true: }
  }

```

Test if the argument is a temporal datum type ID (timestamp, date or time):

```
\prg_new_conditional:Npnn \datatool_if_temporal_datum_type:n #1
  { p, T, F, TF }
  {
    \bool_lazy_or:nnTF
      { \int_compare_p:nNn { #1 } < { \c_datatool_datetime_int } }
      { \int_compare_p:nNn { #1 } > { \c_datatool_time_int } }
    { \prg_return_false: }
    { \prg_return_true: }
  }
}
```

Test if the argument is an integer or decimal datum type ID (not currency or temporal):

```
\prg_new_conditional:Npnn \datatool_if_number_only_datum_type:n #1
  { p, T, F, TF }
  {
    \bool_lazy_or:nnTF
      { \int_compare_p:nNn { #1 } = { \c_datatool_integer_int } }
      { \int_compare_p:nNn { #1 } = { \c_datatool_decimal_int } }
    { \prg_return_true: }
    { \prg_return_false: }
  }
}
```

Test if the argument is any datum type that has an integer value (integer or date):

```
\prg_new_conditional:Npnn \datatool_if_any_int_datum_type:n #1
  { p, T, F, TF }
  {
    \bool_lazy_or:nnTF
      { \int_compare_p:nNn { #1 } = { \c_datatool_integer_int } }
      { \int_compare_p:nNn { #1 } = { \c_datatool_date_int } }
    { \prg_return_true: }
    { \prg_return_false: }
  }
}
```

The null commands were originally in `datatool` but as from v3.0, the lower-level commands are now in `datatool-base` since commands like `\DTLdatumvalue` need to check for null. The `person` package, which may be used with just `datatool-base` and not `datatool`, performs a null test.

`\@dtlnovalue` The old internal command `\@dtlnovalue` has been replaced with the constant `\c_datatool_nullvalue_tl`. This is similar in concept to `c_novalue_tl` but is intended to represent missing values in `datatool` return values, particularly when querying database values. This starts with a space in the event that a null value is expanded in a context that tests for an initial letter without checking the category code. It ends with a space that has a letter category code. This mixture of category codes is designed to make it harder to accidentally identify the string “Undefined Value” as null.

Note that neither the old internal command nor this new constant are intended to be included in a list of data or in a database. `DatatoolTk` does still use the old command name as a marker for its own internal use, although it shouldn't make its way into an output file.

```

\tl_const:Nx \c_datatool_nullvalue_tl
{
  \c_catcode_other_space_tl
  \tl_to_str:n { Undefined }
  \c_catcode_other_space_tl
  \tl_to_str:n { Value }
  \char_generate:nn { 32 } { 11 }
}

```

`\dtlnovalue`

```

\newcommand* \dtlnovalue { \c_datatool_nullvalue_tl }

```

`\DTLstringnull` String null value:

```

\newcommand* \DTLstringnull { \@dtlstringnull }

```

`\@dtlstringnull` String null value:

```

\newcommand* \@dtlstringnull {NULL}

```

`\DTLnumbernull` Number null value:

```

\newcommand* \DTLnumbernull { \@dtlnumbernull }

```

`\@dtlnumbernull` Number null value:

```

\newcommand*{\@dtlnumbernull}{0}

```

Constant representing an empty datum value with unknown type.

```

\tl_const:Nn \c_datatool_empty_datum_tl
{
  \__datatool_datum:nnnn { } { } { } { } { \c_datatool_unknown_int }
}

```

`\DTLifnull` is still defined in `datatool`. Provide low-level commands. Test token for null. NB this doesn't test against the expansion text of the string and number null values as they could easily be valid non-null values, but it will test against the actual null constant value.

```

\prg_new_conditional:Npnn \datatool_if_null:N #1
{ p, T, F, TF }
{
  \bool_lazy_any:nTF
  {
    { \tl_if_eq_p:NN #1 \dtlnovalue }
    { \tl_if_eq_p:NN #1 \DTLstringnull }
    { \tl_if_eq_p:NN #1 \DTLnumbernull }
    { \tl_if_eq_p:NN #1 \c_datatool_nullvalue_tl }
  }
  { \prg_return_true: }
  { \prg_return_false: }
}
\cs_generate_variant:Nn \datatool_if_null:NTF { CTF }

```

Test for null where the argument may be a single token or may be a token list. If the argument is a single token, then the test is the same as the above otherwise the result will be false.

```

\prg_new_conditional:Npnn \datatool_if_null:n #1
  { T, F, TF }
{
  \tl_if_single_token:nTF { #1 }
  {
    \bool_lazy_any:nTF
    {
      { \tl_if_eq_p:NN #1 \dtlnovalue }
      { \tl_if_eq_p:NN #1 \DTLstringnull }
      { \tl_if_eq_p:NN #1 \DTLnumbernull }
      { \tl_if_eq_p:NN #1 \c_datatool_nullvalue_tl }
    }
    { \prg_return_true: }
  }
  \tl_if_eq:NnTF \dtlnovalue { #1 }
  { \prg_return_true: }
  {
    \tl_if_eq:NnTF \DTLstringnull { #1 }
    { \prg_return_true: }
    {
      \tl_if_eq:NnTF \DTLnumbernull { #1 }
      { \prg_return_true: }
      { \prg_return_false: }
    }
  }
}
}
{
  \tl_if_eq:NnTF \c_datatool_nullvalue_tl { #1 }
  { \prg_return_true: }
  { \prg_return_false: }
}
}

```

Test for null or empty. This includes testing for the empty datum.

```

\prg_new_conditional:Npnn \datatool_if_null_or_empty:N #1
  { p, T, F, TF }
{
  \bool_lazy_any:nTF
  {
    { \tl_if_empty_p:N #1 }
    { \tl_if_eq_p:NN #1 \dtlnovalue }
    { \tl_if_eq_p:NN #1 \DTLstringnull }
    { \tl_if_eq_p:NN #1 \DTLnumbernull }
    { \tl_if_eq_p:NN #1 \c_datatool_nullvalue_tl }
    { \tl_if_eq_p:NN #1 \c_datatool_empty_datum_tl }
  }
}

```

```

    { \prg_return_true: }
    { \prg_return_false: }
  }

```

Test for null or empty where the argument may be a single token or may be a token list. If the argument is a single token, then the test is the same as the above. If the argument isn't a single token the result will be false unless the argument is empty.

```

\prg_new_conditional:Npnn \datatool_if_null_or_empty:n #1
  { T, F, TF }
{
  \tl_if_single_token:nTF { #1 }
  {
    \bool_lazy_any:nTF
    {
      { \tl_if_empty_p:N #1 }
      { \tl_if_eq_p:NN #1 \dtlnovalue }
      { \tl_if_eq_p:NN #1 \DTLstringnull }
      { \tl_if_eq_p:NN #1 \DTLnumbernull }
      { \tl_if_eq_p:NN #1 \c_datatool_nullvalue_tl }
      { \tl_if_eq_p:NN #1 \c_datatool_empty_datum_tl }
    }
    { \prg_return_true: }
    {
      \tl_if_eq:NnTF \dtlnovalue { #1 }
      { \prg_return_true: }
      {
        \tl_if_eq:NnTF \DTLstringnull { #1 }
        { \prg_return_true: }
        {
          \tl_if_eq:NnTF \DTLnumbernull { #1 }
          { \prg_return_true: }
          { \prg_return_false: }
        }
      }
    }
  }
}
{
  \tl_if_empty:nTF { #1 }
  { \prg_return_true: }
  {
    \tl_if_eq:NnTF \c_datatool_nullvalue_tl { #1 }
    { \prg_return_true: }
    {
      \tl_if_eq:NnTF \c_datatool_empty_datum_tl { #1 }
      { \prg_return_true: }
      { \prg_return_false: }
    }
  }
}
}

```

Datum marker. The first argument is the original content. The second should expand to a (non-locale) numeric representation or empty for non-numeric data. (The second argument may contain additional content that will ordinarily be discarded on expansion, but may be retrieved if required.) The third argument is the currency symbol or empty if not currency. The final argument is the integer data type identifier.

```
\cs_new:Nn \__datatool_datum:nnnn { \exp_not:n { #1 } }
```

This means that the datum control sequence content consists of five things: the datum marker and its four arguments.

The weird datum is designed to allow easy lookup in databases. It uses a similar trick to `etoolbox` that uses the bar `|` character with category code 3 as a marker.

```
\group_begin:
```

Locally change category code of `|`

```
\char_set_catcode_math_toggle:N \|
```

Create a constant token list that expands to this character with this category code.

```
\tl_const:Nn \c__datatool_datum_weird_marker_tl { | }
```

Define the weird function to expand to the regular datum function. This is designed for expandable contexts to perform a quick conversion without expanding the arguments.

```
\cs_new:Npn \__datatool_datum:w | #1 | #2 | #3 | #4 |
{
  \exp_not:N \__datatool_datum:nnnn
  { \exp_not:n { #1 } }
  { \exp_not:n { #2 } }
  { \exp_not:n { #3 } }
  { \exp_not:n { #4 } }
}
```

Allow marker to expand.

```
\cs_new:Npn \__datatool_datum_use:w | #1 | #2 | #3 | #4 |
{
  \__datatool_datum:nnnn
  { #1 } { #2 } { #3 } { #4 }
}
```

Only the first argument (but don't expand that):

```
\cs_new:Npn \__datatool_datum_use_i:w | #1 | #2 | #3 | #4 |
{
  \exp_not:n { #1 }
}
```

Define the reverse. Four arguments provided (datum marker not included). This only prevents the string and currency arguments from expanding.

```
\cs_new:Nn \__datatool_weird_datum:nnnn
{
  \exp_not:N \__datatool_datum:w
  | \exp_not:n { #1 }
  | #2
  | \exp_not:n { #3 }
}
```

```

    | #4 |
}

```

Five arguments provided, starting with the datum marker that needs to be discarded.

```

\cs_new:Nn \__datatool_weird_datum:Nnnnn
{
  \exp_not:N \__datatool_datum:w
  | \exp_not:n { #2 }
  | \exp_not:n { #3 }
  | \exp_not:n { #4 }
  | \exp_not:n { #5 } |
}

```

Parse content that starts with `__datatool_weird_datum:w`.

```

\cs_new:Npn \__datatool_get_weird_datum:w
\__datatool_datum:w | #1 | #2 | #3 | #4 | #5 \q_stop
{
  \quark_if_nil:nTF { #5 }
  {
    \@dtl@datatype = #4
    \tl_set:Nn \l__datatool_datum_original_value_tl { #1 }
    \tl_set:Nn \l__datatool_datum_value_tl { #2 }
    \tl_set:Nn \l__datatool_datum_currency_tl { #3 }
  }
  {
    \@dtl@datatype = \c_datatool_string_int
  }
}

```

Restore category code.

```

\group_end:
  Test for equality where one or other value might be in either datum format.
  Syntax: <tl var1> <tl var2> {<true>}{<false>}
\prg_new_conditional:Npnn \datatool_if_value_eq:NN #1 #2
{ T, F, TF }
{
  \exp_args:NV \tl_if_head_eq_meaning:nNTF
  #1 \__datatool_datum:w
  {
    \exp_args:NV \tl_if_head_eq_meaning:nNTF
    #2 \__datatool_datum:w
    {
      \datatool_if_value_eq:eeTF
      { #1 } { #2 }
      { \prg_return_true: }
      { \prg_return_false: }
    }
  }
  {
    \datatool_if_value_eq:eVTF
    { #1 } #2
  }
}

```



```

    }
    {
      \datatool_if_value_eq:nVTF { #1 } #2
      { \prg_return_true: }
      { \prg_return_false: }
    }
  }
}

```

Syntax: $\{ \langle tl1 \rangle \} \{ \langle tl2 \rangle \} \{ \langle true \rangle \} \{ \langle false \rangle \}$

```

\prg_new_conditional:Npnn \datatool_if_value_eq:nn #1 #2
{ T, F, TF }
{
  \tl_if_eq:nnTF { #1 } { #2 }
  { \prg_return_true: }
  {
    \tl_if_head_eq_meaning:nNTF { #1 } \__datatool_datum:nnnn
    {
      \tl_if_head_eq_meaning:nNTF { #2 } \__datatool_datum:nnnn
      {

```

Both in datum format. If both numeric use numeric comparison, otherwise use string comparison.

```

\bool_lazy_and:nnTF
{
  \int_compare_p:nNn
  { \__datatool_datum_type:n { #1 } }
  >
  { \c_datatool_string_int }
}
{
  \int_compare_p:nNn
  { \__datatool_datum_type:n { #2 } }
  >
  { \c_datatool_string_int }
}
{

```

Both numeric. Test both the value and currency symbol.

```

\tl_if_eq:eeTF
{ \__datatool_datum_currency:n { #1 } }
{ \__datatool_datum_currency:n { #2 } }
{
  \fp_compare:nNnTF
  { \__datatool_datum_value:n { #1 } }
  =
  { \__datatool_datum_value:n { #2 } }
  { \prg_return_true: }
  { \prg_return_false: }
}
{ \prg_return_false: }
}

```

```

    {
One or other isn't numeric. Compare string values only.
    \tl_if_eq:eeTF
      { \__datatool_datum_string:n { #1 } }
      { \__datatool_datum_string:n { #2 } }
      { \prg_return_true: }
      { \prg_return_false: }
    }
  }
{

```

First in datum format, second isn't. Compare string values only

```

    \tl_if_eq:enTF { #1 } { #2 }
    { \prg_return_true: }
    { \prg_return_false: }
  }
{

```

First isn't in datum format. Compare string values only

```

    \tl_if_eq:enTF { #1 } { #2 }
    { \prg_return_true: }
    { \prg_return_false: }
  }
}

```

```

\cs_generate_variant:Nn \datatool_if_value_eq:nnTF
{ VVTF , VnTF , nVTF, eeTF, neTF, enTF, eVTF, VeTF }

```

Function to convert a token list variable so that it contains a weird datum function if the original contained a datum marker but don't parse and convert otherwise.

```

\cs_new:Nn \__datatool_to_weird_datum_no_parse:N
{
  \exp_args:NV \__datatool_to_weird_datum_no_parse:nN #1 #1
}
\cs_new:Nn \__datatool_to_weird_datum_no_parse:nN
{
  \tl_if_head_eq_meaning:nNTF
    { #1 } \__datatool_datum:nnnn
  {
    \tl_set:Nx #2 { \__datatool_weird_datum:Nnnnn #1 }
  }
  {
    \tl_set:Nn #2 { #1 }
  }
}

```

Function to convert a token list variable so that it contains a weird datum function.

```

\cs_new:Nn \__datatool_to_weird_datum:N
{
  \exp_args:NV \__datatool_to_weird_datum:nN #1 #1
}

```

```

}
\cs_new:Nn \__datatool_to_weird_datum:nN
{
  \tl_if_head_eq_meaning:nNTF
    { #1 } \__datatool_datum:w
    {

```

Already in weird format.

```

      \tl_set:Nn #2 { #1 }
    }
  {

```

Convert to datum.

```

      \__datatool_to_datum:nN { #1 } #2

```

Leave null unprocessed.

```

      \datatool_if_null:NF #2
    {

```

At this point the token list variable should start with the datum marker but check to make sure.

```

      \tl_if_head_eq_meaning:nNT
        { #1 } \__datatool_datum:nNn
        {
          \tl_put_left:Nn #2 { \__datatool_weird_datum:Nnnn }
          \tl_set:Nx #2 { #2 }
        }
      }
    }
  }
}

```

Function to convert a token list variable so that it contains a normal datum function.

```

\cs_new:Nn \__datatool_to_datum:N
{
  \exp_args:NV \__datatool_to_datum:nN #1 #1
}

```

Function to convert a token list so that it contains a normal datum function and save it in the token list variable.

```

\cs_new:Nn \__datatool_to_datum:nN
{
  \datatool_if_null:nTF { #1 }
  {

```

Set variable to null.

```

    \tl_set_eq:NN #2 \dtlnovalue
  }
  {
    \tl_if_head_eq_meaning:nNTF
      { #1 } \__datatool_datum:w
    {

```



```

    {
Convert from weird format:
    \tl_set:Nx #2 { #1 }
    }
    {
    \tl_set:Nn #2 { #1 }
    }
}

```

Remove either datum.

```

\cs_new:Nn \__datatool_rm_datum:N
{
  \exp_args:NV \__datatool_rm_datum:nN #1 #1
}
\cs_new:Nn \__datatool_rm_datum:nN
{
  \__datatool_rm_weird_datum:nN { #1 } #2
  \exp_args:NV \tl_if_head_eq_meaning:nNT
    #2 \__datatool_datum:nNnn
  {

```

Convert from datum format:

```

    \tl_set:Nx #2 { #2 }
  }
}

```

Used to encapsulate floating point datum value. The first argument is the (non-locale) original floating point value. The second is the l3fp content to allow for reconstruction. The third is the decimal value for use where scientific notation can't be parsed. For example, with fp functions.

```

\tl_if_eq:NnTF \@dtl@mathprocessor { fp }
{
  \cs_new:Nn \datatool_datum_fp:nnn { #3 }
}
{
  \cs_new:Nn \datatool_datum_fp:nnn { #1 }
}

```

Pick out the l3fp content:

```

\cs_new:Nn \datatool_datum_fp:Nnnn { \exp_not:n { #3 } }
\cs_new:Nn \datatool_set_fp:Nn
{
  \tl_if_single_token:nTF { #2 }
  {
    \exp_args:No \tl_if_head_eq_meaning:nNTF { #2 } \__datatool_datum:nNnn
    {
      \exp_last_unbraced:NV \__datatool_get_datum:w #2 \q_nil \q_stop
    }
  }
  {
    \exp_args:No \tl_if_head_eq_meaning:nNTF { #2 } \__datatool_datum:w

```

```

        {
          \exp_last_unbraced:NV \__datatool_get_weird_datum:w #2 \q_nil \q_stop
        }
        {
          \exp_args:No \__datatool_parse_datum:n { #2 }
        }
      }
    }
  {
    \tl_if_head_eq_meaning:nNTF { #2 } \__datatool_datum:nnnn
    {
      \__datatool_get_datum:w #2 \q_nil \q_stop
    }
    {
      \tl_if_head_eq_meaning:nNTF { #2 } \__datatool_datum:w
      {
        \__datatool_get_weird_datum:w #2 \q_nil \q_stop
      }
      {
        \__datatool_parse_datum:n { #2 }
      }
    }
  }
}
\datatool_if_numeric_datum_type:nF { \@dtl@datatype }
{
  \exp_args:Nx \__datatool_parse_datum:n
  { \tl_trim_spaces:e { \text_expand:n { #2 } } }
}
\tl_if_empty:NTF \l__datatool_datum_value_tl
{
  \fp_zero:N #1
}
{
  \exp_args:NV \tl_if_head_eq_meaning:nNTF
  \l__datatool_datum_value_tl
  { \datatool_datum_fp:nnn }
  {
    \tl_set:Nx #1
    {
      \exp_after:wN \datatool_datum_fp:Nnnn \l__datatool_datum_value_tl
    }
  }
  {
    \fp_set:Nn #1 { \l__datatool_datum_value_tl }
  }
}
}
\cs_generate_variant:Nn \datatool_set_fp:Nn { NV, No }

```

\DTLusedatum

\DTLusedatum{<tl>}

```

\cs_new:Nn \__datatool_datum_string:n { \datatool_datum_string:Nnnnn #1 }
\newcommand{\DTLusedatum} [1]
{
  \tl_if_eq:NNTF #1 \dtlnovalue
  { \dtlnovalue }
  { \exp_args:NV \__datatool_datum_string:n #1 }
}

```

At the time of writing there were no \use... commands for five arguments. There now are, but these are provided anyway in case of a slightly older kernel and they are better semantically.

```

\cs_new:Nn \datatool_datum_string:Nnnnn { #2 }

```

\DTLdatumvalue

\DTLdatumvalue{<tl>}

```

\cs_new:Nn \__datatool_datum_value:n { \datatool_datum_value:Nnnnn #1 }
\newcommand{\DTLdatumvalue} [1]
{
  \tl_if_eq:NNTF #1 \dtlnovalue
  { \DTLnumbernull }
  { \exp_args:NV \__datatool_datum_value:n #1 }
}

```

```

\cs_new:Nn \datatool_datum_value:Nnnnn { #3 }

```

\DTLdatumcurrency

\DTLdatumcurrency{<tl>}

```

\cs_new:Nn \__datatool_datum_currency:n { \datatool_datum_currency:Nnnnn #1 }
\newcommand{\DTLdatumcurrency} [1]
{
  \tl_if_eq:NNTF #1 \dtlnovalue
  { \dtlnovalue }
  { \exp_args:NV \__datatool_datum_currency:n #1 }
}

```

```

\cs_new:Nn \datatool_datum_currency:Nnnnn { \exp_not:n { #4 } }

```

\DTLdatumtype

\DTLdatumtype{<tl>}

```

\cs_new:Nn \__datatool_datum_type:n { \datatool_datum_type:Nnnnn #1 }
\newcommand{\DTLdatumtype} [1]
{
  \tl_if_eq:NNTF #1 \dtlnovalue
  { \int_use:N \c_datatool_unknown_int }
  { \int_eval:n { \exp_args:NV \__datatool_datum_type:n #1 } }
}

\cs_new:Nn \datatool_datum_type:Nnnnn { #5 }
  Debugging:
\cs_new:Nn \datatool_datum_show:N
{
  \int_compare:nNnTF { \tl_count:N #1 } = { 5 }
  {
    \exp_after:wN \__datatool_datum_show:NNnnnn
    \exp_after:wN #1 #1
  }
  {
    \datatool_if_null:NTF #1
    {
      \msg_show:nnnV
      { datatool-base }
      { show-datum-var-null }
      { #1 }
      #1
    }
    {
      \tl_if_empty:NTF #1
      {
        \msg_show:nnn
        { datatool-base }
        { show-datum-var-empty }
        { #1 }
      }
      {
        \PackageError { datatool-base }
        { \tl_to_str:N #1 \c_space_tl is ~ not ~ a ~ datum ~ variable }
        { }
      }
    }
  }
}
}

\cs_new:Nn \__datatool_datum_show:NNnnnn
{
  \tl_if_eq:NNTF #2 \__datatool_datum:nnnn
  {
    \int_case:nnF { #6 }
    {

```

```

{ \c_datatool_unknown_int }
{
  \msg_show:nnnn
  { datatool-base }
  { show-datum-var-unset }
  { #1 }
  { #3 }
}
{ \c_datatool_string_int }
{
  \msg_show:nnnn
  { datatool-base }
  { show-datum-var-string }
  { #1 }
  { #3 }
}
{ \c_datatool_integer_int }
{
  \msg_show:nnnnn
  { datatool-base }
  { show-datum-var-integer }
  { #1 }
  { #3 }
  { #4 }
}
{ \c_datatool_decimal_int }
{
  \msg_show:nnnnn
  { datatool-base }
  { show-datum-var-decimal }
  { #1 }
  { #3 }
  { #4 }
}
{ \c_datatool_currency_int }
{
  \msg_show:nnnnn
  { datatool-base }
  { show-datum-var-currency }
  { #1 }
  { #3 }
  { #4 }
  { #5 }
}
{ \c_datatool_datetime_int }
{
  \msg_show:nnnnn
  { datatool-base }
  { show-datum-var-datetime }
  { #1 }
}

```

```

        { #3 }
        { #4 }
    }
    { \c_datatool_date_int }
    {
        \msg_show:nnnn
        { datatool-base }
        { show-datum-var-date }
        { #1 }
        { #3 }
        { #4 }
    }
    { \c_datatool_time_int }
    {
        \msg_show:nnnn
        { datatool-base }
        { show-datum-var-time }
        { #1 }
        { #3 }
        { #4 }
    }
}
{
    \PackageError { datatool-base }
    {
        datum ~ variable ~
        \tl_to_str:N #1 \c_space_tl has ~ invalid ~ data ~ type: ~
        \int_eval:n { #6 }
    }
    { }
}
}
{
    \tl_if_eq:NNTF #2 \__datatool_datum:w
    {
        \int_case:nnF { #6 }
        {
            { \c_datatool_unknown_int }
            {
                \msg_show:nnnn
                { datatool-base }
                { show-weird-datum-var-unset }
                { #1 }
                { #3 }
            }
        }
        { \c_datatool_string_int }
        {
            \msg_show:nnnn
            { datatool-base }
            { show-weird-datum-var-string }
        }
    }
}

```

```

        { #1 }
        { #3 }
    }
{ \c_datatool_integer_int }
{
    \msg_show:nnnnn
    { datatool-base }
    { show-weird-datum-var-integer }
    { #1 }
    { #3 }
    { #4 }
}
{ \c_datatool_decimal_int }
{
    \msg_show:nnnnn
    { datatool-base }
    { show-weird-datum-var-decimal }
    { #1 }
    { #3 }
    { #4 }
}
{ \c_datatool_currency_int }
{
    \msg_show:nnnnnn
    { datatool-base }
    { show-weird-datum-var-currency }
    { #1 }
    { #3 }
    { #4 }
    { #5 }
}
{ \c_datatool_datetime_int }
{
    \msg_show:nnnnn
    { datatool-base }
    { show-weird-datum-var-datetime }
    { #1 }
    { #3 }
    { #4 }
}
{ \c_datatool_date_int }
{
    \msg_show:nnnnn
    { datatool-base }
    { show-weird-datum-var-date }
    { #1 }
    { #3 }
    { #4 }
}
{ \c_datatool_time_int }

```

```

    {
      \msg_show:nnnn
      { datatool-base }
      { show-weird-datum-var-time }
      { #1 }
      { #3 }
      { #4 }
    }
  }
  {
    \PackageError { datatool-base }
    {
      weird ~ datum ~ variable ~
      \tl_to_str:N #1 \c_space_tl has ~ invalid ~ data ~ type: ~
      \int_eval:n { #6 }
    }
  }
}
{
  \PackageError { datatool-base }
  {
    Can't ~ show ~ \tl_to_str:N #1 : ~
    \tl_to_str:N #2 \c_space_tl is ~ not ~ a ~ datum ~ marker
  }
}
}
}

```

Messages:

```

\msg_new:nnn { datatool-base }
{ show-datum-var-null }
{
  variable ~ \tl_to_str:N #1 \c_space_tl is ~ null \\  

  > ~ #2
}
\msg_new:nnn { datatool-base }
{ show-datum-var-empty }
{
  variable ~ \tl_to_str:N #1 \c_space_tl is ~ empty
}
\msg_new:nnn { datatool-base }
{ show-datum-var-unset }
{
  Showing ~ unset ~ datum ~ variable ~ \tl_to_str:N #1 \\  

  > ~ string ~ value ~ ` #2 '
}
\msg_new:nnn { datatool-base }

```

```

{ show-weird-datum-var-unset }
{
  Showing ~ unset ~ weird ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ ` #2 '
}
\msg_new:nnn { datatool-base }
{ show-datum-var-string }
{
  Showing ~ string ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2
}
\msg_new:nnn { datatool-base }
{ show-weird-datum-var-string }
{
  Showing ~ string ~ weird ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2
}
\msg_new:nnn { datatool-base }
{ show-datum-var-integer }
{
  Showing ~ integer ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3
}
\msg_new:nnn { datatool-base }
{ show-weird-datum-var-integer }
{
  Showing ~ integer ~ weird ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3
}
\msg_new:nnn { datatool-base }
{ show-datum-var-decimal }
{
  Showing ~ decimal ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3
}
\msg_new:nnn { datatool-base }
{ show-weird-datum-var-decimal }
{
  Showing ~ decimal ~ weird ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3
}
\msg_new:nnn { datatool-base }
{ show-datum-var-currency }

```

```

{
  Showing ~ currency ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3 \\
  > ~ currency ~ symbol ~ #4
}
\msg_new:nnn { datatool-base }
{ show-weird-datum-var-currency }
{
  Showing ~ currency ~ weird ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3 \\
  > ~ currency ~ symbol ~ #4
}
\msg_new:nnn { datatool-base }
{ show-datum-var-datetime }
{
  Showing ~ datetime ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3
}
\msg_new:nnn { datatool-base }
{ show-weird-datum-var-datetime }
{
  Showing ~ datetime ~ weird ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3
}
\msg_new:nnn { datatool-base }
{ show-datum-var-date }
{
  Showing ~ date ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3
}
\msg_new:nnn { datatool-base }
{ show-weird-datum-var-date }
{
  Showing ~ date ~ weird ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3
}
\msg_new:nnn { datatool-base }
{ show-datum-var-time }
{
  Showing ~ time ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\

```

```

    > ~ numeric ~ value ~ #3
  }
\msg_new:nnn { datatool-base }
{ show-weird-datum-var-time }
{
  Showing ~ time ~ weird ~ datum ~ variable ~ \tl_to_str:N #1 \\
  > ~ string ~ value ~ #2 \\
  > ~ numeric ~ value ~ #3
}

```

The above document commands can be used on `<cs>` obtained from parsing data.
Document commands:

```
\DTLparse{<cs>}{<arg>}
```

\DTLparse

Note that any dates or times will be treated as strings.

```

\NewDocumentCommand \DTLparse { m m }
{
  \__datatool_parse:Nn #1 { #2 }
}

```

Internal function easier to remember the argument order:

```

\cs_new:Nn \__datatool_parse:Nn
{
  \tl_clear:N \l__datatool_datum_value_tl
  \tl_clear:N \l__datatool_datum_currency_tl
  \tl_clear:N \l__datatool_datum_update_value_tl
  \datatool_if_null:nTF { #2 }
  {
    \tl_set_eq:NN #1 \dtlnovalue
    \tl_set:Nn \l__datatool_datum_original_value_tl { #2 }
    \int_set_eq:NN \@dtl@datatype \c_datatool_unknown_int
  }
  {
    \tl_if_head_eq_meaning:nNTF
    { #2 } \__datatool_datum:w
    {

```

Convert from weird format:

```

    \tl_set:Nx #1 { #2 }
  }
  {
    \tl_set:Nn #1 { #2 }
  }
\exp_args:NV \tl_if_head_eq_meaning:nNTF
#1 \__datatool_datum:nnnn
{
  \int_set:Nn \@dtl@datatype
  { \exp_args:NV \__datatool_datum_type:n #1 }
}

```

```

\l_datatool_datum_original_value_tl { #1 }
\l_datatool_datum_currency_tl
{ \exp_args:NV \__datatool_datum_currency:n #1 }
\l_datatool_datum_value_tl
{ \exp_args:NV \__datatool_datum_value:n #1 }
}

```

```

{
\exp_args:NV \__datatool_parse_datum:n #1
\l_if_empty:NTF \l_datatool_datum_update_value_tl
{
\int_compare:nNnTF
{ \@dtl@datatype }
=
{ \c_datatool_unknown_int }
}
}

```

NB this may be blank (only a space) not empty, but it's still classed as unknown.

```

\l_set:Nn #1
{
\__datatool_datum:nnnn { #2 } { } { }
{ \c_datatool_unknown_int }
}
}
{
\l_set_eq:NN #1 \l_datatool_datum_original_value_tl
}
}
{
\l_set_eq:NN #1 \l_datatool_datum_update_value_tl
}
}
}
}
\cs_generate_variant:Nn \__datatool_parse:Nn
{ NV }
\cs_new:Nn \__datatool_parse:N
{
\exp_args:NNV \__datatool_parse:Nn #1 #1
}
}

```

`\DTLxparse{<cs>}{<arg>}`

\DTLxparse

As above but expands second argument.

```

\NewDocumentCommand \DTLxparse { m m }
{
\exp_args:NNx \__datatool_parse:Nn #1 { #2 }
}

```

Low-level set datum parts.

```
\datatool_set_datum:Nnnnn <datum-var> {<string>}
{<value>} {<currency symbol>} {<type>}
```

The type may be an integer expression

```
\cs_new:Nn \datatool_set_datum:Nnnnn
{
  \int_case:nnF { #5 }
  {
    { \c_datatool_unknown_int }
    {
      \tl_set:Nn #1
      {
        \__datatool_datum:nnnn
        { #2 } { } { } { } { \c_datatool_unknown_int }
      }
    }
  }
  { \c_datatool_string_int }
  {
    \tl_set:Nn #1
    {
      \__datatool_datum:nnnn
      { #2 } { } { } { } { \c_datatool_string_int }
    }
  }
  { \c_datatool_integer_int }
  {
    \tl_set:Nn #1
    {
      \__datatool_datum:nnnn
      { #2 } { #3 } { } { } { \c_datatool_integer_int }
    }
  }
  { \c_datatool_decimal_int }
  {
    \tl_set:Nn #1
    {
      \__datatool_datum:nnnn
      { #2 } { #3 } { } { } { \c_datatool_decimal_int }
    }
  }
  { \c_datatool_currency_int }
  {
    \tl_set:Nn #1
    {
      \__datatool_datum:nnnn
      { #2 } { #3 } { #4 } { } { \c_datatool_currency_int }
    }
  }
}
```

```

}
{ \c_datatool_datetime_int }
{
  \tl_set:Nn #1
  {
    \__datatool_datum:nnnn
    { #2 } { #3 } { } { \c_datatool_datetime_int }
  }
}
{ \c_datatool_date_int }
{
  \tl_set:Nn #1
  {
    \__datatool_datum:nnnn
    { #2 } { #3 } { } { \c_datatool_date_int }
  }
}
{ \c_datatool_time_int }
{
  \tl_set:Nn #1
  {
    \__datatool_datum:nnnn
    { #2 } { #3 } { } { \c_datatool_time_int }
  }
}
}
{
  \PackageError { datatool-base }
  { Unsupported ~ datum ~ type ~ \int_eval:n { #5 } }
  { }
}
}
\cs_generate_variant:Nn \datatool_set_datum:Nnnnn
{ Neeen , Nnenn , NnVn , NnVnn }
No sanity check:
\cs_new:Nn \__datatool_set_datum:Nnnnn
{
  \tl_set:Nn #1
  {
    \__datatool_datum:nnnn { #2 } { #3 } { #4 } { #5 }
  }
}
\cs_generate_variant:Nn \__datatool_set_datum:Nnnnn
{ Neeen , NnVnn , NeVnn }
Document-level commands:

```

```
\DTLsetintegerdatum{<cs>}{<formatted value>}{<value>}
```

\DTLsetintegerdatum

Sets $\langle cs \rangle$ to an integer datum.

```
\NewDocumentCommand \DTLsetintegerdatum { m m m }
{
  \tl_set:Nn #1
  {
    \__datatool_datum:nnnn
    { #2 } { #3 } { }
    { \c_datatool_integer_int }
  }
}
```

$\backslash\text{DTLxsetintegerdatum}\{\langle cs \rangle\}\{\langle formatted\ value \rangle\}\{\langle value \rangle\}$

$\backslash\text{DTLxsetintegerdatum}$

As above but expands $\langle formatted\ value \rangle$ and $\langle value \rangle$.

```
\NewDocumentCommand \DTLxsetintegerdatum { m m m }
{
  \exp_args:Neee \DTLsetintegerdatum { \exp_not:N #1 }
  { #2 } { #3 }
}
```

$\backslash\text{DTLsetdecimaldatum}\{\langle cs \rangle\}\{\langle formatted\ value \rangle\}\{\langle value \rangle\}$

$\backslash\text{DTLsetfpdatum}$

Sets $\langle cs \rangle$ to a floating point datum.

```
\NewDocumentCommand \DTLsetfpdatum { m m m }
{
  \fp_set:Nn \l__datatool_datum_value_fp { #3 }
  \tl_set:Nx #1
  {
    \exp_not:N \__datatool_datum:nnnn
    { \exp_not:n { #2 } }
    {
      \exp_not:N \datatool_datum_fp:nnn
      { #3 }
      { \exp_not:V \l__datatool_datum_value_fp }
      { \fp_to_decimal:N \l__datatool_datum_value_fp }
    }
    { }
    { \c_datatool_decimal_int }
  }
}
```

$\backslash\text{DTLsetdecimaldatum}\{\langle cs \rangle\}\{\langle formatted\ value \rangle\}\{\langle value \rangle\}$

$\backslash\text{DTLsetdecimaldatum}$

Sets $\langle cs \rangle$ to a decimal datum.

```

\NewDocumentCommand \DTLsetdecimaldatum { m m m }
{
  \tl_set:Nn #1
  {
    \__datatool_datum:nnnn
    { #2 } { #3 } { }
    { \c_datatool_decimal_int }
  }
}

```

`\DTLxsetdecimaldatum{<cs>}{<formatted value>}{<value>}`

\DTLxsetdecimaldatum

As above but expands *<formatted value>* and *<value>*.

```

\NewDocumentCommand \DTLxsetdecimaldatum { m m m }
{
  \exp_args:Neee \DTLsetdecimaldatum { \exp_not:N #1 }
  { #2 } { #3 }
}

```

`\DTLsetcurrencydatum{<cs>}{<formatted value>}{<value>}{<currency symbol>}`

\DTLsetcurrencydatum

Sets *<cs>* to a currency datum.

```

\NewDocumentCommand \DTLsetcurrencydatum { m m m m }
{
  \tl_set:Nn #1
  {
    \__datatool_datum:nnnn
    { #2 } { #3 } { #4 }
    { \c_datatool_currency_int }
  }
}

```

`\DTLxsetcurrencydatum{<cs>}{<formatted value>}{<value>}{<currency symbol>}`

\DTLxsetcurrencydatum

As above but expands *<formatted value>*, *<value>* and *<currency symbol>*.

```

\NewDocumentCommand \DTLxsetcurrencydatum { m m m m }
{
  \exp_args:Neee \DTLsetcurrencydatum { \exp_not:N #1 }
  { #2 } { #3 } { #4 }
}

```

\DTLsettemporaldatum

`\DTLsettemporaldatum{<cs>}{<formatted value>}{<ISO>}`

Sets <cs> to a date/time datum. The actual type is determined by parsing <ISO>. If the formatted value should be automatically calculated, use `\DTLsetup{datetime=reformat}\DTLparse{<cs>}{<ISO>}` and adjust the formatting commands as applicable.

```

\NewDocumentCommand \DTLsettemporaldatum { m m m }
{
  \__datatool_parse_datetime:nTF { #3 }
  {
    \__datatool_set_datetime_value:Nn #1 { #2 }
  }
  {
    \PackageError { datatool-base }
    { Invalid ~ date/time format ~ ` \tl_to_str:n { #3 } ' }
    {
      The ~ date/time ~ value ~ needs ~ to ~ be ~ a ~
      date ~ in ~ the ~ form ~ YYYY-MM-DD ~ or ~ a ~
      time ~ in ~ the ~ form ~ hh:mm ~ or ~ hh:mm:ss ~ or ~ a ~
      timestamp ~ in ~ the ~ form ~ YYYY-MM-DD ~ hh:mm:ssTZ ~
      where ~ the ~ timezone ~ TZ ~ is ~ optional ~
      and ~ may ~ be ~ the ~ letter ~
      `Z' ~ or ~ in ~ the ~ form ~ [+~]hh:mm ~
      (if ~ omitted ~ `Z' ~ is ~ assumed). ~ The ~
      separator ~ may ~ either ~ be ~ a ~ space ~ or ~
      the ~ letter ~ `T'
    }
  }
}

```

`\DTLxsetdatetimedatum{<cs>}{<formatted value>}{<ISO>}`

\DTLxsettemporaldatum

As above but expands all but the first argument.

```

\NewDocumentCommand \DTLxsettemporaldatum { m m m }
{
  \exp_args:Neee \DTLsettemporaldatum { \exp_not:N #1 }
  { #2 } { #3 }
}

```

`\DTLsetstringdatum{<cs>}{<string>}`

\DTLsetstringdatum

Sets <cs> to a string datum.

```

\NewDocumentCommand \DTLsetstringdatum { m m }
{
  \tl_set:Nn #1
  {

```

```

    \__datatool_datum:nnnn
    { #2 } { } { }
    { \c_datatool_string_int }
  }
}

```

`\DTLxsetstringdatum{<cs>}{<string>}`

`\DTLxsetstringdatum`

As above but expands *<string>*.

```

\NewDocumentCommand \DTLxsetstringdatum { m m }
{
  \exp_args:NNe \DTLxsetstringdatum #1 { #2 }
}

```

Temporary storage used when extracting data. The original value:

```
\tl_new:N \l__datatool_datum_original_value_tl
```

The numeric value:

```
\tl_new:N \l__datatool_datum_value_tl
```

The currency symbol:

```
\tl_new:N \l__datatool_datum_currency_tl
```

The currency code:

```
\tl_new:N \l__datatool_datum_currency_code_tl
```

If the data hasn't been parsed yet, the following is set to the tagged information:

```
\tl_new:N \l__datatool_datum_update_value_tl
```

Regular expression for scientific notation. Version 3.4: bug fix (expression needs to be anchored)

```

\regex_const:Nn \c_datatool_sci_regex
{ \A [+\\-]? [0-9]* \.? [0-9]+ \s* [eE] [+\\-]? [0-9]+ \Z }

```

Determine data type. For temporal data types, the argument must match the relevant format. See `__datatool_parse_datetime_if_enabled:n` and `__datatool_parse_datetime:n` conditionals.

```

\cs_new:Nn \__datatool_parse_datum:n
{

```

Initialise to unknown.

```

  \@dtl@datatype = \c_datatool_unknown_int
  \tl_set:Nn \l__datatool_datum_original_value_tl { #1 }
  \tl_clear:N \l__datatool_datum_value_tl
  \tl_clear:N \l__datatool_datum_currency_tl
  \tl_clear:N \l__datatool_datum_currency_code_tl
  \tl_clear:N \l__datatool_datum_update_value_tl
  \tl_if_blank:nF { #1 }
  {

```

Has the argument already had its data type set?

```
\tl_if_head_eq_meaning:nNTF { #1 } \__datatool_datum:nnnn
{ \__datatool_get_datum:w #1 \q_nil \q_stop }
{
  \tl_if_head_eq_meaning:nNTF { #1 } \__datatool_datum:w
  { \__datatool_get_weird_datum:w #1 \q_nil \q_stop }
  {
```

Doesn't start with the special marker, so it needs parsing. First check for scientific notation.

```
\regex_match:NnTF \c_datatool_sci_regex { #1 }
{
  \fp_set:Nn \l__datatool_datum_value_fp { #1 }
  \@dtl@datatype = \c_datatool_decimal_int
  \tl_set:Nx \l__datatool_datum_value_tl
  {
    \exp_not:N \datatool_datum_fp:nnn
    { #1 }
    { \exp_not:V \l__datatool_datum_value_fp }
    { \fp_to_decimal:N \l__datatool_datum_value_fp }
  }
  \__datatool_if_auto_reformat_on:nTF { si }
  {
```

Auto-reformat on.

```
\tl_set:Nx \l__datatool_datum_update_value_tl
{
  \exp_not:N \__datatool_datum:nnnn
  {
    \exp_not:N \DTLscinum
    { \exp_not:n { #1 } }
  }
  { \exp_not:V \l__datatool_datum_value_tl }
  { }
  { \exp_not:N \c_datatool_decimal_int }
}
}
{
  \tl_set:Nx \l__datatool_datum_update_value_tl
  {
    \exp_not:N \__datatool_datum:nnnn
    { \exp_not:n { #1 } }
    { \exp_not:V \l__datatool_datum_value_tl }
    { }
    { \exp_not:N \c_datatool_decimal_int }
  }
}
}
{
```

Next for date/time if applicable.


```

    \__datatool_parse_numeric:n { #1 }
    \int_compare:nNnT
      { \@dtl@datatype } = { \c_datatool_unknown_int }
    {
      \int_set_eq:NN \@dtl@datatype \c_datatool_string_int
    }
  }
{

```

Starts (or ends) with a currency symbol. Is it followed by a numeric value?

```

    \tl_trim_spaces:N \l__datatool_suffix_tl
    \__datatool_parse_numeric:N \l__datatool_suffix_tl
    \int_compare:nNnTF
      { \@dtl@datatype } = { \c_datatool_string_int }
    {
      \tl_clear:N \l__datatool_datum_currency_tl
    }
    {
      \int_set_eq:NN \@dtl@datatype \c_datatool_currency_int
    }
  }
}
}

```

Check for a double sign which will be treated as a string.

```

\__tl_if_empty:nF { #2 }
{
  \int_compare:nNnT
    { \@dtl@datatype } > { \c_datatool_string_int }
  {
    \bool_lazy_or:nnTF
      { \tl_if_head_eq_meaning_p:nN { #1 } + }
      { \tl_if_head_eq_meaning_p:nN { #1 } - }
    {
      \int_set_eq:NN \@dtl@datatype \c_datatool_string_int
    }
  }
  {
    \tl_if_eq:nnT { #2 } { - }
    {
      \tl_set:Nx \l__datatool_datum_value_tl
        { \fp_to_tl:n { - ( \l__datatool_datum_value_tl ) } }
    }
  }
}
}
}
\int_case:nn { \@dtl@datatype }
{
  { \c_datatool_string_int }
  {

```

Non-numeric.

```
\tl_set:Nn \l__datatool_datum_update_value_tl
{
  \__datatool_datum:nnnn { #2 #1 } { } { }
  { \c_datatool_string_int }
}
}
{ \c_datatool_integer_int }
{
```

Integer.

```
\__datatool_if_auto_reformat_on:nTF { integer }
{
```

Auto-reformat on.

```
\tl_set:Nx
  \l__datatool_datum_update_value_tl
  { \int_eval:n { \l__datatool_datum_value_tl } }
\regex_replace_case_once:nN
{
  \c_datatool_integer_grps_i_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3 }
  \c_datatool_integer_grps_ii_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3
    \u{__datatool_numbergroup_tl} \4 }
  \c_datatool_integer_grps_iii_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3
    \u{__datatool_numbergroup_tl} \4
    \u{__datatool_numbergroup_tl} \5 }
}
\l__datatool_datum_update_value_tl
\tl_set:Ne \l__datatool_datum_update_value_tl
{
  \exp_not:N \__datatool_datum:nnnn
  {
    \exp_not:V \l__datatool_datum_update_value_tl
  }
  { \int_eval:n { \l__datatool_datum_value_tl } } { }
  { \c_datatool_integer_int }
}
}
{
\tl_set:Nx \l__datatool_datum_update_value_tl
{
  \exp_not:N \__datatool_datum:nnnn
  { \exp_not:n { #2 #1 } }
  { \int_eval:n { \l__datatool_datum_value_tl } } { }
  { \c_datatool_integer_int }
}
}
```

```

}
{ \c_datatool_decimal_int }
{

```

Decimal.

```

\tl_set_eq:NN
  \l_datatool_datum_update_value_tl
  \l_datatool_datum_value_tl
\fp_set:Nn \l_datatool_datum_value_fp
{ \l_datatool_datum_value_tl }
\tl_set:Nx \l_datatool_datum_value_tl
{
  \exp_not:N \datatool_datum_fp:nnn
  { \exp_not:V \l_datatool_datum_value_tl }
  { \exp_not:V \l_datatool_datum_value_fp }
  { \fp_to_decimal:N \l_datatool_datum_value_fp }
}
\__datatool_if_auto_reformat_on:nTF { decimal }
{

```

Auto-reformat on.

```

  \regex_replace_case_once:nN
  {
    \c_datatool_decimal_grps_regex
    { \1 \2 \u{__datatool_decimal_tl} \3 }
    \c_datatool_decimal_grps_i_regex
    { \1 \2 \u{__datatool_numbergroup_tl} \3 \u{__datatool_decimal_tl} \4 }
    \c_datatool_decimal_grps_ii_regex
    { \1 \2 \u{__datatool_numbergroup_tl} \3
      \u{__datatool_numbergroup_tl} \4
      \u{__datatool_decimal_tl} \5 }
    \c_datatool_decimal_grps_iii_regex
    { \1 \2 \u{__datatool_numbergroup_tl} \3
      \u{__datatool_numbergroup_tl} \4
      \u{__datatool_numbergroup_tl} \5
      \u{__datatool_decimal_tl} \6 }
  }
  \l_datatool_datum_update_value_tl
\tl_set:Ne \l_datatool_datum_update_value_tl
{
  \exp_not:N \__datatool_datum:nnnn
  {
    \exp_not:V \l_datatool_datum_update_value_tl
  }
  { \exp_not:V \l_datatool_datum_value_tl }
  { }
  { \c_datatool_decimal_int }
}
}
{

```

Auto-reformat off.

```
\tl_set:Nx \l__datatool_datum_update_value_tl
{
  \exp_not:N \__datatool_datum:nnnn
  { \exp_not:n { #2 #1 } }
  { \exp_not:V \l__datatool_datum_value_tl }
  { }
  { \c_datatool_decimal_int }
}
}
}
{ \c_datatool_currency_int }
{
```

Currency.

```
\__datatool_if_auto_reformat_on:nTF { currency }
{
```

Auto-reformat on.

```
\__datatool_decimal_to_currency:VVNV
\l__datatool_datum_currency_tl
\l__datatool_datum_value_tl
\l__datatool_datum_update_value_tl
\l__datatool_datum_currency_code_tl
}
{
```

Auto-reformat off.

```
\tl_set:Nx \l__datatool_datum_update_value_tl
{
  \exp_not:N \__datatool_datum:nnnn
  { \exp_not:n { #2 #1 } }
  { \l__datatool_datum_value_tl }
  { \exp_not:V \l__datatool_datum_currency_tl }
  { \c_datatool_currency_int }
}
}
}
}
\tl_set:Nn \l__datatool_datum_original_value_tl { #2 #1 }
}
```

Parse for a numeric value, using the current group and decimal characters.

```
\tl_new:N \l__datatool_parser_num_tl
\cs_new:Nn \__datatool_parse_numeric:N
{
  \exp_args:No \__datatool_parse_numeric:n { #1 }
}
\cs_new:Nn \__datatool_parse_numeric:n
{
  \tl_set:Nn \l__datatool_parser_num_tl { #1 }
}
```


If suffix is blank then it may just be the symbol.

```
\exp_args:NV \tl_if_blank:nT \l__datatool_suffix_tl
{
  \tl_clear:N \l__datatool_datum_currency_tl
}
}
```

Handler macro for currency iterator for property map.

```
\cs_new:Nn \__datatool_prop_parse_currency_do:nn
{
  \__datatool_if_starts_or_ends_with:VvTF
  \l__datatool_datum_original_value_tl
  { dtl@curr@ #2 @tl }
  {
    \tl_set_eq:NN \l__datatool_datum_currency_tl \l__datatool_prefix_tl
    \tl_set:Nn \l__datatool_datum_currency_code_tl { #2 }
  }
  {
    \__datatool_if_starts_or_ends_with:VvTF
    \l__datatool_datum_original_value_tl
    { dtl@curr@ #2 @sym }
    {
      \tl_set_eq:NN \l__datatool_datum_currency_tl \l__datatool_prefix_tl
      \tl_set:Nn \l__datatool_datum_currency_code_tl { #2 }
    }
    {
      \cs_if_exist:cT { datatool #1 symbolprefix }
      {
        \__datatool_if_starts_or_ends_with:VeTF
        \l__datatool_datum_original_value_tl
        { #1 \exp_not:v { dtl@curr@ #2 @tl } }
        {
          \tl_set_eq:NN \l__datatool_datum_currency_tl \l__datatool_prefix_tl
          \tl_set:Nn \l__datatool_datum_currency_code_tl { #2 }
        }
        {
          \__datatool_if_starts_or_ends_with:VeTF
          \l__datatool_datum_original_value_tl
          { #1 \exp_not:v { dtl@curr@ #2 @sym } }
          {
            \tl_set_eq:NN \l__datatool_datum_currency_tl \l__datatool_prefix_tl
            \tl_set:Nn \l__datatool_datum_currency_code_tl { #2 }
          }
        }
      }
    }
  }
}
\__datatool_if_empty:NF \l__datatool_datum_currency_tl
{
  \prop_map_break:
}
```



```

{
  \quark_if_nil:nTF { #3 }
  {
    \__datatool_parse_numeric:n { #2 }
    \ifnum\@dtl@datatype = \c_datatool_string_int
    \else
      \@dtl@datatype = \c_datatool_currency_int
      \tl_set:Nn \l__datatool_datum_currency_tl { #1 }
    \fi
  }
  {
    \@dtl@datatype = \c_datatool_string_int
  }
}

```

Parse content that starts with \DTLfmtcurr.

```

\cs_new:Npn \__datatool_get_fmtcurr_datum:w
  \DTLfmtcurr #1 #2 #3 \q_stop
  {
    \quark_if_nil:nTF { #3 }
    {
      \__datatool_parse_numeric:n { #2 }
      \ifnum\@dtl@datatype = \c_datatool_string_int
      \else
        \tl_set:Nn \l__datatool_datum_currency_code_tl { #1 }
        \@dtl@datatype = \c_datatool_currency_int
        \tl_set:Nn \l__datatool_datum_currency_tl { \DTLcurr { #1 } }
      \fi
    }
    {
      \@dtl@datatype = \c_datatool_string_int
    }
  }
}

```

Only parse for dates and times if enabled. Note that the boolean setting is just for general parsing commands. Temporal values can be explicitly parsed.

```

\prg_new_conditional:Npnn \__datatool_parse_datetime_if_enabled:n #1
  { T, F, TF }
  {
    \bool_if:NTF \l__datatool_parse_datetime_bool
    {
      \__datatool_parse_datetime:nTF { #1 }
      { \prg_return_true: }
      { \prg_return_false: }
    }
    { \prg_return_false: }
  }
}

```

Test if the given argument is a token list containing datum.

```

\cs_new:Nn \__datatool_if_datum_tl:nTF
  {

```

```

\tl_if_single_token:nTF { #1 }
{
  \exp_args:No \tl_if_head_eq_meaning:nTF { #1 } \__datatool_datum:nnnn
  { #2 }
  { #3 }
}
{ #3 }
}
Added v3.1: Not a number warning:
\cs_new:Nn \datatool_warn_not_number:n
{
  \PackageWarning { datatool-base } { #1 }
}

```

\DTLconverttodecimal{<num>}{<cmd>}

\DTLconverttodecimal

\DTLconverttodecimal will convert locale dependent <num> a decimal number in a standard form that can be used in arithmetical calculations. The resulting number is stored in <cmd>.

```

\NewDocumentCommand \DTLconverttodecimal { m m }
{
  \tl_if_single_token:nTF { #1 }
  {
    \exp_args:No \__datatool_parse_datum:n { #1 }
  }
  {
    \__datatool_parse_datum:n { #1 }
  }
  \datatool_if_numeric_datum_type:nF { \@dtl@datatype }
  {
    \datatool_warn_not_number:n
    { Can't ~ convert ~ non-numerical ~ ` #1 ' ~ to ~ decimal }
  }
  \tl_if_empty:NTF \l__datatool_datum_value_tl
  { \tl_set:Nn #2 { 0 } }
  { \tl_set_eq:NN #2 \l__datatool_datum_value_tl }
}

```

\DTLdecimaltolocale{<number>}{<cmd>}

\DTLdecimaltolocale

Define command to convert a decimal number into the locale dependent format. Stores result in <cmd> which must be a control sequence.

```

\newrobustcmd*{\DTLdecimaltolocale}[2]{%
  \tl_set:Nn #2 { #1 }
  \regex_replace_case_once:nN

```

```

{
  \c_datatool_numeric_leading_zeros_regex { \1 \2 }
  \c_datatool_decimal_redundant_zeros_regex { \1 \2 }
  \c_datatool_decimal_implicit_zero_regex { \1 0 \2 }
}
#2
\regex_replace_case_once:nNTF
{
  \c_datatool_decimal_grps_regex
  { \1 \2 \u{__datatool_decimal_tl} \3 }
  \c_datatool_decimal_grps_i_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3 \u{__datatool_decimal_tl} \4 }
  \c_datatool_decimal_grps_ii_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3
    \u{__datatool_numbergroup_tl} \4
    \u{__datatool_decimal_tl} \5 }
  \c_datatool_decimal_grps_iii_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3
    \u{__datatool_numbergroup_tl} \4
    \u{__datatool_numbergroup_tl} \5
    \u{__datatool_decimal_tl} \6 }
}
#2
{
  \tl_set:Ne #2
  {
    \exp_not:N \__datatool_datum:nnnn
    { \exp_not:V #2 }
    { #1 }
    { }
    { \exp_not:N \c_datatool_decimal_int }
  }
}
\regex_replace_case_once:nNTF
{
  \c_datatool_integer_grps_i_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3 }
  \c_datatool_integer_grps_ii_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3
    \u{__datatool_numbergroup_tl} \4 }
  \c_datatool_integer_grps_iii_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3
    \u{__datatool_numbergroup_tl} \4
    \u{__datatool_numbergroup_tl} \5 }
}
This last one ensures that the true branch is followed:
  \c_datatool_integer_no_grps_regex { \1 \2 }
}
#2

```

```

{
  \tl_set:Nc #2
  {
    \exp_not:N \__datatool_datum:nnnn
    { \exp_not:V #2 }
    { #1 }
    { }
    { \exp_not:N \c_datatool_integer_int }
  }
}
{

```

This is only a warning rather than an error to allow for databases that contain markup (e.g. `\textendash` or “N/A”) to indicate a missing value. The numeric functions may either interpret strings as zero or skip them.

```

  \datatool_warn_not_number:n
  {
    Can't ~ convert ~ `#1' ~ to ~ decimal: ~ not ~ a ~ number
  }
  \tl_set:Nn #2
  {
    \__datatool_datum:nnnn
    { #1 }
    { }
    { }
    { \c_datatool_string_int }
  }
}
}
}
}

```

```

\DTLdecimaltocurrency[<currency symbol>]{<number>}
{<cmd>}

```

`\DTLdecimaltocurrency`

This converts a decimal number into the locale dependent currency format. Stores result in `<cmd>` which must be a control sequence. An empty value will be treated as zero.

```

\NewDocumentCommand{\DTLdecimaltocurrency} { O{} m m }
{
  \__datatool_decimal_to_currency:nnN { #1 } { #2 } { #3 }
}

```

Round currency to this many places (set to empty for no rounding):

```

\newcommand\DTLCurrentLocaleCurrencyDP{2}
\cs_new:Nn \__datatool_decimal_to_currency:nnN
{
  \__datatool_decimal_to_currency:nnNn { #1 } { #2 } #3 { }
}

```

```

}
\cs_generate_variant:Nn \__datatool_decimal_to_currency:nnN { VVN , nVN }
\cs_new:Nn \__datatool_decimal_to_currency:nnNn
{
\regex_match:NnTF \c_datatool_any_numeric_regex { #2 }
{
\tl_if_empty:NNTF \DTLCurrentLocaleCurrencyDP
{
\tl_set:Nn #3 { #2 }
\tl_if_empty:NNTF #3
{
\tl_set:Nn #3 { 0 }
}
}
\regex_replace_once:NnN
\c_datatool_integer_leading_zeros_regex { \1 \2 } #3
}
}
{
\tl_if_empty:NNTF { #2 }
{
\dtlround { #3 } { 0 } { \DTLCurrentLocaleCurrencyDP }
}
{
\dtlround { #3 } { #2 } { \DTLCurrentLocaleCurrencyDP }
}
\tl_set:Ne #3
{
\exp_args:Ne \__datatool_decimal_trunc_pad_zeros:nn
{ #3 }
{ \DTLCurrentLocaleCurrencyDP }
}
}
\regex_replace_case_once:nN
{
\c_datatool_decimal_grps_regex { \1 \2 \u{__datatool_decimal_tl} \3 }
\c_datatool_decimal_grps_i_regex
{ \1 \2 \u{__datatool_numbergroup_tl} \3 \u{__datatool_decimal_tl} \4 }
\c_datatool_decimal_grps_ii_regex
{ \1 \2 \u{__datatool_numbergroup_tl} \3
\u{__datatool_numbergroup_tl} \4
\u{__datatool_decimal_tl} \5 }
\c_datatool_decimal_grps_iii_regex
{ \1 \2 \u{__datatool_numbergroup_tl} \3
\u{__datatool_numbergroup_tl} \4
\u{__datatool_numbergroup_tl} \5
\u{__datatool_decimal_tl} \6 }
\c_datatool_integer_grps_i_regex
{ \1 \2 \u{__datatool_numbergroup_tl} \3 }

```

```

\c_datatool_integer_grps_ii_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3
    \u{__datatool_numbergroup_tl} \4 }
\c_datatool_integer_grps_iii_regex
  { \1 \2 \u{__datatool_numbergroup_tl} \3
    \u{__datatool_numbergroup_tl} \4
    \u{__datatool_numbergroup_tl} \5 }
}
#3
\tl_set:Ne \l__datatool_datum_currency_code_tl { #4 }
\tl_if_blank:nTF { #1 }
{
  \tl_if_empty:NTF \l__datatool_datum_currency_code_tl
  {
    \seq_if_in:NVTF
      \l_datatool_regional_currencies_seq
      \DTLCurrencyCode
    {
      \tl_set:Ne #3
      {
        \exp_not:N \__datatool_datum:nxxx
        {
          \exp_not:N \DTLfmtcurr
            { \DTLCurrencyCode }
            { \exp_not:V #3 }
        }
        { #2 }
        { \exp_not:V \@dtl@currency }
        { \exp_not:N \c_datatool_currency_int }
      }
    }
  }
  {
    \tl_set:Ne #3
    {
      \exp_not:N \__datatool_datum:nxxx
      {
        \exp_not:N \DTLfmtcurrency
          { \exp_not:V \@dtl@currency }
          { \exp_not:V #3 }
        }
        { #2 }
        { \exp_not:V \@dtl@currency }
        { \exp_not:N \c_datatool_currency_int }
      }
    }
  }
}
{
  \tl_set:Ne #3
  {
    \exp_not:N \__datatool_datum:nxxx
  }
}

```

```

    {
      \exp_not:N \DTLfmtcurr
      { \l__datatool_datum_currency_code_tl }
      { \exp_not:V #3 }
    }
    { #2 }
    {
      \exp_not:N \DTLcurr
      { \l__datatool_datum_currency_code_tl }
    }
    { \exp_not:N \c_datatool_currency_int }
  }
}
{
  \tl_if_empty:NT \l__datatool_datum_currency_code_tl
  {
    \datatool_get_currency_code:NV
    \l__datatool_datum_currency_code_tl
    \l__datatool_datum_currency_tl
    \tl_if_eq:NnT
    \l__datatool_datum_currency_code_tl { XXX }
    {
      \tl_clear:N \l__datatool_datum_currency_code_tl
    }
  }
}
\tl_if_empty:NTF \l__datatool_datum_currency_code_tl
{
  \tl_set:Ne #3
  {
    \exp_not:N \__datatool_datum:nxxx
    {
      \exp_not:N \DTLfmtcurrency
      { \exp_not:n { #1 } }
      { \exp_not:V #3 }
    }
    { #2 }
    { \exp_not:n { #1 } }
    { \exp_not:N \c_datatool_currency_int }
  }
}
{
  \tl_set:Ne #3
  {
    \exp_not:N \__datatool_datum:nxxx
    {
      \exp_not:N \DTLfmtcurr
      { \l__datatool_datum_currency_code_tl }
      { \exp_not:V #3 }
    }
  }
}

```

```

    { #2 }
    { \exp_not:n { #1 } }
    { \exp_not:N \c_datatool_currency_int }
  }
}
}
{

```

This is only a warning rather than an error to allow for databases that contain markup (e.g. `\textendash` or “N/A”) to indicate a missing value. The numeric functions may either interpret strings as zero or skip them.

```

\datatool_warn_not_number:n
{
  Can't ~ convert ~ `#2' ~ to ~ currency: ~ not ~ a ~ number
}
\tl_set:Nn #3
{
  \__datatool_datum:nnnn
  { #2 }
  { }
  { }
  { \c_datatool_string_int }
}
}
}
\cs_generate_variant:Nn \__datatool_decimal_to_currency:nnNn
{ VVNV , nVNV }

```

```
\DTLdecimaltodatetime{<number>}{<cmd>}
```

`\DTLdecimaltodatetime`

Define command to convert a decimal number into a datetime datum. Stores result in `<cmd>` which must be a control sequence.

```

\NewDocumentCommand \DTLdecimaltodatetime { m m }
{
  \datatool_decimal_to_temporal:Nnn
  #2 { \c_datatool_datetime_int } { #1 }
}

```

```
\DTLdecimaltodate{<JDN>}{<cmd>}
```

`\DTLdecimaltodate`

Define command to convert a number (a Julian Day Number) into a date datum. Stores result in `<cmd>` which must be a control sequence.

```

\NewDocumentCommand \DTLdecimaltodate { m m }
{
  \datatool_decimal_to_temporal:Nnn

```

```

    #2 { \c_datatool_date_int } { #1 }
}

```

```

\DTLdecimaltotime{<JT>}{<cmd>}

```

\DTLdecimaltotime

Define command to convert a decimal number (Julian time of day fraction) into a time datum. Stores result in *<cmd>* which must be a control sequence.

```

\NewDocumentCommand \DTLdecimaltotime { m m }
{
  \datatool_decimal_to_temporal:Nnn
    #2 { \c_datatool_time_int } { #1 }
}

```

2.4.2 Dates and Times

New to version 3.0. No localisation is performed. These functions just deal with parsing ISO dates, times and timestamps. There are in total eight numeric elements of a timestamp: year, month number (1–12), day of month number (1–31), hour of day number (0–23), minute of hour number (0–59), seconds of minute number (0–59), time zone hour offset (–12+12), and time zone minute offset (0–59). This can lead to commands with a lot of arguments, so a specially formatted sequence with 8 items is sometimes used instead. Each item is formatted when it is set in the sequence to make it easier to reconstruct a timestamp.

Dates, times and timestamps can be represented numerically. The Julian Day Number (JDN) is the integer number of whole solar days since noon Universal Time. A value of zero represents Monday 1st January 4713 BC, according to the proleptic Julian Calendar. So, noon 1st January 2000 has the Julian Day Number 2451545. The time of day is represented as a fractional number from noon. A negative value is a time before noon. A positive number is a time after noon. Noon has a value of 0.0. Twelve hours before noon, that is, the previous midnight has a value of –0.5. Twelve hours after noon, that is, the following midnight has a value of 0.5.

The Julian Date is a decimal that is simply the sum of the Julian Day Number and the time fraction. For example, $2451545 + 0.5 = 2451545.5$ is midnight after noon 2000-01-01 and $2451545 - 0.5 = 2451544.5$ is midnight before noon 2000-01-01. Note that while the term “Julian Date” is sometimes used to refer to the ordinal day of year in other works, from `datatool`’s point of view, “Julian Date” is the decimal sum of the JDN and the time of day fraction.

Since JDN 0 is a Monday, the day of the week (starting with Monday=0) can be obtained from the remainder of the integer division of the Julian Day Number and 7 (that is, $\langle JDN \rangle$ modulo 7).

A temporal datum command has the data type set to one of the temporal identifiers (datetime, date or time). The string part may be the original string parsed or maybe a formatted version of the temporal value.

`\DTLtemporalvalue` It's useful to retain the original ISO specification. Since the string part of the datum variable may be used to provide a localised format, the original ISO format is hidden in the value part, which is set to:

```
\DTLtemporalvalue{<number>}{<ISO>}
```

This allows both the original ISO representation to be extracted as well as the corresponding numerical value. The default definition allows the ISO part to be discarded in numerical contexts. This means that using `\DTLdatumvalue` will still expand to a numeric value, but it requires more expansion than the other numeric data types.

This command isn't an internal command as it may occur in a dbtex-3 file, which expects the normal document category codes. The number depends on the datum type: a decimal Julian date for timestamps, an integer Julian day for date only or a decimal (fraction of a day) for time only.

```
\newcommand \DTLtemporalvalue [2] { #1 }
```

```
\datatool_decimal_to_temporal:Nnn
<datum-cs>{<data-type>}{<number>}
```

Converts a number to a datum-cs.

```
\cs_new_nopar:Nn \datatool_decimal_to_temporal:Nnn
{
  \int_case:nnF { #2 }
  {
    { \c_datatool_datetime_int }
    {
      \datatool_from_julian_date:nN { #3 }
      \l_datatool_datetime_seq
      \datatool_timestamp_to_datetime_datum:NeN
      \l_datatool_datetime_seq
      { #3 }
      #1
    }
  }
  { \c_datatool_date_int }
  {
    \int_set:Nn \l_datatool_julian_int { \fp_to_int:n { #3 } }
    \datatool_from_julian_day:VNNN \l_datatool_julian_int
    \l_datatool_year_int
    \l_datatool_month_int
    \l_datatool_day_int
    \tl_set:Ne #1
    {
      \exp_not:N \_datatool_datum:nnnn
      {% formatted string
        \exp_not:N \DataToolDateFmt
        { \int_use:N \l_datatool_year_int }
        { \int_use:N \l_datatool_month_int }
      }
    }
  }
}
```

```

        { \int_use:N \l__datatool_day_int }
        {
          \datatool_julian_day_to_dow:n { \l__datatool_julian_int }
        }
      }
    {% value
      \exp_not:N \DTLtemporalvalue
      { \int_use:N \l__datatool_julian_int }
      {
        \int_use:N \l__datatool_year_int
        -
        \datatool_two_digits:N \l__datatool_month_int
        -
        \datatool_two_digits:N \l__datatool_day_int
      }
    }
    { }% no currency symbol
    { \exp_not:N \c_datatool_date_int }
  }
}
{ \c_datatool_time_int }
{
  \datatool_from_julian_time:eNNN { #3 }
  \l__datatool_hour_int
  \l__datatool_minute_int
  \l__datatool_second_int
  \tl_set:Ne #1
  {
    \exp_not:N \__datatool_datum:nnnn
    {% formatted string
      \exp_not:N \DataToolTimeFmt
      { \int_use:N \l__datatool_hour_int }
      { \int_use:N \l__datatool_minute_int }
      { \int_use:N \l__datatool_second_int }
    }
    {% value
      \exp_not:N \DTLtemporalvalue
      { #3 }
      {
        \datatool_two_digits:n { \l__datatool_hour_int }
        \c_colon_str
        \datatool_two_digits:N \l__datatool_minute_int
        \c_colon_str
        \datatool_two_digits:N \l__datatool_second_int
      }
    }
  }
  { }% no currency symbol
  { \exp_not:N \c_datatool_time_int }
}
}

```

```

}
{
\PackageError { datatool-base }
{ Invalid ~ data ~ type ~ \int_eval:n { #2 }: ~ not ~ a ~ temporal ~ type }
{
The ~ second ~ argument ~ of
\token_to_str:N \datatool_decimal_to_temporal:Nnn ~
\c_space_tl ~ should ~ be ~ one ~ of: ~
\exp_not:N \c_datatool_datetime_int , ~
\exp_not:N \c_datatool_date_int , ~ or ~
\exp_not:N \c_datatool_time_int
}
}
}
\cs_generate_variant:Nn \datatool_decimal_to_temporal:Nnn
{ NnV }

```

```

\datatool_extract_timestamp:NN{<datum-cs>}
{<result-tl>}

```

Extracts the date/time data stored in the given datum command and defines the supplied token list command to that value. If there's no date/time data in the datum command, the result token list variable will be set to empty. This may mean that the datum variable isn't a temporal variable, but may also mean that the value has lost its special markup due to expansion.

```

\cs_new:Nn \datatool_extract_timestamp:NN
{
\tl_clear:N #2
\group_begin:
\cs_set_eq:NN \DTLtemporalvalue \use_ii:nn
\tl_set:Ne \l__datatool_tmpa_tl
{ \DTLdatumvalue { #1 } }
\regex_match:NVTF
\c_datatool_temporal_regex \l__datatool_tmpa_tl
{
\tl_set:Ne \l__datatool_tmpa_tl
{ \exp_not:N \tl_set:Nn \exp_not:N #2 { \l__datatool_tmpa_tl } }
}
{
\tl_clear:N \l__datatool_tmpa_tl
}
\exp_after:wN
\group_end:
\l__datatool_tmpa_tl
}

```

\DTLdatumtoDTM{<datum-cs>}{<DTM-name>}

\DTLdatumtoDTM

Converts the time stamp stored in the given datum command to a datetime2 date saved with \DTMsavetimestamp, \DTMsavedate, or \DTLsavetime. If the time stamp is missing, this will attempt to recalculate the relevant information based on the numeric value and data type.

```
\NewDocumentCommand \DTLdatumtoDTM { m m }
{
  \cs_if_exist:NTF \DTMsavetimestamp
  {
    \group_begin:
      \cs_set_eq:NN \DTLtemporalvalue \use_ii:nn
```

If the value contains \DTLtemporalvalue the temporary token list variable will be set to the ISO format in the second argument.

```
\tl_set:Nc \l__datatool_tmpa_tl
  { \DTLdatumvalue { #1 } }
\regex_match:NVTF
  \c_datatool_timestamp_regex \l__datatool_tmpa_tl
  {
```

Result matches a timestamp, so use \DTMsavetimestamp.

```
\tl_set:Nc \l__datatool_tmpa_tl
  { \exp_not:N \DTMsavetimestamp { #2 } { \l__datatool_tmpa_tl } }
}
{
  \regex_match:NVTF
    \c_datatool_date_regex \l__datatool_tmpa_tl
    {
```

Result only matches a date, so use \DTMsavedate.

```
\tl_set:Nc \l__datatool_tmpa_tl
  { \exp_not:N \DTMsavedate { #2 } { \l__datatool_tmpa_tl } }
}
{
  \regex_extract_once:NVNTF
    \c_datatool_time_regex
    \l__datatool_tmpa_tl
    \l_datatool_timestamp_match_seq
    {
```

Result only matches a time, so use \DTMsavetime but the seconds may be missing, which are required.

```
\tl_if_empty:eTF
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
  {
    \tl_set:Nc \l__datatool_tmpa_tl
      { \exp_not:N \DTMsavetime { #2 } { \l__datatool_tmpa_tl : 00 } }
  }
  {
```

```

\l_set:Ne \l__datatool_tmpa_tl
  { \exp_not:N \DTMSavetime { #2 } { \l__datatool_tmpa_tl } }
}
}
{
\l_if_empty:NTF \l__datatool_tmpa_tl
  {
  \PackageError { datatool-base }
  {
  Can't ~ obtain ~ timestamp. ~
  No ~ value ~ associated with ` \token_to_str:N #1 '
  }
  {
  The ~ provided ~ value ~ doesn't ~ seem ~ to ~
  be ~ numeric. ~ If ~ you ~ were ~ expecting ~ it ~
  to ~ be ~ parsed ~ as ~ a ~ date/time ~ then ~
  \bool_if:NTF \l__datatool_parse_datetime_bool
  {
  use ~ \token_to_str:N \DTLsetup { datetime=parse-
only } ~
  or ~ \token_to_str:N \DTLsetup { datetime=reformat }
  }
  {
  check ~ the ~ original ~ source ~ matched ~
  the ~ correct ~ format
  }
  }
}
}
{
\int_set:Nn \@dtl@datatype { \DTLdatumtype { #1 } }
\int_case:nn { \@dtl@datatype }
{
{ \c_datatool_integer_int }
{
\int_set_eq:NN \@dtl@datatype \c_datatool_date_int
}
{ \c_datatool_decimal_int }
{
\fp_compare:nNnTF
  { \fp_abs:n { \l__datatool_tmpa_tl } }
  < { \c_one_fp }
  {
  \int_set_eq:NN \@dtl@datatype \c_datatool_time_int
  }
  {
  \int_set_eq:NN \@dtl@datatype \c_datatool_datetime_int
  }
}
}
\int_case:nnF { \@dtl@datatype }

```

```

{
  { \c_datatool_datetime_int }
  {
    \PackageWarning { datatool-base }
    {
      No ~ timestamp ~ could ~ be ~ found ~ in ~ the ~
      provided ~ datum ~ command. ~ Value ~ found: ~
      \l_datatool_tmpa_tl . ~ I'm ~ going ~
      to ~ assume ~ this ~ is ~ a ~ Julian ~ Date
    }
    \datatool_from_julian_date:VN
    \l_datatool_tmpa_tl
    \l_datatool_datetime_seq
    \tl_set:Ne \l_datatool_tmpa_tl
    {
      \exp_not:N \DTMsavetimestamp { #2 }
      {
        \datatool_timestamp_to_iso:N
        \l_datatool_datetime_seq
      }
    }
  }
}
{ \c_datatool_date_int }
{
  \PackageWarning { datatool-base }
  {
    No ~ timestamp ~ could ~ be ~ found ~ in ~ the ~
    provided ~ datum ~ command. ~ Value ~ found: ~
    \l_datatool_tmpa_tl . ~ I'm ~ going ~
    to ~ assume ~ this ~ is ~ a ~ Julian ~ Day ~ Number
  }
  \int_set:Nn \l_datatool_julian_int
  { \l_datatool_tmpa_tl }
  \datatool_from_julian_day:VNNN
  \l_datatool_julian_int
  \l_datatool_year_int
  \l_datatool_month_int
  \l_datatool_day_int
  \tl_set:Ne \l_datatool_tmpa_tl
  {
    \exp_not:N \DTMsavenoparsedate { #2 }
    { \int_use:N \l_datatool_year_int }
    { \int_use:N \l_datatool_month_int }
    { \int_use:N \l_datatool_day_int }
    {
      \datatool_julian_day_to_dow:n
      { \l_datatool_julian_int }
    }
  }
}
}

```

```

{ \c_datatool_time_int }
{
  \PackageWarning { datatool-base }
  {
    No ~ timestamp ~ could ~ be ~ found ~ in ~ the ~
    provided ~ datum ~ command. ~ Value ~ found: ~
    \l_datatool_tmpa_tl . ~ I'm ~ going ~
    to ~ assume ~ this ~ is ~ a ~ Julian ~
    time ~ of ~ day ~ fraction
  }
  \fp_set:Nn \l_datatool_julian_fp
  { \l_datatool_tmpa_tl }
  \datatool_from_julian_time:nNNN
  { \l_datatool_julian_fp }
  \l_datatool_hour_int
  \l_datatool_minute_int
  \l_datatool_second_int
  \tl_set:Ne \l_datatool_tmpa_tl
  {
    \exp_not:N \DTMSavetime { #2 }
    {
      \int_use:N \l_datatool_year_int
      \c_colon_str
      \int_use:N \l_datatool_month_int
      \c_colon_str
      \int_use:N \l_datatool_day_int
    }
  }
}
}
{
  \PackageError { datatool-base }
  {
    No ~ timestamp ~ could ~ be ~ found ~ in ~ the ~
    provided ~ datum ~ command. ~ Value ~ found: ~
    \l_datatool_tmpa_tl
  }
  {
    The ~ datum ~ value ~ supplied ~ can't ~ be ~
    interpreted ~ as ~ a ~ timestamp, ~ date ~ or ~ time.
  }
}
}
}
}
}
}
\exp_after:wN
\group_end: \l_datatool_tmpa_tl
}

```

```

{
  \PackageError { datatool-base }
  {
    \token_to_str:N \DTLdatumtoDTM ~ \c_space_tl ~
    can't ~ save ~ time ~ stamp. ~
    Command ~ \token_to_str:N \DTMsavetimestamp ~ \c_space_tl ~
    undefined ~ (datetime2 ~ required)
  }
  { You ~ need ~ to ~ load ~ datetime2.sty }
}
}

```

Formatting Syntax: $\langle datum-cs \rangle \langle value-cs \rangle \{ \langle string value \rangle \}$

Used to set the value part of a temporal datum and the update token list variable. If the $\{ \langle string value \rangle \}$ argument is empty, the string part is obtained by formatting the temporal value.

```

\cs_new:Nn \__datatool_set_datetime_value:NNn
{
  \int_case:nn { \@dtl@datatype }
  {
    { \c_datatool_datetime_int }
    {
      \tl_set:Ne #2
      {
        \exp_not:N \DTLtemporalvalue
        { \fp_use:N \l__datatool_julian_fp }
        {
          \__datatool_tm_iso:
        }
      }
    }
    \tl_if_empty:nTF { #3 }
    {
      \__datatool_set_datum:NeVnn #1
      {
        \exp_not:N \DataToolDateTimeFmt
        {
          { \__datatool_tm_yr: }
          { \__datatool_tm_mn: }
          { \__datatool_tm_dy: }
          { \__datatool_tm_dow: }
        }
        {
          { \__datatool_tm_hr: }
          { \__datatool_tm_mi: }
          { \__datatool_tm_se: }
        }
        {
          { \__datatool_tm_tzh: }
          { \__datatool_tm_tzm: }
        }
      }
    }
  }
}

```

```

    }
  }
  #2
  { }
  { \c_datatool_datetime_int }
}
{
  \__datatool_set_datum:NnVnn #1
  { #3 }
  #2
  { }
  { \c_datatool_datetime_int }
}
}
{ \c_datatool_date_int }
{
  \tl_set:Ne #2
  {
    \exp_not:N \DTLtemporalvalue
    { \int_use:N \l__datatool_julian_int }
    {
      \__datatool_tm_iso_date:
    }
  }
}
\tl_if_empty:nTF { #3 }
{
  \__datatool_set_datum:NeVnn #1
  {
    \exp_not:N \DataToolDateFmt
    { \__datatool_tm_yr: }
    { \__datatool_tm_mn: }
    { \__datatool_tm_dy: }
    { \__datatool_tm_dow: }
  }
  #2
  { }
  { \c_datatool_date_int }
}
{
  \__datatool_set_datum:NnVnn #1
  { #3 }
  #2
  { }
  { \c_datatool_date_int }
}
}
{ \c_datatool_time_int }
{
  \tl_set:Ne #2
  {

```


Re-initialise date/time individual scratch variables. That is, set them all back to zero.

```
\cs_new:Nn \__datatool_tm_var_init:
{
  \int_zero:N \l__datatool_year_int
  \int_zero:N \l__datatool_month_int
  \int_zero:N \l__datatool_day_int
  \int_zero:N \l__datatool_hour_int
  \int_zero:N \l__datatool_minute_int
  \int_zero:N \l__datatool_second_int
  \int_zero:N \l__datatool_tzhour_int
  \int_zero:N \l__datatool_tzminute_int
  \int_zero:N \l__datatool_julian_int
  \fp_zero:N \l__datatool_julian_fp
  \fp_zero:N \l__datatool_time_fp
}
```

Date time stamp regular expression. Time zone may be omitted. Separator between date and time may be either space or “T”.

```
\regex_const:Nn \c_datatool_timestamp_regex
{
  \A \s*
  ( \d+ ) \x { 2D } ( \d{2} ) \x { 2D } ( \d{2} )
  (?: \x { 54 } | \s+ )
  ( \d{2} ) \x { 3A } ( \d{2} ) \x { 3A } ( \d{2} )
  ( \x { 5A } | [+\-]? \d{2} \x { 3A } ? \d{2} ) ?
  \s* \Z
}
```

Date only.

```
\regex_const:Nn \c_datatool_date_regex
{
  \A \s*
  ( \d+ ) \x { 2D } ( \d{2} ) \x { 2D } ( \d{2} )
  \s* \Z
}
```

Time only. Seconds are optional.

```
\regex_const:Nn \c_datatool_time_regex
{
  \A \s*
  ( [+\-]? \d{2} ) \x { 3A } ( \d{2} ) (?: \x { 3A } ( \d{2} ) ) ?
  \s* \Z
}
```

Maybe timestamp or just date or just time:

```
\regex_const:Nn \c_datatool_temporal_regex
{
  (?:
    (?: \d+ ) \x { 2D } (?: \d{2} ) \x { 2D } (?: \d{2} )
    (?:
      (?: \x { 54 } | \s+ )

```

```

        (?: \d{2} ) \x { 3A } (?: \d{2} ) \x { 3A } (?: \d{2} )
        (?: \x { 5A } | [\+\-]? \d{2} \x { 3A } ? \d{2} ) ?
    ) ?
) |
(?:
    (?: \d{2} ) \x { 3A } (?: \d{2} ) (?: \x { 3A } (?: \d{2} ) )?
)
}

```

Timestamp Sequences Time stamp sequences are just a nine-item sequence, where each item is a numeric value. All but the year (item 1) and day of week (item 9) should be correctly zero-padded. The year should include the century. For example, if the year is given as 24 then that means 0024 not 2024. The day of week item may be negative to indicate a missing value.

The following commands are simply wrappers that use normal sequence commands.

```

\cs_new:Nn \datatool_timestamp_new:N
{
    \seq_new:N #1
    \datatool_timestamp_zero:N #1
}

```

Constant representing 0000-00-00T00:00:00+00:00 (used for initialisation).

```

\seq_const_from_clist:Nn \c_datatool_timestamp_zero_seq
{ 0000 , 00 , 00 , 00 , 00 , 00 , +00 , 00 , -1 }

```

Resets all elements of a timestamp sequence.

```

\cs_new:Nn \datatool_timestamp_zero:N
{
    \seq_set_eq:NN #1 \c_datatool_timestamp_zero_seq
}

```

Shortcut for internal scratch variable.

```

\cs_new:Nn \__datatool_tm_seq_init:
{
    \datatool_timestamp_zero:N
    \l__datatool_datetime_seq
}

```

The following commands assume the provided sequence has been correctly defined with nine numeric items, as described above. Check for empty argument as regex match can have optional parts.

Extract year from a timestamp sequence. (First item.)

```

\cs_new:Nn \datatool_timestamp_get_year:N
{
    \seq_item:Nn #1 { 1 }
}

```

Shortcut for internal scratch variable.

```

\cs_new:Nn \__datatool_tm_yr:
{

```

```

        \datatool_timestamp_get_year:N
        \l__datatool_datetime_seq
    }
Set year (item 1). If empty, assume current year.
\cs_new:Nn \datatool_timestamp_set_year:Nn
{
    \tl_if_empty:nTF { #2 }
    {
        \exp_args:NNne \seq_set_item:Nnn #1
            { 1 } { \int_use:N \c_sys_year_int }
    }
    {
        \seq_set_item:Nnn #1 { 1 } { #2 }
    }
}
\cs_generate_variant:Nn \datatool_timestamp_set_year:Nn
{ Ne, NV }
As above but add century if between 0 and 99.
\cs_new:Nn \datatool_timestamp_set_year_add_century:Nn
{
    \tl_if_empty:nTF { #2 }
    {
        \exp_args:NNne \seq_set_item:Nnn #1
            { 1 } { \int_use:N \c_sys_year_int }
    }
    {
        \bool_lazy_or:nnTF
            { \int_compare_p:nNn { #2 } < { \c_zero_int } }
            { \int_compare_p:nNn { #2 } > { 99 } }
        {
            \seq_set_item:Nnn #1 { 1 } { #2 }
        }
        {
            \datatool_timestamp_set_year:Ne #1
            {
                \int_eval:n
                {
                    ( \int_div_truncate:nn { \c_sys_year_int } { 100 } ) * 100
                    + #2
                }
            }
        }
    }
}
\cs_generate_variant:Nn \datatool_timestamp_set_year_add_century:Nn
{ Ne, NV }
Shortcut for internal scratch variable.
\cs_new:Nn \__datatool_tm_set_yr:n

```

```

{
  \datatool_timestamp_set_year:Nn
    \l__datatool_datetime_seq { #1 }
}
\cs_generate_variant:Nn \__datatool_tm_set_yr:n { e }
  Extract month from sequence. (Second item.)
\cs_new:Nn \datatool_timestamp_get_month:N
{
  \seq_item:Nn #1 { 2 }
}
Shortcut for internal scratch variable.
\cs_new:Nn \__datatool_tm_mn:
{
  \datatool_timestamp_get_month:N
    \l__datatool_datetime_seq
}
Set month (item 2):
\cs_new:Nn \datatool_timestamp_set_month:Nn
{
  \tl_if_empty:nTF { #2 }
  {
    \seq_set_item:Nnn #1 { 2 } { 00 }
  }
  {
    \exp_args:NNne \seq_set_item:Nnn
      #1 { 2 } { \datatool_two_digits:n { #2 } }
  }
}
\cs_generate_variant:Nn \datatool_timestamp_set_month:Nn
{ Ne, NV }
Shortcut for internal scratch variable.
\cs_new:Nn \__datatool_tm_set_mn:n
{
  \datatool_timestamp_set_month:Nn
    \l__datatool_datetime_seq { #1 }
}
\cs_generate_variant:Nn \__datatool_tm_set_mn:n { e }
  Extract day from sequence. (Third item.)
\cs_new:Nn \datatool_timestamp_get_day:N
{
  \seq_item:Nn #1 { 3 }
}
Shortcut for internal scratch variable.
\cs_new:Nn \__datatool_tm_dy:
{
  \datatool_timestamp_get_day:N

```

```

        \l__datatool_datetime_seq
    }
Set day (item 3):
\cs_new:Nn \datatool_timestamp_set_day:Nn
{
    \tl_if_empty:nTF { #2 }
    {
        \seq_set_item:Nnn #1 { 3 } { 00 }
    }
    {
        \exp_args:NNne \seq_set_item:Nnn
            #1 { 3 } { \datatool_two_digits:n { #2 } }
    }
}
\cs_generate_variant:Nn \datatool_timestamp_set_day:Nn
{ Ne, NV }
Shortcut for internal scratch variable.
\cs_new:Nn \__datatool_tm_set_dy:n
{
    \datatool_timestamp_set_day:Nn
        \l__datatool_datetime_seq { #1 }
}
\cs_generate_variant:Nn \__datatool_tm_set_dy:n { e }
    Extract hour from sequence. (Fourth item.)
\cs_new:Nn \datatool_timestamp_get_hour:N
{
    \seq_item:Nn #1 { 4 }
}
Shortcut for internal scratch variable.
\cs_new:Nn \__datatool_tm_hr:
{
    \datatool_timestamp_get_hour:N
        \l__datatool_datetime_seq
}
Set hour (item 4):
\cs_new:Nn \datatool_timestamp_set_hour:Nn
{
    \tl_if_empty:nTF { #2 }
    {
        \seq_set_item:Nnn #1 { 4 } { 00 }
    }
    {
        \exp_args:NNne \seq_set_item:Nnn
            #1 { 4 } { \datatool_two_digits:n { #2 } }
    }
}
\cs_generate_variant:Nn \datatool_timestamp_set_hour:Nn

```

```
{ Ne, NV }
```

Shortcut for internal scratch variable.

```
\cs_new:Nn \__datatool_tm_set_hr:n  
{  
  \datatool_timestamp_set_hour:Nn  
    \l__datatool_datetime_seq { #1 }  
}  
\cs_generate_variant:Nn \__datatool_tm_set_hr:n { e }  
  Extract minute from sequence. (Fifth item.)  
\cs_new:Nn \datatool_timestamp_get_minute:N  
{  
  \seq_item:Nn #1 { 5 }  
}
```

Shortcut for internal scratch variable.

```
\cs_new:Nn \__datatool_tm_mi:  
{  
  \datatool_timestamp_get_minute:N  
    \l__datatool_datetime_seq  
}
```

Set minute (item 5):

```
\cs_new:Nn \datatool_timestamp_set_minute:Nn  
{  
  \tl_if_empty:nTF { #2 }  
  {  
    \seq_set_item:Nnn #1 { 5 } { 00 }  
  }  
  {  
    \exp_args:NNne \seq_set_item:Nnn  
      #1 { 5 } { \datatool_two_digits:n { #2 } }  
  }  
}  
\cs_generate_variant:Nn \datatool_timestamp_set_minute:Nn  
{ Ne, NV }
```

Shortcut for internal scratch variable.

```
\cs_new:Nn \__datatool_tm_set_mi:n  
{  
  \datatool_timestamp_set_minute:Nn  
    \l__datatool_datetime_seq { #1 }  
}  
\cs_generate_variant:Nn \__datatool_tm_set_mi:n { e }  
  Extract second from sequence. (Sixth item.)  
\cs_new:Nn \datatool_timestamp_get_second:N  
{  
  \seq_item:Nn #1 { 6 }  
}
```

Shortcut for internal scratch variable.

```
\cs_new:Nn \__datatool_tm_se:
{
  \datatool_timestamp_get_second:N
  \l__datatool_datetime_seq
}
```

Set second (item 6):

```
\cs_new:Nn \datatool_timestamp_set_second:Nn
{
  \tl_if_empty:nTF { #2 }
  {
    \seq_set_item:Nnn #1 { 6 } { 00 }
  }
  {
    \exp_args:NNne \seq_set_item:Nnn
    #1 { 6 } { \datatool_two_digits:n { #2 } }
  }
}
\cs_generate_variant:Nn \datatool_timestamp_set_second:Nn
{ Ne, NV }
```

Shortcut for internal scratch variable.

```
\cs_new:Nn \__datatool_tm_set_se:n
{
  \datatool_timestamp_set_second:Nn
  \l__datatool_datetime_seq { #1 }
}
\cs_generate_variant:Nn \__datatool_tm_set_se:n { e }
Extract time zone hour from sequence. (Seventh item.)
\cs_new:Nn \datatool_timestamp_get_tzhour:N
{
  \seq_item:Nn #1 { 7 }
}
```

Shortcut for internal scratch variable.

```
\cs_new:Nn \__datatool_tm_tzh:
{
  \datatool_timestamp_get_tzhour:N
  \l__datatool_datetime_seq
}
```

Set time zone hour (item 7):

```
\cs_new:Nn \datatool_timestamp_set_tzhour:Nn
{
  \tl_if_empty:nTF { #2 }
  {
    \seq_set_item:Nnn #1 { 7 } { +00 }
  }
  {

```

```

        \exp_args:NNne \seq_set_item:Nnn
        #1 { 7 }
        { \datatool_signed_two_digits:n { #2 } }
    }
}
\cs_generate_variant:Nn \datatool_timestamp_set_tzhour:Nn
{ Ne, NV }

```

Shortcut for internal scratch variable.

```

\cs_new:Nn \__datatool_tm_set_tzh:n
{
    \datatool_timestamp_set_tzhour:Nn
    \l__datatool_datetime_seq { #1 }
}
\cs_generate_variant:Nn \__datatool_tm_set_tzh:n { e }
    Extract time zone minute from sequence. (Eighth item.)
\cs_new:Nn \datatool_timestamp_get_tzminute:N
{
    \seq_item:Nn #1 { 8 }
}

```

Shortcut for internal scratch variable.

```

\cs_new:Nn \__datatool_tm_tzm:
{
    \datatool_timestamp_get_tzminute:N
    \l__datatool_datetime_seq
}

```

Set time zone minute (item 8):

```

\cs_new:Nn \datatool_timestamp_set_tzminute:Nn
{
    \tl_if_empty:nTF { #2 }
    {
        \seq_set_item:Nnn #1 { 8 } { 00 }
    }
    {
        \exp_args:NNne \seq_set_item:Nnn
        #1 { 8 } { \datatool_two_digits:n { #2 } }
    }
}
\cs_generate_variant:Nn \datatool_timestamp_set_tzminute:Nn
{ Ne, NV }

```

Shortcut for internal scratch variable.

```

\cs_new:Nn \__datatool_tm_set_tzm:n
{
    \datatool_timestamp_set_tzminute:Nn
    \l__datatool_datetime_seq { #1 }
}
\cs_generate_variant:Nn \__datatool_tm_set_tzm:n { e }

```

Extract day of week from sequence. (Ninth item.)

```
\cs_new:Nn \datatool_timestamp_get_dow:N
{
  \seq_item:Nn #1 { 9 }
}
```

Shortcut for internal scratch variable.

```
\cs_new:Nn \__datatool_tm_dow:
{
  \datatool_timestamp_get_dow:N
  \l__datatool_datetime_seq
}
```

Set day of week (item 9):

```
\cs_new:Nn \datatool_timestamp_set_dow:Nn
{
  \tl_if_empty:nTF { #2 }
  {
    \seq_set_item:Nnn #1 { 9 } { -1 }
  }
  {
    \exp_args:NNne \seq_set_item:Nnn
    #1 { 9 } { #2 }
  }
}
\cs_generate_variant:Nn \datatool_timestamp_set_dow:Nn
{ Ne, NV }
```

Shortcut for internal scratch variable.

```
\cs_new:Nn \__datatool_tm_set_dow:n
{
  \datatool_timestamp_set_dow:Nn
  \l__datatool_datetime_seq { #1 }
}
\cs_generate_variant:Nn \__datatool_tm_set_dow:n { e, V }
```

Convert timestamp sequence to ISO string. Note that the supplied argument must be a timestamp sequence. That is, a sequence with 8 numeric items that have already been correctly zero-padded.

```
\cs_new:Nn \datatool_timestamp_to_iso:N
{
  \datatool_timestamp_get_year:N #1
  -
  \datatool_timestamp_get_month:N #1
  -
  \datatool_timestamp_get_day:N #1
  T
  \datatool_timestamp_get_hour:N #1
  \c_colon_str
  \datatool_timestamp_get_minute:N #1
  \c_colon_str
}
```

```

\datatool_timestamp_get_second:N #1
\datatool_timestamp_get_tzhour:N #1
\c_colon_str
\datatool_timestamp_get_tzminute:N #1
}

```

Shortcut for internal scratch variable.

```

\cs_new:Nn \__datatool_tm_iso:
{
\datatool_timestamp_to_iso:N
\l__datatool_datetime_seq
}

```

Just the year, month and date:

```

\cs_new:Nn \datatool_timestamp_to_iso_date:N
{
\datatool_timestamp_get_year:N #1
-
\datatool_timestamp_get_month:N #1
-
\datatool_timestamp_get_day:N #1
}

```

Shortcut for internal scratch variable.

```

\cs_new:Nn \__datatool_tm_iso_date:
{
\datatool_timestamp_to_iso_date:N
\l__datatool_datetime_seq
}

```

Just the time (hours, minutes and seconds):

```

\cs_new:Nn \datatool_timestamp_to_iso_time:N
{
\datatool_timestamp_get_hour:N #1
\c_colon_str
\datatool_timestamp_get_minute:N #1
\c_colon_str
\datatool_timestamp_get_second:N #1
}

```

Shortcut for internal scratch variable.

```

\cs_new:Nn \__datatool_tm_iso_time:
{
\datatool_timestamp_to_iso_time:N
\l__datatool_datetime_seq
}

```

```

\datatool_timestamp_to_datetime_datum:NnN
<timestamp seq-var>
{<Julian Date>}
<datum cs>

```

Convert a timestamp sequence variable to a datetime datum variable.

```

\cs_new:Nn \datatool_timestamp_to_datetime_datum:NnN
{
  \tl_set:Ne #3
  {
    \exp_not:N \__datatool_datum:nnnn
    {% formatted string
      \exp_not:N \DataToolDateTimeFmt
      {
        { \datatool_timestamp_get_year:N #1 }
        { \datatool_timestamp_get_month:N #1 }
        { \datatool_timestamp_get_day:N #1 }
        { \datatool_timestamp_get_dow:N #1 }
      }
      {
        { \datatool_timestamp_get_hour:N #1 }
        { \datatool_timestamp_get_minute:N #1 }
        { \datatool_timestamp_get_second:N #1 }
      }
      {
        { \datatool_timestamp_get_tzhour:N #1 }
        { \datatool_timestamp_get_tzminute:N #1 }
      }
    }
    {% value
      \exp_not:N \DTLtemporalvalue
      { #2 }
      {
        \datatool_timestamp_to_iso:N #1
      }
    }
    { }% no currency symbol
    { \exp_not:N \c_datatool_datetime_int }
  }
}
\cs_generate_variant:Nn \datatool_timestamp_to_datetime_datum:NnN
{ NeN, NVN }

```

```

\datatool_timestamp_to_date_datum:NnN
<timestamp seq-var>
{<Julian Day>}
<datum cs>

```

Convert a timestamp sequence variable to a date datum variable.

```

\cs_new:Nn \datatool_timestamp_to_date_datum:NnN
{
  \tl_set:Ne #3
  {
    \exp_not:N \__datatool_datum:nnnn
    {% formatted string
      \exp_not:N \DataToolDateFmt
      { \datatool_timestamp_get_year:N #1 }
      { \datatool_timestamp_get_month:N #1 }
      { \datatool_timestamp_get_day:N #1 }
      {
        \datatool_julian_day_to_dow:n { #2 }
      }
    }
    {% value
      \exp_not:N \DTLtemporalvalue
      { #2 }
      {
        \datatool_timestamp_to_iso_date:N #1
      }
    }
    { }% no currency symbol
    { \exp_not:N \c_datatool_date_int }
  }
}
\cs_generate_variant:Nn \datatool_timestamp_to_date_datum:NnN
{ NeN, NVN }

```

```

\datatool_timestamp_to_time_datum:NnN
<timestamp seq-var>
{<Julian Time>}
<datum cs>

```

Convert a timestamp sequence variable to a time datum variable.

```

\cs_new:Nn \datatool_timestamp_to_time_datum:NnN
{
  \tl_set:Ne #3
  {
    \exp_not:N \__datatool_datum:nnnn
    {% formatted string
      \exp_not:N \DataToolTimeFmt

```

```

        { \datatool_timestamp_get_hour:N #1 }
        { \datatool_timestamp_get_minute:N #1 }
        { \datatool_timestamp_get_second:N #1 }
    }
    {% value
    \exp_not:N \DTLtemporalvalue
    { #2 }
    {
        \datatool_timestamp_to_iso_time:N #1
    }
    }
    { }% no currency symbol
    { \exp_not:N \c_datatool_time_int }
}
}
\cs_generate_variant:Nn \datatool_timestamp_to_time_datum:NnN
{ NeN, NVN }

```

Calculations Convert Unix time to Julian date.

```

\cs_new:Nn \datatool_unix_to_julian:n
{
    \fp_eval:n { #1 / 86400 + 2440587.5 }
}

```

Convert a Julian date to Unix time. Note that the Unix time may be too large to be a TeX integer. The result will be a decimal.

```

\cs_new:Nn \datatool_julian_to_unix:n
{
    \fp_eval:n { ( #1 - 2440587.5 ) * 86400 }
}

```

```

\datatool_julian_day_to_dow:n
{<JDN>}

```

Obtains the day of week from the integer Julian Day Number.

```

\cs_new:Nn \datatool_julian_day_to_dow:n
{
    \int_mod:nn { #1 } { 7 }
}

```

```

\datatool_calc_julian_date:NN
<result fp-var>
<timestamp seq-var>

```

Calculate the Julian Date for the timestamp data contained in the timestamp sequence variable *<timestamp seq-var>* and store the resulting value in the floating-point variable *<result fp-var>*.

```

\cs_new:Nn \datatool_calc_julian_date:NN
{
  \int_compare:nNnTF { \seq_count:N #2 } = { 8 }
  {
    \seq_set_eq:NN \l_datatool_datetime_seq #2
    \datatool_calc_julian_date:
    \fp_set_eq:NN #1 \l_datatool_julian_fp
  }
  {
    \PackageError { datatool-base }
    {
      Not ~ a ~ timestamp ~ sequence: ~
      \token_to_str:N #2
    }
    {
      The ~ second ~ argument ~ of ~
      \token_to_str:N \datatool_calc_julian_date:NN ~
      \c_string_tl ~ must ~ be ~ a ~ sequence ~ containing ~
      8 ~ integer ~ elements
    }
  }
}

```

```

\datatool_calc_julian_day:Nnnn <result fp-var>
{<year>} {<month>} {<day>}

```

Calculate the Julian Day value from the given year, month and day. NB very sensitive to rounding! Don't rearrange.

```

\cs_new:Nn \datatool_calc_julian_day:Nnnn
{
  \int_set:Nn #1
  {
    #4 - 32075
    +
    \int_div_truncate:nn
    {
      1461
      *
      ( #2 + 4800 + \int_div_truncate:nn { #3 - 14 } { 12 } )
    }
    { 4 }
    +
    \int_div_truncate:nn
    {
      367
      *
      ( #3 - 2
      - \int_div_truncate:nn { #3 - 14 } { 12 } * 12 )
    }
  }
}

```

```

        { 12 }
    -
    \int_div_truncate:nn
    {
        3
        *
        (
            \int_div_truncate:nn
            {
                #2 + 4900
                + \int_div_truncate:nn { #3 - 14 } { 12 }
            }
            { 100 }
        )
    }
    { 4 }
}
}
\cs_generate_variant:Nn \datatool_calc_julian_day:Nnnn
{ NVVV , Neee }

```

`\datatool_from_julian_time:nNNN`
`{<JT>} <hour int var> <minute int var> <second int var>`

Calculate the time of day from the Julian time decimal fraction.

```

\cs_new:Nn \datatool_from_julian_time:nNNN
{
    \int_set:Nn #4 { 43200 + \fp_to_int:n { #1 * 86400 } }
    \int_set:Nn #3
    {
        \int_mod:nn { \int_div_truncate:nn { #4 } { 60 } } { 60 }
    }
    \int_set:Nn #2
    {
        \int_div_truncate:nn { #4 } { 3600 }
    }
    \int_set:Nn #4 { \int_mod:nn { #4 } { 60 } }
}
\cs_generate_variant:Nn \datatool_from_julian_time:nNNN
{ VNNN, eNNN }

```

`\datatool_from_julian_day:nNNN`
`{<JDN>} <year int var> <month int var> <day int var>`

Calculate the year, month and day from the Julian Day Number.

```

\cs_new:Nn \datatool_from_julian_day:nNNN
{
    \int_set:Nn \l__datatool_tmpa_int { #1 + 68569 }
}

```

```

\int_set:Nn \l_datatool_tmpb_int
  { \int_div_truncate:nn { 4 * \l_datatool_tmpa_int } { 146097 } }
\int_set:Nn \l_datatool_tmpa_int
  {
    \l_datatool_tmpa_int
    - \int_div_truncate:nn { 146097 * \l_datatool_tmpb_int + 3 } { 4 }
  }
\int_set:Nn \l_datatool_tmpc_int
  {
    \int_div_truncate:nn { 4000 * \l_datatool_tmpa_int + 1 } { 1461001 }
  }
\int_set:Nn \l_datatool_tmpa_int
  {
    \l_datatool_tmpa_int
    - \int_div_truncate:nn { 1461 * \l_datatool_tmpc_int } { 4 }
    + 31
  }
\int_set:Nn \l_datatool_tmpd_int
  {
    \int_div_truncate:nn { 80 * \l_datatool_tmpa_int } { 2447 }
  }
\int_set:Nn #4
  {
    \l_datatool_tmpa_int
    - \int_div_truncate:nn { 2447 * \l_datatool_tmpd_int } { 80 }
  }
\int_set:Nn \l_datatool_tmpa_int
  {
    \int_div_truncate:nn { \l_datatool_tmpd_int } { 11 }
  }
\int_set:Nn \l_datatool_tmpd_int
  {
    \l_datatool_tmpd_int + 2 - 12 * \l_datatool_tmpa_int
  }
\int_set:Nn \l_datatool_tmpc_int
  {
    100 * ( \l_datatool_tmpb_int - 49 )
    + \l_datatool_tmpc_int + \l_datatool_tmpa_int
  }
\int_set_eq:NN #2 \l_datatool_tmpc_int
\int_set_eq:NN #3 \l_datatool_tmpd_int
}
\cs_generate_variant:Nn \datatool_from_julian_day:nNNN
{ VNNN , eNNN }

```

$\langle JD \rangle$ $\langle year \ int \ var \rangle$ $\langle month \ int \ var \rangle$ $\langle day \ int \ var \rangle$
 $\langle hour \ int \ var \rangle$ $\langle minute \ int \ var \rangle$ $\langle second \ int \ var \rangle$

Calculate the timestamp (UTC+0) from the Julian Date.

```
\cs_new:Nn \datatool_from_julian_date:nNNNNNN
{
  \int_set:Nn \l__datatool_julian_int
    { \fp_to_int:n { round ( #1 ) } }
  \datatool_from_julian_day:nNNN
    { \l__datatool_julian_int }
    #2 #3 #4
  \exp_args:Ne \datatool_from_julian_time:nNNN
    { \fp_eval:n { #1 - \l__datatool_julian_int } }
    #5 #6 #7
}
\cs_generate_variant:Nn \datatool_from_julian_date:nNNNNNN
{ VNNNNNN, eNNNNNN }
```

```
\datatool_from_julian_date:nN {<JD>} <timestamp
seq-var>
```

As above but the result should be stored in a timestamp sequence variable.

```
\cs_new:Nn \datatool_from_julian_date:nN
{
  \datatool_from_julian_date:nNNNNNN
    { #1 }
  \l__datatool_year_int
  \l__datatool_month_int
  \l__datatool_day_int
  \l__datatool_hour_int
  \l__datatool_minute_int
  \l__datatool_second_int
  \datatool_timestamp_zero:N #2
  \datatool_timestamp_set_year:NV #2 \l__datatool_year_int
  \datatool_timestamp_set_month:NV #2 \l__datatool_month_int
  \datatool_timestamp_set_day:NV #2 \l__datatool_day_int
  \datatool_timestamp_set_hour:NV #2 \l__datatool_hour_int
  \datatool_timestamp_set_minute:NV #2 \l__datatool_minute_int
  \datatool_timestamp_set_second:NV #2 \l__datatool_second_int
  \datatool_timestamp_set_dow:Ne #2
    {
      \datatool_julian_day_to_dow:n
        { \fp_eval:n { round ( #1 ) } }
    }
}
\cs_generate_variant:Nn \datatool_from_julian_date:nN { VN , eN }
```

Internal Calculation Functions Calculate the Julian day from values provided by the scratch date and time variables (which needs to be set first). Time zone adjustment needed:

```
\cs_new:Nn \__datatool_calc_julian_day_tmz:
```

```

{
  \__datatool_calc_julian_day:
Keep a record of the unadjusted Julian day:
  \int_set_eq:NN \l__datatool_local_julian_int \l__datatool_julian_int
Implement time zone shift:
  \int_if_zero:nF { \l__datatool_tzminute_int }
  {
    \int_sub:Nn \l__datatool_minute_int { \l__datatool_tzminute_int }
    \int_compare:nNnTF { \l__datatool_minute_int } < { \c_zero_int }
    {
      \int_add:Nn \l__datatool_minute_int { 60 }
      \int_decr:N \l__datatool_hour_int
    }
    {
      \int_compare:nNnT { \l__datatool_minute_int } > { 59 }
      {
        \int_sub:Nn \l__datatool_minute_int { 60 }
        \int_incr:N \l__datatool_hour_int
      }
    }
  }
  \int_if_zero:nF { \l__datatool_tzhour_int }
  {
    \int_sub:Nn \l__datatool_hour_int { \l__datatool_tzhour_int }
  }
  \int_compare:nNnTF { \l__datatool_hour_int } < { \c_zero_int }
  {
    \int_add:Nn \l__datatool_hour_int { 23 }
    \int_decr:N \l__datatool_julian_int
  }
  {
    \int_compare:nNnT { \l__datatool_hour_int } > { 23 }
    {
      \int_decr:Nn \l__datatool_hour_int { 24 }
      \int_incr:N \l__datatool_julian_int
    }
  }
}
}
Calculate the Julian day number from just the year, month and day scratch variables
(noon UTC+0).
\cs_new:Nn \__datatool_calc_julian_day:
{
  \datatool_calc_julian_day:Nnnn
  \l__datatool_julian_int
  { \l__datatool_year_int }
  { \l__datatool_month_int }
  { \l__datatool_day_int }
}

```

Calculate the Julian time, which is a fraction of the day starting from 12noon. (Note that this isn't the same as TeX's `\time` value, which is an integer number of minutes since midnight.) For example, 6am is $(6 - 12)/24 + 0/1440 + 0/86400 = -0.25$ and 6pm is $(18 - 12)/24 + 0/1440 + 0/86400 = +0.25$.

```
\cs_new:Nn \__datatool_calc_julian_time:
{
  \fp_set:Nn \l__datatool_time_fp
  {
    ( \l__datatool_hour_int - 12 ) / 24
    + \l__datatool_minute_int / 1440
    + \l__datatool_second_int / 86400
  }
}
```

The Julian date can then be obtained by adding the Julian day and Julian time.

Perform the reverse:

```
\cs_new:Nn \__datatool_from_julian_time:
{
  \__datatool_from_julian_time:n { \l__datatool_time_fp }
}
\cs_new:Nn \__datatool_from_julian_time:n
{
  \datatool_from_julian_time:nNNN { #1 }
  \l__datatool_hour_int
  \l__datatool_minute_int
  \l__datatool_second_int
}
```

Convert Julian Day number (integer) to Gregorian year, month and day.

```
\cs_new:Nn \__datatool_from_julian_day:
{
  \__datatool_from_julian_day:n { \l__datatool_julian_int }
}
\cs_new:Nn \__datatool_from_julian_day:n
{
  \datatool_from_julian_day:nNNN { #1 }
  \l__datatool_year_int
  \l__datatool_month_int
  \l__datatool_day_int
}
```

Convert from decimal Julian date to UTC+0.

```
\cs_new:Nn \__datatool_from_julian_date:
{
  \__datatool_from_julian_date:n { \l__datatool_julian_int }
}
\cs_new:Nn \__datatool_from_julian_date:n
{
  \datatool_from_julian_date:nNNNNNN { #1 }
  \l__datatool_year_int
}
```

```

    \l_datatool_month_int
    \l_datatool_day_int
    \l_datatool_hour_int
    \l_datatool_minute_int
    \l_datatool_second_int
}

```

Parsing Timestamps, dates and times must be in ISO format in order to be parsed correctly unless support is provided by localisation files.

```

\datatool_parse_timestamp:NnTF
<timestamp seq var>
{<ISO>}
{<true>} {<false>}

```

Parse *<ISO>* timestamp and save the numeric values in the provided timestamp sequence variable. Does *<true>* if *<ISO>* successfully parsed. Otherwise does *<false>*. The timestamp format should be in the form *<YYYY>-<MM>-<DD>T<hh>:<mm>:<ss><TZhr>:<TZmin>*. The time zone parts may be omitted or may simply be the letter “Z”, in which case the time zone is UTC+0. The “T” separator may be a space instead. Leading and trailing space is ignored.

```

\prg_new_conditional:Npnn \datatool_parse_timestamp:Nn #1 #2
{ T, F, TF }
{
  \__datatool_parse_timestamp:nTF { #2 }
  {
    \seq_set_eq:NN #1 \l_datatool_datetime_seq
    \prg_return_true:
  }
  { \prg_return_false: }
}

```

```

\datatool_parse_date:NnTF
<timestamp seq var>
{<date>}
{<true>} {<false>}

```

Parses the *<date>* argument, which must be in the form *<YYYY>-<MM>-<DD>* and saves the year, month and date in the provided timestamp sequence variable. Note that the other elements aren’t changed unless the sequence was originally empty. Does *<true>* if *<date>* successfully parsed. Otherwise does *<false>*.

```

\prg_new_conditional:Npnn \datatool_parse_date:Nn #1 #2
{ T, F, TF }
{
  \__datatool_parse_date:nTF { #2 }
  {

```

```

\seq_if_empty:NTF #1
{
  \seq_set_eq:NN #1 \l__datatool_datetime_seq
}
{
  \datatool_timestamp_set_year:Ne #1
  { \__datatool_tm_yr: }
  \datatool_timestamp_set_month:Ne #1
  { \__datatool_tm_mn: }
  \datatool_timestamp_set_day:Ne #1
  { \__datatool_tm_day: }
}
\prg_return_true:
}
{ \prg_return_false: }
}

```

```

\datatool_parse_time:NnTF
<timestamp seq var>
{<time>}
{<true>} {<false>}

```

Parses the *<time>* argument, which must be in the form *<hh>:<mm>:<ss>* or *<hh>:<mm>* and saves the hour, minute and second (0, if omitted) in the provided timestamp sequence variable. Note that the other elements aren't changed unless the sequence was originally empty. Does *<true>* if *<time>* successfully parsed. Otherwise does *<false>*.

```

\prg_new_conditional:Npnn \datatool_parse_time:Nn #1 #2
{ T, F, TF }
{
  \__datatool_parse_time:NnTF { #2 }
  {
    \seq_if_empty:NTF #1
    {
      \seq_set_eq:NN #1 \l__datatool_datetime_seq
    }
    {
      \datatool_timestamp_set_hour:Ne #1
      { \__datatool_tm_hr: }
      \datatool_timestamp_set_minute:Ne #1
      { \__datatool_tm_mi: }
      \datatool_timestamp_set_second:Ne #1
      { \__datatool_tm_se: }
    }
    \prg_return_true:
  }
  { \prg_return_false: }
}
}

```

Parse given timestamp and save values in the datetime scratch sequence variable.

```

\prg_new_conditional:Npnn \__datatool_parse_timestamp:n #1
  { T, F, TF }
  {
    \bool_if:NTF \l__datatool_parse_datetime_iso_bool
      {
        \regex_extract_once:NnNTF
          \c_datatool_timestamp_regex { #1 }
          \l_datatool_timestamp_match_seq
          {
            Initialise all elements to zero.
            \__datatool_tm_seq_init:
            Year:
              \__datatool_tm_set_yr:e
              { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
            Month:
              \__datatool_tm_set_mn:e
              { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
            Day:
              \__datatool_tm_set_dy:e
              { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
            Hour:
              \__datatool_tm_set_hr:e
              { \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
            Minute:
              \__datatool_tm_set_mi:e
              { \seq_item:Nn \l_datatool_timestamp_match_seq { 6 } }
            Second:
              \__datatool_tm_set_se:e
              { \seq_item:Nn \l_datatool_timestamp_match_seq { 7 } }
            Check time zone present.
            \tl_if_empty:eF
              { \seq_item:Nn \l_datatool_timestamp_match_seq { 8 } }
              {
                \exp_args:NNe \regex_extract_once:NnNT
                  \c_datatool_time_regex
                  { \seq_item:Nn \l_datatool_timestamp_match_seq { 8 } }
                  \l_datatool_timestamp_match_seq
                  {
                    \__datatool_tm_set_tzh:e
                    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
                    \__datatool_tm_set_tzm:e
                    { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
                  }
              }
            \prg_return_true:

```

```

}
{
\bool_if:NTF \l__datatool_parse_datetime_regional_bool
{
\DTLCurrentLocaleParseTimeStamp
\l__datatool_datetime_seq
{ #1 }
{ \prg_return_true: }
{ \prg_return_false: }
}
{ \prg_return_false: }
}
}
{
\bool_if:NTF \l__datatool_parse_datetime_regional_bool
{
\DTLCurrentLocaleParseTimeStamp
\l__datatool_datetime_seq
{ #1 }
{ \prg_return_true: }
{ \prg_return_false: }
}
{ \prg_return_false: }
}
}
}

```

`\DTLCurrentLocaleParseTimeStamp{<seq>}{<value>}`
`{<true>}{<false>}`

entLocaleParseTimeStamp

Allow for regional support. If implemented, this should set the given timestamp sequence variable and do *<true>* otherwise it should do *<false>*.

`\newcommand{\DTLCurrentLocaleParseTimeStamp}[4]{#4}`

Parse a date (no time):

```

\prg_new_conditional:Npnn \__datatool_parse_date:n #1
{ T, F, TF }

```

```

{
\bool_if:NTF \l__datatool_parse_datetime_iso_bool
{
\regex_extract_once:NnNTF
\c_datatool_date_regex { #1 }
\l__datatool_timestamp_match_seq
{

```

Initialise all elements to zero:

```

\__datatool_tm_seq_init:

```

Year:

```

\__datatool_tm_set_yr:e

```

```

        { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
Month:
    \__datatool_tm_set_mn:e
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
Day:
    \__datatool_tm_set_dy:e
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
    \prg_return_true:
}
{
    \bool_if:NTF \l__datatool_parse_datetime_regional_bool
    {
        \DTLCurrentLocaleParseDate
        \l__datatool_datetime_seq
        { #1 }
        { \prg_return_true: }
        { \prg_return_false: }
    }
    { \prg_return_false: }
}
}
{
    \bool_if:NTF \l__datatool_parse_datetime_regional_bool
    {
        \DTLCurrentLocaleParseDate
        \l__datatool_datetime_seq
        { #1 }
        { \prg_return_true: }
        { \prg_return_false: }
    }
    { \prg_return_false: }
}
}
}
}

```

```

\DTLCurrentLocaleParseDate{<seq>}{<value>}{<true>}
{<false>}

```

DTLCurrentLocaleParseDate

Allow for regional support. If implemented, this should set the given date sequence variable and do *<true>* otherwise it should do *<false>*.

```
\newcommand{\DTLCurrentLocaleParseDate}[4]{#4}
```

Parse a time (no date):

```

\prg_new_conditional:Npnn \__datatool_parse_time:n #1
{ T, F, TF }
{
    \bool_if:NTF \l__datatool_parse_datetime_iso_bool
    {

```

```

\regex_extract_once:NnNTF
  \c_datatool_time_regex { #1 }
  \l_datatool_timestamp_match_seq
  {
    \__datatool_tm_seq_init:
Hour:
    \__datatool_tm_set_hr:e
      { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
Minute:
    \__datatool_tm_set_mi:e
      { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
Second:
    \__datatool_tm_set_se:e
      { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
    \prg_return_true:
  }
  {
    \bool_if:NTF \l__datatool_parse_datetime_regional_bool
    {
      \DTLCurrentLocaleParseTime
        \l__datatool_datetime_seq
        { #1 }
        { \prg_return_true: }
        { \prg_return_false: }
    }
    { \prg_return_false: }
  }
}
{
  \bool_if:NTF \l__datatool_parse_datetime_regional_bool
  {
    \DTLCurrentLocaleParseTime
      \l__datatool_datetime_seq
      { #1 }
      { \prg_return_true: }
      { \prg_return_false: }
  }
  { \prg_return_false: }
}
}
}

```

```

\DTLCurrentLocaleParseTime{<seq>}{<value>}{<true>}
{<false>}

```

DTLCurrentLocaleParseTime

Allow for regional support. If implemented, this should set the given date sequence variable and do *<true>* otherwise it should do *<false>*.

```
\newcommand{\DTLCurrentLocaleParseTime}[4]{#4}
```

Parse argument to determine if it's a timestamp, date only, time only or none of those. In the last case, false part is done, otherwise \@dtl@datatype will be set to the applicable data type, and the Julian Day number, Julian Date decimal and time fraction will be calculated, and then true part is done.

```
\prg_new_conditional:Npnn \__datatool_parse_datetime:n #1
  { T, F, TF }
{
  \seq_clear:N \l__datatool_datetime_seq
  \fp_zero:N \l__datatool_julian_fp
  \fp_zero:N \l__datatool_time_fp
  \int_zero:N \l__datatool_local_julian_int
  \int_zero:N \l__datatool_julian_int
  \__datatool_parse_timestamp:nTF { #1 }
  {
    \@dtl@datatype = \c_datatool_datetime_int
  }
  {
    \__datatool_parse_date:nTF { #1 }
    {
      \@dtl@datatype = \c_datatool_date_int
    }
    {
      \__datatool_parse_time:nT { #1 }
      {
        \@dtl@datatype = \c_datatool_time_int
      }
    }
  }
  \seq_if_empty:NTF \l__datatool_datetime_seq
  { \prg_return_false: }
  {
    \__datatool_calc_julian_date:
    \prg_return_true:
  }
}
```

Calculate the Julian Date from the scratch timestamp sequence.

```
\cs_new:Nn \__datatool_calc_julian_date:
{
  \int_set:Nn \l__datatool_year_int { \__datatool_tm_yr: }
  \int_set:Nn \l__datatool_month_int { \__datatool_tm_mn: }
  \int_set:Nn \l__datatool_day_int { \__datatool_tm_dy: }
  \int_set:Nn \l__datatool_hour_int { \__datatool_tm_hr: }
  \int_set:Nn \l__datatool_minute_int { \__datatool_tm_mi: }
  \int_set:Nn \l__datatool_second_int { \__datatool_tm_se: }
  \int_set:Nn \l__datatool_tzhour_int { \__datatool_tm_tzh: }
  \int_set:Nn \l__datatool_tzminute_int { \__datatool_tm_tzm: }
```

Calculate the Julian day with time zone adjustment.

```
\__datatool_calc_julian_day_tmz:
```

Update the day of week item in the timestamp sequence.

```
\__datatool_tm_set_dow:e  
{  
  \datatool_julian_day_to_dow:n  
  { \l__datatool_local_julian_int }  
}
```

Calculate the Julian date. First the time part:

```
\__datatool_calc_julian_time:
```

Then add the day and time values:

```
\fp_set:Nn \l__datatool_julian_fp  
{  
  \int_use:N \l__datatool_julian_int  
  + \l__datatool_time_fp  
}
```

Set the update token variable for a temporal datum

```
\cs_new:Nn \__datatool_set_datetime_value:  
{  
  \__datatool_set_datetime_value:n { }  
}  
\cs_new:Nn \__datatool_set_datetime_value:n  
{  
  \__datatool_set_datetime_value:NNn  
  \l__datatool_datum_update_value_tl  
  \l__datatool_datum_value_tl  
  { #1 }  
}  
\cs_new:Nn \__datatool_set_datetime_value:NNn  
{  
  \__datatool_set_datetime_value:NNn  
  #1 \l__datatool_datum_value_tl { #2 }  
}
```

Some common formats for use with regions. First a property variable to store time-zone mappings.

```
\prop_new:N \l__datatool_timezone_map_prop  
\tl_new:N \l__datatool_timezone_map_value_tl
```

The regions can store applicable time zones in the format *<region-tag>* / *<zone-id>* (for example, GB / GMT and GB / BST). The value should be in the form *<sign><hh>:<mm>*.

```
\cs_new:Nn \datatool_region_set_timezone_map:nn  
{  
  \prop_put:Nnn \l__datatool_timezone_map_prop { #1 } { #2 }  
}
```

Get the value and store in the scratch token list.

```
\cs_new:Nn \datatool_region_get_timezone_map:n
{
  \prop_get:NnN \l_datatool_timezone_map_prop
    { #1 }
    \l_datatool_timezone_map_value_tl
}
```

Add regionless identifiers UTC and Z:

```
\datatool_region_set_timezone_map:nn { UTC } { +00:00 }
\datatool_region_set_timezone_map:nn { Z } { +00:00 }
\newcommand{\DTLCurrentLocaleGetTimeZoneMap}[1]{
  \tl_set_eq:NN \l_datatool_timezone_map_value_tl \q_no_value
}
```

Similarly for month name to number mappings:

```
\prop_new:N \l_datatool_monthname_map_prop
\tl_new:N \l_datatool_monthname_map_value_tl
```

Set month name mapping:

```
\cs_new:Nn \datatool_region_set_monthname_map:nn
{
  \prop_put:Nnn \l_datatool_monthname_map_prop { #1 } { #2 }
}
```

Get the value and store in the scratch token list.

```
\cs_new:Nn \datatool_region_get_monthname_map:n
{
  \prop_get:NnN \l_datatool_monthname_map_prop
    { #1 }
    \l_datatool_monthname_map_value_tl
}
\newcommand{\DTLCurrentLocaleGetMonthNameMap}[1]{
  \tl_set_eq:NN \l_datatool_monthname_map_value_tl \q_no_value
}
```

Day of month regular expression (1-31):

```
\regex_const:Nn \c_datatool_day_of_month_regex
{
  ( 0?[1-9] | [12][0-9] | 30 | 31 )
}
```

One or two digit month number (1-12):

```
\regex_const:Nn \c_datatool_month_number_regex
{
  ( 0?[1-9] | 10 | 11 | 12 )
}
```

One or two digit hour (0-24):

```
\regex_const:Nn \c_datatool_hour_regex
{
```

```

    ( 0?[0-9] | 1[0-9] | 2[0-4] )
  }

```

Two digit minute or second (0-59):

```

\regex_const:Nn \c_datatool_minsec_regex
{
  [0-5][0-9]
}

```

Time zone offset, optionally prefixed with GMT or UTC or UT:

```

\regex_const:Nn \c_datatool_timezone_regex
{
  (?:GMT|UTC)?
  ( [\+\-]? \ur{c_datatool_hour_regex} )
  (?: \: ? ( \ur{c_datatool_minsec_regex} ) ) ?
}

```

Time zone (either uppercase identifier, which will require a mapping, or offset):

```

\regex_const:Nn \c_datatool_timezone_id_regex
{
  [A-Z]+ | \ur{c_datatool_timezone_regex}
}

```

```

\DTLCurrentLocaleIfpmTF{<id>}{<true>}{<false>}

```

\DTLCurrentLocaleIfpmTF

If the identifier is recognised as indicating the afternoon, do true, otherwise do false. Localisation support should redefine this as appropriate.

```

\newcommand \DTLCurrentLocaleIfpmTF [ 3 ]
{
  \tl_if_eq:nnTF { #1 } { pm } { #2 } { #3 }
}

```

The following regular expression constants are for common formats. Localisation support may use the applicable expression or provide custom patterns. Note that it's important that the captured groups match the applicable parsing function.

Non-anchored expressions allow them to be used as a sub-expression for timestamp parsing.

Common dd mm yyyy formats.

```

\regex_const:Nn \c_datatool_slash_ddmmyyyy_date_regex
{
  ( \ur{c_datatool_day_of_month_regex} )
  \/
  ( \ur{c_datatool_month_number_regex} )
  \/ ( \d+ )
}

```

```

\regex_const:Nn \c_datatool_slash_anchored_ddmmyyyy_date_regex
{
  \A \s*

```

```

    ( \ur{c_datatool_day_of_month_regex} )
    \/
    ( \ur{c_datatool_month_number_regex} )
    \/ ( \d+ )
    \s* \Z
  }
\regex_const:Nn \c_datatool_slash_ddmmyy_date_regex
{
  ( \ur{c_datatool_day_of_month_regex} )
  \/
  ( \ur{c_datatool_month_number_regex} )
  \/ ( \d{2} )
}
\regex_const:Nn \c_datatool_slash_anchored_ddmmyy_date_regex
{
  \A \s*
  ( \ur{c_datatool_day_of_month_regex} )
  \/
  ( \ur{c_datatool_month_number_regex} )
  \/ ( \d{2} )
  \s* \Z
}
\regex_const:Nn \c_datatool_hyphen_ddmmyyyy_date_regex
{
  ( \ur{c_datatool_day_of_month_regex} )
  \-
  ( \ur{c_datatool_month_number_regex} )
  \- ( \d+ )
}
\regex_const:Nn \c_datatool_hyphen_anchored_ddmmyyyy_date_regex
{
  \A \s*
  ( \ur{c_datatool_day_of_month_regex} )
  \-
  ( \ur{c_datatool_month_number_regex} )
  \- ( \d+ )
  \s* \Z
}
\regex_const:Nn \c_datatool_hyphen_ddmmyy_date_regex
{
  ( \ur{c_datatool_day_of_month_regex} )
  \-
  ( \ur{c_datatool_month_number_regex} )
  \- ( \d{2} )
}
\regex_const:Nn \c_datatool_hyphen_anchored_ddmmyy_date_regex
{

```

```

    \A \s*
    ( \ur{c_datatool_day_of_month_regex} )
    \-
    ( \ur{c_datatool_month_number_regex} )
    \- ( \d{2} )
    \s* \Z
}
\regex_const:Nn \c_datatool_dot_ddmmyyyy_date_regex
{
  ( \ur{c_datatool_day_of_month_regex} )
  \.
  ( \ur{c_datatool_month_number_regex} )
  \. ( \d+ )
}
\regex_const:Nn \c_datatool_dot_anchored_ddmmyyyy_date_regex
{
  \A \s*
  ( \ur{c_datatool_day_of_month_regex} )
  \.
  ( \ur{c_datatool_month_number_regex} )
  \. ( \d+ )
  \s* \Z
}
\regex_const:Nn \c_datatool_dot_ddmmyy_date_regex
{
  ( \ur{c_datatool_day_of_month_regex} )
  \.
  ( \ur{c_datatool_month_number_regex} )
  \. ( \d{2} )
}
\regex_const:Nn \c_datatool_dot_anchored_ddmmyy_date_regex
{
  \A \s*
  ( \ur{c_datatool_day_of_month_regex} )
  \.
  ( \ur{c_datatool_month_number_regex} )
  \. ( \d{2} )
  \s* \Z
}
}
Common mm dd yyyy formats.
\regex_const:Nn \c_datatool_slash_mmdyyy_date_regex
{
  ( \ur{c_datatool_month_number_regex} )
  \/
  ( \ur{c_datatool_day_of_month_regex} )
  \/ ( \d+ )
}
}

```

```

\regex_const:Nn \c_datatool_slash_anchored_mmddyyyy_date_regex
{
  \A \s*
  ( \ur{c_datatool_month_number_regex} )
  \/
  ( \ur{c_datatool_day_of_month_regex} )
  \/ ( \d+ )
  \s* \Z
}

\regex_const:Nn \c_datatool_slash_mmddyy_date_regex
{
  ( \ur{c_datatool_month_number_regex} )
  \/
  ( \ur{c_datatool_day_of_month_regex} )
  \/ ( \d{2} )
}

\regex_const:Nn \c_datatool_slash_anchored_mmddyy_date_regex
{
  \A \s*
  ( \ur{c_datatool_month_number_regex} )
  \/
  ( \ur{c_datatool_day_of_month_regex} )
  \/ ( \d{2} )
  \s* \Z
}

\regex_const:Nn \c_datatool_hyphen_mmddyyyy_date_regex
{
  ( \ur{c_datatool_month_number_regex} )
  \-
  ( \ur{c_datatool_day_of_month_regex} )
  \- ( \d+ )
}

\regex_const:Nn \c_datatool_hyphen_anchored_mmddyyyy_date_regex
{
  \A \s*
  ( \ur{c_datatool_month_number_regex} )
  \-
  ( \ur{c_datatool_day_of_month_regex} )
  \- ( \d+ )
  \s* \Z
}

\regex_const:Nn \c_datatool_hyphen_mmddyy_date_regex
{
  ( \ur{c_datatool_month_number_regex} )
  \-
  ( \ur{c_datatool_day_of_month_regex} )
  \- ( \d{2} )
}

```

```

\regex_const:Nn \c_datatool_hyphen_anchored_mmddyy_date_regex
{
  \A \s*
  ( \ur{c_datatool_month_number_regex} )
  \-
  ( \ur{c_datatool_day_of_month_regex} )
  \- ( \d{2} )
  \s* \Z
}

\regex_const:Nn \c_datatool_dot_mmddyyyy_date_regex
{
  ( \ur{c_datatool_month_number_regex} )
  \.
  ( \ur{c_datatool_day_of_month_regex} )
  \. ( \d+ )
}

\regex_const:Nn \c_datatool_dot_anchored_mmddyyyy_date_regex
{
  \A \s*
  ( \ur{c_datatool_month_number_regex} )
  \.
  ( \ur{c_datatool_day_of_month_regex} )
  \. ( \d+ )
  \s* \Z
}

\regex_const:Nn \c_datatool_dot_mmddyy_date_regex
{
  ( \ur{c_datatool_month_number_regex} )
  \.
  ( \ur{c_datatool_day_of_month_regex} )
  \. ( \d{2} )
}

\regex_const:Nn \c_datatool_dot_anchored_mmddyy_date_regex
{
  \A \s*
  ( \ur{c_datatool_month_number_regex} )
  \.
  ( \ur{c_datatool_day_of_month_regex} )
  \. ( \d{2} )
  \s* \Z
}

Common yyyy mm dd formats.

\regex_const:Nn \c_datatool_slash_yyyymmdd_date_regex
{
  ( \d+ ) \/
  ( \ur{c_datatool_month_number_regex} )
  \/
}

```

```

    ( \ur{c_datatool_day_of_month_regex} )
  }
\regex_const:Nn \c_datatool_slash_anchored_yyyymmdd_date_regex
{
  \A \s*
  ( \d+ ) \/
  ( \ur{c_datatool_month_number_regex} )
  \/
  ( \ur{c_datatool_day_of_month_regex} )
  \s* \Z
}
\regex_const:Nn \c_datatool_slash_yymmdd_date_regex
{
  ( \d{2} ) \/
  ( \ur{c_datatool_month_number_regex} )
  \/
  ( \ur{c_datatool_day_of_month_regex} )
}
\regex_const:Nn \c_datatool_slash_anchored_yymmdd_date_regex
{
  \A \s*
  ( \d{2} ) \/
  ( \ur{c_datatool_month_number_regex} )
  \/
  ( \ur{c_datatool_day_of_month_regex} )
  \s* \Z
}
\regex_const:Nn \c_datatool_hyphen_yyyymmdd_date_regex
{
  ( \d+ ) \-
  ( \ur{c_datatool_month_number_regex} )
  \-
  ( \ur{c_datatool_day_of_month_regex} )
}
\regex_const:Nn \c_datatool_hyphen_anchored_yyyymmdd_date_regex
{
  \A \s*
  ( \d+ ) \-
  ( \ur{c_datatool_month_number_regex} )
  \-
  ( \ur{c_datatool_day_of_month_regex} )
  \s* \Z
}
\regex_const:Nn \c_datatool_hyphen_yymmdd_date_regex
{
  ( \d{2} ) \-
  ( \ur{c_datatool_month_number_regex} )
}

```

```

    \-
    ( \ur{c_datatool_day_of_month_regex} )
}
\regex_const:Nn \c_datatool_hyphen_anchored_yymmdd_date_regex
{
  \A \s*
  ( \d{2} ) \-
  ( \ur{c_datatool_month_number_regex} )
  \-
  ( \ur{c_datatool_day_of_month_regex} )
  \s* \Z
}
\regex_const:Nn \c_datatool_dot_yyyymmdd_date_regex
{
  ( \d+ ) \.
  ( \ur{c_datatool_month_number_regex} )
  \.
  ( \ur{c_datatool_day_of_month_regex} )
}
\regex_const:Nn \c_datatool_dot_anchored_yyyymmdd_date_regex
{
  \A \s*
  ( \d+ ) \.
  ( \ur{c_datatool_month_number_regex} )
  \.
  ( \ur{c_datatool_day_of_month_regex} )
  \s* \Z
}
\regex_const:Nn \c_datatool_dot_yymmdd_date_regex
{
  ( \d{2} ) \.
  ( \ur{c_datatool_month_number_regex} )
  \.
  ( \ur{c_datatool_day_of_month_regex} )
}
\regex_const:Nn \c_datatool_dot_anchored_yymmdd_date_regex
{
  \A \s*
  ( \d{2} ) \.
  ( \ur{c_datatool_month_number_regex} )
  \.
  ( \ur{c_datatool_day_of_month_regex} )
  \s* \Z
}

```

Time formats. If a regional format needs to support other am/pm identifiers, they'll need to provide their own regular expressions.

```
\regex_const:Nn \c_datatool_colon_hhmmss_time_regex
```

```

{
  ( \ur{c_datatool_hour_regex} )
  \: ( \ur{c_datatool_minsec_regex} )
  (?: \: ( \ur{c_datatool_minsec_regex} ) ) ?
  (?: \s* ( am | pm ) ) ?
}
\regex_const:Nn \c_datatool_colon_anchored_hhmmss_time_regex
{
  \A \s*
  ( \ur{c_datatool_hour_regex} )
  \: ( \ur{c_datatool_minsec_regex} )
  (?: \: ( \ur{c_datatool_minsec_regex} ) ) ?
  (?: \s* ( am | pm ) ) ?
  \s* \Z
}
\regex_const:Nn \c_datatool_dot_hhmmss_time_regex
{
  ( \ur{c_datatool_hour_regex} )
  \. ( \ur{c_datatool_minsec_regex} )
  (?: \. ( \ur{c_datatool_minsec_regex} ) ) ?
  (?: \s* ( am | pm ) ) ?
}
\regex_const:Nn \c_datatool_dot_anchored_hhmmss_time_regex
{
  \A \s*
  ( \ur{c_datatool_hour_regex} )
  \. ( \ur{c_datatool_minsec_regex} )
  (?: \. ( \ur{c_datatool_minsec_regex} ) ) ?
  (?: \s* ( am | pm ) ) ?
  \s* \Z
}

```

The timestamp parsing functions may either have a single regular expression that captures both the date and time, or may have two separate regular expressions for the date and time. In either case, the time zone part is optional and will be parsed with `\datatool_parse_regional_timezone:NnTF`.

Once the date, time and timestamp have been extracted, they can then be matched separately. This would be easier if named captured groups were supported, but they aren't at the time of writing, so multiple functions are needed to reference the groups by index.

Syntax: `<date-regex> <time-regex> <timestamp-var> {<date>} {<time>} {<timezone>}`
`{<return true>} {<return false>}`

```

\cs_new:Nn \datatool_ddmmyyyy_hhmmss_tz_parse_datetime:NNNNnTF
{

```

First extract the date:

```

\regex_extract_once:NnNTF #1 { #4 }
  \l_datatool_timestamp_match_seq
  {

```

Set the month first, to skip rest on failure:

```
\datatool_parse_regional_month:NeTF #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
{
```

Successfully set month. Set the day of month:

```
\datatool_timestamp_set_day:Ne #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
```

Set the year:

```
\datatool_timestamp_set_year:Ne #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
```

Now extract the time.

```
\regex_extract_once:NnNTF #2 { #5 }
\l_datatool_timestamp_match_seq
{
```

Set the hour:

```
\exp_args:Ne \DTLCurrentLocaleIfpmTF
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
{
  \datatool_timestamp_set_hour:Ne #3
  {
    \int_eval:n
    {
      12 +
      \seq_item:Nn \l_datatool_timestamp_match_seq { 2 }
    }
  }
}
{
  \datatool_timestamp_set_hour:Ne #3
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
}
```

Set the minute:

```
\datatool_timestamp_set_minute:Ne #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
```

Set the second:

```
\datatool_timestamp_set_second:Ne #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
}
{ #8 }
```

Parse timezone if present:

```
\datatool_parse_regional_timezone:NnTF #3
{ #6 } { #7 } { #8 }
}
{
```

No match on month:

```
        #8
      }
    }
  { #8 }
}
\cs_generate_variant:Nn
\datatool_ddmmyyy_hhmmss_tz_parse_datetime:NNNnnnTF
{ NNNeeeTF }
```

As above but century needs to be added.

```
\cs_new:Nn \datatool_ddmmyy_hhmmss_tz_parse_datetime:NNNnnnTF
{
```

First extract the date:

```
  \regex_extract_once:NnNTF #1 { #4 }
  \l_datatool_timestamp_match_seq
  {
```

Set the month first, to skip rest on failure:

```
  \datatool_parse_regional_month:NeTF #3
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
  {
```

Successfully set month. Set the day of month:

```
  \datatool_timestamp_set_day:Ne #3
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
```

Set the year:

```
  \datatool_timestamp_set_year_add_century:Ne #3
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
```

Now extract the time.

```
  \regex_extract_once:NnNTF #2 { #5 }
  \l_datatool_timestamp_match_seq
  {
```

Set the hour:

```
  \exp_args:Ne \DTLCurrentLocaleIfpmTF
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
  {
    \datatool_timestamp_set_hour:Ne #3
    {
      \int_eval:n
      {
        12 +
        \seq_item:Nn \l_datatool_timestamp_match_seq { 2 }
      }
    }
  }
  {
    \datatool_timestamp_set_hour:Ne #3
```

```

        { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
    }
Set the minute:
    \datatool_timestamp_set_minute:Ne #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
Set the second:
    \datatool_timestamp_set_second:Ne #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
    }
    { #8 }
Parse timezone if present:
    \datatool_parse_regional_timezone:NnTF #3
    { #6 } { #7 } { #8 }
    }
    {
No match on month:
    #8
    }
    }
    { #8 }
    }
\cs_generate_variant:Nn
\datatool_ddmmyy_hhmmss_tz_parse_datetime:NNNnnnTF
{ NNNeeeTF }
    Same again but the month is in the first captured group and the day is in the second.
    Syntax: <date-regex> <time-regex> <timestamp-var> {<date>} {<time>} {<timezone>}
    {<return true>} {<return false>}
\cs_new:Nn \datatool_mddyyyy_hhmmss_tz_parse_datetime:NNNnnnTF
{
First extract the date:
    \regex_extract_once:NnNTF #1 { #4 }
    \l_datatool_timestamp_match_seq
    {
Set the month first, to skip rest on failure:
    \datatool_parse_regional_month:NeTF #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
    {
Successfully set month. Set the day of month:
    \datatool_timestamp_set_day:Ne #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
Set the year:
    \datatool_timestamp_set_year:Ne #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }

```

Now extract the time.

```
\regex_extract_once:NnNTF #2 { #5 }  
  \l_datatool_timestamp_match_seq  
  {
```

Set the hour:

```
\exp_args:Ne \DTLCurrentLocaleIfpmTF  
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }  
  {  
    \datatool_timestamp_set_hour:Ne #3  
    {  
      \int_eval:n  
      {  
        12 +  
        \seq_item:Nn \l_datatool_timestamp_match_seq { 2 }  
      }  
    }  
  }  
  {  
    \datatool_timestamp_set_hour:Ne #3  
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }  
  }
```

Set the minute:

```
\datatool_timestamp_set_minute:Ne #3  
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
```

Set the second:

```
\datatool_timestamp_set_second:Ne #3  
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }  
}  
{ #8 }
```

Parse timezone if present:

```
\datatool_parse_regional_timezone:NnTF #3  
  { #6 } { #7 } { #8 }  
}  
{
```

No match on month:

```
  #8  
  }  
}  
{ #8 }
```

```
\cs_generate_variant:Nn  
  \datatool_mmdyy_hhmmss_tz_parse_datetime:NNNnnTF  
  { NNNeeeTF }
```

As above but century needs to be added:

```
\cs_new:Nn \datatool_mmdyy_hhmmss_tz_parse_datetime:NNNnnTF  
{
```

First extract the date:

```
\regex_extract_once:NnNTF #1 { #4 }
  \l_datatool_timestamp_match_seq
  {
```

Set the month first, to skip rest on failure:

```
\datatool_parse_regional_month:NeTF #3
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
  {
```

Successfully set month. Set the day of month:

```
\datatool_timestamp_set_day:Ne #3
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
```

Set the year:

```
\datatool_timestamp_set_year_add_century:Ne #3
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
```

Now extract the time.

```
\regex_extract_once:NnNTF #2 { #5 }
  \l_datatool_timestamp_match_seq
  {
```

Set the hour:

```
\exp_args:Ne \DTLCurrentLocaleIfpmTF
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
  {
    \datatool_timestamp_set_hour:Ne #3
    {
      \int_eval:n
      {
        12 +
        \seq_item:Nn \l_datatool_timestamp_match_seq { 2 }
      }
    }
  }
  {
    \datatool_timestamp_set_hour:Ne #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
  }
}
```

Set the minute:

```
\datatool_timestamp_set_minute:Ne #3
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
```

Set the second:

```
\datatool_timestamp_set_second:Ne #3
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
}
{ #8 }
```

Parse timezone if present:

```
\datatool_parse_regional_timezone:NnTF #3
{ #6 } { #7 } { #8 }
}
{
```

No match on month:

```
    #8
  }
}
{ #8 }
}
\cs_generate_variant:Nn
\datatool_mmddyy_hhmmss_tz_parse_datetime:NNNnnnTF
{ NNNeeeTF }
```

Same again but the year is in the first captured group, the month is in the second captured group and the day is in the third.

Syntax: $\langle date\text{-}regex \rangle \langle time\text{-}regex \rangle \langle timestamp\text{-}var \rangle \{ \langle date \rangle \} \{ \langle time \rangle \} \{ \langle timezone \rangle \}$
 $\{ \langle return\ true \rangle \} \{ \langle return\ false \rangle \}$

```
\cs_new:Nn \datatool_yyyymmdd_hhmmss_tz_parse_datetime:NNNnnnTF
{
```

First extract the date:

```
\regex_extract_once:NnNTF #1 { #4 }
\l_datatool_timestamp_match_seq
{
```

Set the month first, to skip rest on failure:

```
\datatool_parse_regional_month:NeTF #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
{
```

Successfully set month. Set the day of month:

```
\datatool_timestamp_set_day:Ne #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
```

Set the year:

```
\datatool_timestamp_set_year:Ne #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
```

Now extract the time.

```
\regex_extract_once:NnNTF #2 { #5 }
\l_datatool_timestamp_match_seq
{
```

Set the hour:

```
\exp_args:Ne \DTLCurrentLocaleIfpmTF
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
{
  \datatool_timestamp_set_hour:Ne #3
  {
```

```

        \int_eval:n
        {
            12 +
            \seq_item:Nn \l_datatool_timestamp_match_seq { 2 }
        }
    }
}
{
    \datatool_timestamp_set_hour:Ne #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
}

Set the minute:
\datatool_timestamp_set_minute:Ne #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }

Set the second:
\datatool_timestamp_set_second:Ne #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
}
{ #8 }

Parse timezone if present:
\datatool_parse_regional_timezone:NnTF #3
{ #6 } { #7 } { #8 }
}
{

No match on month:
    #8
    }
}
{ #8 }
}
\cs_generate_variant:Nn
\datatool_yyyymmdd_hhmmss_tz_parse_datetime:NNNnnnTF
{ NNNeeeTF }

As above, but the century needs to be added. (Unlikely with year first format, but
provided for completeness.)
\cs_new:Nn \datatool_yymmdd_hhmmss_tz_parse_datetime:NNNnnnTF
{

First extract the date:
    \regex_extract_once:NnNTF #1 { #4 }
    \l_datatool_timestamp_match_seq
    {

Set the month first, to skip rest on failure:
    \datatool_parse_regional_month:NeTF #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
    {

```

Successfully set month. Set the day of month:

```
\datatool_timestamp_set_day:Ne #3  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
```

Set the year:

```
\datatool_timestamp_set_year_add_century:Ne #3  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
```

Now extract the time.

```
\regex_extract_once:NnNTF #2 { #5 }  
\l_datatool_timestamp_match_seq  
{
```

Set the hour:

```
\exp_args:Ne \DTLCurrentLocaleIfpmTF  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }  
{  
  \datatool_timestamp_set_hour:Ne #3  
  {  
    \int_eval:n  
    {  
      12 +  
      \seq_item:Nn \l_datatool_timestamp_match_seq { 2 }  
    }  
  }  
}  
{  
  \datatool_timestamp_set_hour:Ne #3  
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }  
}
```

Set the minute:

```
\datatool_timestamp_set_minute:Ne #3  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
```

Set the second:

```
\datatool_timestamp_set_second:Ne #3  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }  
}  
{ #8 }
```

Parse timezone if present:

```
\datatool_parse_regional_timezone:NnTF #3  
{ #6 } { #7 } { #8 }  
}  
{
```

No match on month:

```
  #8  
}  
}  
{ #8 }
```

```

}
\cs_generate_variant:Nn
\datatool_yymmdd_hhmmss_tz_parse_datetime:NNNnnTF
{ NNNeeeTF }

The timestamp separator used when date and time patterns provided separately:
\regex_new:N \l_datatool_regional_timestamp_sep_regex
\regex_set:Nn \l_datatool_regional_timestamp_sep_regex { \,? \s+ }

Syntax: {<date-regex-varname>} {<time-regex-varname>} <timestamp seq-var>
{<text>} {<return true>} {<return false>}

The date regular expression should have the following groups (in order): day,
month, year. The time regular expression should have the following groups: hour,
minute, second (may be empty), am/pm (may be empty). The am/pm part can be any-
thing that \DTLCurrentLocaleIfpmTF can detect as afternoon (that is, add 12 to
the hour). This assumes that the date comes first and is separated from the time by
\l_datatool_regional_timestamp_sep_regex.
\cs_new:Nn \datatool_ddmmyyyy_hhmmss_tz_parse_timestamp:NNNnTF
{
  \tl_set_eq:NN \l_datatool_tmpa_regex #1
  \tl_set_eq:NN \l_datatool_tmppb_regex #2
  \regex_extract_once:nnNTF
  {
    \A \s*
    ( \ur{l_datatool_tmpa_regex} )
    \ur{l_datatool_regional_timestamp_sep_regex}
    ( \ur{l_datatool_tmppb_regex} )
    \s*
    ( \ur{c_datatool_timezone_id_regex} ) ?
    \s*
    \Z
  }
  { #4 }
  \l_datatool_timestamp_match_seq
  {
    \datatool_timestamp_zero:N #3
    \datatool_ddmmyyyy_hhmmss_tz_parse_datetime:NNNeeeTF
    #1 #2 #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
    { #5 } { #6 }
  }
  { #6 }
}
\cs_generate_variant:Nn
\datatool_ddmmyyyy_hhmmss_tz_parse_timestamp:NNNnTF
{ ccNnTF }

```

As above, but century needs to be added.

```

\cs_new:Nn \datatool_ddmmyy_hhmmss_tz_parse_timestamp:NNNnTF
{
  \tl_set_eq:NN \l_datatool_tmpa_regex #1
  \tl_set_eq:NN \l_datatool_tmpb_regex #2
  \regex_extract_once:nnNTF
  {
    \A \s*
    ( \ur{l_datatool_tmpa_regex} )
    \ur{l_datatool_regional_timestamp_sep_regex}
    ( \ur{l_datatool_tmpb_regex} )
    \s*
    ( \ur{c_datatool_timezone_id_regex} ) ?
    \s*
    \Z
  }
  { #4 }
  \l_datatool_timestamp_match_seq
  {
    \datatool_timestamp_zero:N #3
    \datatool_ddmmyy_hhmmss_tz_parse_datetime:NNNeeTF
    #1 #2 #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
    { #5 } { #6 }
  }
  { #6 }
}
\cs_generate_variant:Nn
\datatool_ddmmyy_hhmmss_tz_parse_timestamp:NNNnTF
{ ccNnTF }
  Same again, but month in first captured group.
\cs_new:Nn \datatool_mmdyyy_hhmmss_tz_parse_timestamp:NNNnTF
{
  \tl_set_eq:NN \l_datatool_tmpa_regex #1
  \tl_set_eq:NN \l_datatool_tmpb_regex #2
  \regex_extract_once:nnNTF
  {
    \A \s*
    ( \ur{l_datatool_tmpa_regex} )
    \ur{l_datatool_regional_timestamp_sep_regex}
    ( \ur{l_datatool_tmpb_regex} )
    \s*
    ( \ur{c_datatool_timezone_id_regex} ) ?
    \s*
    \Z
  }
  { #4 }
  \l_datatool_timestamp_match_seq

```

```

    {
      \datatool_timestamp_zero:N #3
      \datatool_mmdyyy_hhmmss_tz_parse_datetime:NNNeeTF
      #1 #2 #3
      { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
      { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
      { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
      { #5 } { #6 }
    }
  { #6 }
}
\cs_generate_variant:Nn
\datatool_mmdyyy_hhmmss_tz_parse_timestamp:NNNnTF
{ ccNnTF }
As above, but century needs to be added.
\cs_new:Nn \datatool_mmdyy_hhmmss_tz_parse_timestamp:NNNnTF
{
  \tl_set_eq:NN \l__datatool_tmpa_regex #1
  \tl_set_eq:NN \l__datatool_tmppb_regex #2
  \regex_extract_once:nnNTF
  {
    \A \s*
    ( \ur{l__datatool_tmpa_regex} )
    \ur{l__datatool_regional_timestamp_sep_regex}
    ( \ur{l__datatool_tmppb_regex} )
    \s*
    ( \ur{c_datatool_timezone_id_regex} ) ?
    \s*
    \Z
  }
  { #4 }
  \l_datatool_timestamp_match_seq
  {
    \datatool_timestamp_zero:N #3
    \datatool_mmdyy_hhmmss_tz_parse_datetime:NNNeeTF
    #1 #2 #3
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
    { #5 } { #6 }
  }
  { #6 }
}
\cs_generate_variant:Nn
\datatool_mmdyy_hhmmss_tz_parse_timestamp:NNNnTF
{ ccNnTF }
Same again, but year in first captured group.
\cs_new:Nn \datatool_yyyymmdd_hhmmss_tz_parse_timestamp:NNNnTF
{

```

```

\tl_set_eq:NN \l_datatool_tmpa_regex #1
\tl_set_eq:NN \l_datatool_tmpb_regex #2
\regex_extract_once:nnNTF
{
  \A \s*
  ( \ur{l_datatool_tmpa_regex} )
  \ur{l_datatool_regional_timestamp_sep_regex}
  ( \ur{l_datatool_tmpb_regex} )
  \s*
  ( \ur{c_datatool_timezone_id_regex} ) ?
  \s*
  \Z
}
{ #4 }
\l_datatool_timestamp_match_seq
{
  \datatool_timestamp_zero:N #3
  \datatool_yyyymmdd_hhmmss_tz_parse_datetime:NNNeeTF
  #1 #2 #3
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
  { #5 } { #6 }
}
{ #6 }
}
\cs_generate_variant:Nn
\datatool_yyyymmdd_hhmmss_tz_parse_timestamp:NNNnTF
{ ccNnTF }

```

As above, but century needs to be added.

```

\cs_new:Nn \datatool_yymmdd_hhmmss_tz_parse_timestamp:NNNnTF
{
  \tl_set_eq:NN \l_datatool_tmpa_regex #1
  \tl_set_eq:NN \l_datatool_tmpb_regex #2
  \regex_extract_once:nnNTF
  {
    \A \s*
    ( \ur{l_datatool_tmpa_regex} )
    \ur{l_datatool_regional_timestamp_sep_regex}
    ( \ur{l_datatool_tmpb_regex} )
    \s*
    ( \ur{c_datatool_timezone_id_regex} ) ?
    \s*
    \Z
  }
  { #4 }
  \l_datatool_timestamp_match_seq
  {
    \datatool_timestamp_zero:N #3
  }
}

```

```

\datatool_yymmdd_hhmmss_tz_parse_datetime:NNNeeTF
#1 #2 #3
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
{ #5 } { #6 }
}
{ #6 }
}
\cs_generate_variant:Nn
\datatool_yymmdd_hhmmss_tz_parse_timestamp:NNNnTF
{ ccNnTF }

```

Syntax: $\langle regex-var \rangle \langle timestamp seq-var \rangle \{ \langle text \rangle \} \{ \langle return true \rangle \} \{ \langle return false \rangle \}$

The regular expression should have the following groups (in order): day, month, year, hour, minute, second (may be empty), am/pm (may be empty), time zone (may be empty). The am/pm part can be anything that `\DTLCurrentLocaleIfpmTF` can detect as afternoon (that is, add 12 to the hour). The constants provided with this base package only match “am” and “pm”. Localisation files may provide their own regular expressions with appropriate patterns.

```

\cs_new:Nn \datatool_ddmmyyyy_hhmmss_tz_parse_timestamp:NNnTF
{
  \regex_extract_once:NnNTF #1 { #3 }
  \l_datatool_timestamp_match_seq
  {

```

Initialise:

```
\datatool_timestamp_zero:N #2
```

Set the month first, to skip rest on failure:

```

\datatool_parse_regional_month:NeTF #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
{

```

Successfully set month. Set the day of month:

```

\datatool_timestamp_set_day:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }

```

Set the year:

```

\datatool_timestamp_set_year:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }

```

Set the hour:

```

\exp_args:Ne \DTLCurrentLocaleIfpmTF
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 8 } }
{
  \datatool_timestamp_set_hour:Ne #2
  {
    \int_eval:n
    {
      12 +
      \seq_item:Nn \l_datatool_timestamp_match_seq { 5 }
    }
  }
}

```

```

    }
  }
  {
    \datatool_timestamp_set_hour:Ne #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
  }
}
Set the minute:
\datatool_timestamp_set_minute:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 6 } }
Set the second:
\datatool_timestamp_set_second:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 7 } }
Parse timezone if present:
\datatool_parse_regional_timezone:NeTF #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 9 } }
{ #4 } { #5 }
}
{
No match on month:
  #5
  }
}
{ #5 } % No match
}
As above but century missing. Syntax: <regex-var> <timestamp seq-var> {<text>}
{<return true>} {<return false>}
\cs_new:Nn \datatool_ddmmyy_hhmmss_tz_parse_timestamp:NNnTF
{
  \regex_extract_once:NnNTF #1 { #3 }
  \l_datatool_timestamp_match_seq
  {
Initialise:
  \datatool_timestamp_zero:N #2
Set the month first, to skip rest on failure:
\datatool_parse_regional_month:NeTF #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
{
Successfully set month. Set the day of month:
\datatool_timestamp_set_day:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
Set the year:
\datatool_timestamp_set_year_add_century:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }

```

Set the hour:

```
\exp_args:Ne \DTLCurrentLocaleIfpmTF
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 8 } }
{
  \datatool_timestamp_set_hour:Ne #2
  {
    \int_eval:n
    {
      12 +
      \seq_item:Nn \l_datatool_timestamp_match_seq { 5 }
    }
  }
}
{
  \datatool_timestamp_set_hour:Ne #2
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
}
```

Set the minute:

```
\datatool_timestamp_set_minute:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 6 } }
```

Set the second:

```
\datatool_timestamp_set_second:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 7 } }
```

Parse timezone if present:

```
\datatool_parse_regional_timezone:NeTF #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 9 } }
{ #4 } { #5 }
}
{
```

No match on month:

```
#5
}
}
{ #5 } % No match
}
```

Syntax: $\langle regex-var \rangle \langle timestamp seq-var \rangle \{ \langle text \rangle \} \{ \langle return true \rangle \} \{ \langle return false \rangle \}$

The regular expression should have the following groups (in order): month, day, year, hour, minute, second (may be empty), am/pm (may be empty), time zone (may be empty).

```
\cs_new:Nn \datatool_mmdyyy_hhmmss_tz_parse_timestamp:NNnTF
{
  \regex_extract_once:NnNTF #1 { #3 }
  \l_datatool_timestamp_match_seq
  {
```

Initialise:

```
\datatool_timestamp_zero:N #2
```

Set the month first, to skip rest on failure:

```
\datatool_parse_regional_month:NeTF #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
{
```

Successfully set month. Set the day of month:

```
\datatool_timestamp_set_day:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
```

Set the year:

```
\datatool_timestamp_set_year:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
```

Set the hour:

```
\exp_args:Ne \DTLCurrentLocaleIfpmTF
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 8 } }
{
  \datatool_timestamp_set_hour:Ne #2
  {
    \int_eval:n
    {
      12 +
      \seq_item:Nn \l_datatool_timestamp_match_seq { 5 }
    }
  }
}
{
  \datatool_timestamp_set_hour:Ne #2
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
}
```

Set the minute:

```
\datatool_timestamp_set_minute:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 6 } }
```

Set the second:

```
\datatool_timestamp_set_second:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 7 } }
```

Parse timezone if present:

```
\datatool_parse_regional_timezone:NeTF #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 9 } }
{ #4 } { #5 }
}
{
```

No match on month:

```
#5
}
}
{ #5 } % No match
}
```

```

    As above but missing century. Syntax: <regex-var> <timestamp seq-var> {<text>}
    {<return true>} {<return false>}
    \cs_new:Nn \datatool_mmdyy_hhmmss_tz_parse_timestamp:NNnTF
    {
      \regex_extract_once:NnNTF #1 { #3 }
      \l_datatool_timestamp_match_seq
      {
Initialise:
        \datatool_timestamp_zero:N #2
Set the month first, to skip rest on failure:
        \datatool_parse_regional_month:NeTF #2
        { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
        {
Successfully set month. Set the day of month:
          \datatool_timestamp_set_day:Ne #2
          { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
Set the year:
          \datatool_timestamp_set_year_add_century:Ne #2
          { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
Set the hour:
          \exp_args:Ne \DTLCurrentLocaleIfpmTF
          { \seq_item:Nn \l_datatool_timestamp_match_seq { 8 } }
          {
            \datatool_timestamp_set_hour:Ne #2
            {
              \int_eval:n
              {
                12 +
                \seq_item:Nn \l_datatool_timestamp_match_seq { 5 }
              }
            }
          }
          {
            \datatool_timestamp_set_hour:Ne #2
            { \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
          }
Set the minute:
          \datatool_timestamp_set_minute:Ne #2
          { \seq_item:Nn \l_datatool_timestamp_match_seq { 6 } }
Set the second:
          \datatool_timestamp_set_second:Ne #2
          { \seq_item:Nn \l_datatool_timestamp_match_seq { 7 } }
Parse timezone if present:
          \datatool_parse_regional_timezone:NeTF #2
          { \seq_item:Nn \l_datatool_timestamp_match_seq { 9 } }

```

```

    { #4 } { #5 }
  }
  {

```

No match on month:

```

    #5
  }
}
{ #5 } % No match
}

```

Syntax: *<regex-var>* *<timestamp seq-var>* {*<text>*} {*<return true>*} {*<return false>*}

The regular expression should have the following groups (in order): year, month, day, hour, minute, second (may be empty), am/pm (may be empty), time zone (may be empty).

```

\cs_new:Nn \datatool_yyyymmdd_hhmmss_tz_parse_timestamp:NNnTF
{
  \regex_extract_once:NnNTF #1 { #3 }
  \l_datatool_timestamp_match_seq
  {

```

Initialise:

```

\datatool_timestamp_zero:N #2

```

Set the month first, to skip rest on failure:

```

\datatool_parse_regional_month:NeTF #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
{

```

Successfully set month. Set the year:

```

\datatool_timestamp_set_year:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }

```

Set the day of month:

```

\datatool_timestamp_set_day:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }

```

Set the hour:

```

\exp_args:Ne \DTLCurrentLocaleIfpmTF
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 8 } }
{
  \datatool_timestamp_set_hour:Ne #2
  {
    \int_eval:n
    {
      12 +
      \seq_item:Nn \l_datatool_timestamp_match_seq { 5 }
    }
  }
}
{
  \datatool_timestamp_set_hour:Ne #2

```

```

        { \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
    }
Set the minute:
    \datatool_timestamp_set_minute:Ne #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 6 } }
Set the second:
    \datatool_timestamp_set_second:Ne #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 7 } }
Parse timezone if present:
    \datatool_parse_regional_timezone:NeTF #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 9 } }
    { #4 } { #5 }
}
{
No match on month:
    #5
}
{ #5 } % No match
}
    As above but missing century. Syntax: <regex-var> <timestamp seq-var> {<text>}
    {<return true>} {<return false>}
    \cs_new:Nn \datatool_yymmdd_hhmmss_tz_parse_timestamp:NNnTF
    {
        \regex_extract_once:NnNTF #1 { #3 }
        \l_datatool_timestamp_match_seq
    }
Initialise:
    \datatool_timestamp_zero:N #2
Set the month first, to skip rest on failure:
    \datatool_parse_regional_month:NeTF #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
    {
Successfully set month. Set the year:
    \datatool_timestamp_set_year_add_century:Ne #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
Set the day of month:
    \datatool_timestamp_set_day:Ne #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
Set the hour:
    \exp_args:Ne \DTLCurrentLocaleIfpmTF
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 8 } }
    {

```

```

\datatool_timestamp_set_hour:Ne #2
{
  \int_eval:n
  {
    12 +
    \seq_item:Nn \l_datatool_timestamp_match_seq { 5 }
  }
}
}
{
  \datatool_timestamp_set_hour:Ne #2
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
}
}

Set the minute:
\datatool_timestamp_set_minute:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 6 } }

Set the second:
\datatool_timestamp_set_second:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 7 } }

Parse timezone if present:
\datatool_parse_regional_timezone:NnTF #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 9 } }
{ #4 } { #5 }
}
{

No match on month:
#5
}
}
{ #5 } % No match
}

Syntax: <timestamp seq-var> {<text>} {<return true>} {<return false>}
\cs_new:Nn \datatool_parse_regional_timezone:NnTF
{
  \tl_if_empty:nTF { #2 }
  {

Missing time zone valid so return true.
#3
}
}
{

Check for known timezone identifier. First try regionless mapping.
\prop_get:NnNF \l_datatool_timezone_map_prop
{ #2 }
\l_datatool_timezone_map_value_tl
{

```

No regionless mapping so now try locale mapping.

```
\DTLCurrentLocaleGetTimeZoneMap { #2 }  
\quark_if_no_value:NT  
\l_datatool_timezone_map_value_tl  
{
```

No mapping so may be numeric.

```
\tl_set:Nn \l_datatool_timezone_map_value_tl { #2 }  
}  
}  
\exp_args:NNV \regex_extract_once:NnNTF  
\c_datatool_timezone_regex  
\l_datatool_timezone_map_value_tl  
\l_datatool_regex_match_seq  
{  
  \datatool_timestamp_set_tzhour:Ne #1  
  { \seq_item:Nn \l_datatool_regex_match_seq { 2 } }  
\tl_if_empty:eF  
  { \seq_item:Nn \l_datatool_regex_match_seq { 3 } }  
  {  
    \datatool_timestamp_set_tzminute:Ne #1  
    { \seq_item:Nn \l_datatool_regex_match_seq { 3 } }  
  }  
  #3  
}  
{ #4 }  
}  
}  
\cs_generate_variant:Nn \datatool_parse_regional_timezone:NnTF  
{ NeTF }  
Syntax: <timestamp seq-var> {<text>} {<return true>} {<return false>}  
\cs_new:Nn \datatool_parse_regional_month:NnTF  
{
```

Check for month name mapping.

```
\DTLCurrentLocaleGetMonthNameMap { #2 }  
\quark_if_no_value:NT  
\l_datatool_monthname_map_value_tl  
{
```

No mapping so check if numeric.

```
\tl_set:Nn \l_datatool_monthname_map_value_tl { #2 }  
}  
\exp_args:NNV \regex_extract_once:NnNTF  
\c_datatool_month_number_regex  
\l_datatool_monthname_map_value_tl  
\l_datatool_regex_match_seq  
{  
  \datatool_timestamp_set_month:Ne #1  
  { \seq_item:Nn \l_datatool_regex_match_seq { 2 } }  
}
```

```

        #3
    }
    { #4 }
}
\cs_generate_variant:Nn \datatool_parse_regional_month:NnTF
{ NeTF }
  Syntax: <regex-var> <timestamp seq-var> {<text>} {<return true>} {<return false>}
  The regular expression should have the following groups (in order): day, month,
year.
\cs_new:Nn \datatool_ddmmyyy_parse_date:NNnTF
{
  \regex_extract_once:NnNTF #1 { #3 }
  \l_datatool_timestamp_match_seq
  {
Initialise:
    \datatool_timestamp_zero:N #2
Set the month first, to skip rest on failure:
    \datatool_parse_regional_month:NeTF #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
    {
Successfully set month. Set the day of month:
    \datatool_timestamp_set_day:Ne #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
Set the year:
    \datatool_timestamp_set_year:Ne #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
Success
    #4
    }
    {
No match on month:
    #5
    }
    { #5 } % No match
  }
  Syntax: <regex-var> <timestamp seq-var> {<text>} {<return true>} {<return false>}
  The regular expression should have the following groups (in order): month, day,
year.
\cs_new:Nn \datatool_mddyyy_parse_date:NNnTF
{
  \regex_extract_once:NnNTF #1 { #3 }
  \l_datatool_timestamp_match_seq
  {

```

Initialise:

```
\datatool_timestamp_zero:N #2
```

Set the month first, to skip rest on failure:

```
\datatool_parse_regional_month:NeTF #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }  
{
```

Successfully set month. Set the day of month:

```
\datatool_timestamp_set_day:Ne #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
```

Set the year:

```
\datatool_timestamp_set_year:Ne #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
```

Success

```
#4  
}  
{
```

No match on month:

```
#5  
}  
}  
{ #5 } % No match  
}
```

Syntax: $\langle regex-var \rangle \langle timestamp seq-var \rangle \{ \langle text \rangle \} \{ \langle return true \rangle \} \{ \langle return false \rangle \}$

The regular expression should have the following groups (in order): year, month, day.

```
\cs_new:Nn \datatool_yyyymmdd_parse_date:NNnTF  
{  
  \regex_extract_once:NnNTF #1 { #3 }  
  \l_datatool_timestamp_match_seq  
  {
```

Initialise:

```
\datatool_timestamp_zero:N #2
```

Set the month first, to skip rest on failure:

```
\datatool_parse_regional_month:NeTF #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }  
{
```

Successfully set month. Set the year:

```
\datatool_timestamp_set_year:Ne #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
```

Set the day of month:

```
\datatool_timestamp_set_day:Ne #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
```

```

Success
    #4
    }
    {
No match on month:
    #5
    }
    }
    { #5 } % No match
}
    As above but century missing: Syntax: <regex-var> <timestamp seq-var> {<text>}
    {<return true>} {<return false>}
    \cs_new:Nn \datatool_ddmmyy_parse_date:NNnTF
    {
        \regex_extract_once:NnNTF #1 { #3 }
        \l_datatool_timestamp_match_seq
        {
Initialise:
        \datatool_timestamp_zero:N #2
Set the month first, to skip rest on failure:
        \datatool_parse_regional_month:NeTF #2
        { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
        {
Successfully set month. Set the day of month:
        \datatool_timestamp_set_day:Ne #2
        { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
Set the year:
        \datatool_timestamp_set_year_add_century:Ne #2
        { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
Success
    #4
    }
    {
No match on month:
    #5
    }
    }
    { #5 } % No match
}
    Syntax: <regex-var> <timestamp seq-var> {<text>} {<return true>} {<return false>}
    \cs_new:Nn \datatool_mmddyy_parse_date:NNnTF
    {
        \regex_extract_once:NnNTF #1 { #3 }
        \l_datatool_timestamp_match_seq
        {

```

Initialise:

```
\datatool_timestamp_zero:N #2
```

Set the month first, to skip rest on failure:

```
\datatool_parse_regional_month:NeTF #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }  
{
```

Successfully set month. Set the day of month:

```
\datatool_timestamp_set_day:Ne #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
```

Set the year:

```
\datatool_timestamp_set_year_add_century:Ne #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
```

Success

```
#4  
}  
{
```

No match on month:

```
#5  
}  
}  
{ #5 } % No match  
}
```

Syntax: $\langle regex-var \rangle \langle timestamp seq-var \rangle \{ \langle text \rangle \} \{ \langle return true \rangle \} \{ \langle return false \rangle \}$

```
\cs_new:Nn \datatool_yymmdd_parse_date:NNnTF  
{  
  \regex_extract_once:NnNTF #1 { #3 }  
  \l_datatool_timestamp_match_seq  
  {
```

Initialise:

```
\datatool_timestamp_zero:N #2
```

Set the month first, to skip rest on failure:

```
\datatool_parse_regional_month:NeTF #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }  
{
```

Successfully set month. Set the year:

```
\datatool_timestamp_set_year_add_century:Ne #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
```

Set the day of month:

```
\datatool_timestamp_set_day:Ne #2  
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
```

Success

```
#4  
}  
{
```

No match on month:

```
    #5
  }
}
{ #5 } % No match
}
```

As above, but year missing. Assume current year: Syntax: *<regex-var>* *<timestamp seq-var>* *{<text>}* *{<return true>}* *{<return false>}*

```
\cs_new:Nn \datatool_ddmm_parse_date:NNnTF
{
  \regex_extract_once:NnNTF #1 { #3 }
  \l_datatool_timestamp_match_seq
  {

```

Initialise:

```
\datatool_timestamp_zero:N #2
```

Set the month first, to skip rest on failure:

```
\datatool_parse_regional_month:NeTF #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
{

```

Successfully set month. Set the day of month:

```
\datatool_timestamp_set_day:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
```

Set the year:

```
\datatool_timestamp_set_year:Nn #2 { }
```

Success

```
    #4
  }
{

```

No match on month:

```
    #5
  }
}
{ #5 } % No match
}
```

Syntax: *<regex-var>* *<timestamp seq-var>* *{<text>}* *{<return true>}* *{<return false>}*

```
\cs_new:Nn \datatool_mmdd_parse_date:NNnTF
{
  \regex_extract_once:NnNTF #1 { #3 }
  \l_datatool_timestamp_match_seq
  {

```

Initialise:

```
\datatool_timestamp_zero:N #2
```

Set the month first, to skip rest on failure:

```
\datatool_parse_regional_month:NeTF #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
{
```

Successfully set month. Set the day of month:

```
\datatool_timestamp_set_day:Ne #2
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
```

Set the year:

```
\datatool_timestamp_set_year:Nn #2 { }
```

Success

```
#4
}
```

No match on month:

```
#5
}
{ #5 } % No match
}
```

Syntax: *<timestamp seq-var>* {*<text>*} {*<return true>*} {*<return false>*}

```
\cs_new:Nn \datatool_hhmmss_parse_time:NnTF
{
  \datatool_hhmmss_parse_time:NNnTF
  \c_datatool_colon_anchored_hhmmss_time_regex #1 { #2 } { #3 } { #4 }
}
```

Syntax: *<regex-var>* *<timestamp seq-var>* {*<text>*} {*<return true>*} {*<return false>*}

```
\cs_new:Nn \datatool_hhmmss_parse_time:NNnTF
{
  \regex_extract_once:NnNTF
  #1 { #3 }
  \l_datatool_timestamp_match_seq
  {
```

Initialise:

```
\datatool_timestamp_zero:N #2
```

Set the hour:

```
\exp_args:Ne \DTLCurrentLocaleIfpmTF
{ \seq_item:Nn \l_datatool_timestamp_match_seq { 5 } }
{
  \datatool_timestamp_set_hour:Ne #2
  {
    \int_eval:n
    {
      12 +
      \seq_item:Nn \l_datatool_timestamp_match_seq { 2 }
    }
  }
```

```

    }
  }
  {
    \datatool_timestamp_set_hour:Ne #2
    { \seq_item:Nn \l_datatool_timestamp_match_seq { 2 } }
  }
Set the minute:
  \datatool_timestamp_set_minute:Ne #2
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 3 } }
Set the second:
  \datatool_timestamp_set_second:Ne #2
  { \seq_item:Nn \l_datatool_timestamp_match_seq { 4 } }
Success
  #4
  }
  { #5 } % No match
}
\cs_generate_variant:Nn \datatool_hhmmss_parse_time:NNnTF
{ cNnTF }

```

2.4.3 Currencies

`\@dtl@currencies` Renamed `\@dtl@currencies` since the internal structure is changed. This will trigger an unknown control sequence error if it's being used by anything. The new name is `\l__datatool_known_currencies_seq` but it needs to be defined before `\datatool_set_currency:nn` is used.

An internal list that stores all known currencies.

```

\seq_put_right:Nn \l__datatool_known_currencies_seq { \$ }
\seq_put_right:Nn \l__datatool_known_currencies_seq { pounds }
\seq_put_right:Nn \l__datatool_known_currencies_seq { \textdollar }
\seq_put_right:Nn \l__datatool_known_currencies_seq { \textstirling }
\seq_put_right:Nn \l__datatool_known_currencies_seq { \texteuro }
\seq_put_right:Nn \l__datatool_known_currencies_seq { \textyen }
\seq_put_right:Nn \l__datatool_known_currencies_seq { \textwon }
\seq_put_right:Nn \l__datatool_known_currencies_seq { \textcurrency }

```

`\@dtl@currency` `\@dtl@currency` is set by `\DTLconverttodecimal` and `\@dtl@checknumerical`. It is used by `\DTLcurrency`. Set to `\$` by default.

```
\newcommand*{\@dtl@currency}{\$}
```

`\DTLcurrencySymbol`

```
\newcommand*{\DTLcurrencySymbol}{\@dtl@currency}
```

`\DTLcurrencyCode`

```
\newcommand*{\DTLcurrencyCode}{XXX}
```

`\DTLsetdefaultcurrency` `\DTLsetdefaultcurrency{<symbol>}` sets the default currency.

```
\NewDocumentCommand \DTLsetdefaultcurrency { m }
{
```

Detokenize in test in case argument isn't a currency code to allow for backward-compatibility.

```
\tl_if_exist:cTF { dtl@curr@ \tl_to_str:n { #1 } @sym }
{
```

Defined currency code.

```
\tl_set:Ne \@dtl@currency { \exp_not:c { DTLcurr #1 } }
\tl_set:Ne \DTLCurrencyCode { #1 }
\tl_set:Ne \DTLfmtcurrency
{ \exp_not:c { dtl@curr@ #1 @fmt } }
}
```

Unknown currency.

```
\tl_set:Nn \DTLCurrencyCode { XXX }
\tl_set:Nn \@dtl@currency { #1 }
}
```

For use with the region files.

```
\cs_new:Nn \datatool_register_regional_currency_code:nn
{
\seq_put_right:Nn \l_datatool_regional_currencies_seq { #2 }
\prop_put:Nnn \l_datatool_regional_currencies_prop { #1 } { #2 }
}
```

```
\cs_new:Nn \datatool_currency_symbol_region_prefix:n
{
\DTLcurrCodeOrSymOrChar
{ }
{ \datatoolcurrencysymbolprefixfmt { #1 } }
{ \datatoolcurrencysymbolprefixfmt { #1 } }
}
```

`\DTLcurrSym`

```
\newcommand{\DTLcurrSym}[1]{\csuse{dtl@curr@ #1 @sym}}
```

`\DTLcurrChar`

```
\newcommand{\DTLcurrChar}[1]{\csuse{dtl@curr@ #1 @tl}}
```

`\DTLcurrStr`

```
\newcommand{\DTLcurrStr}[1]{\csuse{dtl@curr@ #1 @str}}
```

`\DTLdefcurrency` Define currency.

```
\DTLdefcurrency[<fmt>]{<iso-code>}{<symbol>}{<string>}
```

NB `\DTLdefcurrency` doesn't pick up the fourth *(string)* argument. Category code of `$` needs to be changed first.

```
\NewDocumentCommand{\DTLdefcurrency} { O{\dtlcurrdefaultfmt} m m }
{
  \group_begin:
  \char_set_catcode_other:N \$
  \__datatool_def_currency:nnnn { #1 } { #2 } { #3 }
}
\cs_new:Nn \__datatool_def_currency:nnnn
{
  \group_end:
  \datatool_def_currency:nnne { #1 } { #2 } { #3 } { #4 }
}
```

Lower-level command. Three arguments, use default format:

```
\cs_new:Nn \datatool_def_currency:nnn
{
  \datatool_def_currency:nnnn
  { \dtlcurrdefaultfmt } { #1 } { #2 } { #3 }
}
\cs_generate_variant:Nn \datatool_def_currency:nnn
{ nnV , nne , nVV }
```

Four arguments, supply formatting command in first argument:

```
\cs_new:Nn \datatool_def_currency:nnnn
{
  \seq_put_right:Nn \l_datatool_currencies_seq { #2 }
  \str_set:cn { dtl@curr@ #2 @str } { #4 }
  \tl_set:cn { dtl@curr@ #2 @tl } { #4 }
  \tl_set:cn { dtl@curr@ #2 @sym } { #3 }
  \csedef { DTLcurr #2 }
  {
    \exp_not:N \dtltxorsort
    {
      \exp_not:N \DTLcurrCodeOrSymOrChar
      { #2 }
      { \exp_not:N \DTLcurrSym { #2 } }
      { \exp_not:N \DTLcurrChar { #2 } }
    }
    {
      \exp_not:N \DTLcurrStr { #2 }
    }
  }
  \DTLnewcurrencysymbol { #3 }
  \DTLnewcurrencysymbol { #4 }
  \exp_args:Nc \DTLnewcurrencysymbol { DTLcurr #2 }
  \csdef { dtl@curr@ #2 @fmt } { #1 }
}
\cs_generate_variant:Nn \datatool_def_currency:nnnn
{ nnnV , nnne , nnVV }
```

Find first declared regional currency code that matches the given symbol. Returns empty if no match. First tests if a match on current currency.

```

\cs_new:Nn \datatool_get_currency_code:Nn
{
  \__datatool_if_current_currency:nTF { #2 }
  {
    \tl_set_eq:NN #1 \DTLCurrencyCode
  }
  {
    \tl_clear:N #1
    \seq_map_inline:Nn \l_datatool_regional_currencies_seq
    {
      \tl_if_eq:nnTF { ##1 } { #2 }
      {
        \tl_set:Nn #1 { ##1 }
        \seq_map_break:
      }
      {
        \tl_if_eq:nnTF { \DTLcurr { ##1 } } { #2 }
        {
          \tl_set:Nn #1 { ##1 }
          \seq_map_break:
        }
        {
          \exp_args:Ne \tl_if_eq:nnTF { \exp_not:c { DTLcurr ##1 } } { #2 }
          {
            \tl_set:Nn #1 { ##1 }
            \seq_map_break:
          }
          {
            \tl_if_eq:cnTF { dtl@curr@ ##1 @sym } { #2 }
            {
              \tl_set:Nn #1 { ##1 }
              \seq_map_break:
            }
            {
              \str_if_eq:vnT { dtl@curr@ ##1 @str } { #2 }
              {
                \tl_set:Nn #1 { ##1 }
                \seq_map_break:
              }
            }
          }
        }
      }
    }
  }
}
\cs_generate_variant:Nn \datatool_get_currency_code:Nn { NV }

```

Test if the supplied token list matches the current symbol or string.

```
\prg_new_conditional:Npnn \__datatool_if_current_currency:n #1
{ T, F, TF }
{
  \tl_if_eq:NnTF \@dtl@currency { #1 }
  {
    \prg_return_true:
  }
  {
    \tl_if_exist:cTF
    { DTLcurr \DTLCurrencyCode }
    {
      \tl_if_eq:cnTF
      { DTLcurr \DTLCurrencyCode }
      { #1 }
      {
        \prg_return_true:
      }
      {
        \exp_args:Nv \tl_if_eq:nnTF
        { dtl@curr@ \DTLCurrencyCode @sym } { #1 }
        {
          \prg_return_true:
        }
        {
          \str_if_eq:vnTF
          { dtl@curr@ \DTLCurrencyCode @str }
          { #1 }
          {
            \prg_return_true:
          }
          {
            \exp_args:Ne \tl_if_eq:nnTF
            { \exp_not:N \DTLcurr { \DTLCurrencyCode } }
            { #1 }
            {
              \prg_return_true:
            }
            {
              \prg_return_false:
            }
          }
        }
      }
    }
  }
}
{
  \prg_return_false:
}
}
```

```

}
    Allow the command used for the currency to be changed. Note that this will add
    the new symbol to the list of known currency symbols but won't remove the old one.
\cs_new:Nn \datatool_set_currency_symbol:nn
{
  \tl_if_exist:cTF { dtl@curr@ #1 @sym }
  {
    \csdef { dtl@curr@ #1 @sym } { #2 }
    \DTLnewcurrencysymbol { #2 }
  }
  {
    \PackageError { datatool-base }
    {
      Can't ~ set ~ currency ~ symbol ~ to ~ \tl_to_str:n { #2 } ~ : ~
      Currency ~ ` #1 ' ~ not ~ defined
    }
    {
      Check ~ that ~ you ~ have ~ spelt ~ the ~
      currency ~ code ~ correctly
    }
  }
}
\cs_generate_variant:Nn \datatool_set_currency_symbol:nn
{ nV , ne }

```

`\DTLcurrency` Format currency using current symbol.

```
\newcommand{\DTLcurrency}[1]{\DTLfmtcurrency{\@dtl@currency}{#1}}
```

`\DTLfmtcurr` Format currency according to the given currency code or use the default format if not defined. May fully expand (unless currency symbol is fragile, which is less likely with newer L^AT_EX kernel).

```
\newcommand{\DTLfmtcurr}[2]{%
  \cs_if_exist:cTF { dtl@curr@ #1 @fmt }
  {
    \use:c { dtl@curr@ #1 @fmt } { \DTLcurr { #1 } } { #2 }
  }
  { \DTLcurrency { #2 } }
}
```

`\DTLfmtcurrency` Format currency using given symbol.

```
\newcommand{\DTLfmtcurrency}{\dtlcurrdefaultfmt}
```

`\dtlcurrdefaultfmt`

```
\newcommand{\dtlcurrdefaultfmt}{\dtlcurrprefixfmt}
```

`\dtlcurrprefixfmt`

```
\newcommand{\dtlcurrprefixfmt}[2]{
  \datatool_prefix_adjust_sign:nnn { #1 } { \dtlcurrfmtsep } { #2 }
}
```

```

\cs_new:Nn \datatool_prefix_adjust_sign:nnn
{
  \bool_lazy_or:nnTF
    { \tl_if_head_eq_charcode_p:nN { #3 } + }
    { \tl_if_head_eq_charcode_p:nN { #3 } - }
  {
    \exp_args:Ne \datatool_adjust_sign_fmt:n { \tl_head:n { #3 } }
    #1 #2
    \tl_tail:n { #3 }
  }
  { #1 #2 #3 }
}

```

Allow the sign to be formatted if outside of math mode.

```

\cs_new:Nn \datatool_adjust_sign_fmt:n
{
  \ifmmode
    #1
  \else
    \tl_if_head_eq_charcode:nNTF { #1 } -
    {
      \textminus
    }
    { #1 }
  \fi
}

```

`\dtlcurrsuffixfmt`

```

\newcommand{\dtlcurrsuffixfmt}[2]{
  \datatool_suffix_adjust_sign:nnn { #1 } { \dtlcurrfmtsep } { #2 }
}

```

```

\cs_new:Nn \datatool_suffix_adjust_sign:nnn
{
  \bool_lazy_or:nnTF
    { \tl_if_head_eq_charcode_p:nN { #3 } + }
    { \tl_if_head_eq_charcode_p:nN { #3 } - }
  {
    \exp_args:Ne \datatool_adjust_sign_fmt:n { \tl_head:n { #3 } }
    \tl_tail:n { #3 }
    #2 #1
  }
  { #3 #2 #1 }
}

```

`\dtlcurrfmtsymsep`

```

\newcommand{\dtlcurrfmtsymsep}{}
\ExplSyntaxOff

```

```

\dtlcurrfmtsep
\newcommand{\dtlcurrfmtsep}{\DTLcurrCodeOrSymOrChar{~}{\dtlcurrfmtsymsep}{\dtlcurrfmtsym}}
\ExplSyntaxOn

```

```

\DTLcurr
\newcommand{\DTLcurr}[1]{\ifcsdef{DTLcurr#1}{\csuse{DTLcurr#1}}{#1}}

```

```

DTLdefaultEURcurrencyfmt
\newcommand{\DTLdefaultEURcurrencyfmt}{\dtlcurrdefaultfmt}

```

```

\DTLcurrXXX
\datatool_def_currency:nnV
{ XXX }
{ \textcurrency }
\l_datatool_currency_str

```

```

\DTLcurrXBT
\cs_if_exist:NT \faBtc
{
\datatool_def_currency:nnV
{ XBT }
{ \faBtc }
\l_datatool_bitcoin_str
}

```

Try to guess the command used for the Euro currency symbol. Mainly provided to retain backward compatibility with pre v3.0. If incorrect, this may be changed with `\datatool_set_currency_symbol:nn` Other currencies can be defined in the applicable region file.

```

\tl_new:N \l__datatool_eurocs_tl
\cs_if_exist:NTF \euro
{
\tl_set:Nn \l__datatool_eurocs_tl { \euro }
}
{
\cs_if_exist:NTF \Euro
{
\tl_set:Nn \l__datatool_eurocs_tl { \Euro }
}
{
\cs_if_exist:NTF \EUR
{
\tl_set:Nn \l__datatool_eurocs_tl { \EUR }
}
{
\cs_if_exist:NTF \faEur
{

```


2.5 Floating Point Arithmetic

The commands defined in this section are designed for localised numeric values. They all have to first convert the formatted value to a numeric value acceptable to the underlying arithmetic function and then convert back again. If the original supplied values had different data types, the data type of the result depends on which type is dominant.

First provide some common functions to update the datum structure after operating on two values with potentially different types.

Determine dominant data type: decimal overrides integer, currency overrides integer and decimal, temporal values override other values, but time should be converted to datetime if added to a date or datetime or other numeric value, and date should be converted to datetime if added to anything other than an integer.

NB if two currencies are added, their symbols are assumed to represent the same currency unit. No exchange rate information is available.

```
\cs_new:Nn \__datatool_update_datatype:
{
  \datatool_update_datatype:NNNN
  \@dtl@datatype
  \l__datatool_tmp_datatype_int
  \l__datatool_datum_currency_tl
  \l__datatool_tmp_currency_tl
}
```

Syntax: $\langle type1 int-var \rangle \langle type2 int-var \rangle \langle curr-sym1 tl-var \rangle \langle curr-sym2 tl-var \rangle$ This will update $\langle type1 int-var \rangle$ to the dominant type and (if the dominant type is currency) $\langle curr-sym1 tl-var \rangle$ to the currency symbol.

```
\cs_new:Nn \datatool_update_datatype:NNNN
{
  \bool_lazy_or:nnF
  { \int_compare_p:nNn { #1 } = { #2 } }
  { \int_compare_p:nNn { #2 } = { \c_datatool_unknown_int } }
  {
    \int_compare:nNnTF { #1 } = { \c_datatool_unknown_int }
    {
      \int_set_eq:NN #1 #2
      \tl_set_eq:NN #3 #4
    }
  }
  {
    \bool_lazy_or:nnTF
    { \datatool_if_temporal_datum_type_p:n { #1 } }
    { \datatool_if_temporal_datum_type_p:n { #2 } }
  }
}
```

If either is a temporal value (and already checked they are not the same type), the result will be a timestamp unless an integer has been added to a date.

```
\bool_lazy_or:nnTF
{
  \bool_lazy_and_p:nn
  { \int_compare_p:nNn { #1 } = { \c_datatool_date_int } }
```



```

    {
      \exp_args:NV \DTLdecimaltolocale #3 #1
    }
    {
      \exp_args:NVV \__datatool_decimal_to_currency:nnN
        #4 #3 #1
    }
  }
}

```

```

\datatool_numeric_fn:NnnNN
<result tl-var> {<num1>} {<num2>}
<decimal-operator-cs> <int-operator-cs>

```

Perform a numerical operation on two values that need parsing or that are already in datum format. If they are both integers, use the *<int-operator-cs>* function, which should take two arguments and expand to the result, otherwise use the *\decimal-operator-cs* function, which should take three arguments where the first is the result token list variable and the others are the numeric values.

```

\cs_new:Nn \datatool_numeric_fn:NnnNN
{
  \DTLconverttodecimal { #2 } \l__datatool_resulta_tl
  \int_set_eq:NN
    \l__datatool_tmp_datatype_int
    \@dtl@datatype
  \tl_set_eq:NN
    \l__datatool_tmp_currency_tl
    \l__datatool_datum_currency_tl
  \DTLconverttodecimal { #3 } \l__datatool_resultb_tl

```

If the data types are different, need to determine the dominant one.

```

  \__datatool_update_datatype:
  Determine which function should be used.
  \datatool_if_any_int_datum_type:nTF { \@dtl@datatype }
  {

```

Version 3.1: changed *\tl_set:Nx* to *\tl_set:Ne* (not sure if this makes difference).

```

    \tl_set:Ne \l__datatool_result_tl
      { #5 { \l__datatool_resulta_tl } { \l__datatool_resultb_tl } }
  }
  {
    #4
    { \l__datatool_result_tl }
    { \l__datatool_resulta_tl }
    { \l__datatool_resultb_tl }
  }
  \__datatool_assign_result:N #1
}

```

```

\datatool_numeric_fn:NnNN
<result t1-var> {<num>}
<decimal-operator-cs> <int-operator-cs>

```

Perform a numerical operation on one value that needs parsing or that is already in datum format. If the value is an integer, use the `<int-operator-cs>` function, which should take one argument and expand to the result, otherwise use the `\decimal-operator-cs` function, which should take two arguments where the first is the result token list variable and the second is the numeric value.

```

\cs_new:Nn \datatool_numeric_fn:NnNN
{
  \DTLconverttodecimal { #2 } \l_datatool_resulta_tl

```

Determine which function should be used.

```

\datatool_if_any_int_datum_type:nTF { \@dtl@datatype }
{

```

Version 3.1: changed `\tl_set:Nx` to `\tl_set:Ne` (not sure if this makes difference).

```

  \tl_set:Ne \l_datatool_result_tl
  { #4 { \l_datatool_resulta_tl } }
}
{
  #3
  { \l_datatool_result_tl }
  { \l_datatool_resulta_tl }
}
\__datatool_assign_result:N #1
}

```

```

\datatool_numeric_fn:NnN
<result t1-var> {<num>}
<decimal-operator-cs>

```

Perform a numerical operation on one value that needs parsing or that is already in datum format. The calculation is performed by `\decimal-operator-cs` function, which should take two arguments where the first is the result token list variable and the second is the numeric value. The result is not expected to be an integer.

```

\cs_new:Nn \datatool_numeric_fn:NnN
{
  \DTLconverttodecimal { #2 } \l_datatool_resulta_tl
  #3
  { \l_datatool_result_tl }
  { \l_datatool_resulta_tl }
  \datatool_if_any_int_datum_type:nTF { \@dtl@datatype }
  {
    \int_set_eq:NN \@dtl@datatype \c_datatool_decimal_int

```

```

}
\_datatool_assign_result:N #1
}

```

```

\datatool_numeric_list_fn:NnNN
<result tl-var> {<num list>}
<decimal-operator-cs> <int-operator-cs>

```

Perform a numerical operation on a list of values that need parsing or that are already in datum format. As `\datatool_numeric_fn:NnnNN` but iterates through the list performing the applicable function sequentially. The result will be set to `\DTLnumbernull` if the list is empty (and a warning will occur).

```

\cs_new:Nn \datatool_numeric_list_fn:NnNN
{

```

Convert the list to the scratch sequence:

```

\@dtl@assigntmpseq { #2 }

```

Keep a note of the number of items in the sequence if required.

```

\int_set:Nn \l_datatool_count_int
{ \seq_count:N \l_datatool_tmp_seq }

```

If sequence is empty, set the result to number null:

```

\int_if_zero:nTF { \l_datatool_count_int }
{
  \PackageWarning { datatool-base }
    { empty ~ list ~ `#2 ' ~ found ~ in ~ aggregate ~ function }
  \tl_set_eq:NN #1 \DTLnumbernull
}
{

```

Pop the first item from the sequence:

```

\seq_pop_left:NN \l_datatool_tmp_seq \l_datatool_resulta_tl
\exp_args:NV \DTLconverttodecimal
  \l_datatool_resulta_tl
  \l_datatool_result_tl
\seq_map_inline:Nn \l_datatool_tmp_seq
{

```

Save previous:

```

\int_set_eq:NN
  \l_datatool_tmp_datatype_int
  \@dtl@datatype
\tl_set_eq:NN
  \l_datatool_tmp_currency_tl
  \l_datatool_datum_currency_tl
\tl_set_eq:NN
  \l_datatool_resulta_tl
  \l_datatool_result_tl

```

Parse this value.

```
\DTLconverttodecimal { ##1 } \l__datatool_resultb_tl
```

If the data types are different, need to determine the dominant one.

```
\__datatool_update_datatype:
```

Determine which function should be used.

```
\datatool_if_any_int_datum_type:nTF { \@dtl@datatype }  
{
```

Version 3.1: changed `\tl_set:Nx` to `\tl_set:Ne` (not sure if this makes difference).

```
\tl_set:Ne \l__datatool_result_tl  
{ #4 { \l__datatool_resulta_tl } { \l__datatool_resultb_tl } }  
}  
{  
#3  
{ \l__datatool_result_tl }  
{ \l__datatool_resulta_tl }  
{ \l__datatool_resultb_tl }  
}  
}  
\__datatool_assign_result:N #1  
}  
}
```

```
\datatool_decimal_list_fn:NnN  
<result fp-var> {<num list>}  
<fp-operator-cs>
```

Similar to the above but the result is expected to be a floating point variable and the function should be a l2fp update function, such as `\fp_add:Nn`.

```
\cs_new:Nn \datatool_decimal_list_fn:NnN  
{
```

Convert the list to the scratch sequence:

```
\@dtl@assigntmpseq { #2 }
```

Keep a note of the number of items in the sequence if required.

```
\int_set:Nn \l__datatool_count_int  
{ \seq_count:N \l__datatool_tmp_seq }
```

Trigger an error if the list is empty:

```
\int_if_zero:nTF { \l__datatool_count_int }  
{  
  \PackageError { datatool-base }  
  { empty ~ list ~ `#2' ~ found ~ in ~ aggregate ~ function }  
  { one ~ or ~ more ~ numeric ~ items ~ are ~ expected }  
}  
{
```

Pop the first item from the sequence:

```
\seq_pop_left:NN \l__datatool_tmp_seq \l__datatool_resulta_tl
\datatool_set_fp:NV #1 \l__datatool_resulta_tl
\seq_map_inline:Nn \l__datatool_tmp_seq
{
```

Save previous datum information:

```
\int_set_eq:NN
\l__datatool_tmp_datatype_int
\@dtl@datatype
\tl_set_eq:NN
\l__datatool_tmp_currency_tl
\l__datatool_datum_currency_tl
```

Get this value as fp variable.

```
\datatool_set_fp:Nn \l__datatool_tmpa_fp { ##1 }
```

If the data types are different, need to determine the dominant one.

```
\__datatool_update_datatype:
```

Perform the update.

```
    #3 #1 { \l__datatool_tmpa_fp }
  }
}
```

```
\DTLadd{<cmd>}{<num1>}{<num2>}
```

\DTLadd

Sets $\langle cmd \rangle = \langle num1 \rangle + \langle num2 \rangle$

```
\NewDocumentCommand \DTLadd { m m m }
{
  \datatool_numeric_fn:NnnNN
  #1 { #2 } { #3 } \dtladd \datatool_int_add:nn
}
```

For use in the above and related commands:

```
\cs_new:Nn \datatool_int_add:nn { \int_eval:n { #1 + #2 } }
```

\DTLgadd Global version

```
\NewDocumentCommand \DTLgadd { m m m }
{
  \DTLadd { \l__datatool_resulta_tl } { #2 } { #3 }
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl
}
```

```
\DTLaddall{<cmd>}{<num list>}
```

\DTLaddall

Sums all the values in $\langle num\ list \rangle$ and stores in $\langle cmd \rangle$ which must be a control sequence.

```
\NewDocumentCommand \DTLaddall { m m }
{
  \datatool_numeric_list_fn:NnnN
  #1 { #2 } \dtladd \datatool_int_add:nn
}
```

\DTLgaddall

$\backslash\text{DTLgaddall}\{\langle cmd \rangle\}\{\langle num\ list \rangle\}$

Global version

```
\NewDocumentCommand \DTLgaddall { m m }
{
  \DTLaddall { \l__datatool_resultb_tl } { #2 }
  \tl_gset_eq:NN #1 \l__datatool_resultb_tl
}
```

\DTLsub

$\backslash\text{DTLsub}\{\langle cmd \rangle\}\{\langle num1 \rangle\}\{\langle num2 \rangle\}$

Sets $\langle cmd \rangle = \langle num1 \rangle - \langle num2 \rangle$

```
\NewDocumentCommand \DTLsub { m m m }
{
  \datatool_numeric_fn:NnnNN
  #1 { #2 } { #3 } \dtlsub \datatool_int_sub:nn
}
```

For use in the above:

```
\cs_new:Nn \datatool_int_sub:nn { \int_eval:n { #1 - ( #2 ) } }
```

\DTLgsub Global version

```
\NewDocumentCommand \DTLgsub { m m m }
{
  \DTLsub { \l__datatool_resulta_tl } {#2} {#3}
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl
}
```

\DTLmul

$\backslash\text{DTLmul}\{\langle cmd \rangle\}\{\langle num1 \rangle\}\{\langle num2 \rangle\}$

Sets $\langle cmd \rangle = \langle num1 \rangle \times \langle num2 \rangle$

```
\NewDocumentCommand \DTLmul { m m m }
{
  \datatool_numeric_fn:NnnNN
  #1 { #2 } { #3 } \dtlmul \datatool_int_mul:nn
}
```

For use in the above:

```
\cs_new:Nn \datatool_int_mul:nn { \int_eval:n { ( #1 ) * ( #2 ) } }
```

\DTLgmul Global version

```
\newcommand*{\DTLgmul}[3]{%  
  \DTLmul{ \l__datatool_resulta_tl } {#2} {#3}  
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl  
}
```

```
\DTLdiv{<cmd>}{<num1>}{<num2>}
```

\DTLdiv

Sets $\langle cmd \rangle = \langle num1 \rangle / \langle num2 \rangle$

```
\NewDocumentCommand \DTLdiv { m m m }  
{  
  \datatool_numeric_fn:NnnNN  
  #1 { #2 } { #3 } \dtldiv \int_div_round:nn  
}
```

\DTLgdiv Global version

```
\NewDocumentCommand \DTLgdiv { m m m }  
{  
  \DTLdiv{ \l__datatool_resulta_tl } {#2} {#3}  
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl  
}
```

```
\DTLabs{<cmd>}{<num>}
```

\DTLabs

Sets $\langle cmd \rangle = \text{abs}(\langle num \rangle)$

```
\NewDocumentCommand \DTLabs { m m }  
{  
  \datatool_numeric_fn:NnnNN  
  #1 { #2 } \dtlabs \int_abs:n  
}
```

\DTLgabs Global version

```
\NewDocumentCommand \DTLgabs { m m }  
{  
  \DTLabs{ \l__datatool_resulta_tl } {#2}  
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl  
}
```

```
\DTLneg{<cmd>}{<num>}
```

\DTLneg

Sets $\langle cmd \rangle = -\langle num \rangle$

```

\NewDocumentCommand \DTLneg { m m }
{
  \datatool_numeric_fn:NnNN
  #1 { #2 } \dtlneg \datatool_int_neg:n
}

```

Integer negation function for use in the above.

```

\cs_new:Nn \datatool_int_neg:n
{ \int_eval:n { - ( #1 ) } }

```

\DTLgneg Global version

```

\NewDocumentCommand \DTLgneg { m m }
{
  \DTLneg{ \l__datatool_resulta_tl } {#2}
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl
}

```

```

\DTLsqrt{<cmd>}{<num>}

```

\DTLsqrt

Sets $\langle cmd \rangle = \text{sqrt}(\langle num \rangle)$

```

\NewDocumentCommand \DTLsqrt { m m }
{
  \datatool_numeric_fn:NnN #1 { #2 } \dtlroot
}

```

\DTLgsqrt Global version

```

\NewDocumentCommand \DTLgsqrt { m m }
{
  \DTLsqrt{ \l__datatool_resulta_tl } {#2}
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl
}

```

```

\DTLmin{<cmd>}{<num1>}{<num2>}

```

\DTLmin

Sets $\langle cmd \rangle = \text{min}(\langle num1 \rangle, \langle num2 \rangle)$

```

\NewDocumentCommand \DTLmin { m m m }
{
  \datatool_numeric_fn:NnnNN
  #1 { #2 } { #3 } \dtlmin \int_min:nn
}

```

\DTLgmin Global version

```

\NewDocumentCommand \DTLgmin { m m m }
{
  \DTLmin{ \l__datatool_resulta_tl } {#2} {#3}
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl
}

```

\DTLminall

`\DTLminall{<cmd>}{<num list>}`

Finds the minimum value in *<num list>* and stores in *<cmd>* which must be a control sequence.

```
\NewDocumentCommand \DTLminall { m m }
{
  \datatool_numeric_list_fn:NnNN
  #1 { #2 } \dtlmin \int_min:nn
}
```

\DTLgminall

`\DTLgminall{<cmd>}{<num list>}`

Global version

```
\NewDocumentCommand \DTLgminall { m m }
{
  \DTLminall{ \l__datatool_resultb_tl } { #2 }
  \tl_gset_eq:NN #1 \l__datatool_resultb_tl
}
```

\DTLmax

`\DTLmax{<cmd>}{<num1>}{<num2>}`

Sets *<cmd>* = max(*<num1>*, *<num2>*)

```
\NewDocumentCommand \DTLmax { m m m }
{
  \datatool_numeric_fn:NnnNN
  #1 { #2 } { #3 } \dtlmax \int_max:nn
}
```

\DTLgmax Global version

```
\NewDocumentCommand \DTLgmax { m m m }
{
  \DTLmax { \l__datatool_resultb_tl } { #2 } { #3 }
  \tl_gset_eq:NN #1 \l__datatool_resultb_tl
}
```

\DTLmaxall

`\DTLmaxall{<cmd>}{<num list>}`

Finds the maximum value in *<num list>* and stores in *<cmd>* which must be a control sequence.

```
\NewDocumentCommand \DTLmaxall { m m }
{
  \datatool_numeric_list_fn:NnNN
  #1 { #2 } \dtlmax \int_max:nn
}
```

`\DTLgmaxall`

`\DTLgmaxall{<cmd>}{<num list>}`

Global version

```
\NewDocumentCommand \DTLgmaxall { m m }
{
  \DTLmaxall{ \l__datatool_resultb_tl } { #2 }
  \tl_gset_eq:NN #1 \l__datatool_resultb_tl
}
```

`\DTLmeanforall`

`\DTLmeanforall{<cmd>}{<num list>}`

Computes the arithmetic mean of all the values in `<num list>` and stores in `<cmd>` which must be a control sequence.

```
\NewDocumentCommand \DTLmeanforall { m m }
{
  \datatool_decimal_list_fn:NnN
  \l__datatool_total_fp { #2 } \fp_add:Nn
  \int_if_zero:nTF { \l__datatool_count_int }
  {
    \tl_set_eq:NN #1 \DTLnumbernull
  }
  {
    \fp_set:Nn
    \l__datatool_mean_fp
    { \l__datatool_total_fp / \l__datatool_count_int }

    \tl_set:Ne
    \l__datatool_result_tl
    { \fp_use:N \l__datatool_mean_fp }
    \__datatool_assign_result:N #1
  }
}
```

`\DTLgmeanforall`

`\DTLgmeanforall{<cmd>}{<num list>}`

Global version

```
\NewDocumentCommand \DTLgmeanforall { m m }
{
  \DTLmeanforall{ \l__datatool_resultb_tl } { #2 }
  \tl_gset_eq:NN #1 \l__datatool_resultb_tl
}
```

`\DTLvarianceforall`

`\DTLvarianceforall{<cmd>}{<num list>}`

Computes the variance of all the values in $\langle num\ list \rangle$ and stores in $\langle cmd \rangle$ which must be a control sequence. This is more complicated than the previous aggregate functions.

```

\NewDocumentCommand \DTLvarianceforall { m m }
{
  \@dtl@assigntmpseq{#2}
  \int_zero:N \l__datatool_count_int
  \fp_zero:N \l__datatool_total_fp
  \int_set_eq:NN \@dtl@datatype \c_datatool_unknown_int
  \tl_clear:N \l__datatool_datum_currency_tl
  \seq_clear:N \l__datatool_tmpb_seq
  \seq_map_inline:Nn \l__datatool_tmp_seq
  {
    \int_incr:N \l__datatool_count_int
  }
  Save previous datum information:
  \int_set_eq:NN
  \l__datatool_tmp_datatype_int
  \@dtl@datatype
  \tl_set_eq:NN
  \l__datatool_tmp_currency_tl
  \l__datatool_datum_currency_tl

  Convert:
  \DTLconverttodecimal { ##1 } \l__datatool_resulta_tl
  \__datatool_update_datatype:
  \seq_put_right:No \l__datatool_tmpb_seq { \l__datatool_resulta_tl }
  \fp_add:Nn
  \l__datatool_total_fp
  { \l__datatool_resulta_tl }
}
\int_if_zero:nTF { \l__datatool_count_int }
{
  \PackageWarning { datatool-base }
  { empty ~ list ~ `#2 ' ~ found ~ in ~ aggregate ~ function }
  \tl_set_eq:NN #1 \DTLnumbernull
}
{
  \fp_set:Nn
  \l__datatool_mean_fp
  { \l__datatool_total_fp / \l__datatool_count_int }
  \fp_zero:N \l__datatool_tmpa_fp
  \seq_map_inline:Nn \l__datatool_tmpb_seq
  {
    \fp_set:Nn \l__datatool_tmpb_fp
    {
      ##1 - \l__datatool_mean_fp
    }
  }
  \fp_add:Nn \l__datatool_tmpa_fp
  {

```

```

        \l_datatool_tmpb_fp * \l_datatool_tmpb_fp
    }
}
\fp_set:Nn \l_datatool_tmpa_fp { \l_datatool_tmpa_fp / \l_datatool_count_int }
\tl_set:Ne
  \l_datatool_result_tl
  { \fp_use:N \l_datatool_tmpa_fp }
  \__datatool_assign_result:N #1
}
}

```

`\DTLgvarianceforall{<cmd>}{<num list>}`

\DTLgvarianceforall

Global version

```

\NewDocumentCommand \DTLgvarianceforall { m m }
{
  \DTLvarianceforall { \l_datatool_resulttb_tl } { #2 }
  \tl_gset_eq:NN #1 \l_datatool_resulttb_tl
}

```

`\DTLsdforall{<cmd>}{<num list>}`

\DTLsdforall

Computes the standard deviation of all the values in `<num list>` and stores in `<cmd>` which must be a control sequence.

```

\NewDocumentCommand \DTLsdforall { m m }
{
  \@dtl@assigntmpseq{#2}
  \int_zero:N \l_datatool_count_int
  \fp_zero:N \l_datatool_total_fp
  \int_set_eq:NN \@dtl@datatype \c_datatool_unknown_int
  \tl_clear:N \l_datatool_datum_currency_tl
  \seq_clear:N \l_datatool_tmpb_seq
  \seq_map_inline:Nn \l_datatool_tmp_seq
  {
    \int_incr:N \l_datatool_count_int

```

Save previous datum information:

```

  \int_set_eq:NN
    \l_datatool_tmp_datatype_int
    \@dtl@datatype
  \tl_set_eq:NN
    \l_datatool_tmp_currency_tl
    \l_datatool_datum_currency_tl

```

Convert:

```

  \DTLconverttodecimal { ##1 } \l_datatool_resulta_tl

```

```

    \__datatool_update_datatype:
    \seq_put_right:No \l__datatool_tmpb_seq { \l__datatool_resulta_tl }
    \fp_add:Nn
      \l__datatool_total_fp
      { \l__datatool_resulta_tl }
  }
\int_if_zero:nTF { \l__datatool_count_int }
{
  \PackageWarning { datatool-base }
    { empty ~ list ~ ` #2 ' ~ found ~ in ~ aggregate ~ function }
  \tl_set_eq:NN #1 \DTLnumbernull
}
{
  \fp_set:Nn
    \l__datatool_mean_fp
    { \l__datatool_total_fp / \l__datatool_count_int }
  \fp_zero:N \l__datatool_tmpa_fp
  \seq_map_inline:Nn \l__datatool_tmpb_seq
    {
      \fp_set:Nn \l__datatool_tmpb_fp
        {
          ##1 - \l__datatool_mean_fp
        }
      \fp_add:Nn \l__datatool_tmpa_fp
        {
          \l__datatool_tmpb_fp * \l__datatool_tmpb_fp
        }
    }
  \fp_set:Nn \l__datatool_tmpa_fp
    { sqrt ( \l__datatool_tmpa_fp / \l__datatool_count_int ) }

  \tl_set:Ne
    \l__datatool_result_tl
    { \fp_use:N \l__datatool_tmpa_fp }
  \__datatool_assign_result:N #1
}
}
}

```

\DTLgsdforall{<cmd>}{<num list>}

\DTLgsdforall

Global version

```

\NewDocumentCommand \DTLgsdforall { m m }
{
  \DTLsdforall { \l__datatool_resultb_tl } { #2 }
  \tl_gset_eq:NN #1 \l__datatool_resultb_tl
}

```

`\DTLround`

`\DTLround{<cmd>}{<num>}{<num digits>}`

Sets *<cmd>* to *<num>* rounded to *<num digits>* digits after the decimal character.

```
\NewDocumentCommand \DTLround { m m m }
{
  \DTLconverttodecimal{#2} \l__datatool_result_tl
  \dtlround
  { \l__datatool_result_tl }
  { \l__datatool_result_tl }
  { #3 }
  \__datatool_assign_result:N #1
}
```

`\DTLground` Global version

```
\NewDocumentCommand \DTLground { m m m }
{
  \DTLround { \l__datatool_resulta_tl } { #2 } { #3 }
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl
}
```

`\DTLtrunc`

`\DTLtrunc{<cmd>}{<num>}{<num digits>}`

Sets *<cmd>* to *<num>* truncated to *<num digits>* digits after the decimal character.

```
\NewDocumentCommand \DTLtrunc { m m m }
{
  \DTLconverttodecimal { #2 } \l__datatool_result_tl
  \dtltrunc
  { \l__datatool_result_tl }
  { \l__datatool_result_tl }
  { #3 }
  \__datatool_assign_result:N #1
}
```

`\DTLgtrunc` Global version

```
\NewDocumentCommand \DTLgtrunc { m m m }
{
  \DTLtrunc{ \l__datatool_resulta_tl } {#2} {#3}
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl
}
```

`\DTLclip`

`\DTLclip{<cmd>}{<num>}`

Sets *<cmd>* to *<num>* with all unnecessary 0's removed.

```
\NewDocumentCommand \DTLclip { m m }
{
```

```

\DTLconverttodecimal{#2} \l__datatool_result_tl
\dtlclip
  { \l__datatool_result_tl }
  { \l__datatool_result_tl }
\__datatool_assign_result:N #1
}

```

\DTLgclip Global version

```

\NewDocumentCommand \DTLgclip { m m }
{
  \DTLclip{ \l__datatool_resulta_tl } {#2}
  \tl_gset_eq:NN #1 \l__datatool_resulta_tl
}

```

2.6 String Macros

ntLocaleGetInitialLetter

```

\newcommand{\DTLCurrentLocaleGetInitialLetter}[2]{%
  \datatool_get_first_letter:nN { #1 } #2
}

\regex_new:N \l__datatool_initial_cs_regex
\regex_set:Nn \l__datatool_initial_cs_regex { \A \c{.+} \cB(.) }

```

\DTLGetInitialLetter Designed to obtain the first letter for initials or letter groups. This can't simply grab the first token as it may be a multi-byte character or may start with a command.

```

\NewDocumentCommand{\DTLGetInitialLetter} { m m }
{
  \bool_if:NTF \l__datatool_initial_purify_early_bool
  {
    \tl_if_head_is_group:nTF { #1 }
    {
      \tl_set:Nx #2 { \text_purify:n { \tl_head:n { #1 } } }
    }
    {
      \exp_args:Nx \__datatool_get_initial_letter:nN
      { \text_purify:n { #1 } } #2
    }
  }
  {
    \__datatool_get_initial_letter:nN { #1 } #2
  }
}
\cs_new:Nn \__datatool_get_initial_letter:nN
{
  \tl_if_blank:nTF { #1 }
  {
    \tl_clear:N #2
  }
}

```

```

{
  \tl_if_head_is_group:nTF { #1 }
  {
    \tl_set:Nx #2 { \tl_head:n { #1 } }
    \tl_set:Nx #2 { \text_purify:n { #2 } }
  }
  {
    \regex_match:NnTF \__datatool_initial_cs_regex { #1 }
    {
      \tl_set:Nx #2 { \tl_tail:n { #1 } }
      \exp_args:NNx \tl_set:Nx #2 { \exp_args:No \tl_head:n { #2 } }
      \exp_args:No \DTLCurrentLocaleGetInitialLetter { #2 } { #2 }
      \tl_set:Nx #2 { \tl_head:n { #1 } { \exp_not:o { #2 } } }
    }
    {
      \DTLCurrentLocaleGetInitialLetter { #1 } { #2 }
    }
  }
}
}
}

```

Get the first grapheme (which may be letter or punctuation):

```

\cs_new:Nn \datatool_get_first_grapheme:nN
{
  \tl_clear:N #2
  \exp_args:Nx \text_map_inline:nn { \text_purify:n { #1 } }
  {
    \tl_set:Nn #2 { ##1 }
    \text_map_break:
  }
}

```

Getting an initial letter but skipping leading punctuation is awkward because `[:alpha:]` only matches ASCII letters. Need to also allow for the fact that UTF-8 characters are actually an active character with one or more arguments with `inputenc` and it's also necessary to allow for control characters that are used to adjust sorting which have been given a letter character code.

So the following first tests if the category code is a letter (which will be the case for UTF-8 letters with $X_{\text{La}}\text{TeX}$ and LuaTeX but not with $\text{pdf}\text{La}\text{TeX}$). If not a letter category code, then the next part is a bit of a hack and is based on the assumption that all letters have a different upper and lower representation. The first argument should be a single grapheme (which may be a multi-byte character). It won't work if the first argument consists of a mixture of letters and non-letters.

```

\prg_new_conditional:Npnn \datatool_if_letter:n #1
{ T, F, TF }
{
  \tl_if_head_eq_catcode:nNTF { #1 } \c_catcode_letter_token
  { \prg_return_true: }
  {

```

```

        \exp_args:Nee \tl_if_eq:nnTF
        { \text_uppercase:n { #1 } } { \text_lowercase:n { #1 } }
        { \prg_return_false: }
        { \prg_return_true: }
    }
}

Get the first letter (skipping any preceding non-letters).
\cs_new:Nn \datatool_get_first_letter:nN
{
  \tl_clear:N #2
  \exp_args:Nx \text_map_inline:nn { \text_purify:n { #1 } }
  {
    \datatool_if_letter:nT { ##1 }
    {
      \tl_set:Nn #2 { ##1 }
      \text_map_break:
    }
  }
}

Convert a string into a sequence of words. NB [:alpha:] only matches ASCII
letters (see above). Multi-byte characters match [:punct:].
\regex_new:N \l_datatool_word_head_regex
\regex_set:Nn \l_datatool_word_head_regex
{
  ([[[:punct:]][:digit:]]*)
  ([^[:punct:]][:digit:]][:space:]\~+?)
  ([[[:punct:]][:digit:]]*)
  ((?[:[:space:]]\~|\c{protect}? \c{(? :nobreak)?space\ ?})+)
}
\regex_set:Nn \l_datatool_word_hyphen_regex
{
  ([[[:punct:]][:digit:]]*)
  ([^[:punct:]][:digit:]][:space:]\~+?)
  ([[[:punct:]][:digit:]]*)
  -{1}
}
\regex_set:Nn \l_datatool_word_apos_regex
{
  ([[[:punct:]][:digit:]]*)
  ([^[:punct:]][:digit:]][:space:]\~+)
  \ur{l_datatool_apos_regex}
  (
    [^[:punct:]][:digit:]][:space:]\~+
    (? \ur{l_datatool_apos_regex} [^[:punct:]][:digit:]][:space:]\~+)*
  )
  ([[[:punct:]][:digit:]]*)
  ((?[:[:space:]]\~|\c{protect}? \c{(? :nobreak)?space\ ?})+)
}

```

```

\regex_set:Nn \l_datatool_word_apos_hyphen_regex
{
  ([[[:punct:]][:digit:]]*)
  ([^[:punct:]][:digit:][:space:]\~)+
  \ur{l_datatool_apos_regex}
  (
    [^[:punct:]][:digit:][:space:]\~)+
    (?:\ur{l_datatool_apos_regex}[^[:punct:]][:digit:][:space:]\~)+*
  )
  ([[[:punct:]][:digit:]]*)
  -{1}
}
\regex_set:Nn \l_datatool_word_apos_tail_regex
{
  ([[[:punct:]][:digit:]]*)
  ([^[:punct:]][:digit:][:space:]\~)+
  \ur{l_datatool_apos_regex}
  (
    [^[:punct:]][:digit:][:space:]\~)+
    (?:\ur{l_datatool_apos_regex}[^[:punct:]][:digit:][:space:]\~)+*
  )
  ([[[:punct:]][:digit:]]*)
  \Z
}
\regex_set:Nn \l_datatool_word_tail_regex
{
  ([[[:punct:]][:digit:]]*)
  ([^[:punct:]][:digit:][:space:]\~)+
  ([[[:punct:]][:digit:]]*)
  \Z
}
\regex_set:Nn \l_datatool_symbols_regex
{
  ((?![!-@\[\]\^_\`{\|\}]|c{[[:alpha:]][:punct:]]+})+)?
  ((?[:space:]\-\~)|c{(?:nobreak)?space})+
}
\regex_set:Nn \l_datatool_other_regex
{
  (.+?)
  ((?[:space:]\-\~)|c{(?:nobreak)?space})+
}
\cs_new:Nn \__datatool_leading_punc:n { \exp_not:n { #1 } }
\cs_new:Nn \__datatool_trailing_punc:n { \exp_not:n { #1 } }
\cs_new:Nn \__datatool_word:n { \exp_not:n { #1 } }
\cs_new:Nn \__datatool_word_hyphen:n { \exp_not:n { #1 } }
\cs_new:Nn \__datatool_word_apos:nn { \exp_not:n { #1 } ' \exp_not:n { #2 } }
\cs_new:Nn \__datatool_word_apos_hyphen:nn { \exp_not:n { #1 } ' \exp_not:n { #2 } }
\cs_new:Nn \__datatool_last_word_apos:nn { \exp_not:n { #1 } ' \exp_not:n { #2 } }
\cs_new:Nn \__datatool_last_word:n { \exp_not:n { #1 } }
\cs_new:Nn \__datatool_word_sep:n { \exp_not:n { #1 } }

```

```

\cs_new:Nn \__datatool_hyphen_sep: { - }
\cs_new:Nn \__datatool_symbol:n { \exp_not:n { #1 } }
\cs_new:Nn \datatool_parse_words:N
{
  \exp_args:NNo \datatool_parse_words:Nn #1 { #1 }
}
\cs_new:Nn \datatool_parse_words:Nn
{
  \tl_set:Nx #1 { \tl_trim_spaces:n { #2 } }
  \regex_replace_case_all:nN
  {
    \l_datatool_word_head_regex
    {
      \c{__datatool_leading_punc:n}{\1}
      \c{__datatool_word:n}{\2}
      \c{__datatool_trailing_punc:n}{\3}
      \c{__datatool_word_sep:n}{\4}
    }
    \l_datatool_word_apos_hyphen_regex
    {
      \c{__datatool_leading_punc:n}{\1}
      \c{__datatool_word_apos_hyphen:nn}{\2}{\3}
      \c{__datatool_trailing_punc:n}{\4}
      \c{__datatool_hyphen_sep:n}
    }
    \l_datatool_word_hyphen_regex
    {
      \c{__datatool_leading_punc:n}{\1}
      \c{__datatool_word_hyphen:n}{\2}
      \c{__datatool_trailing_punc:n}{\3}
      \c{__datatool_hyphen_sep:n}
    }
    \l_datatool_word_apos_regex
    {
      \c{__datatool_leading_punc:n}{\1}
      \c{__datatool_word_apos:nn}{\2}{\3}
      \c{__datatool_trailing_punc:n}{\4}
      \c{__datatool_word_sep:n}{\5}
    }
    \l_datatool_word_apos_tail_regex
    {
      \c{__datatool_leading_punc:n}{\1}
      \c{__datatool_last_word_apos:nn}{\2}{\3}
      \c{__datatool_trailing_punc:n}{\4}
    }
    \l_datatool_word_tail_regex
    {
      \c{__datatool_leading_punc:n}{\1}
      \c{__datatool_last_word:n}{\2}
      \c{__datatool_trailing_punc:n}{\3}
    }
  }
}

```

```

    }
    \l_datatool_symbols_regex
    {
      \c{__datatool_symbol:n}{\1}
      \c{__datatool_word_sep:n}{\4}
    }
    \l_datatool_other_regex
    {
      \c{__datatool_symbol:n}{\1}
      \c{__datatool_word_sep:n}{\4}
    }
  }
  #1
}

```

\DTLinitials

`\DTLinitials{<string>}`

Convert a string into initials. (Any ~ character found is first converted into a space.) As from v3.0 this just uses \DTLstoreinitials with a temporary command. The extra grouping probably isn't necessary.

```

\NewDocumentCommand \DTLinitials { m }
{
  \group_begin:
  \DTLstoreinitials { #1 } { \l__datatool_tmpb_tl }
  \l__datatool_tmpb_tl
  \group_end:
}

```

\xDTLinitials

`\xDTLinitials{<cmd>}`

```

\NewDocumentCommand \xDTLinitials { m }
{
  \exp_args:No \DTLinitials { #1 }
}

```

\DTLstoreinitials

`\DTLstoreinitials{<string>}{<cmd>}`

Convert a string into initials and store in <cmd>. (Any ~ character found is first converted into a space.)

```

\NewDocumentCommand \DTLstoreinitials { m m }
{
  \tl_clear:N #2
  \tl_if_empty:nF { #1 }
}

```

```

{
  \datatool_parse_words:Nn \l__datatool_tmpa_tl { #1 }
  \tl_put_right:Nn \l__datatool_tmpa_tl { \q_recursion_tail }
  \__datatool_store_initials:N #2
  \q_recursion_stop
}
}
\cs_new:Nn \__datatool_store_initials:N
{
  \tl_set:Nx \l__datatool_tmp_initial_tl { \tl_head:N \l__datatool_tmpa_tl }
  \tl_set:Nx \l__datatool_tmpa_tl { \tl_tail:N \l__datatool_tmpa_tl }
  \tl_if_eq:NnTF
  \l__datatool_tmp_initial_tl { \__datatool_word:n }
  {
    \tl_set:Nx \l__datatool_tmp_initial_tl { \tl_head:N \l__datatool_tmpa_tl }
    \tl_set:Nx \l__datatool_tmpa_tl { \tl_tail:N \l__datatool_tmpa_tl }
    \exp_args:No \DTLStoreInitialGetLetter
    { \l__datatool_tmp_initial_tl } \l__datatool_tmp_initial_tl
    \tl_if_empty:NF \l__datatool_tmp_initial_tl
    {
      \tl_put_right:Nn #1 { \DTLinitialpunc }
      \tl_put_right:Nx #1 { { \l__datatool_tmp_initial_tl } }
      \tl_put_right:Nn #1 { { \DTLbetweeninitials } }
    }
  }
}
{
  \tl_if_eq:NnTF
  \l__datatool_tmp_initial_tl { \__datatool_last_word:n }
  {
    \tl_set:Nx \l__datatool_tmp_initial_tl { \tl_head:N \l__datatool_tmpa_tl }
    \tl_set:Nx \l__datatool_tmpa_tl { \tl_tail:N \l__datatool_tmpa_tl }
    \exp_args:No \DTLStoreInitialGetLetter
    { \l__datatool_tmp_initial_tl } \l__datatool_tmp_initial_tl
    \tl_if_empty:NF \l__datatool_tmp_initial_tl
    {
      \tl_put_right:Nn #1 { \DTLinitialpunc }
      \tl_put_right:Nx #1 { { \l__datatool_tmp_initial_tl } }
      \tl_put_right:Nn #1 { { \DTLafterinitials } }
    }
  }
}
{
  \tl_if_eq:NnTF
  \l__datatool_tmp_initial_tl { \__datatool_word_hyphen:n }
  {
    \tl_set:Nx \l__datatool_tmp_initial_tl { \tl_head:N \l__datatool_tmpa_tl }
    \tl_set:Nx \l__datatool_tmpa_tl { \tl_tail:N \l__datatool_tmpa_tl }
    \exp_args:No \DTLStoreInitialGetLetter
    { \l__datatool_tmp_initial_tl } \l__datatool_tmp_initial_tl
    \tl_if_empty:NF \l__datatool_tmp_initial_tl
    {

```

```

\l_datatool_tmp_initial_tl { \l_datatool_word_apos:nn }
{
\l_if_eq:NnTF
\l_datatool_tmp_initial_tl { \l_datatool_word_apos:nn }
{
\l_set:Nx \l_datatool_tmp_initial_tl { \tl_head:N \l_datatool_tmpa_tl
\l_set:Nx \l_datatool_tmpa_tl { \tl_tail:N \l_datatool_tmpa_tl }
\exp_args:No \DTLStoreInitialGetLetter
{ \l_datatool_tmp_initial_tl } \l_datatool_tmp_initial_tl
\l_if_empty:NTF \l_datatool_tmp_initial_tl
{
\l_set:Nx \l_datatool_tmp_initial_tl { \tl_head:N \l_datatool_tmpa_
\l_set:Nx \l_datatool_tmpa_tl { \tl_tail:N \l_datatool_tmpa_tl }
\exp_args:No \DTLStoreInitialGetLetter
{ \l_datatool_tmp_initial_tl } \l_datatool_tmp_initial_tl
\l_if_empty:NF \l_datatool_tmp_initial_tl
{
\l_put_right:Nn #1 { \DTLinitialpunc }
\l_put_right:Nx #1 { { \l_datatool_tmp_initial_tl } }
\l_put_right:Nn #1 { { \DTLbetweeninitials } }
}
}
}
\l_put_right:Nn #1 { \DTLaposinitialpunc }
\l_put_right:Nx #1 { { \l_datatool_tmp_initial_tl } }
\l_set:Nx \l_datatool_tmp_initial_tl { \tl_head:N \l_datatool_tmpa_
\l_set:Nx \l_datatool_tmpa_tl { \tl_tail:N \l_datatool_tmpa_tl }
\exp_args:No \DTLStoreInitialGetLetter
{ \l_datatool_tmp_initial_tl } \l_datatool_tmp_initial_tl
\l_put_right:Nx #1 { { \l_datatool_tmp_initial_tl } }
\l_put_right:Nn #1 { { \DTLbetweeninitials } }
}
}
}
\l_if_eq:NnTF
\l_datatool_tmp_initial_tl { \l_datatool_word_apos_hyphen:nn }
{
\l_set:Nx \l_datatool_tmp_initial_tl { \tl_head:N \l_datatool_tmpa_
\l_set:Nx \l_datatool_tmpa_tl { \tl_tail:N \l_datatool_tmpa_tl }
\exp_args:No \DTLStoreInitialGetLetter
{ \l_datatool_tmp_initial_tl } \l_datatool_tmp_initial_tl
\l_if_empty:NTF \l_datatool_tmp_initial_tl
{
\l_set:Nx \l_datatool_tmp_initial_tl
{ \tl_head:N \l_datatool_tmpa_tl }
}
}
}

```

```

\tl_set:Nx \l_datatool_tmpa_tl
  { \tl_tail:N \l_datatool_tmpa_tl }
\exp_args:No \DTLStoreInitialGetLetter
  { \l_datatool_tmp_initial_tl } \l_datatool_tmp_initial_tl
\tl_if_empty:NF \l_datatool_tmp_initial_tl
  {
    \tl_put_right:Nn #1 { \DTLinitialpunc }
    \tl_put_right:Nx #1 { { \l_datatool_tmp_initial_tl } }
    \tl_put_right:Nn #1 { { \DTLafterinitialbeforehyphen } }
    \tl_put_right:Nn #1 { \DTLinitialhyphen }
  }
}
{
\tl_put_right:Nn #1 { \DTLaposinitialpunc }
\tl_put_right:Nx #1 { { \l_datatool_tmp_initial_tl } }
\tl_set:Nx \l_datatool_tmp_initial_tl
  { \tl_head:N \l_datatool_tmpa_tl }
\tl_set:Nx \l_datatool_tmpa_tl
  { \tl_tail:N \l_datatool_tmpa_tl }
\exp_args:No \DTLStoreInitialGetLetter
  { \l_datatool_tmp_initial_tl } \l_datatool_tmp_initial_tl
\tl_put_right:Nx #1 { { \l_datatool_tmp_initial_tl } }
\tl_put_right:Nn #1 { { \DTLafterinitialbeforehyphen } }
\tl_put_right:Nn #1 { \DTLinitialhyphen }
}
}
{
\tl_if_eq:NnT
  \l_datatool_tmp_initial_tl { \__datatool_last_word_apos:nn }
  {
    \tl_set:Nx \l_datatool_tmp_initial_tl
      { \tl_head:N \l_datatool_tmpa_tl }
    \tl_set:Nx \l_datatool_tmpa_tl
      { \tl_tail:N \l_datatool_tmpa_tl }
    \exp_args:No \DTLStoreInitialGetLetter
      { \l_datatool_tmp_initial_tl } \l_datatool_tmp_initial_tl
    \tl_if_empty:NTF \l_datatool_tmp_initial_tl
      {
        \tl_set:Nx \l_datatool_tmp_initial_tl
          { \tl_head:N \l_datatool_tmpa_tl }
        \tl_set:Nx \l_datatool_tmpa_tl
          { \tl_tail:N \l_datatool_tmpa_tl }
        \exp_args:No \DTLStoreInitialGetLetter
          { \l_datatool_tmp_initial_tl } \l_datatool_tmp_initial_tl
        \tl_if_empty:NF \l_datatool_tmp_initial_tl
          {
            \tl_put_right:Nn #1 { \DTLinitialpunc }
            \tl_put_right:Nx #1 { { \l_datatool_tmp_initial_tl } }
            \tl_put_right:Nn #1 { { \DTLafterinitials } }
          }
      }
  }
}

```

```

}
{
  \tl_put_right:Nn #1 { \DTLaposinitialpunc }
  \tl_put_right:Nx #1 { { \l_datatool_tmp_initial_tl } }
  \tl_set:Nx \l_datatool_tmp_initial_tl
    { \tl_head:N \l_datatool_tmpa_tl }
  \tl_set:Nx \l_datatool_tmpa_tl
    { \tl_tail:N \l_datatool_tmpa_tl }
  \exp_args:No \DTLStoreInitialGetLetter
    { \l_datatool_tmp_initial_tl } \l_datatool_tmp_initial_tl
  \tl_put_right:Nx #1 { { \l_datatool_tmp_initial_tl } }
  \tl_put_right:Nn #1 { { \DTLafterinitials } }
}
}
}
}
}
}
}
}
\quark_if_recursion_tail_stop:N \l_datatool_tmpa_tl
\_datatool_store_initials:N #1
}

```

DTLStoreInitialGetLetter

```
\newcommand{\DTLStoreInitialGetLetter}[2]{\DTLGetInitialLetter{#1}{#2}}
```

\DTLafterinitials Defines what to do after the final initial.

```
\newcommand*{\DTLafterinitials}{.}
```

\DTLbetweeninitials Defines what to do between initials.

```
\newcommand*{\DTLbetweeninitials}{.}
```

afterinitialbeforehyphen Defines what to do before a hyphen.

```
\newcommand*{\DTLafterinitialbeforehyphen}{.}
```

\DTLinitialhyphen Defines what to do at the hyphen

```
\newcommand*{\DTLinitialhyphen}{-}
```

\DTLinitialpunc

```
\newcommand{\DTLinitialpunc}[2]{#1#2}
```

\DTLaposinitialpunc

```
\newcommand{\DTLaposinitialpunc}[3]{#1#3}
```

```
\DTLifAllUpperCase{<string>}{<true part>}{<>false
part>}
```

\DTLifAllUpperCase

If *⟨string⟩* only contains uppercase characters do *⟨true part⟩*, otherwise do *⟨false part⟩*. This needs to take UTF-8 characters into account. NB regular expression `lower` and `upper` character classes doesn't match UTF-8 characters (regardless of the engine).

```
\newrobustcmd*{\DTLifAllUpperCase}[3]{%
  \tl_set:Nx \l__datatool_tmpa_tl { \text_purify:n { #1 } }
  \tl_set:Nx \l__datatool_tmpb_tl
    { \text_uppercase:n { \l__datatool_tmpa_tl } }
  \tl_if_eq:NNTF
    \l__datatool_tmpa_tl \l__datatool_tmpb_tl
    { #2 } { #3 }
}
```

`\DTLifAllLowerCase{⟨string⟩}{⟨true part⟩}{⟨false part⟩}`

`\DTLifAllLowerCase`

If *⟨string⟩* only contains lowercase characters do *⟨true part⟩*, otherwise do *⟨false part⟩*.

```
\newrobustcmd*{\DTLifAllLowerCase}[3]{%
  \tl_set:Nx \l__datatool_tmpa_tl { \text_purify:n { #1 } }
  \tl_set:Nx \l__datatool_tmpb_tl
    { \text_lowercase:n { \l__datatool_tmpa_tl } }
  \tl_if_eq:NNTF
    \l__datatool_tmpa_tl \l__datatool_tmpb_tl
    { #2 } { #3 }
}
```

`\DTLsubstitute{⟨cmd⟩}{⟨original⟩}{⟨replacement⟩}`

`\DTLsubstitute`

Substitutes first occurrence of *⟨original⟩* with *⟨replacement⟩* within the string given by *⟨cmd⟩*

```
\newrobustcmd{\DTLsubstitute}[3]{%
  \tl_replace_once:Nnn #1 { #2 } { #3 }
}
```

`\DTLsplitstring{⟨string⟩}{⟨split text⟩}{⟨before cmd⟩}{⟨after cmd⟩}`

`\DTLsplitstring`

Splits string at *⟨split text⟩* stores the pre split text in *⟨before cmd⟩* and the post split text in *⟨after cmd⟩*.

```
\newrobustcmd*{\DTLsplitstring}[4]{%
  \def\dtl@splitstr##1#2##2\@nil{%
    \def#3{##1}%
    \def#4{##2}%
    \ifdefempty{#4}%

```

```

    {%
      \let\@dtl@replaced=\@empty
    }%
    {%
      \def\@dtl@replaced{#2}%
      \dtl@split@str##2\@nil
    }%
  }%
  \def\dtl@split@str##1#2\@nil{\def#4{##1}}%
  \dtl@splitstr#1#2\@nil
}

```

```

\DTLxsplitstring{<string>}{<split text>}{<before
cmd>}{<after cmd>}

```

\DTLxsplitstring

As above but expands the first two arguments

```

\newrobustcmd*{\DTLxsplitstring}[2]{%
  \exp_args:Noo \DTLsplitstring { #1 } { #2 }
}

```

```

\DTLsubstituteall{<cmd>}{<original>}{<replacement>}

```

\DTLsubstituteall

Substitutes all occurrences of *<original>* with *{<replacement>}* within the string given by *<cmd>*

```

\newrobustcmd{\DTLsubstituteall}[3]{%
  \tl_replace_all:Nnn #1 { #2 } { #3 }
}

```

2.7 Conditionals

\if@dtl@condition

```

\newif\if@dtl@condition

```

2.7.1 Testing for a prefix

The following are used when splitting content.

```

\tl_new:N \l__datatool_prefix_tl
\tl_new:N \l__datatool_suffix_tl

```

Use to store the length:

```

\int_new:N \l__datatool_prefix_int
\int_new:N \l__datatool_suffix_int

```

Used to test for currency symbol at either end, but consider the symbol the ‘prefix’ and the rest the ‘suffix’ regardless of which way round they are. The first argument is the token list the second is the possible prefix or suffix.

```

\prg_new_conditional:Npnn \__datatool_if_starts_or_ends_with:nn #1 #2
{ T, F, TF}
{
  \tl_clear:N \l__datatool_prefix_tl
  \tl_clear:N \l__datatool_suffix_tl
  \tl_if_eq:nnTF { #1 } { #2 }
  {
    \tl_set:Nn \l__datatool_prefix_tl { #2 }
    \prg_return_true:
  }
  {
    \int_set:Nn \l__datatool_prefix_int { \tl_count:n { #2 } }
    \int_set:Nn \l__datatool_suffix_int { \tl_count:n { #1 } }
    \int_compare:nNnTF { \l__datatool_suffix_int } > { \l__datatool_prefix_int }
    {
      \tl_if_eq:enTF
      { \tl_range:nnn { #1 } { \c_one_int } { \l__datatool_prefix_int } }
      { #2 }
      {
        \tl_set:Nn \l__datatool_prefix_tl { #2 }
        \tl_set:Ne \l__datatool_suffix_tl
        {
          \tl_range:nnn { #1 }
          { \l__datatool_prefix_int + \c_one_int }
          { \l__datatool_suffix_int }
        }
      }
      \prg_return_true:
    }
    {
      \int_sub:Nn \l__datatool_suffix_int { \l__datatool_prefix_int }
      \tl_if_eq:enTF
      {
        \tl_range:nnn { #1 }
        { \l__datatool_suffix_int + \c_one_int }
        { - \c_one_int }
      }
      { #2 }
      {
        \tl_set:Nn \l__datatool_prefix_tl { #2 }
        \tl_set:Ne \l__datatool_suffix_tl
        {
          \tl_range:nnn { #1 }
          { \c_one_int }
          { \l__datatool_suffix_int }
        }
      }
      \prg_return_true:
    }
  }
  \prg_return_false:
}

```

```

    }
  }
  {
    \prg_return_false:
  }
}
}
\cs_generate_variant:Nn \__datatool_if_starts_or_ends_with:nnTF
{ VvTF , VeTF, VnTF }

```

The following tests if the token list in the first argument starts with the tokens in the second argument (without taking the category code into account). If true, the prefix token list will contain the tokens in the second argument (the prefix) and the suffix token list will contain the remaining tokens. If false the prefix token list will be empty and the suffix will contain all the tokens in the first argument.

```

\cs_new:Nn \__datatool_if_starts_with:NnTF
{
  \exp_args:NV \__datatool_if_starts_with:nnTF #1 { #2 } { #3 } { #4 }
}
\cs_new:Nn \__datatool_if_starts_with:nnTF
{

```

Initialise the prefix to an empty list and the suffix to the token list under examination.

```

  \tl_clear:N \l__datatool_prefix_tl
  \tl_set:Nn \l__datatool_suffix_tl { #1 }
  \tl_set:Nn \l__datatool_tmpa_tl { #1 \q_recursion_tail }
  \tl_set:Nn \l__datatool_tmpb_tl { #2 \q_recursion_tail }
  \__datatool_if_starts_with:
  \q_recursion_stop
  \__datatool_result:nn { #3 } { #4 }
}
\cs_new:Nn \__datatool_if_starts_with:
{
  \exp_args:No \tl_if_head_is_space:nTF { \l__datatool_tmpa_tl }
  {
    \tl_set:Nn \l__datatool_tmpc_tl { ~ }
    \tl_set:Nx \l__datatool_tmpa_tl
      { \tl_head:N \l__datatool_tmpa_tl \tl_tail:N \l__datatool_tmpa_tl }
  }
  {
    \tl_set:Nx \l__datatool_tmpc_tl
      { \tl_head:N \l__datatool_tmpa_tl }
    \tl_set:Nx \l__datatool_tmpa_tl
      { \tl_tail:N \l__datatool_tmpa_tl }
  }
  \exp_args:No \tl_if_head_is_space:nTF { \l__datatool_tmpb_tl }
  {
    \tl_set:Nn \l__datatool_tmpd_tl { ~ }
    \tl_set:Nx \l__datatool_tmpb_tl
      { \tl_head:N \l__datatool_tmpb_tl \tl_tail:N \l__datatool_tmpb_tl }
  }
}

```

```

{
  \tl_set:Nx \l__datatool_tmpd_tl
    { \tl_head:N \l__datatool_tmpb_tl }
  \tl_set:Nx \l__datatool_tmpb_tl
    { \tl_tail:N \l__datatool_tmpb_tl }
}
\cs_set:Nn \__datatool_next: { }
\if_meaning:w \q_recursion_tail \l__datatool_tmpd_tl
  \cs_set_eq:NN \__datatool_next: \__datatool_starts_with_true:
\else
  \if_meaning:w \q_recursion_tail \l__datatool_tmpc_tl
    \cs_set_eq:NN \__datatool_next: \__datatool_starts_with_false:
  \else
    \str_if_eq:NNTF \l__datatool_tmpc_tl \l__datatool_tmpd_tl
      {
        \tl_put_right:No \l__datatool_prefix_tl { \l__datatool_tmpd_tl }
      }
      {
        \cs_set_eq:NN \__datatool_next: \__datatool_starts_with_false:
      }
    \fi
  \fi
  \__datatool_next:
  \__datatool_if_starts_with:
}
\cs_new:Nn \__datatool_starts_with_false:
{
  \cs_set:Nn \__datatool_result:nn { ##2 }
  \tl_clear:N \l__datatool_prefix_tl
  \use_none_delimit_by_q_recursion_stop:w
}
\cs_new:Nn \__datatool_starts_with_true:
{
  \cs_set:Nn \__datatool_result:nn { ##1 }
  \if_meaning:w \q_recursion_tail \l__datatool_tmpc_tl
    \tl_clear:N \l__datatool_suffix_tl
  \else
    \tl_set_eq:NN \l__datatool_suffix_tl \l__datatool_tmpc_tl
    \exp_after:wN \__datatool_suffix_tail:w \l__datatool_tmpa_tl
  \fi
  \use_none_delimit_by_q_recursion_stop:w
}
\cs_new:Npn \__datatool_suffix_tail:w #1\q_recursion_tail
{
  \tl_put_right:Nn \l__datatool_suffix_tl { #1 }
}
\cs_new:Npn \__datatool_if_starts_with:NnT #1#2#3
{
  \__datatool_if_starts_with:NnTF #1 { #2 } { #3 } { }
}

```

Retain original internal command for checking if an argument is numerical but updated to use new parsing.

```
\@dtl@checknumerical{<arg>}
```

\@dtl@checknumerical

Checks if *<arg>* is numerical (includes decimal numbers, but not scientific notation.) Sets \@dtl@datatype.

```
\newcommand{\@dtl@checknumerical}[1]{%
  \tl_if_single_token:nTF { #1 }
  { \exp_args:No \__datatool_parse_datum:n { #1 } }
  { \__datatool_parse_datum:n { #1 } }
}
```

```
\DTLifnumerical{<arg>}{<true part>}{<false part>}
```

\DTLifnumerical

Tests the first argument, if it's numerical do second argument, otherwise do third argument.

```
\newrobustcmd{\DTLifnumerical}[3]{%
  \@dtl@checknumerical { #1 }
  \datatool_if_numeric_datum_type:nTF { \@dtl@datatype }
  { #2 } { #3 }
}
```

```
\DTLiftemporal{<arg>}{<true part>}{<false part>}
```

\DTLiftemporal

Tests the first argument, if it's temporal do second argument, otherwise do third argument.

```
\NewDocumentCommand \DTLiftemporal { m m m }
{
  \tl_if_single_token:nTF { #1 }
  { \exp_args:No \__datatool_parse_datum:n { #1 } }
  { \__datatool_parse_datum:n { #1 } }
  \datatool_if_temporal_datum_type:nTF { \@dtl@datatype }
  { #2 } { #3 }
}
```

```
\dtl@testbothnumerical{<arg1>}{<arg2>}
```

\dtl@testbothnumerical

Tests if both arguments are numerical. This sets the conditional \@dtl@condition.

```
\newcommand*{\dtl@testbothnumerical}[2]{%
  \DTLifnumerical { #1 }
  {
    \DTLifnumerical { #2 } { \@dtl@conditiontrue } { \@dtl@conditionfalse }
  }
}
```

```

    { \@dtl@conditionfalse }
}

```

\DTLifreal

`\DTLifreal{<arg>}{<true part>}{<false part>}`

Tests the first argument, if it's a real number (not an integer or currency) do second argument, otherwise do third argument.

```

\newrobustcmd{\DTLifreal}[3]{%
  \tl_if_single_token:nTF { #1 }
  { \exp_args:No \__datatool_parse_datum:n { #1 } }
  { \__datatool_parse_datum:n { #1 } }
  \int_compare:nNnTF { \@dtl@datatype } = { \c_datatool_decimal_int }
  { #2 } { #3 }
}

```

\DTLifint

`\DTLifint{<arg>}{<true part>}{<false part>}`

Tests the first argument, if it's an integer do second argument, otherwise do third argument.

```

\newrobustcmd{\DTLifint}[3]{%
  \tl_if_single_token:nTF { #1 }
  { \exp_args:No \__datatool_parse_datum:n { #1 } }
  { \__datatool_parse_datum:n { #1 } }
  \int_compare:nNnTF { \@dtl@datatype } = { \c_datatool_integer_int }
  { #2 } { #3 }
}

```

\DTLifdatetime

`\DTLifdatetime{<arg>}{<true part>}{<false part>}`

Tests the first argument, if it's a timestamp (date and time) do second argument, otherwise do third argument.

```

\NewDocumentCommand \DTLiftimestamp { m m m }
{
  \tl_if_single_token:nTF { #1 }
  { \exp_args:No \__datatool_parse_datum:n { #1 } }
  { \__datatool_parse_datum:n { #1 } }
  \int_compare:nNnTF { \@dtl@datatype } = { \c_datatool_datetime_int }
  { #2 } { #3 }
}

```

\DTLifdate

`\DTLifdate{<arg>}{<true part>}{<false part>}`

Tests the first argument, if it's a date (no time) do second argument, otherwise do third argument.

```
\NewDocumentCommand \DTLifdate { m m m }
{
  \tl_if_single_token:nTF { #1 }
  { \exp_args:No \__datatool_parse_datum:n { #1 } }
  { \__datatool_parse_datum:n { #1 }}
  \int_compare:nNnTF { \@dtl@datatype } = { \c_datatool_date_int }
  { #2 } { #3 }
}
```

`\DTLiftime{<arg>}{<true part>}{<false part>}`

\DTLiftime

Tests the first argument, if it's a time (no date) do second argument, otherwise do third argument.

```
\NewDocumentCommand \DTLiftime { m m m }
{
  \tl_if_single_token:nTF { #1 }
  { \exp_args:No \__datatool_parse_datum:n { #1 } }
  { \__datatool_parse_datum:n { #1 }}
  \int_compare:nNnTF { \@dtl@datatype } = { \c_datatool_time_int }
  { #2 } { #3 }
}
```

`\DTLifstring{<arg>}{<true part>}{<false part>}`

\DTLifstring

Tests the first argument, if it's a string do second argument, otherwise do third argument.

```
\newrobustcmd{\DTLifstring}[3]{%
  \tl_if_single_token:nTF { #1 }
  { \exp_args:No \__datatool_parse_datum:n { #1 } }
  { \__datatool_parse_datum:n { #1 }}
  \int_compare:nNnTF { \@dtl@datatype } = { \c_datatool_string_int }
  { #2 } { #3 }
}
```

`\DTLifcurrency{<arg>}{<true part>}{<false part>}`

\DTLifcurrency

Tests the first argument, if it's currency do second argument, otherwise do third argument.

```
\newrobustcmd{\DTLifcurrency}[3]{%
  \tl_if_single_token:nTF { #1 }
  { \exp_args:No \__datatool_parse_datum:n { #1 } }
  { \__datatool_parse_datum:n { #1 }}
}
```

```

\int_compare:nNnTF { \@dtl@datatype } = { \c_datatool_currency_int }
{ #2 } { #3 }
}

```

`\DTLifcurrencyunit{<arg>}{<symbol>}{<true part>}{<false part>}`

`\DTLifcurrencyunit`

This tests if `<arg>` is currency, and uses the currency unit `<symbol>`. If true do third argument, otherwise do fourth argument.

```

\newrobustcmd*\DTLifcurrencyunit[4]{%
\tl_if_single_token:nTF { #1 }
{ \exp_args:No \__datatool_parse_datum:n { #1 } }
{ \__datatool_parse_datum:n { #1 } }
\ifnum\@dtl@datatype=\c_datatool_currency_int
\tl_if_eq:NnTF \l_datatool_datum_currency_tl { #2 }
{ #3 }
{
\tl_if_eq:NnTF \l_datatool_datum_currency_tl { \@dtl@currency }
{
\tl_if_eq:NnTF \@dtl@currency { #2 }
{ #3 }
{ #4 }
}
}
{ #4 }
}
\else
#4
\fi
}

```

`\DTLifcasedatatype{<arg>}{<string case>}{<int case>}{<real case>}{<currency case>}`

`\DTLifcasedatatype`

If `<arg>` is a string, do `<string case>`, if `<arg>` is an integer do `<int case>`, if `<arg>` is a real number, do `<real case>`, if `<arg>` is currency, do `<currency case>`. Does nothing with other cases (unknown, or any data types introduced in new versions, such as date/time).

Deprecated as it doesn't allow for new types. Note that it's more efficient to convert to a datum variable first and use `\int_case:nn` on the datum type (which can be obtained with `\DTLdatumtype`).

```

\newrobustcmd*\DTLifcasedatatype[5]{%
\tl_if_single_token:nTF { #1 }
{ \exp_args:No \__datatool_parse_datum:n { #1 } }
{ \__datatool_parse_datum:n { #1 } }
\ifcase\@dtl@datatype
#2% string
\or

```

```

    #3% integer
  \or
    #4% number
  \or
    #5% currency
  \fi
}

```

2.7.2 Locale Numerical Comparisons

Parse two numerical values for comparison. Any non-numeric value will be treated as zero.

```

\cs_new:Nn \__datatool_parse_numbers_ii:nnNN
{
  \tl_if_single_token:nTF { #1 }
  { \exp_args:No \__datatool_parse_datum:n { #1 } }
  { \__datatool_parse_datum:n { #1 } }
  \ifnum\@dtl@datatype > \c_datatool_string_int
    \tl_set_eq:NN #3 \l__datatool_datum_value_tl
  \else
    \tl_set:Nn #3 { 0 }
  \fi
  \int_set_eq:NN \l__datatool_tmp_datatype_int \@dtl@datatype
  \tl_if_single_token:nTF { #2 }
  { \exp_args:No \__datatool_parse_datum:n { #2 } }
  { \__datatool_parse_datum:n { #2 } }
  \ifnum\@dtl@datatype > \c_datatool_string_int
    \tl_set_eq:NN #4 \l__datatool_datum_value_tl
  \else
    \tl_set:Nn #4 { 0 }
  \fi
}

```

Ensure that the dominant data type can be picked up afterwards.

```

\int_compare:nNnT
{ \l__datatool_tmp_datatype_int } > { \@dtl@datatype }
{
  \int_set_eq:NN \@dtl@datatype \l__datatool_tmp_datatype_int
}
}

```

Parse three numerical values.

```

\cs_new:Nn \__datatool_parse_numbers_iii:nnnNNN
{
  \__datatool_parse_numbers_ii:nnNN { #1 } { #2 } #4 #5
  \tl_if_single_token:nTF { #3 }
  { \exp_args:No \__datatool_parse_datum:n { #3 } }
  { \__datatool_parse_datum:n { #3 } }
  \ifnum\@dtl@datatype > \c_datatool_string_int
    \tl_set_eq:NN #6 \l__datatool_datum_value_tl
  \else

```

```

\l_set:Nn #6 { 0 }
\fi
}

```

\DTLifnumlt

`\DTLifnumlt{<num1>}{<num2>}{<true part>}{<false part>}`

Determines if $\langle num1 \rangle < \langle num2 \rangle$. The numeric values need to be obtained to ensure that they work with `\dtlifnumlt`.

```

\newrobustcmd*{\DTLifnumlt}[4]{%
  \__datatool_parse_numbers_ii:nnNN { #1 } { #2 } \@dtl@numi \@dtl@numii
  \dtlifnumlt{\@dtl@numi}{\@dtl@numii} { #3 } { #4 }
}

```

\DTLifnumgt

`\DTLifnumgt{<num1>}{<num2>}{<true part>}{<false part>}`

Determines if $\langle num1 \rangle > \langle num2 \rangle$. The numeric values need to be obtained to ensure that they work with `\dtlifnumgt`.

```

\newrobustcmd*{\DTLifnumgt}[4]{%
  \__datatool_parse_numbers_ii:nnNN { #1 } { #2 } \@dtl@numi \@dtl@numii
  \dtlifnumgt{\@dtl@numi}{\@dtl@numii} { #3 } { #4 }
}

```

\DTLifnumeq

`\DTLifnumeq{<num1>}{<num2>}{<true part>}{<false part>}`

Determines if $\langle num1 \rangle = \langle num2 \rangle$. The numeric values need to be obtained to ensure that they work with `\dtlifnumeq`.

```

\newrobustcmd*{\DTLifnumeq}[4]{%
  \__datatool_parse_numbers_ii:nnNN { #1 } { #2 } \@dtl@numi \@dtl@numii
  \dtlifnumeq{\@dtl@numi}{\@dtl@numii} { #3 } { #4 }
}

```

\DTLifnumclosedbetween

`\DTLifnumclosedbetween{<num>}{<min>}{<max>}{<true part>}{<false part>}`

Determines if $\langle min \rangle \leq \langle num \rangle \leq \langle max \rangle$.

```

\newrobustcmd*{\DTLifnumclosedbetween}[5]{%
  \__datatool_parse_numbers_iii:nnNNN { #1 } { #2 } { #3 }
  \@dtl@numi \@dtl@numii \@dtl@numiii
  \DTLifFPclosedbetween{\@dtl@numi}{\@dtl@numii}{\@dtl@numiii}{#4}{#5}%
}

```

\DTLifnumopenbetween

`\DTLifnumopenbetween{<num>}{<min>}{<max>}{<true part>}{<false part>}`

Determines if $\langle min \rangle < \langle num \rangle < \langle max \rangle$.

```
\newrobustcmd*{\DTLifnumopenbetween}[5]{%
  \__datatool_parse_numbers_iii:nnnNNN { #1 } { #2 } { #3 }
  \@dtl@numi \@dtl@numii \@dtl@numiii
  \DTLifFPopenbetween{\@dtl@numi}{\@dtl@numii}{\@dtl@numiii}{#4}{#5}%
}
```

\DTLnumcompare

`\DTLnumcompare<int var>{<num1>}{<num2>}`

```
\NewDocumentCommand \DTLnumcompare { m m m }
{
  \__datatool_parse_numbers_ii:nnNN { #2 } { #3 } \@dtl@numi \@dtl@numii
  \int_compare:nNnTF
    { \@dtl@datatype } < { \c_datatool_decimal_int }
  {
    \int_compare:nNnTF { \@dtl@numi } < { \@dtl@numii }
    { \int_set:Nn #1 { -1 } }
    {
      \int_compare:nNnTF { \@dtl@numi } > { \@dtl@numii }
      { \int_set_eq:NN #1 \c_one_int }
      { \int_zero:N #1 }
    }
  }
}
{
  \fp_compare:nNnTF { \@dtl@numi } < { \@dtl@numii }
  { \int_set:Nn #1 { -1 } }
  {
    \fp_compare:nNnTF { \@dtl@numi } > { \@dtl@numii }
    { \int_set_eq:NN #1 \c_one_int }
    { \int_zero:N #1 }
  }
}
}
```

2.7.3 String Comparisons

\dtlcompare

`\dtlcompare{<count>}{<string1>}{<string2>}`

Compares $\langle string1 \rangle$ and $\langle string2 \rangle$, and stores the result in the count register $\langle count \rangle$. The result may be one of:

- 1 if $\langle string1 \rangle$ is considered to be less than $\langle string2 \rangle$
- 0 if $\langle string1 \rangle$ is considered to be the same as $\langle string2 \rangle$
- 1 if $\langle string1 \rangle$ is considered to be greater than $\langle string2 \rangle$

Note that for the purposes of string comparisons, commands within $\langle string1 \rangle$ and $\langle string2 \rangle$ are ignored, except for `\space` and `~`, which are both treated as a space (character code 32.) The following examples assume that the count register `\mycount` has been defined as follows:

```
%\newcount\mycount
%
```

Examples:

1. `%\dtlcompare{\mycount}{Z"oe}{Zoe}\number\mycount`
`%`
 produces: -1, since the accent command is ignored.
2. `%\dtlcompare{\mycount}{foo}{Foo}\number\mycount`
`%`
 produces: 1, since the comparison is case sensitive, however, note the following example:
3. `%\dtlcompare{\mycount}{foo}{\uppercase{f}oo}\number\mycount`
`%`

which produces: 1, since the `\uppercase` command is ignored.

4. A control sequence is treated as having the character code value of 0. Pre version 2.32, `\dtlcompare` was advertised here as skipping control sequences when actually it was treating a control sequence as character 0. To avoid breaking backward-compatibility where a control sequence is expected to have this behaviour, we now have a switch to determine whether to treat control sequences as 0 or to skip them.

So you can now “trick” `\dtlcompare` using a command which doesn’t output any text if switch this conditional on. Suppose you have defined the following command:

```
%\newcommand*\noopsort}[1]{}
```

then `\noopsort{a}foo` produces the text: foo, however the following

```
%\dtlcompare{\mycount}{\noopsort{a}foo}{bar}\number\mycount
%
```

produces: -1, since the command `\noopsort` is disregarded when the comparison is made, so `\dtlcompare` just compares `{a}foo` with `bar`, and since `a` is less than `b`, the first string is considered to be less than the second string.

5. Note that this also means that:

```
%\def\mystr{abc}%  
\dtlcompare{\mycount}{\mystr}{abc}\number\mycount  
%
```

produces: -1, since the command `\mystr` is disregarded, which means that `\dtlcompare` is comparing an empty string with the string `abc`.

6. Spaces count in the comparison:

```
%\dtlcompare{\mycount}{ab cd}{abcd}\number\mycount  
%
```

produces: -1, but sequential spaces are treated as a single space:

```
%\dtlcompare{\mycount}{ab cd}{ab cd}\number\mycount  
%
```

produces: 0.

7. As usual, spaces following command names are ignored, so

```
%\dtlcompare{\mycount}{ab\relax cd}{ab cd}\number\mycount  
%
```

produces: -1.

8. `~` and `\space` are considered to be the same as a space:

```
%\dtlcompare{\mycount}{ab cd}{ab~cd}\number\mycount  
%
```

produces: 0.

To ensure backward-compatibility, this still needs to strip commands so that the `\noop` example can continue to work, but it's better to prepare the sort values first for sorting lists.

```
\newcommand*\dtlcompare}[3]{%  
  \__datatool_get_compare_sort:Nn \l__datatool_tmpa_str { #2 }  
  \__datatool_get_compare_sort:Nn \l__datatool_tmpb_str { #3 }  
  \__datatool_strcmp:NNN #1 \l__datatool_tmpa_str \l__datatool_tmpb_str  
}
```

```
\dtlicompare{<count>}{<string1>}{<string2>}
```

`\dtlicompare`

As `\dtlcompare` but ignores case.

```
\newcommand*{\dtlicompare}[3]{%
  \__datatool_get_icompare_sort:Nn \l__datatool_tmpa_str { #2 }
  \__datatool_get_icompare_sort:Nn \l__datatool_tmpb_str { #3 }
  \__datatool_strcmp:NNN #1 \l__datatool_tmpa_str \l__datatool_tmpb_str
}
```

Compare two strings provided as token lists and store the result in the count register provided in the first argument.

```
\cs_new:Nn \__datatool_strcmp:NNN
{
  \exp_args:NNo \__datatool_strcmp:Nnn #1 { #2 } { #3 }
}
```

If `\pdfstrcmp` or `\strcmp` is defined, use that for string comparisons otherwise use L^AT_EX3 string comparison commands.

```
\cs_if_exist:NTF \strcmp
{
  \cs_new:Nn \__datatool_strcmp:Nnn
  {
    \int_set:Nn #1 { \strcmp { #2 } { #3 } }
  }
  \cs_new:Nn \datatool_strcmp:nn
  {
    \strcmp { #1 } { #2 }
  }
}
{
  \cs_if_exist:NTF \pdfstrcmp
  {
    \cs_new:Nn \__datatool_strcmp:Nnn
    {
      \int_set:Nn #1 { \pdfstrcmp{ #2 } { #3 } }
    }
    \cs_new:Nn \datatool_strcmp:nn
    {
      \pdfstrcmp { #1 } { #2 }
    }
  }
}
```

Most likely LuaTeX.

```
\cs_new:Nn \__datatool_strcmp:Nnn
{
  \str_if_eq:nnTF { #2 } { #3 }
  { \int_zero:N #1 }
  {
    \str_compare:nNnTF { #2 } < { #3 }
    { \int_set:Nn #1 { -1 } }
    { \int_set_eq:NN #1 \c_one_int }
  }
}
```

```

    }
  }
  \cs_new:Nn \datatool_strcmp:nn
  {
    \str_if_eq:nnTF { #1 } { #2 }
    { \c_zero_int }
    {
      \str_compare:nNnTF { #1 } < { #2 }
      { -1 }
      { \c_one_int }
    }
  }
}

```

Compare two numeric values and store the result in the count register provided in the first argument.

```

\cs_new:Nn \__datatool_numcmp:Nnn
{
  \dtlifnumlt { #2 } { #3 }
  { #1=-1\relax }
  {
    \dtlifnumgt { #2 } { #3 } { #1=1\relax } { #1=0\relax }
  }
}
\tl_new:N \l__datatool_cmpa_tl
\tl_new:N \l__datatool_cmpb_tl

```

The token list mapping function skips spaces, so need to replace spaces with a token that represents a space.

```

\tl_const:Nn \c__datatool_space_tl { ~ }

```

Case-sensitive:

```

\cs_new:Nn \__datatool_get_compare_sort:Nn
{
  \bool_if:NTF \l__datatool_compare_expand_cs_bool
  {
    \tl_set:Nx \l__datatool_cmpb_tl { \text_purify:n { #2 } }
  }
  {
    \tl_set:Nn \l__datatool_cmpb_tl { #2 }
  }
}
\tl_replace_all:Nnn \l__datatool_cmpb_tl { ~ } { \c__datatool_space_tl }
\tl_clear:N \l__datatool_cmpa_tl
\exp_args:No \tl_map_function:nN
{ \l__datatool_cmpb_tl }
  \__datatool_get_compare_sort_fn:n
\bool_if:NTF \l__datatool_compare_expand_cs_bool
{
  \str_set:Nx #1 { \l__datatool_cmpa_tl }
}

```

```

    }
    {
      \str_set:Nx #1 { \text_purify:n { \l__datatool_cmpa_tl } }
    }
  }
}
Case-insensitive:
\cs_new:Nn \__datatool_get_icompare_sort:Nn
{
  \bool_if:NTF \l__datatool_compare_expand_cs_bool
  {
    \tl_set:Nx \l__datatool_cmpb_tl { \text_purify:n { #2 } }
  }
  {
    \tl_set:Nn \l__datatool_cmpb_tl { #2 }
  }
  \tl_replace_all:Nnn \l__datatool_cmpb_tl { ~ } { \c__datatool_space_tl }
  \tl_clear:N \l__datatool_cmpa_tl
  \exp_args:No \tl_map_function:nN
  { \l__datatool_cmpb_tl }
  \__datatool_get_compare_sort_fn:n
  \bool_if:NTF \l__datatool_compare_expand_cs_bool
  {
    \str_set:Nx #1 { \text_lowercase:n { \l__datatool_cmpa_tl } }
  }
  {
    \str_set:Nx #1
    { \text_purify:n { \text_lowercase:n { \l__datatool_cmpa_tl } } }
  }
}
\cs_new:Nn \__datatool_get_compare_sort_fn:n
{
  \tl_if_head_eq_catcode:nNTF { #1 } \relax
  {
    \tl_if_eq:nnTF { \c__datatool_space_tl } { #1 }
    {
      \tl_put_right:Nn \l__datatool_cmpa_tl { ~ }
    }
    {
      \ifdtlcompareskipcs
      \else
      \tl_put_right:Nn \l__datatool_cmpa_tl { ^^J }
      \fi
    }
  }
  { \tl_put_right:Nn \l__datatool_cmpa_tl { #1 } }
}

```

`\dtlwordindexcompare` Word breaks come before all other letters of the alphabet (since the space character comes before all visible characters). Note that, as from v3.0, `\@dtl@wordbreak` is

no longer used, except to provide a non-empty fourth argument for `\@dtldictcompare`.

```
\newcommand*\dtlwordindexcompare}[3]{%  
  \@dtldictcompare{#1}{#2}{#3}{\@dtl@wordbreak}%  
}
```

`\dtlletterindexcompare` Word breaks are ignored.

```
\newcommand*\dtlletterindexcompare}[3]{%  
  \@dtldictcompare{#1}{#2}{#3}{}%  
}
```

`\@dtldictcompare` Word or letter compare. Fourth argument should be empty for letter compare.

```
\newcommand*\@dtldictcompare}[4]{%  
  \group_begin:  
  \dtl@SortWordCommands@hook  
  \exp_args:Nxx \__datatool_set_tmp_dictcomp:nn { #2 } { #3 }  
  \tl_if_empty:nT { #4 }  
  {  
    \tl_replace_all:Nnn \l__datatool_dictcompa_tl { ~ } {}  
    \tl_replace_all:Nnn \l__datatool_dictcompb_tl { ~ } {}  
  }  
  \str_set:NV \l__datatool_tmpa_str \l__datatool_dictcompa_tl  
  \str_set:NV \l__datatool_tmpb_str \l__datatool_dictcompb_tl  
  \__datatool_strcmp:NNN #1 \l__datatool_tmpa_str \l__datatool_tmpb_str  
}  
\tl_new:N \l__datatool_dictcompa_tl  
\tl_new:N \l__datatool_dictcompb_tl  
\cs_new:Nn \__datatool_set_tmp_dictcomp:nn  
{  
  \group_end:  
  \DTLsortwordhandler { #1 } { \l__datatool_dictcompa_tl }  
  \DTLsortwordhandler { #2 } { \l__datatool_dictcompb_tl }  
}
```

Need to indicate type of inversion.

`\datatoolpersoncomma`

```
\newcommand*\datatoolpersoncomma}{, \space}
```

`\datatoolplacecomma`

```
\newcommand*\datatoolplacecomma}{, \space}
```

`\datatoolsubjectcomma`

```
\newcommand*\datatoolsubjectcomma}{, \space}
```

`\datatoolparenstart`

```
\newcommand*\datatoolparenstart}{\space}
```

`\datatoolparen`

```
\newcommand*\datatoolparen}[1]{\space (#1)}
```

The following commands `\dtlicomparewords` and `\dtlcomparewords` were never documented and don't seem to do anything different from `\dtlicompare` and `\dtlcompare`. They have existed since at least v2.25.

`\dtlicomparewords`

```
\dtlicomparewords{<count>}{<word A>}{<word B>}
```

This does a case insensitive comparison.

```
\newcommand{\dtlicomparewords}[3]{%
  \dtlicompare{#1}{#2}{#3}%
}
```

`\dtlcomparewords`

```
\dtlcomparewords{<count>}{<word A>}{<word B>}
```

This does a case sensitive comparison.

```
\newcommand{\dtlcomparewords}[3]{%
  \dtlcompare{#1}{#2}{#3}%
}
```

macro

```
\dtlifecyclegroup{<char>}{<case letter>}{<case
digit>}{<case symbol>}
```

```
\newrobustcmd*{\dtlifecyclegroup}[4]{%
  \regex_match:nnTF { \A \d \Z } { #1 }
  { #3 }
  {
    \regex_match:nnTF { \A [[:alpha:]] \Z } { #1 }
    { #2 }
    { #3 }
  }
}
```

`\dtlparsewords`

```
\dtlparsewords{<phrase>}{<handler cs>}
```

Iterates through the given phrase. Hyphens are considered word boundaries. Punctuation and digits before and after words are discarded.

```
\newcommand*{\dtlparsewords}[2]{%
  \group_begin:
  \tl_set:Nx \l__datatool_tmpa_tl { \tl_trim_spaces:n { #1 } }
  \regex_replace_case_all:nN
  {
    \l__datatool_word_head_regex
    {
```

```

        \2 \cM\|
      }
    \l_datatool_word_hyphen_regex
    {
      \2 \cM\|
    }
    \l_datatool_word_tail_regex
    {
      \2
    }
    \l_datatool_symbols_regex
    { }
  }
  \l_datatool_tmpa_tl
  \forlistloop { #2 } { \l_datatool_tmpa_tl }
\group_end:
}

```

`\DTLifstringlt{<string1>}{<string2>}{<true part>}{<false part>}`

`\DTLifstringlt`

String comparison (Starred version ignores case)

```

\NewDocumentCommand \DTLifstringlt { s m m m m }
{
  \IfBooleanTF { #1 }
  {
    \@sDTLifstringlt { #2 } { #3 } { #4 } { #5 }
  }
  {
    \@DTLifstringlt { #2 } { #3 } { #4 } { #5 }
  }
}

```

The internals are used by `\DTLiflt` as well.

`\@DTLifstringlt` Unstarred version (case-sensitive).

```

\newcommand*{\@DTLifstringlt}[4]{
  \exp_args:NNo \__datatool_get_compare_sort:Nn
  \l_datatool_tmpa_str { #1 }
  \exp_args:NNo \__datatool_get_compare_sort:Nn
  \l_datatool_tmpb_str { #2 }
  \str_compare:eNeTF
  { \l_datatool_tmpa_str }
  <
  { \l_datatool_tmpb_str }
  { #3 } { #4 }
}

```

`\s@DTLifstringlt` Starred version (case-sensitive).

```
\newcommand*\s@DTLifstringlt}[4]{
  \exp_args:NNo \__datatool_get_icompare_sort:Nn
  \l__datatool_tmpa_str { #1 }
  \exp_args:NNo \__datatool_get_icompare_sort:Nn
  \l__datatool_tmpb_str { #2 }
  \str_compare:eNeTF
  { \l__datatool_tmpa_str }
  <
  { \l__datatool_tmpb_str }
  { #3 } { #4 }
}
```

`\DTLiflt{<arg1>}{<arg2>}{<true part>}{<false part>}`

`\DTLiflt`

Does `\DTLifnumlt` if both `<arg1>` and `<arg2>` are numerical, otherwise do `\DTLifstringlt` (unstarred version) or `\DTLifstringlt*` (starred version).

```
\NewDocumentCommand \DTLiflt { s m m m m }
{
  \IfBooleanTF { #1 }
  {
    \s@DTLiflt { #2 } { #3 } { #4 } { #5 }
  }
  {
    \DTLiflt { #2 } { #3 } { #4 } { #5 }
  }
}
```

`\@DTLiflt` Unstarred version (also used in `\DTLisilt`).

```
\newcommand*\@DTLiflt}[4]{
  \dtl@testbothnumerical {#1} {#2}
  \if@dtl@condition
  \DTLifnumlt {#1} {#2} {#3} {#4}
  \else
  \@DTLifstringlt {#1} {#2} {#3} {#4}
  \fi
}
```

`\s@DTLiflt` Starred version (also used in `\DTLisilt`).

```
\newcommand*\s@DTLiflt}[4]{
  \dtl@testbothnumerical {#1} {#2}
  \if@dtl@condition
  \DTLifnumlt {#1} {#2} {#3} {#4}
  \else
  \s@DTLifstringlt {#1} {#2} {#3} {#4}
  \fi
}
```

```
\DTLifstringgt{<string1>}{<string2>}{<true part>}
{<false part>}
```

\DTLifstringgt

String comparison (starred version ignores case)

```
\NewDocumentCommand \DTLifstringgt { s m m m m }
{
  \IfBooleanTF { #1 }
  {
    \@sDTLifstringgt { #2 } { #3 } { #4 } { #5 }
  }
  {
    \@DTLifstringgt { #2 } { #3 } { #4 } { #5 }
  }
}
```

The internals are used by \DTLifgt as well.

\@DTLifstringgt Unstarred version (case-sensitive).

```
\newcommand*{\@DTLifstringgt}[4]{
  \exp_args:NNo \__datatool_get_compare_sort:Nn
  \l__datatool_tmpa_str { #1 }
  \exp_args:NNo \__datatool_get_compare_sort:Nn
  \l__datatool_tmpb_str { #2 }
  \str_compare:eNeTF
  { \l__datatool_tmpa_str }
  >
  { \l__datatool_tmpb_str }
  { #3 } { #4 }
}
```

\@sDTLifstringgt Starred version (case-insensitive).

```
\newcommand*{\@sDTLifstringgt}[4]{
  \exp_args:NNo \__datatool_get_icompare_sort:Nn
  \l__datatool_tmpa_str { #1 }
  \exp_args:NNo \__datatool_get_icompare_sort:Nn
  \l__datatool_tmpb_str { #2 }
  \str_compare:eNeTF
  { \l__datatool_tmpa_str }
  >
  { \l__datatool_tmpb_str }
  { #3 } { #4 }
}
```

```
\DTLifgt{<arg1>}{<arg2>}{<true part>}{<false part>}
```

\DTLifgt

Does \DTLifnumgt if both <arg1> and <arg2> are numerical, otherwise do \DTLifstringgt or \DTLifstringgt*.

```

\NewDocumentCommand \DTLifgt { s m m m m }
{
  \IfBooleanTF { #1 }
  {
    \@sDTLifgt { #2 } { #3 } { #4 } { #5 }
  }
  {
    \@DTLifgt { #2 } { #3 } { #4 } { #5 }
  }
}

```

\@DTLifgt Unstarred version (also used in \DTLislt).

```

\newcommand*\@DTLifgt[4]{
  \dtl@testbothnumerical {#1} {#2}
  \if@dtl@condition
  \DTLifnumgt {#1} {#2} {#3} {#4}
  \else
  \@DTLifstringgt {#1} {#2} {#3} {#4}
  \fi
}

```

\@sDTLifgt Starred version (also used in \DTLisigt).

```

\newcommand*\@sDTLifgt[4]{
  \dtl@testbothnumerical {#1} {#2}
  \if@dtl@condition
  \DTLifnumgt {#1} {#2} {#3} {#4}
  \else
  \@sDTLifstringgt {#1} {#2} {#3} {#4}
  \fi
}

```

\DTLifstringeq{<string1>}{<string2>}{<true part>}
{<false part>}

\DTLifstringeq

String comparison (starred version ignores case)

```

\NewDocumentCommand \DTLifstringeq { s m m m m }
{
  \IfBooleanTF { #1 }
  {
    \@sDTLifstringeq { #2 } { #3 } { #4 } { #5 }
  }
  {
    \@DTLifstringeq { #2 } { #3 } { #4 } { #5 }
  }
}

```

The internals are used by \DTLifeq as well.

`\@DTLifstringeq` Unstarred version (case-sensitive).

```
\newcommand*\@DTLifstringeq}[4]{
  \exp_args:NNo \__datatool_get_compare_sort:Nn
  \l__datatool_tmpa_str { #1 }
  \exp_args:NNo \__datatool_get_compare_sort:Nn
  \l__datatool_tmpb_str { #2 }
  \str_compare:eNeTF
  { \l__datatool_tmpa_str }
  =
  { \l__datatool_tmpb_str }
  { #3 } { #4 }
}
```

`\@sDTLifstringeq` Starred version (case-insensitive).

```
\newcommand*\@sDTLifstringeq}[4]{
  \exp_args:NNo \__datatool_get_icompare_sort:Nn
  \l__datatool_tmpa_str { #1 }
  \exp_args:NNo \__datatool_get_icompare_sort:Nn
  \l__datatool_tmpb_str { #2 }
  \str_compare:eNeTF
  { \l__datatool_tmpa_str }
  =
  { \l__datatool_tmpb_str }
  { #3 } { #4 }
}
```

`\DTLifeq{<arg1>}{<arg2>}{<true part>}{<>false part>}`

`\DTLifeq`

Does `\DTLifnumeq` if both `<arg1>` and `<arg2>` are numerical, otherwise do `\DTLifstringeq` or `\DTLifstringeq*`.

```
\NewDocumentCommand \DTLifeq { s m m m m }
{
  \IfBooleanTF { #1 }
  {
    \@sDTLifeq { #2 } { #3 } { #4 } { #5 }
  }
  {
    \@DTLifeq { #2 } { #3 } { #4 } { #5 }
  }
}
```

`\@DTLifeq` Unstarred version (also used in `\DTLifseq`).

```
\newcommand*\@DTLifeq}[4]{
  \dtl@testbothnumerical {#1} {#2}
  \if@dtl@condition
  \DTLifnumeq {#1} {#2} {#3} {#4}
  \else
```

```

\@DTLifstringeq {#1} {#2} {#3} {#4}
\fi
}

```

\@SDTLifeq Starred version (also used in \DTLisieq).

```

\newcommand*\@SDTLifeq[4]{
\dtl@testbothnumerical {#1} {#2}
\if@dtl@condition
\DTLifnumeq {#1} {#2} {#3} {#4}
\else
\@SDTLifstringeq {#1} {#2} {#3} {#4}
\fi
}

```

```

\regex_new:N \l_datatool_space_regex
\regex_set:Nn \l_datatool_space_regex
{
((?:[[:space:]\~])|(?:\c{protect}? \c{(?:nobreak)?space\ ?}))
}

```

\DTLifSubString{<string>}{<sub string>}{<true part>}{<false part>}

\DTLifSubString

If <sub string> is contained in <string> does <true part>, otherwise does <false part>. Spaces are replaced with ~ to prevent leading/trailing spaces from being trimmed.

```

\newrobustcmd*\DTLifSubString{\@ifstar\@SDTLifSubString\@DTLifSubString}

```

\@DTLifSubString

```

\newcommand*\@DTLifSubString[4]{%
\tl_set:Nx \l__datatool_tmpa_tl { \text_purify:n { #1 } }
\tl_set:Nx \l__datatool_tmpb_tl { \text_purify:n { #2 } }
\regex_replace_all:NnN \l_datatool_space_regex { \~ } \l__datatool_tmpa_tl
\regex_replace_all:NnN \l_datatool_space_regex { \~ } \l__datatool_tmpb_tl
\exp_args:NVV \str_if_in:nnTF
\l__datatool_tmpa_tl \l__datatool_tmpb_tl
{ #3 } { #4 }
}

```

\@SDTLifSubString

```

\newcommand*\@SDTLifSubString[2]{%
\@DTLifSubString{ \text_lowercase:n { #1 } }{ \text_lowercase:n { #2 } }%
}

```

\DTLifStartsWith{<string>}{<substring>}{<true part>}{<false part>}

\DTLifStartsWith

If $\langle string \rangle$ starts with $\langle substring \rangle$, this does $\langle true part \rangle$, otherwise it does $\langle false part \rangle$.

```
\newrobustcmd*{\DTLifStartsWith}{\@ifstar\@sDTLifStartsWith\@DTLifStartsWith}
```

$\@DTLifStartsWith$

```
\newcommand*{\@DTLifStartsWith}[4]{%
  \tl_set:Nx \l__datatool_tmpa_tl { \text_purify:n { #1 } }
  \tl_set:Nx \l__datatool_tmpb_tl { \text_purify:n { #2 } }
  \regex_replace_all:NnN \l__datatool_space_regex { \~ } \l__datatool_tmpa_tl
  \regex_replace_all:NnN \l__datatool_space_regex { \~ } \l__datatool_tmpb_tl
  \exp_args:NVV \__datatool_if_starts_with:nnTF
    \l__datatool_tmpa_tl \l__datatool_tmpb_tl
  { #3 } { #4 }
}
```

$\@sDTLifStartsWith$

```
\newcommand*{\@sDTLifStartsWith}[2]{%
  \@DTLifStartsWith{ \text_lowercase:n { #1 } }{ \text_lowercase:n { #2 } }%
}
```

$\DTLifEndsWith\langle string \rangle\langle substring \rangle\langle true part \rangle\langle false part \rangle$

\DTLifEndsWith

If $\langle string \rangle$ ends with $\langle substring \rangle$, this does $\langle true part \rangle$, otherwise it does $\langle false part \rangle$.

```
\newrobustcmd*{\DTLifEndsWith}{\@ifstar\@sDTLifEndsWith\@DTLifEndsWith}
```

$\@DTLifEndsWith$

```
\newcommand*{\@DTLifEndsWith}[4]{%
  \tl_set:Nx \l__datatool_tmpa_tl { \text_purify:n { #1 } }
  \tl_set:Nx \l__datatool_tmpb_tl { \text_purify:n { #2 } }
  \regex_replace_all:NnN \l__datatool_space_regex { \~ } \l__datatool_tmpa_tl
  \regex_replace_all:NnN \l__datatool_space_regex { \~ } \l__datatool_tmpb_tl
  \tl_reverse:N \l__datatool_tmpa_tl
  \tl_reverse:N \l__datatool_tmpb_tl
  \exp_args:NVV \__datatool_if_starts_with:nnTF
    \l__datatool_tmpa_tl \l__datatool_tmpb_tl
  { #3 } { #4 }
}
```

$\@sDTLifEndsWith$

```
\newcommand*{\@sDTLifEndsWith}[2]{%
  \@DTLifEndsWith{ \text_lowercase:n { #1 } }{ \text_lowercase:n { #2 } }%
}
```

$\DTLifstringclosedbetween\langle string \rangle\langle min \rangle\langle max \rangle\langle true part \rangle\langle false part \rangle$

$\DTLifstringclosedbetween$

String comparison (starred version ignores case)

```
\NewDocumentCommand \DTLifstringclosedbetween { s m m m m m }
{
  \IfBooleanTF { #1 }
  {
    \@sDTLifstringclosedbetween { #2 } { #3 } { #4 } { #5 } { #6 }
  }
  {
    \@DTLifstringclosedbetween { #2 } { #3 } { #4 } { #5 } { #6 }
  }
}
```

DTLifstringclosedbetween Unstarred version (case-sensitive).

```
\newcommand*{\@DTLifstringclosedbetween}[5]{%
  \exp_args:NNo \__datatool_get_compare_sort:Nn
    \l__datatool_tmpa_str { #1 }
  \exp_args:NNo \__datatool_get_compare_sort:Nn
    \l__datatool_tmpb_str { #2 }
  \exp_args:NNo \__datatool_get_compare_sort:Nn
    \l__datatool_tmpc_str { #3 }
  \str_compare:eNeTF
    { \l__datatool_tmpa_str }
    <
    { \l__datatool_tmpb_str }
  { #5 }
  {
    \str_compare:eNeTF
      { \l__datatool_tmpa_str }
      >
      { \l__datatool_tmpc_str }
    { #5 } { #4 }
  }
}
```

DTLifstringclosedbetween Starred version (case-sensitive).

```
\newcommand*{\@sDTLifstringclosedbetween}[5]{%
  \exp_args:NNo \__datatool_get_icompare_sort:Nn
    \l__datatool_tmpa_str { #1 }
  \exp_args:NNo \__datatool_get_icompare_sort:Nn
    \l__datatool_tmpb_str { #2 }
  \exp_args:NNo \__datatool_get_icompare_sort:Nn
    \l__datatool_tmpc_str { #3 }
  \str_compare:eNeTF
    { \l__datatool_tmpa_str }
    <
    { \l__datatool_tmpb_str }
  { #5 }
  {
    \str_compare:eNeTF
```

```

        { \l_datatool_tmpa_str }
        >
        { \l_datatool_tmpc_str }
        { #5 } { #4 }
    }
}

```

`\DTLifclosedbetween{<arg>}{<min>}{<max>}{<>true part>}{<>false part>}`

`\DTLifclosedbetween`

Does `\DTLifnumclosedbetween` if `{<arg>}`, `<min>` and `<max>` are numerical, otherwise do `\DTLifstringclosedbetween` or `\DTLifstringclosedbetween*`.

```

\NewDocumentCommand \DTLifclosedbetween { s m m m m m }
{
  \IfBooleanTF { #1 }
  {
    \@sDTLifclosedbetween { #2 } { #3 } { #4 } { #5 } { #6 }
  }
  {
    \@DTLifclosedbetween { #2 } { #3 } { #4 } { #5 } { #6 }
  }
}

```

`\@DTLifclosedbetween` Unstarred version

```

\newcommand*{\@DTLifclosedbetween}[5]{%
  \dtl@testbothnumerical{#2}{#3}%
  \if@dtl@condition
    \DTLifnumerical { #1 }
    {
      \DTLifnumclosedbetween {#1} {#2} {#3} {#4} {#5}
    }
    {
      \@DTLifstringclosedbetween {#1} {#2} {#3} {#4} {#5}
    }
  }
  \else
    \@DTLifstringclosedbetween {#1} {#2} {#3} {#4} {#5}
  \fi
}

```

`\@sDTLifclosedbetween` Starred version

```

\newcommand*{\@sDTLifclosedbetween}[5]{%
  \dtl@testbothnumerical{#2}{#3}%
  \if@dtl@condition
    \DTLifnumerical { #1 }
    {
      \DTLifnumclosedbetween {#1} {#2} {#3} {#4} {#5}
    }
  }
}

```

```

    {
      \@sDTLifstringclosedbetween {#1} {#2} {#3} {#4} {#5}
    }
  \else
    \@sDTLifstringclosedbetween {#1} {#2} {#3} {#4} {#5}
  \fi
}

```

\DTLifstringopenbetween{<string>}{<min>}{<max>}{<true part>}{<false part>}

\DTLifstringopenbetween

String comparison (starred version ignores case)

```

\NewDocumentCommand \DTLifstringopenbetween { s m m m m m m }
{
  \IfBooleanTF { #1 }
  {
    \@sDTLifstringopenbetween { #2 } { #3 } { #4 } { #5 } { #6 }
  }
  {
    \@DTLifstringopenbetween { #2 } { #3 } { #4 } { #5 } { #6 }
  }
}

```

Unstarred version:

```

\newcommand*\@DTLifstringopenbetween}[5]{%
  \exp_args:NNo \__datatool_get_compare_sort:Nn
    \l__datatool_tmpa_str { #1 }
  \exp_args:NNo \__datatool_get_compare_sort:Nn
    \l__datatool_tmpb_str { #2 }
  \exp_args:NNo \__datatool_get_compare_sort:Nn
    \l__datatool_tmpc_str { #3 }
  \str_compare:eNeTF
    { \l__datatool_tmpa_str }
    >
    { \l__datatool_tmpb_str }
  {
    \str_compare:eNeTF
      { \l__datatool_tmpa_str }
      <
      { \l__datatool_tmpc_str }
      { #4 } { #5 }
    }
  { #5 }
}

```

@sDTLifstringopenbetween Starred version (case-sensitive).

```

\newcommand*\@sDTLifstringopenbetween}[5]{%
  \exp_args:NNo \__datatool_get_icompare_sort:Nn

```

```

    \l_datatool_tmpa_str { #1 }
\exp_args:NNo \__datatool_get_icompare_sort:Nn
    \l_datatool_tmpb_str { #2 }
\exp_args:NNo \__datatool_get_icompare_sort:Nn
    \l_datatool_tmpc_str { #3 }
\str_compare:eNeTF
    { \l_datatool_tmpa_str }
    >
    { \l_datatool_tmpb_str }
    {
    \str_compare:eNeTF
    { \l_datatool_tmpa_str }
    <
    { \l_datatool_tmpc_str }
    { #4 } { #5 }
    }
    { #5 }
}
}

```

`\DTLifopenbetween{<arg>}{<min>}{<max>}{<true part>}{<false part>}`

`\DTLifopenbetween`

Does `\DTLifnumopenbetween` if `{<arg>}`, `<min>` and `<max>` are numerical, otherwise do `\DTLifstringopenbetween` or `\DTLifstringopenbetween*`.

```

\NewDocumentCommand \DTLifopenbetween { s m m m m m }
{
  \IfBooleanTF { #1 }
  {
    \@sDTLifopenbetween { #2 } { #3 } { #4 } { #5 } { #6 }
  }
  {
    \@DTLifopenbetween { #2 } { #3 } { #4 } { #5 } { #6 }
  }
}

```

`\@DTLifopenbetween` Unstarred version

```

\newcommand*{\@DTLifopenbetween}[5]{
  \dtl@testbothnumerical {#2} {#3}
  \if@dtl@condition
  \DTLifnumerical { #1 }
  {
    \DTLifnumopenbetween {#1} {#2} {#3} {#4} {#5}
  }
  {
    \@DTLifstringopenbetween {#1} {#2} {#3} {#4} {#5}
  }
}
\else
  \@DTLifstringopenbetween {#1} {#2} {#3} {#4} {#5}

```

```

\fi
}

```

\@sDTLifopenbetween Starred version

```

\newcommand*\@sDTLifopenbetween}[5]{
\dtl@testbothnumerical {#2} {#3}
\if@dtl@condition
\DTLifnumerical { #1 }
{
\DTLifnumopenbetween {#1} {#2} {#3} {#4} {#5}
}
{
\@sDTLifstringopenbetween {#1} {#2} {#3} {#4} {#5}
}
\else
\@sDTLifstringopenbetween {#1} {#2} {#3} {#4} {#5}
\fi
}
\ExplSyntaxOff

```

\DTLifFPopenbetween

```

\DTLifFPopenbetween{<num>}{<min>}{<max>}{<true part>}
{<false part>}

```

Determines if $\langle min \rangle < \langle num \rangle < \langle max \rangle$ where all arguments are in standard fixed point notation. (Command name maintained for backward compatibility.)

```

\let\DTLifFPopenbetween\dtlifnumopenbetween

```

\DTLifFPclosedbetween

```

\DTLifFPclosedbetween{<num>}{<min>}{<max>}{<true part>}
{<false part>}

```

Determines if $\langle min \rangle \leq \langle num \rangle \leq \langle max \rangle$. (Command name maintained for backward compatibility.)

```

\let\DTLifFPclosedbetween\dtlifnumclosedbetween

```

2.7.4 ifthen Conditionals

The following commands provide conditionals \DTLis... which can be used in \ifthenelse.

\dtl@testlt Command to test if first argument is less than second argument. If either argument is a string, a case sensitive string comparison is used instead. This sets \if@dtl@condition.

```

\newcommand*\dtl@testlt}[2]{%
\@DTLiflt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`\DTLislt` Provide conditional command for use in `\ifthenelse`

```

\newcommand*{\DTLislt}[2]{%
  \TE@throw\noexpand\dtl@testlt{#1}{#2}\noexpand\if@dtl@condition
}

```

`\dtl@testiclt` Command to test if first argument is less than second argument. If either argument is a string, a case insensitive string comparison is used instead. This sets `\if@dtl@condition`.

```

\newcommand*{\dtl@testiclt}[2]{%
  \@sDTLiflt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`\DTLisilt` Provide conditional command for use in `\ifthenelse`

```

\newcommand*{\DTLisilt}[2]{%
  \TE@throw\noexpand\dtl@testiclt{#1}{#2}\noexpand\if@dtl@condition
}

```

`\dtl@testgt` Command to test if first argument is greater than second argument. This sets `\if@dtl@condition`.

```

\newcommand*{\dtl@testgt}[2]{%
  \@DTLifgt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`\DTLisgt` Provide conditional command for use in `\ifthenelse`

```

\newcommand*{\DTLisgt}[2]{%
  \TE@throw\noexpand\dtl@testgt{#1}{#2}\noexpand\if@dtl@condition
}

```

`\dtl@testicgt` Command to test if first argument is greater than second argument (ignores case). This sets `\if@dtl@condition`.

```

\newcommand*{\dtl@testicgt}[2]{%
  \@sDTLifgt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`\DTLisigt` Provide conditional command for use in `\ifthenelse`

```

\newcommand*{\DTLisigt}[2]{%
  \TE@throw\noexpand\dtl@testicgt{#1}{#2}\noexpand\if@dtl@condition
}

```

`\dtl@testeq` Command to test if first argument is equal to the second argument. This sets `\if@dtl@condition`.

```

\newcommand*{\dtl@testeq}[2]{%
  \@DTLifeq{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`\DTLiseq` Provide conditional command for use in `\ifthenelse`

```

\newcommand*{\DTLiseq}[2]{%
  \TE@throw\noexpand\dtl@testeq{#1}{#2}\noexpand\if@dtl@condition
}

```

```

\dtl@testiceq Command to test if first number is equal to the second number (ignores case). This sets
\if@dtl@condition.
\newcommand*\dtl@testiceq}[2]{%
  \@sDTLifEq{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

\DTLisEq Provide conditional command for use in \ifthenelse
\newcommand*\DTLisEq}[2]{%
  \TE@throw\noexpand\dtl@testiceq{#1}{#2}\noexpand\if@dtl@condition
}

\dtl@testifsubstring Command to test if second argument is a substring of the first argument. This sets
\if@dtl@condition.
\newcommand*\dtl@testifsubstring}[2]{%
  \@DTLifSubString{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

\DTLisSubString Tests if second argument is contained in first argument.
\newcommand*\DTLisSubString}[2]{%
  \TE@throw\noexpand\dtl@testifsubstring{#1}{#2}%
  \noexpand\if@dtl@condition
}

\dtl@testifisubstring Command to test if second argument is a substring of the first argument. This sets
\if@dtl@condition.
\newcommand*\dtl@testifisubstring}[2]{%
  \@sDTLifSubString{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

\DTLisiSubString Tests if second argument is contained in first argument (no case).
\newcommand*\DTLisiSubString}[2]{%
  \TE@throw\noexpand\dtl@testifisubstring{#1}{#2}%
  \noexpand\if@dtl@condition
}

\dtl@teststartswith Command to test if second argument is a prefix of the first argument. This sets
\if@dtl@condition.
\newcommand*\dtl@teststartswith}[2]{%
  \@DTLifStartsWith{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

\DTLisPrefix Tests if first argument starts with second argument.
\newcommand*\DTLisPrefix}[2]{%
  \TE@throw\noexpand\dtl@teststartswith{#1}{#2}%
  \noexpand\if@dtl@condition
}

```

```

\dtl@testistartswith Command to test if second argument is a prefix of the first argument. This sets
\if@dtl@condition.
\newcommand*\dtl@testistartswith}[2]{%
  \@sDTLifStartsWith{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

\DTLisiPrefix Tests if first argument starts with second argument.
\newcommand*\DTLisiPrefix}[2]{%
  \TE@throw\noexpand\dtl@testistartswith{#1}{#2}%
  \noexpand\if@dtl@condition
}

\dtl@testendswith Command to test if second argument is a suffix of the first argument. This sets
\if@dtl@condition.
\newcommand*\dtl@testendswith}[2]{%
  \@DTLifEndsWith{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

\DTLisSuffix Tests if first argument ends with second argument.
\newcommand*\DTLisSuffix}[2]{%
  \TE@throw\noexpand\dtl@testendswith{#1}{#2}%
  \noexpand\if@dtl@condition
}

\dtl@testiendswith Command to test if second argument is a suffix of the first argument. This sets
\if@dtl@condition.
\newcommand*\dtl@testiendswith}[2]{%
  \@sDTLifEndsWith{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

\DTLisiSuffix Tests if first argument ends with second argument.
\newcommand*\DTLisiSuffix}[2]{%
  \TE@throw\noexpand\dtl@testiendswith{#1}{#2}%
  \noexpand\if@dtl@condition
}

\DTLisinlist Tests if first argument is an element of the comma-separated list given in the second
argument.
\newcommand*\DTLisinlist}[2]{%
  \TE@throw\noexpand\dtl@testinlist{#1}{#2}%
  \noexpand\if@dtl@condition
}

\dtl@testinlist
\newcommand*\dtl@testinlist}[2]{%
  \DTLifinlist{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`dtl@testnumclosedbetween` Command to test if first number lies between second and third numbers. (End points included, all arguments are fixed point numbers in standard format.) This sets `\if@dtl@condition`.

```
\newcommand*{\dtl@testnumclosedbetween}[3]{%
  \DTLifnumclosedbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

Provide conditional command for use in `\ifthenelse`

`\DTLisnumclosedbetween`

```
\newcommand*{\DTLisnumclosedbetween}[3]{%
  \TE@throw\noexpand\dtl@testnumclosedbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}
```

`\DTLisFPclosedbetween` Keep old command name for backwards compatibility:

```
\let\DTLisFPclosedbetween\DTLisnumclosedbetween
```

`\dtl@testnumopenbetween` Command to test if first number lies between second and third numbers. (End points excluded, all arguments are fixed point numbers in standard format.) This sets `\if@dtl@condition`.

```
\newcommand*{\dtl@testnumopenbetween}[3]{%
  \DTLifnumopenbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

`\DTLisnumopenbetween` Provide conditional command for use in `\ifthenelse`

```
\newcommand*{\DTLisnumopenbetween}[3]{%
  \TE@throw\noexpand\dtl@testnumopenbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}
```

`\DTLisFPopenbetween` Keep old command name for backwards compatibility:

```
\let\DTLisFPopenbetween\DTLisnumopenbetween
```

`\dtl@testclosedbetween` Command to test if first value lies between second and third values. (End points included, case sensitive.) This sets `\if@dtl@condition`.

```
\newcommand*{\dtl@testclosedbetween}[3]{%
  \DTLifclosedbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
```

`\DTLisclosedbetween` Provide conditional command for use in `\ifthenelse`

```
\newcommand*{\DTLisclosedbetween}[3]{%
  \TE@throw\noexpand\dtl@testclosedbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}
```

`\dtl@testiclosedbetween` Command to test if first value lies between second and third values. (End points included, case ignored.) This sets `\if@dtl@condition`.

```

\newcommand*\dtl@testiclosedbetween}[3]{%
  \@sDTLifclosedbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`\DTLisiclosedbetween` Provide conditional command for use in `\ifthenelse`

```

\newcommand*\DTLisiclosedbetween}[3]{%
  \TE@throw\noexpand\dtl@testiclosedbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}

```

`\dtl@testopenbetween` Command to test if first value lies between second and third values. (End points excluded, case sensitive.) This sets `\if@dtl@condition`.

```

\newcommand*\dtl@testopenbetween}[3]{%
  \@DTLifopenbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`\DTLisopenbetween` Provide conditional command for use in `\ifthenelse`

```

\newcommand*\DTLisopenbetween}[3]{%
  \TE@throw\noexpand\dtl@testopenbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}

```

`\dtl@testiopenbetween` Command to test if first value lies between second and third values. (End points excluded, case ignored.) This sets `\if@dtl@condition`.

```

\newcommand*\dtl@testiopenbetween}[3]{%
  \@sDTLifopenbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}

```

`\DTLisiopenbetween` Provide conditional command for use in `\ifthenelse`

```

\newcommand*\DTLisiopenbetween}[3]{%
  \TE@throw\noexpand\dtl@testiopenbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}

```

`\dtl@testFPislt` Command to test if first number is less than second number where both numbers are in standard format (dot for decimal separator and no group separators). This sets `\if@dtl@condition`.

```

\newcommand*\dtl@testFPislt}[2]{%
  \dtlifnumlt{#1}{#2}%
  {%
    \@dtl@conditiontrue
  }%
  {%
}

```

```

        \@dtl@conditionfalse
    }%
}

\DTLisnumlt Provide conditional command for use in \ifthenelse
\newcommand*\DTLisnumlt}[2]{%
    \TE@throw\noexpand\dtl@testFPislt{#1}{#2}%
    \noexpand\if@dtl@condition
}

\DTLisFPlt Synonym of \DTLisnumlt.
\let\DTLisFPlt\DTLisnumlt

\dtl@testFPisgt Command to test if first number is greater than second number where both numbers are
in standard format. This sets \if@dtl@condition.
\newcommand*\dtl@testFPisgt}[2]{%
    \dtlifnumgt{#1}{#2}%
    {%
        \@dtl@conditiontrue
    }%
    {%
        \@dtl@conditionfalse
    }%
}

\DTLisnumgt Provide conditional command for use in \ifthenelse
\newcommand*\DTLisnumgt}[2]{%
    \TE@throw\noexpand\dtl@testFPisgt{#1}{#2}%
    \noexpand\if@dtl@condition
}

\DTLisFPgt Synonym
\let\DTLisFPgt\DTLisnumgt

\dtl@testFPiseq Command to test if two numbers are equal, where both numbers are in standard decimal
format
\newcommand*\dtl@testFPiseq}[2]{%
    \dtlifnumeq{#1}{#2}%
    {%
        \@dtl@conditiontrue
    }%
    {%
        \@dtl@conditionfalse
    }%
}

\DTLisnumeq Provide conditional command for use in \ifthenelse
\newcommand*\DTLisnumeq}[2]{%
    \TE@throw\noexpand\dtl@testFPiseq{#1}{#2}%

```

```

\noexpand\if@dtl@condition
}

```

\DTLisFPeq Synonym.

```

\let\DTLisFPeq\DTLisnumeq

```

\dtl@testFPislteq Command to test if first number is less than or equal to second number where both numbers are in standard format. This sets \if@dtl@condition.

```

\newcommand*\dtl@testFPislteq}[2]{%
\dtlifnumlt{#1}{#2}%
{%
\@dtl@conditiontrue
}%
{%
\@dtl@conditionfalse
}%
\if@dtl@condition
\else
\dtl@testFPiseq{#1}{#2}%
\fi
}

```

\DTLisnumlteq Provide conditional command for use in \ifthenelse

```

\newcommand*\DTLisnumlteq}[2]{%
\TE@throw\noexpand\dtl@testFPislteq{#1}{#2}%
\noexpand\if@dtl@condition
}

```

\DTLisFPlteq Synonym.

```

\let\DTLisFPlteq\DTLisnumlteq

```

\dtl@testFPisgteq Command to test if first number is greater than or equal to second number where both numbers are in standard format. This sets \if@dtl@condition.

```

\newcommand*\dtl@testFPisgteq}[2]{%
\dtlifnumgt{#1}{#2}%
{%
\@dtl@conditiontrue
}%
{%
\@dtl@conditionfalse
}%
\if@dtl@condition
\else
\dtl@testFPiseq{#1}{#2}%
\fi
}

```

\DTLisnumgteq Provide conditional command for use in \ifthenelse

```

\newcommand*\DTLisnumgteq}[2]{%

```

```
\TE@throw\noexpand\dtl@testFPisgteq{#1}{#2}%  
\noexpand\if@dtl@condition}
```

`\DTLisFPgteq` Synonym.

```
\let\DTLisFPgteq\DTLisnumgteq
```

`\dtl@teststring` Command to test if argument is a string. This sets `\if@dtl@condition`

```
\newcommand*\dtl@teststring}[1]{%  
  \DTLifstring{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}
```

`\DTLisstring` Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLisstring}[1]{%  
  \TE@throw\noexpand\dtl@teststring{#1}\noexpand\if@dtl@condition}
```

`\dtl@testnumerical` Command to test if argument is a numerical. This sets `\if@dtl@condition`

```
\newcommand*\dtl@testnumerical}[1]{%  
  \DTLifnumerical{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%  
}
```

`\DTLisnumerical` Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLisnumerical}[1]{%  
  \TE@throw\noexpand\dtl@testnumerical{#1}\noexpand\if@dtl@condition}
```

`\dtl@testint` Command to test if argument is an integer. This sets `\if@dtl@condition`

```
\newcommand*\dtl@testint}[1]{%  
  \DTLifint{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}
```

`\DTLisint` Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLisint}[1]{%  
  \TE@throw\noexpand\dtl@testint{#1}\noexpand\if@dtl@condition}
```

`\dtl@testreal` Command to test if argument is a real. This sets `\if@dtl@condition`

```
\newcommand*\dtl@testreal}[1]{%  
  \DTLifreal{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}
```

`\DTLisreal` Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLisreal}[1]{%  
  \TE@throw\noexpand\dtl@testreal{#1}\noexpand\if@dtl@condition}
```

`\dtl@testcurrency` Command to test if argument is a currency. This sets `\if@dtl@condition`

```
\newcommand*\dtl@testcurrency}[1]{%  
  \DTLifcurrency{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}
```

`\DTLiscurrency` Provide conditional command for use in `\ifthenelse`

```
\newcommand*\DTLiscurrency}[1]{%  
  \TE@throw\noexpand\dtl@testcurrency{#1}\noexpand\if@dtl@condition}
```

```

\dtl@testcurrencyunit Command to test if argument is a currency with given unit. This sets \if@dtl@condition
\newcommand*\dtl@testcurrencyunit[2]{%
  \DTLifcurrencyunit{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}

\DTLiscurrencyunit Provide conditional command for use in \ifthenelse
\newcommand*\DTLiscurrencyunit[2]{%
  \TE@throw\noexpand\dtl@testcurrencyunit{#1}{#2}%
  \noexpand\if@dtl@condition
}

```

2.8 Loops

```

\dtlbreak Break out of loop at the end of current iteration.
\newcommand*\dtlbreak{%
  \PackageError{datatool}{Can't break out of anything}{}%
}

```

`\dtlforint` NB L^AT_EX3 now provides a better integer step function, which should be used instead. This is retained for backward-compatibility.

```

\dtlforint<ct>=<start>\to<end>\step
<inc>\do{<body>}

```

`<ct>` is a count register, `<start>`, `<end>` and `<inc>` are integers. Group if nested or use `\dtlforint`. An infinite loop may result if `<inc>= 0` and `<start> ≤ <end>` and `\dtlbreak` isn't used.

```

\long\def\dtlforint#1=#2\to#3\step#4\do#5{%

```

Make a copy of old version of break function

```

\let\@dtl@orgbreak\dtlbreak
\def\@dtl@endloophook{%

```

Setup break function for the loop (sets `<ct>` to `<end>` at the end of the current iteration).

```

\def\dtlbreak{\def\@dtl@endloophook{#1=#3}}%

```

Initialise `<ct>`

```

#1=#2\relax

```

Check if the steps are positive or negative.

```

\ifnum#4<0\relax

```

Counting down

```

\whiledo{\( #1>#3\)\TE@or\(#1=#3\)}%
{%
  #5%
  \@dtl@endloophook
  \advance#1 by #4\relax
}%
\else

```

Counting up

```
\whiledo{\(#1<#3\)\TE@or\(#1=#3\)}%
{%
#5%
\@dtl@endloophook
\advance#1 by #4\relax
}%
\fi
```

Restore break function.

```
\let\dtlbreak\@dtl@orgbreak
}
```

`\@dtl@foreach@level` Count register to keep track of global nested loops.

```
\newcount\@dtl@foreach@level
```

```
\dtlgforint<ct>=<start>\to<end>\step
<inc>\do{<body>}
```

`\dtlgforint`

`<ct>` is a count register, `<start>`, `<end>` and `<inc>` are integers. An infinite loop may result if `<inc>`=0 and `<start>` ≤ `<end>` and `\dtlbreak` isn't used.

```
\long\def\dtlgforint#1=#2\to#3\step#4\do#5{%
```

Initialise

```
\global#1=#2\relax
```

Increment level counter to allow for nested loops

```
\global\advance\@dtl@foreach@level by 1\relax
```

Set up end loop hook

```
\expandafter\global\expandafter
\let\csname @dtl@endhook@\the\@dtl@foreach@level\endcsname
\relax
```

Set up the break function: Copy current definition

```
\expandafter\global\expandafter
\let\csname @dtl@break@\the\@dtl@foreach@level\endcsname
\dtlbreak
```

Set up definition for this level (sets `<ct>` to `<end>` at the end of the current iteration).

```
\gdef\dtlbreak{\expandafter
\gdef\csname @dtl@endhook@\the\@dtl@foreach@level\endcsname{%
#1=#3}}%
```

check the direction

```
\ifnum#4<0\relax
```

Counting down

```
\whiledo{\(#1>#3\)\TE@or\(#1=#3\)}%
{%
```

```

        #5%
        \csname @dtl@endhook@\the\@dtl@foreach@level\endcsname
        \global\advance#1 by #4\relax
    }%
\else
Counting up (or 0 increments)
    \whiledo{\(#1<#3\)\TE@or\(#1=#3\)}%
    {%
        #5%
        \csname @dtl@endhook@\the\@dtl@foreach@level\endcsname
        \global\advance#1 by #4\relax
    }%
\fi
Restore break function
    \expandafter\global\expandafter\let\expandafter\dtlbreak
    \csname @dtl@break@\the\@dtl@foreach@level\endcsname
Decrement level counter
    \global\advance\@dtl@foreach@level by -1\relax
}

```

`dtlenvgforint` (*env.*) Environment form (contents are gathered, so verbatim can't be used):

```

\NewDocumentEnvironment{dtlenvgforint}
{ m +b }
{\dtlgforint#1\do{#2}}
{}

```

`dtlenvgforint*` (*env.*) Starred form suppresses space-trimming:

```

\NewDocumentEnvironment{dtlenvgforint*}
{ m +!b }
{\dtlgforint#1\do{#2}}
{}

```

2.9 Localisation Support

Load localisation support. None provided with `datatool`, but support can be added by defining a file called `datatool-(tag).ldf` that adds a redefinition of `\DTLCurrentLocaleWordHandler` and `\DTLCurrentLocaleGetInitialLetter` to the language hook. If a region is supplied, also set the currency.

```
\ExplSyntaxOn
```

Provide quick way to reset all localisation support.

`\DTLresetLanguage` Reset all language (not region) related commands.

```

\newcommand\DTLresetLanguage
{
    \tl_clear:N \l_datatool_current_language_tl
    \renewcommand \DTLandname { \& }
}

```

```

\renewcommand \DTLdatatypeunsetname { unset }
\renewcommand \DTLdatatypestringname { string }
\renewcommand \DTLdatatypeintegername { integer }
\renewcommand \DTLdatatypedecimalname { decimal }
\renewcommand \DTLdatatypecurrencyname { currency }
\renewcommand \DTLdatatypedatetimename { date-time }
\renewcommand \DTLdatatypedatename { date }
\renewcommand \DTLdatatypetimenename { time }
\renewcommand \DTLdatatypeinvalidname { invalid }
\renewcommand \DTLCurrentLocaleWordHandler [1] { }
\renewcommand \DTLCurrentLocaleGetInitialLetter [2]
{
  \datatool_get_first_letter:nN { ##1 } ##2
}
\renewcommand \DTLCurrentLocaleGetGroupString [3]
{
  \tl_set:Nn ##3 { ##1 }
}
\renewcommand \DTLCurrentLocaleGetMonthNameMap [1]
{
  \tl_set_eq:NN \l_datatool_monthname_map_value_tl \q_no_value
}
\renewcommand \DTLCurrentLocaleIfpmTF [ 3 ]
{
  \tl_if_eq:nnTF { ##1 } { pm } { ##2 } { ##3 }
}
\renewcommand \dtllettergroup [1]
{
  \text_titlecase_first:n { ##1 }
}
\renewcommand \dtlnonlettergroup [1]
{
  \detokenize { ##1 }
}
\renewcommand \dtlnumbergroup [1] { ##1 }
\renewcommand \dtlcurrencygroup [2] { ##1 }
\renewcommand \dtldatetimegroup [1] { ##1 }
\renewcommand \dtldategroup [1] { ##1 }
\renewcommand \dtltimegroup [1] { ##1 }
}

```

\DTLresetRegion Reset all region related commands.

```

\newcommand\DTLresetRegion
{
  \tl_clear:N \l_datatool_current_region_tl
  \DTLsetnumberchars { , } { . }
  \DTLsetdefaultcurrency { XXX }
  \renewcommand \DTLCurrentLocaleCurrencyDP { 2 }
  \renewcommand \dtlcurrfmtsymsep { }
  \renewcommand \DTLCurrentLocaleParseTimeStamp [ 4 ] { ##4 }
}

```

```

\renewcommand \DTLCurrentLocaleParseDate [ 4 ] { ##4 }
\renewcommand \DTLCurrentLocaleParseTime [ 4 ] { ##4 }
\renewcommand \DTLCurrentLocaleGetTimeZoneMap [ 1 ]
{
  \tl_set_eq:NN \l_datatool_timezone_map_value_tl \q_no_value
}
\renewcommand \DTLCurrentLocaleFormatDate [ 4 ]
{
  \datatool_default_date_fmt:nnnn { ##1 } { ##2 } { ##3 } { ##4 }
}
\renewcommand \DTLCurrentLocaleFormatTime [ 3 ]
{
  \datatool_default_time_fmt:nnn { ##1 } { ##2 } { ##3 }
}
\renewcommand \DTLCurrentLocaleFormatTimeZone [ 2 ]
{
  \datatool_default_timezone_fmt:nn { ##1 } { ##2 }
}
\renewcommand \DTLCurrentLocaleFormatTimeStampNoZone [7]
{
  \datatool_default_timestamp_fmt:nnnnnnn
  { ##1 } { ##2 } { ##3 } { ##4 } { ##5 } { ##6 } { ##7 }
}
\renewcommand \DTLCurrentLocaleFormatTimeStampWithZone [9]
{
  \datatool_default_timestamp_fmt:nnnnnnnn
  { ##1 } { ##2 } { ##3 } { ##4 } { ##5 } { ##6 } { ##7 } { ##8 } { ##9 }
}
\renewcommand \DTLCurrentLocaleTimeStampFmtSep { ~ }
}

```

\RequireDatatoolDialect

```

\newcommand \RequireDatatoolDialect [1]
{
  \tl_clear:N \l_datatool_current_language_tl
  \__datatool_require_ldf:
  [
    Ensure region language file is loaded, if it exists.
    \tl_if_empty:NF \CurrentTrackedRegion
    {
      \TrackLangRequireResource { \CurrentTrackedRegion }
    }
  ]
}

```

Note that the region file is only loaded once. This means that if there are multiple dialects that share a region, the region hook would only be added to the first dialect with that region. Therefore, the region file shouldn't add anything to the captions hook but should instead just define a command called `\DTL<Region>LocaleHook` where `<Region>` is the two letter (uppercase) region code. This means that it can be added here, even if the file wasn't loaded at this point.

```

\tl_if_exist:cTF { DTL \CurrentTrackedRegion LocaleHook }

```

```

    {
      \exp_args:Nc \TrackLangAddToCaptions
        { DTL \CurrentTrackedRegion LocaleHook }
    }
    {
      \tl_new:c { DTL \CurrentTrackedRegion LocaleHook }
      \datatool_locale_warn:nn
        { datatool-base }
        {
          No ~ locale ~ hook ~ available ~ for ~ region ~ ` \CurrentTrackedRegion '
        }
    }
  }
}

```

Search as usual from the locale tag to pick up any specific language + region, sub-languages or scripts.

```

  \TrackLangRequireResource { \CurrentTrackedTag }
]
{ datatool } { #1 }
\tl_if_empty:NT \l_datatool_current_language_tl
{

```

No support for this language so clear the token list in the language hook.

```

  \@TrackLangAddToHook
  {
    \tl_clear:N \l_datatool_current_language_tl
  }
  { captions }
}
\tl_if_empty:NF \CurrentTrackedRegion
{

```

If the region isn't empty but the hook hasn't been defined then the region file wasn't loaded. This may be because there's no language support.

```

  \tl_if_exist:cF { DTL \CurrentTrackedRegion LocaleHook }
  {
    \cs_if_exist:NT \TrackLangRequireDialectOmitDialectLabel
    {
      \TrackLangRequireDialectOmitDialectLabel { datatool } { #1 }
      \csuse { DTL \CurrentTrackedRegion LocaleHook }
    }
  }
}
}
}

```

It's best to omit dialect label and region code from search to ensure the search isn't prematurely terminated.

```

\cs_new:Nn \__datatool_require_ldf:
{
  \TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
}

```

Provide interface for locale options. Define options using l3keys interface.

```
\cs_new:Nn \datatool_locale_define_keys:nn
{
  \keys_define:nn { datatool / locale / #1 } { #2 }
}
```

```
\DTLsetLocaleOptions[<parent module(s)>]{<module(s)>}
{<key-val list>}
```

\DTLsetLocaleOptions

User command for setting options for the given locale. The starred version ignores unknown keys.

```
\NewDocumentCommand \DTLsetLocaleOptions { s O{} m m }
{
  \IfBlankTF { #2 }
  {
    \IfBooleanTF { #1 }
    {
      \datatool_set_known_locale_options:nn { #3 } { #4 }
    }
    {
      \datatool_set_locale_options:nn { #3 } { #4 }
    }
  }
  {
    \clist_map_inline:nn { #2 }
    {
      \IfBooleanTF { #1 }
      {
        \datatool_set_known_locale_options:nn { ##1 / #3 } { #4 }
      }
      {
        \datatool_set_locale_options:nn { ##1 / #3 } { #4 }
      }
    }
  }
}
```

Set options (error on unknown):

```
\cs_new:Nn \datatool_set_locale_options:nn
{
  \clist_map_inline:nn { #1 }
  {
    \keys_set:nn { datatool / locale / ##1 } { #2 }
  }
}
```

Set options (ignore unknown):

```
\cs_new:Nn \datatool_set_known_locale_options:nn
```

```

{
  \clist_map_inline:nn { #1 }
  {
    \keys_set_known:nn { datatool / locale / ##1 } { #2 }
  }
}

```

Provided for the ldf files to add to the captions hook to allow the preferred label for language and region (that may be different from the dialect or language label).

```

\tl_new:N \l_datatool_current_language_tl
\tl_new:N \l_datatool_current_region_tl

```

```

\datatool_if_current_lang_region:nn {<lang>}
{<region>}

```

Check if current language and region match *<lang>* and *<region>*.

```

\prg_new_conditional:Npnn \datatool_if_current_lang_region:nn #1 #2
{ T, F, TF }
{
  \tl_if_eq:NnTF \l_datatool_current_language_tl { #1 }
  {
    \tl_if_eq:NnTF \l_datatool_current_region_tl { #2 }
    { \prg_return_true: }
    { \prg_return_false: }
  }
  { \prg_return_false: }
}

```

Check if empty language.

```

\cs_new:Nn \datatool_warn_check_language_empty:nnn
{
  \tl_if_empty:NTF \l_datatool_current_language_tl
  {
    \cs_if_exist:NTF \TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
    {
      \datatool_locale_warn:nn
      { #1 }
      {
        #3 ~
        (check ~ your ~ localisation ~ setting ~ includes ~
        language ~ and ~ region)
      }
    }
  }
  {
    \datatool_locale_warn:nn
    { #1 }
    {
      #2 ~
      (try ~ updating ~ tracklang ~ to ~ at ~ least ~ version ~ 1.6.3)
    }
  }
}

```

```

    }
  }
  { \datatool_locale_warn:nn { #1 } { #3 } }
}

```

Check if token list starts with or is `\l_datatool_current_language_tl` and issue applicable warning.

```

\cs_new:Nn \datatool_warn_check_head_language_empty:nnnn
{
  \tl_if_head_eq_meaning:nNTF { #1 } \l_datatool_current_language_tl
  {
    \datatool_warn_check_language_empty:nnn { #2 } { #3 } { #4 }
  }
  {
    \datatool_locale_warn:nn { #2 } { #4 }
  }
}
\cs_generate_variant:Nn \datatool_warn_check_head_language_empty:nnnn
{ Vnnn }

```

Track each additional locale requested in the `locales/lang` package option. Note that `\TrackLanguageTag` requires the language first but, for `datatool`, allow just the region. This needs to test if the supplied tag has exactly two uppercase characters. If extra information, such as the script is required, then the language part must be included.

```

\clist_map_inline:Nn \l__datatool_extra_locales_clist
{
  \regex_match:nnTF { \A [A-Z]{2} \Z } { #1 }
  {
    \tl_set:Nn \l__datatool_tmpa_tl
    {
      \dtl@message { Adding ~ tracked ~ locale ~ `und-#1 ' }
      \TrackLanguageTag { und-#1 }
    }
    \ForEachTrackedDialect{\l__datatool_dialect_tl}
    {
      \IfTrackedIsoCode
      { \TwoLetterIsoCountryCode }
      { \l__datatool_dialect_tl }
      {
        \dtl@message
        {
          Dialect ~ ` \l__datatool_dialect_tl ' ~ already ~ has ~ region
        }
      }
    }
    {
      \dtl@message
      { Adding ~ region ~ `#1' ~ to ~ locale ~ ` \l__datatool_dialect_tl ' }
      \AddTrackedRegion { #1 } { \l__datatool_dialect_tl }
      \tl_clear:N \l__datatool_tmpa_tl
    }
  }
}

```

```

    }
  }
  \l__datatool_tmpa_tl
}
{
  \TrackIfKnownLanguage { #1 }
  {
    \dtl@message { Adding ~ tracked ~ locale ~ ` #1 ' }
  }
  {
    \datatool_locale_warn:nn
    { datatool-base }
    { Unrecognised ~ language ~ in ~ locale ~ tag ~ ` #1 ' }
  }
}
}

```

datatool@do@load@locales The actual ldf loading needs to be after L^AT_EX3 syntax has been switched off, so define a command for use afterwards.

```

\newcommand{\datatool@do@load@locales}{}
\datatool@load@locales
{
  \renewcommand\datatool@do@load@locales
  {
    \AnyTrackedLanguages
    {
      \cs_if_exist:NF
      \TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
      {
        \datatool_locale_warn:nn
        {
          old ~ version ~ of ~ tracklang: ~ localisation ~ files ~
          may ~ not ~ all ~ load. ~ Upgrade ~ to ~ at ~ least ~
          tracklang ~ v1.6.3 ~ for ~ better ~ support
        }
        \cs_set:Nn \__datatool_require_ldf:
        { \TrackLangRequireDialect }
      }
      \ForEachTrackedDialect { \l__datatool_dialect_tl }
      {
        \RequireDatatoolDialect { \l__datatool_dialect_tl }
      }
    }
  }
}
}

```

Switch off L^AT_EX3 syntax:

```
\ExplSyntaxOff
```

Now load applicable locale files for each tracked dialect.

```
\datatool@do@load@locales
```

`\@dtl@gobbletonil` NB still used by `datatool.sty`. May be removed in future.

```
\def\@dtl@gobbletonil#1\@nil{}
```

`\@dtl@countdigits` NB still used by `datatool-pgfmath.def` May be removed in future.

```
\def\@dtl@countdigits#1#2\relax{%
  \advance\@dtl@tmpcount by 1\relax
  \ifx.#2\relax
    \let\@dtl@countnext=\@gobble
  \else
    \let\@dtl@countnext=\@dtl@countdigits
  \fi
  \@dtl@countnext#2\relax
}
```

2.10 Deprecated

These commands are being phased out and should not be used.

`\dtlenableUTFviii` Deprecated.

```
\newcommand*\dtlenableUTFviii{\booltrue{@dtl@utf8}}
```

`\dtldisableUTFviii` Deprecated.

```
\newcommand*\dtldisableUTFviii{\boolfalse{@dtl@utf8}}
```

`\long@collect@body` Need long versions of `amsmath's \collect@body`. These macros are adapted from the macros defined by `amsmath`. Use `xparse` instead.

```
\long\def\long@collect@body#1{%
  \@envbody{\@xp#1\@xp{\the\@envbody}}%
  \edef\process@envbody{\the\@envbody\@nx\end{\@currentenv}}%
  \@envbody\@emptytoks \def\begin@stack{b}%
  \begingroup
  \@xp\let\csname\@currentenv\endcsname\long@collect@@body
  \edef\process@envbody{\@xp\@nx\csname\@currentenv\endcsname}%
  \process@envbody
}
```

`\long@addto@envbody` Adapted from `amsmath's \addto@envbody`

```
\long\def\long@addto@envbody#1{%
  \toks@{#1}%
  \edef\@dtl@tmp{\the\@envbody\the\toks@}%
  \global\@envbody\@xp{\@dtl@tmp}%
}
```

`\long@collect@@body` Adapted from `amsmath`'s `\collect@body`

```

\long\def\long@collect@@body#1\end#2{%
  \protected@edef\begin@stack{%
    \long@push@begins#1\begin\end \@xp\@gobble\begin@stack
  }%
  \ifx\@empty\begin@stack
    \endgroup
    \@checkend{#2}%
    \long@addto@envbody{#1}%
  \else
    \long@addto@envbody{#1\end{#2}}%
  \fi
  \process@envbody
}

```

`\long@push@begins` Adapted from `amsmath`'s `\push@begins`

```

\long\def\long@push@begins#1\begin#2{%
  \ifx\end#2\else b\@xp\long@push@begins\fi
}

```

`\dtl@ifsingle{<arg>}{<true part>}{<false part>}`

`\dtl@ifsingle`

If there is only one object in `<arg>` (without expansion) do `<true part>`, otherwise do false part. This now just uses the new `LATEX3` command to test for a single token. Old versions of `glossaries` use `\dtl@ifsingle`.

```

\ExplSyntaxOn
\newcommand \dtl@ifsingle [ 3 ]
{
  \tl_if_single_token:nTF { #1 } { #2 } { #3 }
}
\ExplSyntaxOff

```

`\@dtl@ifsingle`

Count registers to store character codes:

```

\newcount \dtl@codeA
\newcount \dtl@codeB

```

`\@listelement@outofrange`

```

\newcommand{\@dtl@listelement@outofrange}[1]{%
  \PackageWarning{datatool-base}{List index `\'number#1' out of range}%
}

```

`\dtl@sortlist` I made a bit of a blunder here. `\dtl@sortlist` was supposed to work with commands like `\dtlcompare`, but those commands require three arguments, the first being the register in which to store the result. This contradicts the requirements of `\dtl@sortlist`. The “bug fix” in v2.26 fixed it to work with commands like

`\dtlcompare`, but that broke the documented design (which breaks the glossaries package). The other problem is that `\dtl@insertinto` actually sorts in the reverse order. So v2.27 undoes the change from v2.26 to ensure backward compatibility and provides an alternative user-level command `\dtl@sortlist`, that's designed to work with the three-argument handler commands like `\dtlcompare`.

```
\dtl@sortlist{<list>}{<criteria cmd>}
```

Performs an insertion sort on `<list>`, where `<criteria cmd>` is a macro which takes two arguments `<a>` and ``. `<criteria cmd>` must set the count register `\dtl@sortresult` to either `-1` (`` less than `<a>`), `0` (`<a>` is equal to ``) or `1` (`` is greater than `<a>`).

DEPRECATED. To be removed. (NB used by `glossaries.sty`)

```
\newcommand{\dtl@sortlist}[2]{%
\def\dtl@sortedlist{}%
\@for\dtl@currentrow:=#1\do{%
\expandafter\dtl@insertinto\expandafter
  {\dtl@currentrow}{\dtl@sortedlist}{#2}%
\@endforfalse}%
\let#1=\dtl@sortedlist
}
```

```
\dtl@insertinto{<element>}{<sorted-list>}{<criteria
cmd>}
```

`\dtl@insertinto`

Inserts `<element>` into the sorted list `<sorted-list>` according to the criteria given by `<criteria cmd>` (see above.) DEPRECATED. To be removed. NB used by `glossaries.sty`

```
\newcommand{\dtl@insertinto}[3]{%
\def\dtl@newsortedlist{}%
\dtl@insertdonefalse
\@for\dtl@srtelement:=#2\do{%
\if\dtl@insertdone
\expandafter\toks@\expandafter{\dtl@srtelement}%
\edef\dtl@newstuff{{\the\toks@}}%
\else
\expandafter#3\expandafter{\dtl@srtelement}{#1}%

\ifnum\dtl@sortresult<0\relax
\expandafter\toks@\expandafter{\dtl@srtelement}%
\dtl@toks{#1}%
\edef\dtl@newstuff{{\the\dtl@toks},{\the\toks@}}%
\dtl@insertdone true
\else
\expandafter\toks@\expandafter{\dtl@srtelement}%
\edef\dtl@newstuff{{\the\toks@}}%
\fi
\fi
}
```

```

\ifdefempty{\@dtl@newsortedlist}%
{%
  \expandafter\toks@\expandafter{\@dtl@newstuff}%
  \edef\@dtl@newsortedlist{\the\toks@}%
}%
{%
  \expandafter\toks@\expandafter{\@dtl@newsortedlist}%
  \expandafter\@dtl@toks@\expandafter{\@dtl@newstuff}%
  \edef\@dtl@newsortedlist{\the\toks@,\the\@dtl@toks}%
}%
\@endforfalse
}%
\ifdefempty{\@dtl@newsortedlist}%
{%
  \@dtl@toks{#1}%
  \edef\@dtl@newsortedlist{{\the\@dtl@toks}}%
}%
{%
  \if@dtl@insertdone
  \else
    \expandafter\toks@\expandafter{\@dtl@newsortedlist}%
    \@dtl@toks{#1}%
    \edef\@dtl@newsortedlist{\the\toks@,{\the\@dtl@toks}}%
  \fi
}%
\global\let#2=\@dtl@newsortedlist
}

```

`\dtl@ifsingleorUTFviii` Test if the argument is a single token or, if utf8 setting on, a two-octet UTF-8 character. This only tests for two octet UTF-8 characters.

```

\ExplSyntaxOn
\newcommand \dtl@ifsingleorUTFviii [ 3 ]
{
  \tl_if_single_token:nTF { #1 }
  { #2 }
  {
    \ifbool{@dtl@utf8}
    {
      \tl_if_head_is_N_type:nTF { #1 }
      {
        \__datatool_isheadactivechar:w#1\q_stop
        {
          \ifnum\tl_count_tokens:n { #1 } = 2
            \expandafter \__datatool_isheadUTFviiiitwooctets \expandafter
            { \__datatool_xpactiveheadchar }
            { #2 }
            { #3 }
          \else
            #3
          \fi
        }
      }
    }
  }
}

```

```

    }
    { #3 }
  }
  { #3 }
}
{ #3 }
}
}

```

Tests if the argument starts with an active character.

```

\catcode\@13\relax
\cs_new:Npn \__datatool_isheadactivechar:w #1 #2 \q_stop #3 #4
{
  \tl_if_head_eq_catcode:nNTF { #1 } @
  { \tl_set:No \__datatool_xpactiveheadchar { #1 } #3 }
  { #4 }
}
\catcode\@11\relax

```

Tests if the first argument starts with \UTFviii@two@octets.

```

\cs_new:Npn \__datatool_isheadUTFviiiitwooctets #1 #2 #3
{
  \tl_if_head_eq_meaning:nNTF { #1 } \UTFviii@two@octets
  { #2 } { #3 }
}
\ExplSyntaxOff

```

\dtl@if@two@octets Check if argument starts with \UTFviii@two@octets Deprecated.

```

\def\dtl@if@two@octets#1#2\dtl@end@if@two@octets#3#4{%
  \ifbool{@dtl@utf8}
  {%
    \ifx\UTFviii@two@octets#1\relax
      #3%
    \else
      #4%
    \fi
  }%
  {%
    #4%
  }%
}

```

\dtl@getfirst@UTFviii Deprecated.

```

\def\dtl@getfirst@UTFviii#1#2#3\end@dtl@getfirst@UTFviii{%
  \def\dtl@first{#1#2}%
  \ifx\@nil#3\relax
    \def\dtl@rest{}%
  \else
    \expandafter\def\expandafter\dtl@rest\expandafter{\@dtl@firsttonil#3}%
  \fi
}

```

```
}
```

```
\@dtl@firsttonil
```

```
\def\@dtl@firsttonil#1\@nil{#1}
```

```
\@dtlgetfirstchar{<text>}{<cs1>}{<cs2>}
```

```
\@dtlgetfirstchar
```

Stores the first character in $\langle text \rangle$ in $\langle cs1 \rangle$ and the remainder in $\langle cs2 \rangle$. Largely redundant, but can be used to obtain the letter group of a UTF-8 string.

```
\ExplSyntaxOn
```

```
\newcommand{\@dtlgetfirstchar}[3]{
```

```
  \tl_if_empty:nTF { #1 }
```

```
  { \cs_set:Nn #2 {} \cs_set:Nn #3 {} }
```

```
  {
```

```
    \tl_if_single_token:nTF { #1 }
```

```
    { \cs_set:Nn #2 { #1 } \cs_set:Nn #3 {} }
```

```
    {
```

```
      \edef #2 { \tl_head:n { #1 } }
```

```
      \edef #3 { \tl_tail:n { #1 } }
```

```
      \ifbool{@dtl@utf8}
```

```
      {
```

```
        \tl_if_head_is_N_type:nTF { #1 }
```

```
        {
```

```
          \__datatool_isheadactivechar:w#1\q_stop
```

```
          {
```

```
            \expandafter \__datatool_isheadUTFviiiitwooctets \expandafter
```

```
            { \__datatool_xpactiveheadchar }
```

```
            {
```

```
              \tl_put_right:Nx #2 { \tl_head:N #3 }
```

```
              \edef #3 { \tl_tail:N #3 }
```

```
            }
```

```
          }
```

```
        }
```

```
      }
```

```
    }
```

```
  }
```

```
{ }
```

```
}
```

```
}
```

```
}
```

```
}
```

```
\ExplSyntaxOff
```

`\dtl@getfirst` Gets the first object, and stores in `\dtl@first`. The remainder is stored in `\dtl@rest`. Deprecated.

```
\def\dtl@getfirst#1#2\end@dtl@getfirst{%
```

```
  \dtlgetfirstchar{#1#2}{\dtl@first}{\dtl@rest}%
```

```
%}
```

`\dtl@setcharcode{<c>}{<count register>}`

`\dtl@setcharcode`

Sets *<count register>* to the character code of *<c>*, or to -1 if *<c>* is empty, or to 0 if *<c>* is a control sequence, unless *<c>* is either `\space` or `|` in which case it sets *<count register>* to the character code of the space character. Largely redundant. Likely to be removed in future.

```
\ExplSyntaxOn
\newcommand*{\dtl@setcharcode}[2]{%
  \exp_args:Nx \__datatool_setcharcode:nN { \text_purify:n { #1 } } #2
}
\cs_new:Npn \__datatool_setcharcode:nN #1#2
{
  \tl_if_empty:nTF { #1 }
  { #2=-1\relax }
  {
    \tl_if_head_is_space:nTF { #1 }
    { #2=32\relax }
    {
      \tl_if_head_eq_catcode:nNTF { #1 } \relax
      { #2=0\relax }
      {
        \tl_if_single_token:nTF { #1 }
        { \dtlsetcharcode{#1}{#2} }
        {
          \exp_args:Nx \dtlsetcharcode { \tl_head:n { #1 } } {#2}
          \ifbool{@dtl@utf8}
          {
            \ifnum#2>127
              \dtlsetUTFviiiicharcode { #1 }{ #2 }
            \fi
          }
          { }
        }
      }
    }
  }
}
\ExplSyntaxOff
```

`\dtlsetcharcode` Set the code for the given character. May be redefined by user for non-UTF8 encodings (e.g. Latin-1). Deprecated.

```
\newcommand*{\dtlsetcharcode}[2]{#2=`#1\relax}
```

`\dtlsetlccharcode` Set the lowercase code for the given character. May be redefined by user for non-UTF8 encodings (e.g. Latin-1). Deprecated.

```
\newcommand*{\dtlsetlccharcode}[2]{#2=\lccode`#1\relax}
```

`\dtlsetUTFviiiicharcode` Default behaviour is to set all UTF8 characters to code 64 (before A). This will need to be redefined according to the relevant alphabet. Deprecated.

```
\newcommand*\dtlsetUTFviiiicharcode[2]{\dtlsetdefaultUTFviiiicharcode{#1}{#2}}
```

`\dtlsetUTFviiilccharcode` Default behaviour is to set all UTF8 characters to code 96 (before a). This will need to be redefined according to the relevant alphabet. Deprecated.

```
\newcommand*\dtlsetUTFviiilccharcode[2]{\dtlsetdefaultUTFviiilccharcode{#1}{#2}}
```

`\dtlsetdefaultUTFviiiicharcode` Default codes for some supplemental Latin characters. Deprecated.

```
\newcommand*\dtlsetdefaultUTFviiiicharcode[2]{%
\ifboolexpr
{
  test {\ifstrequal{#1}{À}}
  or test {\ifstrequal{#1}{Á}}
  or test {\ifstrequal{#1}{Â}}
  or test {\ifstrequal{#1}{Ã}}
  or test {\ifstrequal{#1}{Ä}}
}%
{%
#2=`A\relax
}%
}%
\ifstrequal{#1}{Ç}%
{%
#2=`C\relax
}%
}%
\ifboolexpr
{
  test {\ifstrequal{#1}{È}}
  or test {\ifstrequal{#1}{É}}
  or test {\ifstrequal{#1}{Ê}}
  or test {\ifstrequal{#1}{Ë}}
}%
{%
#2=`E\relax
}%
}%
\ifboolexpr
{
  test {\ifstrequal{#1}{Ì}}
  or test {\ifstrequal{#1}{Í}}
  or test {\ifstrequal{#1}{Î}}
  or test {\ifstrequal{#1}{Ï}}
}%
{%
#2=`I\relax
}%
}%
```

```

\ifstrequal{#1}{Ñ}%
{%
  #2=`N\relax
}%
{%
\ifboolexpr
{
  test {\ifstrequal{#1}{Ò}}
  or test {\ifstrequal{#1}{Ó}}
  or test {\ifstrequal{#1}{Ô}}
  or test {\ifstrequal{#1}{Õ}}
  or test {\ifstrequal{#1}{Ö}}
}%
{%
  #2=`O\relax
}%
{%
\ifboolexpr
{
  test {\ifstrequal{#1}{Û}}
  or test {\ifstrequal{#1}{Ü}}
  or test {\ifstrequal{#1}{Ý}}
  or test {\ifstrequal{#1}{Û}}
}%
{%
  #2=`U\relax
}%
{%
\ifstrequal{#1}{Ý}%
{%
  #2=`Y\relax
}%
{%
\ifboolexpr
{
  test {\ifstrequal{#1}{à}}
  or test {\ifstrequal{#1}{á}}
  or test {\ifstrequal{#1}{â}}
  or test {\ifstrequal{#1}{ã}}
  or test {\ifstrequal{#1}{ä}}
}%
{%
  #2=`a\relax
}%
{%
\ifstrequal{#1}{ç}%
{%
  #2=`c\relax
}%
{%

```

```

\ifboolexpr
{
  test {\ifstrequal{#1}{è}}
  or test {\ifstrequal{#1}{é}}
  or test {\ifstrequal{#1}{ê}}
  or test {\ifstrequal{#1}{ë}}
}%
{%
  #2=`e\relax
}%
{%
\ifboolexpr
{
  test {\ifstrequal{#1}{ì}}
  or test {\ifstrequal{#1}{í}}
  or test {\ifstrequal{#1}{î}}
  or test {\ifstrequal{#1}{ï}}
}%
{%
  #2=`i\relax
}%
{%
\ifstrequal{#1}{ñ}%
{%
  #2=`n\relax
}%
{%
\ifboolexpr
{
  test {\ifstrequal{#1}{ò}}
  or test {\ifstrequal{#1}{ó}}
  or test {\ifstrequal{#1}{ô}}
  or test {\ifstrequal{#1}{õ}}
  or test {\ifstrequal{#1}{ö}}
}%
{%
  #2=`o\relax
}%
{%
\ifboolexpr
{
  test {\ifstrequal{#1}{ù}}
  or test {\ifstrequal{#1}{ú}}
  or test {\ifstrequal{#1}{û}}
  or test {\ifstrequal{#1}{ü}}
}%
{%
  #2=`u\relax
}%
{%

```



```

\ExplSyntaxOn
\newcommand \DTLundLocaleHook
{
  \DTLresetLanguage
  \tl_set:Nn \l_datatool_current_language_tl { und }
}
\ExplSyntaxOff
Add to captions hook.
\TrackLangAddToCaptions{\DTLundLocaleHook}

```

4 datatool-latin1.ldf

ISO-8859-1 (Latin-1) strings.

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesFile{datatool-latin1.ldf}[2025/04/03 v3.4 (NLCT)]
\ExplSyntaxOn
\datatool_set_currency_sign_from_charcode:ne
{ cent } { "A2 }
\datatool_set_currency_sign_from_charcode:nn
{ pound } { "A3 }
\datatool_set_currency_sign_from_charcode:nn
{ currency } { "A4 }
\datatool_set_currency_sign_from_charcode:nn
{ yen } { "A5 }
\datatool_set_symbol_from_charcode:nn
{ middot } { "B7 }
\ExplSyntaxOff

```

No available ISO-8859-1 characters to support other commands

5 datatool-utf8.ldf

UTF-8 strings.

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesFile{datatool-utf8.ldf}[2025/04/03 v3.4 (NLCT)]
\ExplSyntaxOn

```

Common numeric and currency formatting symbols.

```

\datatool_set_currency_sign:nn { cent } { ¢ }
\datatool_set_currency_sign:nn { pound } { £ }
\datatool_set_currency_sign:nn { currency } { ¤ }
\datatool_set_currency_sign:nn { yen } { ¥ }
\datatool_set_symbol:nn { middot } { · }
\datatool_set_currency_sign:nn { florin } { ₣ }
\datatool_set_currency_sign:nn { baht } { ฿ }
\datatool_set_currency_sign:nn { ecu } { ₠ }
\datatool_set_currency_sign:nn { colonsign } { ₤ }

```

```

\datatool_set_currencysign:nn { cruzerio } { ₣ }
\datatool_set_currencysign:nn { frenchfranc } { ₣ }
\datatool_set_currencysign:nn { lira } { ₺ }
\datatool_set_currencysign:nn { mill } { ₯ }
\datatool_set_currencysign:nn { naira } { ₦ }
\datatool_set_currencysign:nn { peseta } { ₧ }
\datatool_set_currencysign:nn { rupee } { ₹ }
\datatool_set_currencysign:nn { won } { ₩ }
\datatool_set_currencysign:nn { shekel } { ₪ }
\datatool_set_currencysign:nn { dong } { ₫ }
\datatool_set_currencysign:nn { euro } { € }
\datatool_set_currencysign:nn { kip } { ₭ }
\datatool_set_currencysign:nn { tugrik } { ₮ }
\datatool_set_currencysign:nn { drachma } { ₯ }
\datatool_set_currencysign:nn { germanpenny } { ¢ }
\datatool_set_currencysign:nn { peso } { ₱ }
\datatool_set_currencysign:nn { guarani } { ₲ }
\datatool_set_currencysign:nn { austral } { ₳ }
\datatool_set_currencysign:nn { hryvnia } { ₴ }
\datatool_set_currencysign:nn { cedi } { ₵ }
\datatool_set_currencysign:nn { livretournois } { ₤ }
\datatool_set_currencysign:nn { spesmiilo } { ₸ }
\datatool_set_currencysign:nn { tenge } { ₸ }
\datatool_set_currencysign:nn { indianrupee } { ₹ }
\datatool_set_currencysign:nn { turkishlira } { ₺ }
\datatool_set_currencysign:nn { nordicmark } { ₰ }
\datatool_set_currencysign:nn { manat } { ₼ }
\datatool_set_currencysign:nn { ruble } { ₸ }
\datatool_set_currencysign:nn { lari } { ₾ }
\datatool_set_currencysign:nn { bitcoin } { ₿ }
\datatool_set_currencysign:nn { som } { ₮ }

```

Regular expression to match apostrophe.

```

\regex_set:Nn \l_datatool_apos_regex { \' | ' }
\ExplSyntaxOff

```

6 datatool-l3fp.sty

Definitions of fixed-point commands that use LaTeX3 commands.

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesFile{datatool-l3fp.def}[2025/04/03 v3.4 (NLCT)]

```

This file provides commands that use l3fp interfaces. The commands defined here match the name and syntax of the commands in the alternative `datatool-(processor).def` files.

6.1 Comparisons

`\dtlifnumeq`

```
\dtlifnumeq{<num1>}{<num2>}{<true part>}{<false part>}
```

Does *<true part>* if $\langle num1 \rangle = \langle num2 \rangle$, otherwise does *<false part>*.

```
\ExplSyntaxOn
\newcommand*{\dtlifnumeq}[4]{%
  \fp_compare:nNnTF { #1 } = { #2 } { #3 } { #4 }
}
```

`\dtlifnumlt`

```
\dtlifnumlt{<num1>}{<num2>}{<true part>}{<false part>}
```

Does *<true part>* if $\langle num1 \rangle < \langle num2 \rangle$, otherwise does *<false part>*.

```
\newcommand*{\dtlifnumlt}[4]{%
  \fp_compare:nNnTF { #1 } < { #2 } { #3 } { #4 }
}
```

`\dtlifnumgt`

```
\dtlifnumgt{<num1>}{<num2>}{<true part>}{<false part>}
```

Does *<true part>* if $\langle num1 \rangle > \langle num2 \rangle$, otherwise does *<false part>*.

```
\newcommand*{\dtlifnumgt}[4]{%
  \fp_compare:nNnTF { #1 } > { #2 } { #3 } { #4 }
}
```

`\dtlifnumopenbetween`

```
\dtlifnumopenbetween{<num>}{<min>}{<max>}{<true part>}
{<false part>}
```

Determines if $\langle min \rangle < \langle num \rangle < \langle max \rangle$.

```
\newcommand*{\dtlifnumopenbetween}[5]{%
  \fp_compare:nTF { #2 < #1 < #3 }
    { #4 } { #5 }
}
```

`\dtlifnumclosedbetween`

```
\dtlifnumclosedbetween{<num>}{<min>}{<max>}{<true part>}
{<false part>}
```

Determines if $\langle min \rangle \leq \langle num \rangle \leq \langle max \rangle$.

```
\newcommand*{\dtlifnumclosedbetween}[5]{%
  \fp_compare:nTF { #2 <= #1 <= #3 }
    { #4 } { #5 }
}
```

```

\fp_compare:nTF { #2 <= #1 <= #3 }
  { #4 } { #5 }
}

```

6.2 Functions

`\dtladd`

```
\dtladd{<cs>}{<num1>}{<num2>}
```

Adds two numbers and stores the result in `<cs>`.

```

\NewDocumentCommand \dtladd { m m m }
{
  \fp_set:Nn \l__datatool_tmpa_fp { #2 + #3 }
  \tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}

```

`\dtladdall`

```
\dtladdall{<cs>}{<num list>}
```

Defines `<cs>` to the sum of all the values in the comma-separated list of numbers.

```

\NewDocumentCommand \dtladdall { m m }
{
  \fp_zero:N \l__datatool_tmpa_fp
  \exp_args:Nx \clist_map_inline:nn { #2 }
  { \fp_add:Nn \l__datatool_tmpa_fp { ##1 } }
  \tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}

```

`\dtlsub`

```
\dtlsub{<cs>}{<num1>}{<num2>}
```

Subtracts two numbers and stores the result in `<cs>`.

```

\NewDocumentCommand \dtlsub { m m m }
{
  \fp_set:Nn \l__datatool_tmpa_fp { #2 - #3 }
  \tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}

```

`\dtlmul`

```
\dtlmul{<cs>}{<num1>}{<num2>}
```

Multiplies two numbers and stores the result in `<cs>`.

```

\NewDocumentCommand \dtlmul { m m m }
{
  \fp_set:Nn \l__datatool_tmpa_fp { #2 * #3 }
  \tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}

```

`\dtldiv`

`\dtldiv{<cs>}{<num1>}{<num2>}`

Divides two numbers and stores the result in `<cs>`.

```
\NewDocumentCommand \dtldiv { m m m }
{
  \fp_set:Nn \l__datatool_tmpa_fp { #2 / #3 }
  \tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}
```

`\dtlsqrt`

`\dtlsqrt{<cs>}{<num>}`

Square root number and store the result in `<cs>`.

```
\NewDocumentCommand \dtlsqrt { m m }
{
  \fp_set:Nn \l__datatool_tmpa_fp { sqrt ( #2 ) }
  \tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}
```

`\dtlroot`

`\dtlroot{<cs>}{<num>}{<n>}`

Nth root number and store the result in `<cs>`.

```
\NewDocumentCommand \dtlroot { m m m }
{
  \exp_args:Nx \tl_if_eq:nnTF { #3 } { 2 }
  {
    \fp_set:Nn \l__datatool_tmpa_fp { sqrt ( #2 ) }
    \tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
  }
  {
    \fp_set:Nn \l__datatool_tmpa_fp { ( #2 ) ^ ( 1 / ( #3 ) ) }
    \tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
  }
}
```

`\dtlround`

`\dtlround{<cs>}{<num>}{<dp>}`

Rounds `<num>` to `<dp>` decimal places and stores the result in `<cs>`.

```
\NewDocumentCommand \dtlround { m m m }
{
  \fp_set:Nn \l__datatool_tmpa_fp { round ( #2, #3 ) }
  \tl_set:Nx #1 { \fp_to_decimal:N \l__datatool_tmpa_fp }
  \datatool_pad_trailing_zeros:Nn #1 { #3 }
}
```

`\dtltrunc`

`\dtltrunc{<cs>}{<num>}{<dp>}`

Truncates $\langle num \rangle$ to $\langle dp \rangle$ decimal places and stores the result in $\langle cs \rangle$.

```
\NewDocumentCommand \dtltrunc { m m m }
{
  \fp_set:Nn \l__datatool_tmpa_fp { trunc ( #2, #3 ) }
  \tl_set:Nx #1 { \fp_to_decimal:N \l__datatool_tmpa_fp }
  \datatool_pad_trailing_zeros:Nn #1 { #3 }
}
```

`\dtlclip`

`\dtlclip{<cs>}{<num>}`

Removes redundant trailing zeros from $\langle num \rangle$ and stores the result in $\langle cs \rangle$.

```
\NewDocumentCommand \dtlclip { m m }
{
  \fp_set:Nn \l__datatool_tmpa_fp { #2 }
  \tl_set:Nx #1 { \fp_to_decimal:N \l__datatool_tmpa_fp }
}
```

`\dtlmin`

`\dtlmin{<cs>}{<num1>}{<num2>}`

Defines $\langle cs \rangle$ to the smaller of the two numbers.

```
\NewDocumentCommand \dtlmin { m m m }
{
  \fp_set:Nn \l__datatool_tmpa_fp { min ( #2, #3 ) }
  \tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}
```

`\dtlminall`

`\dtlminall{<cs>}{<num list>}`

Defines $\langle cs \rangle$ to the minimum in the comma-separated list of numbers.

```
\NewDocumentCommand \dtlminall { m m }
{
  \fp_set:Nn \l__datatool_tmpa_fp { min ( #2 ) }
  \tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}
```

`\dtlmax`

`\dtlmax{<cs>}{<num1>}{<num2>}`

Defines $\langle cs \rangle$ to the larger of the two numbers.

```
\NewDocumentCommand \dtlmax { m m m }
{
```

```

\fp_set:Nn \l__datatool_tmpa_fp { max ( #2, #3 ) }
\tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}

```

\dtlmaxall

`\dtlmaxall{<cs>}{<num list>}`

Defines <cs> to the maximum in the comma-separated list of numbers.

```

\NewDocumentCommand \dtlmaxall { m m }
{
\fp_set:Nn \l__datatool_tmpa_fp { max ( #2 ) }
\tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}

```

\dtlabs

`\dtlabs{<cs>}{<num>}`

Defines <cs> to the absolute value of <num>.

```

\NewDocumentCommand \dtlabs { m m }
{
\fp_set:Nn \l__datatool_tmpa_fp { abs ( #2 ) }
\tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}

```

\dtlneg

`\dtlneg{<cs>}{<num>}`

Defines <cs> to the negative of <num>.

```

\NewDocumentCommand \dtlneg { m m }
{
\fp_set:Nn \l__datatool_tmpa_fp { - ( #2 ) }
\tl_set:Nx #1 { \fp_use:N \l__datatool_tmpa_fp }
}

```

\dtlmeanforall

`\dtlmeanforall{<cs>}{<num list>}`

Defines <cs> to the mean (average) of all the values in the comma-separated list of numbers.

```

\NewDocumentCommand \dtlmeanforall { m m }
{
\fp_zero:N \l__datatool_total_fp
\int_zero:N \l__datatool_count_int
\exp_args:No \clist_map_inline:nn { #2 }
{
\int_incr:N \l__datatool_count_int
\fp_add:Nn \l__datatool_total_fp { ##1 }
}
}

```

```

    }
    \fp_set:Nn \l__datatool_mean_fp
      { \l__datatool_total_fp / \l__datatool_count_int }
    \tl_set:Nx #1 { \fp_use:N \l__datatool_mean_fp }
  }

```

`\dtlvarianceforall[⟨mean⟩]{⟨cs⟩}{⟨num list⟩}`

`\dtlvarianceforall`

Defines `⟨cs⟩` to the variance of all the values in the comma-separated list of numbers. If the mean value has already been calculated, it can be supplied in the optional argument.

```

\NewDocumentCommand \dtlvarianceforall { o m m }
{
  \IfNoValueTF { #1 }
  {
    \fp_zero:N \l__datatool_total_fp
    \int_zero:N \l__datatool_count_int
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \int_incr:N \l__datatool_count_int
      \fp_add:Nn \l__datatool_total_fp { ##1 }
    }
    \fp_set:Nn \l__datatool_mean_fp
      { \l__datatool_total_fp / \l__datatool_count_int }
    \fp_zero:N \l__datatool_total_fp
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \fp_set:Nn \l__datatool_tmpa_fp
        { ##1 - \l__datatool_mean_fp }
      \fp_add:Nn \l__datatool_total_fp
        { \l__datatool_tmpa_fp * \l__datatool_tmpa_fp }
    }
  }
  {
    \fp_set:Nn { \l__datatool_mean_fp } { #1 }
    \fp_zero:N \l__datatool_total_fp
    \int_zero:N \l__datatool_count_int
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \int_incr:N \l__datatool_count_int
      \fp_set:Nn \l__datatool_tmpa_fp
        { ##1 - \l__datatool_mean_fp }
      \fp_add:Nn \l__datatool_total_fp
        { \l__datatool_tmpa_fp * \l__datatool_tmpa_fp }
    }
  }
  \fp_set:Nn \l__datatool_tmpa_fp
    { \l__datatool_total_fp / \l__datatool_count_int }
  \tl_set:Nx #2 { \fp_use:N \l__datatool_tmpa_fp }
}

```

}

`\dtlsdforall[mean]{cs}{num list}`

`\dtlsdforall`

Defines *cs* to the standard deviation of all the values in the comma-separated list of numbers. If the mean value has already been calculated, it can be supplied in the optional argument.

```
\NewDocumentCommand \dtlsdforall { o m m }
{
  \IfNoValueTF { #1 }
  {
    \fp_zero:N \l__datatool_total_fp
    \int_zero:N \l__datatool_count_int
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \int_incr:N \l__datatool_count_int
      \fp_add:Nn \l__datatool_total_fp { ##1 }
    }
    \fp_set:Nn \l__datatool_mean_fp
    { \l__datatool_total_fp / \l__datatool_count_int }
    \fp_zero:N \l__datatool_total_fp
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \fp_set:Nn \l__datatool_tmpa_fp
      { ##1 - \l__datatool_mean_fp }
      \fp_add:Nn \l__datatool_total_fp
      { \l__datatool_tmpa_fp * \l__datatool_tmpa_fp }
    }
  }
  {
    \fp_set:Nn \l__datatool_mean_fp { #1 }
    \fp_zero:N \l__datatool_total_fp
    \int_zero:N \l__datatool_count_int
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \int_incr:N \l__datatool_count_int
      \fp_set:Nn \l__datatool_tmpa_fp { ##1 - \l__datatool_mean_fp }
      \fp_add:Nn \l__datatool_total_fp
      { \l__datatool_tmpa_fp * \l__datatool_tmpa_fp }
    }
  }
  \fp_set:Nn \l__datatool_tmpa_fp
  { sqrt ( \l__datatool_total_fp / \l__datatool_count_int ) }
  \tl_set:Nx #2 { \fp_use:N \l__datatool_tmpa_fp }
}
\ExplSyntaxOff
```

7 datatool-lua.def

Definitions of fixed-point commands that use Lua. Only for use with Lua^AT_EX.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesFile{datatool-lua.def}[2025/04/03 v3.4 (NLCT)]
```

This file provides commands that use `\directlua`. The commands defined here match the name and syntax of the commands in the alternative `datatool-(processor).def` files.

7.1 Comparisons

`\dtlifnumeq`

```
\dtlifnumeq{<num1>}{<num2>}{<true part>}{<false
part>}
```

Does *<true part>* if $\langle num1 \rangle = \langle num2 \rangle$, otherwise does *<false part>*.

```
\newcommand*{\dtlifnumeq}[4]{%
  \ifnum\directlua{if #1==#2 then tex.print(1) else tex.print(0) end}=1
  #3%
  \else
  #4%
  \fi
}
```

`\dtlifnumlt`

```
\dtlifnumlt{<num1>}{<num2>}{<true part>}{<false
part>}
```

Does *<true part>* if $\langle num1 \rangle < \langle num2 \rangle$, otherwise does *<false part>*.

```
\newcommand*{\dtlifnumlt}[4]{%
  \ifnum\directlua{if #1<#2 then tex.print(1) else tex.print(0) end}=1
  #3%
  \else
  #4%
  \fi
}
```

`\dtlifnumgt`

```
\dtlifnumgt{<num1>}{<num2>}{<true part>}{<false
part>}
```

Does *<true part>* if $\langle num1 \rangle > \langle num2 \rangle$, otherwise does *<false part>*.

```
\newcommand*{\dtlifnumgt}[4]{%
  \ifnum\directlua{if #1>#2 then tex.print(1) else tex.print(0) end}=1
  #3%
  \else
  #4%
  \fi
}
```

```

#4%
\fi
}

```

```

\dtlifnumopenbetween{<num>}{<min>}{<max>}{<true part>}
{<false part>}

```

\dtlifnumopenbetween

Determines if $\langle min \rangle < \langle num \rangle < \langle max \rangle$.

```

\newcommand*{\dtlifnumopenbetween}[5]{%
\ifnum\directlua{if #2 < #1 and #1 < #3 then tex.print(1) else tex.print(0) end}=1
#4%
\else
#5%
\fi
}

```

```

\dtlifnumclosedbetween{<num>}{<min>}{<max>}{<true
part>}{<false part>}

```

\dtlifnumclosedbetween

Determines if $\langle min \rangle \leq \langle num \rangle \leq \langle max \rangle$.

```

\newcommand*{\dtlifnumclosedbetween}[5]{%
\ifnum\directlua{if #2 <= #1 and #1 <= #3 then tex.print(1) else tex.print(0) end}=1
#4%
\else
#5%
\fi
}

```

7.2 Functions

```

\dtladd{<cs>}{<num1>}{<num2>}

```

\dtladd

Adds two numbers and stores the result in $\langle cs \rangle$.

```

\NewDocumentCommand\dtladd{mmm}{%
\edef#1{\directlua{ tex.print(#2+(#3)) }}%
}

```

```

\dtladdall{<cs>}{<num list>}

```

\dtladdall

Adds all numbers and stores the result in $\langle cs \rangle$.

```

\NewDocumentCommand\dtladdall{mm}{%
\edef#1{\directlua{
x = 0;

```

```

    array = { #2 };
    for key,val in ipairs(array) do
      x = x + val;
    end
    tex.print(x);
  }}%
}

```

`\dtlsub{<cs>}{<num1>}{<num2>}`

`\dtlsub` Subtracts two numbers and stores the result in `<cs>`.

```

\NewDocumentCommand\dtlsub{mmm}{%
  \edef#1{\directlua{ tex.print(#2-(#3)) }}%
}

```

`\dtlmul{<cs>}{<num1>}{<num2>}`

`\dtlmul` Multiplies two numbers and stores the result in `<cs>`.

```

\NewDocumentCommand\dtlmul{mmm}{%
  \edef#1{\directlua{ tex.print(#2*#3) }}%
}

```

`\dtldiv{<cs>}{<num1>}{<num2>}`

`\dtldiv` Divides two numbers and stores the result in `<cs>`.

```

\NewDocumentCommand\dtldiv{mmm}{%
  \edef#1{\directlua{ tex.print(#2/#3) }}%
}

```

`\dtlsqrt{<cs>}{<num>}`

`\dtlsqrt` Square root number and store the result in `<cs>`.

```

\NewDocumentCommand\dtlsqrt{mm}{%
  \edef#1{\directlua{ tex.print(math.sqrt(#2)) }}%
}

```

`\dtlroot{<cs>}{<num>}{<n>}`

`\dtlroot` Nth root number and store the result in `<cs>`.

```

\NewDocumentCommand\dtlroot{mmm}{%
  \edef#1{\directlua{ tex.print((#2)^(1/(#3))) }}%
}

```

`\dtlround`

`\dtlround{<cs>}{<num>}{<dp>}`

Rounds `<num>` to `<dp>` decimal places and stores the result in `<cs>`.

```
\NewDocumentCommand\dtlround{mmm}{%
  \edef#1{"\@percentchar0.\number#3f", #2}%
  \edef#1{\directlua{ tex.print(string.format(#1)) }}%
}
```

`\dtltrunc`

`\dtltrunc{<cs>}{<num>}{<dp>}`

Truncates `<num>` to `<dp>` decimal places and stores the result in `<cs>`.

```
\NewDocumentCommand\dtltrunc{mmm}{%
  \edef#1{\directlua{
    local m = 10^(#3);
    tex.print(string.format("\@percentchar.#3f", math.floor(#2 * m)/m))
  }}%
}
```

`\dtlclip`

`\dtlclip{<cs>}{<num>}`

Removes redundant trailing zeros from `<num>` and stores the result in `<cs>`.

```
\NewDocumentCommand\dtlclip{mm}{%
  \edef#1{\directlua{
    local s = "#2";
    tex.print(s:match("^(\\@percentchar d*\\@percentchar.?0?\\@percentchar d-
)0*$"))
  }}%
}
```

`\dtlmin`

`\dtlmin{<cs>}{<num1>}{<num2>}`

Defines `<cs>` to the smaller of the two numbers.

```
\NewDocumentCommand\dtlmin{mmm}{%
  \edef#1{\directlua{tex.print(math.min(#2,#3))}}%
}
```

`\dtlminall`

`\dtlminall{<cs>}{<num list>}`

Defines `<cs>` to the minimum in the comma-separated list of numbers.

```
\NewDocumentCommand\dtlminall{mm}{%
  \edef#1{\directlua{tex.print(math.min(#2))}}%
}
```

`\dtlmax`

```
\dtlmax{<cs>}{<num1>}{<num2>}
```

Defines `<cs>` to the larger of the two numbers.

```
\NewDocumentCommand\dtlmax{mmm}{%  
  \edef#1{\directlua{tex.print(math.max(#2,#3))}}%  
}
```

`\dtlmaxall`

```
\dtlmaxall{<cs>}{<num list>}
```

Defines `<cs>` to the maximum in the comma-separated list of numbers.

```
\NewDocumentCommand\dtlmaxall{mm}{%  
  \edef#1{\directlua{tex.print(math.max(#2))}}%  
}
```

`\dtlabs`

```
\dtlabs{<cs>}{<num>}
```

Defines `<cs>` to the absolute value of `<num>`.

```
\NewDocumentCommand\dtlabs{mm}{%  
  \edef#1{\directlua{tex.print(math.abs(#2))}}%  
}
```

`\dtlneg`

```
\dtlneg{<cs>}{<num>}
```

Defines `<cs>` to the negative of `<num>`.

```
\NewDocumentCommand\dtlneg{mm}{%  
  \edef#1{\directlua{tex.print(-(#2))}}%  
}
```

`\dtlmeanforall`

```
\dtlmeanforall{<cs>}{<num list>}
```

Computes the mean and stores the result in `<cs>`.

```
\NewDocumentCommand\dtlmeanforall{mm}{%  
  \edef#1{\directlua{  
    x = 0;  
    n = 0;  
    array = { #2 };  
    for key,val in ipairs(array) do  
      n = n + 1;  
      x = x + val;  
    end  
    tex.print(x/n);  
  }}%  
}
```

`\dtlvvarianceforall`

`\dtlvvarianceforall[<mean>]{<cs>}{<num list>}`

Computes the variance and stores the result in *<cs>*.

```
\NewDocumentCommand \dtlvvarianceforall { o m m }
{%
  \IfNoValueTF{#1}%
  {%
    \edef#2{\directlua{
      n = 0;
      mean = 0;
      array = { #3 };
      for key,val in ipairs(array) do
        n = n + 1;
        mean = mean + val;
      end
      mean = mean / n;
      variance = 0;
      for key,val in ipairs(array) do
        x = val - mean;
        variance = variance + x * x;
      end
      variance = variance / n;
      tex.print(variance);
    }}%
  }%
  {%
    \edef#2{\directlua{
      n = 0;
      mean = #1;
      array = { #3 };
      variance = 0;
      for key,val in ipairs(array) do
        n = n + 1;
        x = val - mean;
        variance = variance + x * x;
      end
      variance = variance / n;
      tex.print(variance);
    }}%
  }%
}
```

`\dtlstdforall`

`\dtlstdforall[<mean>]{<cs>}{<num list>}`

Computes the standard deviation and stores the result in *<cs>*.

```
\NewDocumentCommand \dtlstdforall { o m m }
{%
```

```

\IfNoValueTF{#1}%
{%
  \edef#2{\directlua{
    n = 0;
    mean = 0;
    array = { #3 };
    for key,val in ipairs(array) do
      n = n + 1;
      mean = mean + val;
    end
    mean = mean / n;
    variance = 0;
    for key,val in ipairs(array) do
      x = val - mean;
      variance = variance + x * x;
    end
    variance = variance / n;
    tex.print(math.sqrt(variance));
  }}%
}%
{%
  \edef#2{\directlua{
    n = 0;
    mean = #1;
    array = { #3 };
    variance = 0;
    for key,val in ipairs(array) do
      n = n + 1;
      x = val - mean;
      variance = variance + x * x;
    end
    variance = variance / n;
    tex.print(math.sqrt(variance));
  }}%
}%
}

```

8 datatool-fp.sty

Definitions of fixed-point commands that use the `fp` package. Provided for backward-compatibility.

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesFile{datatool-fp.def}[2025/04/03 v3.4 (NLCT)]

```

Required package:

```
\RequirePackage{fp}
```

If `fp`'s `verbose` option set, switch on `verbose` for `datatool-base` as well:

```
\ifFPmessages
```

```
\dtlverbosetrue
\fi
```

8.1 Comparison Commands

```
\dtlifnumeq{<num1>}{<num2>}{<true part>}{<false part>}
```

`\dtlifnumeq`

Does *<true part>* if $\langle num1 \rangle = \langle num2 \rangle$, otherwise does *<false part>*. The numbers must use a full stop as the decimal character and no number group separator.

```
\newrobustcmd*{\dtlifnumeq}[4]{%
  \FPifeq{#1}{#2}%
  #3%
  \else
  #4%
  \fi
}
```

```
\dtlifnumlt{<num1>}{<num2>}{<true part>}{<false part>}
```

`\dtlifnumlt`

Does *<true part>* if $\langle num1 \rangle < \langle num2 \rangle$, otherwise does *<false part>*. The numbers must use a full stop as the decimal character and no number group separator.

```
\newrobustcmd*{\dtlifnumlt}[4]{%
  \FPiflt{#1}{#2}%
  #3%
  \else
  #4%
  \fi
}
```

```
\dtlifnumgt{<num1>}{<num2>}{<true part>}{<false part>}
```

`\dtlifnumgt`

Does *<true part>* if $\langle num1 \rangle > \langle num2 \rangle$, otherwise does *<false part>*. The numbers must use a full stop as the decimal character and no number group separator.

```
\newrobustcmd*{\dtlifnumgt}[4]{%
  \FPifgt{#1}{#2}%
  #3%
  \else
  #4%
  \fi
}
```

```
\dtlifnumopenbetween{<num>}{<min>}{<max>}{<true part>}
{<false part>}
```

\dtlifnumopenbetween

Determines if $\langle min \rangle < \langle num \rangle < \langle max \rangle$ where all numerical arguments are in standard fixed point notation.

```
\newrobustcmd*{\dtlifnumopenbetween}[5]{%
  \let\@dtl@dovalue\relax
  \dtlifnumgt{#1}{#2}%
  {%
  }%
  \def\@dtl@dovalue{#5}%
}%
\dtlifnumlt{#1}{#3}%
{%
  \ifx\@dtl@dovalue\relax
    \def\@dtl@dovalue{#4}%
  \fi
}%
}%
\def\@dtl@dovalue{#5}%
}%
\@dtl@dovalue
}
```

```
\dtlifnumclosedbetween{<num>}{<min>}{<max>}{<true
part>}{<false part>}
```

\dtlifnumclosedbetween

Determines if $\langle min \rangle \leq \langle num \rangle \leq \langle max \rangle$ where all numerical arguments are in standard fixed point notation.

```
\newrobustcmd*{\dtlifnumclosedbetween}[5]{%
  \let\@dtl@dovalue\relax
  \dtlifnumgt{#1}{#2}%
  {%
  }%
  \dtlifnumeq{#1}{#2}%
  {%
  }%
  \def\@dtl@dovalue{#4}%
}%
\def\@dtl@dovalue{#5}%
}%
}%
\dtlifnumlt{#1}{#3}%
{%
  \ifx\@dtl@dovalue\relax
    \def\@dtl@dovalue{#4}%
  \fi
}
```

```

}%
{%
\dtlifnumeq{#1}{#3}%
{%
\def\@dtl@dovalue{#4}%
}%
{%
\def\@dtl@dovalue{#5}%
}%
}%
\@dtl@dovalue
}

```

8.2 Functions

`\dtladd` Adds two numbers using fp.

```

\NewDocumentCommand{\dtladd}{mmm}{%
\FPadd{#1}{#2}{#3}%
}

```

`\dtladdall` `\dtladdall{<cs>}{<num list>}`

Defines `<cs>` to the sum of all the numbers in the comma-separated list of numbers.

```

\NewDocumentCommand{\dtladdall}{mm}{%
\def#1{0}%
\@for\@dtl@tmp:=#2\do{%
\FPadd{#1}{#1}{\@dtl@tmp}%
}%
}

```

`\dtlsub` Subtracts two numbers using fp.

```

\NewDocumentCommand{\dtlsub}{mmm}{%
\FPsub{#1}{#2}{#3}%
}

```

`\dtlmul` Multiplies two numbers using fp.

```

\NewDocumentCommand{\dtlmul}{mmm}{%
\FPmul{#1}{#2}{#3}%
}

```

`\dtldiv` Divides two numbers using fp.

```

\NewDocumentCommand{\dtldiv}{mmm}{%
\FPdiv{#1}{#2}{#3}%
}

```

`\dtlsqrt` Square root using fp.

```

\NewDocumentCommand{\dtlsqrt}{mm}{%

```

```

        \FProot{#1}{#2}{2}%
    }

\dtlroot Nth root using fp.
    \NewDocumentCommand{\dtlroot}{mmm}{%
        \FProot{#1}{#2}{#3}%
    }

\dtlround Rounds using fp.
    \NewDocumentCommand{\dtlround}{mmm}{%
        \FPround{#1}{#2}{#3}%
    }

\dtltrunc Truncates using fp. (Third argument is the number of digits.)
    \NewDocumentCommand{\dtltrunc}{mmm}{%
        \FPtrunc{#1}{#2}{#3}%
    }

\dtlclip
    \NewDocumentCommand{\dtlclip}{mm}{%
        \FPclip{#1}{#2}%
    }

\dtlmin Minimum of two numbers using fp.
    \NewDocumentCommand{\dtlmin}{mmm}{%
        \FPmin{#1}{#2}{#3}%
    }

\dtlminall \dtlminall{<cs>}{<num list>}
    Defines <cs> to the minimum in the comma-separated list of numbers.
    \NewDocumentCommand{\dtlminall}{mm}{%
        \let#1\empty
        \@for\@dtl@tmp:=#2\do{%
            \ifx\empty
                \let#1\@dtl@tmp
            \else
                \FPmin#1{#1}{\@dtl@tmp}%
            \fi
        }%
    }

\dtlmax Maximum of two numbers using fp.
    \NewDocumentCommand{\dtlmax}{mmm}{%
        \FPmax{#1}{#2}{#3}%
    }

```

`\dtlmaxall`

`\dtlmaxall{<cs>}{<num list>}`

Defines $\langle cs \rangle$ to the maximum in the comma-separated list of numbers.

```
\NewDocumentCommand{\dtlmaxall}{mm}{%
  \let#1\empty
  \@for\dtl@tmp:=#2\do{%
    \ifx\empty
      \let#1\dtl@tmp
    \else
      \FPmax#1{#1}{\dtl@tmp}%
    \fi
  }%
}
```

`\dtlabs` Absolute value using fp.

```
\NewDocumentCommand{\dtlabs}{mm}{%
  \FPabs{#1}{#2}%
}
```

`\dtlneg` Negative of a value using fp.

```
\NewDocumentCommand{\dtlneg}{mm}{%
  \FPneg{#1}{#2}%
}
```

`\dtlmeanforall`

`\dtlmeanforall{<cs>}{<num list>}`

Defines $\langle cs \rangle$ to the mean (average) of all the numbers in the comma-separated list of numbers.

```
\NewDocumentCommand{\dtlmeanforall}{mm}{%
  \def#1{0}%
  \count@=0\relax
  \@for\dtl@tmp:=#2\do{%
    \advance\count@ by \@ne
    \FPadd{#1}{#1}{\dtl@tmp}%
  }%
  \FPdiv{#1}{#1}{\number\count@}%
}
```

`\dtlvvarianceforall`

`\dtlvvarianceforall[<mean>]{<cs>}{<num list>}`

Defines $\langle cs \rangle$ to the variance of all the numbers in the comma-separated list of numbers. If the mean has already been calculated it can be supplied in the optional argument.

```
\NewDocumentCommand{\dtlvvarianceforall}{omm}{%
  \IfNoValueTF{#1}%
  {%
```

```

\def\@dtl@mean{0}%
\count@=0\relax
\@for\@dtl@tmp:=#3\do{%
  \advance\count@ by \@ne
  \FPadd{\@dtl@mean}{\@dtl@mean}{\@dtl@tmp}%
}%
\FPdiv{\@dtl@mean}{\@dtl@mean}{\number\count@}%
\def#2{0}%
\@for\@dtl@tmp:=#3\do{%
  \FPsub{\@dtl@tmp}{\@dtl@tmp}{\@dtl@mean}%
  \FPMul{\@dtl@tmp}{\@dtl@tmp}{\@dtl@tmp}%
  \FPadd{#2}{#2}{\@dtl@tmp}%
}%
\FPdiv{#2}{#2}{\number\count@}%
}%
{%
  \def\@dtl@mean{#1}%
  \count@=0\relax
  \def#2{0}%
  \@for\@dtl@tmp:=#3\do{%
    \advance\count@ by \@ne
    \FPsub{\@dtl@tmp}{\@dtl@tmp}{\@dtl@mean}%
    \FPMul{\@dtl@tmp}{\@dtl@tmp}{\@dtl@tmp}%
    \FPadd{#2}{#2}{\@dtl@tmp}%
  }%
  \FPdiv{#2}{#2}{\number\count@}%
}%
}

```

`\dtlsdforall`

`\dtlsdforall[mean]{cs}{num list}`

Defines *cs* to the standard deviation of all the numbers in the comma-separated list of numbers. If the mean has already been calculated it can be supplied in the optional argument.

```

\NewDocumentCommand{\dtlsdforall}{omm}{%
  \IfNoValueTF{#1}{%
    {%
      \def\@dtl@mean{0}%
      \count@=0\relax
      \@for\@dtl@tmp:=#3\do{%
        \advance\count@ by \@ne
        \FPadd{\@dtl@mean}{\@dtl@mean}{\@dtl@tmp}%
      }%
      \FPdiv{\@dtl@mean}{\@dtl@mean}{\number\count@}%
      \def#2{0}%
      \@for\@dtl@tmp:=#3\do{%
        \FPsub{\@dtl@tmp}{\@dtl@tmp}{\@dtl@mean}%
        \FPMul{\@dtl@tmp}{\@dtl@tmp}{\@dtl@tmp}%
      }%
    }%
  }%
}

```

```

        \FPadd{#2}{#2}{\@dtl@tmp}%
    }%
}%
{%
\def\@dtl@mean{#1}%
\count@=0\relax
\def#2{0}%
\@for\@dtl@tmp:=#3\do{%
\advance\count@ by \@ne
\FPsub{\@dtl@tmp}{\@dtl@tmp}{\@dtl@mean}%
\FPmul{\@dtl@tmp}{\@dtl@tmp}{\@dtl@tmp}%
\FPadd{#2}{#2}{\@dtl@tmp}%
}%
}%
\FPdiv{#2}{#2}{\number\count@}%
\FProot{#2}{#2}{2}%
}

```

9 datatool-fp.sty

Definitions of fixed-point commands that use the `fp` package. Note that the newer `datatool-l3fp` or `datatool-lua` are preferable.

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```
\DeclareRelease{v2.32}{2019-09-27}{datatool-fp-2019-09-27.sty}
\DeclareCurrentRelease{v3.4}{2025-04-03}
```

Declare package:

```
\ProvidesPackage{datatool-fp}[2025/04/03 v3.4 (NLCT)]
```

This package is deprecated.

```
\PackageWarning{datatool-fp}%
{datatool-fp.sty deprecated. Use
\string\usepackage[math=fp]{datatool} instead or
(better still) \string\usepackage{datatool}
}
\RequirePackage[math=fp]{datatool}
```

10 datatool-pgfmath.sty

Definitions of fixed-point commands that use the `pgfmath` package. Provided for backward-compatibility. The newer `datatool-l3fp.def` or `datatool-lua.def` are preferable.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesFile{datatool-pgfmath.def}[2025/04/03 v3.4 (NLCT)]
```

Required packages:

```
\RequirePackage{pgfrcs,pgfkeys,pgfmath}
```

Old code has only been partially rewritten with L^AT_EX3.
`\ExplSyntaxOn`

10.1 Comparison Commands

`\dtlifnumeq`

```
\dtlifnumeq{<num1>}{<num2>}{<true part>}{<false part>}
```

Does *<true part>* if $\langle num1 \rangle = \langle num2 \rangle$, otherwise does *<false part>*. The numbers must use a full stop as the decimal character and no number group separator. The `\number0` part allows an empty argument to be treated as zero. (`\number` required to prevent a zero prefix indicating an octal number.)

```
\NewDocumentCommand \dtlifnumeq { m m m m }
{
  \def\@dtl@truepart{#3}%
  \def\@dtl@falsepart{#4}%
  \exp_args:Nx \pgfmathifthenelse {#1==#2}%
    {"\exp_not:N \@dtl@truepart"}{"\exp_not:N \@dtl@falsepart"}%
  \pgfmathresult
}
```

`\dtlifnumlt`

```
\dtlifnumlt{<num1>}{<num2>}{<true part>}{<false part>}
```

Does *<true part>* if $\langle num1 \rangle < \langle num2 \rangle$, otherwise does *<false part>*. The numbers must use a full stop as the decimal character and no number group separator.

```
\NewDocumentCommand \dtlifnumlt { m m m m }
{
  \def\@dtl@truepart{#3}%
  \def\@dtl@falsepart{#4}%
  \exp_args:Nx \pgfmathifthenelse {#1 < #2}%
    {"\exp_not:N \@dtl@truepart"}{"\exp_not:N \@dtl@falsepart"}%
  \pgfmathresult
}
```

`\dtlifnumgt`

```
\dtlifnumgt{<num1>}{<num2>}{<true part>}{<false part>}
```

Does *<true part>* if $\langle num1 \rangle > \langle num2 \rangle$, otherwise does *<false part>*. The numbers must use a full stop as the decimal character and no number group separator.

```
\NewDocumentCommand \dtlifnumgt { m m m m }
{
  \def\@dtl@truepart{#3}%
  \def\@dtl@falsepart{#4}%
}
```

```

\exp_args:Nx \pgfmathifthenelse {#1 > #2}%
{"\exp_not:N \@dtl@truepart"}{"\exp_not:N \@dtl@falsepart"}%
\pgfmathresult
}

```

```

\dtlifnumopenbetween{<num>}{<min>}{<max>}{<true part>}
{<false part>}

```

`\dtlifnumopenbetween`

Determines if $\langle min \rangle < \langle num \rangle < \langle max \rangle$ where all numerical arguments are in standard fixed point notation.

```

\NewDocumentCommand \dtlifnumopenbetween { m m m m m }
{
  \dtlifnumlt { #1 } { #3 }
  { \dtlifnumgt { #1 } { #2 } { #4 } { #5 } }
  { #5 }
}

```

```

\dtlifnumclosedbetween{<num>}{<min>}{<max>}{<true
part>}{<false part>}

```

`\dtlifnumclosedbetween`

Determines if $\langle min \rangle \leq \langle num \rangle \leq \langle max \rangle$ where all numerical arguments are in standard fixed point notation.

```

\NewDocumentCommand \dtlifnumclosedbetween { m m m m m }
{
  \dtlifnumlt { #1 } { #2 }
  { #5 }
  { \dtlifnumgt { #1 } { #3 } { #5 } { #4 } }
}

```

10.2 Functions

`\dtladd` Adds two numbers using PGF math engine.

```

\NewDocumentCommand \dtladd { m m m }
{
  \pgfmathadd{#2}{#3}%
  \let#1\pgfmathresult
}

```

```

\dtladdall{<cs>}{<num list>}

```

`\dtladdall`

Defines $\langle cs \rangle$ to the sum of all the numbers in the comma-separated list of numbers.

```

\NewDocumentCommand \dtladdall { m m }
{
  \tl_set:Nn \pgfmathresult { 0 }
}

```

```

        \exp_args:No \clist_map_inline:nn { #2 }
        {
            \pgfmathadd { \pgfmathresult } { ##1 }
        }
        \tl_set_eq:NN #1 \pgfmathresult
    }

\dtlsub Subtracts two numbers using PGF math engine.
\NewDocumentCommand \dtlsub { m m m }
{
    \pgfmathsubtract{#2}{#3}%
    \let#1\pgfmathresult
}

\dtlmul Multiplies two numbers using PGF math engine.
\NewDocumentCommand \dtlmul { m m m }
{%
    \pgfmathmultiply{#2}{#3}%
    \let#1\pgfmathresult
}

\dtldiv Divides two numbers using PGF math engine.
\NewDocumentCommand \dtldiv { m m m }
{%
    \pgfmathdivide{#2}{#3}%
    \let#1\pgfmathresult
}

\dtlsqrt Root using PGF math engine.
\NewDocumentCommand \dtlsqrt { m m }
{%
    \pgfmathsqrt{#2}%
    \let#1\pgfmathresult
}

\dtlroot Root using PGF math engine.
\NewDocumentCommand \dtlroot { m m m }
{
    \exp_args:Nx \tl_if_eq:nnTF { #3 } { 2 }
    {
        \exp_args:Nx \pgfmathsqrt { #2 }
        \let#1\pgfmathresult
    }
    {
        \exp_args:Nxx \pgfmathpow { #2 } { 1 / ( #3 ) }
        \let#1\pgfmathresult
    }
}

```

`\dtlround` Rounds using PGF math engine.

```
\NewDocumentCommand{\dtlround}{mmm}{%
  \ifnum#3=0\relax
    \exp_args:Nx \pgfmathparse { int( round ( #2 ) ) }
    \let#1\pgfmathresult
  \else
    \exp_args:Nx \pgfmathparse { int ( 10 \exp_not:N ^ #3 ) }
    \let\dtl@tmpshift\pgfmathresult
```

Need to be careful not to trigger the dimension too large error, so this is a bit convoluted.

```
\exp_args:Nx \pgfmathparse { int ( floor ( #2 ) ) }%
\let\dtl@int@round\pgfmathresult
\exp_args:Nx \pgfmathparse
  { int ( round ( ( #2 - \dtl@int@round ) * \dtl@tmpshift ) ) }
```

This bit is awkward because simply dividing by multiples of 10 in pgfmath can cause rounding errors, so need to employ another method.

```
\@dtl@tmpcount=0\relax
\expandafter\@dtl@countdigits\pgfmathresult.\relax
\advance\@dtl@tmpcount by -#3\relax
\def\@dtl@intpart{ }%
\def\@dtl@fracpart{ }%
\expandafter\@dtl@gatherintfrac\pgfmathresult\relax
\tl_if_empty:NT \@dtl@intpart { \tl_set:Nn \@dtl@intpart { 0 } }
\edef\@dtl@intpart{\number\numexpr\dtl@int@round + \@dtl@intpart}%
\edef#1{\@dtl@intpart.\@dtl@fracpart}%
\fi
}
```

`\@dtl@gatherintfrac`

```
\newcommand*{\@dtl@gatherintfrac}[1]{%
  \ifx\relax#1\relax
  \else
    \advance\@dtl@tmpcount by -1\relax
    \ifnum\@dtl@tmpcount<0\relax
      \edef\@dtl@fracpart{\@dtl@fracpart#1}%
    \else
      \edef\@dtl@intpart{\@dtl@intpart#1}%
    \fi
    \expandafter\@dtl@gatherintfrac
  \fi
}
```

`\dtltrunc` Truncates using PGF math engine. (Third argument is the number of digits.) This suffers from the same problems as `\dtlround`. Can cause dimension too large error or rounding errors.

```
\NewDocumentCommand \dtltrunc { m m m }
{
  \ifnum#3=0\relax
    \exp_args:Nx \pgfmathparse { int ( floor ( #2 ) ) }%
```

```

\let#1\pgfmathresult
\else
\exp_args:Nx \pgfmathparse { int ( 10 \exp_not:N ^ #3 ) }
\let\dtl@tmpshift\pgfmathresult

```

Need to be careful not to trigger the dimension too large error, so this is a bit convoluted.

```

\exp_args:Nx \pgfmathparse { int ( floor ( #2 ) ) }
\let\dtl@int@trunc\pgfmathresult
\exp_args:Nx \pgfmathparse
{ int ( floor ( ( #2 - \dtl@int@trunc ) * \dtl@tmpshift ) ) }

```

This bit is awkward because simply dividing by multiples of 10 in pgfmath can cause rounding errors, so need to employ another method.

```

\@dtl@tmpcount=0\relax
\expandafter\@dtl@countdigits\pgfmathresult.\relax
\advance\@dtl@tmpcount by -#3\relax
\def\@dtl@intpart{ }%
\def\@dtl@fracpart{ }%
\expandafter\@dtl@gatherintfrac\pgfmathresult\relax
\tl_if_empty:NT \@dtl@intpart { \tl_set:Nn \@dtl@intpart { 0 } }
\edef\@dtl@intpart{\number\numexpr\dtl@int@trunc
+ \@dtl@intpart}%
\edef#1{\@dtl@intpart.\@dtl@fracpart}%
\fi
}

```

`\dtlclip` There isn't a clip in pgfmath so use \LaTeX 3 instead.

```

\NewDocumentCommand \dtlclip { m m }
{
\fp_set:Nn { \l__datatool_tmpa_fp } { #2 }
\tl_set:Nx #1 { \fp_use:N { \l__datatool_tmpa_fp } }
}

```

`\dtlmin` Minimum of two numbers using PGF math engine.

```

\NewDocumentCommand \dtlmin { m m m }
{
\exp_args:Nxx \pgfmathmin { #2 } { #3 }
\let#1\pgfmathresult
}

```

```
\dtlminall{<cs>}{<num list>}
```

`\dtlminall`

Defines `<cs>` to the minimum in the comma-separated list of numbers.

```

\NewDocumentCommand \dtlminall { m m }
{
\exp_args:Nx \pgfmathmin { #2 } { }
\let#1\pgfmathresult
}

```

`\dtlmax` Maximum of two numbers using PGF math engine.

```

\NewDocumentCommand \dtlmax { m m m }
{
  \exp_args:Nx \pgfmathmax { #2 } { #3 }
  \let#1\pgfmathresult
}

```

`\dtlmaxall{<cs>}{<num list>}`

`\dtlmaxall` Defines `<cs>` to the maximum in the comma-separated list of numbers.

```

\NewDocumentCommand \dtlmaxall { m m }
{
  \exp_args:Nx \pgfmathmax { #2 } { }
  \let#1\pgfmathresult
}

```

`\dtlabs` Absolute value using PGF math engine.

```

\NewDocumentCommand \dtlabs { m m }
{
  \exp_args:Nx \pgfmathabs { #2 }
  \let#1\pgfmathresult
}

```

`\dtlneg` Negative of a value using PGF math engine.

```

\NewDocumentCommand \dtlneg { m m }
{
  \exp_args:Nx \pgfmathneg { #2 }
  \let#1\pgfmathresult
}

```

`\dtlmeanforall{<cs>}{<num list>}`

`\dtlmeanforall` Defines `<cs>` to the mean of all the numbers in the comma-separated list of numbers.

```

\NewDocumentCommand \dtlmeanforall { m m }
{
  \tl_set:Nn \pgfmathresult { 0 }
  \int_zero:N \l__datatool_count_int
  \exp_args:No \clist_map_inline:nn { #2 }
  {
    \int_incr:N \l__datatool_count_int
    \exp_args:Nxx \pgfmathadd { \pgfmathresult } { ##1 }
  }
  \exp_args:Nxx \pgfmathdivide
  { \pgfmathresult }
  { \int_use:N \l__datatool_count_int }
  \tl_set_eq:NN #1 \pgfmathresult
}

```

`\dtlvarianceforall[⟨mean⟩]{⟨cs⟩}{⟨num list⟩}`

`\dtlvarianceforall`

Defines $\langle cs \rangle$ to the variance of all the numbers in the comma-separated list of numbers. If the mean has already been computed it can be supplied in the optional argument.

```

\NewDocumentCommand {\dtlvarianceforall} { o m m }
{%
  \IfNoValueTF { #1 }
  {
    \tl_set:Nn \pgfmathresult { 0 }
    \int_zero:N \l__datatool_count_int
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \int_incr:N \l__datatool_count_int
      \exp_args:Nxx \pgfmathadd { \pgfmathresult } { ##1 }
    }
    \exp_args:Nxx \pgfmathdivide
      { \pgfmathresult }
      { \int_use:N \l__datatool_count_int }
    \tl_set_eq:NN \@dtl@mean \pgfmathresult
    \tl_set:Nn #2 { 0 }
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \exp_args:Nxx \pgfmathsubtract { ##1 } { \@dtl@mean }
      \exp_args:Nxx \pgfmathmultiply { \pgfmathresult } { \pgfmathresult }
      \exp_args:Nxx \pgfmathadd { #2 } { \pgfmathresult }
      \tl_set_eq:NN #2 \pgfmathresult
    }
  }
  {
    \tl_set:Nx \@dtl@mean { #1 }
    \int_zero:N \l__datatool_count_int
    \tl_set:Nn #2 { 0 }
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \int_incr:N \l__datatool_count_int
      \exp_args:Nxx \pgfmathsubtract { ##1 } { \@dtl@mean }
      \exp_args:Nxx \pgfmathmultiply
        { \pgfmathresult } { \pgfmathresult }
      \exp_args:Nxx \pgfmathadd { #2 } { \pgfmathresult }
      \tl_set_eq:NN #2 \pgfmathresult
    }
  }
  \exp_args:Nxx \pgfmathdivide
    { #2 }
    { \int_use:N \l__datatool_count_int }
  \tl_set_eq:NN #2 \pgfmathresult
}

```

`\dtlsdforall[⟨mean⟩]{⟨cs⟩}{⟨num list⟩}`

`\dtlsdforall`

Defines $\langle cs \rangle$ to the standard deviation of all the numbers in the comma-separated list of numbers. If the mean has already been computed it can be supplied in the optional argument.

```

\NewDocumentCommand{\dtlsdforall} { o m m }
{%
  \IfNoValueTF{#1}%
  {%
    \tl_set:Nn \pgfmathresult { 0 }
    \int_zero:N \l__datatool_count_int
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \int_incr:N \l__datatool_count_int
      \exp_args:Nxx \pgfmathadd { \pgfmathresult } { ##1 }
    }
    \exp_args:Nxx \pgfmathdivide
      { \pgfmathresult }
      { \int_use:N \l__datatool_count_int }
    \tl_set_eq:NN \@dtl@mean \pgfmathresult
    \tl_set:Nn #2 { 0 }
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \exp_args:Nxx \pgfmathsubtract { ##1 } { \@dtl@mean }
      \exp_args:Nxx \pgfmathmultiply { \pgfmathresult } { \pgfmathresult }
      \exp_args:Nxx \pgfmathadd { #2 } { \pgfmathresult }
      \tl_set_eq:NN #2 \pgfmathresult
    }
  }
  {
    \tl_set:Nn \@dtl@mean { #1 }
    \int_zero:N \l__datatool_count_int
    \tl_set:Nn #2 { 0 }
    \exp_args:No \clist_map_inline:nn { #3 }
    {
      \int_incr:N \l__datatool_count_int
      \exp_args:Nxx \pgfmathsubtract { ##1 } { \@dtl@mean }
      \exp_args:Nxx \pgfmathmultiply
        { \pgfmathresult } { \pgfmathresult }
      \exp_args:Nxx \pgfmathadd { #2 } { \pgfmathresult }
      \tl_set_eq:NN #2 \pgfmathresult
    }
  }
  \exp_args:Nxx \pgfmathdivide
    { #2 } { \int_use:N \l__datatool_count_int }
  \exp_args:Nx \pgfmathsqrt { \pgfmathresult }
  \tl_set_eq:NN #2 \pgfmathresult
}

```

```
\ExplSyntaxOff
```

11 datatool-pgfmath.sty

Definitions of fixed-point commands that use the `pgfmath` package. Note that the newer `datatool-l3fp` or `datatool-lua` are preferable.

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```
\DeclareRelease{v2.32}{2019-09-27}{datatool-pgfmath-2019-09-27.sty}  
\DeclareCurrentRelease{v3.4}{2025-04-03}
```

Declare package:

```
\ProvidesPackage{datatool-pgfmath}[2025/04/03 v3.4 (NLCT)]
```

This package is deprecated.

```
\PackageWarning{datatool-pgfmath}%  
{datatool-pgfmath.sty deprecated. Use  
\string\usepackage[math=pgfmath]{datatool} instead or  
(better still) \string\usepackage{datatool}  
}  
\RequirePackage[math=pgfmath]{datatool}
```

12 datatool.sty

12.1 Package Declaration

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```
\DeclareRelease{v2.32}{2019-09-27}{datatool-2019-09-27.sty}  
\DeclareCurrentRelease{v3.4}{2025-04-03}
```

Declare package:

```
\ProvidesPackage{datatool}[2025/04/03 v3.4 (NLCT)]
```

Version 3.0: no longer using `xkeyval`. Load required packages:

```
\RequirePackage{ifthen}  
\RequirePackage{xfor}  
\RequirePackage{etoolbox}  
\RequirePackage{tracklang}
```

Version 3.0: partial rewrite using \LaTeX 3 (mainly for the CSV file parsing) so there's a mix of new and old style commands. This rewrite needs to take into account the format of `dbtex` files, which can be read and written by `datatooltk`. There are three file format versions: 1, 2 and 3. The first two are almost identical. Version 2 has the final line that defines `\dtl\lastloadeddb`. The internal commands are defined to allow a fast load that doesn't require any parsing to split on separators or to determine data types. This means that the internal structure of the database needs to remain the same. Also, it's not possible to enable \LaTeX 3 syntax in the `dbtex` file because the category

code change will affect the data (the space character in particular). The version 3 file format is new to datatool v3.0. An undefined command on loading a dbtex will likely indicate that a newer dbtex is being used with an old datatool version and so should be considered incompatible.

12.2 Package Options

```
\ExplSyntaxOn
\cs_new:Nn \__datatool_char_to_hex:nN
{
  \tl_set:Nx #2 { \int_to_hex:n { `#1 } }
}
```

`\@dtl@separator` The data separator character (comma by default) is stored in `\@dtl@separator`. This is the separator used in external data files, not in the \LaTeX code, which always uses a comma separator.

```
\newcommand*\@dtl@separator{,}
```

`\DTLsetseparator{<char>}`

`\DTLsetseparator`

The sets `\@dtl@separator`, and constructs the relevant macros that require this character to be hardcoded into their definition.

```
\NewDocumentCommand \DTLsetseparator { m }
{
  \tl_if_single_token:nTF { #1 }
  {
    \tl_set:Nx \@dtl@separator { \tl_to_str:n { #1 } }
    \__datatool_char_to_hex:nN { #1 } \l__datatool_tmpa_tl
    \exp_args:NNx \regex_set:Nn \l__datatool_blank_row_regex
    {
      \exp_not:N \A
      \exp_not:N \c0 (?: \exp_not:N \x { \l__datatool_tmpa_tl } ) *
      \exp_not:N \Z
    }
  }
  {
    \PackageError{datatool}{Separator ~ must ~ be ~ a ~ single ~
      token ~ (found ~ \tl_count_tokens:n { #1 } ~ tokens) }{}
  }
}
\regex_new:N \l__datatool_blank_row_regex
\DTLsetseparator{,}
\ExplSyntaxOff

\begingroup
\catcode\^^I12
```

`\DTLsettabseparator` `\DTLsettabseparator` makes it easier to set a tab separator.
`\gdef\DTLsettabseparator{%`

```

\catcode\^^I12
\DTLsetseparator{^^I}%
}

```

`\DTLmaketabspace`

```

\gdef\DTLmaketabspace{%
\catcode\^^I10\relax
}
\endgroup

```

`\@dtl@delimiter` The data delimiter character (double quote by default) is stored in `\@dtl@delimiter`. This is used in external data files, not in the \LaTeX code.

```
\newcommand{\@dtl@delimiter}{"}

```

```
\ExplSyntaxOn

```

This may have already been defined if `datatool` was loaded first.

```
\tl_clear_new:N \l__datatool_tmpa_tl

```

`\DTLsetdelimiter{<char>}`

`\DTLsetdelimiter`

This sets the delimiter.

```

\NewDocumentCommand \DTLsetdelimiter { m }
{
\tl_if_single_token:nTF { #1 }
{
\tl_set:Nx \@dtl@delimiter { \tl_to_str:n { #1 } }
\__datatool_char_to_hex:nN { #1 } \l__datatool_tmpa_tl
\exp_args:NNx \regex_set:Nn \l__datatool_delim_left_regex
{
\exp_not:N \A \exp_not:N \s *
\exp_not:N \c0 {?: \exp_not:N \x { \l__datatool_tmpa_tl } )
}
\exp_args:NNx \regex_set:Nn \l__datatool_delim_both_regex
{
\exp_not:N \A \exp_not:N \s *
\exp_not:N \c0 {?: \exp_not:N \x { \l__datatool_tmpa_tl } )
( .* )
\exp_not:N \c0 {?: \exp_not:N \x { \l__datatool_tmpa_tl } )
\exp_not:N \s * \exp_not:N \Z
}
\exp_args:NNx \regex_set:Nn \l__datatool_delim_right_regex
{
\exp_not:N \c0 {?: \exp_not:N \x { \l__datatool_tmpa_tl } )
\exp_not:N \s * \exp_not:N \Z
}
\exp_args:NNx \regex_set:Nn \l__datatool_escape_delim_bksl_regex
{

```

```

    ( \exp_not:N \\\ | \exp_not:N \c0 ( \exp_not:N \x { \l_datatool_tmpa_tl } ) )
  }
\exp_args:NNx \regex_set:Nn \l_datatool_escape_delim_regex
{
  ( \exp_not:N \c0 ( \exp_not:N \x { \l_datatool_tmpa_tl } ) )
}
\exp_args:NNx \regex_set:Nn \l_datatool_unescape_str_delim_bksl_regex
{
  \exp_not:N \c0 (?: \exp_not:N \x { 5c } )
  ( \exp_not:N \c0
    ( \exp_not:N \x { \l_datatool_tmpa_tl } | \exp_not:N \x { 5c } )
  )
}
\exp_args:NNx \regex_set:Nn \l_datatool_unescape_str_double_delim_regex
{
  \exp_not:N \c0 (?: \exp_not:N \x { \l_datatool_tmpa_tl } )
  ( \exp_not:N \c0 ( \exp_not:N \x { \l_datatool_tmpa_tl } ) )
}
\exp_args:NNx \regex_set:Nn \l_datatool_unescape_cs_double_delim_regex
{
  (
    \exp_not:N \c
    {
      ( \exp_not:N \x { \l_datatool_tmpa_tl } )
    }
  )
  \exp_not:N \x { \l_datatool_tmpa_tl }
}
\exp_args:NNx \regex_set:Nn \l_datatool_unescape_str_delim_regex
{
  \exp_not:N \c0 (?: \exp_not:N \x { 5c } )
  ( \exp_not:N \c0 ( \exp_not:N \x { \l_datatool_tmpa_tl } ) )
}
\exp_args:NNx \regex_set:Nn \l_datatool_unescape_cs_delim_regex
{
  \exp_not:N \c
  {
    ( \exp_not:N \x { \l_datatool_tmpa_tl } )
  }
}
}
{
  \PackageError{datatool}{Delimiter ~ must ~ be ~ a ~ single ~
  token ~ (found ~ \tl_count_tokens:n { #1 } ~ tokens) }{}
}
}
\regex_new:N \l_datatool_delim_left_regex
\regex_new:N \l_datatool_delim_right_regex
\regex_new:N \l_datatool_delim_both_regex
\regex_new:N \l_datatool_escape_delim_regex

```

```

\regex_new:N \l__datatool_escape_delim_bksl_regex
\regex_new:N \l__datatool_unescape_str_delim_regex
\regex_new:N \l__datatool_unescape_str_delim_bksl_regex
\regex_new:N \l__datatool_unescape_cs_delim_regex
\regex_new:N \l__datatool_unescape_str_double_delim_regex
\regex_new:N \l__datatool_unescape_cs_double_delim_regex

```

Initialise:

```
\DTLsetdelimiter{"}
```

Default database name.

```

\tl_new:N \l__datatool_default_dbname_tl
\tl_set:Nn \l__datatool_default_dbname_tl { untitled }

```

Determine whether to use the local or global function.

```

\bool_new:N \l__datatool_db_global_bool
\bool_set_true:N \l__datatool_db_global_bool

```

Determine whether or not to trim spaces around new entries.

```

\bool_new:N \l__datatool_new_element_trim_bool
\bool_set_true:N \l__datatool_new_element_trim_bool

```

Version 3.0: provide boolean to check on the current new value expansion setting:

```
\bool_new:N \l__datatool_new_element_expand_bool
```

Determine whether or not to expand values before adding them to the database.

`\dtlexpandnewvalue` Expand new value before adding to database

```

\newcommand*{\dtlexpandnewvalue}{
  \bool_set_true:N \l__datatool_new_element_expand_bool
  \def\@dtl@setnewvalue##1{
    \protected@edef\@dtl@tmp{ ##1 }
    \bool_if:NT\l__datatool_new_element_trim_bool
    {
      \tl_trim_spaces:N \@dtl@tmp
    }
    \expandafter\@dtl@toks\expandafter{\@dtl@tmp}
  }
}

```

`\dtlnoexpandnewvalue` Don't expand new value before adding to database

```

\newcommand*{\dtlnoexpandnewvalue}{%
  \bool_set_false:N \l__datatool_new_element_expand_bool
  \def\@dtl@setnewvalue##1{
    \bool_if:NTF\l__datatool_new_element_trim_bool
    {
      \tl_set:Nn \l__datatool_item_value_tl { ##1 }
      \tl_trim_spaces:N \l__datatool_item_value_tl
      \exp_args:NV \@dtl@toks \l__datatool_item_value_tl
    }
    {

```

```

        \@dtl@toks{##1}
      }
    }
  }

```

`\@dtl@setnewvalue` Do this by default. This will define `\@dtl@setnewvalue`.

```

\dtlnoexpandnewvalue

```

Note that `__datatool_process_new_value:n` should be used to preprocess values. That uses `\dtl@setnewvalue` to follow the trim and expansion settings but then checks the store datum boolean. TODO remove `\@dtl@setnewvalue` and replace with another boolean?

Determine whether or not to store values in the database in datum format.

```

\bool_new:N \__datatool_db_store_datum_bool

```

Define options. The default-name value is expanded for consistency because it will be expanded if used as a package option so it should therefore also expand when used in `\DTLsetup`.

```

\keys_define:nn { datatool }
{
  default-name .str_set_x:N = \__datatool_default_dbname_tl,
  global .bool_set:N = \__datatool_db_global_bool,
  store-datum .bool_set:N = \__datatool_db_store_datum_bool,
  separator .code:n = { \DTLsetseparator { #1 } },
  delimiter .code:n = { \DTLsetdelimiter { #1 } },
  new-value-trim .bool_set:N = \__datatool_new_element_trim_bool,
  new-value-expand .choice:,
  new-value-expand / true .code:n = { \dtlexpandnewvalue },
  new-value-expand / false .code:n = { \dtlnoexpandnewvalue },
  new-value-expand .default:n = true,
}
\ExplSyntaxOff

```

If `datatool-base` may have already been loaded by another package, in which case the options need processing now.

```

\IfPackageLoadedTF{datatool-base}
{
  \ProcessKeyOptions[datatool]
}
{

```

The `datatool-base` package hasn't been loaded, so pass all options to that.

```

\DeclareOption*{\PassOptionsToPackage{\CurrentOption}{datatool-
base}}
\ProcessOptions
Load base package:
\RequirePackage{datatool-base}
}
\ExplSyntaxOn

```

Private variables.

Token lists:

```
\tl_new:N \l_datatool_item_key_tl
\tl_new:N \l_datatool_item_type_tl
\tl_new:N \l_datatool_item_head_tl
\tl_new:N \l_datatool_item_value_tl
\tl_new:N \l_datatool_item_currency_tl
\tl_new:N \l_datatool_item_currency_ii_tl
\tl_new:N \l_datatool_row_tl
\tl_new:N \l_datatool_keydata_tl
\tl_new:N \l_datatool_content_tl
\tl_new:N \l_datatool_align_tl
\tl_new:N \l_datatool_before_tl
\tl_new:N \l_datatool_after_tl
\tl_new:N \l_datatool_cs_builder_tl
```

Numeric values that may be set to null to need a token list variable.

```
\tl_new:N \l_datatool_item_col_tl
```

Replaces `\dtl@rowidx`:

```
\tl_new:N \l_datatool_row_idx_tl
```

Integers:

```
\int_new:N \l_datatool_max_cols_int
\int_new:N \l_datatool_col_idx_int
\int_new:N \l_datatool_row_idx_int
\int_new:N \l_datatool_item_type_int
```

Sequences:

```
\seq_new:N \l_datatool_column_indexes_seq
\seq_new:N \l_datatool_column_keys_seq
```

Floating point:

```
\fp_new:N \l_datatool_min_fp
\fp_new:N \l_datatool_min_ii_fp
\fp_new:N \l_datatool_max_fp
\fp_new:N \l_datatool_max_ii_fp
\fp_new:N \l_datatool_total_ii_fp
```

Temporary list:

```
\clist_new:N \l_datatool_tmpa_clist
```

`\DTLpar` Many of the commands used by this package are short commands. This means that you can't use `\par` in the data. This command needs to be robust so it doesn't get expanded when written to a file. We also can't just use a synonym for `\@@par` because it may be used in a context where `\par` has a different meaning to `\@@par`.

```
\newrobustcmd{\DTLpar}{\par}
```

`\DTLaction`

```
\DTLaction[<options>]{<action>}
```

General purpose action command to avoid typing long command names. Note that since some commands may only have a local effect, it's not possible to include grouping in `\DTLaction` (although some of the underlying commands may introduce grouping). Therefore the options need to be reset at the start, and so there's no provision for use of those options in `\DTLsetup`.

```
\NewDocumentCommand \DTLaction { o m }
{
```

Initialise settings. Column index:

```
\int_zero:N \l__datatool_action_column_int
\int_zero:N \l__datatool_action_column_ii_int
```

Column key:

```
\tl_clear:N \l__datatool_action_key_tl
\tl_clear:N \l__datatool_action_key_ii_tl
```

Data type:

```
\int_set_eq:NN
\l__datatool_action_type_int
\c_datatool_unknown_int
```

Row index:

```
\int_zero:N \l__datatool_action_row_int
\int_zero:N \l__datatool_action_row_ii_int
```

Value:

```
\tl_set:Nn \l__datatool_action_value_tl { \q_no_value }
```

List settings:

```
\clist_clear:N \l__datatool_action_options_clist
\clist_clear:N \l__datatool_action_assign_clist
\clist_clear:N \l__datatool_action_keys_clist
\clist_clear:N \l__datatool_action_columns_clist
\seq_clear:N \l__datatool_action_columns_seq
\seq_clear:N \l__datatool_action_names_seq
```

Return formatting:

```
\bool_set_false:N \l__datatool_action_datum_bool
\int_set:Nn \l__datatool_action_datum_round_int { -1 }
\bool_set_true:N \l__datatool_action_datum_locale_decimal_bool
\bool_set_false:N \l__datatool_action_datum_locale_integer_bool
\tl_set:Nn \l__datatool_action_datum_currency_tl
{ \l__datatool_item_currency_tl }
```

Return Values:

```
\clist_clear:N \l__datatool_action_return_clist
\tl_set_eq:NN \l__datatool_action_return_tl \dtlnovalue
\prop_clear:N \l__datatool_action_return_prop
\IfValueT { #1 }
{ \keys_set:nn { datatool/action } { #1 } }
```

Get database name for actions that require a single name:

```
\seq_if_empty:NTF \l__datatool_action_names_seq
{
```

Name not set so use default name.

```
\tl_set_eq:NN
  \l__datatool_action_name_tl
  \l__datatool_default_dbname_tl
}
```

Set name to first one in the list.

```
\tl_set:Nx \l__datatool_action_name_tl
{
  \seq_item:Nn \l__datatool_action_names_seq
  { \c_one_int }
}
```

Save action name:

```
\tl_set:Nx \l__datatool_action_tl { \tl_trim_spaces:n { #2 } }
```

Do action:

```
\cs_if_exist_use:cF { __datatool_action_ \l__datatool_action_tl : }
{
  \PackageError { datatool }
  { Unknown ~ action ~ ` \l__datatool_action_tl ' }
  { The ~ action ~ in ~ the ~ mandatory ~ argument ~ of ~
    \token_to_str:N \DTLaction \c_space_tl ~ is ~ not ~ recognised }
}
```

Assign return values to provided token list variables, if set.

```
\clist_if_empty:NF \l__datatool_action_return_clist
{
  \keyval_parse:NNV
  \__datatool_cskey_missing_val:n
  \__datatool_action_get:nn
  \l__datatool_action_return_clist
}
}
```

Internal variables for \DTLaction:

```
\tl_new:N \l__datatool_action_tl
\tl_new:N \l__datatool_action_name_tl
\tl_new:N \l__datatool_action_key_tl
\tl_new:N \l__datatool_action_key_ii_tl
\int_new:N \l__datatool_action_column_int
\int_new:N \l__datatool_action_column_ii_int
\int_new:N \l__datatool_action_row_int
\int_new:N \l__datatool_action_row_ii_int
\int_new:N \l__datatool_action_type_int
```

```

\int_set_eq:NN \l_datatool_action_type_int \c_datatool_unknown_int
\tl_new:N \l_datatool_action_value_tl
\tl_set:Nn \l_datatool_action_value_tl { \q_no_value }
\bool_new:N \l_datatool_action_datum_bool
\seq_new:N \l_datatool_action_names_seq
\clist_new:N \l_datatool_action_options_clist
\clist_new:N \l_datatool_action_assign_clist
\clist_new:N \l_datatool_action_return_clist
\clist_new:N \l_datatool_action_keys_clist
\clist_new:N \l_datatool_action_columns_clist
\seq_new:N \l_datatool_action_columns_seq

Scratch variables.
\tl_new:N \l_datatool_action_tmpa_tl
\tl_new:N \l_datatool_action_tmpb_tl
\seq_new:N \l_datatool_action_tmp_options_seq
\seq_new:N \l_datatool_action_tmp_data_seq

Define keys. (These can only be set in the optional argument of \DTLaction.)
\keys_define:nn { datatool/action }
{
  name .code:n =
  {
    \exp_args:NNx \seq_set_from_clist:Nn
      \l_datatool_action_names_seq { #1 }
  },
  name .value_required:n = true,
  key .str_set_x:N = \l_datatool_action_key_tl,
  key .value_required:n = true,
  key2 .str_set_x:N = \l_datatool_action_key_ii_tl,
  key2 .value_required:n = true,
  column .int_set:N = \l_datatool_action_column_int,
  column .value_required:n = true,
  column2 .int_set:N = \l_datatool_action_column_ii_int,
  column2 .value_required:n = true,
  row .int_set:N = \l_datatool_action_row_int,
  row .value_required:n = true,
  row2 .int_set:N = \l_datatool_action_row_ii_int,
  row2 .value_required:n = true,
  value .tl_set:N = \l_datatool_action_value_tl,
  value .value_required:n = true,
  expand-value .tl_set_x:N = \l_datatool_action_value_tl,
  expand-value .value_required:n = true,
  expand-once-value .code:n =
  { \tl_set:No \l_datatool_action_value_tl { #1 } },
  expand-once-value .value_required:n = true,
  options .clist_set:N = \l_datatool_action_options_clist,
  options .value_required:n = true,
  assign .clist_set:N = \l_datatool_action_assign_clist,
  assign .value_required:n = true,
  keys .clist_set:N = \l_datatool_action_keys_clist,

```

```

keys .value_required:n = true,
columns .clist_set:N = \l_datatool_action_columns_clist,
columns .value_required:n = true,
return .clist_set:N = \l_datatool_action_return_clist,
return .value_required:n = true,
type .choice:,
type .value_required:n = true,
type / string .code:n =
  {
    \int_set_eq:NN \l_datatool_action_type_int \c_datatool_string_int
  },
type / integer .code:n =
  {
    \int_set_eq:NN \l_datatool_action_type_int \c_datatool_integer_int
  },

```

Synonym:

```

type / int .code:n =
  {
    \int_set_eq:NN \l_datatool_action_type_int \c_datatool_integer_int
  },
type / decimal .code:n =
  {
    \int_set_eq:NN \l_datatool_action_type_int \c_datatool_decimal_int
  },

```

Synonym:

```

type / real .code:n =
  {
    \int_set_eq:NN \l_datatool_action_type_int \c_datatool_real_int
  },
type / currency .code:n =
  {
    \int_set_eq:NN \l_datatool_action_type_int \c_datatool_currency_int
  },
type / datetime .code:n =
  {
    \int_set_eq:NN \l_datatool_action_type_int \c_datatool_datetime_int
  },

```

Synonym:

```

type / timestamp .code:n =
  {
    \int_set_eq:NN \l_datatool_action_type_int \c_datatool_datetime_int
  },
type / date .code:n =
  {
    \int_set_eq:NN \l_datatool_action_type_int \c_datatool_date_int
  },
type / time .code:n =
  {

```

```

        \int_set_eq:NN \l_datatool_action_type_int \c_datatool_time_int
    },
    datum .code:n =
    {
        \tl_if_eq:nnTF { #1 } { false }
        {
            \bool_set_false:N \l_datatool_action_datum_bool
        }
        {
            \bool_set_true:N \l_datatool_action_datum_bool
            \tl_if_eq:nnF { #1 } { true }
            {
                \keys_set:nn { datatool/action/datum } { #1 }
            }
        }
    },
    datum .default:n = true ,
}

```

Sub keys for datum option:

```

\int_new:N \l_datatool_action_datum_round_int
\int_set:Nn \l_datatool_action_datum_round_int { -1 }
\bool_new:N \l_datatool_action_datum_locale_decimal_bool
\bool_set_true:N \l_datatool_action_datum_locale_decimal_bool
\bool_new:N \l_datatool_action_datum_locale_integer_bool
\tl_new:N \l_datatool_action_datum_currency_tl
\tl_set:Nn \l_datatool_action_datum_currency_tl
{ \l_datatool_item_currency_tl }

```

Define keys:

```

\keys_define:nn { datatool/action/datum }
{
    round .code:n =
    {
        \tl_if_eq:nnTF { #1 } { false }
        {
            \int_set:Nn \l_datatool_action_datum_round_int { -1 }
        }
        {
            \int_set:Nn \l_datatool_action_datum_round_int { #1 }
        }
    },
    round .default:n = 0 ,
    locale-decimal .bool_set:N =
        \l_datatool_action_datum_locale_decimal_bool ,
    locale-integer .bool_set:N =
        \l_datatool_action_datum_locale_integer_bool ,
    currency .choice: ,
    currency / false .code:n =
    {
        \tl_clear:N \l_datatool_action_datum_currency_tl
    }
}

```

```

    } ,
    currency / match .code:n =
    {
        \tl_set:Nn
            \l__datatool_action_datum_currency_tl
            { \l__datatool_item_currency_tl }
    } ,
    currency / default .code:n =
    {
        \tl_set:Nn
            \l__datatool_action_datum_currency_tl
            { \@dtl@currency }
    } ,
    currency / unknown .code:n =
    {
        \tl_set:Nn
            \l__datatool_action_datum_currency_tl
            { #1 }
    } ,
    currency .default:n = default ,
}

```

Return value(s):

```

\tl_new:N \l__datatool_action_return_tl
\tl_set_eq:NN \l__datatool_action_return_tl \dtlnovalue
\tl_new:N \l__datatool_action_secondary_tl
\prop_new:N \l__datatool_action_return_prop

```

The datum option only governs the secondary return results. The primary return result isn't converted.

Secondary return result is a string:

```

\cs_new:Nn \__datatool_put_return_action_string:nn
{
    \tl_if_head_eq_meaning:nNTF
        { #2 } \__datatool_datum:w
    {

```

In weird format. Needs conversion.

```

        \prop_put:Nnx \l__datatool_action_return_prop
            { #1 } { #2 }
    }
    {
        \tl_if_head_eq_meaning:nNTF
            { #2 } \__datatool_datum:nnnn
    }

```

Already in datum format. Leave it as is.

```

        \prop_put:Nnn \l__datatool_action_return_prop
            { #1 } { #2 }
    }
    {

```

```

    \bool_if:NTF \l__datatool_action_datum_bool
    {
      \prop_put:Nnn \l__datatool_action_return_prop
        { #1 }
      {
        \__datatool_datum:nxxx
          { #2 } { } { } { \c_datatool_string_int }
        }
      }
    }
  }
}
\cs_generate_variant:Nn \__datatool_put_return_action_string:nn
{ nV, nv, nx, xV }
Secondary return result is an integer:
\cs_new:Nn \__datatool_put_return_action_int:nn
{
  \bool_if:NTF \l__datatool_action_datum_bool
  {
    \bool_if:NTF \l__datatool_action_datum_locale_integer_bool
    {
      \DTLdecimaltolocale { #2 }
      \l__datatool_action_secondary_tl
      \prop_put:Nnx \l__datatool_action_return_prop
        { #1 }
      {
        \exp_not:N \__datatool_datum:nxxx
          { \l__datatool_action_secondary_tl }
          { #2 }
          { }
          { \exp_not:N \c_datatool_integer_int }
        }
      }
    }
  }
  \tl_if_head_eq_meaning:nNTF
  { #2 } \__datatool_datum:w
  {
    In weird format. Needs conversion.
    \prop_put:Nnx \l__datatool_action_return_prop
      { #1 } { #2 }
    }
  }
  \tl_if_head_eq_meaning:nNTF
  { #2 } \__datatool_datum:nxxx
  {

```

Already in datum format. Leave it as is.

```
        \prop_put:Nnn \l__datatool_action_return_prop
        { #1 } { #2 }
      }
    {
      \prop_put:Nnn \l__datatool_action_return_prop
      { #1 }
      {
        \__datatool_datum:nnnn
        { #2 } { #2 } { } { \c_datatool_integer_int }
      }
    }
  }
}
{
  \prop_put:Nnn \l__datatool_action_return_prop
  { #1 } { #2 }
}
}
\cs_generate_variant:Nn \__datatool_put_return_action_int:nn
{ nV, nv, nx }
```

Secondary return result is a decimal.

```
\cs_new:Nn \__datatool_put_return_action_decimal:nn
{
  \tl_set:Nn \l__datatool_action_secondary_tl { #2 }
  \__datatool_rm_weird_datum:N
  \l__datatool_action_secondary_tl
  \exp_args:NV \tl_if_head_eq_meaning:nNTF
  \l__datatool_action_secondary_tl
  \__datatool_datum:nnnn
  {
    \tl_set:Nx \l__datatool_action_secondary_tl
    { \DTLdatumvalue { \l__datatool_action_secondary_tl } }
  }
}
\bool_if:NTF \l__datatool_action_datum_bool
{
  \int_compare:nNnT
  { \l__datatool_action_datum_round_int } > { -1 }
  {
    \dtlround
    \l__datatool_action_secondary_tl
    \l__datatool_action_secondary_tl
    { \int_use:N \l__datatool_action_datum_round_int }
  }
}
\bool_if:NT \l__datatool_action_datum_locale_decimal_bool
{
  \exp_args:NV \DTLdecimaltolocale
  \l__datatool_action_secondary_tl
}
```

```

        \l__datatool_action_secondary_tl
    }
\l_if_empty:NF \l__datatool_action_datum_currency_tl
{
    \l_if_eq:NnTF
        \l__datatool_action_datum_currency_tl
        { \l__datatool_item_currency_tl }
    {
        \l_if_empty:NF \l__datatool_item_currency_tl
        {
            \l_set:Nx \l__datatool_action_secondary_tl
            {
                \exp_not:N \DTLfmtcurrency
                { \exp_not:V \l__datatool_item_currency_tl }
                { \exp_not:V \l__datatool_action_secondary_tl }
            }
        }
    }
}
{
    \l_if_eq:NnTF
        \l__datatool_action_datum_currency_tl
        { \@dtl@currency }
    {
        \l_set:Nx \l__datatool_action_secondary_tl
        {
            \exp_not:N \DTLfmtcurrency
            { \exp_not:V \@dtl@currency }
            { \exp_not:V \l__datatool_action_secondary_tl }
        }
    }
}
{
    \l_set:Nx \l__datatool_action_secondary_tl
    {
        \exp_not:N \DTLfmtcurrency
        { \exp_not:V \l__datatool_action_datum_currency_tl }
        { \exp_not:V \l__datatool_action_secondary_tl }
    }
}
}
}
\prop_put:Nnx \l__datatool_action_return_prop
{ #1 }
{
    \exp_not:N \__datatool_datum:nnnn
    { \exp_not:V \l__datatool_action_secondary_tl }
    { #2 } { }
    { \exp_not:N \c_datatool_decimal_int }
}
}
{

```

```

        \prop_put:NnV \l__datatool_action_return_prop
        { #1 } \l__datatool_action_secondary_tl
    }
}
\cs_generate_variant:Nn \__datatool_put_return_action_decimal:nn
{ nV, nv, nx }
Secondary result should be parsed if applicable.
\cs_new:Nn \__datatool_put_return_action_parse:nn
{
    \bool_if:NTF \l__datatool_action_datum_bool
    {
        \__datatool_parse:Nn
        \l__datatool_action_secondary_tl { #2 }
    }
    {
        \tl_set:Nn \l__datatool_action_secondary_tl { #2 }
        \__datatool_rm_weird_datum:N
        \l__datatool_action_secondary_tl
    }
    \prop_put:NnV \l__datatool_action_return_prop
    { #1 } \l__datatool_action_secondary_tl
}
\cs_generate_variant:Nn \__datatool_put_return_action_parse:nn
{ VV, xV }
Assign secondary return properties using column keys as name and value obtained
from corresponding element in the given row specs.
\cs_new:Nn \__datatool_set_return_from_row:nn
{
    \int_step_inline:nn
    { \DTLcolumncount { #2 } }
    {
        \__datatool_get_entry_from_row:Nnn \l__datatool_item_value_tl
        { ##1 } { #1 }
        \datatool_if_null:NF \l__datatool_item_value_tl
        {
            \@dtl@getkeyforcolumn
            \l__datatool_item_key_tl
            { #2 }
            { ##1 }
            \__datatool_put_return_action_parse:VV
            \l__datatool_item_key_tl
            \l__datatool_item_value_tl
        }
    }
}
\cs_generate_variant:Nn \__datatool_set_return_from_row:nn
{ Vn }
Add to options sequence unless already present:

```

```

\cs_new:Nn \__datatool_add_action_option:n
{
  \seq_if_in:NnF
    \l__datatool_action_tmp_options_seq { #1 }
    {
      \seq_put_right:Nn
        \l__datatool_action_tmp_options_seq { #1 }
    }
}

```

Tests if the given option has been added:

```

\cs_new:Nn \__datatool_if_action_option:nTF
{
  \seq_if_in:NnTF
    \l__datatool_action_tmp_options_seq { #1 }
    { #2 } { #3 }
}
\cs_new:Nn \__datatool_if_action_option:nT
{
  \seq_if_in:NnT
    \l__datatool_action_tmp_options_seq { #1 }
    { #2 }
}

```

\DTLifaction{<prop-key>}{<true>}{<false>}

\DTLifaction

```

\newcommand{\DTLifaction}[3]{
  \tl_if_empty:nTF { #1 }
  {
    \tl_if_eq:NNTF \l__datatool_action_return_tl \dtlnovalue
      { #3 } { #2 }
  }
  {
    \prop_if_in:NnTF \l__datatool_action_return_prop { #1 }
      { #2 } { #3 }
  }
}

```

\DTLget Get the return value. The first argument should either be empty or a property key. The second argument should be a token list in which to store the return value.

```

\NewDocumentCommand \DTLget { O{} m }
{
  \tl_if_blank:nTF { #1 }
  {
    \tl_set_eq:NN #2 \l__datatool_action_return_tl
  }
  {

```

```

    \__datatool_action_get:nn { #2 } { #1 }
  }
}
\cs_new:Nn \__datatool_action_get:nn
{
  \tl_if_single:nTF { #1 }
  {
    \prop_get:NnN \l__datatool_action_return_prop { #2 }
      #1
    \quark_if_no_value:NT #1
    {
      \tl_set_eq:NN #1 \dtlnovalue
    }
  }
}
{
  \PackageError { datatool }
  {
    Control ~ sequence ~ expected ~ (to ~ store ~ return ~
    value): ~ found ~ \tl_to_str:n { #1 }
  }
  {
    To ~ fetch ~ an ~ action ~ return ~ value ~ you ~ need ~
    to ~ provide ~ a ~ command ~ to ~ be ~ defined ~ to ~
    the ~ returned ~ value
  }
}
}
}
\cs_new:Nn \__datatool_cskey_missing_val:n
{
  \PackageError { datatool}
  {
    Invalid ~ cs=key ~ assignment ~ syntax ~ in ~
    '\tl_to_str:n { #1 }' : ~
    missing ~ key ~ or ~ property ~ name
  }
  {
    Column ~ or ~ property ~ assignment ~ lists ~ need ~ to ~
    have ~ each ~ element ~ in ~ the ~ list ~ in ~ the ~
    form ~ <cs>=<label> ~ where ~ <cs> ~ is ~ a ~ control ~
    sequence ~ (placeholder ~ command) ~ and ~ <label> ~
    is ~ the ~ label ~ identifying ~ the ~ required ~ column ~ or ~ property
  }
}
}

```

\DTLuse Use the return value. As \DTLget but typesets the result. Partially expandable.

```

\newcommand* \DTLuse [ 1 ]
{
  \tl_if_empty:nTF { #1 }
  { \l__datatool_action_return_tl }
}

```

```

    { \@dtl@userresult { #1 } }
  }
\@dtl@userresult Robust.
\newrobustcmd* \@dtl@userresult [ 1 ]
{
  \tl_if_blank:nTF { #1 }
  {
    \l__datatool_action_return_tl
  }
  {
    \prop_get:NnN \l__datatool_action_return_prop { #1 }
    \l__datatool_tmpb_tl
    \quark_if_no_value:NTF \l__datatool_tmpb_tl
    {
      \dtlnovalue
    }
    {
      \l__datatool_tmpb_tl
    }
  }
}
\cs_new:Nn \__datatool_action_noop:Nn
{
  \PackageError {datatool}
  {
    Action ~ `#2' ~ may ~ only ~ be ~ used ~ within ~ \token_to_str:N #1
  }
  {}
}
\cs_new:Nn \__datatool_action_error:nnn
{
  \PackageError { #1 }
  {
    Action ~ ` \l__datatool_action_tl ' : ~ #2
  }
  { #3 }
}
\cs_new:Nn \__datatool_action_error:nn
{
  \__datatool_action_error:nnn { datatool } { #1 } { #2 }
}
\cs_new:Nn \__datatool_action_error:n
{
  \__datatool_action_error:nn { #1 } { }
}

```

Commands provided for checking common syntax problems for actions. The true argument is done if successful. The false argument is done if an error occurs.

```

\cs_new:Nn \__datatool_require_database:TF
{
  \DTLifdbexists { \l__datatool_action_name_tl }
  {
    #1
  }
  {
    \__datatool_action_error:nn
    {
      Database ~ ``\l__datatool_action_name_tl' ~ doesn't ~ exist
    }
    {
      Check ~ you ~ have ~ spelt ~ the ~ database ~ name ~
      correctly ~ in ~
      \token_to_str:N \DTLaction [name={ \l__datatool_action_name_tl }]
      { \l__datatool_action_tl } ~ or ~ check ~ the ~ default-
name ~
      option ~ in ~ \token_to_str:N \DTLsetup
    }
    #2
  }
}
\cs_new:Nn \__datatool_require_database:T
{
  \__datatool_require_database:TF { #1 } { }
}

```

For actions where the database name should be in \dtldbname not specified by the name key.

```

\cs_new:Nn \__datatool_requires_dbname:T
{
  \tl_if_empty:NTF \dtldbname
  {
    \__datatool_action_error:nn
    {
      no ~ current ~ database ~ selected ~
      or ~ \token_to_str:N \dtldbname \c_space_tl ~
      has ~ unexpectedly ~ been ~ cleared
    }
    {
      The ~ action ~ ``\l__datatool_action_tl' ~
      is ~ for ~ use ~ within ~ certain ~ types ~
      of ~ loops ~ or ~ after ~ a ~ row ~ has ~
      been ~ identified ~ as ~ the ~ current ~ row ~
      or ~ other ~ type ~ of ~ command ~ that ~ sets ~
      the ~ placeholder ~ \token_to_str:N \dtldbname
    }
  }
  {
    \tl_if_eq:NNF

```

```

\l__datatool_action_name_tl
\l__datatool_default_dbname_tl
{
  \tl_if_eq:NNF
    \l__datatool_action_name_tl
    \dtldbname
  {
    \PackageWarning { datatool }
    {
      Ignoring ~ name = { \l__datatool_action_name_tl } ~
      for ~ action ~ ` \l__datatool_action_tl '
    }
  }
}
\l__datatool_action_name_tl
\dtldbname
\DTLifdbexists { \dtldbname }
{ #1 }
{
  \__datatool_action_error:nn
  {
    No ~ current ~ row ~ selected ~ or ~
    \token_to_str:N \dtldbname \c_space_tl ~
    has ~ been ~ changed
  }
  { }
}
}
}
}

```

Gathers placeholder=colkey assignment and sets temporary sequence with each element in the form $\{\langle cs \rangle\}\{\langle col\text{-key} \rangle\}\{\langle col\text{-idx} \rangle\}\{\langle col\text{-type} \rangle\}$

```

\cs_new:Nn \__datatool_get_placeholder_assign:
{
  \seq_clear:N \l__datatool_action_tmp_data_seq
  \keyval_parse:nnV
  { \__datatool_cskey_missing_val:n }
  { \__datatool_action_placeholder_cskey:nn }
  \l__datatool_action_assign_clist
}
\cs_new:Nn \__datatool_action_placeholder_cskey:nn
{
  \tl_if_single_token:nTF { #1 }
  {
    \tl_set:Nn #1 { \c_datatool_nullvalue_tl }
  }
}

```

Get the column index:

```

\tl_if_exist:cTF { dtl@ci@ \l__datatool_action_name_tl @ #2 }
{

```

```

    \__datatool_get_col_type:vv
    { dtlkeys@ \l__datatool_action_name_tl }
    { dtl@ci@ \l__datatool_action_name_tl @ #2 }
    \seq_put_right:Ne \l__datatool_action_tmp_data_seq
    {
      { \exp_not:N #1 } { #2 }
      { \tl_use:c { dtl@ci@ \l__datatool_action_name_tl @ #2 } }
      { \int_use:N \l__datatool_item_type_int }
    }
  }
  {
    \__datatool_action_error:nn
    {
      Unknown ~ column ~ ` #2 '
    }
    {
      Database ~ ` \l__datatool_action_name_tl ' ~ does ~ not ~
      have ~ a ~ column ~ labelled ~ ` #2 '
    }
  }
}
{
  \__datatool_action_error:nn
  {
    Single ~ placeholder ~ command ~ required ~ in ~ assignment, ~ found ~
    ` \tl_to_str:n { #1 } '
  }
  {
    The ~ `assign' ~ option ~ requires ~ a ~ list ~ with ~
    elements ~ in ~ the ~ form ~ <tl-var>=<column-key>
  }
}
}
}
Perform assignments on given row specs
\cs_new:Nn \__datatool_do_action_assignments:n
{
  \seq_map_inline:Nn \l__datatool_action_tmp_data_seq
  {
    Each element in the form: {<cs>}{<col-key>}{<col-idx>}{<col-type>}
    \__datatool_do_action_row_assign:nNnn { #1 } ##1
  }
}
Perform assignment.
\cs_new:Nn \__datatool_do_action_row_assign:nNnn
{
  \__datatool_get_entry_from_row:Nnn #2 { #4 } { #1 }
  \tl_if_eq:NnT #2 { \c_datatool_nullvalue_tl }
  {

```

```

        \datatool_if_numeric_datum_type:nTF { #5 }
        {
            \tl_set_eq:NN #2 \DTLnumbernull
        }
        {
            \tl_set_eq:NN #2 \DTLstringnull
        }
    }
}

Generate error if both key and column found with given help message on error.
\cs_new:Nn \__datatool_forbid_key_and_column:n
{
    \int_if_zero:nF { \l__datatool_action_column_int }
    {
        \__datatool_action_error:nn
        {
            `column' ~ not ~ permitted
        }
        { #1 }
    }
    \tl_if_empty:NF \l__datatool_action_key_tl
    {
        \__datatool_action_error:nn
        {
            `key' ~ not ~ permitted
        }
        { #1 }
    }
}

Require 'value'.
\cs_new:Nn \__datatool_require_value:TF
{
    \quark_if_no_value:NTF \l__datatool_action_value_tl
    { #2 }
    { #1 }
}
\cs_new:Nn \__datatool_require_value:T
{
    \__datatool_require_value:TF
    { #1 }
    {
        \__datatool_action_error:nn
        { missing ~ value }
        {
            You ~ need ~ to ~ set ~ `value' ~ in ~ the ~ optional ~ argument ~
            of ~ \token_to_str:N \DTLaction[...]
            { \l__datatool_action_tl }. ~
            If ~ an ~ empty ~ value ~ is ~ required, ~ do ~
            value={ }
        }
    }
}

```

```

    }
  }
}
Arguments: <row int var>{<not set>}{<true>}{<false>}
\cs_new:Nn \__datatool_optional_row:NnTF
{
  \int_if_zero:nTF { #1 }
  { #2 }
  {
    \bool_lazy_or:nnTF
    {
      \int_compare_p:nNn { #1 } < { \c_zero_int }
    }
    {
      \int_compare_p:nNn
      { #1 }
      >
      { \DTLrowcount { \l__datatool_action_name_tl } }
    }
  }
  {
    \__datatool_action_error:nn
    {
      Invalid ~ row ~ index ~ \int_use:N #1
    }
    {
      Database ~ ``\l__datatool_action_name_tl' ~ row ~ index ~
      must ~ be ~ in ~ the ~ range ~
      [ 1 , ~ \DTLrowcount { \l__datatool_action_name_tl } ]
    }
  }
  #4
}
{ #3 }
}
}
\cs_new:Nn \__datatool_optional_row:NnTF
{
  \__datatool_optional_row:NnTF #1 { #3 } { #2 } { #3 }
}
\cs_new:Nn \__datatool_optional_row:NnNF
{
  \__datatool_optional_row:NnTF #1 { } { #2 }
}
}
Arguments: {(key setting name)}{key str var}{(column setting name)}{col int
var}{(not set)}{(true)}{(false)}
One column may be identified: 'key' or 'column' allowed but both not permitted. A
negative column index is an error and will reset the index to zero. The (no set) argument
is done if neither set.
\cs_new:Nn \__datatool_optional_key_xor_column:nNnNnTF

```

```

{
Check the column index hasn't been set to a negative number.
\int_compare:nNnTF
  { #4 }
  <
  { \c_zero_int }
{
\_datatool_action_error:nn
{
Negative ~ `#3' ~ value ~
\int_use:N #4 \c_space_tl
not ~ permitted
}
{
You ~ need ~ to ~ correct ~ the ~ value ~ in ~ the ~
`#3' ~ setting ~ in ~
\token_to_str:N \DTLaction
[#3=\int_use:N #4 \c_space_tl,...]
{ \l_datatool_action_tl } ~
(or ~ use ~ `#1' ~ instead)
}
\int_zero:N #4

```

Negative column index is a failure (do false).

```

#7
}
{
\tl_if_empty:NTF #2
{

```

No key has been supplied. Has a column index been provided?

```

\int_if_zero:nTF #4
{

```

Neither provided. Do *(no set)* argument.

```

#5
}
{

```

A column index has been provided. Success (but no guarantee the column is defined).

Do true argument.

```

#6
}
}
{

```

A key has been supplied. Has a column index been provided?

```

\int_if_zero:nTF #4
{

```

A key has been supplied but no column index. Success (but no guarantee the key is valid). Do true argument.

```

#6
}
{

```

A column index has been provided as well. Failure. Do false argument.

```

\__datatool_action_error:nn
{
  can't ~ have ~ both ~ `#1' ~ and ~ `#3' ~ set
}
{
  either ~ have ~ `#1' ~ or ~ `#3' ~ in ~ the ~ optional ~
  argument ~ of ~ \token_to_str:N \DTLaction [...]
  { \l__datatool_action_tl } ~ but ~ not ~ both
}
#7
}
}
}
}

```

Arguments: $\langle not\ set \rangle$ $\langle true \rangle$ $\langle false \rangle$

One column may be identified: ‘key’ or ‘column’ allowed but both not permitted. A negative column index is an error and will reset the index to zero. The first argument is done if neither set.

```

\cs_new:Nn \__datatool_optional_key_xor_column:nTF
{
  \__datatool_optional_key_xor_column:nNnNnTF
  { key } \l__datatool_action_key_tl
  { column } \l__datatool_action_column_int
  { #1 } { #2 } { #3 }
}

```

Second column may be identified: ‘key2’ or ‘column2’ allowed but both not permitted. A negative column index is an error and will reset the index to zero. The first argument is done if neither set.

```

\cs_new:Nn \__datatool_optional_key_ii_xor_column_ii:nTF
{
  \__datatool_optional_key_xor_column:nNnNnTF
  { key2 } \l__datatool_action_key_ii_tl
  { column2 } \l__datatool_action_column_ii_int
  { #1 } { #2 } { #3 }
}

```

Arguments: $\langle key\ setting\ name \rangle$ $\langle key\ str\ var \rangle$ $\langle column\ setting\ name \rangle$ $\langle col\ int\ var \rangle$ $\langle not\ set \rangle$ $\langle key\ undef \rangle$ $\langle true \rangle$ $\langle false \rangle$

One column may be identified: ‘key’ or ‘column’ optional but both not permitted. If the key is provided, obtain the index. The $\langle not\ set \rangle$ argument is done if no key or column index provided. The $\langle key\ undef \rangle$ argument is done if no column matches the given key.

```

\cs_new:Nn \__datatool_optional_key_xor_column_get_column:nNnNnTF

```

```
{
  \__datatool_optional_key_xor_column:nNnNnTF
  { #1 } { #2 } { #3 } { #4 }
  {
```

No key or column index provided. Do *<not set>* argument.

```
    #5
  }
  {
```

A column has been identified either by key or column index.

```
    \int_if_zero:nTF #4
  {
```

No column index so it must have been identified by key. Get the corresponding index.

```
    \tl_if_exist:cTF
    {
      dtl @ ci
      @ \__datatool_action_name_tl
      @ #2
    }
  {
```

Column index found. Success. Do true argument.

```
    \exp_args:NNv \int_set:Nn
    #4
    {
      dtl @ ci
      @ \__datatool_action_name_tl
      @ #2
    }
    #7
  }
  {
```

No match on key. Do *<key undef>* argument.

```
    #6
  }
  {
```

Column index was provided (but no guarantee it's within range). Success. Do true argument.

```
    #7
  }
  {
```

Invalid key or column setting (negative index or both set). Failure. Do false argument.

```
    #8
  }
}
```

Arguments: {<not set>}{<key undef>}{<true>}{<false>}

```
\cs_new:Nn \__datatool_optional_key_xor_column_get_column:nnTF
{
  \__datatool_optional_key_xor_column_get_column:nNnNnnTF
  { key } \l__datatool_action_key_tl
  { column } \l__datatool_action_column_int
  { #1 } { #2 } { #3 } { #4 }
}
\cs_new:Nn \__datatool_optional_key_xor_column:TF
{
  \__datatool_optional_key_xor_column:nTF { #1 } { #1 } { #2 }
}

```

Second column may be identified:

```
\cs_new:Nn \__datatool_optional_key_ii_xor_column_ii_get_column:nnTF
{
  \__datatool_optional_key_xor_column_get_column:nNnNnnTF
  { key2 } \l__datatool_action_key_ii_tl
  { column2 } \l__datatool_action_column_ii_int
  { #1 } { #2 } { #3 } { #4 }
}
\cs_new:Nn \__datatool_optional_key_ii_xor_column_ii:TF
{
  \__datatool_optional_key_ii_xor_column_ii:nTF { #1 } { #1 } { #2 }
}

```

Arguments: {<key setting name>}{<key str var>}{<column setting name>}{<col int var>}{<not set>}{<true>}{<false>}

'key' or 'column' optional but both not permitted. If the key is provided, obtain the index. The <not set> argument is done if no key or column index provided. Require column existence if key or column provided.

```
\cs_new:Nn \__datatool_optional_key_xor_column_get_column:nNnNnTF
{
  \__datatool_optional_key_xor_column_get_column:nNnNnnTF
  { #1 } { #2 } { #3 } { #4 }
  { #5 }
}

```

Column key not valid. Failure. Do false.

```
\__datatool_action_error:nn
{
  no ~ column ~ found ~ with ~ key ~
  ` #2 ' ~
  in ~ database ~ ` \l__datatool_action_name_tl '
}
{
  Check ~ that ~ you ~ have ~ correctly ~ spelt ~
  the ~ column ~ key ~ in ~ the ~ optional ~
  argument ~ of ~ \token_to_str:N \DTLaction [...]
}

```

```

        { \l__datatool_action_tl } ~ and ~ that ~
        the ~ database ~ name ~ is ~ correct
    }
    #7
}
{

```

Positive column index provided or obtained from the key. Check that column index is less than the total number of columns for the database.

```

\int_compare:nNnTF
{ #4 }
>
{
  \int_use:c
  { dtlcols@ \l__datatool_action_name_tl }
}
{

```

Out of range. Failure. Do false. (If the key was originally provided, then the column index must be valid unless the internals are incorrect.)

```

\__datatool_action_error:nn
{
  `#3' ~ value ~
  \int_use:N #4 \c_space_tl ~
  out ~ of ~ range ~ for ~ database ~
  ` \l__datatool_action_name_tl '
}
{
  The ~ database ~ ` \l__datatool_action_name_tl ' ~
  only ~ has ~
  \int_use:c { dtlcols@ \l__datatool_action_name_tl }
  \c_space_tl ~ column(s)
}
#7
}
{

```

Valid. Success. Do true.

```

    #6
  }
}
{ #7 }
}
\cs_new:Nn \__datatool_optional_key_xor_column_get_column:nTF
{
  \__datatool_optional_key_xor_column_get_column:nNnNnTF
  { key } \l__datatool_action_key_tl
  { column } \l__datatool_action_column_int
  { #1 } { #2 } { #3 }
}

```

```

\cs_new:Nn \__datatool_optional_key_ii_xor_column_ii_get_column:nTF
{
  \__datatool_optional_key_xor_column_get_column:nNnNnTF
  { key2 } \l__datatool_action_key_ii_tl
  { column2 } \l__datatool_action_column_ii_int
  { #1 } { #2 } { #3 }
}

```

Arguments: $\langle\{key\ setting\ name\}\rangle\langle\{key\ str\ var\}\rangle\langle\{column\ setting\ name\}\rangle\langle\{col\ int\ var\}\rangle\langle\{not\ set\}\rangle\langle\{true\}\rangle\langle\{false\}\rangle$

One column may be identified: ‘key’ or ‘column’ optional but both not permitted. If the column index is provided, obtain the key. The $\langle\{not\ set\}\rangle$ argument is done if no key or column index provided. An error will be triggered if the index exceeds the column count.

```

\cs_new:Nn
  \__datatool_optional_key_xor_column_get_key:nNnNnTF
{
  \__datatool_optional_key_xor_column:nNnNnTF
  { #1 } { #2 } { #3 } { #4 }
  {

```

No key or column index provided. Do $\langle\{not\ set\}\rangle$ argument.

```

#5
}
{

```

A column has been identified either by key or column index.

```

\tl_if_empty:NTF #2
{

```

No key so column must’ve been identified by its index. Check if index doesn’t exceed the total number of columns.

```

\int_compare:nNnTF
{ #4 }
>
{ \DTLcolumncount { \l__datatool_action_name_tl } }
{

```

Index too large. Failure. Do false.

```

\__datatool_action_error:nn
{
  `#3' ~ index ~
  \int_use:N #4 \c_space_tl ~
  out ~ of ~ range ~ for ~ database ~
  ` \l__datatool_action_name_tl '
}
{
  The ~ database ~ ` \l__datatool_action_name_tl ' ~
  only ~ has ~
  \int_use:c { dtlcols@ \l__datatool_action_name_tl }
  \c_space_tl ~ column(s)
}

```

```

    }
    #7
  }
  {

```

Index in range. Find the key.

```

    \__datatool_get_col_key:vV
    { dtlkeys @ \l__datatool_action_name_tl }
    \l__datatool_action_column_int
    \quark_if_no_value:NTF \l__datatool_item_key_tl
    {

```

No key was found. Unlikely to happen given that the column index is in range. Has a column been removed from the column data without adjusting the other indexes?

```

    \__datatool_action_error:nn
    {
      No ~ key ~ can ~ be ~ found ~ for ~
      column ~ index ~
      \int_use:N #4 \c_space_tl ~ in ~
      ` \l__datatool_action_name_tl '
    }
    {
      Something ~ seems ~ to ~ have ~ gone ~
      wrong ~ with ~ the ~ column ~ metadata
    }
    #7
  }
  {

```

Key found. Success. Do true.

```

    \tl_set_eq:NN #2 \l__datatool_item_key_tl
    #6
  }
}
{

```

Key provided. Success. Do true.

```

    #6
  }
}
{

```

Invalid key or column setting (negative index or both set). Failure. Do false argument.

```

    #7
  }
}

```

Arguments: {<not set>}{<true>}{<false>}

```

\cs_new:Nn
\__datatool_optional_key_xor_column_get_key:nTF
{

```

```

    \__datatool_optional_key_xor_column_get_key:nNnNnTF
    { key } \l__datatool_action_key_tl
    { column } \l__datatool_action_column_int
    { #1 } { #2 } { #3 }
  }

```

If second column allowed:

```

\cs_new:Nn
  \__datatool_optional_key_ii_xor_column_ii_get_key:nTF
{
  \__datatool_optional_key_xor_column_get_key:nNnNnTF
  { key2 } \l__datatool_action_key_ii_tl
  { column2 } \l__datatool_action_column_ii_int
  { #1 } { #2 } { #3 }
}

```

Arguments: $\langle\textit{key setting name}\rangle\langle\textit{key str var}\rangle\langle\textit{column setting name}\rangle\langle\textit{col int var}\rangle\langle\textit{true}\rangle\langle\textit{false}\rangle$

One column required: ‘key’ or ‘column’ required but both not permitted. A negative column index will reset it to zero. No check if the key is valid or if the column index is less than the total number of columns.

```

\cs_new:Nn
  \__datatool_requires_key_xor_column:nNnNnTF
{
  \__datatool_optional_key_xor_column:nNnNnTF
  { #1 } #2 { #3 } #4
  {

```

No key or column provided. Failure. Do false.

```

  \__datatool_action_error:nn
  { missing ~ `#1' ~ or ~ `#3' }
  {
    You ~ need ~ to ~ set ~ `#1' ~ or ~ `#3' ~ in ~ the ~ optional ~
    argument ~ of ~ \token_to_str:N \DTLaction [...]
    { \l__datatool_action_tl } ~ to ~
    a ~ non-empty ~ value ~ (#1) ~ or ~ positive ~ integer ~ (#3) ~
    identifying ~ the ~ required ~ column
  }
  #6
}
{

```

Key or column provided. Success (but no guarantee that column index isn’t greater than the total number of columns). Do true.

```

  #5
}
{

```

Invalid syntax (negative column index or key and column both provided). Failure. Do false.

```

  #6

```

```

    }
  }
}

```

First column required:

```

\cs_new:Nn \__datatool_requires_key_xor_column:TF
{
  \__datatool_requires_key_xor_column:nNnNTF
  { key } \l__datatool_action_key_tl
  { column } \l__datatool_action_column_int
  { #1 } { #2 }
}

```

Do nothing if false (error messages will be triggered).

```

\cs_new:Nn \__datatool_requires_key_xor_column:T
{
  \__datatool_requires_key_xor_column:TF { #1 } { }
}

```

Second column required:

```

\cs_new:Nn \__datatool_requires_key_ii_xor_column_ii:TF
{
  \__datatool_requires_key_xor_column:nNnNTF
  { key2 } \l__datatool_action_key_ii_tl
  { column2 } \l__datatool_action_column_ii_int
  { #1 } { #2 }
}

```

Do nothing if false (error messages will be triggered).

```

\cs_new:Nn \__datatool_requires_key_ii_xor_column_ii:T
{
  \__datatool_requires_key_ii_xor_column_ii:TF { #1 } { }
}

```

Arguments: $\langle key\ setting\ name \rangle \langle key\ str\ var \rangle \langle column\ setting\ name \rangle \langle col\ int\ var \rangle \langle not\ set \rangle \langle true \rangle \langle false \rangle$

One column required: ‘key’ or ‘column’ required but both not permitted. The column index is required so if the key is provided, obtain the index. The $\langle not\ set \rangle$ argument is done if no column matches the given key.

```

\cs_new:Nn
  \__datatool_requires_key_xor_column_get_column:nNnNnTF
{
  \__datatool_requires_key_xor_column:TF
  {
    \int_if_zero:nTF #4
    {

```

No column index so it must have been identified by key. Get the corresponding index.

```

  \tl_if_exist:cTF
  {
    dtl @ ci
    @ \l__datatool_action_name_tl
    @ #2

```

```

    }
  {
    \exp_args:NNv \int_set:Nn
      #4
    {
      dtl @ ci
      @ \l_datatool_action_name_tl
      @ #2
    }
  }

```

Column index found. Success. Do true argument.

```

    #6
  }
  {

```

No match on key. Do *(not set)* argument.

```

    #5
  }
}
{

```

Column index was provided (but no guarantee it's within range). Success. Do true argument.

```

    #6
  }
}
{

```

Invalid key or column setting (negative index or both set). Failure. Do false argument.

```

    #7
  }
}

```

First column required.

```

\cs_new:Nn
  \__datatool_requires_key_xor_column_get_column:nTF
{
  \__datatool_requires_key_xor_column_get_column:nNnNnTF
  { key } \l_datatool_action_key_tl
  { column } \l_datatool_action_column_int
  { #1 } { #2 } { #3 }
}

```

Second column required.

```

\cs_new:Nn
  \__datatool_requires_key_ii_xor_column_ii_get_column:nTF
{
  \__datatool_requires_key_ii_xor_column_ii_get_column:nNnNnTF
  { key2 } \l_datatool_action_key_ii_tl
  { column2 } \l_datatool_action_column_ii_int
  { #1 } { #2 } { #3 }
}

```

Arguments: $\{\langle key\ setting\ name\rangle\}\langle key\ str\ var\rangle\{\langle column\ setting\ name\rangle\}\langle col\ int\ var\rangle\{\langle true\rangle\}\{\langle false\rangle\}$

One column required: 'key' or 'column' required but both not permitted. The column index is required so if the key is provided, obtain the index. Require column existence if key or column provided.

```
\cs_new:Nn
  \__datatool_requires_key_xor_column_get_column:nNnNTF
{
  \__datatool_requires_key_xor_column_get_column:nTF
  {
```

Column key not valid. Failure.

```
  \__datatool_action_error:nn
  {
    invalid ~ `#1' ~ value. ~
    No ~ column ~ found ~ with ~ key ~ `#2' ~
    in ~ database ~ ` \l__datatool_action_name_tl '
  }
  {
    Check ~ that ~ you ~ have ~ correctly ~ spelt ~
    the ~ value ~ of ~ `#1' ~ in ~ the ~ optional ~
    argument ~ of ~ \token_to_str:N \DTLaction [...]
    { \l__datatool_action_tl } ~ and ~ that ~
    the ~ database ~ name ~ is ~ correct
  }
  #6
}
{
```

Positive column index provided or obtained from the key. Check that column index is less than the total number of columns for the database.

```
\int_compare:nNnTF
{ #4 }
>
{
  \int_use:c
  { dtlcols@ \l__datatool_action_name_tl }
}
{
```

Out of range. Failure. Do false. (If the key was originally provided, then the column index must be valid unless the internals are incorrect.)

```
\__datatool_action_error:nn
{
  invalid ~ `#3' ~ value.
  Column ~ index ~
  \int_use:N #4 \c_space_tl ~
  out ~ of ~ range ~ for ~ database ~
  ` \l__datatool_action_name_tl '
}
```

```

    {
      The ~ database ~ ` \l__datatool_action_name_tl ' ~
      only ~ has ~
      \int_use:c { dtlcols@ \l__datatool_action_name_tl }
      \c_space_tl ~ columns.
      Check ~ that ~ you ~ have ~ correctly ~ spelt ~
      the ~ value ~ of ~ `#3' ~ in ~ the ~ optional ~
      argument ~ of ~ \token_to_str:N \DTLaction [...]
      { \l__datatool_action_tl } ~ and ~ that ~
      the ~ database ~ name ~ is ~ correct
    }
    #6
  }
  {

```

Valid. Success. Do true.

```

    #5
  }
}
{ #6 }
}

```

First column required.

```

\cs_new:Nn
  \__datatool_requires_key_xor_column_get_column:TF
{
  \__datatool_requires_key_xor_column_get_column:nNnNTF
  { key } \l__datatool_action_key_tl
  { column } \l__datatool_action_column_int
  { #1 } { #2 }
}
\cs_new:Nn \__datatool_requires_key_xor_column_get_column:T
{
  \__datatool_requires_key_xor_column_get_column:TF { #1 } { }
}

```

Second column required.

```

\cs_new:Nn
  \__datatool_requires_key_ii_xor_column_ii_get_column:TF
{
  \__datatool_requires_key_xor_column_get_column:nNnNTF
  { key2 } \l__datatool_action_key_ii_tl
  { column2 } \l__datatool_action_column_ii_int
  { #1 } { #2 }
}
\cs_new:Nn
  \__datatool_requires_key_ii_xor_column_ii_get_column:T
{
  \__datatool_requires_key_ii_xor_column_ii_get_column:TF
  { #1 } { }
}

```

Arguments: $\{\langle col1 not set \rangle\}\{\langle col2 not set \rangle\}\{\langle true \rangle\}\{\langle false \rangle\}$

Two columns may be identified: ‘key’ or ‘column’ allowed for first column but both not permitted; ‘key2’ or ‘column2’ allowed for second column but both not permitted. If an error occurs while attempting to get the first column, the check for the second will be omitted. If the first column hasn’t been identified (with key or column) $\langle col1 not set \rangle$ will be done. If the second column hasn’t been identified (with key2 or column2) $\langle col2 not set \rangle$ will be done.

```
\cs_new:Nn
  \__datatool_optional_ii_key_xor_column:nTF
{
```

Get the first column:

```
  \__datatool_optional_key_xor_column_get_column:nTF
  { #1 }
  {
```

Get the second column:

```
    \__datatool_optional_key_ii_xor_column_ii_get_column:nTF
    { #2 } { #3 } { #4 }
  }
  { #4 }
```

```
}
\cs_new:Nn \__datatool_optional_ii_key_xor_column:TF
{
  \__datatool_optional_ii_key_xor_column:nTF
  { } { } { #1 } { #2 }
}
```

```
\cs_new:Nn \__datatool_optional_ii_key_xor_column:
{
  \__datatool_optional_ii_key_xor_column:nTF
  { } { } { } { }
}
```

Arguments: $\{\langle col2 not set \rangle\}\{\langle true \rangle\}\{\langle false \rangle\}$

Similar but the first column is required and the second optional.

```
\cs_new:Nn \__datatool_requires_i_optional_ii_key_xor_column:nTF
{
```

Get the first column:

```
  \__datatool_requires_key_xor_column_get_column:TF
  {
```

Get the second column:

```
    \__datatool_optional_key_ii_xor_column_ii_get_column:nTF
    { #1 } { #2 } { #3 }
  }
  { #3 }
}
```

For actions that allow an arbitrary number of columns (up to the total number in the database). These may be specified by ‘keys’ and/or ‘columns’ options. The resulting list

will be save in the sequence variable `\l__datatool_action_columns_seq`. The ‘columns’ list may include ranges. Any keys will need to be defined. Note that the sequence won’t be ordered (unless the user has supplied the order). If an ordered list is required, it will need to be sorted.

```
\cs_new:Nn \__datatool_optional_columns:
{
```

First check the ‘columns’ setting.

```
\clist_map_inline:Nn
  \l__datatool_action_columns_clist
  {
    \__datatool_optional_columns:w ##1 - \q_nil \q_stop
  }
```

Next check the ‘keys’ setting.

```
\clist_map_inline:Nn
  \l__datatool_action_keys_clist
  {
    \__datatool_optional_keys:w ##1 - \q_nil \q_stop
  }
```

Make sure that the user hasn’t accidentally used key.

```
\tl_if_empty:NF \l__datatool_action_key_tl
{
  \clist_if_empty:NTF \l__datatool_action_keys_clist
  {
    \PackageWarning { datatool }
    {
      Ignoring ~ key={\l__datatool_action_key_tl} ~
      for ~ action ~ ``\l__datatool_action_tl'. ~
      Did ~ you ~ mean ~
      keys = { \l__datatool_action_key_tl } ?
    }
  }
  {
    \PackageWarning { datatool }
    {
      Ignoring ~ key={\l__datatool_action_key_tl} ~
      for ~ action ~ ``\l__datatool_action_tl'. ~
      (Append ~ to ~ the ~ `keys' ~ list ~ if ~
      required.)
    }
  }
}
```

Make sure that the user hasn’t accidentally used key.

```
\tl_if_empty:NF \l__datatool_action_key_ii_tl
{
  \clist_if_empty:NTF \l__datatool_action_keys_clist
  {
    \PackageWarning { datatool }
```

```

    {
      Ignoring ~ key2={\l__datatool_action_key_ii_tl} ~
      for ~ action ~ ``\l__datatool_action_tl'. ~
      Did ~ you ~ mean ~
      keys = { \l__datatool_action_key_ii_tl } ?
    }
  }
  {
    \PackageWarning { datatool }
    {
      Ignoring ~ key2={\l__datatool_action_key_ii_tl} ~
      for ~ action ~ ``\l__datatool_action_tl'. ~
      (Append ~ to ~ the ~ `keys' ~ list ~ if ~
      required.)
    }
  }
}

```

Make sure that the user hasn't accidentally used column.

```

\int_if_zero:nF \l__datatool_action_column_int
{
  \clist_if_empty:NTF \l__datatool_action_columns_clist
  {
    \PackageWarning { datatool }
    {
      Ignoring ~ column=
      { \int_use:N \l__datatool_action_column_int } ~
      for ~ action ~ ``\l__datatool_action_tl'. ~
      Did ~ you ~ mean ~
      columns =
      { \int_use:N \l__datatool_action_column_int } ?
    }
  }
  {
    \PackageWarning { datatool }
    {
      Ignoring ~ column=
      { \int_use:N \l__datatool_action_column_int } ~
      for ~ action ~ ``\l__datatool_action_tl'. ~
      (Append ~ to ~ the ~ `columns' ~ list ~ if ~
      required.)
    }
  }
}

```

Make sure that the user hasn't accidentally used column2.

```

\int_if_zero:nF \l__datatool_action_column_ii_int
{
  \clist_if_empty:NTF \l__datatool_action_columns_clist
  {
    \PackageWarning { datatool }

```



```

    { \DTLcolumncount { \l__datatool_action_tl } }
  }
  {
    \__datatool_if_column_index_valid:nT { #2 }
    { #2 }
    {
      \__datatool_optional_columns_add_range:nn
      { 1 } { #2 }
    }
  }
}
}
{
  \tl_if_empty:nTF { #2 }
  {
End at the total number of columns.
    \__datatool_if_column_index_valid:nT { #1 }
    {
      \__datatool_optional_columns_add_range:nn
      { #1 }
      { \DTLcolumncount { \l__datatool_action_tl } }
    }
  }
  {
    \__datatool_if_column_index_valid:nT { #1 }
    {
      \__datatool_if_column_index_valid:nT { #2 }
      {
        \int_compare:nNnTF
        { #2 } > { #1 }
        {
          \__datatool_action_error:nn
          {
            Invalid ~ column ~ range ~ `#1-#2'. ~
            Start ~ of ~ range ~ can't ~ be ~
            greater ~ than ~ end ~ of ~ range ~
          }
          {
            Check ~ the ~ syntax ~ of ~ the ~ `columns' ~
            setting ~ in ~ the ~ optional ~
            argument ~ of ~ \token_to_str:N \DTLaction [...]
            { \l__datatool_action_tl }
          }
        }
      }
      {
        \__datatool_optional_columns_add_range:nn
        { #1 } { #2 }
      }
    }
  }
}

```

```

    }
  }
}
Add a column range.
\cs_new:Nn
  \__datatool_optional_columns_add_range:nn
{
  \int_step_inline:nnn
    { #1 } { #2 }
  {
    \__datatool_optional_columns_add:n { ##1 }
  }
}
\cs_generate_variant:Nn
  \__datatool_optional_columns_add_range:nn
  { vn, nv, vv }
Parse a column index range.
\cs_new:Nn \__datatool_if_column_index_valid:nT
{
  \int_compare:nNnTF
    { #1 } < { \c_one_int }
  {
    \__datatool_action_error:nn
      {
        Invalid ~ column ~ index ~ `#1'
      }
    {
      Check ~ the ~ syntax ~ of ~ the ~ `columns' ~
      setting ~ in ~ the ~ optional ~
      argument ~ of ~ \token_to_str:N \DTLaction [...]
      { \__datatool_action_tl }
    }
  }
}
\int_compare:nNnTF
  { #1 }
  >
  { \DTLcolumncount { \__datatool_action_name_tl } }
  {
    \__datatool_action_error:nn
      {
        Invalid ~ column ~ index ~ `#1' ~
        (exceeds ~ column ~ count ~ of ~ database ~
        ` \__datatool_action_name_tl ')
      }
    {
      Check ~ the ~ syntax ~ of ~ the ~ `columns' ~
      setting ~ in ~ the ~ optional ~
      argument ~ of ~ \token_to_str:N \DTLaction [...]
    }
  }
}

```

```

        { \l__datatool_action_tl } ~ and ~ that ~
        the ~ database ~ name ~ is ~ correct
      }
    }
  { #2 }
}

```

Add a column index to the sequence if not already there.

```

\cs_new:Nn \__datatool_optional_columns_add:n
{
  \seq_if_in:NnF
    \l__datatool_action_columns_seq { #1 }
  {
    \seq_put_right:Nn
      \l__datatool_action_columns_seq { #1 }
  }
}
\cs_generate_variant:Nn
  \__datatool_optional_columns_add:n { x , v }

```

Parse a column key range.

```

\cs_new:Npn
  \__datatool_optional_keys:w #1 - #2 \q_stop
{
  \quark_if_nil:nTF { #2 }
  {
    \__datatool_if_column_key_valid:nT { #1 }
    {
      \__datatool_optional_columns_add:v
        {
          dtl@ci
          @ \l__datatool_action_name_tl
          @ #1
        }
    }
  }
}
\__datatool_optional_keys_add_range:w #1 - #2 \q_stop
}
\cs_new:Npn
  \__datatool_optional_keys_add_range:w
  #1 - #2 - \q_nil \q_stop
{
  \tl_if_empty:nTF { #1 }
  {
    Start at 1.
    \tl_if_empty:nTF { #2 }
    {

```

End at the total number of columns.

```
    \__datatool_optional_columns_add_range:nn
    { 1 }
    { \DTLcolumncount { \l__datatool_action_name_tl } }
  }
  {
    \__datatool_if_column_key_valid:nT { #2 }
    {
      \__datatool_optional_columns_add_range:nv
      { 1 }
      {
        dtl@ci
        @ \l__datatool_action_name_tl
        @ #2
      }
    }
  }
}
{
  \tl_if_empty:nTF { #2 }
  {
```

End at the total number of columns.

```
    \__datatool_if_column_key_valid:nT { #1 }
    {
      \__datatool_optional_columns_add_range:nv
      {
        dtl@ci
        @ \l__datatool_action_name_tl
        @ #1
      }
      { \DTLcolumncount { \l__datatool_action_name_tl } }
    }
  }
  {
    \__datatool_if_column_key_valid:nT { #1 }
    {
      \__datatool_if_column_key_valid:nT { #2 }
      {
```

Unlike the column index ranges, with a key range, if the start key has a smaller index than the end key, switch them round.

```
    \int_compare:nNnTF
    {
      \tl_use:c
      {
        dtl@ci
        @ \l__datatool_action_name_tl
        @ #2
      }
    }
```



```

    }
    { #2 }
  {
    \__datatool_action_error:nn
    {
      Unknown ~ column ~ key ~ `#1' ~
      in ~ database ~ ``\l__datatool_action_name_tl'
    }
    {
      Check ~ the ~ `keys' ~
      setting ~ in ~ the ~ optional ~
      argument ~ of ~ \token_to_str:N \DTLaction [...]
      { \l__datatool_action_tl }
    }
  }
}
}

Define actions. New database (action=new):
\cs_new:cn { __datatool_action_new: }
{
  \DTLifdbexists
  { \l__datatool_action_name_tl }
  {
    \__datatool_action_error:nn
    {
      Database ~ ``\l__datatool_action_name_tl' ~
      already ~ exists
    }
    {
      Did ~ you ~ forget ~ to ~ specify ~ the ~
      database ~ name ~ in ~ the ~ options ~ for ~
      \token_to_str:N \DTLaction [ ... ]
      { \l__datatool_action_tl } ~
      or ~ change ~ the ~ default ~ name ~ in ~
      \token_to_str:N \DTLsetup?
    }
  }
}
}
{
  \__datatool_new_db:n { \l__datatool_action_name_tl }
}

Set the return value:
\tl_set_eq:NN \l__datatool_action_return_tl \l__datatool_action_name_tl

Duplicate this as a secondary return value.
\__datatool_put_return_action_string:nV
{ name } \l__datatool_action_name_tl
}
}

Delete database (action=delete):
\cs_new:cn { __datatool_action_delete: }

```

```

{
  \__datatool_require_database:T
  {
Set the column and row return values first.
    \int_if_exist:cT { dtlrows@ \l__datatool_action_name_tl }
    {
      \__datatool_put_return_action_int:nv
      { rows }
      { dtlrows@ \l__datatool_action_name_tl }
    }
    \int_if_exist:cT { dtlcols@ \l__datatool_action_name_tl }
    {
      \__datatool_put_return_action_int:nv
      { columns }
      { dtlcols@ \l__datatool_action_name_tl }
    }
Delete the database:
    \DTLdeletedb { \l__datatool_action_name_tl }
Set the primary return value:
    \tl_set_eq:NN
      \l__datatool_action_return_tl
      \l__datatool_action_name_tl
    \__datatool_put_return_action_string:nv
    { name } \l__datatool_action_name_tl
  }
For consistency with the other actions, also set the name property.
}
Clear database (action=clear):
\cs_new:cn { __datatool_action_clear: }
{
  \__datatool_require_database:T
  {
Set the column and row return values first.
    \int_if_exist:cT { dtlrows@ \l__datatool_action_name_tl }
    {
      \__datatool_put_return_action_int:nv
      { rows }
      { dtlrows@ \l__datatool_action_name_tl }
    }
    \int_if_exist:cT { dtlcols@ \l__datatool_action_name_tl }
    {
      \__datatool_put_return_action_int:nv
      { columns }
      { dtlcols@ \l__datatool_action_name_tl }
    }
  }
}

```

Clear the database:

```
\DTLcleardb { \l__datatool_action_name_tl }
```

Set the primary return value:

```
\tl_set_eq:NN  
  \l__datatool_action_return_tl  
  \l__datatool_action_name_tl  
}
```

For consistency with the other actions, also set the name property.

```
\__datatool_put_return_action_string:nV  
  { name } \l__datatool_action_name_tl  
}
```

New row (action=new row):

```
\cs_new:cn { __datatool_action_new ~ row: }  
{  
  \__datatool_require_database:T  
  {  
    \tl_clear:N \l__datatool_action_value_tl
```

Check for column and key in case user has confused this action with 'new entry'.

```
\__datatool_forbid_key_and_column:n  
{  
  The ~ action ~ ` \l__datatool_action_tl ' ~ should ~ have ~  
  column-key = value ~ comma ~ separated ~ list ~ in ~ the ~  
  `assign' ~ setting ~ to ~ add ~ entries ~ to ~ the ~  
  new ~ row  
}
```

Check for 'options' in case user has confused it for 'assign'.

```
\clist_if_empty:NF \l__datatool_action_options_clist  
{  
  \PackageWarning { datatool }  
  {  
    `options' ~ setting ~ ignored ~ in ~ action ~  
    ` \l__datatool_action_tl ' ~  
    (did ~ you ~ mean ~ `assign'?)  
  }  
}  
\keyval_parse:NNV  
  \__datatool_new_entry:n  
  \__datatool_new_entry:nn  
  \l__datatool_action_assign_clist  
\bool_if:NTF \l__datatool_db_global_bool  
{
```

Increment row count.

```
\int_gincr:c { dtlrows@ \l__datatool_action_name_tl }  
}  
{
```

Increment row count.

```
\int_incr:c { dtlrows@ \l__datatool_action_name_tl }  
}
```

Append the new row to the database

```
\__datatool_dtldb_put_right:Vx  
  \l__datatool_action_name_tl  
  {  
    \__datatool_row_markup:vV  
    { dtlrows@ \l__datatool_action_name_tl }  
    \l__datatool_action_value_tl  
  }
```

The primary return value is the row count:

```
\tl_set:Nv \l__datatool_action_return_tl  
  { dtlrows@ \l__datatool_action_name_tl }  
}
```

Set the return value:

```
\__datatool_put_return_action_string:nV  
  { name } \l__datatool_action_name_tl  
\__datatool_put_return_action_int:nx  
  { row }  
  { \DTLrowcount { \l__datatool_action_name_tl } }  
}
```

__datatool_new_entry:nn{<key>}{<value>} adds value to \l__datatool_action_value_tl using database column markup

```
\cs_new:Nn \__datatool_new_entry:nn  
{  
  \tl_set:Nx \l__datatool_item_key_tl { #1 }
```

This bit is as \@dtl@storeandupdate. Store the value of this entry in \l__datatool_item_value_tl and also the older \@dtl@toks taking the expansion setting into account. This will also parse and set the data type in \@dtl@datatype.

```
\__datatool_process_new_value:n { #2 }
```

Is there already a column with the given key?

```
\tl_if_exist:cTF  
{  
  dtl@ci@  
  \l__datatool_action_name_tl  
  @ \l__datatool_item_key_tl  
}  
{
```

This column already exists. Get the column index from the key.

```
\exp_args:Nnc \int_set:Nn \l__datatool_action_column_int  
{  
  dtl@ci@  
  \l__datatool_action_name_tl  
  @ \l__datatool_item_key_tl  
}
```

Does the meta data need updating?

```
\__datatool_get_col_type:vV
  { dtlkeys @ \l__datatool_action_name_tl }
  \l__datatool_action_column_int
\int_compare:nNnT
  { \@dtl@datatype } > { \l__datatool_item_type_int }
  {
    \int_set_eq:NN
      \l__datatool_item_type_int
      \@dtl@datatype
```

Column type needs updating. Get current properties.

```
\__datatool_get_props:NNNNnVv
  \l__datatool_item_key_tl
  \l__datatool_item_type_tl
  \l__datatool_item_head_tl
  \l__datatool_before_tl
  \l__datatool_after_tl
  { dtlkeys@ \l__datatool_action_name_tl }
  \l__datatool_action_column_int
```

Update underlying token register.

```
\__datatool_dtlkeys_set:Vx
  \l__datatool_action_name_tl
  {
    \exp_not:V \l__datatool_before_tl
    \__datatool_column_markup:VVV
      \l__datatool_action_column_int
      \l__datatool_item_key_tl
      \l__datatool_item_type_int
      \l__datatool_item_head_tl
    \exp_not:V \l__datatool_after_tl
  }
}
```

Column doesn't exist so create it.

```
\int_set:Nn \l__datatool_action_column_int
  { \DTLcolumncount { \l__datatool_action_name_tl } + 1 }
```

Append to column metadata list.

```
\__datatool_dtlkeys_put_right:Vx
  \l__datatool_action_name_tl
  {
    \__datatool_column_markup:VVV
      \l__datatool_action_column_int
      \l__datatool_item_key_tl
      \@dtl@datatype
      \l__datatool_item_key_tl
  }
```

```

        \bool_if:NTF \l__datatool_db_global_bool
        {
Assign key to column index mapping.
        \tl_gset:cV
        {
            dtl@ci@
            \l__datatool_action_name_tl
            @ \l__datatool_item_key_tl
        }
        \l__datatool_action_column_int
Update column count.
        \int_gset_eq:cN
        { dtlcols@ \l__datatool_action_name_tl }
        \l__datatool_action_column_int
        }
        {
Assign key to column index mapping.
        \tl_set:cV
        {
            dtl@ci@
            \l__datatool_action_name_tl
            @ \l__datatool_item_key_tl
        }
        \l__datatool_action_column_int
Update column count.
        \int_set_eq:cN
        { dtlcols@ \l__datatool_action_name_tl }
        \l__datatool_action_column_int
        }
        }
Append to token list variable used to store the current row.
        \tl_put_right:Nx \l__datatool_action_value_tl
        {
            \__datatool_row_element_markup:VV
            \l__datatool_action_column_int
            \l__datatool_item_value_tl
        }
        }
Value not provided:
\cs_new:Nn \__datatool_new_entry:n
{
    \__datatool_action_error:nn
    {
        Invalid ~ option ~ setting ~ ` \tl_to_str:n { #1 } '
    }
}

```

```

The ~ action ~ ` \l__datatool_action_tl ' ~ should ~ have ~
column-key = {value} ~ comma ~ separated ~ list ~ in ~ the ~
`assign' ~ setting ~ to ~ add ~ entries ~ to ~ the ~ new ~
row. ~ If ~ you ~ want ~ an ~
empty ~ value ~ do ~ \token_to_str:N \DTLaction
  [ assign = { column-key = { ... }, ... } ] { \l__datatool_action_tl }
}
}

```

New entry (action=new entry):

```

\cs_new:cn { __datatool_action_new ~ entry: }
{
  \__datatool_require_database:T
  {
    \int_set_eq:NN \@dtl@datatype \c_datatool_unknown_int
    \__datatool_require_value:T
    {
      \__datatool_requires_key_xor_column:T
      {
        \tl_if_empty:NTF \l__datatool_action_key_tl
        {

```

No key so the column index was provided instead. First check if there is a corresponding column.

```

  \int_set_eq:NN
  \dtlcolumnnum
  \l__datatool_action_column_int

```

This bit is as \@dtl@storeandupdate. Store the value of this entry in \@dtl@toks taking the expansion setting into account. This will also set the \l__datatool_item_value_tl and \@dtl@datatype variables.

```

  \__datatool_process_new_value:V
  \l__datatool_action_value_tl

```

Is there a key associated with this column index? (This also gets the data type.)

```

  \__datatool_get_col_type_key:vV
  { dtlkeys @ \l__datatool_action_name_tl }
  \l__datatool_action_column_int
  \quark_if_no_value:NTF \l__datatool_item_key_tl
  {

```

No key, so this must be a new column. Create a default key.

```

  \tl_set:Nx \l__datatool_item_key_tl
  {
    \dtldefaultkey
    \int_use:N \l__datatool_action_column_int
  }

```

Append to property list

```

  \__datatool_dtlkeys_put_right:Vx
  \l__datatool_action_name_tl
  {

```

```

        \__datatool_column_markup:VVV
        \l__datatool_action_column_int
        \l__datatool_item_key_tl
        \@dtl@datatype
        \l__datatool_item_key_tl
    }
\bool_if:NTF \l__datatool_db_global_bool
{
  \tl_gset:cV
  {
    dtl@ci
    @ \l__datatool_action_name_tl
    @ \l__datatool_item_key_tl
  }
  \l__datatool_action_column_int
  Is the column index greater than the current size?
  \int_compare:nNnT
  { \l__datatool_action_column_int }
  >
  { \int_use:c { dtlcols@ \l__datatool_action_name_tl } }
  {
    \int_gset_eq:cN
    { dtlcols@ \l__datatool_action_name_tl }
    \l__datatool_action_column_int
  }
}
{
  \tl_set:cV
  {
    dtl@ci
    @ \l__datatool_action_name_tl
    @ \l__datatool_item_key_tl
  }
  \l__datatool_action_column_int
  Is the column index greater than the current size?
  \int_compare:nNnT
  { \l__datatool_action_column_int }
  >
  {
    \int_use:c
    { dtlcols@ \l__datatool_action_name_tl }
  }
  {
    \int_set_eq:cN
    { dtlcols@ \l__datatool_action_name_tl }
    \l__datatool_action_column_int
  }
}
}
}

```

```

{
This column already exists. Does the meta data need updating?
  \int_set_eq:NN \l_datatool_item_type_int
  \c_datatool_unknown_int
  \tl_if_empty:NTF \l_datatool_item_type_tl
  {
  \int_compare:nNnF
  { \@dtl@datatype } = { \c_datatool_unknown_int }
  {
  \int_set_eq:NN
  \l_datatool_item_type_int
  \@dtl@datatype
  }
  }
  {
  \int_compare:nNnT
  { \@dtl@datatype } > { \l_datatool_item_type_tl }
  {
  \int_set_eq:NN
  \l_datatool_item_type_int
  \@dtl@datatype
  }
  }
  \int_compare:nNnT
  { \l_datatool_item_type_int } > { \c_datatool_unknown_int }
  {

```

Column type needs updating.

```

  \__datatool_get_props:NNNNNVV
  \l_datatool_item_key_tl
  \l_datatool_item_type_tl
  \l_datatool_item_head_tl
  \l_datatool_before_tl
  \l_datatool_after_tl
  { dtlkeys@ \l_datatool_action_name_tl }
  \dtlcolumnnum

```

Update underlying token register.

```

  \__datatool_dtlkeys_set:Vx
  \l_datatool_action_name_tl
  {
  \exp_not:V \l_datatool_before_tl
  \__datatool_column_markup:VVVV
  \dtlcolumnnum
  \l_datatool_item_key_tl
  \l_datatool_item_type_int
  \l_datatool_item_head_tl
  \exp_not:V \l_datatool_after_tl
  }
}

```

```
}
```

Now split off the last row and insert the new entry. This expects the value to be in `\@dtl@toks`:

```
\@s@DTLnewdbentry \l__datatool_action_name_tl  
}  
{
```

Key provided, use `\DTLnewdbentry`:

```
\int_zero:N \dtlcolumnnum  
\exp_args:NNVV \DTLnewdbentry  
  \l__datatool_action_name_tl  
  \l__datatool_action_key_tl  
  \l__datatool_action_value_tl
```

Get the column index for the return value.

```
\int_set_eq:NN \l__datatool_action_column_int \dtlcolumnnum  
}
```

The primary return value is only set if successful.

```
\tl_set:NV \l__datatool_action_return_tl  
  \l__datatool_action_column_int
```

Set the return values to indicate success.

```
  \__datatool_put_return_action_int:nV  
  { column } \l__datatool_action_column_int  
  \__datatool_put_return_action_string:nV  
  { key } \l__datatool_action_key_tl  
  \__datatool_put_return_action_int:nV  
  { type } \@dtl@datatype  
}  
}
```

The row property is just the row count:

```
  \__datatool_put_return_action_int:nV  
  { row }  
  { dtlrows@ \l__datatool_action_name_tl }  
}
```

Always set the name as a secondary return value to help debugging:

```
  \__datatool_put_return_action_string:nV  
  { name } \l__datatool_action_name_tl  
}
```

Get column index (action=column index):

```
\cs_new:cn { __datatool_action_column ~ index: }  
{
```

Column must be identified by its label. (No point identifying it by the column index as that's what's being queried.)

```
\tl_if_empty:NTF \l__datatool_action_key_tl  
{
```

No key has been supplied.

```
\__datatool_action_error:nn
{ Missing ~ `key' }
{
  \token_to_str:N \DTLaction [...] { \l__datatool_action_tl } ~
  needs ~ the ~ `key' ~ setting ~ in ~ the ~ optional ~
  argument ~ to ~ identify ~ the ~ required ~ column
}
}
{
  \__datatool_require_database:T
  {
    \exp_args:NVV \@sDTLifhaskey
    \l__datatool_action_name_tl
    \l__datatool_action_key_tl
  }
}
```

Primary return value is the column index:

```
\@sdtl@getcolumnindex
{ \l__datatool_action_return_tl }
{ \l__datatool_action_name_tl }
{ \l__datatool_action_key_tl }
```

Duplicate as a secondary return value:

```
\__datatool_put_return_action_int:nV
{ column } \l__datatool_action_return_tl
}
{ }
}
}
```

Set the secondary return values:

```
\__datatool_put_return_action_string:nV
{ name } \l__datatool_action_name_tl
\__datatool_put_return_action_string:nV
{ key } \l__datatool_action_key_tl
}
}
```

Get column metadata (action=column data):

```
\cs_new:cn { __datatool_action_column ~ data: }
{
  \__datatool_require_database:T
  {

```

Initialise:

```
\tl_set:Nn \l__datatool_item_head_tl
  { \q_no_value }
\int_set_eq:NN
  \l__datatool_item_type_int
  \c_datatool_unknown_int
\__datatool_requires_key_xor_column_get_column:T
```

```

{
  \__datatool_get_col_data:vV
  { dtlkeys@ \l__datatool_action_name_tl }
  \l__datatool_action_column_int

```

Set the return values:

```

\quark_if_no_value:NF \l__datatool_item_key_tl
{
  \__datatool_put_return_action_string:nV
  { key } \l__datatool_item_key_tl

```

Primary return value is the key.

```

\tl_set_eq:NN
  \l__datatool_action_return_tl
  \l__datatool_item_key_tl

```

Duplicate as secondary return value.

```

  \__datatool_put_return_action_string:nV
  { key } \l__datatool_item_key_tl
}

```

Set the secondary return values:

```

\quark_if_no_value:NF \l__datatool_item_head_tl
{
  \__datatool_put_return_action_string:nV
  { header } \l__datatool_item_head_tl
}
\__datatool_put_return_action_int:nV
{ type } \l__datatool_item_type_int
\int_if_zero:NF \l__datatool_action_column_int
{
  \__datatool_put_return_action_int:nV
  { column } \l__datatool_action_column_int
}
}
\__datatool_put_return_action_string:nV
{ name } \l__datatool_action_name_tl
}
}

```

Display data (action=display):

```

\cs_new:cn { __datatool_action_display: }
{
  \__datatool_require_database:T
  {
    \group_begin:
    \clist_if_empty:NF \l__datatool_action_options_clist
    {
      \keys_set_filter:nnVN
      { datatool/display } { longtable }
      \l__datatool_action_options_clist
      \l__datatool_action_tmpb_tl
    }
  }
}

```

```

\tl_if_empty:NF \l__datatool_action_tmpb_tl
{
  \PackageWarning { datatool }
  {
    Ignoring ~ unsupported ~
    \token_to_str:N \DTLaction
    { \l__datatool_action_tl } ~
    option(s): ~ \exp_not:o { \l__datatool_action_tmpb_tl }
  }
}
\tl_set_eq:NN \dtldbname \l__datatool_action_name_tl
\__datatool_display_db:

```

Need to set return properties after the group ends:

```

\tl_set:Nx \l__datatool_action_tmpb_tl
{
  \exp_not:N \group_end:
  \exp_not:N \__datatool_put_return_action_int:nn
  { columns }
  { \int_use:N \dtlcolumnnum }
  \exp_not:N \__datatool_put_return_action_int:nn
  { rows }
  { \int_use:N \dtlrownum }
}
\l__datatool_action_tmpb_tl
}

```

Set the secondary return values:

```

\__datatool_put_return_action_string:nV
{ name } \l__datatool_action_name_tl
}

```

Display data in a longtable (action=display long):

```

\cs_new:cn { __datatool_action_display ~ long: }
{
  \__datatool_require_database:T
  {
    \group_begin:
    \clist_if_empty:NF \l__datatool_action_options_clist
    {
      \keys_set_filter:nnVN
      { datatool/display } { tabular }
      \l__datatool_action_options_clist
      \l__datatool_action_tmpb_tl
    }
    \tl_if_empty:NF \l__datatool_action_tmpb_tl
    {
      \PackageWarning { datatool }
      {
        Ignoring ~ unsupported ~
        \token_to_str:N \DTLaction
      }
    }
  }
}

```

```

        { \l__datatool_action_tl } ~
        option(s): ~ \exp_not:o { \l__datatool_action_tmpb_tl }
      }
    }
  }
  \tl_set_eq:NN \dtldbname \l__datatool_action_name_tl
  \__datatool_display_long_db:

```

Need to set return properties after the group ends:

```

  \tl_set:Nx \l__datatool_action_tmpb_tl
  {
    \exp_not:N \group_end:
    \exp_not:N \__datatool_put_return_action_int:nn
    { columns }
    { \int_use:N \dtlcolumnnum }
    \exp_not:N \__datatool_put_return_action_int:nn
    { rows }
    { \int_use:N \dtlrownum }
  }
  \l__datatool_action_tmpb_tl
}

```

Set the secondary return values:

```

  \__datatool_put_return_action_string:nV
  { name } \l__datatool_action_name_tl
}

```

Add a new column (action=add column):

```

\cs_new:cn { __datatool_action_add ~ column: }
{
  \__datatool_require_database:T
  {
    \int_if_zero:nF { \l__datatool_action_column_int }
    {
      \__datatool_action_error:nn
      {
        `column' ~ setting ~ not ~ supported. ~ Ignoring
      }
      {
        You ~ need ~ to ~ use ~ `key' ~ not ~ `column' ~ to ~
        reference ~ a ~ column ~ with ~ action ~ ` \l__datatool_action_tl '
      }
    }
  }
}

```

The column index will be one more than the current number of columns.

```

  \int_set:Nn \l__datatool_action_column_int
  { \DTLcolumncount \l__datatool_action_name_tl + 1 }

```

If no key has been set, assign the default.

```

  \tl_if_empty:NT \l__datatool_action_key_tl
  {
    \tl_set:Nx \l__datatool_action_key_tl

```

```

    {
      \dtldefaultkey
      \int_use:N \l__datatool_action_column_int
    }
  }

```

If no value has been set, assume the header is the same as the key.

```

\quark_if_no_value:NTF \l__datatool_action_value_tl
{
  \tl_set_eq:NN
  \l__datatool_action_value_tl
  \l__datatool_action_key_tl
}
\exp_args:NVV \@sDTLifhaskey
  \l__datatool_action_name_tl
  \l__datatool_action_key_tl
{
  \__datatool_action_error:nn
  {
    Can't ~ add ~ new ~ column ~ ` \l__datatool_action_key_tl ' ~
    to ~ database ~ ` \l__datatool_action_name_tl ': ~
    column ~ with ~ that ~ key ~ already ~ exists
  }
  {
    Check ~ the ~ key ~ setting ~ in ~ the ~ optional ~
    argument ~ of ~ \token_to_str:N \DTLaction [...]
    { \l__datatool_action_tl }
  }
}
}
{
  \__datatool_add_column_with_header:VVVV
  \l__datatool_action_name_tl
  \l__datatool_action_key_tl
  \l__datatool_action_type_int
  \l__datatool_action_value_tl

```

The primary return value is only set if successful.

```

  \tl_set:NV \l__datatool_action_return_tl
  \l__datatool_action_column_int

```

Duplicate as a secondary return value.

```

  \__datatool_put_return_action_int:nV
  { column } \l__datatool_action_column_int
}

```

Set the return values:

```

  \__datatool_put_return_action_string:nV
  { key } \l__datatool_action_key_tl
  \__datatool_put_return_action_int:nV
  { type } \l__datatool_action_type_int
  \quark_if_no_value:NF \l__datatool_action_value_tl

```

```

    {
      \__datatool_put_return_action_string:nV
      { header } \l__datatool_action_value_tl
    }
  }
  \__datatool_put_return_action_string:nV
  { name } \l__datatool_action_name_tl
}
  Get column aggregates (action=aggregate):
  \cs_new:cn { __datatool_action_aggregate: }
  {
Check if database exists:
  \__datatool_require_database:T
  {
Initialise:
  \fp_set_eq:NN \l__datatool_min_fp \c_inf_fp
  \fp_set_eq:NN \l__datatool_min_ii_fp \c_inf_fp
  \fp_set_eq:NN \l__datatool_max_fp \c_minus_inf_fp
  \fp_set_eq:NN \l__datatool_max_ii_fp \c_minus_inf_fp
  \fp_zero:N \l__datatool_total_fp
  \fp_zero:N \l__datatool_total_ii_fp
  \tl_clear:N \l__datatool_item_currency_tl
  \tl_clear:N \l__datatool_item_currency_ii_tl
List of aggregate types required:
  \seq_clear:N \l__datatool_tmp_seq
  \clist_if_empty:NF \l__datatool_action_options_clist
  {
    \clist_map_inline:Nn
      \l__datatool_action_options_clist
    {
      \clist_if_in:nnTF
        { sum , mean , variance, sd , min , max } { ##1 }
        {
          \seq_put_right:Nn \l__datatool_tmp_seq { ##1 }
        }
        {
          \PackageWarning { datatool }
          {
            Unknown ~ aggregate ~ function ~ `##1' ~ in ~
            \token_to_str:N \DTLaction
            [ options={\l__datatool_action_options_clist}, ... ]
            {` \l__datatool_action_tl ' }
          }
        }
      }
    }
  }
}
  Add dependent types if omitted:

```

```

\seq_if_in:NnT
  \l__datatool_tmp_seq { sd }
  {
    \seq_if_in:NnF
      \l__datatool_tmp_seq { variance }
      {
        \seq_put_right:Nn \l__datatool_tmp_seq { variance }
      }
  }
\seq_if_in:NnT
  \l__datatool_tmp_seq { variance }
  {
    \seq_if_in:NnF
      \l__datatool_tmp_seq { mean }
      {
        \seq_put_right:Nn \l__datatool_tmp_seq { mean }
      }
  }
\seq_if_in:NnT
  \l__datatool_tmp_seq { mean }
  {
    \seq_if_in:NnF
      \l__datatool_tmp_seq { sum }
      {
        \seq_put_right:Nn \l__datatool_tmp_seq { sum }
      }
  }

```

List of numeric values:

```

\seq_clear:N \l__datatool_tmpa_seq
\seq_clear:N \l__datatool_tmpb_seq

```

Check the key and column settings, which will set the index for column 1 and column 2:

```

__datatool_optional_ii_key_xor_column:

```

Iterate and compute required aggregates:

```

\DTLmapdata [ name = { \l__datatool_action_name_tl }, read-
only ]
{
  \exp_args:NNVV
  \dtl@getentryfromrow
  \l__datatool_item_value_tl
  \l__datatool_action_column_int
  \l__datatool_map_data_row_tl
  \datatool_if_null:NF \l__datatool_item_value_tl
  {
    __datatool_parse:N \l__datatool_item_value_tl
  }
}

```

Check that the value is numerical.

```

\datatool_if_numeric_datum_type:nT { \@dtl@datatype }
{

```



```

    \l_datatool_action_column_ii_int
    \l_datatool_map_data_row_tl
\datatool_if_null:NF \l_datatool_item_value_tl
{
  \__datatool_parse:N
  \l_datatool_item_value_tl

```

Check that the value is numerical.

```

\datatool_if_numeric_datum_type:nT { \@dtl@datatype }
{
  \int_compare:nNnT
  { \@dtl@datatype } = { \c_datatool_currency_int }
  {
    \tl_if_empty:NT \l_datatool_item_currency_ii_tl
    {
      \tl_set_eq:NN
      \l_datatool_item_currency_ii_tl
      \l_datatool_datum_currency_tl
    }
  }
  \fp_set:Nn \l_datatool_tmpb_fp
  { \DTLdatumvalue { \l_datatool_item_value_tl } }
  \seq_put_right:Nx \l_datatool_tmpb_seq
  { \fp_to_decimal:N \l_datatool_tmpb_fp }
  \seq_if_in:NnT \l_datatool_tmp_seq { sum }
  {
    \fp_add:Nn \l_datatool_total_ii_fp
    \l_datatool_tmpb_fp
  }
  \seq_if_in:NnT \l_datatool_tmp_seq { min }
  {
    \fp_compare:nNnT
    { \l_datatool_min_ii_fp }
    >
    { \l_datatool_tmpb_fp }
    {
      \fp_set_eq:NN
      \l_datatool_min_ii_fp
      \l_datatool_tmpb_fp
    }
  }
  \seq_if_in:NnT \l_datatool_tmp_seq { max }
  {
    \fp_compare:nNnT
    { \l_datatool_max_ii_fp }
    <
    { \l_datatool_tmpb_fp }
    {
      \fp_set_eq:NN
      \l_datatool_max_ii_fp
    }
  }

```



```

    \__datatool_put_return_action_decimal:nx
    { sum }
    { \fp_to_decimal:N \l__datatool_total_fp }

```

Calculate the mean.

```

\seq_if_in:NnT \l__datatool_tmp_seq { mean }
{
  \fp_set:Nn \l__datatool_mean_fp
  { \l__datatool_total_fp / \l__datatool_count_int }
  \__datatool_put_return_action_decimal:nx
  { mean }
  { \fp_to_decimal:N \l__datatool_mean_fp }
}

```

Calculate the variance.

```

\seq_if_in:NnT \l__datatool_tmp_seq { variance }
{
  \fp_zero:N \l__datatool_tmpa_fp
  \seq_map_inline:Nn \l__datatool_tmpa_seq
  {
    \fp_set:Nn \l__datatool_tmpb_fp
    {
      ##1 - \l__datatool_mean_fp
    }
    \fp_add:Nn \l__datatool_tmpa_fp
    {
      \l__datatool_tmpb_fp * \l__datatool_tmpb_fp
    }
  }
  \fp_set:Nn \l__datatool_tmpa_fp
  { \l__datatool_tmpa_fp / \l__datatool_count_int }
  \__datatool_put_return_action_decimal:nx
  { variance }
  { \fp_to_decimal:N \l__datatool_tmpa_fp }
}

```

Calculate the standard deviation.

```

\seq_if_in:NnT \l__datatool_tmp_seq { sd }
{
  \fp_set:Nn \l__datatool_tmpa_fp
  { sqrt ( \l__datatool_tmpa_fp ) }
  \__datatool_put_return_action_decimal:nx
  { sd }
  { \fp_to_decimal:N \l__datatool_tmpa_fp }
}
}
}
}
}
}
}
}
\int_if_zero:nF { \l__datatool_action_column_ii_int }
{
  \tl_if_empty:NF \l__datatool_item_currency_ii_tl
  {

```

```

\tl_set_eq:NN
  \l_datatool_item_currency_tl
  \l_datatool_item_currency_ii_tl
}
\_datatool_put_return_action_int:nV
{ column2 } \l_datatool_action_column_ii_int

```

Number of column2 items counted:

```

\int_set:Nn
  \l_datatool_count_int
  { \seq_count:N \l_datatool_tmpb_seq }
\_datatool_put_return_action_int:nV
{ count2 } \l_datatool_count_int
\prop_put:NnV \l_datatool_action_return_prop
{ seq2 } \l_datatool_tmpb_seq
\int_if_zero:nF { \l_datatool_count_int }
{
  \seq_if_in:NnT \l_datatool_tmp_seq { min }
  {
    \fp_compare:nNnT
      { \l_datatool_min_ii_fp }
      <
      { \c_inf_fp }
    {
      \_datatool_put_return_action_decimal:nx
        { min2 }
        { \fp_to_decimal:N \l_datatool_min_ii_fp }
    }
  }
}
\seq_if_in:NnT \l_datatool_tmp_seq { max }
{
  \fp_compare:nNnT
    { \l_datatool_max_ii_fp }
    >
    { \c_minus_inf_fp }
  {
    \_datatool_put_return_action_decimal:nx
      { max2 }
      { \fp_to_decimal:N \l_datatool_max_ii_fp }
  }
}
\seq_if_in:NnT \l_datatool_tmp_seq { sum }
{
  \_datatool_put_return_action_decimal:nx
    { sum2 }
    { \fp_to_decimal:N \l_datatool_total_ii_fp }
}

```

Calculate the mean.

```

\seq_if_in:NnT \l_datatool_tmp_seq { mean }
{
  \fp_set:Nn \l_datatool_mean_fp

```



```

    \DTLmapdata
    { row ~ aggregate: }
}

```

Action within \DTLmapdata:

```

\cs_new:Nn \__datatool_action_row_aggregate_op:
{
  \exp_args:NV \__datatool_action_row_aggregate:n
  \l_datatool_map_data_row_tl
}

```

Get row aggregates (action=current row aggregate) for use with \dtlcurrentrow:

```

\cs_new:cn { __datatool_action_current ~ row ~ aggregate: }
{
  \exp_args:NV \__datatool_action_row_aggregate:n
  \dtlcurrentrow
}

```

Underlying action of both “row aggregate” and “current row aggregate”:

```

\cs_new:Nn \__datatool_action_row_aggregate:n
{
  \__datatool_requires_dbname:T
  {
    \tl_if_empty:nT { #1 }
    {
      \PackageWarning { datatool }
      {
        Action ~ ` \l_datatool_action_tl ': ~ empty ~ row
      }
    }
  }
}

```

Initialise:

```

\fp_set_eq:NN \l_datatool_min_fp \c_inf_fp
\fp_set_eq:NN \l_datatool_max_fp \c_minus_inf_fp
\fp_zero:N \l_datatool_total_fp
\tl_clear:N \l_datatool_item_currency_tl

```

List of aggregate types required. These will be stored in the options sequence:

```

\seq_clear:N \l_datatool_action_tmp_options_seq

```

Iterate through the list of options supplied by the user:

```

\clist_if_empty:NF \l_datatool_action_options_clist
{
  \clist_map_inline:Nn
  \l_datatool_action_options_clist
  {
    \clist_if_in:nnTF
    { sum , mean , variance, sd , min , max } { ##1 }
    {
      \__datatool_add_action_option:n { ##1 }
    }
  }
}

```

```

\PackageWarning { datatool }
{
  Unknown ~ aggregate ~ function ~ `##1' ~ in ~
  \token_to_str:N \DTLaction
  [ options={\l__datatool_action_options_clist}, ... ]
  {` \l__datatool_action_tl ' }
}
}
}
}

```

Add dependent types if omitted:

```

\seq_if_in:NnT
  \l__datatool_action_tmp_options_seq { sd }
  {
    \__datatool_add_action_option:n { variance }
  }
\seq_if_in:NnT
  \l__datatool_action_tmp_options_seq { variance }
  {
    \__datatool_add_action_option:n { mean }
  }
\seq_if_in:NnT
  \l__datatool_action_tmp_options_seq { mean }
  {
    \__datatool_add_action_option:n { sum }
  }

```

List of numeric values:

```

\seq_clear:N \l__datatool_action_tmp_data_seq

```

Populate the column sequence `\l__datatool_action_columns_seq` with all the required columns:

```

  \__datatool_optional_columns:

```

Iterate over all identified columns (or all if no subset provided).

```

\seq_if_empty:NTF \l__datatool_action_columns_seq
{
  \int_step_inline:nnn
  { 1 }
  { \DTLcolumncount { \l__datatool_action_name_tl } }
  {
    \__datatool_action_row_aggregate_col:nn { ##1 } { #1 }
  }
}
{
  \seq_map_inline:Nn \l__datatool_action_columns_seq
  {
    \__datatool_action_row_aggregate_col:nn { ##1 } { #1 }
  }
}

```

Primary return value is the number of numeric items. This should be non-zero if no problems have occurred.

```

\int_set:Nn
  \l__datatool_count_int
  { \seq_count:N \l__datatool_action_tmp_data_seq }
\tl_set:NV
  \l__datatool_action_return_tl
  \l__datatool_count_int

```

Set the secondary return values.

```

\__datatool_put_return_action_int:nV
  { count } \l__datatool_count_int
\__datatool_put_return_action_string:nx
  { columns }
  { \seq_use:Nn \l__datatool_action_columns_seq { , } }
\prop_put:NnV \l__datatool_action_return_prop
  { seq } \l__datatool_action_tmp_data_seq
\int_if_zero:nF { \l__datatool_count_int }
  {
    \__datatool_if_action_option:nT { min }
    {
      \fp_compare:nNnT
        { \l__datatool_min_fp }
        <
        { \c_inf_fp }
      {
        \__datatool_put_return_action_decimal:nx
          { min }
          { \fp_to_decimal:N \l__datatool_min_fp }
        }
      }
    }
  }
\__datatool_if_action_option:nT { max }
  {
    \fp_compare:nNnT
      { \l__datatool_max_fp }
      >
      { \c_minus_inf_fp }
    {
      \__datatool_put_return_action_decimal:nx
        { max }
        { \fp_to_decimal:N \l__datatool_max_fp }
      }
    }
  }
\__datatool_if_action_option:nT { sum }
  {
    \__datatool_put_return_action_decimal:nx
      { sum }
      { \fp_to_decimal:N \l__datatool_total_fp }
    }
  }

```

Calculate the mean.

```

    \__datatool_if_action_option:nT { mean }
    {
      \fp_set:Nn \l__datatool_mean_fp
      { \l__datatool_total_fp / \l__datatool_count_int }
      \__datatool_put_return_action_decimal:nx
      { mean }
      { \fp_to_decimal:N \l__datatool_mean_fp }
    }

```

Calculate the variance.

```

    \__datatool_if_action_option:nT { variance }
    {
      \fp_zero:N \l__datatool_tmpa_fp
      \seq_map_inline:Nn
      \l__datatool_action_tmp_data_seq
      {
        \fp_set:Nn \l__datatool_tmpb_fp
        {
          ##1 - \l__datatool_mean_fp
        }
        \fp_add:Nn \l__datatool_tmpa_fp
        {
          \l__datatool_tmpb_fp * \l__datatool_tmpb_fp
        }
      }
      \fp_set:Nn \l__datatool_tmpa_fp
      { \l__datatool_tmpa_fp / \l__datatool_count_int }
      \__datatool_put_return_action_decimal:nx
      { variance }
      { \fp_to_decimal:N \l__datatool_tmpa_fp }
    }

```

Calculate the standard deviation.

```

    \__datatool_if_action_option:nT { sd }
    {
      \fp_set:Nn \l__datatool_tmpa_fp
      { sqrt ( \l__datatool_tmpa_fp ) }
      \__datatool_put_return_action_decimal:nx
      { sd }
      { \fp_to_decimal:N \l__datatool_tmpa_fp }
    }
  }
}

```

Supplementary secondary return values. Database name:

```

    \__datatool_put_return_action_string:nV
    { name } \dtldbname

```

Row index:

```

    \__datatool_put_return_action_int:nV
    { row } \dtlrownum

```

```

}
}
Arguments: <col-idx>{<row markup>}
Parse given column in the current row.
\cs_new:Nn \__datatool_action_row_aggregate_col:nn
{
\dtl@getentryfromrow
\l__datatool_item_value_tl { #1 } { #2 }
\datatool_if_null:NF \l__datatool_item_value_tl
{
\__datatool_parse:N \l__datatool_item_value_tl
Check that the value is numerical.
\datatool_if_numeric_datum_type:nT { \@dtl@datatype }
{
\int_compare:nNnT
{ \@dtl@datatype } = { \c_datatool_currency_int }
{
\tl_if_empty:NT \l__datatool_item_currency_tl
{
\tl_set_eq:NN
\l__datatool_item_currency_tl
\l__datatool_datum_currency_tl
}
}
\fp_set:Nn \l__datatool_tmpa_fp
{ \DTLdatumvalue { \l__datatool_item_value_tl } }
\seq_put_right:Nx \l__datatool_action_tmp_data_seq
{ \fp_to_decimal:N \l__datatool_tmpa_fp }
\__datatool_if_action_option:nT { sum }
{
\fp_add:Nn \l__datatool_total_fp
\l__datatool_tmpa_fp
}
\__datatool_if_action_option:nT { min }
{
\fp_compare:nNnT
{ \l__datatool_min_fp }
>
{ \l__datatool_tmpa_fp }
{
\fp_set_eq:NN
\l__datatool_min_fp
\l__datatool_tmpa_fp
}
}
\__datatool_if_action_option:nT { max }
{
\fp_compare:nNnT
{ \l__datatool_max_fp }

```



```

        \l__datatool_action_column_int
    }
}
{
No match on column. Do nothing. User can check return value.
}
}
{
\int_set_eq:NN \dtlrownum \l__datatool_action_row_int
Row index provided, so check column and key haven't been set.
\tl_if_empty:NF \l__datatool_action_key_tl
{
\__datatool_action_error:nn
{
    can't ~ use ~ both ~ `key' ~ and ~ `row'. ~ Ignoring ~
    key = \l__datatool_action_key_tl
}
{
    Either ~ use ~ `key' ~ or ~ `row' ~ but ~ not ~ both ~
    in the optional argument of \token_to_str:N \DTLaction
    [...] { \l__datatool_action_tl }
}
}
\int_if_zero:NF \l__datatool_action_column_int
{
\__datatool_action_error:nn
{
    can't ~ use ~ both ~ `column' ~ and ~ `row'. ~ Ignoring ~
    column = \int_use:N \l__datatool_action_column_int
}
{
    Either ~ use ~ `column' ~ or ~ `row' ~ but ~ not ~ both ~
    in the optional argument of \token_to_str:N \DTLaction
    [...] { \l__datatool_action_tl }
}
\int_zero:N \l__datatool_action_column_int
}
\exp_args:NNV \dtlgetrow
\l__datatool_action_name_tl
\l__datatool_action_row_int
}
Primary return value is the row index.
\int_if_zero:NF \dtlrownum
{
\tl_set:NV
    \l__datatool_action_return_tl
    \dtlrownum
}

```

Set the secondary return values (column keys).

```

    \__datatool_map_current_row:Nn
    \l__datatool_item_value_tl
    {
      \exp_args:NNVV \@dtl@getkeyforcolumn
      \l__datatool_item_key_tl
      \l__datatool_action_name_tl
      \dtlcolumnnum
      \__datatool_put_return_action_parse:VV
      \l__datatool_item_key_tl
      \l__datatool_item_value_tl
    }
    \int_set_eq:NN
    \dtlcolumnnum
    \l__datatool_action_column_int
  }
}
}

```

Get each entry from the current row (action=current row values):

```

\cs_new:cn { __datatool_action_current ~ row ~ values: }
{
  \__datatool_requires_dbname:T
  {
    \clist_if_empty:NTF
    \l__datatool_action_options_clist
    {
      \seq_clear:N \l__datatool_column_keys_seq
    }
    {
      \seq_set_from_clist:NN \l__datatool_column_keys_seq
      \l__datatool_action_options_clist
    }
  }
}

```

Populate the column sequence \l__datatool_action_columns_seq with all the required columns:

```

  \__datatool_optional_columns:
  \seq_if_empty:NTF \l__datatool_action_columns_seq
  {

```

No columns supplied so get all column values.

```

  \int_step_inline:nn { \DTLcolumncount { \dtldbname } }
  {
    \dtlgetentryfromcurrentrow
    \l__datatool_item_value_tl
    { ##1 }
    \datatool_if_null:NF \l__datatool_item_value_tl
    {
      \@dtl@getkeyforcolumn
      \l__datatool_item_key_tl
      \dtldbname
    }
  }
}

```

```

        { ##1 }
        \__datatool_put_return_action_parse:VV
        \l__datatool_item_key_tl
        \l__datatool_item_value_tl
      }
    }
  }
{

```

Iterate over subset

```

\seq_map_inline:Nn \l__datatool_action_columns_seq
{
  \dtlgetentryfromcurrentrow
  \l__datatool_item_value_tl
  { ##1 }
  \datatool_if_null:NF
  \l__datatool_item_value_tl
  {
    \@dtl@getkeyforcolumn
    \l__datatool_item_key_tl
    \dtldbname
    { ##1 }
    \__datatool_put_return_action_parse:VV
    \l__datatool_item_key_tl
    \l__datatool_item_value_tl
  }
}
}
}
}

```

Primary return value is the total number of entries found in the current row.

```

\tl_set:Nx
  \l__datatool_action_return_tl
  { \prop_count:N \l__datatool_action_return_prop }
}

```

Options for action=find. Match function:

```

\cs_new:Nn \__datatool_action_find_if:T { #1 }

```

Search direction:

```

\bool_new:N \__datatool_action_find_asc_bool

```

Select row if match found:

```

\bool_new:N \__datatool_action_find_select_bool

```

```

\keys_define:nn { datatool / action / find }
{

```

```

  select .bool_set:N = \__datatool_action_find_select_bool ,
  direction .choice: ,
  direction / ascending .code:n =
  {
    \bool_set_true:N \__datatool_action_find_asc_bool

```

```

    },
    direction / asc .code:n =
    {
        \bool_set_true:N \__datatool_action_find_asc_bool
    },
    direction / descending .code:n =
    {
        \bool_set_false:N \__datatool_action_find_asc_bool
    },
    direction / desc .code:n =
    {
        \bool_set_false:N \__datatool_action_find_asc_bool
    },
    direction .value_required:n = true ,
    inline .cs_set:Np = \__datatool_action_find_if:T #1 ,
    inline .value_required:n = true ,
    function .code =
    {
        \cs_set_eq:NN \__datatool_action_find_if:T #1
    },
    function .value_required:n = true ,
}

```

Find a row matching criteria given in options (action=find):

```

\cs_new:cn { __datatool_action_find: }
{

```

Check if database exists:

```

    \__datatool_require_database:T
    {
        \__datatool_forbid_key_and_column:n
        {
            The ~ action ~ ` \l__datatool_action_tl ' ~ should ~ have ~
            cs = column-key ~ comma ~ separated ~ list ~ in ~ the ~
            `assign' ~ setting ~ to ~ reference ~ column ~ values
        }
        \@DTLifdbempty { \l__datatool_action_name_tl }
        { }
    }

```

The row and row2 settings may be used to limit the search range.

```

    \__datatool_optional_row:Nf \l__datatool_action_row_int
    {
        \int_set_eq:NN \l__datatool_action_row_int \c_one_int
    }
    \__datatool_optional_row:Nf \l__datatool_action_row_ii_int
    {
        \int_set:Nn \l__datatool_action_row_ii_int
        { \DTLrowcount { \l__datatool_action_name_tl } }
    }

```

Set options. The default is to select the first row. This makes it easier to select a row simply by index.

```
\cs_set_eq:NN \__datatool_action_find_if:T \use:n
\bool_set_true:N \__datatool_action_find_asc_bool
\bool_set_false:N \__datatool_action_find_select_bool
\keys_set:nV { datatool / action / find }
\l_datatool_action_options_clist
```

Gather assignment information, if provided.

```
\__datatool_get_placeholder_assign:
```

If ascending, row should be less than row2 value.

```
\bool_if:NTF \__datatool_action_find_asc_bool
{
  \int_compare:nNnT
  { \l_datatool_action_row_ii_int }
  <
  { \l_datatool_action_row_int }
  {
    \datatool_swap_ints:NN
    \l_datatool_action_row_int
    \l_datatool_action_row_ii_int
  }
}
```

Iterate over all rows in ascending order.

```
\int_until_do:nn
{
  \l_datatool_action_row_int
  >
  \l_datatool_action_row_ii_int
}
{
  \__datatool_action_find_loop_body:
  \int_incr:N \l_datatool_action_row_int
}
}
```

If descending, row2 should be less than row value.

```
\int_compare:nNnT
{ \l_datatool_action_row_ii_int }
>
{ \l_datatool_action_row_int }
{
  \datatool_swap_ints:NN
  \l_datatool_action_row_int
  \l_datatool_action_row_ii_int
}
```

Iterate over all rows in descending order.

```
\int_until_do:nn
```

```

        {
            \l_datatool_action_row_int
            <
            \l_datatool_action_row_ii_int
        }
        {
            \__datatool_action_find_loop_body:
            \int_decr:N \l_datatool_action_row_int
        }
    }
}
}
}
}
}

```

Loop body for ‘find’ action (but doesn’t update loop row counter):

```

\cs_new:Nn \__datatool_action_find_loop_body:
{

```

Get specs for this row.

```

    \__datatool_get_row:vVN
    { dtldb@ \l_datatool_action_name_tl }
    \l_datatool_action_row_int
    \l_datatool_action_tmpa_tl

```

Perform assignments.

```

    \exp_args:NV \__datatool_do_action_assignments:n
    \l_datatool_action_tmpa_tl

```

Perform test.

```

    \__datatool_action_find_if:T
    {

```

The primary return value is the row index, if successful

```

        \tl_set:Nx
        \l_datatool_action_return_tl
        { \int_use:N \l_datatool_action_row_int }

```

Set secondary return values.

```

        \__datatool_set_return_from_row:Vn
        \l_datatool_action_tmpa_tl
        { \l_datatool_action_name_tl }

```

Select the row if applicable.

```

        \bool_if:NT \__datatool_action_find_select_bool
        {
            \exp_args:NNV \dtlgetrow
            \l_datatool_action_name_tl
            \l_datatool_action_row_int
        }

```

Break out of loop.

```

        \int_set_eq:NN
        \l_datatool_action_row_int

```

```

        \l__datatool_action_row_ii_int
    }
}
Sort data (action=sort):
\cs_new:cn { __datatool_action_sort: }
{
    \__datatool_require_database:T
    {
Check that the user hasn't accidentally used 'columns' or 'keys' instead of 'assign':
        \clist_if_empty:NF
            \l__datatool_action_columns_clist
            {
                \__datatool_action_error:n
                {
                    `columns' ~ action ~ setting ~ not ~ available. ~ Ignoring
                }
            }
        \clist_if_empty:NF
            \l__datatool_action_keys_clist
            {
                \__datatool_action_error:n
                {
                    `keys' ~ action ~ setting ~ not ~ available. ~ Ignoring
                }
            }
    }
}
Check that the user has provided 'assign':
        \clist_if_empty:NTF
            \l__datatool_action_assign_clist
            {
                \__datatool_action_error:nn
                {
                    Missing ~ `assign' ~ setting. ~
                    Unable ~ to ~ sort ~ without ~ any ~
                    sort ~ criteria!
                }
                {
                    The ~ `assign' ~ setting ~ corresponds ~ to ~
                    the ~ final ~ `criteria' ~ argument ~ of ~
                    \token_to_str:N \DTLsortdata
                }
            }
        {
            \seq_clear:N \l__datatool_wordlist_seq
            \__datatool_db_sort:VVV
            \l__datatool_action_options_clist
            \l__datatool_action_name_tl
            \l__datatool_action_assign_clist

```

The primary return value is the element count of word list. This will be empty if the sort failed. If successful, it should equal the number of rows.

```
\seq_if_empty:NF \l__datatool_wordlist_seq
{
  \tl_set:Nx \l__datatool_action_return_tl
  { \seq_count:N \l__datatool_wordlist_seq }
```

Set the secondary return values:

```
\__datatool_put_return_action_int:nx
{ rows }
{ \DTLrowcount { \l__datatool_action_name_tl } }
\__datatool_put_return_action_int:nx
{ columns }
{ \DTLcolumncount { \l__datatool_action_name_tl } }
}
}
```

The name is always set as a secondary return value:

```
\__datatool_put_return_action_string:nv
{ name } \l__datatool_action_name_tl
}
```

12.3 Defining New Databases

As from v2.0, the internal structure of the database has changed to make it more efficient.¹ The database is now stored in a token register instead of a macro. Each row is represented as:

```
\db@row@elt@w \db@row@id@w <row idx> \db@row@id@end@ <column data>
\db@row@id@w <row idx> \db@row@id@end@ \db@row@elt@end@
```

where *<row idx>* is the row index and *<column data>* is the data for each column in the row. Each column for a given row is stored as:

```
\db@col@id@w <column idx> \db@col@id@end@ \db@col@elt@w <value> \db@col@elt@end@
\db@col@id@w <column idx> \db@col@id@end@
```

where *<column idx>* is the column index and *<value>* is the entry for the given column and row.

Note that L^AT_EX3 syntax isn't used. Old dbtex files still need to be supported.

Each row only has an associated index, but columns have a unique identifying key as well as an associated index. Columns also have an associated data type which may be: 0 (column contains strings), 1 (column contains integers), 2 (column contains real numbers), 3 (column contains currency) or *<empty>* (column contains no data). Since the key sometimes has to be expanded, a header is also available in the event that the user wants to use `\DTLdisplaydb` or `\DTLdisplaylongdb` and requires a column header that would cause problems if used as a key. The general column information is stored in a token register where each column has information stored in the form:

¹Thanks to Morten Høgholm for the suggestion.

```

\__datatool__column_markup:nnnn{<column
idx>}{<key>}{<type>}{<header>}

```

The column name (<key>) is mapped to the column index using \dtl@ci@(<db>@(<key> where <db> is the database name.

```

\__datatool__column_markup:nnnn{<column
idx>}{<key>}{<type>}{<header>}

```

Expands to the column markup for the given column.

```

\cs_new:Nn \__datatool__column_markup:nnnn
{
  \__datatool__column_markup_full:nnnn
  { #1 } { #2 } { #3 } { \exp_not:n { #4 } }
}

```

NB don't include x variant or it won't expand.

```

\cs_generate_variant:Nn
  \__datatool__column_markup:nnnn
  { VVVV, VVVn, VnVn, VnVV, Vnnn, nVVV, nVnV, VnnV }
\cs_new:Nn \__datatool__column_markup_full:nnnn
{

```

Start of column block.

```

\exp_not:N \db@plist@elt@w

```

Column index

```

\exp_not:N \db@col@id@w
#1
\exp_not:N \db@col@id@end@

```

Column key

```

\exp_not:N \db@key@id@w
#2
\exp_not:N \db@key@id@end@

```

Column type

```

\exp_not:N \db@type@id@w
#3
\exp_not:N \db@type@id@end@

```

Column header

```

\exp_not:N \db@header@id@w
#4
\exp_not:N \db@header@id@end@

```

Column index

```

\exp_not:N \db@col@id@w
#1
\exp_not:N \db@col@id@end@

```

End of Column block

```
\exp_not:N \db@plist@elt@end@  
}
```

```
\__datatool_row_markup:nn{<row idx>}{<content>}
```

Expands to the row markup for the given row.

```
\cs_new:Nn \__datatool_row_markup:nn  
{  
  \__datatool_row_markup_full:nn  
  { #1 } { \exp_not:n { #2 } }  
}
```

NB don't include x variant or it won't expand.

```
\cs_generate_variant:Nn  
  \__datatool_row_markup:nn  
  { vn , Vn , vV, VV, vv , nV }
```

Don't inhibit expansion:

```
\cs_new:Nn \__datatool_row_markup_full:nn  
{
```

Start of row block.

```
\exp_not:N \db@row@elt@w
```

Row ID marker:

```
\exp_not:N \db@row@id@w  
  #1 % row ID  
\exp_not:N \db@row@id@end@
```

Content:

```
  #2
```

Matching end row ID marker:

```
\exp_not:N \db@row@id@w  
  #1 % row ID  
\exp_not:N \db@row@id@end@
```

End of row block

```
\exp_not:N \db@row@elt@end@  
}  
\cs_generate_variant:Nn  
  \__datatool_row_markup_full:nn  
  { vn }
```

```
\__datatool_row_element_markup:nn{<col idx>  
{<content>}
```

Expands to the element markup for the given row but prevents content from expanding.

```
\cs_new:Nn \__datatool_row_element_markup:nn
```

```
{
  \__datatool_row_element_markup_full:nn
  { #1 } { \exp_not:n { #2 } }
}
```

NB don't include x variant or it won't expand.

```
\cs_generate_variant:Nn
  \__datatool_row_element_markup:nn
  { vn, Vn , vV , VV, vv, nV }
```

Don't inhibit expansion of content:

```
\cs_new:Nn \__datatool_row_element_markup_full:nn
{
```

Column ID:

```
\exp_not:N \db@col@id@w
  #1
\exp_not:N \db@col@id@end@
\exp_not:N \db@col@elt@w
```

Content:

```
#2
\exp_not:N \db@col@elt@end@
```

Matching end of column ID:

```
\exp_not:N \db@col@id@w
  #1
\exp_not:N \db@col@id@end@
}
```

```
\DTLnewdb{<db name>}
```

\DTLnewdb

Initialises a database called *<name>*.

```
\NewDocumentCommand \DTLnewdb { m }
{
```

Check if there is already a database with this name.

```
\DTLifdbexists{#1}
{
  \PackageError{datatool}{Database ~ `#1' ~ already ~ exists}{}
}
{
  \__datatool_new_db:n { #1 }
}
}
```

New registers are global. So new databases will always be globally defined.

```
\cs_new:Nn \__datatool_new_db:n
{%
```

Define new database. Add information message if in verbose mode.

```
\dtl@message {Creating ~ database ~ `#1'}
```

Define token register used to store the contents of the database.

```
\exp_args:Nc \newtoks { dtldb @ #1 }
```

Define token register used to store the column header information.

```
\exp_args:Nc \newtoks { dtlkeys @ #1 }
```

Define count register used to store the row count.

```
\int_new:c { dtlrows @ #1 }
```

Define count register used to store the column count.

```
\int_new:c { dtlcols @ #1 }
```

```
}
```

```
\DTLcleardb{<db name>}
```

\DTLcleardb

Clears the database. (Makes it empty, but still defined.)

```
\NewDocumentCommand \DTLcleardb { m }
{
  \bool_if:NTF \l__datatool_db_global_bool
  {
    \DTLgcleardb { #1 }
  }
  {
    \DTLifdbexists { #1 }
    {
      \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
      {
        \tl_set_eq:cN { dtl@ci@ #1 @ \@dtl@key } \undefined
      }
      \__datatool_token_register_set:cn { dtldb@ #1 } { }
      \__datatool_token_register_set:cn { dtlkeys@ #1 } { }
      \int_zero:c { dtlrows@ #1 }
      \int_zero:c { dtlcols@ #1 }
    }
    {
      \PackageError { datatool }
      {
        Can't ~ clear ~ database ~ `#1': ~
        database ~ doesn't ~ exist
      }
      { }
    }
  }
}
```

`\DTLdeletedb{<db name>}`

`\DTLdeletedb`

Deletes a database.

```
\NewDocumentCommand \DTLdeletedb { m }
{
  \bool_if:NTF \l__datatool_db_global_bool
  {
    \DTLgdeletedb { #1 }
  }
  {
    \DTLifdbexists {#1}
    {
      \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
      {
        \expandafter\let\csname dtl@ci@#1@\@dtl@key\endcsname\undefined
      }
      \expandafter\let\csname dtldb@#1\endcsname\undefined
      \expandafter\let\csname dtlkeys@#1\endcsname\undefined
      \expandafter\let\csname dtlrows@#1\endcsname\undefined
      \expandafter\let\csname dtlcols@#1\endcsname\undefined
    }
    {
      \PackageError{datatool}{Can't ~ delete ~ database ~ `#1': ~
        database ~ doesn't ~ exist}{}%
    }
  }
}
```

`\DTLgnewdb{<db name>}`

`\DTLgnewdb`

Since new registers are always globally defined, this is equivalent to `\DTLnewdb`.

```
\newcommand\DTLgnewdb{\DTLnewdb}
```

`\DTLgdeletedb{<db name>}`

`\DTLgdeletedb`

Deletes a database. (Global version.)

```
\NewDocumentCommand \DTLgdeletedb { m } {
  \DTLifdbexists { #1 }
  {
    \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
    {
      \cs_undefine:c { dtl@ci@ #1 @ \@dtl@key }
    }
    \cs_undefine:c { dtldb@#1 }
    \cs_undefine:c { dtlkeys@#1 }
  }
}
```

```

\cs_undefine:c { dtlrows@#1 }
\cs_undefine:c { dtlcols@#1 }
}
{
\PackageError {datatool}
{
Can't ~ delete ~ database ~ `#1': ~
database ~ doesn't ~ exist
}
{ }
}
}
}

```

`\DTLgcleardb{<db name>}`

`\DTLgcleardb`

Clears the database. (Global version.)

```

\NewDocumentCommand \DTLgcleardb { m }
{
\DTLifdbexists { #1 }
{
\dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
{
\cs_undefine:c { dtl@ci@ #1 @ \@dtl@key }
}
\__datatool_token_register_gset:cn { dtldb@ #1 } { }
\__datatool_token_register_gset:cn { dtlkeys@ #1 } { }
\int_gzero:c { dtlrows@ #1 }
\int_gzero:c { dtlcols@ #1 }
}
{
\PackageError {datatool}
{
Can't ~ clear ~ database ~ `#1': ~
database ~ doesn't ~ exist
}
{ }
}
}
}

```

`\DTLrowcount{<db name>}`

`\DTLrowcount`

The number of rows in the database called *<db name>*. (Doesn't check if database exists.)

```

\newcommand*{\DTLrowcount}[1]{
\int_use:c { dtlrows@ #1 }
}

```

\DTLcolumncount

`\DTLcolumncount{<db name>}`

The number of columns in the database called <db name>. (Doesn't check if database exists.)

```
\newcommand*\DTLcolumncount[1]{
  \int_use:c { dtlcols@ #1 }
}
```

Syntax: {<db-name>}{<not empty>}{<empty>}{<no exists>}

```
\cs_new:Nn \datatool_db_state:nnnn
{
  \DTLifdbexists { #1 }
  { \@DTLifdbempty { #1 } { #3 } { #2 } }
  { #4 }
}
```

\DTLifdbempty

`\DTLifdbempty{<name>}{<true part>}{<false part>}`

Check if named database is empty (i.e. no rows have been added).

```
\NewDocumentCommand \DTLifdbempty { m +m +m }
{
  \DTLifdbexists { #1 }
  { \@DTLifdbempty { #1 } { #2 } { #3 } }
  {
    \PackageError {datatool}
    {
      \token_to_str:N \DTLifdbempty : ~
      Can't ~ check ~ if ~ database ~ `#1' ~ is ~ empty: ~
      database ~ doesn't ~ exist
    }
    { }
  }
}
```

\@DTLifdbempty

`\@SDTLifdbempty{<name>}{<true part>}{<false part>}`

Check if named existing database is empty. (No check performed to determine if the database exists.)

```
\newcommand{\@DTLifdbempty}[3]{%
  \int_if_zero:nTF
  { \int_use:c { dtlrows@ #1 } }
  { #2 } { #3 }
}
```

`\DTLnewrow`

`\DTLnewrow{<db name>}`

Add a new row to named database. The starred version doesn't check for the existence of the database.

```
\NewDocumentCommand \DTLnewrow { s m }
{
  \IfBooleanTF { #1 }
  { \@sDTLnewrow { #2 } }
  { \@DTLnewrow { #2 } }
}
```

`\@DTLnewrow`

`\@DTLnewrow{<db name>}`

Add a new row to named database. (Checks for the existence of the database.)

```
\newcommand*\@DTLnewrow[1]{
  \DTLifdbexists { #1 }
  { \@sDTLnewrow { #1 } }
  {
    \PackageError { datatool }
    {
      \token_to_str:N \DTLnewrow : ~
      Can't ~ add ~ new ~ row ~ to ~ database ~ `#1': ~
      database ~ doesn't ~ exist
    }
    {}
  }
}
```

`\@sDTLnewrow`

`\@sDTLnewrow{<db name>}`

Add a new row to named existing database. (No check performed to determine if the database exists.) Version 3.0: check global boolean. Note that pre 3.0 this command only made a global change.

```
\newcommand*\@sDTLnewrow[1]{%
  \bool_if:NTF \l__datatool_db_global_bool
  {
```

Globally increment row count.

```
  \int_gincr:c { dtlrows@#1 }
  }
```

Locally increment row count.

```
  \int_incr:c { dtlrows@#1 }
  }
```

Append an empty row to the database

```
\_datatool_dtlldb_put_right:nx
{ #1 }
{
  \_datatool_row_markup:vn
  { dtlrows@#1 } % row count
  { }
}
```

Display message on terminal and log file if in verbose mode.

```
\dtl@message
{ New ~ row ~ added ~ to ~ database ~ `#1' }
}
```

\dtlcolumnnum Count register to keep track of column index.

```
\newcount\dtlcolumnnum
```

\dtlrownum Count register to keep track of row index.

```
\newcount\dtlrownum
```

```
\DTLifhaskey<db name><key><true part><>false
part>
```

\DTLifhaskey

Checks if the named database *<db name>* has a column with label *<key>*. If column exists, do *<true part>* otherwise do *<>false part>*. The starred version doesn't check if the named database exists.

```
\NewDocumentCommand \DTLifhaskey { s m m m m }
{
  \IfBooleanTF { #1 }
  {
    \sDTLifhaskey { #2 } { #3 } { #4 } { #5 }
  }
  {
    \@DTLifhaskey { #2 } { #3 } { #4 } { #5 }
  }
}
```

\@DTLifhaskey Unstarred version of \DTLifhaskey

```
\newcommand{\@DTLifhaskey} [4]
{
  \DTLifdbexists { #1 }
  {
    \sDTLifhaskey { #1 } { #2 } { #3 } { #4 }
  }
  {
    \PackageError { datatool }
    { Database ~ `#1' ~ doesn't ~ exist }
    { }
  }
}
```

```

    }
}

```

\@sDTLifhaskey Starred version of \DTLifhaskey. This simply tests for the existence of the key to column command.

```

\newcommand{\@sDTLifhaskey}{ \datatool_if_has_key:nnTF }

```

Version 3.0: the above now defined to use the new conditional:

```

\prg_new_conditional:Npnn \datatool_if_has_key:nn #1 #2 { p, T, F, TF }
{
  \tl_if_exist:cTF { dtl@ci@ #1 @ #2 }
  {

```

Key defined

```

    \prg_return_true:
  }
  {

```

Key not defined

```

    \prg_return_false:
  }
}

```

```

\DTLgetcolumnindex{<cs>}{<db>}{<key>}

```

\DTLgetcolumnindex

Gets index for column with label <key> from database <db> and stores in <cs> which must be a control sequence. Unstarred version checks if database and key exist, unstarred version doesn't perform any checks.

```

\NewDocumentCommand \DTLgetcolumnindex { s m m }
{
  \IfBooleanTF { #1 }
  { \@sdtl@getcolumnindex { #2 } { #3 } }
  { \@dtl@getcolumnindex { #2 } { #3 } }
}

```

\@dtl@getcolumnindex Unstarred version of \DTLgetcolumnindex

```

\newcommand*{\@dtl@getcolumnindex} [3]
{

```

Check if database exists.

```

  \DTLifdbexists { #2 }
  {

```

Database exists. Now check if key exists.

```

    \@sDTLifhaskey { #2 } { #3 }
  {

```

Key exists so go ahead and get column index.

```

    \@sdtl@getcolumnindex { #1 } { #2 } { #3 }
  }
  {

```

Key doesn't exists in named database.

```
\PackageError { datatool }
{ Database ~ `#2' ~ doesn't ~ contain ~ key ~ `#3' }
{ }
}
}
{
```

Named database doesn't exist.

```
\PackageError { datatool }
{ Database ~ `#2' ~ doesn't ~ exist }
{ }
}
}
```

`\@dtl@getcolumnindex` Starred version of `\DTLgetcolumnindex`.

```
\newcommand*\@sdtl@getcolumnindex}[3]{%
  \tl_set_eq:Nc #1 { dtl@ci@#2@#3 }
}
```

`\dtlcolumnindex`

`\dtlcolumnindex{<db>}{<key>}`

Column index corresponding to `<key>` in database `<db>`. Expands to zero if the key or database doesn't exist.

```
\newcommand*\dtlcolumnindex}[2]{%
  \tl_if_exist:cTF { dtl@ci@#1@#2 }
  { \tl_use:c { dtl@ci@#1@#2 } }
  { \c_zero_int }
}
```

`\ExplSyntaxOff`

`\DTLgetkeyforcolumn`

`\DTLgetkeyforcolumn{<key cs>}{<db>}{<column index>}`

Gets the key associated with the given column index and stores in `<key cs>`. Unstarred version doesn't perform checks.

```
\newrobustcmd*\DTLgetkeyforcolumn}{%
  \@ifstar\@sdtlgetkeyforcolumn\@dtlgetkeyforcolumn}
```

`\@dtlgetkeyforcolumn`

```
\newcommand*\@dtlgetkeyforcolumn}[3]{%
  \DTLifdbexists{#2}%
  {%
```

Check if index is in range.

```
\ifnum#3<1\relax
  \PackageError{datatool}{Invalid column index \number#3}{%
```

```

        Column indices start at 1}%
    \else
        \expandafter\ifnum\csname dtlcols@#2\endcsname<#3\relax
        \PackageError{datatool}{Index \number#3\space out of
        range for database `#2'}{Database `#2' only has
        \expandafter\number\csname dtlcols@#2\endcsname\space
        columns}%
        \else
            \@sdtlgetkeyforcolumn{#1}{#2}{#3}%
        \fi
    \fi
}%
}%
\PackageError{datatool}{Database `#2' doesn't exists}{}%
}%
}

```

\@sdtlgetkeyforcolumn{<key cs>}{<db>}{<column index>}

\@sdtlgetkeyforcolumn

Gets the key associated with the given column index and stores in <key cs>

```

\newcommand*{\@sdtlgetkeyforcolumn}[3]{%
    \edef\@dtl@dogetkeyforcolumn{\noexpand\@dtl@getkeyforcolumn
        \noexpand#1}{#2}{\number#3}}%
    \@dtl@dogetkeyforcolumn
}

```

\@dtl@getkeyforcolumn Column index must be fully expanded before use.

```

\newcommand*{\@dtl@getkeyforcolumn}[3]{%
    \def\@dtl@get@keyforcolumn##1% before stuff
        \db@plist@elt@w% start of block
        \db@col@id@w #3\db@col@id@end@% index
        \db@key@id@w ##2\db@key@id@end@% key
        \db@type@id@w ##3\db@type@id@end@% data type
        \db@header@id@w ##4\db@header@id@end@% header
        \db@col@id@w #3\db@col@id@end@% index
        \db@plist@elt@end@% end of block
        ##5\q@nil{\def#1{##2}}%
    \edef\@dtl@tmp{\expandafter\the\csname dtlkeys@#2\endcsname}%
    \expandafter\@dtl@get@keyforcolumn\@dtl@tmp
        \db@plist@elt@w% start of block
        \db@col@id@w #3\db@col@id@end@% index
        \db@key@id@w \@nil\db@key@id@end@% key
        \db@type@id@w \db@type@id@end@% data type
        \db@header@id@w \db@header@id@end@% header
        \db@col@id@w #3\db@col@id@end@% index
        \db@plist@elt@end@% end of block
        \q@nil
}

```

Define some commands to indicate the various data types a database may contain.
Version 3.0: note that `datatool-base` now has constants but the unknown type is -1 in that case.

```

\DTLunsettype Unknown data type. (All entries in the column are blank so the type can't be determined.)
    \newcommand*\DTLunsettype{}

\DTLstringtype Data type representing strings.
    \newcommand*\DTLstringtype{0}

\DTLinttype Data type representing integers.
    \newcommand*\DTLinttype{1}

\DTLrealtype Data type representing real numbers.
    \newcommand*\DTLrealtype{2}

\DTLcurrencytype Data type representing currency.
    \newcommand*\DTLcurrencytype{3}

\DTLgetdatatype \DTLgetdatatype{<cs>}{<db>}{<key>}
    Gets data type associated with column labelled <key> in database <db> and stores in <cs>. Type may be: <empty> (unset), 0 (string), 1 (int), 2 (real), 3 (currency). Unstarred version checks if the database and key exist, starred version doesn't.
    \newrobustcmd*\DTLgetdatatype{%
        \@ifstar\@sdtlgetdatatype\@dtlgetdatatype
    }

\@dtlgetdatatype Unstarred version of \DTLgetdatatype.
    \newcommand*\@dtlgetdatatype}[3]{%
        Check if database exists.
        \DTLifdbexists{#2}%
        {%
            Check if key exists in this database.
            \@sDTLifhaskey{#2}{#3}%
            {%
                Get data type for this database and key.
                \@sdtlgetdatatype{#1}{#2}{#3}%
            }%
            {%
                Key doesn't exist in this database.
                \PackageError{datatool}{Key `#3' undefined in database `#2'}{ }%
            }%
        }%
    }%

```

Database doesn't exist.

```
\PackageError{datatool}{Database `#2' doesn't exist}{}%
}%
}
```

`\@sdtlgetdatatype` Starred version of `\DTLgetdatatype`. This ensures that the key is fully expanded before being passed to `\@dtl@getdatatype`.

```
\newcommand*{\@sdtlgetdatatype}[3]{%
\edef\@dtl@dogetdata{\noexpand\@dtl@getdatatype{\noexpand#1}%
\expandafter\the\csname dtlkeys@#2\endcsname}%
\dtlcolumnindex{#2}{#3}}%
\@dtl@dogetdata
}
```

```
\@dtl@getdatatype{<cs>}{<data specs>}{<column index>}
```

`\@dtl@getdatatype`

Column index must be expanded.

```
\newcommand*{\@dtl@getdatatype}[3]{%
\def\@dtl@get@keydata##1% stuff before
\@db@plist@elt@w% start of key block
\@db@col@id@w #3\@db@col@id@end@% column index
\@db@key@id@w ##2\@db@key@id@end@% key id
\@db@type@id@w ##3\@db@type@id@end@% data type
\@db@header@id@w ##4\@db@header@id@end@% header
\@db@col@id@w #3\@db@col@id@end@% column index
\@db@plist@elt@end@% end of key block
##5% stuff afterwards
\q@nil{\def#1{##3}}%
\@dtl@get@keydata#2\q@nil
}
\ExplSyntaxOn
```

```
\@dtl@getprops{<key cs>}{<type cs>}{<header toks>}
{<before toks>}{<after toks>}{<data specs>}{<column
index>}
```

`\@dtl@getprops`

Column index must be expanded.

```
\newcommand*{\@dtl@getprops}[7]{%
\__datatool_get_keydata:NNNNNn #1 #2 #3 #4 #5 { #6 } { #7 }
}
\cs_new:Nn \__datatool_get_keydata:NNNNNn
{
\cs_set:Npn \__datatool_get_keydata:w
##1 % stuff before
\@db@plist@elt@w % start of key block
```

```

        \db@col@id@w #7\db@col@id@end@ % column index
        \db@key@id@w ##2\db@key@id@end@ % key id
        \db@type@id@w ##3\db@type@id@end@ % data type
        \db@header@id@w ##4\db@header@id@end@ % header
        \db@col@id@w #7\db@col@id@end@ % column index
        \db@plist@elt@end@ % end of key block
        ##5% stuff afterwards
        \q_nil
    {
        \tl_set:Nn #1 { ##2 } % key
        \tl_set:Nn #2 { ##3 } % data type
        \__datatool_token_register_set:Nn #3 { ##4 } % header
        \__datatool_token_register_set:Nn #4 { ##1 } % before stuff
        \__datatool_token_register_set:Nn #5 { ##5 } % after stuff
    }
    \__datatool_get_keydata:w #6 \q_nil
}
\cs_generate_variant:Nn \__datatool_get_keydata:NNNNNnn
{ NNNNNvV , NNNNNve }

```

Provide a newer L3 alternative. NB unlike `\@dtl@getprops` this uses token list variables not registers. Syntax: `<key cs><type cs><header tl var><before tl var><after tl var>{<data specs>}{<column index>}`

```

\cs_new:Nn \__datatool_get_props:NNNNNnn
{
    \cs_set:Npn \__datatool_get_keydata:w
        ##1 % stuff before
        \db@plist@elt@w % start of key block
        \db@col@id@w #7\db@col@id@end@ % column index
        \db@key@id@w ##2\db@key@id@end@ % key id
        \db@type@id@w ##3\db@type@id@end@ % data type
        \db@header@id@w ##4\db@header@id@end@ % header
        \db@col@id@w #7\db@col@id@end@ % column index
        \db@plist@elt@end@ % end of key block
        ##5 % stuff afterwards
        \q_nil
    {
        \tl_set:Nn #1 { ##2 } % key
        \tl_set:Nn #2 { ##3 } % data type
        \tl_set:Nn #3 { ##4 } % header
        \tl_set:Nn #4 { ##1 } % before stuff
        \tl_set:Nn #5 { ##5 } % after stuff
    }
    \__datatool_get_keydata:w #6 \q_nil
}
\cs_generate_variant:Nn \__datatool_get_props:NNNNNnn
{ NNNNNvx, NNNNNvV, NNNNNvn }

```

Get all meta data for the given column where the before and after stuff isn't required. Automatically sets scratch variables.

```

Syntax: {<col specs>}{<col idx>}
Sets: \l__datatool_item_key_tl, \l__datatool_item_head_tl
and \l__datatool_item_type_int.
\cs_new:Nn \__datatool_get_col_data:nn
{
  \tl_if_empty:nTF { #1 }
  {
    \tl_set:Nn \l__datatool_item_head_tl { \q_no_value }
    \int_set_eq:NN \l__datatool_item_type_int \c_datatool_unknown_int
    \tl_set:Nn \l__datatool_item_key_tl { \q_no_value }
  }
  {
    \cs_set:Npn \__datatool_get_col_data:w ##1% stuff before
      \db@plist@elt@w% start of key block
      \db@col@id@w #2\db@col@id@end@% column index
      \db@key@id@w ##2\db@key@id@end@% key id
      \db@type@id@w ##3\db@type@id@end@% data type
      \db@header@id@w ##4\db@header@id@end@% header
      \db@col@id@w #2\db@col@id@end@% column index
      \db@plist@elt@end@% end of key block
      ##5% stuff afterwards
      \q_nil
      {
        \tl_set:Nn \l__datatool_item_key_tl { ##2 }
        \tl_set:Nn \l__datatool_item_head_tl { ##4 }
        \tl_if_empty:nTF { ##3 }
        {
          \int_set_eq:NN \l__datatool_item_type_int \c_datatool_unknown_int
        }
        {
          \int_set:Nn \l__datatool_item_type_int { ##3 }
        }
      }
    }
  }
  \__datatool_get_col_data:w #1
}

```

In case the column isn't defined:

```

      \db@plist@elt@w% start of key block
      \db@col@id@w #2\db@col@id@end@% column index
      \db@key@id@w \q_no_value \db@key@id@end@% key id
      \db@type@id@w \db@type@id@end@% data type
      \db@header@id@w \q_no_value \db@header@id@end@% header
      \db@col@id@w #2\db@col@id@end@% column index
      \db@plist@elt@end@% end of key block
      \q_nil
    }
  }
  \cs_generate_variant:Nn \__datatool_get_col_data:nn { vV, vN }
}

```

Similar but only type required.

```

\cs_new:Nn \__datatool_get_col_type:nn

```

```

{
  \tl_if_empty:nTF { #1 }
  {
    \int_set_eq:NN \l__datatool_item_type_int \c_datatool_unknown_int
  }
  {
    \cs_set:Npn \__datatool_get_col_type:w ##1% stuff before
      \db@plist@elt@w% start of key block
      \db@col@id@w #2\db@col@end@% column index
      \db@key@id@w ##2\db@key@end@% key id
      \db@type@id@w ##3\db@type@end@% data type
      \db@header@id@w ##4\db@header@end@% header
      \db@col@id@w #2\db@col@end@% column index
      \db@plist@elt@end@% end of key block
      ##5% stuff afterwards
      \q_nil
      {
        \tl_if_empty:nTF { ##3 }
        {
          \int_set_eq:NN \l__datatool_item_type_int \c_datatool_unknown_int
        }
        {
          \int_set:Nn \l__datatool_item_type_int { ##3 }
        }
      }
    }
  \__datatool_get_col_type:w #1
}

```

In case the column isn't defined:

```

  \db@plist@elt@w% start of key block
  \db@col@id@w #2\db@col@end@% column index
  \db@key@id@w \q_no_value \db@key@end@% key id
  \db@type@id@w \db@type@end@% data type
  \db@header@id@w \q_no_value \db@header@end@% header
  \db@col@id@w #2\db@col@end@% column index
  \db@plist@elt@end@% end of key block
  \q_nil
}

```

```

\cs_generate_variant:Nn \__datatool_get_col_type:nn { vn, vV, vV }

```

Only type and header required:

```

\cs_new:Nn \__datatool_get_col_type_header:nn
{
  \tl_if_empty:nTF { #1 }
  {
    \tl_set:Nn \l__datatool_item_head_tl { \q_no_value }
    \int_set_eq:NN \l__datatool_item_type_int \c_datatool_unknown_int
  }
  {
    \cs_set:Npn \__datatool_get_col_type_header:w ##1% stuff before
      \db@plist@elt@w% start of key block

```

```

\db@col@id@w #2\db@col@id@end@% column index
\db@key@id@w ##2\db@key@id@end@% key id
\db@type@id@w ##3\db@type@id@end@% data type
\db@header@id@w ##4\db@header@id@end@% header
\db@col@id@w #2\db@col@id@end@% column index
\db@plist@elt@end@% end of key block
##5% stuff afterwards
\q_nil
{
\tl_set:Nn \l__datatool_item_head_tl { ##4 }
\tl_if_empty:nTF { ##3 }
{
\tint_set_eq:NN \l__datatool_item_type_int \c_datatool_unknown_int
}
{
\tint_set:Nn \l__datatool_item_type_int { ##3 }
}
}
}
__datatool_get_col_type_header:w #1

```

In case the column isn't defined:

```

\db@plist@elt@w% start of key block
\db@col@id@w #2\db@col@id@end@% column index
\db@key@id@w \q_no_value \db@key@id@end@% key id
\db@type@id@w \db@type@id@end@% data type
\db@header@id@w \q_no_value \db@header@id@end@% header
\db@col@id@w #2\db@col@id@end@% column index
\db@plist@elt@end@% end of key block
\q_nil
}
}

```

Only type and key required:

```

\cs_new:Nn \__datatool_get_col_type_key:nn
{
\tl_if_empty:nTF { #1 }
{
\tl_set:Nn \l__datatool_item_key_tl { \q_no_value }
\tint_set_eq:NN \l__datatool_item_type_int \c_datatool_unknown_int
}
{
\cs_set:Npn \__datatool_get_col_type_header:w ##1% stuff before
\db@plist@elt@w% start of key block
\db@col@id@w #2\db@col@id@end@% column index
\db@key@id@w ##2\db@key@id@end@% key id
\db@type@id@w ##3\db@type@id@end@% data type
\db@header@id@w ##4\db@header@id@end@% header
\db@col@id@w #2\db@col@id@end@% column index
\db@plist@elt@end@% end of key block
##5% stuff afterwards
\q_nil
}
}

```

```

    {
      \tl_set:Nn \l__datatool_item_key_tl { ##2 }
      \tl_if_empty:nTF { ##3 }
      {
        \int_set_eq:NN \l__datatool_item_type_int \c_datatool_unknown_int
      }
      {
        \int_set:Nn \l__datatool_item_type_int { ##3 }
      }
    }
  }
  \__datatool_get_col_type_header:w #1

```

In case the column isn't defined:

```

    \db@plist@elt@w% start of key block
    \db@col@id@w #2\db@col@end@% column index
    \db@key@id@w \q_no_value \db@key@end@% key id
    \db@type@id@w \db@type@end@% data type
    \db@header@id@w \db@header@end@% header
    \db@col@id@w #2\db@col@end@% column index
    \db@plist@elt@end@% end of key block
    \q_nil
  }
}

```

```
\cs_generate_variant:Nn \__datatool_get_col_type_key:nn { vV, VV }
```

Only key required:

```

\cs_new:Nn \__datatool_get_col_key:nn
{
  \tl_if_empty:nTF { #1 }
  {
    \tl_set:Nn \l__datatool_item_key_tl { \q_no_value }
  }
  {
    \cs_set:Npn \__datatool_get_col_type_header:w ##1% stuff before
    \db@plist@elt@w% start of key block
    \db@col@id@w #2\db@col@end@% column index
    \db@key@id@w ##2\db@key@end@% key id
    \db@type@id@w ##3\db@type@end@% data type
    \db@header@id@w ##4\db@header@end@% header
    \db@col@id@w #2\db@col@end@% column index
    \db@plist@elt@end@% end of key block
    ##5% stuff afterwards
    \q_nil
    {
      \tl_set:Nn \l__datatool_item_key_tl { ##2 }
    }
  }
  \__datatool_get_col_type_header:w #1
}

```

In case the column isn't defined:

```

    \db@plist@elt@w% start of key block
    \db@col@id@w #2\db@col@end@% column index

```

```

        \db@key@id@w \q_no_value \db@key@id@end@% key id
        \db@type@id@w \db@type@id@end@% data type
        \db@header@id@w \db@header@id@end@% header
        \db@col@id@w #2\db@col@id@end@% column index
        \db@plist@elt@end@% end of key block
    \q_nil
}
}
\cs_generate_variant:Nn \__datatool_get_col_key:nn { vV, VV }
\ExplSyntaxOff

\@dtl@before
\newtoks\@dtl@before

\@dtl@after
\newtoks\@dtl@after

\@dtl@colhead
\newtoks\@dtl@colhead

\ExplSyntaxOn
Set dtlkeys@<db-name> register according to the global setting. Syntax: {<db-name>}
{<content>}
\cs_new:Nn \__datatool_dtlkeys_set:nn
{
  \bool_if:NTF \l__datatool_db_global_bool
  {
    \__datatool_token_register_gset:cn
    { dtlkeys@ #1 } { #2 }
  }
  {
    \__datatool_token_register_set:cn
    { dtlkeys@ #1 } { #2 }
  }
}
\cs_generate_variant:Nn \__datatool_dtlkeys_set:nn
{ nx, vx, vV }
Append to dtlkeys@<db-name> register according to the global setting. Syntax: {<db-
name>}{<content>}
\cs_new:Nn \__datatool_dtlkeys_put_right:nn
{
  \bool_if:NTF \l__datatool_db_global_bool
  {
    \__datatool_token_register_gput_right:cn
    { dtlkeys@ #1 } { #2 }
  }
  {
    \__datatool_token_register_put_right:cn

```

```

        { dtlkeys@ #1 } { #2 }
    }
}
\cs_generate_variant:Nn \__datatool_dtlkeys_put_right:nn
{ nx, vx }
Set dtldb@<db-name> register according to the global setting. Syntax: {<db-name>}
{<content>}
\cs_new:Nn \__datatool_dtldb_set:nn
{
    \bool_if:NTF \l__datatool_db_global_bool
    {
        \__datatool_token_register_gset:cn
        { dtldb@ #1 } { #2 }
    }
    {
        \__datatool_token_register_set:cn
        { dtldb@ #1 } { #2 }
    }
}
\cs_generate_variant:Nn \__datatool_dtldb_set:nn
{ nx, vx, nV, VV }
Append to dtldb@<db-name> register according to the global setting. Syntax: {<db-
name>}{<content>}
\cs_new:Nn \__datatool_dtldb_put_right:nn
{
    \bool_if:NTF \l__datatool_db_global_bool
    {
        \__datatool_token_register_gput_right:cn
        { dtldb@ #1 } { #2 }
    }
    {
        \__datatool_token_register_put_right:cn
        { dtldb@ #1 } { #2 }
    }
}
\cs_generate_variant:Nn \__datatool_dtldb_put_right:nn
{ nx, vx }
Set dtldb@<db-name> register according to the global setting where concatenation is
used with before and after registers. Syntax: {<db-name>}<before reg>{<content>}<after
reg>
\cs_new:Nn \__datatool_dtldb_concat:nNnN
{
    \bool_if:NTF \l__datatool_db_global_bool
    {
        \__datatool_token_register_gconcat_middle:cNnN
        { dtldb@#1 } #2 { #3 } #4
    }
    {

```

```

    \__datatool_token_register_concat_middle:cNnN
      { dtldb@#1 } #2 { #3 } #4
  }
}
\cs_generate_variant:Nn \__datatool_dtldb_concat:nNnN
{ nNxN , VNxN }
  Expands to numeric value of the given data type. Empty will expand to -1.
\cs_new:Nn \__datatool_use_datatype:n
{
  \tl_if_empty:nTF { #1 }
  { -1 }
  {
    \tl_if_single:nTF { #1 }
    {
      \tl_if_empty:NTF #1 { -1 } { \int_eval:n { #1 } }
    }
    { \int_eval:n { #1 } }
  }
}
}

```

`\DTLaddcolumn{<db>}{<key>}`

`\DTLaddcolumn`

Adds a column with given key to given column. No data is added to the column. The starred version doesn't check for the existence of the database.

```

\newrobustcmd*{\DTLaddcolumn}{%
  \@ifstar\@sDTLaddcolumn\@DTLaddcolumn
}
\newcommand{\@DTLaddcolumn}[2]{
  \DTLifdbexists { #1 }
  {
    \@sDTLifhaskey { #1 } { #2 }
    {
      \PackageError {datatool}
      {
        Can't ~ add ~ new ~ column ~ `#2' ~ to ~ database ~ `#1': ~
        column ~ with ~ that ~ key ~ already ~ exists
      }
    }
  }
  {
    \@sDTLaddcolumn { #1 } { #2 }
  }
}
{
  \PackageError {datatool}
  {
    Can't ~ add ~ new ~ column ~ to ~ database ~ `#1': ~

```

```

        database ~ doesn't ~ exist
    }
    { }
}
}
\newcommand{\s@DTLaddcolumn}[2]{%
    \__datatool_add_column_with_header:nxn { #1 } { #2 } { -1 } { #2 }
}

```

\DTLaddcolumnwithheader{<db>}{<key>}{<header>}

\DTLaddcolumnwithheader

```

\NewDocumentCommand \DTLaddcolumnwithheader { s m m m }
{
    \IfBooleanTF { #1 }
    {
        \__datatool_add_column_with_header:nxn { #2 } { #3 } { -1 } { #4 }
    }
    {
        \@DTLaddcolumnwithheader { #2 } { #3 } { #4 }
    }
}

```

\@DTLaddcolumnwithheader

```

\newcommand \@DTLaddcolumnwithheader [3]
{
    \DTLifdbexists { #1 }
    {
        \@sDTLifhaskey {#1} {#2}
        {
            \PackageError {datatool}
            {
                Can't ~ add ~ new ~ column ~ `#2' ~ to ~ database ~ `#1': ~
                column ~ with ~ that ~ key ~ already ~ exists
            }
            {}
        }
    }
    {
        \__datatool_add_column_with_header:nxn { #1 } { #2 } { -
1 } { #3 }
    }
}
{
    \PackageError {datatool}
    {
        Can't ~ add ~ new ~ column ~ to ~ database ~ `#1': ~
        database ~ doesn't ~ exist
    }
    {}
}

```

```

    }
  }
  Syntax: {<db>}{<key>}{<type>}{<header>}
  \cs_new:Nn \__datatool_add_column_with_header:nnnn
  {
    \bool_if:NTF \l__datatool_db_global_bool
    {
      Globally increment column count.
      \int_gincr:c { dtlcols@#1 }
      \int_set_eq:Nc \dtlcolumnnum { dtlcols@#1 }
      Set column index for this key.
      \csxdef{dtl@ci@#1@#2}{\number\dtlcolumnnum}%
      Globally append to property list
      \__datatool_token_register_gput_right:cx
      { dtlkeys@#1 }
      {
        \__datatool_column_markup:Vnnn
        \dtlcolumnnum { #2 } { #3 } { #4 }
      }
    }
  }
  {
    Locally increment column count.
    \int_incr:c { dtlcols@#1 }
    \int_set_eq:Nc \dtlcolumnnum { dtlcols@#1 }
    Set column index for this key.
    \csedef{dtl@ci@#1@#2}{\number\dtlcolumnnum}%
    Locally append to property list
    \__datatool_token_register_put_right:cx
    { dtlkeys@#1 }
    {
      \__datatool_column_markup:Vnnn
      \dtlcolumnnum { #2 } { #3 } { #4 }
    }
  }
}
\cs_generate_variant:Nn \__datatool_add_column_with_header:nnnn
{ nxxn, nxnn, nxxx, VVVV, VVnV }

```

\@dtl@updatekeys

\@dtl@updatekeys{<db>}{<key>}{<value>}

Adds key to database's key list if it doesn't exist. The value is used to update the data type associated with that key. Key must be fully expanded. Doesn't check if database exists.

\newcommand*{\@dtl@updatekeys}[3]{%

Check if key already exists

```
\@sDTLifhaskey{#1}{#2}%  
{%
```

Key exists, may need to update data type. First get the column index.

```
\int_set:Nn \dtlcolumnnum { \dtlcolumnindex { #1 } { #2 } }
```

Get the properties for this column

```
\__datatool_get_keydata:NNNNNV  
\@dtl@key \@dtl@type \@dtl@colhead \@dtl@before \@dtl@after  
{ dtlkeys@#1 } \dtlcolumnnum
```

Is the value empty?

```
\ifstrempty{#3}%  
{%
```

Leave data type as it is

```
}%  
{%
```

Make a copy of current data type

```
\let\@dtl@oldtype\@dtl@type
```

Check the data type for this entry (stored in \@dtl@datatype)

```
\@dtl@checknumerical{#3}%  
\ifnum \@dtl@datatype = \c_datatool_unknown_int  
\else
```

If this column currently has no data type assigned to it then use the new type.

```
\ifdefempty{\@dtl@type}%  
{%  
\edef\@dtl@type{\number\@dtl@datatype}%  
}%  
{%
```

This column already has an associated data type but it may need updating.

```
\ifcase\@dtl@datatype % string
```

String overrides all other types

```
\def\@dtl@type{0}%  
\or % int
```

All other types override int, so leave it as it is

```
\or % real
```

Real overrides int, but not currency or string

```
\ifnum\@dtl@type=1\relax  
\def\@dtl@type{2}%  
\fi  
\or % currency
```

Currency overrides int and real but not string

```
\ifnum\@dtl@type>0\relax  
\def\@dtl@type{3}%
```

```

        \fi
    \fi
}%
\fi
Has the data type been updated?
    \ifx\@dtl@oldtype\@dtl@type
No change needed
    \else
Update required
    \tl_if_empty:NTF \@dtl@type
    {
        \int_set:Nn \@dtl@datatype { \c_datatool_unknown_int }
    }
    {
        \int_set:Nn \@dtl@datatype { \@dtl@type }
    }
\bool_if:NTF \l__datatool_db_global_bool
{
    \__datatool_token_register_gconcat_middle:cNxN
    { dtlkeys@#1 }
    \@dtl@before
    {
        \__datatool_column_markup:VnVV
        \dtlcolumnnum
        { #2 }
        \@dtl@datatype
        \@dtl@colhead
    }
    \@dtl@after
}
{
    \__datatool_token_register_concat_middle:cNxN
    { dtlkeys@#1 }
    \@dtl@before
    {
        \__datatool_column_markup:VnVV
        \dtlcolumnnum
        { #2 }
        \@dtl@datatype
        \@dtl@colhead
    }
    \@dtl@after
}
\fi
}%
}%
{%
\bool_if:NTF \l__datatool_db_global_bool

```

```

    {
Key doesn't exist. Increment column count.
    \int_gincr:c { dtlcols @ #1}
    \int_set_eq:Nc \dtlcolumnnum { dtlcols @ #1 }
Set column index for this key.
    \tl_gset:cV { dtl@ci@#1@#2 } \dtlcolumnnum
    }
    {
    \int_incr:c { dtlcols @ #1}
    \int_set_eq:Nc \dtlcolumnnum { dtlcols @ #1 }
    \tl_set:cV { dtl@ci@#1@#2 } \dtlcolumnnum
    }
Get data type for this entry (stored in \@dtl@datatype)
    \tl_if_empty:nTF { #3 }
    {
    \tl_clear:N \@dtl@type % don't know data type yet
    \int_set_eq:NN \@dtl@datatype \c_datatool_unknown_int
    }
    {
    \@dtl@checknumerical { #3 }
    \int_compare:nNnTF
    { \@dtl@datatype } = { \c_datatool_unknown_int }
    {
    \tl_clear:N \@dtl@type
    }
    {
    \tl_set:NV \@dtl@type \@dtl@datatype
    }
    }
Append to property list
    \bool_if:NTF \l__datatool_db_global_bool
    {
    \__datatool_token_register_gput_right:cx
    { dtlkeys @ #1 }
    {
    \__datatool_column_markup:VnVn
    \dtlcolumnnum
    { #2 }
    \@dtl@datatype
    { #2 }
    }
    }
    {
    \__datatool_token_register_put_right:cx
    { dtlkeys @ #1 }
    {
    \__datatool_column_markup:VnVn

```


Update required

```
\__datatool_dtlkeys_set:nx { #1 }
{
  \exp_not:V \l__datatool_before_tl
  \__datatool_column_markup:VnVV
  \dtlcolumnnum
  { #2 }
  \@dtl@datatype
  \l__datatool_item_head_tl
  \exp_not:V \l__datatool_after_tl
}
}
{
  \bool_if:NTF \l__datatool_db_global_bool
  {
```

Key doesn't exist. Increment column count.

```
\int_gincr:c { dtlcols @ #1}
\int_set_eq:Nc \dtlcolumnnum { dtlcols @ #1 }
```

Set column index for this key.

```
\tl_gset:cV { dtl@ci@#1@#2 } \dtlcolumnnum
}
{
  \int_incr:c { dtlcols @ #1}
  \int_set_eq:Nc \dtlcolumnnum { dtlcols @ #1 }
  \tl_set:cV { dtl@ci@#1@#2 } \dtlcolumnnum
}
}
```

Append to property list

```
\bool_if:NTF \l__datatool_db_global_bool
{
  \__datatool_token_register_gput_right:cx
  { dtlkeys @ #1 }
  {
    \__datatool_column_markup:Vnnn
    \dtlcolumnnum
    { #2 } { #3 } { #2 }
  }
}
{
  \__datatool_token_register_put_right:cx
  { dtlkeys @ #1 }
  {
    \__datatool_column_markup:Vnnn
    \dtlcolumnnum
    { #2 } { #3 } { #2 }
  }
}
}
```

```

}
\cs_generate_variant:Nn
  \__datatool_update_meta_data_with_type:nnn
  { nnV, VVV }
  Syntax: {<db>}{<col idx>}{<type>}
  Similar but the column is referenced by its index.
\cs_new:Nn \__datatool_update_meta_data_col_index_with_type:nnn
  {

```

Does the column already exist?

```

  \int_compare:nNnTF
    { #2 } > { \DTLcolumncount { #1 } }
  {

```

New column but the index can only be one more than the total column count.

```

  \int_compare:nNnTF
    { #2 } = { \DTLcolumncount { #1 } + \c_one_int }
  {

```

Create default column key and add new column.

```

    \tl_set:Nn \l__datatool_item_key_tl { \dtldefaultkey #2 }
    \int_gincr:c { dtlcols @ #1}

```

Append to property list

```

  \bool_if:NTF \l__datatool_db_global_bool
  {
    \__datatool_token_register_gput_right:cx
      { dtlkeys @ #1 }
    {
      \__datatool_column_markup:nVnV
        { #2 }
        \l__datatool_item_key_tl
        { #3 }
        \l__datatool_item_key_tl
    }
  }
  {
    \__datatool_token_register_put_right:cx
      { dtlkeys @ #1 }
    {
      \__datatool_column_markup:nVnV
        { #2 }
        \l__datatool_item_key_tl
        { #3 }
        \l__datatool_item_key_tl
    }
  }
}
{
  \PackageError { datatool }
  {

```

```

Invalid ~ column ~ index ~ #2 . ~ A ~ new ~ column ~
requires ~ the ~ index ~ to ~ be ~ one ~ more ~ than ~
the ~ current ~ column ~ count
}
{
The ~ database ~ ` #1 ' ~ only ~ has ~
\DTLcolumncount { #1 } ~ column(s). ~ The ~ index ~
#2 ~ is ~ too ~ large
}
}
}
{

```

Check index not invalid.

```

\int_compare:nNnTF { #2 } < { \c_one_int }
{
\PackageError { datatool }
{
Invalid ~ column ~ index ~ #2 . ~ The ~ column ~
index ~ must ~ start ~ at ~ 1
}
{
The ~ supplied ~ column ~ index ~ to ~ update ~
column ~ meta ~ data ~ must ~ be ~ from ~ 1 ~
to ~ one ~ more ~ than ~ the ~ total ~ number ~
of ~ columns ~ (\DTLcolumncount { #1 }+1 ~ for ~
database ~ `#1' )
}
}
{

```

Existing column. Get the properties.

```

\__datatool_get_props:NNNNNvn
\l_datatool_item_key_tl
\l_datatool_item_type_tl
\l_datatool_item_head_tl
\l_datatool_before_tl
\l_datatool_after_tl
{ dtlkeys@ #1 } { #2 }

```

Treat empty type as unknown.

```

\tl_if_empty:NT
\l_datatool_item_type_tl
{
\tl_set:Nn
\l_datatool_item_type_tl
{ \c_datatool_unknown_int }
}

```

If the original type is a string, don't update.

```

\int_compare:nNnF

```

```

        { \l_datatool_item_type_tl }
        =
        { \c_datatool_string_int }
    {
If the new type is greater than the old, then it needs updating.
        \int_compare:nNnT
        { #3 } > { \l_datatool_item_type_tl }
        {
Update required
        \bool_if:NTF \l_datatool_db_global_bool
        {
        \__datatool_token_register_gconcat_middle:cNxN
        { dtlkeys@ #1 }
        \l_datatool_before_tl
        {
        \__datatool_column_markup:nVnV
        { #2 }
        \l_datatool_item_key_tl
        { #3 }
        \l_datatool_item_head_tl
        }
        \l_datatool_after_tl
        }
        {
        \__datatool_token_register_concat_middle:cNxN
        { dtlkeys@#1 }
        \l_datatool_before_tl
        {
        \__datatool_column_markup:nVnV
        { #2 }
        \l_datatool_item_key_tl
        { #3 }
        \l_datatool_item_head_tl
        }
        \l_datatool_after_tl
        }
        }
        }
        }
    }
}
\cs_generate_variant:Nn
\__datatool_update_meta_data_col_index_with_type:nnn
{ nnV, VVV, VnV }

```

```
\DTLsetheader{<db>}{<key>}{<header>}
```

\DTLsetheader

Sets header for column given by $\langle key \rangle$ in database $\langle db \rangle$. Starred version doesn't check for existence of database or key.

```
\newrobustcmd*{\DTLsetheader}{\@ifstar\@sDTLsetheader\@DTLsetheader}
```

$\@DTLsetheader$ Unstarred version

```
\newcommand*{\@DTLsetheader}[3]{%
```

Check if database exists

```
\DTLifdbexists{#1}%
```

```
{%
```

Check if key exists.

```
\@sDTLifhaskey{#1}{#2}%
```

```
{%
```

```
\@sDTLsetheader{#1}{#2}{#3}%
```

```
}%
```

```
{%
```

```
\PackageError{datatool}{Database ~ `#1' ~ doesn't ~ contain ~ key ~ `#2'}{}
```

```
}%
```

```
}%
```

```
{%
```

```
\PackageError{datatool}{Database ~ `#1' ~ doesn't ~ exist}{}
```

```
}%
```

```
}
```

$\@sDTLsetheader$ Starred version

```
\newcommand*{\@sDTLsetheader}[3]{%
```

```
\expandafter\dtlcolumnnum\expandafter
```

```
=\dtlcolumnindex{#1}{#2}\relax
```

```
\@dtl@setheaderforindex{#1}{\dtlcolumnnum}{#3}%
```

```
}
```

```
\@dtl@setheaderforindex{\langle db \rangle}{\langle column index \rangle}
{\langle header \rangle}
```

$\@dtl@setheaderforindex$

Sets the header for column given by $\langle column index \rangle$ in database $\langle db \rangle$. The header must be expanded.

```
\newcommand*{\@dtl@setheaderforindex}[3]{%
```

Get the properties for this column

```
\__datatool_get_keydata:NNNNNve
```

```
\@dtl@key \@dtl@type \@dtl@colhead \@dtl@before \@dtl@after
```

```
{ dtlkeys@#1 } { \int_eval:n { #2 } }
```

Ensure data type variable is numeric.

```
\tl_if_empty:NTF \@dtl@type
```

```
{
```

```
\int_set_eq:NN \@dtl@datatype \c_datatool_unknown_int
```

```

    }
    {
        \int_set:Nn \@dtl@datatype { \@dtl@type }
    }
Store the header in \@dtl@toks
\@dtl@colhead={#3}%
Reconstruct property list
\tl_set:Nx \@dtl@colnum { \int_eval:n { #2 } }
\bool_if:NTF \l__datatool_db_global_bool
{
    \__datatool_token_register_gconcat_middle:cNxN
    { dtlkeys@#1 }
    \@dtl@before
    {
        \__datatool_column_markup:VVVV
        \@dtl@colnum
        \@dtl@key
        \@dtl@datatype
        \@dtl@colhead
    }
    \@dtl@after
}
{
    \__datatool_token_register_concat_middle:cNxN
    { dtlkeys@#1 }
    \@dtl@before
    {
        \__datatool_column_markup:VVVV
        \@dtl@colnum
        \@dtl@key
        \@dtl@datatype
        \@dtl@colhead
    }
    \@dtl@after
}
}
}

```

Process value to be added to a database according to the above settings. This will set both \@dtl@toks and \l__datatool_item_value_tl

```

\cs_new:Nn \__datatool_process_new_value:n
{
    \tl_set:Nn \l__datatool_item_value_tl { #1 }
    \datatool_if_null:NTF
        \l__datatool_item_value_tl
    {
        \int_set_eq:NN \@dtl@datatype \c_datatool_unknown_int
    }
    {

```

Special case if value starts with `\dtlspecialvalue`:

```
\tl_if_head_eq_meaning:nNTF
  { #1 } \dtlspecialvalue
  {
    \group_begin:
```

Expand and parse to get the data type.

```
  \exp_args:Nx \__datatool_parse_datum:n { #1 }
  \exp_args:NNNV
  \group_end:
  \int_set:Nn \@dtl@datatype \@dtl@datatype
```

Store as is without following the expansion, trim or store datum settings.

```
  \@dtl@toks { #1 }
  \tl_set:NV \l__datatool_item_value_tl \@dtl@toks
}
{
```

This sets the `\@dtl@toks` token register for backward-compatibility. It also follows the trim and expand new value settings.

```
  \@dtl@setnewvalue { #1 }
```

Update `\l__datatool_item_value_tl` (which won't be set if trim not on.)

```
  \tl_set:NV \l__datatool_item_value_tl \@dtl@toks
  \bool_if:NTF \l__datatool_db_store_datum_bool
  {
    \__datatool_parse:N \l__datatool_item_value_tl
  }
  {
```

Just parse to get the data type.

```
    \exp_args:NV \__datatool_parse_datum:n
      \l__datatool_item_value_tl
  }
```

In case the value was provided in datum format.

```
  \__datatool_to_weird_datum_no_parse:N
  \l__datatool_item_value_tl
```

Update `\@dtl@toks`:

```
  \datatool_if_null:NF
  \l__datatool_item_value_tl
  {
    \__datatool_token_register_set:NV
      \@dtl@toks
      \l__datatool_item_value_tl
  }
}
```

```
}
}
\cs_generate_variant:Nn
  \__datatool_process_new_value:n
  { V }
```

`\@dtl@storeandupdate`

```
\newcommand*\@dtl@storeandupdate}[3]{%
```

Store the value of this entry in `\@dtl@toks` taking the expansion setting into account.

```
  \__datatool_process_new_value:n { #3 }
```

This will have parsed the value and set `\@dtl@datatype` so it can be passed here:

```
  \__datatool_update_meta_data_with_type:nnV  
    { #1 } { #2 } \@dtl@datatype  
}
```

```
\DTLnewdbentry{<db name>}{<id>}{<value>}.
```

`\DTLnewdbentry`

Adds an entry to the last row (adds new row if database is empty) and updates general column information if necessary. The starred version doesn't check if the database exists.

```
\NewDocumentCommand \DTLnewdbentry { s }  
{  
  \int_zero:N \dtlcolumnnum  
  \IfBooleanTF { #1 } { \sDTLnewdbentry } { \@DTLnewdbentry }  
}
```

`\@DTLnewdbentry` Unstarred version of `\DTLnewdbentry`.

```
\newcommand{\@DTLnewdbentry}[3]{%  
  \DTLifdbexists { #1 }  
  {  
    \exp_args:Nv \int_if_zero:nTF { dtlrows@#1 }  
    {  
      \PackageError { datatool }  
      {  
        Can't ~ add ~ an ~ entry ~ to ~ the ~ last ~ row ~ of ~ `#1': ~  
        database ~ has ~ no ~ rows  
      }  
      {  
        You ~ need ~ to ~ create ~ a ~ new ~ row ~ before ~ you ~  
        can ~ add ~ an ~ entry ~ to ~ it ~ with ~  
        \token_to_str:N \DTLnewrow {#1} ~ or ~  
        \token_to_str:N \DTLaction [name={#1}] { new ~ row }  
      }  
    }  
  }  
  {  
    \sDTLnewdbentry { #1 } { #2 } { #3 }  
  }  
  {  
    \PackageError { datatool }  
    {
```

```

        Can't ~ add ~ new ~ entry ~ to ~ database ~ `#1': ~
        database ~ doesn't ~ exist
    }
    {
        You ~ need ~ to ~ define ~ the ~ database ~ first ~ with ~
        \token_to_str:N \DTLnewdb {#1} ~ or ~
        \token_to_str:N \DTLaction [name={#1}] { new }
    }
}
}
}

```

\@sDTLnewdbentry Starred version of \DTLnewdbentry (doesn't check if the database exists).

```

    \newcommand*\@sDTLnewdbentry}[3]{%
Store the value of this entry in \@dtl@toks and update key list.
    \@dtl@storeandupdate { #1 } { #2 } { #3 }
Get the column index
    \int_set:Nn \dtlcolumnnum
    { \dtlcolumnindex { #1 } { #2 } }
Now split off the last row and insert the new entry:
    \tl_set:Nn \__datatool_item_key_tl { #2 }
    \@s@DTLnewdbentry { #1 }
}

```

\@s@DTLnewdbentry Argument is the database name. The value is expected to be in \@dtl@toks, having been pre-processed by __datatool_process_new_value:n

```

    \newcommand*\@s@DTLnewdbentry}[1]{%
Get the current row:
    \dtlgetrow { #1 } { \int_use:c { dtlrows@#1 } }
Check if this row already has an entry for the given column.
    \exp_args:NNV
    \dtlgetentryfromcurrentrow
    \dtl@entry
    \dtlcolumnnum
    \datatool_if_null:NTF \dtl@entry
    {
There are no entries in this row for the given column. Add this entry.
        \__datatool_token_register_put_right:Nx
        \dtlcurrentrow
        {
            \__datatool_row_element_markup:VV
            \dtlcolumnnum
            \@dtl@toks
        }
        \__datatool_dtldb_concat:nNxN
        { #1 }
        \dtlbeforerow
    }
}

```

```

    {
      \__datatool_row_markup:vV
      { dtlrows@#1 }
      \dtlcurrentrow
    }
  \dtlafterrow

```

Print information message if in verbose mode.

```

\dtl@message
{
  Added ~ \l__datatool_item_key_tl \c_space_tl ~
  -> ~ \the\@dtl@toks \c_space_tl ~ to ~ database ~ `#1'
}
}
{

```

There's already an entry for the given column in this row

```

\PackageError { datatool }
{
  Can't ~ add ~ entry ~ with ~ ID ~
  '\l__datatool_item_key_tl' ~ to ~
  current ~ row ~ of ~ database ~ `#1' ~ in ~ column ~
  \int_use:N \dtlcolumnnum
}
{
  There ~ is ~ already ~ an ~ entry ~ in ~ this ~
  column ~ in ~ the ~ current ~ row
}
}
}

```

`\DTLifdbexists{<db name>}{<true part>}{<false part>}`

`\DTLifdbexists`

Checks if a data base with the given name exists.

```

\newcommand{\DTLifdbexists}[3]{
  \ifcsdef { dtldb@#1 } { #2 } { #3 }
}

```

These commands are provided for DTLTEX v3.0 format.

`\DTLdbNewRow`

```

\NewDocumentCommand \DTLdbNewRow { }
{
  \@sDTLnewrow { \l__datatool_default_dbname_tl }
}

```

`\DTLdbNewEntry`

```

\NewDocumentCommand \DTLdbNewEntry { m m }

```

```
{
  \@sDTLnewdbentry { \l__datatool_default_dbname_tl } { #1 } { #2 }
}
```

\DTLdbSetHeader

```
\NewDocumentCommand \DTLdbSetHeader { m m }
{
  \@sDTLsetheader { \l__datatool_default_dbname_tl } { #1 } { #2 }
}
```

12.4 Accessing Data

```
\DTLassign{<db>}{<row idx>}{<assign list>}
```

\DTLassign

Assigns values given in *<assign list>* for row *<row idx>* in database *<db>*. (Where *<assign list>* is in the same form as in \DTLforeach.) This command doesn't check the 'global' option.

```
\NewDocumentCommand \DTLassign { m m m }
{
  \DTLifdbexists { #1 }
  {
```

Grouped in the event that \dtlcurrentrow is already in use. (Assignments in \@dtl@assign are global.)

```
    {
      \dtlgetrow { #1 } { #2 }
      \@dtl@assign { #3 } { #1 }
    }
  }
  {
    \PackageError {datatool}
    {
      \token_to_str:N \DTLassign : ~
      Database ~ `#1' ~ doesn't ~ exist
    }
    {
      Check ~ that ~you ~ have ~ spelt ~ the ~
      database ~ name ~ correctly
    }
  }
}
```

```
\DTLassignfirstmatch{<db>}{<col key>}{<value>}{<assign list>}
```

\DTLassignfirstmatch

Applies the assignment list to the first row that has the given value in the given column. (Value must be expanded.) This command doesn't check the 'global' option.

```

\NewDocumentCommand \DTLassignfirstmatch { m m m m }
{
  \dtl@assignfirstmatch { #3 } { #1 } { #2 } { #4 }
}

```

```

\xDTLassignfirstmatch{<db>}{<col key>}{<value>}
{<assign list>}

```

\xDTLassignfirstmatch

Applies the assignment list to the first row that has the given value in the given column. (Performs *one level* expansion on *<value>*.)

```

\NewDocumentCommand \xDTLassignfirstmatch { m m m m }
{
  \exp_args:Nx
  \dtl@assignfirstmatch
  { \expandonce { #3 } }
  { #1 } { #2 } { #4 }
}

```

```

\dtl@assignfirstmatch{<value>}{<db>}{<col key>}
{<assign list>}

```

\dtl@assignfirstmatch

Internal swaps the ordering around so the value is first. (This just makes it easier for \xDTLassignfirstmatch.)

```

\newcommand*{\dtl@assignfirstmatch}[4]{
  \DTLifdbexists { #2 }
  {%

```

Grouped in the event that \dtlcurrentrow is already in use. (Assignments in \@dtl@assign are global.)

```
{
```

Get row idx:

```

  \dtlgetrowindex \dtl@asg@rowidx
  { #2 }
  { \dtlcolumnindex { #2 } { #3 } }
  { #1 }
  \datatool_if_null:NTF \dtl@asg@rowidx
  {
    \PackageError {datatool}
    {
      No ~ match ~ found ~ for ~
      \token_to_str:N \DTLassignfirstmatch
      \tl_to_str:n { { #2 } { #3 } { #1 } { #4 } }
    }
  }
  {
    The ~ database ~ `#2' ~ doesn't ~ contain ~
    an ~ entry ~ that ~ exactly ~ matches ~

```

```

        \tl_to_str:n { #1 } ' ~ for ~ column ~
        `#3'
      }
    }
  {
    \dtlgetrow { #2 } \dtl@asg@rowidx
    \@dtl@assign { #4 } { #2 }
  }
}
}
{
  \PackageError {datatool}
  {
    Can't ~ assign ~ first ~ match : ~ database ~ `#2' ~
    doesn't ~ exist
  }
  {
    Check ~ that ~ you ~ have ~ correctly ~ spelt ~
    the ~ database ~ name
  }
}
}
}
}
}

```

`\DTLassignfromcurrentrow{<assign list>}`

`\DTLassignfromcurrentrow`

For use where the current row has already been selected. The placeholder `\dtldbname` should already have been set. Unlike the above, this performs a local assignment.

```

\NewDocumentCommand \DTLassignfromcurrentrow { m }
{
  \tl_if_empty:NTF \dtldbname
  {
    \PackageError { datatool }
    {
      Can't ~ assign ~ from ~ current ~ row: ~
      current ~ row ~ not ~ assigned ~ or ~ placeholders ~
      have ~ been ~ changed
    }
    {
      You ~ need ~ to ~ select ~ the ~ current ~ row ~
      (for ~ example ~ with ~ \token_to_str:N \dtlgetrow ) ~
      before ~ you ~ can ~ query ~ the ~ current ~ row
    }
  }
}
{
  \DTLifdbexists { \dtldbname }
  {
    \__datatool_assign_cskey_list:nnn { #1 }
    { \dtldbname } { \c_false_bool }
  }
}
}

```

```

    }
    {
      \PackageError { datatool }
      {
        Can't ~ assign ~ from ~ current ~ row: ~
        database ~ ``dtldbname' ~ doesn't ~ exist
      }
      {
        It ~ seems ~ that ~ a ~ placeholder ~ normally ~ assigned ~
        when ~ a ~ row ~ is ~ selected ~ as ~ the ~ current ~ row ~
        doesn't ~ match ~ a ~ defined ~ database
      }
    }
  }
}

```

\@dtl@assign

`\@dtl@assign{<list>}{<db>}`

Assigns commands according to the given keys. The current row must be stored in `\dtlcurrentrow`. Version 3.0: definition rewritten in \LaTeX 3. The command name and syntax remains the same.

```

\newcommand*\@dtl@assign[2]{%
  \__datatool_assign_cskey_list:nnn { #1 } { #2 } { \c_true_bool }
}

```

New implementation:

```

\cs_new:Nn \__datatool_assign_cskey_list:nnn
{
  \keyval_parse:nnn
  { \__datatool_cskey_missing_val:n }
  { \__datatool_assign_parsed_cskey:nnnn { #2 } { #3 } }
  { #1 }
}
\cs_new:Nn \__datatool_assign_parsed_cskey:nnnn
{
  \__datatool_assign_cskey:Nnnn { #3 } { #4 } { #1 } { #2 }
}

```

`__datatool_assign_cskey:Nnn <tl var>{<key>}{<db name>}`

Assign command to the value of the item in the current row at the column identified by key. Local assignment:

```

\cs_new:Nn \__datatool_assign_cskey:Nnn
{
  \__datatool_assign_cskey:Nnnn { #1 } { #2 } { #3 } { \c_false_bool }
}

```

Global assignment:

```
\cs_new:Nn \__datatool_gassign_cskey:Nnn
{
  \__datatool_assign_cskey:Nnnn { #1 } { #2 } { #3 } { \c_false_bool }
}
```

```
\__datatool_assign_cskey:Nnnn <tl
var>{<key>}{<db name>}{<bool>}
```

If *<bool>* true assign globally, otherwise local assignment.

```
\cs_new:Nn \__datatool_assign_cskey:Nnnn
{
  \tl_if_single:nTF { #1 }
  {
```

Replicate old behaviour of `\@dtl@assigncmd` which set `\@dtl@dbname` to the database name:

```
\tl_gset:Nx \@dtl@dbname { #3 }
```

Check if the given key exists:

```
\@sDTLifhaskey { #3 } { #2 }
{
  \exp_args:NNx \dtlgetentryfromcurrentrow
  #1
  { \dtlcolumnindex { #3 } { #2 } }
  \datatool_if_null:NT #1
  {
    \__datatool_set_null:Nnn { #1 } { #2 } { \@dtl@dbname }
  }
  \bool_if:nT { #4 }
  {
    \tl_gset_eq:NN #1 #1
  }
}
{
  \PackageError { datatool }
  {
    Can't ~ assign ~ \tl_to_str:n { #1 = #2 }': ~ there ~
    is ~ no ~ key ~ `#2' ~ in ~ database ~ `#3'
  }
  {
    Check ~ that ~ you ~ have ~ correctly ~ spelt ~ the ~
    column ~ key
  }
  \bool_if:nTF { #4 }
  {
    \tl_gset_eq:NN #1 \DTLstringnull
  }
  {
```

```

        \tl_set_eq:NN #1 \DTLstringnull
      }
    }
  {
    \PackageError { datatool}
    {
      Invalid ~ cs=key ~ assignment ~ syntax ~ in ~
      '\tl_to_str:n { #1 = #2 }': ~
      single ~ control ~ sequence ~ required ~ before ~ '='
    }
    {
      Check ~ that ~ you ~ have ~ the ~ assignment ~ the ~ correct ~
      way ~ round
    }
  }
}

```

```
\@dtl@assigncmd<cmd>=<id>\@nil
```

\@dtl@assigncmd

Version 3.0: removed.

\@dtl@assigncmdnoop Version 3.0: removed.

\@dtl@setnull \@dtl@setnull{<cmd>}{<id>} globally sets <cmd> to either \@dtlstringnull or \@dtlnumbernull depending on the data type for <id>. (Database name should be stored in \@dtl@dbname prior to use.)

```
\newcommand*\@dtl@setnull}[2]{
```

Check if database given by \@dtl@dbname has the required key.

```
\@sDTLifhaskey { \@dtl@dbname } { #2 }
{
```

Set to the null applicable to the column data type.

```
\@@dtl@setnull #1 {#2}
}
{
```

Key not defined in database \@dtl@dbname.

```
\tl_gset_eq:NN #1 \DTLstringnull
}
}
```

\@@dtl@setnull As above, but doesn't check if key exists

```
\newcommand*\@@dtl@setnull}[2]{%
  \__datatool_gset_null:Nnn #1 { #2 } { \@dtl@dbname }
}
```

New to v3.0:

Global assignment:

```
\cs_new:Nn \__datatool_gset_null:Nnn  
{
```

Get the data type associated with this key and store in \@dtl@type.

```
\@sdtlgetdatatype \@dtl@type { #3 } { #2 }
```

Check data type.

```
\bool_lazy_or:nnTF  
  { \tl_if_empty_p:N \@dtl@type }  
  { \int_compare_p:n { \@dtl@type < 1 } }  
{
```

Data type is unknown or 0, so set to string null.

```
\tl_gset_eq:NN #1 \DTLstringnull  
}  
{
```

Data type is numerical, so set to number null.

```
\tl_gset_eq:NN #1 \DTLnumbernull  
}  
}
```

Local assignment:

```
\cs_new:Nn \__datatool_set_null:Nnn  
{
```

Get the data type associated with this key and store in \@dtl@type.

```
\@sdtlgetdatatype \@dtl@type { #3 } { #2 }
```

Check data type.

```
\bool_lazy_or:nnTF  
  { \tl_if_empty_p:N \@dtl@type }  
  { \int_compare_p:n { \@dtl@type < 1 } }  
{
```

Data type is unknown or 0, so set to string null.

```
\tl_set_eq:NN #1 \DTLstringnull  
}  
{
```

Data type is numerical, so set to number null.

```
\tl_set_eq:NN #1 \DTLnumbernull  
}  
}
```

\DTLifnull

```
\DTLifnull{<command>}{<true part>}{<false part>}
```

Checks if <command> is null (either \DTLstringnull or \DTLnumbernull) if true, does <true part> otherwise does <false part>.

```
\newcommand*\DTLifnull}[3]{%
  \datatool_if_null:nTF { #1 } { #2 } { #3 }
}
```

```
\DTLifnullloempty{<command>}{<true part>}{<>false
part>}
```

\DTLifnullloempty

```
\newcommand*\DTLifnullloempty}[3]{%
  \datatool_if_null_or_empty:nTF { #1 } { #2 } { #3 }
}
```

```
\DTLgetkeydata{<key>}{<db>}{<col cs>}{<type cs>
}{<header cs>}
```

\DTLgetkeydata

Gets data for given key in database *<db>*: the column index is stored in *<col cs>* and data type is stored in *<type cs>*. The unstarred version checks for the existence of the database and key, the starred version doesn't.

```
\newrobustcmd*\DTLgetkeydata}{%
  \@ifstar\@sdtlgetkeydata\@dtlgetkeydata
}
```

\@dtlgetkeydata Unstarred version of \DTLgetkeydata

```
\newcommand*\@dtlgetkeydata}[5]{
```

Check if the database exists.

```
\DTLifdbexists { #2 }
{
```

Check if the given key exists in the database.

```
\@sDTLifhaskey { #2 } { #1 }
{
```

Get the data.

```
\@sdtlgetkeydata { #1 } { #2 } #3 #4 #5
}
{
```

Key not defined in the given database.

```
\PackageError {datatool}
{
  Can't ~ get ~ data ~ for ~ key ~ `#1' :
  key ~ `#1' ~ not ~ defined ~ in ~ database ~ `#2'
}
{
  Check ~ that ~ you ~ have ~ correctly ~ spelt ~
  the ~ column ~ key ~ and ~ the ~ database ~ name
```

```

    }
  }
}
{
Database not defined.
  \PackageError {datatool}
  {
    Can't ~ get ~ data ~ for ~ key ~ `#1' :
    database ~ `#2' ~ doesn't ~ exist
  }
  {
    Check ~ that ~ you ~ have ~ correctly ~ spelt ~
    the ~ database ~ name
  }
}
}

```

`\@sdtlgetkeydata` `\@sdtlgetkeydata{<key>}{<db>}{<col cs>}{<type cs>}{<header cs>}` Starred version of `\DTLgetkeydata`.

```

\newcommand*{\@sdtlgetkeydata}[5]{
  \@sdtl@getcolumnindex #3 { #2 } { #1 }
  \_datatool_get_props:NNNNVx
  \@dtl@key #4 #5
  \l__datatool_before_tl
  \l__datatool_after_tl
  { dtlkeys@#2 }
  { #3 }
}

```

Backward-compatibility. TODO is this needed?

```

\_datatool_token_register_set:NV
  \@dtl@colhead
  \l__datatool_item_head_tl
\_datatool_token_register_set:NV
  \@dtl@before
  \l__datatool_before_tl
\_datatool_token_register_set:NV
  \@dtl@after
  \l__datatool_after_tl
}

```

The gather value commands are used in `datatool`.

```
\dtl@gathervalues[<label>]{<db name>}{<row toks>}
```

`\dtl@gathervalues`

Stores each element of `<row>` in `<db name>` into the command `\@dtl@<label>@<key>`, where `<key>` is the key for that element, and `<label>` defaults to `key`.

```

\newcommand{\dtl@gathervalues}[3][key]{
  \dtlforeachkey

```

```

( \dtl@key , \dtl@col , \dtl@type , \dtl@head )
\in { #2 }
\do
{
\dtlgetentryfromrow \dtl@tmp { \dtl@col } #3
\datatool_if_null:NT \dtl@tmp
{
\dtl@setnull \dtl@tmp \dtl@key
}
\tl_set_eq:cN { @dtl@#1@ \dtl@key } \dtl@tmp
}
}

```

`\dtl@g@gathervalues[⟨label⟩]{⟨db name⟩}{⟨row toks⟩}`

`\dtl@g@gathervalues`

As above but makes global assignments

```

\newcommand{\dtl@g@gathervalues}[3][key]{%
\dtlforeachkey
( \dtl@key , \dtl@col , \dtl@type , \dtl@head )
\in { #2 }
\do
{
\dtlgetentryfromrow \dtl@tmp { \dtl@col } #3
\datatool_if_null:NT \dtl@tmp
{
\dtl@setnull \dtl@tmp \dtl@key
}
\tl_gset_eq:cN { @dtl@#1@ \dtl@key } \dtl@tmp
}
}

```

`\dtlcurrentrow` Define token register to store current row.

`\newtoks\dtlcurrentrow`

`\dtlbeforerow` Define token register to store everything before the current row.

`\newtoks\dtlbeforerow`

`\dtlafterrow` Define token register to store everything after the current row.

`\newtoks\dtlafterrow`

`\dtlgetrow{⟨db⟩}{⟨row idx⟩}`

`\dtlgetrow`

Gets row with index `⟨row idx⟩` from database named `⟨db⟩` and stores the row in `\dtlcurrentrow`, the preceding rows in `\dtlbeforerow` and the following rows in `\dtlafterrow`. The row index, `⟨row idx⟩`, is stored in `\dtlrownum` and the

database name, $\langle db \rangle$, is stored in $\backslash dtldbname$. This assumes that the given row exists.

```

\NewDocumentCommand \dtlgetrow { m m }
{
  \datatool_get_row:nnTF { #1 } { #2 } { } { }
}

\cs_new:Nn \datatool_get_row:nnTF
{
  \int_compare:nNnTF
  { #2 } < { \c_one_int }
  {
    \PackageError { datatool }
    {
      \token_to_str:N \dtlgetrow : ~ invalid ~ row ~
      index ~ \int_eval:n { #1 } ~ for ~ database ~
      ` #1 '
    }
    {
      The ~ row ~ index ~ must ~ be ~ between ~ 1 ~
      and ~ the ~ total ~ number ~ of ~ rows ~ in ~ database
    }
  }
  #4
}
{
  \int_compare:nNnTF
  { #2 } > { \DTLrowcount { #1 } }
  {
    \PackageError { datatool }
    {
      \token_to_str:N \dtlgetrow : ~ row ~
      index ~ \int_eval:n { #1 } ~ out ~ of ~ range
      ~ for ~ database ~ ` #1 '
    }
    {
      Database ~ `#1' ~ only ~ has ~ \DTLrowcount{#1} ~ row(s)
    }
  }
  #4
}
{
  \int_set:Nn \dtlrownum { #2 }
  \tl_set:Nx \dtldbname { #1 }
  \__datatool_get_row:vx
  { dtldb@#1 } { \int_eval:n { #2 } }
  \int_compare:nNnTF { \__datatool_row_idx_int } = { -1 }
  {
    \PackageError { datatool }
    {
      \token_to_str:N \dtlgetrow : ~
      Something's ~ gone ~ wrong. ~ ~
    }
  }
}

```

```

        No ~ such ~ row ~ \int_eval:n { #2 } ~ \c_space_tl ~
        found ~ in ~ database ~ `#1'
      }
    {
      Database ~ `#1' ~ seems ~ to ~ be ~ missing ~ row ~
      \int_eval:n { #2 }
    }
  #4
}
{ #3 }
}
}
\cs_new:Nn \datatool_get_row:nnT
{
  \datatool_get_row:nnTF { #1 } { #2 } { #3 } { }
}

```

`\edtlgetrowforvalue{<db>}{<column idx>}{<value>}`

`\edtlgetrowforvalue`

A version of `\dtlgetrowforvalue` that expands its arguments.

```

\newrobustcmd{\edtlgetrowforvalue}[3]{%
  \__datatool_get_row_for_value:xxx
  { #1 } { \int_eval:n { #2 } } { #3 }
}

```

`\DTLfetch{<db name>}{<column1 name>}{<column1 value>}{<column2 name>}`

`\DTLfetch`

Fetches and displays the value for `<column2 name>` in the first row where the value of `<column1 name>` is `<column1 value>`. Note that all arguments are expanded.

```

\NewDocumentCommand \DTLfetch { m m m m }
{
  \edtlgetrowforvalue
  { #1 } { \dtlcolumnindex { #1 } { #2 } } { #3 }
  \dtlgetentryfromcurrentrow
  \dtlcurrentvalue { \dtlcolumnindex { #1 } { #4 } }
  \dtlcurrentvalue
}

```

`\dtlgetrowforvalue{<db>}{<column idx>}{<value>}`

`\dtlgetrowforvalue`

Like `\dtlgetrow`, but gets the row where the entry in column `<column index>` matches `<value>`. Produces an error if row not found.

```

\NewDocumentCommand \dtlgetrowforvalue { m m m }
{
  \__datatool_get_row_for_value:xxn
  { #1 } { \int_eval:n { #2 } } { #3 }
}

```

Triggers an error if row not found:

```

\cs_new:Nn \__datatool_get_row_for_value:nnn
{
  \__datatool_get_row_for_value:nnnF { #1 } { #2 } { #3 }
  {
    \PackageError {datatool}
    {
      No ~ row ~ found ~ in ~ database ~ `#1' ~ for ~
      column ~ ` \int_eval:n { #2 } ' ~ matching ~
      ` \tl_to_str:n { #3 } '
    }
  }
}
\cs_generate_variant:Nn
\__datatool_get_row_for_value:nnn
{ xxn , xvn , xxx }
\cs_new:Nn \__datatool_get_row_for_value:nnnTF
{
  \__datatool_get_row_index:Nnnn
  \l__datatool_row_idx_tl { #1 } { #2 } { #3 }
  \datatool_if_null:NTF \l__datatool_row_idx_tl
  { #5 }
  {
    \int_set:Nn \dtlrownum { \l__datatool_row_idx_tl }
    \tl_set:Nx \dtldbname { #1 }
    \__datatool_get_row:vx
    { dtldb@#1 } { \l__datatool_row_idx_tl }
    #4
  }
}
\cs_generate_variant:Nn
\__datatool_get_row_for_value:nnnTF
{ xxxTF }
\cs_new:Nn \__datatool_get_row_for_value:nnnT
{
  \__datatool_get_row_for_value:nnnTF
  { #1 } { #2 } { #3 } { #4 } { }
}
\cs_generate_variant:Nn
\__datatool_get_row_for_value:nnnT
{ xxnT , xvnT , xxxT , VVVT }

```

```

\cs_new:Nn \__datatool_get_row_for_value:nnnF
{
  \__datatool_get_row_for_value:nnnTF
    { #1 } { #2 } { #3 } { } { #4 }
}
\cs_generate_variant:Nn
  \__datatool_get_row_for_value:nnnF
  { xxnF , xvnF , xxxF }

```

\@dtlgetrow{<data specs>}{<row idx>}

\@dtlgetrow

Gets the row specs from <data specs> for row with index <row idx> which must be fully expanded.

```

\newcommand*{\@dtlgetrow}[2]{%
  \__datatool_get_row:nn { #1 } { #2 }
}
\cs_new:Nn \__datatool_get_row:nn
{
  \tl_if_in:nnTF { #1 } { \db@row@id@w #2\db@row@id@end@ }
  {
    \cs_set:Npn \__datatool_get_row:w ##1% before stuff
      \db@row@elt@w% start of the row
      \db@row@id@w #2\db@row@id@end@% row id
      ##2%
      \db@row@id@w #2\db@row@id@end@% row id
      \db@row@elt@end@% end of the row
      ##3% after stuff
    \q_nil
  }
  {
    \dtlbeforerow = {##1}
    \dtlcurrentrow = {##2}
    \dtlafterrow = {##3}
    \int_set:Nn \l__datatool_row_idx_int { #2 }
  }
  \__datatool_get_row:w #1 \q_nil
}
{
  No such row.
  \dtlbeforerow = { }
  \dtlcurrentrow = { }
  \dtlafterrow = { }
  \int_set:Nn \l__datatool_row_idx_int { -1 }
}
}
\cs_generate_variant:Nn \__datatool_get_row:nn
  { vn , vV, vx }

```

```

\__datatool_get_row:nnN{<data specs>}{<row index>}{tl
var}

```

Similar but provide variables in which to store row markup. Before and after content not required. The token list will be cleared if row not found, otherwise it will be set to the row content.

```

\cs_new:Nn \__datatool_get_row:nnN
{
  \tl_if_in:nnTF { #1 } { \db@row@id@w #2\db@row@id@end@ }
  {
    \cs_set:Npn \__datatool_get_row:w ##1% before stuff
      \db@row@elt@w% start of the row
      \db@row@id@w #2\db@row@id@end@% row id
      ##2%
      \db@row@id@w #2\db@row@id@end@% row id
      \db@row@elt@end@% end of the row
      ##3% after stuff
    \q_nil
  }
  {
    \tl_set:Nn #3 { ##2 }
  }
  \__datatool_get_row:w #1 \q_nil
}
{
  \tl_clear:N #3
}
}
\cs_generate_variant:Nn \__datatool_get_row:nnN
{ vnN, vVN }

```

```

\dtlrecombine

```

\dtlrecombine

Recombines database contents from \dtlbeforerow, \dtlcurrentrow and \dtlafterrow. Version 3.0: check global option.

```

\newrobustcmd* \dtlrecombine
{
  \__datatool_dtlconcat:VNxN
  \dtldbname
  \dtlbeforerow
  {
    \__datatool_row_markup:VV
    \dtlrownum
    \dtlcurrentrow
  }
  \dtlafterrow
}

```

\dtlrecombineomitcurrent

\dtlrecombineomitcurrent

Like \dtlrecombine but omits \dtlcurrentrow. Version 3.0: check global option.

```
\newrobustcmd* \dtlrecombineomitcurrent
{
```

Decrement row indices in \dtlafterrow:

```
\dtl@decrementrows{\dtlafterrow}{\dtlrownum}
```

Reconstruct database contents by concatenating \dtlbeforerow and \dtlafterrow

```
\__datatool_dtl_db_set:Vx
\dtldbname
{
\exp_not:V \dtlbeforerow
\exp_not:V \dtlafterrow
}
```

Decrement row counter.

```
\bool_if:NTF \__datatool_db_global_bool
{
\int_gdecr:c { dtlrows@ \dtldbname }
}
{
\int_decr:c { dtlrows@ \dtldbname }
}
\dtl@message
{
Removed ~ row ~ \int_use:N \dtlrownum \c_space_tl ~
from ~ database ~ ` \dtldbname '
}
}
```

\dtlsplitrow

\dtlsplitrow{<row specs>}{<col num>}{<before cs>}{<after cs>}

Splits the row around the entry given by <col num>. The entries before the split are stored in <before cs> and the entries after the split are stored in <after cs>. <row specs> and <col num> need to be expanded before use.

```
\NewDocumentCommand \dtlsplitrow { m m m m }
{
\exp_args:Nnx
\__datatool_split_row:nnNN
{ #1 } { \int_eval:n { #2 } } #3 #4
}
```

Syntax: {<row specs>}{<col idx>}{<before var>}{<after var>}
\cs_new:Nn __datatool_split_row:nnNN

```

{
  \__datatool_if_split_row:nnNFF
  { #1 } { #2 } #3 #4
  {
    \PackageWarning { datatool }
    {
      \token_to_str:N \dtlsplitrow : ~
      no ~ column ~ with ~ index ~ \tl_to_str:n { #2 } ~
      in ~ current ~ row
    }
  }
}
\cs_generate_variant:Nn \__datatool_split_row:nnNN
{ VvNN , VVNN, VxNN, VnNN }
\cs_new:Nn \__datatool_if_split_row:nnNNTF
{
  \tl_if_in:nnTF
  { #1 } { \db@col@id@w #2 \db@col@id@end@ }
  {
    \cs_set:Npn \__datatool_split_row:w
      ##1 % before stuff
      \db@col@id@w #2\db@col@id@end@ % column id
      ##2 % unwanted stuff
      \db@col@id@w #2\db@col@id@end@ % column id
      ##3 % after stuff
      \q_nil
      {
        \tl_set:Nn #3 { ##1 }
        \tl_set:Nn #4 { ##3 }
        #5
      }
    \__datatool_split_row:w #1 \q_nil
  }
  {
    \tl_set:Nn #3 { #1 }
    \tl_clear:N #4
    #6
  }
}
\cs_new:Nn \__datatool_if_split_row:nnNNT
{
  \__datatool_if_split_row:nnNNTF
  { #1 } { #2 } #3 #4 { #5 } { }
}
\cs_new:Nn \__datatool_if_split_row:nnNFF
{
  \__datatool_if_split_row:nnNNTF
  { #1 } { #2 } #3 #4 { } { #5 }
}

```

replaceentryincurrentrow

`\dtlreplaceentryincurrentrow{<new value>}{<col num>}`

Replaces entry for column *<col num>* in `\dtlcurrentrow` with *<new value>*

```

\NewDocumentCommand \dtlreplaceentryincurrentrow { m m }
{
  \__datatool_replace_in_current:nx
  { #1 } { \int_eval:n { #2 } }
}

\cs_new:Nn \__datatool_replace_in_current:nn
{

```

Split row

```

  \__datatool_split_row:VnNN
  \dtlcurrentrow
  { #2 }
  \l__datatool_before_tl
  \l__datatool_after_tl

```

Process value according to current options, which will save the value in the token register `\@dtl@toks` and in the token list variable `\l__datatool_item_value_tl`. The datatype will also be set in the `\dtl@datatype` variable.

```

  \__datatool_process_new_value:n { #1 }

```

Recombine with new value and store in `\dtlcurrentrow`

```

  \__datatool_token_register_set:Nx
  \dtlcurrentrow
  {
    \exp_not:V \l__datatool_before_tl
    \__datatool_row_element_markup:nV
    { #2 } \l__datatool_item_value_tl
    \exp_not:V \l__datatool_after_tl
  }

```

Update column specs. This will set `\l__datatool_item_key_tl`

```

  \__datatool_update_meta_data_col_index_with_type:VnV
  \dtldbname { #2 } \@dtl@datatype
  \dtl@message
  {
    Updated ~ \l__datatool_item_key_tl \c_space_tl ~ -> ~
    \exp_not:n { #1 } ~ in ~ database ~ ` \dtldbname '
  }
}

\cs_generate_variant:Nn
  \__datatool_replace_in_current:nn
  { nx }

```

`\dtlremoveentryincurrentrow{<col idx>}`

lremoveentryincurrentrow

Removes entry for column $\langle col\ idx\rangle$ from $\backslash dtlcurrentrow$.

```
\NewDocumentCommand \dtlremoveentryincurrentrow { m }  
{
```

Split row

```
  \__datatool_split_row:VxNN  
  \dtlcurrentrow  
  { \int_eval:n { #1 } }  
  \l__datatool_before_tl  
  \l__datatool_after_tl
```

Recombine without given column and store in $\backslash dtlcurrentrow$

```
  \__datatool_token_register_set:Nx  
  \dtlcurrentrow  
  {  
    \exp_not:V \l__datatool_before_tl  
    \exp_not:V \l__datatool_after_tl  
  }  
  \dtl@message  
  {  
    Removed ~ entry ~ from ~ column ~ \int_eval:n { #1 } \c_space_tl ~  
    in ~ database ~ `dtldbname'  
  }  
}
```

```
\dtlswapentriesincurrentrow{<col1  
num>}{<col2 num>}
```

lswapentriesincurrentrow

Swaps columns $\langle col1\ num\rangle$ and $\langle col2\ num\rangle$ in $\backslash dtlcurrentrow$

```
\NewDocumentCommand \dtlswapentriesincurrentrow { m m }  
{  
  \dtlgetentryfromcurrentrow \@dtl@entryI { #1 }  
  \dtlgetentryfromcurrentrow \@dtl@entryII { #2 }  
  \exp_args:NV \dtlreplaceentryincurrentrow  
  \@dtl@entryII { #1 }  
  \exp_args:NV \dtlreplaceentryincurrentrow  
  \@dtl@entryI { #2 }  
}
```

```
\dtlgetentryfromcurrentrow{<cs>}{<col num>}
```

tlgetentryfromcurrentrow

Gets value for column $\langle col\ num\rangle$ from $\backslash dtlcurrentrow$ and stores in $\langle cs\rangle$. If not found, $\langle cs\rangle$ is set to $\backslash dtlnovalue$.

```
\NewDocumentCommand \dtlgetentryfromcurrentrow { m m }  
{  
  \dtlgetentryfromrow { #1 } { #2 } \dtlcurrentrow  
}
```

\dtlgetentryfromrow

\dtlgetentryfromrow{<cs>}{<col num>}{<row toks>}

```
\NewDocumentCommand \dtlgetentryfromrow { m m m }
{
  \__datatool_get_entry_from_row:NxV
  #1 { \int_eval:n { #2 } } #3
}
```

\dtl@getentryfromrow

\dtl@getentryfromrow{<cs>}{<col num>}{<row specs>}

```
\newcommand*{\dtl@getentryfromrow}[3]{%
  \__datatool_get_entry_from_row:Nnn #1 { #2 } { #3 }
}

\cs_new:Nn \__datatool_get_entry_from_row:Nnn
{
  \cs_set:Npn \__datatool_get_entry_from_row:w
    ##1 % before stuff
    \db@col@id@w #2\db@col@id@end@ % Column id
    \db@col@elt@w ##2\db@col@elt@end@ % Value
    \db@col@id@w #2\db@col@id@end@ % Column id
    ##3 % Remaining stuff
    \q_nil { \tl_set:Nn #1 { ##2 } }
  \__datatool_get_entry_from_row:w
  #3
  \db@col@id@w #2 \db@col@id@end@
  \db@col@elt@w \c_datatool_nullvalue_tl \db@col@elt@end@
  \db@col@id@w #2 \db@col@id@end@
  \q_nil
  \__datatool_rm_weird_datum:N #1
}
\cs_generate_variant:Nn
  \__datatool_get_entry_from_row:Nnn
  { NVV, NxV, NVn }
```

\dtlappendentrytocurrentrow

\dtlappendentrytocurrentrow{<key>}{<value>}

Appends entry to \dtlcurrentrow. NB this originally always expanded <value>. As from v3.0, this will use the same settings as \DTLnewdbentry.

```
\NewDocumentCommand \dtlappendentrytocurrentrow { m m }
{
```

Parse and process value. This will set \l__datatool_item_value_tl and \@dtl@datatype

```
  \__datatool_process_new_value:n { #2 }
```

Update information about this column (adding new column if necessary).

```
  \__datatool_update_meta_data_with_type:nnV
    { \dtldbname } { #1 } \@dtl@datatype
```

Get column index and store in \dtlcolumnnum

```
  \int_set:Nn \dtlcolumnnum
    { \dtlcolumnindex { \dtldbname } { #1 } }
```

Does this row already have an entry with this key?

```
  \exp_args:NNV \dtlgetentryfromcurrentrow
    \dtl@entry \dtlcolumnnum
  \datatool_if_null:NTF \dtl@entry
    {
```

There are no entries in this row for the given key. Append this entry to the current row.

```
  \bool_if:NTF \l__datatool_db_global_bool
    {
      \__datatool_token_register_gput_right:Nx
        \dtlcurrentrow
      {
        \__datatool_row_element_markup:VV
          \dtlcolumnnum
          \l__datatool_item_value_tl
      }
    }
  {
    \__datatool_token_register_put_right:Nx
      \dtlcurrentrow
    {
      \__datatool_row_element_markup:VV
        \dtlcolumnnum
        \l__datatool_item_value_tl
    }
  }
}
```

Print information to terminal and log file if in verbose mode.

```
  \dtl@message
    {
      Appended ~ #1 \c_space_tl ->
      \exp_not:V \l__datatool_item_value_tl \c_space_tl ~
      to ~ current ~ row ~ of ~ database ~ ``\dtldbname'
    }
  }
  {
```

There is already an entry in this row for the given key

```
  \PackageError {datatool}
    {
      Can't ~ append ~ entry ~ to ~ row: ~ there ~ is ~
      already ~ an ~ entry ~ for ~ key ~ `#1' ~ in ~
      the ~ current ~ row
    }
```

```

    }
    {
      Use ~ \token_to_str:N \dtlupdateentryincurrentrow
      \c_space_tl ~ to ~ replace ~ an ~ existing ~ entry
    }
  }
}

```

`\dtlupdateentryincurrentrow{<key>}{<value>}`

lupdateentryincurrentrow

Appends entry to `\dtlcurrentrow` if column with given key doesn't exist, otherwise updates the value.

```

\NewDocumentCommand \dtlupdateentryincurrentrow { m m }
{

```

Parse and process value. This will set `\l__datatool_item_value_tl` and `\@dtl@datatype`

```

  \__datatool_process_new_value:n { #2 }

```

Update information about this column (adding new column if necessary)

```

  \__datatool_update_meta_data_with_type:nnV
  { \dtldbname } { #1 } \@dtl@datatype

```

Get column index and store in `\dtlcolumnnum`

```

  \int_set:Nn \dtlcolumnnum
  { \dtlcolumnindex { \dtldbname } { #1 } }

```

Does this row already have an entry with this key?

```

  \exp_args:NNV \dtlgetentryfromcurrentrow
  \dtl@entry \dtlcolumnnum
  \datatool_if_null:NTF \dtl@entry
  {

```

There are no entries in this row for the given key. Append this entry to the current row.

NB this used to always globally append. Version 3.0: check boolean setting.

```

  \bool_if:NTF \l__datatool_db_global_bool
  {
    \__datatool_token_register_gput_right:Nx
    \dtlcurrentrow
    {
      \__datatool_row_element_markup:VV
      \dtlcolumnnum
      \l__datatool_item_value_tl
    }
  }
  {
    \__datatool_token_register_put_right:Nx
    \dtlcurrentrow
    {
      \__datatool_row_element_markup:VV

```

```

        \dtlcolumnnum
        \l__datatool_item_value_tl
    }
}

```

Print information to terminal and log file if in verbose mode.

```

\dtl@message
{
  Appended ~ #1 \c_space_tl -> ~
  \exp_not:V \l__datatool_item_value_tl
  \c_space_tl ~ to ~ the ~ current ~ row ~ of ~
  database ~ ` \dtldbname '
}
}
{

```

There is already an entry in this row for the given key Split row

```

\_datatool_split_row:VVNN
  \dtlcurrentrow
  \dtlcolumnnum
  \l__datatool_before_tl
  \l__datatool_after_tl

```

Recombine with new value and store in \dtlcurrentrow

```

\_datatool_token_register_set:Nx
  \dtlcurrentrow
  {
    \exp_not:V \l__datatool_before_tl
    \_datatool_row_element_markup:VV
    \dtlcolumnnum \l__datatool_item_value_tl
    \exp_not:V \l__datatool_after_tl
  }
  \dtl@message
  {
    Updated ~ #1 \c_space_tl ~ -> ~
    \exp_not:V \l__datatool_item_value_tl \c_space_tl ~
    in ~ database ~ ` \dtldbname '
  }
}
}

```

`\DTLgetvalue{<cs>}{<db>}{<r>}{<c>}`

\DTLgetvalue

Gets the element in row $\langle r \rangle$, column $\langle c \rangle$ from database $\langle db \rangle$ and stores in $\langle cs \rangle$.

```

\NewDocumentCommand \DTLgetvalue { m m m m }
{
  \_datatool_get_value:Nnxx #1 { #2 }
  { \int_eval:n { #3 } }
  { \int_eval:n { #4 } }
}

```

```

\datatool_if_null:NT #1
{
  \PackageError { datatool }
  {
    There ~ is ~ no ~ element ~ at ~ (row=#3, ~ column=#4) ~
    in ~ database ~ `#2'
  }
  { }
}
}

```

\dtl@getvalue

```

\newcommand*{\dtl@getvalue}[4]{%
  \__datatool_get_value:Nnnn #1 { #2 } { #3 } { #4 }
  \datatool_if_null:NT #1
  {
    \PackageError { datatool }
    {
      There ~ is ~ no ~ element ~ at ~ (row=#3, ~ column=#4) ~
      in ~ database ~ `#2'
    }
    { }
  }
}

```

Syntax: <tl var> {<db>}{<r>}{<c>}

```

\cs_new:Nn \__datatool_get_value:Nnnn
{
  \cs_set:Npn \__datatool_get_value:w ##1 % stuff before row <r>
  \db@row@id@w #3\db@row@id@end@ % row <r> id
  ##2 % stuff in row <r> before column <c>
  \db@col@id@w #4\db@col@id@end@ % column <c> id
  \db@col@elt@w ##3\db@col@elt@end@ % value
  \db@col@id@w #4\db@col@id@end@ % column <c> id
  ##4 % stuff after value
  \q_nil
  {
    \tl_set:Nn #1 { ##3 }
  }
  \exp_last_unbraced:Nv \__datatool_get_value:w
  { dtldb@ #2 }
  \db@row@id@w #3 \db@row@id@end@
  \db@col@id@w #4 \db@col@id@end@
  \db@col@elt@w
  \c_datatool_nullvalue_tl % undefined value
  \db@col@elt@end@
  \db@col@id@w #4 \db@col@id@end@
  \q_nil
}
\cs_generate_variant:Nn \__datatool_get_value:Nnnn

```

{ NnVV , Nnxx }

```
\DTLgetlocation{<row cs>}{<column cs>}{<database>}
{<value>}
```

\DTLgetlocation

Assigns <row cs> and <column cs> to the indices of the first entry in <database> that matches <value>.

```
\NewDocumentCommand \DTLgetlocation { m m m m }
{
  \__datatool_get_location:Nn #1 #2 { #3 } { #4 }
  \datatool_if_null:NT #1
  {
    \PackageError { datatool }
    {
      There ~ is ~ no ~ element ~
      ` \exp_not:n { #4 } ' ~ in ~ database ~ `#3'
    }
  }
}
```

Syntax: <row tl var> <column tl var> {<database>} {<value>}

```
\cs_new:Nn \__datatool_get_location:Nn
{
  \tl_set_eq:NN #1 \dtlnovalue
```

Test if the value starts with datum marker.

```
\tl_if_head_eq_meaning:nNT
  { #4 } \__datatool_datum:n
  {
    \__datatool_get_location:NnnnwNn
    #4 \q_stop #1 #2 { #3 }
  }
  \tl_if_eq:NNT #1 \dtlnovalue
  {
```

Try an exact match.

```
\cs_set:Npn \__datatool_get_location:w
  ##1 % stuff before value
  \db@col@elt@w #4\db@col@elt@end@ % value
  \db@col@id@w ##2\db@col@id@end@ % column id
  ##3 % stuff after this column
  \db@row@id@w ##4\db@row@id@end@ % row id
  ##5 % stuff after row
  \q_nil
  {
    \tl_set:Nn #1 { ##4 }
    \tl_set:Nn #2 { ##2 }
  }
```

```

\exp_last_unbraced:Nv \__datatool_get_location:w
{ dtldb@#3 } % contents of data base
\db@col@elt@w
#4 % value
\db@col@elt@end@
\db@col@id@w
  \c_datatool_nullvalue_tl % undefined column id
\db@col@id@end@
\db@row@id@w
  \c_datatool_nullvalue_tl % undefined row id
\db@row@id@end@
\q_nil
}
\tl_if_eq:NNT #1 \dtlnovalue
{

```

Try matching weird datum.

```

\tl_set:Nn \l__datatool_cs_builder_tl
{
  \cs_set:Npn \__datatool_get_location:w
    ##1 % stuff before value
    \db@col@elt@w

```

Encapsulate value with weird datum

```

  \__datatool_datum:w
}
\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \c__datatool_datum_weird_marker_tl
  \exp_not:n { #4 } % string value
  \c__datatool_datum_weird_marker_tl
}
\tl_put_right:Nn \l__datatool_cs_builder_tl
{ ##2 } % numeric value
\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \c__datatool_datum_weird_marker_tl
}
\tl_put_right:Nn \l__datatool_cs_builder_tl
{ ##3 } % currency symbol
\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \c__datatool_datum_weird_marker_tl
}
\tl_put_right:Nn \l__datatool_cs_builder_tl
{ ##4 } % data type
\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \c__datatool_datum_weird_marker_tl
}
\tl_put_right:Nn \l__datatool_cs_builder_tl

```

```

    {
      \db@col@elt@end@
      \db@col@id@w ##5\db@col@id@end@ % column id
      ##6 % stuff after this column
      \db@row@id@w ##7\db@row@id@end@ % row id
      ##8 % stuff after row
      \q_nil
      {
        \tl_set:Nn #1 { ##7 } % row
        \tl_set:Nn #2 { ##5 } % column
      }
      \exp_last_unbraced:Nv \__datatool_get_location:w
      { dtldb@#3 } % contents of data base
      \db@col@elt@w
    }
  \tl_put_right:Nx \l__datatool_cs_builder_tl
  {
    \__datatool_weird_datum:nnnn
    { #4 } { } { } { }
  }
  \tl_put_right:Nn \l__datatool_cs_builder_tl
  {
    \db@col@elt@end@
    \db@col@id@w
    \c_datatool_nullvalue_tl % undefined column id
    \db@col@id@end@
    \db@row@id@w
    \c_datatool_nullvalue_tl % undefined row id
    \db@row@id@end@
    \q_nil
  }
  \l__datatool_cs_builder_tl
}
}
\cs_generate_variant:Nn
  \__datatool_get_location:NNnn
  { NNnx , NNnV }
  Similarly but to match a value supplied as a datum marker. Arguments: <datum-
  marker-cs>{<string>}{<value>}{<currency>}{<type>} <extra>\q_stop <row tl var>
  <column tl var> {<database>} If <extra> isn't empty then there's some trailing material.
  \cs_new:Npn \__datatool_get_location:NnnnnwNNn
    #1 #2 #3 #4 #5 #6 \q_stop #7 #8 #9
  {
    \tl_if_empty:nT { #6 }
    {
      No trailing material. Just match on the string value.
      \__datatool_get_location:NNnn #7 #8 { #9 } { #2 }
    }
  }
}

```

```
\DTLgetrowindex{<row cs>}{<database>}{<column index>}
{<value>}
```

\DTLgetrowindex

Assigns <row cs> to the row index of the first entry in <database> where the entry in <column index> matches <value>.

```
\NewDocumentCommand \DTLgetrowindex { s m m m m }
{
  \IfBooleanTF { #1 }
  { \dtlgetrowindex { #2 } { #3 } { #4 } { #5 } }
  { \@DTLgetrowindex { #2 } { #3 } { #4 } { #5 } }
}
```

\@DTLgetrowindex

```
\newcommand{\@DTLgetrowindex}[4]{%
  \__datatool_get_row_index:NnXn #1
  { #2 } { \int_eval:n { #3 } } { #4 }
  \datatool_if_null:NT #1
  {
    \PackageError {datatool}
    {
      There ~ is ~ no ~ element ~ `#4' ~ for ~ column ~
      \int_eval:n { #3 } ~ in ~ database ~ `#2'
    }
  }
}
```

```
\dtlgetrowindex{<row cs>}{<database>}{<column index>}
{<value>}
```

\dtlgetrowindex

As above but doesn't produce an error if not found.

```
\newrobustcmd*{\dtlgetrowindex}[4]{%
  \__datatool_get_row_index:NnXn #1
  { #2 } { \int_eval:n { #3 } } { #4 }
}
```

```
\xdtlgetrowindex{<row cs>}{<database>}{<column index>}
{<value>}
```

\xdtlgetrowindex

As above but expands the value.

```
\newcommand*{\xdtlgetrowindex}[4]{%
  \__datatool_get_row_index:NnXx #1
  { #2 } { \int_eval:n { #3 } } { #4 }
}
```

```
\@dtlgetrowindex{<row cs>}{<database>}{<column index>}
{<value>}
```

\@dtlgetrowindex

Column index must be fully expanded.

```
\newcommand*\@dtlgetrowindex[4]{
  \__datatool_get_row_index:Nnnn #1 { #2 } { #3 } { #4 }
}
```

Arguments: {<row tl var>}{<database>}{<column index>} {<value>} NB the value mustn't contain any groups or other awkward tokens that can't be used in function parameter syntax.

```
\cs_new:Nn \__datatool_get_row_index:Nnnn
{
  \tl_set_eq:NN #1 \dtlnovalue
```

Test if value starts with datum marker:

```
\tl_if_head_eq_meaning:nNT { #4 } \__datatool_datum:nnnn
{
  \__datatool_get_row_index:NnnnnwNnn
  #4 \q_stop #1 { #2 } { #3 }
}
```

Try an exact match.

```
\tl_if_eq:NNT #1 \dtlnovalue
{
  \cs_set:Npn \__datatool_get_row_index:w
    ##1 % before
    \db@col@id@w #3\db@col@id@end@ % column id
    \db@col@elt@w #4\db@col@elt@end@ % value
    \db@col@id@w #3\db@col@id@end@ % column id
    ##2 % remainder of row
    \db@row@id@w ##3\db@row@id@end@ % row id
    ##4 % after row
    \q_nil
  {
    \tl_set:Nn #1 { ##3 }
  }
}
\exp_last_unbraced:Nv \__datatool_get_row_index:w
{ dtldb@#2 }
\db@col@id@w #3\db@col@id@end@% column id
\db@col@elt@w
#4
\db@col@elt@end@
\db@col@id@w #3\db@col@id@end@% column id
\db@row@id@w
\c_datatool_nullvalue_tl % undefined row id
\db@row@id@end@
\q_nil
}
```

```
\tl_if_eq:NNT #1 \dtlnovalue
{
```

Try matching weird datum.

```
\tl_set:Nn \l__datatool_cs_builder_tl
{
  \cs_set:Npn \__datatool_get_row_index:w
    ##1 % before
    \db@col@id@w #3\db@col@id@end@ % column id
    \db@col@elt@w
```

Encapsulate value with weird datum

```
\__datatool_datum:w
}
\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \c__datatool_datum_weird_marker_tl
  \exp_not:n { #4 }
  \c__datatool_datum_weird_marker_tl
}
\tl_put_right:Nn \l__datatool_cs_builder_tl
{ ##2 }
\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \c__datatool_datum_weird_marker_tl
}
\tl_put_right:Nn \l__datatool_cs_builder_tl
{ ##3 }
\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \c__datatool_datum_weird_marker_tl
}
\tl_put_right:Nn \l__datatool_cs_builder_tl
{ ##4 }
\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \c__datatool_datum_weird_marker_tl
}
\tl_put_right:Nn \l__datatool_cs_builder_tl
{
  \db@col@elt@end@
  \db@col@id@w #3\db@col@id@end@ % column id
  ##5 % remainder of row
  \db@row@id@w ##6\db@row@id@end@ % row id
  ##7 % after row
  \q_nil
  {
    \tl_set:Nn #1 { ##6 }
  }
  \exp_last_unbraced:Nv \__datatool_get_row_index:w
  { dtldb@#2 }
```

```

        \db@col@id@w #3\db@col@id@end@% column id
        \db@col@elt@w
    }
\trl_put_right:Nx \l__datatool_cs_builder_tl
{
    \__datatool_weird_datum:nnnn
    { #4 } { } { } { }
}
\trl_put_right:Nn \l__datatool_cs_builder_tl
{
    \db@col@elt@end@
    \db@col@id@w #3\db@col@id@end@% column id
    \db@row@id@w
    \c_datatool_nullvalue_tl % undefined row id
    \db@row@id@end@
    \q_nil
}
\l__datatool_cs_builder_tl
}
}
\cs_generate_variant:Nn
\__datatool_get_row_index:Nnnn
{ Nnnx , Nxxx, Nxvn, Nnxn }

```

Similarly but to match a value supplied as a datum marker. Arguments: $\langle datum\text{-}marker\text{-}cs \rangle \{ \langle string \rangle \} \{ \langle value \rangle \} \{ \langle currency \rangle \} \{ \langle type \rangle \} \langle extra \rangle \backslash q_stop \{ \langle row\ tl\ var \rangle \} \{ \langle database \rangle \} \{ \langle column\ index \rangle \}$ If $\langle extra \rangle$ isn't empty then there's some trailing material.

```

\cs_new:Npn \__datatool_get_row_index:NnnnwNnn
    #1 #2 #3 #4 #5 #6 \q_stop #7 #8 #9
{
    \trl_set_eq:NN #7 \dtlnovalue
    \trl_if_empty:nT { #6 }
    {

```

First try an exact match.

```

    \trl_set:Nn \l__datatool_cs_builder_tl
    {
        \cs_set:Npn \__datatool_get_row_index:w
            ##1 % before
            \db@col@id@w #9\db@col@id@end@ % column id
            \db@col@elt@w
    }

```

Encapsulate value with weird datum

```

\trl_put_right:Nx \l__datatool_cs_builder_tl
{
    \__datatool_weird_datum:nnnn
    { #2 } { #3 } { #4 } { #5 }
}
\trl_put_right:Nn \l__datatool_cs_builder_tl

```

```

{
  \db@col@elt@end@
  \db@col@id@w #9\db@col@id@end@ % column id
  ##2 % remainder of row
  \db@row@id@w ##3\db@row@id@end@ % row id
  ##4 % after row
  \q_nil
  {
    \tl_set:Nn #7 { ##3 }
  }
  \exp_last_unbraced:Nv \__datatool_get_row_index:w
  { dtldb@#8 }
  \db@col@id@w #9\db@col@id@end@% column id
  \db@col@elt@w
}
\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \__datatool_weird_datum:nnnn
  { #2 } { #3 } { #4 } { #5 }
}
\tl_put_right:Nn \l__datatool_cs_builder_tl
{
  \db@col@elt@end@
  \db@col@id@w #9\db@col@id@end@% column id
  \db@row@id@w
  \c_datatool_nullvalue_tl % undefined row id
  \db@row@id@end@
  \q_nil
}
\l__datatool_cs_builder_tl
\tl_if_eq:NNT #7 \dtlnovalue
{

```

Try with just the string part.

```

\tl_set:Nn \l__datatool_cs_builder_tl
{
  \cs_set:Npn \__datatool_get_row_index:w
  ##1 % before
  \db@col@id@w #9\db@col@id@end@ % column id
  \db@col@elt@w
}

```

Encapsulate value with weird datum

```

\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \__datatool_weird_datum:nnnn
  { #2 } { ##2 } { ##3 } { ##4 }
}
\tl_put_right:Nn \l__datatool_cs_builder_tl
{
  \db@col@elt@end@

```

```

\db@col@id@w #9\db@col@id@end@ % column id
##5 % remainder of row
\db@row@id@w ##6\db@row@id@end@ % row id
##7 % after row
\q_nil
{
  \tl_set:Nn #7 { ##6 }
}
\exp_last_unbraced:Nv \__datatool_get_row_index:w
{ dtldb@#8 }
\db@col@id@w #9\db@col@id@end@% column id
\db@col@elt@w
}
\tl_put_right:Nx \l__datatool_cs_builder_tl
{
  \__datatool_weird_datum:nnnn
  { #2 } { } { } { }
}
\tl_put_right:Nn \l__datatool_cs_builder_tl
{
  \db@col@elt@end@
  \db@col@id@w #9\db@col@id@end@% column id
  \db@row@id@w
  \c_datatool_nullvalue_tl % undefined row id
  \db@row@id@end@
  \q_nil
}
\l__datatool_cs_builder_tl
}
}
}
}

```

12.5 Iterating Through Databases

Temporary variables for use in `\DTLmapdata`

```

\tl_new:N \l__datatool_map_data_tl
\tl_new:N \l__datatool_map_data_loop_body_tl
\tl_new:N \l__datatool_map_data_row_tl
\tl_new:N \l__datatool_map_data_pending_tl
\bool_new:N \l__datatool_map_data_readonly_bool
\bool_new:N \l__datatool_map_data_update_pending_bool
\int_new:N \l__datatool_map_data_max_cols_int
\prop_new:N \l__datatool_map_data_col_type_prop

```

Options for `\DTLmapdata`:

```

\keys_define:nn { datatool/mapdata }
{
  name .str_set_x:N = \dtldbname,
  read-only .bool_set:N = \l__datatool_map_data_readonly_bool,
  allow-edits .bool_set_inverse:N = \l__datatool_map_data_readonly_bool,

```

```
}
```

\DTLmapdata

```
\DTLmapdata[<options>]{<loop>}
```

\DTLforeach has a lot of extra overhead. Version 3.0 provides \DTLmapdata, which is designed to be simpler but shouldn't be used in a tabular context.

```
\NewDocumentCommand \DTLmapdata
{ 0{} +m }
{
```

Initialise defaults:

```
\tl_set_eq:NN
  \dtldbname \l__datatool_default_dbname_tl
\bool_set_true:N \l__datatool_map_data_readonly_bool
\keys_set:nn { datatool/mapdata } { #1 }
\DTLifdbexists { \dtldbname }
{
  \__datatool_map_data_enable:
```

Get the contents of the database token register:

```
\tl_set:Nv \l__datatool_map_data_tl { dtldb@\dtldbname }
```

Save the loop action:

```
\tl_set:Nn \l__datatool_map_data_loop_body_tl { #2 }
\int_zero:N \dtlrownum
```

Recurse:

```
\exp_after:wN \__datatool_map_data:w
  \l__datatool_map_data_tl
  \db@row@elt@w
  \db@row@id@w \q_recursion_tail \db@row@id@end@
  \db@row@id@w \q_recursion_tail \db@row@id@end@
  \db@row@elt@end@
  \q_recursion_stop
\prg_break_point:Nn \__datatool_map_data_break: { }
```

Update database if not read-only.

```
\bool_if:NF \l__datatool_map_data_readonly_bool
{
```

Add any pending updates.

```
\__datatool_append_map_data_pending:
```

Append any remaining. The row indexes may be out if any rows have been removed, so iterate.

```
\int_step_inline:nnn
{ \dtlrownum + 1 } { \DTLrowcount { \dtldbname } }
{
  \exp_args:Nv \@dtlgetrow { dtldb@\dtldbname } { ##1 }
  \int_incr:N \l__datatool_row_idx_int
  \tl_put_right:Nx \l__datatool_map_data_pending_tl
```

```

    {
      \__datatool_row_markup:VV
      \__datatool_row_idx_int
      \dtlcurrentrow
    }
  }
}
Have any column types changed?
\tl_clear:N \__datatool_tmpa_tl
\prop_if_empty:NF
  \__datatool_map_data_col_type_prop
{
  \int_step_inline:nn
  { \__datatool_map_data_max_cols_int }
  {
Get the column metadata if it exists.
    \__datatool_get_col_data:vn
    { dtlkeys@ \dtldbname }
    { ##1 }
Has the metadata been updated for this column?
    \__datatool_map_data_get_col_type_prop:n { ##1 }
Ensure the data type is an integer.
    \tl_if_empty:NTF \__datatool_item_type_tl
    {
      \int_set_eq:NN
      \__datatool_item_type_int
      \c_datatool_unknown_int
    }
    {
      \int_set:Nn \__datatool_item_type_int
      { \__datatool_item_type_tl }
    }
}
Append markup for this column in the temporary token list.
\tl_put_right:Nx \__datatool_tmpa_tl
{
  \__datatool_column_markup:nVVV
  { ##1 }
  \__datatool_item_key_tl
  \__datatool_item_type_int
  \__datatool_item_head_tl
}
Any new columns will need to have the key to column mapping defined:
\tl_if_exist:cF
{
  dtl@ci@ \dtldbname
  @ \__datatool_item_key_tl
}

```

```

    {
      \bool_if:NTF \l__datatool_db_global_bool
      {
        \tl_gset:cn
        {
          dtl@ci@ \dtldbname
          @ \l__datatool_item_key_tl
        }
        { ##1 }
      }
      {
        \tl_set:cn
        {
          dtl@ci@ \dtldbname
          @ \l__datatool_item_key_tl
        }
        { ##1 }
      }
    }
  }
}

```

Update database:

```

\__datatool_dtldb_set:VV
\dtldbname
\l__datatool_map_data_pending_tl

```

Update the column metadata if it has changed.

```

\tl_if_empty:NF \l__datatool_tmpa_tl
{
  \__datatool_dtlkeys_set:VV
  \dtldbname
  \l__datatool_tmpa_tl
}
\bool_if:NTF \l__datatool_db_global_bool
{

```

Update the row count.

```

\int_gset_eq:cN { dtlrows@\dtldbname }
\l__datatool_row_idx_int

```

Update the column count.

```

\int_gset_eq:cN
{ dtlcols@\dtldbname }
\l__datatool_map_data_max_cols_int
}
{

```

Update the row count.

```

\int_set_eq:cN { dtlrows@\dtldbname }
\l__datatool_row_idx_int

```

Update the column count.

```
\int_set_eq:cN
{ dtlcols@\dtldbname }
\l_datatool_map_data_max_cols_int
}
```

Disable \DTLmaponly commands.

```
\__datatool_map_data_disable:
}
{
\PackageError { datatool }
{ database ~ '\dtldbname' ~ does ~ not ~ exist }
{ }
}
}

\cs_new:Nn \__datatool_map_data_break:
{ \prg_map_break:Nn \__datatool_map_data_break: { } }
```

\DTLmapdatabreak Break out of the \DTLmapdata loop. The starred form will discard edits.

```
\NewDocumentCommand \DTLmapdatabreak { s }
{
\IfBooleanT { #1 }
{
\bool_set_true:N \l_datatool_map_data_readonly_bool
}
\__datatool_map_data_break:
}
```

DTLenvmapdata (env.) Environment equivalent.

```
\NewDocumentEnvironment { DTLenvmapdata }
{ 0{} +b }
{ \DTLmapdata [ #1 ] { #2 } }
{ }

Recursive command for \DTLmapdata:
\cs_new:Npn \__datatool_map_data:w
\db@row@elt@w
\db@row@id@w #1 \db@row@id@end@
#2
\db@row@id@w #3 \db@row@id@end@
\db@row@elt@end@
{
\quark_if_recursion_tail_stop:n { #1 }
\int_set:Nn \dtlrownum { #1 }
\bool_if:NF \l__datatool_map_data_readonly_bool
{
\bool_set_true:N \l__datatool_map_data_update_pending_bool
}
}
```

```

\tl_set:Nn \l_datatool_map_data_row_tl { #2 }
\l_datatool_map_data_loop_body_tl
\bool_if:NF \l_datatool_map_data_readonly_bool
{
  \__datatool_append_map_data_pending:
}
\__datatool_map_data:w
}
Append current row to pending:
\cs_new:Nn \__datatool_append_map_data_pending:
{
  \bool_if:NT \l_datatool_map_data_update_pending_bool
  {
    \tl_if_empty:NF \l_datatool_map_data_row_tl
    {
      \int_incr:N \l_datatool_row_idx_int
      \tl_put_right:Nx \l_datatool_map_data_pending_tl
      {
        \__datatool_row_markup:VV
          \l_datatool_row_idx_int
          \l_datatool_map_data_row_tl
      }
    }
  }
  \bool_set_false:N \l_datatool_map_data_update_pending_bool
}
}
Command to enable commands that may only be used in \DTLmapdata.
\cs_new:Nn \__datatool_map_data_enable:
{
Enable \DTLmapget:
  \cs_set_eq:NN
    \__datatool_map_get:n
    \__datatool_map_get_op:n
Enable \DTLmapgetvalues:
  \cs_set_eq:NN
    \__datatool_map_get_values:n
    \__datatool_map_get_values_op:n
  \cs_set_eq:NN
    \__datatool_map_get_values_noerr:n
    \__datatool_map_get_values_noerr_op:n
Enable \DTLmaprow:
  \cs_set_eq:NN
    \__datatool_map_row:Nn
    \__datatool_map_row_op:Nn
Enable 'row aggregate' action:
  \cs_set_eq:cN

```

```

    { __datatool_action_row ~ aggregate: }
    \__datatool_action_row_aggregate_op:

```

Adjust settings according to read-only setting.

```

\bool_if:NTF \l__datatool_map_data_readonly_bool
{
  \RenewDocumentCommand \DTLrmrow { }
  {
    \__datatool_map_data_cs_noedit:N \DTLrmrow
  }
  \RenewDocumentCommand \DTLsetentry { m }
  {
    \__datatool_map_data_cs_noedit:N \DTLsetentry
  }
  \RenewDocumentCommand \DTLrmentry { m }
  {
    \__datatool_map_data_cs_noedit:N \DTLrmentry
  }
}
{

```

If not read-only, setup token registers to reconstruct database:

```

\tl_clear:N \l__datatool_map_data_pending_tl
\int_zero:N \l__datatool_row_idx_int
\prop_clear:N \l__datatool_map_data_col_type_prop
\int_set:Nn \l__datatool_map_data_max_cols_int
{ \DTLcolumncount { \dtldbname } }
\RenewDocumentCommand \DTLrmrow { }
{
  \__datatool_map_data_rm_row:
}
\RenewDocumentCommand \DTLsetentry { m }
{
  \__datatool_map_data_set_column:n { ##1 }
}
\RenewDocumentCommand \DTLrmentry { m }
{
  \__datatool_map_data_rm_column:n { ##1 }
}
}
}

```

Command to disable commands that may only be used in \DTLmapdata.

```

\cs_new:Nn \__datatool_map_data_disable:
{
  \cs_set_eq:NN
  \__datatool_map_get:n
  \__datatool_map_get_noop:n
  \cs_set_eq:NN
  \__datatool_map_get_values:n
  \__datatool_map_get_values_noop:n
}

```

```

\cs_set_eq:NN
  \__datatool_map_get_values_noerr:n
  \__datatool_map_get_values_noop:n
\cs_set_eq:NN
  \__datatool_map_row:Nn
  \__datatool_map_row_noop:Nn
\RenewDocumentCommand \DTLrmrow { }
{
  \__datatool_map_data_cs_noop:N \DTLrmrow
}
\RenewDocumentCommand \DTLrmentry { m }
{
  \__datatool_map_data_cs_noop:N \DTLrmentry
}
\RenewDocumentCommand \DTLsetentry { m }
{
  \__datatool_map_data_cs_noop:N \DTLsetentry
}
\tl_clear:N \l__datatool_map_data_tl
\tl_clear:N \l__datatool_map_data_loop_body_tl
\tl_clear:N \l__datatool_map_data_row_tl

```

Disable 'row aggregate' action:

```

\cs_set:cn { __datatool_action_row ~ aggregate: }
{
  \__datatool_action_noop:Nn
  \DTLmapdata
  { row ~ aggregate: }
}
}

```

Provide commands to edit data. Note that the database won't be updated until the loop has finished.

```

\cs_new:Nn \__datatool_map_data_cs_noop:N
{
  \PackageError { datatool }
  {
    \token_to_str:N #1 \c_space_tl ~ may ~ only ~ be ~ used ~
    in ~ the ~ loop ~ body ~ of ~ \token_to_str:N \DTLmapdata
  }
  { }
}

```

Read-only no-op:

```

\cs_new:Nn \__datatool_map_data_cs_noedit:N
{
  \PackageError { datatool }
  {
    \token_to_str:N #1 \c_space_tl ~ requires ~ read-only=false ~
    setting ~ in ~ \token_to_str:N \DTLmapdata
  }
}

```

```

    {
      Use ~ \token_to_str:N \DTLmapdata [ read-only=false ] { ... } ~
      or ~ \token_to_str:N \DTLmapdata [ allow-edits=true ] { ... }
    }
  }
}

```

Options for editing commands:

```

\int_new:N \l__datatool_map_data_edit_column_int
\tl_new:N \l__datatool_map_data_edit_key_tl
\tl_new:N \l__datatool_map_data_edit_value_tl
\keys_define:nn { datatool/mapdata/edit }
{
  value .tl_set:N = \l__datatool_map_data_edit_value_tl,
  expand-value .tl_set_x:N = \l__datatool_map_data_edit_value_tl,
  expand-once-value .code =
  {
    \tl_set:No \l__datatool_map_data_edit_value_tl { #1 }
  },
  column .code:n =
  {
    \int_compare:nNnTF { #1 } > { 0 }
    {
      \int_set:Nn \l__datatool_map_data_edit_column_int { #1 }
    }
    {
      \PackageError { datatool }
      {
        Column ~ index ~ must ~ be ~ greater ~ than ~ 0
      }
      {}
    }
  },
  key .str_set_x:N = \l__datatool_map_data_edit_key_tl,
}

```

Initialise edit options:

```

\cs_new:Nn \__datatool_if_init_mapdata_edit_options:NnT
{
  \int_zero:N \l__datatool_map_data_edit_column_int
  \tl_clear:N \l__datatool_map_data_edit_key_tl
  \tl_set:Nn \l__datatool_map_data_edit_value_tl { \c_novalue_tl }
  \keys_set:nn { datatool/mapdata/edit } { #2 }
  \int_if_zero:nTF \l__datatool_map_data_edit_column_int
  {
    \tl_if_empty:NTF \l__datatool_map_data_edit_key_tl
    {
      \PackageError { datatool }
      {
        Missing ~ column ~ identifier ~ in ~ \token_to_str:N #1
      }
      {}
    }
  }
}

```


\DTLsetentry Set the value in the given column.

```

\NewDocumentCommand \DTLsetentry { m }
{
  \__datatool_map_data_cs_noop:N \DTLsetentry
}
\cs_new:Nn \__datatool_map_data_set_column:n
{
  \__datatool_if_init_mapdata_edit_options:NnT \DTLsetentry { #1 }
  {
    \exp_args:No
    \tl_if_novalue:nTF { \l__datatool_map_data_edit_value_tl }
    {
      \PackageError { datatool }
      {
        Missing ~ value ~ in ~ \token_to_str:N \DTLsetentry
      }
      {
        Use ~ value={ } ~ to ~ set ~ an ~ empty ~ value ~
        or ~ use ~ \token_to_str:N \DTLrmentry \c_space_tl ~ to ~
        remove ~ a ~ column
      }
    }
  }
}

```

Save the value in the token register \@dtl@toks and in the token list variable \l__datatool_item_value_tl according to new-value-expand, trim and store datum settings.

```

\__datatool_process_new_value:V
\l__datatool_map_data_edit_value_tl

```

Does the current row already have this column set?

```

\exp_args:NNx \tl_if_in:NnTF
  \l__datatool_map_data_row_tl
  {
    \exp_not:N \db@col@id@w
    \int_use:N \l__datatool_map_data_edit_column_int
    \exp_not:N \db@col@id@end@
  }
}

```

Replace existing entry.

```

\exp_args:NVV \dtlsplitrow
  \l__datatool_map_data_row_tl
  \l__datatool_map_data_edit_column_int
  { \l__datatool_map_data_edit_before_tl }
  { \l__datatool_map_data_edit_after_tl }
\tl_set_eq:NN
  \l__datatool_map_data_row_tl
  \l__datatool_map_data_edit_before_tl
\tl_put_right:Nx
  \l__datatool_map_data_row_tl

```

```

    {
      \__datatool_row_element_markup:VV
      \l_datatool_map_data_edit_column_int
      \l_datatool_item_value_tl
    }
  \tl_put_right:NV
  \l_datatool_map_data_row_tl
  \l_datatool_map_data_edit_after_tl
}
{

```

Append new entry.

```

  \tl_put_right:Nx
  \l_datatool_map_data_row_tl
  {
    \__datatool_row_element_markup:VV
    \l_datatool_map_data_edit_column_int
    \l_datatool_item_value_tl
  }
  \int_compare:nNnT
  { \l_datatool_map_data_edit_column_int }
  >
  { \l_datatool_map_data_max_cols_int }
  {
    \int_set_eq:NN
    \l_datatool_map_data_max_cols_int
    \l_datatool_map_data_edit_column_int
  }
}

```

Does the metadata for this column need updating?

```

\tl_if_empty:NTF \l_datatool_map_data_edit_key_tl
{
  \tl_clear:N \l_datatool_item_key_tl
}
{
  \tl_set_eq:NN
  \l_datatool_item_key_tl
  \l_datatool_map_data_edit_key_tl
}
\int_set_eq:NN \l_datatool_item_type_int \@dtl@datatype
\tl_clear:N \l_datatool_item_head_tl

```

Has this column already been changed in a previous row?

```

\__datatool_map_data_get_col_type_prop:V
\l_datatool_map_data_edit_column_int

```

Update property.

```

\__datatool_map_data_put_col_type_prop:VVV
\l_datatool_map_data_edit_column_int
\l_datatool_item_type_tl

```

```

        \l__datatool_item_key_tl
    }
}
}

```

Add column type property. Syntax: `{<col-index>}{<col-type>}{<col-key>}` The `<col-key>` may be empty to denote no change or use the default.

```

\cs_new:Nn \__datatool_map_data_put_col_type_prop:nnn
{
  \prop_put:Nnn \l__datatool_map_data_col_type_prop
  { #1 } { { #2 } { #3 } }
}
\cs_generate_variant:Nn
  \__datatool_map_data_put_col_type_prop:nnn
  { VVV, Vxx, xxx }

```

Get the column type property. NB get the current metadata first which should set

`\l__datatool_item_type_int`, `\l__datatool_item_key_tl` and `\l__datatool_item_head_tl`.

```

\cs_new:Nn \__datatool_map_data_get_col_type_prop:n
{
  \tl_clear:N \l__datatool_item_type_tl
  \prop_get:NnNT
    \l__datatool_map_data_col_type_prop
    { #1 }
    \l__datatool_tmpb_tl
  {
    \tl_set:Nx \l__datatool_item_type_tl
      { \exp_after:wN \use_i:nn \l__datatool_tmpb_tl }
    \tl_set:Nx \l__datatool_tmpb_tl
      { \exp_after:wN \use_ii:nn \l__datatool_tmpb_tl }
    \tl_if_empty:NF \l__datatool_tmpb_tl
    {
      \tl_set_eq:NN \l__datatool_item_key_tl \l__datatool_tmpb_tl
    }
  }
}
\exp_args:No \quark_if_no_value:nT { \l__datatool_item_key_tl }
{
  \tl_set:Nx \l__datatool_item_key_tl { \dtldefaultkey #1 }
}
\exp_args:No \quark_if_no_value:nT { \l__datatool_item_head_tl }
{
  \tl_set_eq:NN \l__datatool_item_head_tl \l__datatool_item_key_tl
}

```

Does the new type override the original type?

```

\tl_if_empty:NTF \l__datatool_item_type_tl
{

```

New type unknown so retain original.

```

  \tl_set:Nx \l__datatool_item_type_tl
  { \int_use:N \l__datatool_item_type_int }

```

```

}
{
  \int_compare:nNt
  { \l__datatool_item_type_tl } > { \c_datatool_string_int }
  {

```

New type not a string, so must be numerical. In which case the higher type dominates.

```

  \int_compare:nNt
  { \l__datatool_item_type_tl } < { \l__datatool_item_type_int }
  {
    \tl_set:Nx \l__datatool_item_type_tl
    { \int_use:N \l__datatool_item_type_int }
  }
}
}
}
\cs_generate_variant:Nn \__datatool_map_data_get_col_type_prop:n
{ V, x }

```

`\DTLrmentry` Removes the given column.

```

\NewDocumentCommand \DTLrmentry { m }
{
  \__datatool_map_data_cs_noop:N \DTLrmentry
}
\cs_new:Nn \__datatool_map_data_rm_column:n
{
  \int_zero:N \l__datatool_map_data_edit_column_int
  \keys_set:nn { datatool/mapdata/edit } { #1 }
  \int_if_zero:nTF \l__datatool_map_data_edit_column_int
  {
    \PackageError { datatool }
    { Missing ~ column ~ in ~ \token_to_str:N \DTLrmentry}
    { }
  }
}

```

Does the current row already have this column set?

```

\exp_args:NNx \tl_if_in:NnT
  \l__datatool_map_data_row_tl
  {
    \exp_not:N \db@col@id@w
    \int_use:N \l__datatool_map_data_edit_column_int
    \exp_not:N \db@col@id@end@
  }
}

```

Remove existing entry.

```

\exp_args:NVV \dtlsplitrow
  \l__datatool_map_data_row_tl
  \l__datatool_map_data_edit_column_int
  { \l__datatool_map_data_edit_before_tl }

```

```

        { \l__datatool_map_data_edit_after_tl }
\l_set_eq:NN
  \l__datatool_map_data_row_tl
  \l__datatool_map_data_edit_before_tl
\l_put_right:NV
  \l__datatool_map_data_row_tl
  \l__datatool_map_data_edit_after_tl
    }
  }
}

```

`\DTLrmrow` Remove the current row.

```

\NewDocumentCommand \DTLrmrow { }
{
  \__datatool_map_data_cs_noop:N \DTLrmrow
}
\cs_new:Nn \__datatool_map_data_rm_row:
{
  \tl_clear:N \l__datatool_map_data_row_tl
}

```

`\DTLmaprow{<cs>}{<body>}`

`\DTLmaprow`

Maps over the columns in the current row.

```

\NewDocumentCommand \DTLmaprow { m m }
{
  \__datatool_map_row:Nn #1 { #2 }
}
\cs_new:Nn \__datatool_map_row_noop:Nn
{
  \__datatool_map_data_cs_noop:N \DTLmaprow
}
\cs_set_eq:NN \__datatool_map_row:Nn \__datatool_map_row_noop:Nn

```

Map over each column in the current row:

```

\cs_new:Nn \__datatool_map_row_op:Nn
{
  \cs_set:Nn \__datatool_map_row_loop_body:n
  {
    \tl_set:Nn #1 { ##1 }
    #2
  }
}
\exp_after:wN \__datatool_map_row:w
  \l__datatool_map_data_row_tl
  \db@col@id@w \q_recursion_tail \db@col@id@end@
  \db@col@elt@w \db@col@elt@end@
  \db@col@id@w \q_recursion_tail \db@col@id@end@

```

```

    \q_recursion_stop
    \prg_break_point:Nn \__datatool_map_row_break: { }
  }

```

Break command.

```

\cs_new:Nn \__datatool_map_row_break:
  { \prg_map_break:Nn \__datatool_map_row_break: { } }

```

\DTLmaprowbreak

```

\newcommand{\DTLmaprowbreak}{ \__datatool_map_row_break: }

```

Macro within loop body:

```

\cs_new:Nn \__datatool_map_row_loop_body:n { }

```

Recursive macro:

```

\cs_new:Npn \__datatool_map_row:w
  \db@col@id@w #1 \db@col@id@end@
  \db@col@elt@w #2 \db@col@elt@end@
  \db@col@id@w #3 \db@col@id@end@
  {
    \quark_if_recursion_tail_stop:n { #1 }
    \int_set:Nn \dtlcolumnnum { #1 }
    \__datatool_map_row_loop_body:n { #2 }
    \__datatool_map_row:w
  }

```

```

\DTLmapget{<key=value options>}

```

\DTLmapget

Gets the value of the given key in the current row.

```

\NewDocumentCommand \DTLmapget { m }
{
  \__datatool_map_get:n { #1 }
}

```

The no-op command:

```

\cs_new:Nn \__datatool_map_get_noop:n
  {
    \PackageError { datatool }
    {
      \token_to_str:N \DTLmapget \c_space_tl ~ is ~ only ~
      available ~ within ~ \token_to_str:N \DTLmapdata
    }
    { }
  }
\cs_set_eq:NN
  \__datatool_map_get:n \__datatool_map_get_noop:n
\tl_new:N \l__datatool_map_get_return_tl

```

```

Define options for \DTLmapget:
\keys_define:nn { datatool/mapdata }
{
  key .code:n =
  {
    \cs_set:Nn
      \__datatool_map_get_action:
    {
      \exp_args:Nx
        \__datatool_map_get_from_key:n { #1 }
    }
  },
  key .value_required:n = true,
  column .code:n =
  {
    \cs_set:Nn
      \__datatool_map_get_action:
    {
      \exp_args:Nx
        \__datatool_map_get_from_idx:n { #1 }
    }
  },
  column .value_required:n = true,
  return .code:n =
  {
    \tl_if_empty:nTF { #1 }
    {
      \cs_set:Nn \__datatool_map_get_action_result:
        { \l__datatool_map_get_return_tl }
    }
    {
      \cs_set:Nn \__datatool_map_get_action_result:
        { \tl_set_eq:NN #1 \l__datatool_map_get_return_tl }
    }
  },
  return .default:n = { },
}

```

The actual command:

```

\cs_new:Nn \__datatool_map_get_op:n
{
  \cs_set_eq:NN
    \__datatool_map_get_action:
    \__datatool_map_get_op_missing:
  \cs_set:Nn \__datatool_map_get_action_result:
    { \l__datatool_map_get_return_tl }
}

```

Parse settings.

```

\keys_set:nn { datatool/mapdata } { #1 }

```

Fetch the required information.

```

    \__datatool_map_get_action:
Save or do the value.
    \__datatool_map_get_action_result:
}
Missing information
\cs_new:Nn \__datatool_map_get_op_missing:
{
    \PackageError { datatool }
    {
        Missing ~ `key' ~ or ~ `column' ~ option ~ in ~ \DTLmapget
    }
    {}
    \tl_set_eq:NN \l__datatool_map_get_return_tl \dtlnovalue
}
    Get value from current row given column index:
\cs_new:Nn \__datatool_map_get_from_idx:n
{
    \tl_if_empty:NTF \l__datatool_map_data_row_tl
    {
        \tl_set_eq:NN \l__datatool_map_get_return_tl \dtlnovalue
    }
    {
        \exp_args:NNno
        \dtl@getentryfromrow
        \l__datatool_map_get_return_tl
        { #1 }
        \l__datatool_map_data_row_tl
    }
}
Was a value found?
    \tl_if_eq:NNT \l__datatool_map_get_return_tl \dtlnovalue
    {
        \__datatool_get_col_type:vn { dtlkeys@ \dtldbname } { #1 }
        \int_case:nnF { \l__datatool_item_type_int }
        {
            { \c_datatool_string_int }
            { \tl_set_eq:NN \l__datatool_map_get_return_tl \DTLstringnull }
            { \c_datatool_unknown_int } { }
        }
        {
            \tl_set_eq:NN \l__datatool_map_get_return_tl \DTLnumbernull
        }
    }
}
}
    Get value from current row given column key:
\cs_new:Nn \__datatool_map_get_from_key:n
{
    \cs_if_exist:cTF { dtl@ci@ \dtldbname @ #1 }

```

```

    {
      \exp_args:Nx
      \__datatool_map_get_from_idx:n
      { \use:c { dtl@ci@ \dtldbname @ #1 } }
    }
    {
      \tl_set_eq:NN \l__datatool_map_get_return_tl \dtlnovalue
    }
  }
}

```

`\DTLmapgetvalues` Gets multiple values using the same assignment syntax as used by `\DTLforeach`

```

\NewDocumentCommand \DTLmapgetvalues { s m }
{
  \IfBooleanTF { #1 }
  {
    \__datatool_map_get_values_noerr:n { #2 }
  }
  {
    \__datatool_map_get_values:n { #2 }
  }
}

```

The no-op command:

```

\cs_new:Nn \__datatool_map_get_values_noop:n
{
  \PackageError { datatool }
  {
    \token_to_str:N \DTLmapgetvalues \c_space_tl ~ is ~ only ~
    available ~ within ~ \token_to_str:N \DTLmapdata
  }
  { }
}
\cs_set_eq:NN
\__datatool_map_get_values:n \__datatool_map_get_values_noop:n

```

Gets values from the current row:

```

\tl_new:N \l__datatool_assign_tl
\cs_new:Nn \__datatool_map_get_values_op:n
{
  \keyval_parse:nnn
  { \__datatool_cskey_missing_val:n }
  { \__datatool_map_assign_cskey:nn }
  { #1 }
}

```

As above but no error if key doesn't exist.

```

\cs_new:Nn \__datatool_map_get_values_noerr_op:n
{
  \keyval_parse:nnn
  { \__datatool_cskey_missing_val:n }
}

```

```

        { \__datatool_map_assign_cskey_noerr:nn }
        { #1 }
    }
    \__datatool_map_assign_cskey:nn{<cs>}{<key>}
\cs_new:Nn \__datatool_map_assign_cskey:nn
{
    \tl_if_exist:cTF { dtl@ci@\dtldbname @ #2 }
    {
        \int_set:Nn \l__datatool_col_idx_int
        { \use:c { dtl@ci@\dtldbname @ #2 } }
        \exp_args:NV
        \__datatool_map_get_from_idx:n
        \l__datatool_col_idx_int
        \tl_set_eq:NN #1 \l__datatool_map_get_return_tl
    }
    {
        \PackageError { datatool }
        {
            Unknown ~ column ~ key ~ `#2' ~ for ~ database ~ \dtldbname
        }
        {
            Check ~ the ~ spelling ~ of ~ the ~ column ~ label ~
            in ~ your ~ assignment ~ \tl_to_str:n { #1 } = #2
        }
        \tl_set_eq:NN #1 \dtlnovalue
    }
}
}

```

As above but no error if column key not defined.

```

\cs_new:Nn \__datatool_map_assign_cskey_noerr:nn
{
    \tl_if_exist:cTF { dtl@ci@\dtldbname @ #2 }
    {
        \int_set:Nn \l__datatool_col_idx_int
        { \use:c { dtl@ci@\dtldbname @ #2 } }
        \exp_args:NV
        \__datatool_map_get_from_idx:n
        \l__datatool_col_idx_int
        \tl_set_eq:NN #1 \l__datatool_map_get_return_tl
    }
    {
        \tl_set_eq:NN #1 \dtlnovalue
    }
}
}
\ExplSyntaxOff

```

```
\@dtlforeachrow(<idx cs>,<row cs>)\in{<db>}
\do{<body>}
```

\@dtlforeachrow

Iterates through each row in database. Assigns the current row index to *<idx cs>* and the row specs to *<row cs>*

```
\long\def\@dtlforeachrow(#1,#2)\in#3\do#4{%
  \edef\dtl@tmp{\expandafter\the\csname dtldb@#3\endcsname}%
  \expandafter\@dtl@foreachrow\dtl@tmp
  \db@row@elt@w%
  \db@row@id@w \@nil\db@row@id@end@%
  \db@row@id@w \@nil\db@row@id@end@%
  \db@row@elt@end@%
  \@@{#1}{#2}{#4}\q@nil
}
```

\@dtl@foreachrow

```
\long\def\@dtl@foreachrow\db@row@elt@w%
\db@row@id@w #1\db@row@id@end@%
#2\db@row@id@w #3\db@row@id@end@%
\db@row@elt@end@#4\@@#5#6#7\q@nil{%
```

Define control sequence given by #5

```
\gdef#5{#1}%
```

Hide the loop body in a macro

```
\gdef\@dtl@loopbody{#7}%
```

Increment level counter to allow for nested loops

```
\global\advance\@dtl@foreach@level by 1\relax
```

Check if we have reached the end of the loop

```
\ifx#5\@nnil
  \expandafter\global\expandafter
  \let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
  =\@dtl@foreachnoop
```

```
\else
```

```
\gdef#6{#2}%
```

Set up the break function: Make a copy of current break function

```
\expandafter\let
\csname @dtl@break@\the\@dtl@foreach@level\endcsname
\dtlbreak
```

Setup break function for this level

```
\gdef\dtlbreak{\expandafter\global\expandafter
\let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
=\@dtl@foreachnoop}%
```

Initialise

```
\expandafter\global\expandafter
\let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
=\@dtl@foreachrow
```

```

Do body of loop
  \@dtl@loopbody
Restore break function
  \expandafter\let\expandafter\dtlbreak
  \csname @dtl@break@the\@dtl@foreach@level\endcsname
\fi
Set up what to do next.
  \expandafter\let\expandafter\@dtl@foreachnext
  \csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
Decrement level counter.
  \global\advance\@dtl@foreach@level by -1\relax
Repeat loop if necessary.
  \@dtl@foreachnext#4\@@{#5}{#6}{#7}\q@nil
}

```

\@dtl@foreachnoop

```
\long\def\@dtl@foreachnoop#1\@@#2\q@nil{}
```

\ExplSyntaxOn

Version 3.0: This is a newer alternative to `\dtlforeachkey` implemented in \LaTeX 3. Note that the unknown type will be -1 not empty so that it can be compared with the integer constants provided by `datatool-base`. To make it consistent with `\dtlforeachkey` the handler function has four arguments: $\{\langle key \rangle\}\{\langle col\ idx \rangle\}\{\langle type \rangle\}\{\langle header \rangle\}$ In line function:

```

\cs_new:Nn \datatool_map_keys_inline:nn
{
  \cs_set:Nn \__datatool_map_keys_fn:nnnn { #2 }
  \tl_set:Nv \l__datatool_keydata_tl { dtlkeys@#1 }
  \tl_if_empty:NF \l__datatool_keydata_tl
  {
    \exp_after:wN \__datatool_map_keys:w
    \l__datatool_keydata_tl
    \db@plist@elt@w
    \db@col@id@w \q_recursion_tail \db@col@id@end@
    \db@key@id@w \db@key@id@end@
    \db@type@id@w \db@type@id@end@
    \db@header@id@w \db@header@id@end@
    \db@col@id@w \q_recursion_tail \db@col@id@end@
    \db@plist@elt@end@
    \q_recursion_stop
  }
}

```

Function handler:

```

\cs_new:Nn \datatool_map_keys_function:nN
{

```

```

\cs_set_eq:NN \__datatool_map_keys_fn:nmmm #2
\tl_set:Nv \l__datatool_keydata_tl { dtlkeys@#1 }
\tl_if_empty:NF \l__datatool_keydata_tl
{
  \exp_after:wN \__datatool_map_keys:w
  \l__datatool_keydata_tl
  \db@plist@elt@w
  \db@col@id@w \q_recursion_tail \db@col@id@end@
  \db@key@id@w \db@key@id@end@
  \db@type@id@w \db@type@id@end@
  \db@header@id@w \db@header@id@end@
  \db@col@id@w \q_recursion_tail \db@col@id@end@
  \db@plist@elt@end@
  \q_recursion_stop
}
}

```

Internal recursive command:

```

\cs_new:Npn \__datatool_map_keys:w
  \db@plist@elt@w
  \db@col@id@w #1 \db@col@id@end@
  \db@key@id@w #2 \db@key@id@end@
  \db@type@id@w #3 \db@type@id@end@
  \db@header@id@w #4 \db@header@id@end@
  \db@col@id@w #5 \db@col@id@end@
  \db@plist@elt@end@
{
  \quark_if_recursion_tail_stop:n { #1 }
  \tl_if_empty:nTF { #3 }
  {
    \__datatool_map_keys_fn:nmmm { #2 } { #1 } { \c_datatool_unknown_int } { #4 }
  }
  {
    \__datatool_map_keys_fn:nmmm { #2 } { #1 } { #3 } { #4 }
  }
  \__datatool_map_keys:w
}
\ExplSyntaxOff

```

```

\dtlforeachkey(<key cs>,<col cs>,<type cs>,<header cs>)
\in{<db>}\do{<body>}

```

\dtlforeachkey

Iterates through all the keys in database *<db>*. In each iteration, *<key cs>* stores the key, *<col cs>* stores the column index, *<type cs>* stores the data type and *<header cs>* stores the header.

```

\long\def\dtlforeachkey(#1,#2,#3,#4)\in#5\do#6{%
  \gdef\@dtl@loopbody{#6}%
  \edef\@dtl@keys{\expandafter\the\csname dtlkeys@#5\endcsname}%
}

```

```

\expandafter\@dtl@foreachkey\@dtl@keys
  \db@plist@elt@w%
  \db@col@id@w -1\db@col@id@end@%
  \db@key@id@w \db@key@id@end@%
  \db@type@id@w \db@type@id@end@%
  \db@header@id@w \db@header@id@end@%
  \db@col@id@w -1\db@col@id@end@%
  \db@plist@elt@end@%
  \@@{\@dtl@updatefkcs{#1}{#2}{#3}{#4}}\q@nil
}

```

\@dtl@updatefkcs

```

\newcommand*{\@dtl@updatefkcs}[8]{%
  \gdef#1{#5}%
  \gdef#2{#6}%
  \gdef#3{#7}%
  \gdef#4{#8}%
}

```

\@dtl@foreachkey Sets everything globally in case it occurs in a tabular environment Loop body needs to be stored in \@dtl@loopbody. #7 indicates an update macro.

```

\long\def\@dtl@foreachkey\db@plist@elt@w%
  \db@col@id@w #1\db@col@id@end@%
  \db@key@id@w #2\db@key@id@end@%
  \db@type@id@w #3\db@type@id@end@%
  \db@header@id@w #4\db@header@id@end@%
  \db@col@id@w #5\db@col@id@end@%
  \db@plist@elt@end@#6\@@#7\q@nil{%
  \ifnum#1=-1\relax

```

Terminate loop

```

  \let\@dtl@foreachnext\@dtl@foreachnoop
  \else

```

Set up loop variables

```

  #7{#2}{#1}{#3}{#4}%

```

Increment level counter to allow for nested loops

```

  \global\advance\@dtl@foreach@level by 1\relax

```

Set up the break function

```

\expandafter\let
  \csname @dtl@break@the\@dtl@foreach@level\endcsname
  \dtlbreak
\gdef\dtlbreak{\expandafter\global\expandafter
  \let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
  =\@dtl@foreachnoop}%

```

Initialise

```

\expandafter\global\expandafter
  \let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
  =\@dtl@foreachkey

```

```

Do body of loop
    \@dtl@loopbody
Set up what to do next
    \expandafter\let\expandafter\@dtl@foreachnext
    \csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
Restore break function
    \expandafter\let\expandafter\dtlbreak
    \csname @dtl@break@\the\@dtl@foreach@level\endcsname
Decrement level counter
    \global\advance\@dtl@foreach@level by -1\relax
    \fi
Recurse if necessary
    \@dtl@foreachnext#6\@@{#7}\q@nil
}
\ExplSyntaxOn

```

```
\dtlforcolumn{<cs>}{<db>}{<key>}{<body>}
```

\dtlforcolumn

Iterates through column given by *<key>* in database *<db>*. *<cs>* is assign to the element of the column in the current iteration. Starred version doesn't check if data base exists

```

\NewDocumentCommand \dtlforcolumn { s }
{
  \IfBooleanTF { #1 } { \@sdtlforcolumn } { \@dtlforcolumn }
}

```

\@dtlforcolumn

```

\newcommand{\@dtlforcolumn}[4]{
Check if data base exists
  \DTLifdbexists { #2 }
  {
    \@DTLifhaskey { #2 } { #3 }
    {
      \@sdtlforcolumn { #1 } { #2 } { #3 } { #4 }
    }
  }
key not in data base
  {
    \PackageError { datatool }
    {
      Database ~ `#2' ~ doesn't ~ contain ~ key ~ `#3'
    }
    { }
  }
}
}

```

```

    {
      \PackageError { datatool }
        { Database ~ `#2' ~ doesn't ~ exist}
        { }
    }
  }
}

\cs_new:Nn \__datatool_for_column:Nnnn
{
  \dtl@forcolumn #1 { #2 } { #3 } { #4 }
}

\cs_generate_variant:Nn \__datatool_for_column:Nnnn
{ Nven }

```

\@sdtlforcolumn

```

\newcommand{\@sdtlforcolumn}[4]{%
  \__datatool_for_column:Nven #1 { dtldb@#2 }
  { \dtlcolumnindex { #2 } { #3 } } { #4 }
}

```

\dtlforcolumnidx

`\dtlforcolumnidx{<cs>}{<db>}{<col num>}{<body>}`

Iterates through the column with index *<col num>* in database *<db>*. Starred version doesn't check if database exists.

```

\NewDocumentCommand \dtlforcolumnidx { s }
{
  \IfBooleanTF { #1 } { \@sdtlforcolumnidx } { \@dtlforcolumnidx }
}

```

\@sdtlforcolumnidx

```

\newcommand{\@sdtlforcolumnidx}[4]{%
  \__datatool_for_column:Nven #1 { dtldb@#2 }
  { \int_eval:n { #3 } } { #4 }
}

```

\ExplSyntaxOff

\@dtlforcolumnidx

```

\newcommand{\@dtlforcolumnidx}[4]{%
  \DTLifdbexists{#2}%
  {%
    \expandafter\ifnum\csname dtlcols@#2\endcsname<#3\relax
    \PackageError{datatool}{Column index \number#3\space out of
      bounds for database `#2'}{Database `#2' only has
      \expandafter\number\csname dtlcols@#2\endcsname\space
      columns}%
    \else
      \ifnum#3<1\relax

```

```

        \PackageError{datatool}{Column index \number#3\space out of
        bounds for database `#2'}{Indices start from 1}%
    \else
        \@sdtlforcolumnidx{#1}{#2}{#3}{#4}%
    \fi
\fi
}%
data base doesn't exist
{%
\PackageError{datatool}{Database `#2' doesn't exist}{}%
}%
}

```

```
\dtl@forcolumn{<cs>}{<db specs>}{<col num>}{<body>}
```

\dtl@forcolumn

```

<col num> needs to be fully expanded
\newcommand{\dtl@forcolumn}[4]{%
make a copy of break function
\let\@dtl@oldbreak\dtlbreak
set up break function
\def\dtlbreak{\let\@dtl@forcolnext=\@dtl@forcolnoop}%
define loop macro for this column
\def\@dtl@forcolumn##1% before stuff
\db@col@id@w #3\db@col@id@end@% column index
\db@col@elt@w ##2\db@col@elt@end@% entry
\db@col@id@w #3\db@col@id@end@% column index
##3% after stuff
\q@nil{%
\def#1{##2}% assign value to <cs>
check if end of loop
\ifx#1\@nnil
\let\@dtl@forcolnext=\@dtl@forcolnoop
\else
do body of loop
#4%
\let\@dtl@forcolnext=\@dtl@forcolumn
\fi
repeat if necessary
\@dtl@forcolnext##3\q@nil
}%
do loop
\@dtl@forcolumn#2%
\db@col@id@w #3\db@col@id@end@%

```

```

\begin@col@elt@w \end@col@elt@end@%
\begin@col@id@w #3\end@col@id@end@q@nil
restore break function
\let\dtlbreak\@dtl@oldbreak
}

```

`\@dtl@forcolnoop`

```
\def\@dtl@forcolnoop#1\q@nil{}
```

`\dtlforeachlevel` `\DTLforeach` can only be nested up to three levels. `\dtlforeachlevel` keeps track of the current level.

```
\newcount\dtlforeachlevel
```

The counter `DTLrow` $\langle n \rangle$ keeps track of each row of data during the $\langle n \rangle$ nested `\DTLforeach`. It is only incremented in the conditions (given by the optional argument) are met. In order to work well with `hyperref`, a parent counter is also defined.

```

\newcounter{DTLrow}
\newcounter{DTLrowi}
\newcounter{DTLrowii}
\newcounter{DTLrowiii}

```

Keep `hyperref` happy

```

\def\theHDTLrow{\arabic{DTLrow}}
\def\theHDTLrowi{\theHDTLrow.\arabic{DTLrowi}}
\def\theHDTLrowii{\theHDTLrowi.\arabic{DTLrowii}}
\def\theHDTLrowiii{\theHDTLrowii.\arabic{DTLrowiii}}

```

Allow use of these counters outside of `\DTLforeach`.

`\DTLrowreset` Reset counter for the next level.

```

\NewDocumentCommand\DTLrowreset{}{%
\ifnum\dtlforeachlevel > 2
\PackageError{datatool}{DTLrow counter level too deep}%
{The current counter level is \number\dtlforeachlevel}%
\else
\refstepcounter{DTLrow}%
\setcounter{DTLrow\romannumeral\numexpr\dtlforeachlevel+\@ne}{0}%
\fi
}

```

`\DTLrowincr` Increment counter for the next level.

```

\NewDocumentCommand\DTLrowincr{}{%
\ifnum\dtlforeachlevel > 2
\PackageError{datatool}{DTLrow counter level too deep}%
{The current counter level is \number\dtlforeachlevel}%
\else
\refstepcounter{DTLrow\romannumeral\numexpr\dtlforeachlevel+\@ne}%
\fi
}

```

`\DTLtherow` Show the counter for the next level.

```
\NewDocumentCommand\DTLtherow{}{%
  \ifnum\dtlforeachlevel > 2
    \PackageError{datatool}{DTLrow counter level too deep}%
    {The current counter level is \number\dtlforeachlevel}%
  \else
    \csuse{theDTLrow\romannumeral\numexpr\dtlforeachlevel+\@ne}%
  \fi
}

\newcount\dtl@rowi
\newcount\dtl@rowii
\newcount\dtl@rowiii

\ExplSyntaxOn
```

Keep track of filtered rows to help `\DTLiflastrow`:

```
\int_new:N \g__filtered_row_i_int
\int_new:N \g__filtered_row_ii_int
\int_new:N \g__filtered_row_iii_int

\ExplSyntaxOff

\newtoks\@dtl@curi
\newtoks\@dtl@previ
\newtoks\@dtl@nexti
\newtoks\@dtl@curii
\newtoks\@dtl@previi
\newtoks\@dtl@nextii
\newtoks\@dtl@curiii
\newtoks\@dtl@previii
\newtoks\@dtl@nextiii
```

`\DTLsaveastrowcount{<cmd>}`

`\DTLsaverowcount`

Stores the maximum row count for the last `\DTLforeach`.

```
\newcommand*{\DTLsaveastrowcount}[1]{%
\ifnum\dtlforeachlevel>2\relax
  \def#1{0}%
\else
  \ifnum\dtlforeachlevel<0\relax
    \def#1{0}%
  \else
    \@dtl@tmpcount=\dtlforeachlevel
    \advance\@dtl@tmpcount by 1\relax
    \edef#1{\expandafter\number
      \csname c@DTLrow\romannumeral\@dtl@tmpcount\endcsname}%
  \fi
\fi}
```

DTLenvforeach (*env.*) Environment form of `\DTLforeach` (contents are gathered, so verbatim can't be used).

```
\NewDocumentEnvironment{DTLenvforeach}{0{\boolean{true}}mm+b}
{%
  \@DTLforeach[#1]{#2}{#3}{#4}%
}
{}
```

DTLenvforeach* (*env.*) Environment form of `\DTLforeach*` (contents are gathered, so verbatim can't be used).

```
\NewDocumentEnvironment{DTLenvforeach*}{0{\boolean{true}}mm+b}
{%
  \@sDTLforeach[#1]{#2}{#3}{#4}%
}
{}
```

NB `\DTLmapdata` is better but `\DTLforeach` retained for backward-compatibility and for use with tabular environments (although there are still situations where it will cause alignment issues).

`\DTLforeach`

```
\DTLforeach[<conditions>]{<db name>}{<values>}{<text>}
```

For each row of data in the database given by *<db name>*, do *<text>*, if the specified conditions are satisfied. The argument *<values>* is a comma separated list of *<cmd>*=*<key>* pairs. At the start of each row, each of the commands in this list are set to the value of the entry with the corresponding key *<key>*. (`\gdef` is used to ensure `\DTLforeach` works in a tabular environment.) The database may be edited in the unstarred version, in the starred version the database is read only.

```
\newrobustcmd*{\DTLforeach}{\@ifstar\@sDTLforeach\@DTLforeach}
```

```
\ExplSyntaxOn
```

Version 3.0: provided common command for starred and unstarred code. Syntax: `{<conditions>}{<db name>}{<values>}{<text>}{<ro>}` The *<ro>* argument should be a boolean indicating if read-only.

```
\cs_new:Nn \__datatool_for_each:nnnnN
{
```

Check database exists

```
\DTLifdbexists { #2 }
{
```

Keep hyperref happy

```
\refstepcounter {DTLrow}
```

Store database name.

```
\tl_gset:Nx \@dtl@dbname { #2 }
```

Increment level and check not exceeded 3

```
\int_gincr:N \dtlforeachlevel
\int_compare:nNnTF
  { \dtlforeachlevel } > { 3 }
{
  \PackageError{datatool}
  {
    \token_to_str:N \DTLforeach \c_space_tl ~ nested ~
    too ~ deeply
  }
  {
    Only ~ 3 ~ levels ~ are ~ allowed
  }
}
{
  \@DTLifdbempty { #2 }
}
```

Do nothing if database is empty

```
{ }
{
```

Set level dependent information (needs to be global to ensure it works in the tabular environment). Row counter:

```
\int_gzero:c
{ c@DTLrow\romannumeral\dtlforeachlevel }
```

Keep track of the number of filtered rows:

```
\int_gzero:c
{
  g__filtered_row_
  \romannumeral \dtlforeachlevel
  _int
}
```

Store previous value of \DTLiffirstrow

```
\cs_gset_eq:cN
{ @dtl@iffirstrow\the\dtlforeachlevel }
\DTLiffirstrow
```

Define current \DTLiffirstrow

```
\cs_gset_eq:NN
\DTLiffirstrow
\_datatool_foreach_if_first_row:TF
```

Store previous value of \DTLiflastrow

```
\cs_gset_eq:cN
{ @dtl@iflastrow\the\dtlforeachlevel }
\DTLiflastrow
```

Define current \DTLiflastrow

```
\cs_gset_eq:NN
\DTLiflastrow
\_datatool_foreach_if_last_row:TF
```

Store previous value of \DTLifoddrow

```
\cs_gset_eq:cN
{ @dtl@ifoddrow\the\dtlforeachlevel }
\DTLifoddrow
```

Define current \DTLifoddrow

```
\cs_gset_eq:NN
\DTLifoddrow
\__datatool_foreach_if_odd_row:TF
```

Store data base name for current level

```
\tl_gset_eq:cN
{ @dtl@dbname@\romannumeral\dtlforeachlevel }
\@dtl@dbname
```

Read only setting.

```
\bool_if:NTF #5
{
  \tl_gset:cN
  { @dtl@ro@\romannumeral\dtlforeachlevel }
  { \c_one_int }
}
{
  \tl_gset:cN
  { @dtl@ro@\romannumeral\dtlforeachlevel }
  { \c_zero_int }
}
```

Loop through each row. Loop counter given by \dtl@row<level>

```
\exp_args:Nc \dtlforint
{ dtl@row\romannumeral\dtlforeachlevel }
=1\to\csname dtlrows@#2\endcsname\step1\do
{
```

Get current row from the data base

```
\exp_args:Nnx
\dtlgetrow { #2 }
{ \int_use:c { dtl@row\romannumeral\dtlforeachlevel } }
```

Store the current row for this level

```
\__datatool_token_register_gset_eq:cN
{ @dtl@cur\romannumeral\dtlforeachlevel }
\dtlcurrentrow
```

Current and previous rows only need to be save if not read only.

```
\bool_if:NF #5
{
```

Store the previous rows for this level.

```
\__datatool_token_register_gset_eq:cN
{ @dtl@prev\romannumeral\dtlforeachlevel }
\dtlbeforerow
```

Store the subsequent rows for this level.

```
    \__datatool_token_register_gset_eq:cN
      { @dtl@next\romannumeral\dtlforeachlevel }
      \dtlafterrow
    }
```

Assign commands to the required entries

```
\ifblank{#3}{ }\@dtl@assign{#3}{#2}}
```

Do the main body of text if condition is satisfied

```
\ifthenelse { #1 }
{
```

Increment user row counter

```
\refstepcounter
  { DTLrow \romannumeral \dtlforeachlevel }
\tl_set:Nx
  \DTLcurrentindex
  {
    \arabic { DTLrow\romannumeral\dtlforeachlevel }
  }
#4
```

Reconstruct database if not read only.

```
\bool_if:NF #5
{
```

Has this row been marked for deletion?

```
\exp_args:Nx \tl_if_eq:nnTF
  {
    \__datatool_token_register_use:c
    { @dtl@cur\romannumeral \dtlforeachlevel }
  }
  { \@nil }
{
```

Row needs to be deleted Decrement row indices for rows with a higher index than this one

```
\exp_args:Ncc
  \dtl@decrementrows
  {
    @dtl@prev
    \romannumeral \dtlforeachlevel
  }
  {
    dtl@row
    \romannumeral \dtlforeachlevel
  }
\exp_args:Ncc
  \dtl@decrementrows
  {
    @dtl@next
```

```

        \romannumeral \dtlforeachlevel
    }
    {
        dtl@row
        \romannumeral \dtlforeachlevel
    }

```

Globally reconstruct data base without this row

```

\__datatool_token_register_gset:cx
{ dtldb@#2 }
{
    \__datatool_token_register_use:c
    {
        @dtl@prev
        \romannumeral \dtlforeachlevel
    }
    \__datatool_token_register_use:c
    {
        @dtl@next
        \romannumeral \dtlforeachlevel
    }
}

```

Decrement the row count for this database:

```

\int_gdecr:c { dtlrows@#2 }

```

Decrement the counter for this loop

```

\int_gdecr:c
{ dtl@row\romannumeral \dtlforeachlevel }
}
{

```

No row deletion. Reconstruct data base.

```

\__datatool_token_register_set_eq:Nc
\@dtl@before
{ @dtl@prev\romannumeral \dtlforeachlevel }
\__datatool_token_register_set_eq:Nc
\@dtl@after
{ @dtl@next\romannumeral \dtlforeachlevel }

```

Concatenate.

```

\__datatool_token_register_gconcat_middle:cNxN
{ dtldb@#2 }
\@dtl@before
{

```

This row

```

\__datatool_row_markup:vv
{ dtl@row\romannumeral \dtlforeachlevel }
{ @dtl@cur\romannumeral \dtlforeachlevel }
}
\@dtl@after

```

```

    }
  }
}

```

Condition not met so just increment the number of filtered rows variable.

```

{
  \int_gincr:c
  {
    g__filtered_row_
    \romannumeral \dtlforeachlevel
    _int
  }
}

```

Restore previous value of \DTLiffirstrow

```

\cs_gset_eq:Nc
\DTLiffirstrow
{ @dtl@iffirstrow\the\dtlforeachlevel }

```

Restore previous value of \DTLiflastrow

```

\cs_gset_eq:Nc
\DTLiflastrow
{ @dtl@iflastrow\the\dtlforeachlevel }

```

Restore previous value of \DTLifoddrow

```

\cs_gset_eq:Nc
\DTLifoddrow
{ @dtl@ifoddrow\the\dtlforeachlevel }
}

```

Decrement level

```

\int_gdecr:N \dtlforeachlevel
}

```

else part (data base doesn't exist):

```

{
  \PackageError {datatool}
  { Database ~ `#2' ~ doesn't ~ exist }
  {}
}
}

```

\@DTLforeach \@DTLforeach is the unstarred version of \DTLforeach. The database is reconstructed to allow for rows to be edited. Use the starred version for faster access.

```

\newcommand{\@DTLforeach}[4][\boolean{true}]{%
  \__datatool_for_each:nnnnN { #1 } { #2 } { #3 } { #4 }
  \c_false_bool
}

```

`\@sDTLforeach` `\@SDTLforeach` is the starred version of `\DTLforeach`. The database rows can't be edited.

```
\newcommand{\@sDTLforeach}[4][\boolean{true}]{
  \__datatool_for_each:nnnnN { #1 } { #2 } { #3 } { #4 }
  \c_true_bool
}
\ExplSyntaxOff
```

`\@dtlifreadonly{<true part>}{<>false part>}`

`\@dtlifreadonly`

Checks if current loop level is read only

```
\newcommand*\@dtlifreadonly}[2]{%
  \expandafter\ifx
  \csname @dtl@ro@\romannumeral\dtlforeachlevel\endcsname1\relax
```

Read only

```
  #1%
```

```
  \else
```

Not read only

```
  #2%
```

```
  \fi
```

```
}
```

```
\ExplSyntaxOn
```

`\DTLappendtorow{<key>}{<value>}`

`\DTLappendtorow`

Appends entry to current row. (The current row is given by `\@dtl@cur<n>` where `<n>` is roman numeral value of `\dtlforeachlevel`. One level expansion is applied to `<value>`).

```
\newrobustcmd*\DTLappendtorow}[2]{%
  \int_if_zero:nTF { \dtlforeachlevel }
  {
    \PackageError {datatool}
    {
      \token_to_str:N \DTLappendrow \c_space_tl ~ can ~ only ~ be ~
      used ~ inside ~ \token_to_str:N \DTLforeach
    }
    { }
  }
}
```

Set `\@dtl@thisdb` to the current database name:

```
\tl_set_eq:Nc \@dtl@thisdb
{ @dtl@dbname@\romannumeral\dtlforeachlevel }
```

Check this isn't in \DTLforeach*

```
\@dtlifreadonly
{%
  \PackageError {datatool}
  {
    \token_to_str:N \DTLappendtorow \c_space_tl ~ can't ~
    be ~ used ~ inside ~ \token_to_str:N \DTLforeach*
  }
  {
    The ~ starred ~ version ~ of ~
    \token_to_str:N \DTLforeach \c_space_tl ~ is ~ read ~ only}
}%
{%
```

Store current row number in \dtlrownum

```
\int_set_eq:Nc \dtlrownum
{ dtl@row\romannumeral\dtlforeachlevel }
```

Update information about this column (adding new column if necessary)

```
\@dtl@updatekeys{\@dtl@thisdb}{#1}{#2}%
```

Get column index and store in \dtlcolumnnum

```
\int_set:Nn \dtlcolumnnum
{ \dtlcolumnindex{\@dtl@thisdb}{#1} }
```

Set \dtlcurrentrow to the current row

```
\dtlcurrentrow =
\csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
```

Does this row already have an entry with this key?

```
\exp_args:NNV
\dtlgetentryfromcurrentrow
\dtl@entry
\dtlcolumnnum
\datatool_if_null:NTF \dtl@entry
{
```

There are no entries in this row for the given key. Expand entry value before storing.

```
\protected@edef\@dtl@tmp{#2}%
\expandafter\@dtl@toks\expandafter{\@dtl@tmp}%
```

Globally append this entry to the current row.

```
\__datatool_token_register_gput_right:cx
{ @dtl@cur\romannumeral\dtlforeachlevel }
{
  \__datatool_row_element_markup:VV
  \dtlcolumnnum
  \@dtl@toks
}
```

Print information to terminal and log file if in verbose mode.

```
\dtl@message{Appended ~ #1\space -> ~ \the\@dtl@toks\space to ~
database ~ ``\@dtl@thisdb'}
```



```

    }%
  }%
  {%
Store current row number in \dtlrownum
  \int_set_eq:Nc \dtlrownum
  { dtl@row\romannumeral\dtlforeachlevel }
Is there a column corresponding to this key?
  \@DTLifhaskey{\@dtl@thisdb}{#1}%
  {%
There exists a column for this key, so get the index:
  \@dtl@getcolumnindex{\thiscol}{\@dtl@thisdb}{#1}\relax
  \dtlcolumnnum=\thiscol\relax
Set \dtlcurrentrow to the current row
  \dtlcurrentrow =
  \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
Does this row have an entry with this key?
  \exp_args:NNV
  \dtlgetentryfromcurrentrow
  \dtl@entry
  \dtlcolumnnum
  \datatool_if_null:NTF \dtl@entry
  {
This row doesn't contain an entry with this key
  \PackageError {datatool}
  {
  {
    Can't ~ remove ~ entry ~ given ~ by ~ `#1' ~
    from ~ current ~ row ~ in ~ database ~
    \@dtl@thisdb': ~ no ~ such ~ entry
  }
  {
    The ~ current ~ row ~ doesn't ~ contain ~ an ~ entry ~
    for ~ key ~ `#1'
  }
  }%
  }
  {
Split the current row around the unwanted entry
  \edef\@dtl@dosplitrow{%
  \noexpand\dtlsplitrow{\the\dtlcurrentrow}%
  {\number\dtlcolumnnum}{\noexpand\dtl@pre}%
  {\noexpand\dtl@post}%
  }%
  \@dtl@dosplitrow
Reconstruct row without unwanted entry
  \expandafter\@dtl@toks\expandafter{\dtl@pre}%
  \expandafter\toks@\expandafter{\dtl@post}%

```



```

        can't ~ be ~ used ~ inside ~ \token_to_str:N \DTLforeach*
    }
    {
        The ~ starred ~ version ~
        of ~ \token_to_str:N \DTLforeach \c_space_tl is ~ read ~ only
    }%
}%
{%

Store current row number in \dtlrownum
\int_set_eq:Nc \dtlrownum
{ dtl@row\romannumeral\dtlforeachlevel }

Is there a column corresponding to this key?
\@DTLifhaskey{\@dtl@thisdb}{#1}%
{%

There exists a column for this key, so get the index:
\@dtl@getcolumnindex{\thiscol}{\@dtl@thisdb}{#1}
\int_set_eq:NN \dtlcolumnnum \thiscol

Set \dtlcurrentrow to the current row
\dtlcurrentrow =
\csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname

Does this row have an entry with this key?
\exp_args:NNV
\dtlgetentryfromcurrentrow
\dtl@entry
\dtlcolumnnum
\datatool_if_null:NTF \dtl@entry
{

This row doesn't contain an entry with this key
\PackageError {datatool}
{
    Can't ~ replace ~ entry ~ given ~ by ~ `#1' ~
    from ~ current ~ row ~ in ~ database ~ ``\@dtl@thisdb': ~
    no ~ such ~ entry
}
{
    The ~ current ~ row ~ doesn't ~ contain ~ an ~ entry ~
    for ~ key ~ `#1'
}%
}
}

Split the current row around the requested entry
\edef\@dtl@dosplitrow{%
\noexpand\dtlsplitrow{\the\dtlcurrentrow}%
{\number\dtlcolumnnum}{\noexpand\dtl@pre}%
{\noexpand\dtl@post}%
}

```

```
}%
\@dtl@dosplitrow
```

Reconstruct row with new value (given by #2).

```
\protected@edef\@dtl@tmp{#2}%
\expandafter\@dtl@toks\expandafter{\@dtl@tmp}% new value
\expandafter\@dtl@before\expandafter{\dtl@pre}%
\expandafter\@dtl@after\expandafter{\dtl@post}%
\__datatool_token_register_gconcat_middle:cNxN
{ @dtl@cur\romannumeral\dtlforeachlevel }
\@dtl@before
{
  \__datatool_row_element_markup:VV
  \dtlcolumnnum
  \@dtl@toks
}
\@dtl@after
```

Print information to terminal and log file if in verbose mode.

```
\dtl@message{Updated ~ #1\space -> \the\@dtl@toks\space
in ~ database ~ ` \@dtl@thisdb' }%
}
}%
{%
```

There doesn't exist a column for this key.

```
\PackageError {datatool}
{
  Can't ~ replace ~ key ~ `#1' ~ - ~ no ~ such ~
  key ~ in ~ database ~ ` \@dtl@thisdb'
}
{}%
}%
}
}
```

\DTLremovecurrentrow

\DTLremovecurrentrow

Removes current row. This just sets the current row to empty

```
\newcommand*{\DTLremovecurrentrow}{%
\int_if_zero:nTF { \dtlforeachlevel }
{
  \PackageError {datatool}
  {
    \token_to_str:N \DTLremovecurrentrow\c_space_tl ~
    can ~ only ~ be ~ used ~ inside ~ \token_to_str:N \DTLforeach
  }
  { }
}
```

```

}
{
Set \@dtl@thisdb to the current database name: TODO why is this needed?
\l_set_eq:Nc
\@dtl@thisdb
{ \@dtl@dbname@\romannumeral\dtlforeachlevel }
Check this isn't in \DTLforeach*
\@dtlifreadonly
{
\PackageError {datatool}
{
\token_to_str:N \DTLreplaceentryforrow\c_space_tl
can't ~ be ~ used ~ inside ~ \token_to_str:N \DTLforeach*
}
{
The ~ starred ~ version ~ of ~
\token_to_str:N \DTLforeach \c_space_tl ~ is ~ read ~ only
}
}
}
{
Set the current row to \@nil (\DTLforeach needs to check for this)
\__datatool_token_register_gset:cn
{ \@dtl@cur\romannumeral\dtlforeachlevel }
{ \@nil }
}
}
}
\ExplSyntaxOff

```

```

\DTLaddentryforrow{<db name>}{<assign list>}
{<condition>}{<key>}{<value>}

```

\DTLaddentryforrow

Adds the entry with key given by *<key>* and value given by *<value>* to the first row in the database *<db name>* which satisfies the condition given by *<condition>*. The *<assign list>* is the same as for `\DTLforeach` and may be used to set the values which are to be tested in *<condition>*.

```
\newcommand{\DTLaddentryforrow}[5]{%
```

Iterate through the data base until condition is met

```

\DTLifdbexists{#1}%
{%
\def\@dtl@notdone{\PackageError{datatool}{Unable to add entry
given by key `#4': condition not met for any row in database
`#1'}}}%

```

Iterate through each row

```
\DTLforeach[#3]{#1}{#2}%  
{%
```

add entry to this row

```
\DTLappendtorow{#4}{#5}%
```

disable error message

```
\let\@dtl@notdone\relax
```

break out of loop

```
\dtlbreak
```

```
}%
```

```
\@dtl@notdone
```

```
}%
```

```
{%
```

```
\PackageError{datatool}{Unable to add entry given by key `#4':  
database `#1' doesn't exist}{}
```

```
}%
```

```
}
```

```
\DTLforeachkeyinrow{<cmd>}{<text>}
```

\DTLforeachkeyinrow

Iterates through each key in the current row of \DTLforeach, and does <text>.

```
\newcommand*{\DTLforeachkeyinrow}[2]{%
```

```
\ifnum\dtlforeachlevel=0\relax
```

```
\PackageError{datatool}{\string\DTLforeachkeyinrow\space can only  
be used inside \string\DTLforeach}{}
```

```
\else
```

Set \@dtl@thisdb to the current database name:

```
\expandafter\let\expandafter\@dtl@thisdb
```

```
\csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname
```

Iterate through key list

```
\dtlforeachkey(\dtlkey,\dtlcol,\dtltype,\dtlheader)\in
```

```
\@dtl@thisdb\do{%
```

store row in \dtlcurrentrow (This may get nested so need to do it here instead of outside this loop in case <text> changes it.)

```
\dtlcurrentrow =
```

```
\csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
```

Get the value for this key and store in #1

```
\edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
```

```
{\noexpand#1}{\dtlcol}}%
```

```
\dtl@dogetentry
```

Check if null

```
\ifx#1\dtlnovalue
```

```
\ifnum0\dtltype=0\relax
```

Data type is *empty* or 0, so set to string null. TODO: why did v2.13 change this to use `\@dtlstringnull` and `\@dtlnumbernull`? (Why not `\DTLstringnull` and `\DTLnumbernull`?)

```
\let#1=\@dtlstringnull
\else
```

Data type is numerical, so set to number null.

```
\let#1=\@dtlnumbernull
\fi
\fi
```

Make #1 global in case this is in a tabular environment (or something similar)

```
\global\let#1#1%
```

Store loop body so that any scoping commands (such as `&`) don't cause a problem for `\ifx`

```
\def\@dtl@loop@body{#2}%
\@dtl@loop@body
}%
\fi
}
```

12.6 DTLforeach Conditionals

The following conditionals are only meant to be used within `\DTLforeach` as they depend on the counter `DTLrow`(*n*).

```
\ExplSyntaxOn
```

```
\DTLiffirstrow{<true part>}{<false part>}
```

`\DTLiffirstrow`

Test if the current row is the first row. (This takes *condition*, the optional argument of `\DTLforeach`, into account, so it may not correspond to row 1 of the database.) Can only be used in `\DTLforeachrow`.

```
\newcommand{\DTLiffirstrow}[2]{
  \PackageError {datatool}
  {
    \token_to_str:N \DTLiffirstrow\c_space_tl ~ can ~ only ~
    be ~ used ~ inside ~ \token_to_str:N \DTLforeach
  }
  {}
}
```

Definition within `\DTLforeach`:

```
\cs_new:Nn \__datatool_foreach_if_first_row:TF
{
  \int_compare:nNnTF
  { \int_use:c { c@DTLrow\romannumerals\dtlforeachlevel } }
```

```

    =
    { \c_one_int }
  { #1 } { #2 }
}

```

```
\DTLiflastrow{<true part>}{<false part>}
```

\DTLiflastrow

Checks if the current row is the last row of the database. It doesn't take the condition (the optional argument of \DTLforeach) into account, so its possible it may never do <true part>, as the last row of the database may not meet the condition. It is therefore not very useful and is confusing since it behaves differently to \DTLiffirstrow which does take the condition into account, so I have removed its description from the main part of the manual. If you need to use the optional argument of \DTLforeach, you will first have to iterate through the database to count up the number of rows which meet the condition, and then do another pass, checking if the current row has reached that number.

```

\newcommand{\DTLiflastrow}[2]{
  \PackageError {datatool}
  {
    \token_to_str:N \DTLiflastrow\c_space_tl ~ can ~ only ~
    be ~ used ~ inside ~ \token_to_str:N \DTLforeach
  }
  {}
}

```

Definition within \DTLforeach:

```

\cs_new:Nn \__datatool_foreach_if_last_row:TF
{
  \int_compare:nNnTF
  { \int_use:c { c@DTLrow\romannumeral\dtlforeachlevel } }
  =
  {
    \int_use:c { dtlrows@ \@dtl@dbname }
    -
    \int_use:c
    {
      g__filtered_row_
      \romannumeral \dtlforeachlevel
      _int
    }
  }
  { #1 } { #2 }
}

```

```
\DTLifoddrow{<true part>}{<false part>}
```

\DTLifoddrow

Determines whether the current row is odd (takes the optional argument of `\DTLforeach` into account.)

```
\newcommand{\DTLifodddrow}[2]{%
  \PackageError
    {datatool}
    {
      \token_to_str:N \DTLifodddrow \c_space_tl ~ can ~ only ~
      be ~ used ~ inside ~ \token_to_str:N \DTLforeach
    }
    {}
}
```

Definition within `\DTLforeach`:

```
\cs_new:Nn \__datatool_foreach_if_odd_row:TF
{
  \int_if_odd:nTF
    { \int_use:c { c@DTLrow\romannumeral\dtlforeachlevel } }
    { #1 } { #2 }
}
\ExplSyntaxOff
```

12.7 Displaying Database

This section defines commands to display the entire database in a tabular or longtable environment.

- `\dtlbetweencols` This specifies what to put between the column alignment specifiers.
`\newcommand*{\dtlbetweencols}{}`
- `\dtlbeforecols` This specifies what to put before the first column alignment specifier.
`\newcommand*{\dtlbeforecols}{}`
- `\dtlaftercols` This specifies what to put after the last column alignment specifier.
`\newcommand*{\dtlaftercols}{}`
- `\dtlstringalign` Alignment character for columns containing strings
`\newcommand*{\dtlstringalign}{l}`
- `\dtlintalign` Alignment character for columns containing integers
`\newcommand*{\dtlintalign}{r}`
- `\dtlrealalign` Alignment character for columns containing real numbers
`\newcommand*{\dtlrealalign}{r}`
- `\dtlcurrencyalign` Alignment character for columns containing currency numbers
`\newcommand*{\dtlcurrencyalign}{r}`

`\dtldatetimealign` Alignment character for columns containing timestamps.

```
\newcommand*\dtldatetimealign{l}
```

`\dtldatealign` Alignment character for columns containing dates.

```
\newcommand*\dtldatealign{l}
```

`\dtltimealign` Alignment character for columns containing times.

```
\newcommand*\dtltimealign{l}
```

```
\ExplSyntaxOn
```

```
\dtladdalign{<cs>}{<type>}{<col num>}{<max cols>}
```

`\dtladdalign`

Adds tabular column alignment character to `<cs>` for column `<col num>` which contains data type `<type>`.

```
\NewDocumentCommand \dtladdalign { m m m m }
{
  \int_compare:nNnTF { #3 } = { 1 }
  {
    \tl_set_eq:NN #1 \dtlbeforecols
  }
  {
    \tl_put_right:NV #1 \dtlbetweencols
  }
  \exp_args:Nx \tl_if_empty:nTF { #2 }
  {
    \int_set_eq:NN
      \l__datatool_tmp_datatype_int \c_datatool_unknown_int
  }
  {
    \int_set:Nn \l__datatool_tmp_datatype_int { #2 }
  }
  \int_case:nnF { \l__datatool_tmp_datatype_int }
  {
    { \c_datatool_string_int }
    {
string
      \tl_put_right:NV #1 \dtlstringalign
    }
    { \c_datatool_integer_int }
    {
integer
      \tl_put_right:NV #1 \dtlintalign
    }
    { \c_datatool_decimal_int }
    {
```

```

real number
    \tl_put_right:NV #1 \dtlrealalign
    }
    { \c_datatool_currency_int }
    {
currency
    \tl_put_right:NV #1 \dtlcurrencyalign
    }
    { \c_datatool_datetime_int }
    {
datetime
    \tl_put_right:NV #1 \dtldatetimealign
    }
    { \c_datatool_date_int }
    {
date
    \tl_put_right:NV #1 \dtldatealign
    }
    { \c_datatool_time_int }
    {
time
    \tl_put_right:NV #1 \dtltimealign
    }
    { \c_datatool_unknown_int }
    {
Unknown type
    \tl_put_right:NV #1 \dtlstringalign
    \PackageWarning { datatool }
    {
        Column ~ \int_eval:n { #3 } ~ has ~ no ~
        associated ~ datatype. ~ Assuming ~
        string, ~ but ~ column ~ may ~ be ~ empty
    }
    }
    }
    {
    \tl_put_right:NV #1 \dtlstringalign
    \PackageError { datatool }
    {
        Invalid ~ data ~ type ~ ``\int_eval:n{ #2 } ' ~
        for ~ column ~ \int_eval:n { #3 } }
    { }
    }
    \int_compare:nNnT { #3 } = { #4 }
    {
    \tl_put_right:NV #1 \dtlaftercols

```

```

}
}
\regex_new:N \l_datatool_colalign_regex
\regex_set:Nn \l_datatool_colalign_regex { [ m p r c l ] }

```

`\dtladdheaderalign{<cs>}{<type>}{<col num>}{<max cols>}`

`\dtladdheaderalign`

Similar but for the column alignment in the header row.

```

\NewDocumentCommand \dtladdheaderalign { m m m m }
{
  \int_compare:nNnTF { #3 } = { 1 }
  {

```

If `\dtlbeforecols` includes m, p, r, c, or l don't append.

```

    \regex_match:NVF \l_datatool_colalign_regex \dtlbeforecols
    {
      \tl_set_eq:NN #1 \dtlbeforecols
    }
  }
  {
    \tl_put_right:NV #1 \dtlbetweencols
  }
  \tl_put_right:Nn #1 { c }
  \int_compare:nNnT { #3 } = { #4 }
  {
    \regex_match:NVF \l_datatool_colalign_regex \dtlaftercols
    {
      \tl_put_right:NV #1 \dtlaftercols
    }
  }
}
}

```

`\dtlheaderformat{<text>}`

`\dtlheaderformat`

Specifies how to format the column title. Pre v3.0 the definition included `\hfil` to centre without affecting vertical lines. This is now dealt with by `\dtlheaderformat`.

```

\newcommand*{\dtlheaderformat}[1]{\textbf{#1}}

```

`\dtlcolumnheader{<align>}{<text>}`

`\dtlcolumnheader`

Newer alternative. This needs to expand to avoid a “Misplaced `\omit`” error.

```

\newcommand \dtlcolumnheader [2]
{

```

```
\multicolumn { 1 } { #1 } { \dtlheaderformat{ #2 } }  
}
```

`\dtlstringformat`

```
\dtlstringformat{<text>}
```

Specifies how to format entries in columns with string data type.
`\newcommand*{\dtlstringformat}[1]{#1}`

`\dtlnumericformat`

```
\dtlnumericformat{<text>}
```

Specifies how to format entries in columns with a numeric data type.
`\newcommand*{\dtlnumericformat}[1]{#1}`

`\dtlintformat`

```
\dtlintformat{<text>}
```

Specifies how to format entries in columns with integer data type.
`\newcommand*{\dtlintformat}[1]{\dtlnumericformat{#1}}`

`\dtlrealformat`

```
\dtlrealformat{<text>}
```

Specifies how to format entries in columns with real data type.
`\newcommand*{\dtlrealformat}[1]{\dtlnumericformat{#1}}`

`\dtlcurrencyformat`

```
\dtlcurrencyformat{<text>}
```

Specifies how to format entries in columns with currency data type.
`\newcommand*{\dtlcurrencyformat}[1]{\dtlnumericformat{#1}}`

NB the `datetime=reformat` setting can instead be used to format dates and times.
These are just wrappers to change the font etc in tables.

`\dtldatetimeformat`

```
\dtldatetimeformat{<text>}
```

Specifies how to format entries in columns with datetime data type.
`\newcommand*{\dtldatetimeformat}[1]{#1}`

`\dtldateformat`

```
\dtldateformat{<text>}
```

Specifies how to format entries in columns with date data type.
`\newcommand*{\dtldateformat}[1]{#1}`

`\dtltimeformat{<text>}`

`\dtltimeformat`

Specifies how to format entries in columns with time data type.

`\newcommand*{\dtltimeformat}[1]{#1}`

`\dtldisplaystarttab` Indicates what to do just after `\begin{tabular}`{<column specs>} (e.g. `\hline`).

`\newcommand*{\dtldisplaystarttab}{}`

`\dtldisplayendtab` Indicates what to do just before `\end{tabular}`.

`\newcommand*{\dtldisplayendtab}{}`

`\dtldisplayafterhead` Indicates what to do after the header row, before the first row of data.

`\newcommand*{\dtldisplayafterhead}{}`

`\dtldisplayvalign` Stores the vertical alignment specifier for the tabular environment used in `\DTLdisplaydb`

`\newcommand*{\dtldisplayvalign}{c}`

`\dtldisplaystartrow` Indicates what to do at the start of each row (not including the header row or the first row of data).

`\newcommand*{\dtldisplaystartrow}{}`

The number of database rows per tabular row.

`\int_new:N \l_datatool_display_per_row_int`

`\int_set_eq:NN \l_datatool_display_per_row_int \c_one_int`

The number of tabular lines (not including header and footer or extra rows inserted by hooks). This value also doesn't take into account filtering. It's simply set to the database row count divided by the above and rounded.

`\int_new:N \l_datatool_display_tab_rows_int`

For use in the display hooks, this tests if the given column number is at the start of the tabular row taking replication into account.

Syntax: `{<row num>}{<column num>}{<true>}{<false>}`

`\prg_new_conditional:Npnn \datatool_if_row_start:nn #1 #2`

`{ p, T, F, TF }`

`{`

`\int_compare:nNnTF`

`{ \l_datatool_display_per_row_int } > { \c_one_int }`

`{`

`\bool_lazy_and:nnTF`

`{ \int_compare_p:nNn { #2 } = { \c_one_int } }`

`{`

`\int_compare_p:nNn`

`{ \int_mod:nn { #1 } { \l_datatool_display_per_row_int } }`
`= { \c_one_int }`

`}`

`{ \prg_return_true: }`

```

    { \prg_return_false: }
  }
  {
    \int_compare:nNnTF { #2 } = { \c_one_int }
    { \prg_return_true: }
    { \prg_return_false: }
  }
}

```

Function (which must expand to an integer) that obtains the database row index from the step function value that uses `__datatool_display_db_row_fn:n`.
`\cs_new:Nn __datatool_display_row_idx:n { #1 }`

`\DTLdisplayTBrowidxmap` Convenient function to produce top to bottom instead of left to right arrangement, but only works if there's no filtering.

```

\newcommand \DTLdisplayTBrowidxmap [1]
{
  \int_mod:nn
  { ( #1 - \c_one_int ) }
  { \l_datatool_display_per_row_int }
  * \l_datatool_display_tab_rows_int
  + \int_div_truncate:nn
  { #1 - \c_one_int }
  { \l_datatool_display_per_row_int } + \c_one_int
}

```

`\dtldisplaycr`

```
\newcommand{\dtldisplaycr}{\tabularnewline}
```

`\dtldisplaydbenv`

```
\newcommand{\dtldisplaydbenv}{tabular}
```

```
\DTLdisplaydbAddBegin{<content t1>}{<align token list>}{<header token list>}
```

`\DTLdisplaydbAddBegin`

```

\NewDocumentCommand \DTLdisplaydbAddBegin { m m m }
{
  \tl_put_right:Nx #1 { \exp_not:N \begin { \dtldisplaydbenv } }

```

Note that `\dtldisplayvalign` needs to expand.

```

\tl_if_empty:NF \dtldisplayvalign
{
  \tl_put_right:Nx #1
  {
    [ \dtldisplayvalign ]
  }
}
\tl_put_right:Nn #1 { { #2 } }

```

Add the header row:

```
\tl_put_right:NV #1 \dtldisplaystarttab  
\tl_put_right:Nn #1 { #3 }  
\tl_put_right:NV #1 \l_datatool_post_head_tl  
\tl_put_right:NV #1 \dtldisplaycr  
\tl_put_right:NV #1 \dtldisplayafterhead  
}
```

`\DTLdisplaydbAddEnd{<content t1>}`

`\DTLdisplaydbAddEnd`

```
\NewDocumentCommand \DTLdisplaydbAddEnd { m }  
{  
  \tl_if_eq:NnF \l_datatool_foot_tl { \c_novalue_tl }  
  {  
    \tl_put_right:NV #1 \dtldisplaycr  
    \tl_put_right:NV #1 \l_datatool_foot_tl  
  }  
  \tl_put_right:NV #1 \dtldisplayendtab  
  \tl_put_right:Nx #1 { \exp_not:N \end { \dtldisplaydbenv } }  
}
```

```
\seq_new:N \l_datatool_omit_columns_seq  
\seq_new:N \l_datatool_only_columns_seq  
\seq_new:N \l_datatool_omit_keys_seq  
\seq_new:N \l_datatool_only_keys_seq  
\cs_new:Nn \__datatool_if_display_row:NnT { #3 }  
\cs_new:Nn \__datatool_display_post_row:Nn { }  
\tl_new:N \l_datatool_pre_display_tl  
\tl_new:N \l_datatool_init_display_tl  
\tl_new:N \l_datatool_user_align_tl  
\tl_new:N \l_datatool_user_header_tl  
\bool_new:N \l_datatool_include_header_bool  
\bool_set_true:N \l_datatool_include_header_bool
```

The following are for `\DTLdisplaylongdb`. These aren't private in case the user wants to customize `\DTLdisplaylongdbAddBegin`. The table caption (no value indicates no caption):

```
\tl_new:N \l_datatool_caption_tl  
\tl_set:Nn \l_datatool_caption_tl { \c_novalue_tl }
```

The short form for the lot (no value indicates use the above):

```
\tl_new:N \l_datatool_short_caption_tl  
\tl_set:Nn \l_datatool_short_caption_tl { \c_novalue_tl }
```

The continuation caption (no value indicates use the main caption):

```
\tl_new:N \l_datatool_cont_caption_tl  
\tl_set:Nn \l_datatool_cont_caption_tl { \c_novalue_tl }
```

The label:

```
\tl_new:N \l_datatool_label_tl  
\tl_set:Nn \l_datatool_label_tl { \c_novalue_tl }
```

The footer:

```
\tl_new:N \l_datatool_foot_tl  
\tl_set:Nn \l_datatool_foot_tl { \c_novalue_tl }
```

The last footer:

```
\tl_new:N \l_datatool_last_foot_tl  
\tl_set:Nn \l_datatool_last_foot_tl { \c_novalue_tl }
```

The following is used for both `\DTLdisplay` and `\DTLdisplaylongdb` after the header but before `\dtldisplaycr` and `\dtldisplayafterhead`:

```
\tl_new:N \l_datatool_post_head_tl  
Keys for \DTLdisplaydb* and \DTLdisplaylongdb:  
\keys_define:nn { datatool/display }  
{  
  omit-columns .code:n =  
  {  
    \seq_set_from_clist:Nn \l__datatool_omit_columns_seq { #1 }  
    \seq_if_empty:NF \l__datatool_omit_columns_seq  
    {  
      \seq_clear:N \l__datatool_only_columns_seq  
      \seq_clear:N \l__datatool_only_keys_seq  
      \seq_clear:N \l__datatool_omit_keys_seq  
    }  
  },  
  only-columns .code:n =  
  {  
    \seq_set_from_clist:Nn \l__datatool_only_columns_seq { #1 }  
    \seq_remove_duplicates:N \l__datatool_only_columns_seq  
    \seq_if_empty:NF \l__datatool_only_columns_seq  
    {  
      \seq_clear:N \l__datatool_omit_columns_seq  
      \seq_clear:N \l__datatool_only_keys_seq  
      \seq_clear:N \l__datatool_omit_keys_seq  
    }  
  },  
  omit-keys .code:n =  
  {  
    \seq_set_from_clist:Nn \l__datatool_omit_keys_seq { #1 }  
    \seq_if_empty:NF \l__datatool_omit_keys_seq  
    {  
      \seq_clear:N \l__datatool_only_columns_seq  
      \seq_clear:N \l__datatool_omit_columns_seq  
      \seq_clear:N \l__datatool_only_keys_seq  
    }  
  },  
  only-keys .code:n =
```

```

{
  \seq_set_from_clist:Nn \l__datatool_only_keys_seq { #1 }
  \seq_remove_duplicates:N \l__datatool_only_keys_seq
  \seq_if_empty:NF \l__datatool_only_keys_seq
  {
    \seq_clear:N \l__datatool_only_columns_seq
    \seq_clear:N \l__datatool_omit_columns_seq
    \seq_clear:N \l__datatool_omit_keys_seq
  }
},
row-condition-inline .cs_set:Np =
  \__datatool_if_display_row:NnT #1 #2 #3 ,
row-condition-function .code:n =
  {
    \cs_set_eq:NN \__datatool_if_display_row:NnT #1
  },
post-row-inline .cs_set:Np =
  \__datatool_display_post_row:Nn #1 #2 ,
post-row-function .code:n =
  {
    \cs_set_eq:NN \__datatool_display_post_row:Nn #1
  } ,
row-idx-map-inline .cs_set:Np =
  \__datatool_display_row_idx:n #1 ,
row-idx-map-function .code:n =
  {
    \cs_set_eq:NN \__datatool_display_row_idx:n #1
  },
init .tl_set:N = \l__datatool_init_display_tl ,
pre-content .tl_set:N = \l__datatool_pre_display_tl ,
pre-head .tl_set:N = \dtldisplaystarttab ,
post-head .tl_set:N = \l__datatool_post_head_tl ,
after-head .tl_set:N = \dtldisplayafterhead ,
align-specs .tl_set:N = \l__datatool_user_align_tl ,
header-row .tl_set:N = \l__datatool_user_header_tl ,
no-header .bool_set_inverse:N = \l__datatool_include_header_bool ,
string-align .tl_set:N = \dtlstringalign,
int-align .tl_set:N = \dtlintalign,
integer-align .tl_set:N = \dtlintalign,
real-align .tl_set:N = \dtlrealalign,
decimal-align .tl_set:N = \dtlrealalign,
currency-align .tl_set:N = \dtlcurrencyalign,
inter-col .tl_set:N = \dtlbetweencols,
pre-col .tl_set:N = \dtlbeforecols,
post-col .tl_set:N = \dtlaftercols,

```

This key is only for the tabular version:

```

tabular-env .choice:,
tabular-env / tabular .code:n =
{

```

```

\l_set:Nn \dtldisplaydbenv { tabular }
\l_if_eq:NnF \dtldisplayvalign { t }
{
  \l_if_eq:NnF \dtldisplayvalign { b }
  {
    \l_set:Nn \dtldisplayvalign { c }
  }
}
},
tabular-env / array .code:n =
{
  \l_set:Nn \dtldisplaydbenv { array }
  \l_if_eq:NnF \dtldisplayvalign { t }
  {
    \l_if_eq:NnF \dtldisplayvalign { b }
    {
      \l_set:Nn \dtldisplayvalign { c }
    }
  }
},
tabular-env / unknown .code:n =
{
  \cs_if_exist:cTF { #1 }
  {
    \l_set:Nn \dtldisplaydbenv { #1 }
    \l_clear:N \dtldisplayvalign
  }
  {
    \PackageError { datatool }
    {
      Unknown ~ environment ~ `#1' ~ specified ~ in ~
      option ~ `tabular-env'
    }
    {
      Check ~ that ~ you ~ have ~ spelt ~ the ~ environment ~
      name ~ correctly ~ and ~ have ~ loaded ~ any ~
      relevant ~ package
    }
  }
}
},
tabular-env .default:n = { tabular },
tabular-env .groups:n = { tabular },

```

These keys are only for the longtable version:

```

longtable-env .code:n =
{
  \cs_if_exist:cTF { #1 }
  {
    \l_set:Nn \dtldisplaylongdbenv { #1 }
  }
}

```

```

{
  \PackageError { datatool }
  {
    Unknown ~ environment ~ `#1' ~ specified ~ in ~
    option ~ `longtable-env'
  }
  {
    Check ~ that ~ you ~ have ~ spelt ~ the ~ environment ~
    name ~ correctly ~ and ~ have ~ loaded ~ any ~
    relevant ~ package
  }
}
},
longtable-env .default:n = { longtable },
longtable-env .groups:n = { longtable },
label .tl_set:N = \l_datatool_label_tl ,
label .groups:n = { longtable },
caption .tl_set:N = \l_datatool_caption_tl ,
caption .groups:n = { longtable },
cont-caption .tl_set:N = \l_datatool_cont_caption_tl ,
cont-caption .groups:n = { longtable },
short-caption .tl_set:N = \l_datatool_short_caption_tl ,
short-caption .groups:n = { longtable },
foot .tl_set:N = \l_datatool_foot_tl ,
last-foot .tl_set:N = \l_datatool_last_foot_tl ,
last-foot .groups:n = { longtable },
per-row .int_set:N = \l_datatool_display_per_row_int ,
Synonyms for backward compatibility:
contcaption .tl_set:N = \l_datatool_cont_caption_tl ,
contcaption .groups:n = { longtable },
shortcaption .tl_set:N = \l_datatool_short_caption_tl ,
shortcaption .groups:n = { longtable },
lastfoot .tl_set:N = \l_datatool_last_foot_tl ,
lastfoot .groups:n = { longtable },
omit .code:n =
{
  \seq_set_from_clist:Nn \l_datatool_omit_keys_seq { #1 }
  \seq_if_empty:NF \l_datatool_omit_keys_seq
  {
    \seq_clear:N \l_datatool_only_columns_seq
    \seq_clear:N \l_datatool_omit_columns_seq
    \seq_clear:N \l_datatool_only_keys_seq
  }
}
},
}

```

```
\DTLdisplaydb[omit list]{db}
```

\DTLdisplaydb

Displays the database $\langle db \rangle$ in a tabular environment. Version 3.0: rewritten so that the content is first built to avoid the problems with having a loop in a tabular context.

```

\NewDocumentCommand \DTLdisplaydb { s o m }
{
  \DTLifdbexists { #3 }
  {
    \group_begin:
    \IfValueT { #2 }
    {
      \IfBooleanTF { #1 }
      {
        \keys_set_filter:nnnN { datatool/display } { longtable } { #2 }
        \l__datatool_tmpb_tl
        \tl_if_empty:NF \l__datatool_tmpb_tl
        {
          \PackageWarning { datatool }
          {
            Ignoring ~ unsupported ~ \token_to_str:N\DTLdisplaydb* ~
            option(s): ~ \exp_not:o { \l__datatool_tmpb_tl }
          }
        }
      }
    }
    {
      \keys_set:nn { datatool/display } { omit-keys = { #2 } }
    }
  }
  \tl_set:Nx \dtldbname { #3 }
  \__datatool_display_db:
  \group_end:
}
{
  \PackageError { datatool }
  { Database ~ `#3' ~ doesn't ~ exist }
  { }
}
}

```

Internal command:

```

\cs_new:Nn \__datatool_display_db:
{

```

Initialise and check supplied options make sense:

```

  \__datatool_if_display_init:T
  {
    \l__datatool_init_display_tl

```

Start constructing the content token list. Add the begin part and header row:

```

  \exp_args:NNVV \DTLdisplaydbAddBegin \l__datatool_content_tl
  \l__datatool_align_tl \l__datatool_row_tl

```

Add the entry rows. There are two row counts: the row index (as given in the database) and the row number (which may be different if any rows are skipped).

```
\int_zero:N \dtlrownum
\int_zero:N \l__datatool_row_idx_int
```

Iterate over all rows:

```
\__datatool_display_loop:
```

Add the end part:

```
\DTLdisplaydbAddEnd \l__datatool_content_tl
```

Do the content:

```
\l__datatool_pre_display_tl
\l__datatool_content_tl
}
}
```

Row loop:

```
\cs_new:Nn \__datatool_display_loop:
{
  \int_step_inline:nn
  { \DTLrowcount { \dtldbname } }
  {
    \exp_args:Nx \__datatool_display_db_row_fn:n
    {
      \int_eval:n { \__datatool_display_row_idx:n { ##1 } }
    }
  }
}
```

Initialise and check supplied options make sense:

```
\cs_new:Nn \__datatool_if_display_init:T
{
  \tl_clear:N \l__datatool_content_tl
  \tl_clear:N \l__datatool_align_tl
  \tl_clear:N \l__datatool_row_tl
  \tl_set:Nv \l__datatool_keydata_tl { dtlkeys@\dtldbname }
}
```

Keep track of which columns should be included:

```
\seq_clear:N \l__datatool_column_indexes_seq
```

If only-keys has been set, obtain the corresponding column indexes:

```
\seq_if_empty:NF \l__datatool_only_keys_seq
{
  \seq_map_inline:Nn \l__datatool_only_keys_seq
  {
    \tl_if_exist:cTF { dtl@ci@\dtldbname @ ##1 }
    {
      \seq_put_right:Nv \l__datatool_only_columns_seq
      { dtl@ci@\dtldbname @ ##1 }
    }
  }
}
```

```

        \PackageWarning { datatool }
        { Ignoring ~ key ~ `##1' ~ in ~ only-keys ~ option: ~
          no ~ such ~ key ~ in ~ database ~ `dtldbname'
        }
      }
    }
  }
}

```

If omit-keys has been set, obtain the corresponding column indexes:

```

\seq_if_empty:NF \l__datatool_omit_keys_seq
{
  \seq_map_inline:Nn \l__datatool_omit_keys_seq
  {
    \tl_if_exist:cTF { dtl@ci@\dtldbname @ ##1 }
    {
      \seq_put_right:Nv \l__datatool_omit_columns_seq
      { dtl@ci@\dtldbname @ ##1 }
    }
    {
      \PackageWarning { datatool }
      { Ignoring ~ key ~ `##1' ~ in ~ omit-keys ~ option: ~
        no ~ such ~ key ~ in ~ database ~ `dtldbname'
      }
    }
  }
}
\seq_if_empty:NTF \l__datatool_only_columns_seq
{

```

No inclusion list supplied. Columns will be ordered by column index, skipping omitted columns.

```

  \exp_args:NNv \int_set:Nn \l__datatool_max_cols_int { dtlcols@\dtldbname }
  \int_step_inline:nn { \l__datatool_max_cols_int }
  {
    \seq_if_in:NnF \l__datatool_omit_columns_seq { ##1 }
    {
      \seq_put_right:Nn \l__datatool_column_indexes_seq { ##1 }
    }
  }
}
{

```

Inclusion list supplied:

```

  \seq_set_eq:NN \l__datatool_column_indexes_seq
  \l__datatool_only_columns_seq
}

```

Total number of columns to be shown:

```

\int_set:Nn \l__datatool_max_cols_int
{ \seq_count:N \l__datatool_column_indexes_seq }

```

Make sure there are 1 or more columns.

```
\int_compare:nNnTF { \l__datatool_max_cols_int } > { \c_zero_int }
{
```

Get the alignment specifications.

```
\int_zero:N \dtlcolumnnum
\tl_if_empty:NF \l__datatool_user_align_tl
{
  \tl_set_eq:NN \l__datatool_align_tl \l__datatool_user_align_tl
}
\tl_if_empty:NTF \l__datatool_user_header_tl
{
  \bool_if:NF \l__datatool_include_header_bool
{
```

If no header, locally set this to a token list containing a single empty value to skip the default header formation, which is redundant in this case.

```
  \tl_set:Nn \l__datatool_user_header_tl { \c_empty_tl }
}
}
{
  \tl_set_eq:NN \l__datatool_row_tl \l__datatool_user_header_tl
}
\bool_lazy_or:nnT
{ \tl_if_empty_p:N \l__datatool_user_align_tl }
{ \tl_if_empty_p:N \l__datatool_user_header_tl }
{
  \seq_map_function:NN \l__datatool_column_indexes_seq
  \__datatool_display_db_metadata_fn:n
}
}
```

If there should be multiple database rows per tabular row, add copies.

```
\int_compare:nNnT
{ \l__datatool_display_per_row_int } > { \c_one_int }
{
  \bool_if:NT \l__datatool_include_header_bool
  {
    \tl_set:Nx \l__datatool_row_tl
    {
      \exp_args:Ne \tl_tail:n
      {
        \prg_replicate:nn { \l__datatool_display_per_row_int }
        { & \exp_not:V \l__datatool_row_tl }
      }
    }
  }
}
\tl_set:Nx \l__datatool_align_tl
{
  \prg_replicate:nn { \l__datatool_display_per_row_int }
  { \exp_not:V \l__datatool_align_tl }
}
}
```

Calculate database row count divided by replicate count. Note that this doesn't take into account any filtering.

```

\int_compare:nNnTF
  { \l_datatool_display_per_row_int } > { \c_one_int }
  {
    \int_set:Nn \l_datatool_display_tab_rows_int
      {
        \int_div_truncate:nn
          { \DTLrowcount { \dtldbname } }
          { \l_datatool_display_per_row_int }
      }
    \int_if_zero:nF
      {
        \int_mod:nn
          { \DTLrowcount { \dtldbname } }
          { \l_datatool_display_per_row_int }
      }
      {
        \int_incr:N \l_datatool_display_tab_rows_int
      }
  }
  {
    \int_set:Nn \l_datatool_display_tab_rows_int
      { \DTLrowcount { \dtldbname } }
  }

```

Initialisation successful, do the main body:

```

#1
}
{

```

Trigger an error or warning if no columns. Only a warning is issued if the database is empty (to allow for saving a database at the end of one run to be loaded at the next).

```

\@DTLifdbempty { \dtldbname }
  {
    \PackageWarning { datatool }
    { Can't ~ display ~ database ~ ``\dtldbname': ~ database ~ empty }
  }
  {
    \PackageError { datatool }
    { Can't ~ display ~ database ~ ``\dtldbname': ~ no ~ columns ~ available }
    {
      Either ~ the ~ database ~ is ~ empty ~ or ~ all ~ columns ~
      are ~ in ~ the ~ omit ~ list
    }
  }
}
}
}

```

Handler for iterating over column data:

```

\cs_new:Nn \__datatool_display_db_metadata_fn:n
{
  \int_incr:N \dtlcolumnnum
  \exp_args:NV \__datatool_get_col_type_header:nn \l__datatool_keydata_tl
  { #1 }
  \tl_if_empty:NT \l__datatool_user_align_tl
  {
    \dtladdalign \l__datatool_align_tl
    { \l__datatool_item_type_int }
    { \dtlcolumnnum }
    { \l__datatool_max_cols_int }
  }
  \tl_if_empty:NT \l__datatool_user_header_tl
  {
    \tl_if_empty:NF \l__datatool_row_tl
    {
      \tl_put_right:Nn \l__datatool_row_tl { & }
    }
    \tl_clear:N \l__datatool_tmpb_tl
    \dtladdheaderalign \l__datatool_tmpb_tl
    { \l__datatool_item_type_int }
    { \dtlcolumnnum }
    { \l__datatool_max_cols_int }
    \tl_put_right:Nn \l__datatool_row_tl { \dtlcolumnheader }
    \tl_put_right:Nx \l__datatool_row_tl
    { { \exp_not:V \l__datatool_tmpb_tl } }
    \tl_put_right:Nx \l__datatool_row_tl
    { { \exp_not:o { \l__datatool_item_head_tl } } }
  }
}
}

Row handler:
\cs_new:Nn \__datatool_display_db_row_fn:n
{
  Get the current row from the given row index. This sets the \dtlcurrentrow token
  register so that the condition can lookup values in the current row if required.
  \exp_args:Nv \@dtlgetrow { dtldb@\dtldbname } { #1 }
  \__datatool_if_display_row:NnT \l__datatool_content_tl { #1 }
  {
    \__datatool_display_db_row:Nn \l__datatool_content_tl { #1 }
  }
}
\cs_new:Nn \__datatool_display_db_row:Nn
{
  \int_compare:nNnTF { \l__datatool_row_idx_int } = { -1 }
  {
    \PackageWarning { datatool }
    { Omitting ~ row ~ #2: ~ not ~ found ~ in ~ database ~ `~\dtldbname' }
  }
}

```

```

\int_incr:N \dtlrownum
\int_compare:nNnT { \dtlrownum } > { \c_one_int }
{
  \int_compare:nNnTF
  { \l_datatool_display_per_row_int } > { \c_one_int }
  {
    \int_compare:nNnTF
    { \int_mod:nn { \dtlrownum } { \l_datatool_display_per_row_int } }
    = { \c_one_int }
    {
      \tl_put_right:NV #1 \dtldisplaycr
      \tl_put_right:NV #1 \dtldisplaystartrow
    }
    {
      \tl_put_right:Nn #1 { & }
    }
  }
  {
    \tl_put_right:NV #1 \dtldisplaycr
    \tl_put_right:NV #1 \dtldisplaystartrow
  }
}
\int_zero:N \l_datatool_col_idx_int
\seq_map_function:NN \l_datatool_column_indexes_seq
  \__datatool_display_db_col_fn:n
  \__datatool_display_post_row:Nn \l_datatool_content_tl { #2 }
}
}

```

Function handler when iterating over columns within a row.

```

\cs_new:Nn \__datatool_display_db_col_fn:n
{
  \int_compare:nNnT { \l_datatool_col_idx_int } > { 0 }
  {
    \tl_put_right:Nn \l_datatool_content_tl { & }
  }
}

```

This may not be the same as #1 if columns are missing or not in sequential order. Use #1 to reference the column.

```

\int_incr:N \l_datatool_col_idx_int

```

Get the entry for the current column and row.

```

\dtlgetentryfromcurrentrow { \l_datatool_item_value_tl } { #1 }
\exp_args:NV \__datatool_get_col_type:n \l_datatool_keydata_tl
{ #1 }

```

Ensure that any null values match their data type.

```

\int_case:nnF { \l_datatool_item_type_int }
{
  { \c_datatool_string_int }
  {

```

```

\tl_set:Nn \l__datatool_tmpb_tl { \dtlstringformat }
\datatool_if_null:NT \l__datatool_item_value_tl
{
\tl_set_eq:NN \l__datatool_item_value_tl \DTLstringnull
}
}
{ \c_datatool_integer_int }
{
\tl_set:Nn \l__datatool_tmpb_tl { \dtlintformat }
\datatool_if_null:NT \l__datatool_item_value_tl
{
\tl_set_eq:NN \l__datatool_item_value_tl \DTLnumbernull
}
}
{ \c_datatool_decimal_int }
{
\tl_set:Nn \l__datatool_tmpb_tl { \dtlrealformat }
\datatool_if_null:NT \l__datatool_item_value_tl
{
\tl_set_eq:NN \l__datatool_item_value_tl \DTLnumbernull
}
}
{ \c_datatool_currency_int }
{
\tl_set:Nn \l__datatool_tmpb_tl { \dtlcurrencyformat }
\datatool_if_null:NT \l__datatool_item_value_tl
{
\tl_set_eq:NN \l__datatool_item_value_tl \DTLnumbernull
}
}
{ \c_datatool_datetime_int }
{
\tl_set:Nn \l__datatool_tmpb_tl { \dtldatetimeformat }
\datatool_if_null:NT \l__datatool_item_value_tl
{
\tl_set_eq:NN \l__datatool_item_value_tl \DTLnumbernull
}
}
{ \c_datatool_date_int }
{
\tl_set:Nn \l__datatool_tmpb_tl { \dtldateformat }
\datatool_if_null:NT \l__datatool_item_value_tl
{
\tl_set_eq:NN \l__datatool_item_value_tl \DTLnumbernull
}
}
{ \c_datatool_time_int }
{
\tl_set:Nn \l__datatool_tmpb_tl { \dtltimeformat }
\datatool_if_null:NT \l__datatool_item_value_tl

```

```

        {
          \tl_set_eq:NN \l__datatool_item_value_tl \DTLnumbernull
        }
      }
    }
  {
    \tl_set:Nn \l__datatool_tmpb_tl { \dtlstringformat }
    \datatool_if_null:NT \l__datatool_item_value_tl
    {
      \tl_set_eq:NN \l__datatool_item_value_tl \DTLstringnull
    }
  }
}

```

Add the item to the content list variable:

```

  \__datatool_display_add_item:NVVVVVn
  \l__datatool_content_tl
  \l__datatool_item_value_tl % item
  \l__datatool_tmpb_tl % fmt-cs
  \l__datatool_item_type_int % type
  \dtlrownum % row num
  \l__datatool_row_idx_int % row idx
  \l__datatool_col_idx_int % col num
  { #1 } % col idx
}

```

```

\DTLdisplaydbAddItem<content-tl>{<item>}{<fmt-cs>}{<type>}{<row>}{<row idx>}{<col>}{<col idx>}

```

\DTLdisplaydbAddItem

Add the column item:

```

\NewDocumentCommand \DTLdisplaydbAddItem { m m m m m m m m }
{
  \tl_put_right:Nn #1 { #3 { #2 } }
}
\cs_new:Nn \__datatool_display_add_item:Nnnnnnnn
{
  \DTLdisplaydbAddItem #1 { #2 } { #3 } { #4 } { #5 } { #6 } { #7 } { #8 }
}
\cs_generate_variant:Nn \__datatool_display_add_item:Nnnnnnnn
{ NVVVVVVn }

```

\dtldisplaylongdbenv

```

\newcommand{\dtldisplaylongdbenv}{longtable}

```

```

\DTLdisplaydblongAddBegin{<content tl>}{<align token list>}{<header token list>}

```

\DTLdisplaylongdbAddBegin

```

\NewDocumentCommand \DTLdisplaylongdbAddBegin { m m m }
{
  \tl_put_right:Nx #1
  {
    \exp_not:N \begin { \dtldisplaylongdbenv }
  }
  \tl_put_right:Nn #1
  {
    { #2 }
  }
}

```

Add the header row. Is there a caption?

```

\tl_if_eq:NnTF \l_datatool_caption_tl { \c_novalue_tl }
{

```

No caption.

```

  \bool_if:NT \l_datatool_include_header_bool
  {
    \tl_put_right:NV #1 \dtldisplaystarttab
    \tl_put_right:Nn #1 { #3 }
    \tl_put_right:NV #1 \l_datatool_post_head_tl
    \tl_if_empty:NF \dtldisplayafterhead
    {
      \tl_put_right:NV #1 \dtldisplaycr
      \tl_put_right:NV #1 \dtldisplayafterhead
    }
    \tl_put_right:Nn #1 { \endhead }
  }
}
{

```

Caption. Is there a short caption?

```

  \tl_put_right:Nn #1 { \caption }
  \tl_if_eq:NnF \l_datatool_short_caption_tl { \c_novalue_tl }
  {
    \tl_put_right:Nn #1 { [ ] }
    \tl_put_right:NV #1 \l_datatool_short_caption_tl
    \tl_put_right:Nn #1 { ] }
  }
  \tl_put_right:Nx #1 { { \exp_not:o { \l_datatool_caption_tl } } }

```

Is there a label?

```

  \tl_if_eq:NnF \l_datatool_label_tl { \c_novalue_tl }
  {
    \tl_put_right:Nx #1
    {
      \exp_not:N \label { \l_datatool_label_tl }
    }
  }
  \bool_if:NT \l_datatool_include_header_bool
  {

```

```

\tl_put_right:NV #1 \dtldisplaycr
\tl_put_right:NV #1 \dtldisplaystarttab
\tl_put_right:Nn #1 { #3 }
\tl_put_right:NV #1 \l_datatool_post_head_tl
\tl_if_empty:NF \dtldisplayafterhead
{
  \tl_put_right:NV #1 \dtldisplaycr
  \tl_put_right:NV #1 \dtldisplayafterhead
}
}
\tl_put_right:Nn #1 { \endfirsthead }
Caption. Is there a continuation caption?
\tl_put_right:Nn #1 { \caption [] }
\tl_if_eq:NnTF \l_datatool_cont_caption_tl { \c_novalue_tl }
{
  \tl_put_right:Nx #1 { { \exp_not:o { \l_datatool_caption_tl } } }
}
{
  \tl_put_right:Nx #1 { { \exp_not:o { \l_datatool_cont_caption_tl } } }
}
\bool_if:NT \l_datatool_include_header_bool
{
  \tl_put_right:NV #1 \dtldisplaycr
  \tl_put_right:NV #1 \dtldisplaystarttab
  \tl_put_right:Nn #1 { #3 }
  \tl_put_right:NV #1 \l_datatool_post_head_tl
  \tl_if_empty:NF \dtldisplayafterhead
  {
    \tl_put_right:NV #1 \dtldisplaycr
    \tl_put_right:NV #1 \dtldisplayafterhead
  }
}
\tl_put_right:Nn #1 { \endhead }
}
Is there a footer?
\tl_if_eq:NnF \l_datatool_foot_tl { \c_novalue_tl }
{
  \tl_put_right:NV #1 \l_datatool_foot_tl
  \tl_put_right:Nn #1 { \endfoot }
}
\tl_if_eq:NnF \l_datatool_last_foot_tl { \c_novalue_tl }
{
  \tl_put_right:NV #1 \l_datatool_last_foot_tl
  \tl_put_right:Nn #1 { \endlastfoot }
}
}

```

`\DTLdisplaylongdbAddEnd{<content tL>}`

`\DTLdisplaylongdbAddEnd`

```
\NewDocumentCommand \DTLdisplaylongdbAddEnd { m }
{
  \tl_put_right:NV #1 \dtldisplayendtab
  \tl_put_right:Nx #1 { \exp_not:N \end { \dtldisplaylongdbenv } }
}
```

`\DTLdisplaylongdb[<options>]{<db>}`

`\DTLdisplaylongdb`

Displays the database `<db>` in a longtable environment. (User needs to load `longtable`).

```
\NewDocumentCommand \DTLdisplaylongdb { o m }
{
  \DTLifdbexists { #2 }
  {
    \group_begin:
    \IfValueT { #1 }
    {
      \keys_set_filter:nnnN { datatool/display } { tabular } { #1 }
      \l_datatool_tmpb_tl
      \tl_if_empty:NF \l_datatool_tmpb_tl
      {
        \PackageWarning { datatool }
        {
          Ignoring ~ unsupported ~ \token_to_str:N\DTLdisplaylongdb
          \c_space_tl option(s): ~ \exp_not:o { \l_datatool_tmpb_tl }
        }
      }
    }
    \tl_set:Nx \dtldbname { #2 }
    \__datatool_display_long_db:
    \group_end:
  }
  {
    \PackageError { datatool }
    { Database ~ `#2' ~ doesn't ~ exist }
    { }
  }
}
```

Inner command:

```
\cs_new:Nn \__datatool_display_long_db:
{
```

Initialise and check supplied options make sense:

```

    \__datatool_if_display_init:T
    {
      \l__datatool_init_display_tl

```

Start constructing the content token list. Add the begin part and header row:

```

    \exp_args:NNVV \DTLdisplaylongdbAddBegin \l__datatool_content_tl
    \l__datatool_align_tl \l__datatool_row_tl

```

The rest is much the same as for `\DTLdisplaydb`:

```

    \int_zero:N \dtlrownum
    \int_zero:N \l__datatool_row_idx_int

```

Iterate over all rows:

```

    \__datatool_display_loop:

```

Add the end part:

```

    \DTLdisplaylongdbAddEnd \l__datatool_content_tl

```

Do the content:

```

    \l__datatool_pre_display_tl
    \l__datatool_content_tl
  }
}

```

12.8 Editing Databases

```
\@dtl@toksA
```

```
\newtoks\@dtl@toksA
```

```
\@dtl@toksB
```

```
\newtoks\@dtl@toksB
```

```
\dtlswaprows{<db>}{<row1 idx>}{<row2 idx>}
```

```
\dtlswaprows
```

Swaps the rows with indices `<row1 idx>` and `<row2 idx>` in the database `<db>`. (Doesn't check if data base exists or if indices are out of bounds.)

```

\newrobustcmd*{\dtlswaprows}[3]{%
  \ifnum#2=#3\relax

```

Attempt to swap row with itself: do nothing.

```

  \else

```

Let row A be the row with the lower index and row B be the row with ther higher index.

```

  \ifnum#2<#3\relax
    \edef\@dtl@rowAidx{\number#2}%
    \edef\@dtl@rowBidx{\number#3}%
  \else
    \edef\@dtl@rowAidx{\number#3}%
    \edef\@dtl@rowBidx{\number#2}%
  \fi

```

Split the database around row A.

```
\edef\@dtl@dospplit{\noexpand\dtlgetrow{#1}{\@dtl@rowAidx}}%  
\@dtl@dospplit
```

Store first part of database in \@dtl@firstpart.

```
\expandafter\def\expandafter\@dtl@firstpart\expandafter  
{\the\dtlbeforerow}%
```

Store row A in \@dtl@toksA.

```
\@dtl@toksA=\dtlcurrentrow
```

Split the second part (everything after row A).

```
\edef\@dtl@dospplit{\noexpand\dtlgetrow  
{\the\dtlafterrow}{\@dtl@rowBidx}}%  
\@dtl@dospplit
```

Store the mid part (everything between row A and row B)

```
\expandafter\def\expandafter\@dtl@secondpart\expandafter  
{\the\dtlbeforerow}%
```

Store row B in \@dtl@toksB.

```
\@dtl@toksB=\dtlcurrentrow
```

Store the last part (everything after row B).

```
\expandafter\def\expandafter\@dtl@thirdpart\expandafter  
{\the\dtlafterrow}%
```

Reconstruct database: store first part in \toks@

```
\toks@=\expandafter{\@dtl@firstpart}%
```

Store mid part in \dtl@toks

```
\@dtl@toks=\expandafter{\@dtl@secondpart}%
```

Format data for first part, row B and mid part.

```
\edef\@dtl@tmp{\the\toks@  
\__datatool_row_markup:VV  
\@dtl@rowAidx  
\@dtl@toksB  
\the\@dtl@toks}%
```

Store data so far in \toks@.

```
\toks@=\expandafter{\@dtl@tmp}%
```

Store last part in \dtl@toks.

```
\@dtl@toks=\expandafter{\@dtl@thirdpart}%
```

Format row A and end part.

```
\edef\@dtl@tmp{\the\toks@  
\__datatool_row_markup:VV  
\@dtl@rowBidx  
\@dtl@toksA  
\the\@dtl@toks  
}%
```

Update the database according to global setting.

```
    \__datatool_dtlldb_set:nV { #1 } \@dtl@tmp
  \fi
}
```

```
\dtl@decrementrows{<toks>}{<n>}
```

\dtl@decrementrows

decrement by 1 all rows in <toks> with row index above <n>. NB this doesn't change the database row count.

```
\newcommand*{\dtl@decrementrows}[2]{%
  \def\@dtl@newlist{}%
  \edef\@dtl@min{\number#2}%
  \expandafter\@dtl@decrementrows\the#1%
  \db@row@elt@w%
  \db@row@id@w \@nil\db@row@id@end@%
  \db@row@id@w \@nil\db@row@id@end@%
  \db@row@elt@end@%
  \@nil
  #1=\expandafter{\@dtl@newlist}%
}
```

\@dtl@decrementrows

```
\def\@dtl@decrementrows\db@row@elt@w\db@row@id@w #1\db@row@id@end@%
#2\db@row@id@w #3\db@row@id@end@\db@row@elt@end@#4\@nil{%
  \def\@dtl@thisrow{#1}%
  \ifx\@dtl@thisrow\@nnil
    \let\@dtl@donextdec=\@dtl@gobbletonil
  \else
    \ifnum\@dtl@thisrow>\@dtl@min
      \@dtl@tmpcount=\@dtl@thisrow\relax
      \int_decr:N \@dtl@tmpcount
      \toks@{#2}%
      \@dtl@toks=\expandafter{\@dtl@newlist}%
      \edef\@dtl@newlist{\the\@dtl@toks
        \__datatool_row_markup:VV
        \@dtl@tmpcount
        \toks@
      }%
    \else
      \toks@{#2}%
      \@dtl@toks=\expandafter{\@dtl@newlist}%
      \edef\@dtl@newlist{\the\@dtl@toks
        \__datatool_row_markup:nV
        { #1 }
        \toks@
      }%
    \fi
    \let\@dtl@donextdec=\@dtl@decrementrows
  }
```

```

\fi
\@dtl@donextdec#4\@nil
}
\ExplSyntaxOff

```

```
\DTLremove row{<db>}{<row index>}
```

\DTLremove row

```

Remove row with given index from database named <db>.
\newcommand*{\DTLremove row}[2]{%
Check database exists
\DTLifdbexists{#1}%
{%
Check index if index is out of bounds
\ifnum#2>0\relax
Check if data base has at least <row index> rows
\expandafter\ifnum\csname dtlrows@#1\endcsname<#2\relax
\expandafter\ifnum\csname dtlrows@#1\endcsname=1\relax
\PackageError{datatool}{Can't remove row ``\number#2' from
database `#1': no such row}{Database `#1' only has
1 row}%
\else
\PackageError{datatool}{Can't remove row ``\number#2' from
database `#1': no such row}{Database `#1' only has
\expandafter\number\csname dtlrows@#1\endcsname\space
rows}%
\fi
\else
\@DTLremove row{#1}{#2}%
\fi
\else
\PackageError{datatool}{Can't remove row \number#2: index
out of bounds}{Row indices start at 1}%
\fi
}%
}%
\PackageError{datatool}{Can't remove row: database `#1' doesn't
exist}{}%
}%
}
\ExplSyntaxOn

```

```
\@DTLremove row{<db>}{<row index>}
```

\@DTLremove row

Doesn't perform any checks for the existence of the database or if the index is in range.

```
\newcommand*{\@DTLremoverow}[2]{%
Get row from data base
    \edef\dtl@dogetrow{\noexpand\dtlgetrow{#1}{\number#2}}%
    \dtl@dogetrow
Update the row indices
    \expandafter\dtl@decrementrows\expandafter
    {\dtlbeforerow}{#2}%
    \expandafter\dtl@decrementrows\expandafter
    {\dtlafterrow}{#2}%
Reconstruct database according to global setting.
    \__datatool_dtlldb_set:nx { #1 }
    {
    \exp_not:V \dtlbeforerow
    \exp_not:V \dtlafterrow
    }
Decrement row counter.
    \bool_if:NTF \l__datatool_db_global_bool
    {
    \int_gdecr:c { dtlrows@ #1 }
    }
    {
    \int_decr:c { dtlrows@ #1 }
    }
}
```

12.9 Database Functions

```
\DTLsumforkeys[condition][assign list]{db list}
{key list}{cmd}
```

\DTLsumforkeys

Sums all entries for key *key* over all databases listed in *db list*, and stores in *cmd*, which must be a control sequence. The first argument *condition* is the same as that for \DTLforeach. The second optional argument provides an assignment list to pass to \DTLforeach in case extra information is need by *condition*. Version 3.0: switched to using \DTLmapdata

```
\NewDocumentCommand \DTLsumforkeys { o o m m m }
{
```

Scope to prevent problems if nested.

```
\group_begin:
\fp_zero:N \l__datatool_total_fp
```

Initialise.

```
\int_set_eq:NN
```

```

    \@dtl@datatype
    \c_datatool_unknown_int
\tl_clear:N \l__datatool_datum_currency_tl
\IfValueTF { #1 }
{
  \cs_set:Nn \__datatool_filter:n
  {
    \ifthenelse { #1 } { ##1 } { }
  }
}
{
  \cs_set_eq:NN \__datatool_filter:n \use:n
}
Iterate over all the listed data bases:
\clist_map_inline:nn { #3 }
{
Iterate over the current database (read only):
  \DTLmapdata [ name = { ##1 }, read-only ]
  {
    \IfValueT { #2 }
    {
      \DTLmapgetvalues { #2 }
    }
    \__datatool_filter:n
    {
Iterate through key list.
      \clist_map_variable:nNn
      { #4 }
      \l__datatool_item_key_tl
      {
        \DTLmapget
        {
          key = \l__datatool_item_key_tl,
          return = \l__datatool_item_value_tl
        }
        \datatool_if_null:NF \l__datatool_item_value_tl
        {
          \__datatool_parse:N
          \l__datatool_item_value_tl
        }
      }
    }
  }
  Check that the value is numerical.
  \datatool_if_numeric_datum_type:nT { \@dtl@datatype }
  {
Save previous settings.
      \tl_set_eq:NN
      \l__datatool_tmp_currency_tl
      \l__datatool_datum_currency_tl
      \int_set_eq:NN

```


Iterate over the database (read only):

```
\DTLmapdata [ name = { #1 }, read-only ]
{
  \DTLmapget
  {
    key = { #2 },
    return = \l_datatool_item_value_tl
  }
  \datatool_if_null:NF \l_datatool_item_value_tl
  {
    \__datatool_parse:N
    \l_datatool_item_value_tl
```

Check that the value is numerical.

```
\datatool_if_numeric_datum_type:nT { \@dtl@datatype }
{
```

Save previous settings.

```
\tl_set_eq:NN
  \l_datatool_tmp_currency_tl
  \l_datatool_datum_currency_tl
\int_set_eq:NN
  \l_datatool_tmp_datatype_int
  \@dtl@datatype
```

Obtain this item's numeric value as a floating point variable.

```
\datatool_set_fp:NV \l_datatool_datum_value_fp
  \l_datatool_item_value_tl
\fp_add:Nn \l_datatool_total_fp
  { \l_datatool_datum_value_fp }
```

Update data type, if applicable.

```
\__datatool_update_datatype:
}
}
```

Convert floating point variable and format result.

```
\tl_set:Ne \l_datatool_result_tl
  { \fp_to_decimal:N \l_datatool_total_fp }
\__datatool_assign_result:N #3
```

Expand to the formatted value if store-datum = false.

```
\bool_if:NF \l_datatool_db_store_datum_bool
  { \tl_set:Nx #3 { #3 } }
```

End scope.

```
\exp_args:NNNV
  \group_end: \tl_set:Nn #3 #3
}
```

\@dtl@elements Count register to keep track of number of elements. TODO remove.

```
\newcount\@dtl@elements
```

```
\DTLmeanforkeys[condition][assign list]{db list}
{key list}{cmd}
```

\DTLmeanforkeys

Computes the arithmetic mean of all entries for each key in *key list* over all databases in *db list*, and stores in *cmd*, which must be a control sequence. The first argument *condition* is the same as that for \DTLforeach. The second optional argument allows an assignment list to be passed to \DTLmapgetvalues. Version 3.0: now uses \DTLmapdata.

```
\NewDocumentCommand \DTLmeanforkeys { o o m m m }
{%
```

Scope to prevent problems if nested.

```
\group_begin:
\int_zero:N \l__datatool_count_int
\fp_zero:N \l__datatool_total_fp
```

Initialise.

```
\int_set_eq:NN
\@dtl@datatype
\c_datatool_unknown_int
\tl_clear:N \l__datatool_datum_currency_tl
\seq_clear:N \l__datatool_tmpb_seq
\IfValueTF { #1 }
{
\cs_set:Nn \__datatool_filter:n
{
\ifthenelse { #1 } { ##1 } { }
}
}
\cs_set_eq:NN \__datatool_filter:n \use:n
}
\__datatool_filtered_calc_mean:nnn { #2 } { #3 } { #4 }
```

Convert floating point variable and format result.

```
\tl_set:Ne \l__datatool_result_tl
{ \fp_to_decimal:N \l__datatool_mean_fp }
\__datatool_assign_result:N #5
```

Expand to the formatted value if store-datum = false.

```
\bool_if:NF \l__datatool_db_store_datum_bool
{ \tl_set:Nx #5 { #5 } }
```

End scope.

```
\exp_args:NNNV
\group_end: \tl_set:Nn #5 #5
}

\cs_new:Nn \__datatool_filtered_calc_mean:nnn
{
```

Iterate over all the listed data bases:

```
\clist_map_inline:nn { #2 }  
{
```

Iterate over the current database (read only):

```
\DTLmapdata [ name = { ##1 }, read-only ]  
{  
  \IfValueT { #1 }  
  {  
    \DTLmapgetvalues { #1 }  
  }  
  \__datatool_filter:n  
  {
```

Iterate through key list.

```
\clist_map_variable:nNn  
{ #3 }  
\l__datatool_item_key_tl  
{  
  \DTLmapget  
  {  
    key = \l__datatool_item_key_tl,  
    return = \l__datatool_item_value_tl  
  }  
  \datatool_if_null:NF \l__datatool_item_value_tl  
  {  
    \__datatool_parse:N  
    \l__datatool_item_value_tl
```

Check that the value is numerical.

```
\datatool_if_numeric_datum_type:nT { \@dtl@datatype }  
{
```

Save previous settings.

```
\tl_set_eq:NN  
  \l__datatool_tmp_currency_tl  
  \l__datatool_datum_currency_tl  
\int_set_eq:NN  
  \l__datatool_tmp_datatype_int  
  \@dtl@datatype
```

Increment item count.

```
\int_incr:N \l__datatool_count_int
```

Obtain this item's numeric value as a floating point variable.

```
\datatool_set_fp:NV \l__datatool_datum_value_fp  
  \l__datatool_item_value_tl  
\fp_add:Nn \l__datatool_total_fp  
  { \l__datatool_datum_value_fp }  
\seq_put_right:Nx \l__datatool_tmpb_seq  
  { \DTLdatumvalue { \l__datatool_item_value_tl } }
```



```

\tl_clear:N \l__datatool_datum_currency_tl
\seq_clear:N \l__datatool_tmpb_seq
\__datatool_column_calc_mean:nn { #1 } { #2 }
Convert floating point variable and format result.
\tl_set:Ne \l__datatool_result_tl
{ \fp_to_decimal:N \l__datatool_mean_fp }
\__datatool_assign_result:N #3
Expand to the formatted value if store-datum = false.
\bool_if:NF \l__datatool_db_store_datum_bool
{ \tl_set:Nx #3 { #3 } }
End scope.
\exp_args:NNNV
\group_end: \tl_set:Nn #3 #3
}
{
\PackageError { datatool }
{
Database ~ `#1' ~ isn't ~ defined
}
{ }
}
}
\cs_new:Nn \__datatool_column_calc_mean:nn
{
\DTLmapdata [ name = { #1 }, read-only ]
{
\DTLmapget
{
key = { #2 },
return = \l__datatool_item_value_tl
}
\datatool_if_null:NF \l__datatool_item_value_tl
{
\__datatool_parse:N
\l__datatool_item_value_tl
}
}
}
Check that the value is numerical.
\datatool_if_numeric_datum_type:nT { \@dtl@datatype }
{
Save previous settings.
\tl_set_eq:NN
\l__datatool_tmp_currency_tl
\l__datatool_datum_currency_tl
\int_set_eq:NN
\l__datatool_tmp_datatype_int
\@dtl@datatype

```

Increment item count.

```
\int_incr:N \l__datatool_count_int
```

Obtain this item's numeric value as a floating point variable.

```
\datatool_set_fp:NV \l__datatool_datum_value_fp
\l__datatool_item_value_tl
\fp_add:Nn \l__datatool_total_fp
{ \l__datatool_datum_value_fp }
\seq_put_right:Nx \l__datatool_tmpb_seq
{ \DTLdatumvalue { \l__datatool_item_value_tl } }
```

Update data type, if applicable.

```
\__datatool_update_datatype:
}
}
\int_if_zero:nTF { \l__datatool_count_int }
{
  \PackageError
  { datatool }
  {
    no ~ numeric ~ data ~ found ~ in ~ column ~ labelled ~ `#2' ~
    in ~ database ~ `#1'
  }
  { }
  \fp_zero:N \l__datatool_mean_fp
}
{
  \fp_set:Nn
  \l__datatool_mean_fp
  { \l__datatool_total_fp / \l__datatool_count_int }
}
}
```

```
\DTLvarianceforkeys[condition][assign list]{db
list}{key list}{cmd}
```

\DTLvarianceforkeys

Computes the variance of all entries for each key in *key list* over all databases in *db list*, and stores in *cmd*, which must be a control sequence. The first optional argument *condition* is the same as that for \DTLforeach. The second optional argument is an assignment list to pass to \DTLmapgetvalues in case it is required for the condition.

Version 3.0: changed to use \DTLmapdata

```
\NewDocumentCommand \DTLvarianceforkeys
{ o o m m m }
{
```

Scope to prevent problems if nested.

```
\group_begin:
\int_zero:N \l__datatool_count_int
```

```

\fp_zero:N \l_datatool_total_fp
Initialise.
\int_set_eq:NN
  \@dtl@datatype
  \c_datatool_unknown_int
\tl_clear:N \l_datatool_datum_currency_tl
\seq_clear:N \l_datatool_tmpb_seq
\IfValueTF { #1 }
{
  \cs_set:Nn \__datatool_filter:n
  {
    \ifthenelse { #1 } { ##1 } { }
  }
}
{
  \cs_set_eq:NN \__datatool_filter:n \use:n
}
}
The mean needs to be calculated first.
  \__datatool_filtered_calc_mean:nnn { #2 } { #3 } { #4 }
\int_if_zero:nF { \l_datatool_count_int }
{
Calculate the variance.
  \fp_zero:N \l_datatool_tmpa_fp
  \seq_map_inline:Nn \l_datatool_tmpb_seq
  {
    \fp_set:Nn \l_datatool_tmpb_fp
    {
      ##1 - \l_datatool_mean_fp
    }
    \fp_add:Nn \l_datatool_tmpa_fp
    {
      \l_datatool_tmpb_fp * \l_datatool_tmpb_fp
    }
  }
  \fp_set:Nn \l_datatool_tmpa_fp
  { \l_datatool_tmpa_fp / \l_datatool_count_int }
Convert floating point variable and format result.
  \tl_set:Ne \l_datatool_result_tl
  { \fp_to_decimal:N \l_datatool_tmpa_fp }
  \__datatool_assign_result:N #5
Expand to the formatted value if store-datum = false.
  \bool_if:NF \l_datatool_db_store_datum_bool
  { \tl_set:Nx #5 { #5 } }
}
End scope.
\exp_args:NNNV

```

```

    \group_end: \tl_set:Nn #5 #5
  }

```

\@dtlvarianceforkeys Version 3.0: removed.

```

\DTLvarianceforcolumn{<db>}{<key>}{<cmd>}

```

\DTLvarianceforcolumn

Quicker version of \DTLvarianceforkeys that just computes the variance over one column (specified by <key>) for a single database (specified by <db>) and stores the result in <cmd>. Version 3.0: switched to \DTLmapdata.

```

\NewDocumentCommand \DTLvarianceforcolumn { m m m }
{

```

Check data base exists

```

  \DTLifdbexists { #1 }
  {

```

Scope to prevent problems if nested.

```

    \group_begin:
    \int_zero:N \l__datatool_count_int
    \fp_zero:N \l__datatool_total_fp

```

Initialise.

```

    \int_set_eq:NN
      \@dtl@datatype
      \c_datatool_unknown_int
    \tl_clear:N \l__datatool_datum_currency_tl

```

The mean needs to be calculated first.

```

    \__datatool_column_calc_mean:nn { #1 } { #2 }
    \int_if_zero:nF { \l__datatool_count_int }
    {

```

Calculate the variance.

```

      \fp_zero:N \l__datatool_tmpa_fp
      \seq_map_inline:Nn \l__datatool_tmpb_seq
      {
        \fp_set:Nn \l__datatool_tmpb_fp
        {
          ##1 - \l__datatool_mean_fp
        }
        \fp_add:Nn \l__datatool_tmpa_fp
        {
          \l__datatool_tmpb_fp * \l__datatool_tmpb_fp
        }
      }
      \fp_set:Nn \l__datatool_tmpa_fp
      { \l__datatool_tmpa_fp / \l__datatool_count_int }

```

Convert floating point variable and format result.

```
\tl_set:N\l__datatool_result_tl  
  { \fp_to_decimal:N \l__datatool_tmpa_fp }  
\__datatool_assign_result:N #3
```

Expand to the formatted value if store-datum = false.

```
\bool_if:N\l__datatool_db_store_datum_bool  
  { \tl_set:Nx #3 { #3 } }  
}
```

End scope.

```
\exp_args:NNNV  
  \group_end: \tl_set:Nn #3 #3  
}  
{  
  \PackageError { datatool }  
  {  
    Database ~ `#1' ~ isn't ~ defined  
  }  
  { }  
}  
}
```

```
\DTLsdforkeys[<condition>][<assign list>]{<db list>}  
{<key list>}{<cmd>}
```

\DTLsdforkeys

Computes the standard deviation of all entries for each key in *<key list>* over all databases in *<db list>*, and stores in *<cmd>*, which must be a control sequence. The first optional argument *<condition>* is the same as that for \DTLmapgetvalues. The second optional argument is an assignment list for \DTLforeach in case it is needed for the condition. Version 3.0: now uses \DTLmapdata.

```
\NewDocumentCommand \DTLsdforkeys  
  { o o m m m }  
{
```

Scope to prevent problems if nested.

```
\group_begin:  
\int_zero:N \l__datatool_count_int  
\fp_zero:N \l__datatool_total_fp
```

Initialise.

```
\int_set_eq:NN  
  \@dtl@datatype  
  \c_datatool_unknown_int  
\tl_clear:N \l__datatool_datum_currency_tl  
\seq_clear:N \l__datatool_tmpb_seq  
\IfValueTF { #1 }  
{  
  \cs_set:Nn \__datatool_filter:n
```

```

    {
      \ifthenelse { #1 } { ##1 } { }
    }
  }
  {
    \cs_set_eq:NN \__datatool_filter:n \use:n
  }

```

The mean needs to be calculated first.

```

  \__datatool_filtered_calc_mean:nnn { #2 } { #3 } { #4 }
  \int_if_zero:nF { \l__datatool_count_int }
  {

```

Calculate the variance.

```

  \fp_zero:N \l__datatool_tmpa_fp
  \seq_map_inline:Nn \l__datatool_tmpb_seq
  {
    \fp_set:Nn \l__datatool_tmpb_fp
    {
      ##1 - \l__datatool_mean_fp
    }
    \fp_add:Nn \l__datatool_tmpa_fp
    {
      \l__datatool_tmpb_fp * \l__datatool_tmpb_fp
    }
  }
  \fp_set:Nn \l__datatool_tmpa_fp
  { sqrt ( \l__datatool_tmpa_fp / \l__datatool_count_int ) }

```

Convert floating point variable and format result.

```

  \tl_set:Ne \l__datatool_result_tl
  { \fp_to_decimal:N \l__datatool_tmpa_fp }
  \__datatool_assign_result:N #5

```

Expand to the formatted value if store-datum = false.

```

  \bool_if:NF \l__datatool_db_store_datum_bool
  { \tl_set:Nx #5 { #5 } }
}

```

End scope.

```

  \exp_args:NNNV
  \group_end: \tl_set:Nn #5 #5
}

```

\@dtLsdforkeys Version 3.0: removed.

```

\DTLsdforcolumn{<db>}{<key>}{<cmd>}

```

\DTLsdforcolumn

Quicker version of \DTLsdforkeys that just computes the standard deviation over one column (specified by <key>) for a single database (specified by <db>) and stores the result in <cmd>. Version 3.0: now uses \DTLmapdata.

```

\NewDocumentCommand \DTLsdforcolumn { m m m }
{
Check data base exists
  \DTLifdbexists { #1 }
  {
Scope to prevent problems if nested.
  \group_begin:
  \int_zero:N \l__datatool_count_int
  \fp_zero:N \l__datatool_total_fp
Initialise.
  \int_set_eq:NN
  \@dtl@datatype
  \c_datatool_unknown_int
  \tl_clear:N \l__datatool_datum_currency_tl
The mean needs to be calculated first.
  \__datatool_column_calc_mean:nn { #1 } { #2 }
  \int_if_zero:nF { \l__datatool_count_int }
  {
Calculate the variance.
  \fp_zero:N \l__datatool_tmpa_fp
  \seq_map_inline:Nn \l__datatool_tmpb_seq
  {
  \fp_set:Nn \l__datatool_tmpb_fp
  {
  ##1 - \l__datatool_mean_fp
  }
  \fp_add:Nn \l__datatool_tmpa_fp
  {
  \l__datatool_tmpb_fp * \l__datatool_tmpb_fp
  }
  }
  \fp_set:Nn \l__datatool_tmpa_fp
  { sqrt ( \l__datatool_tmpa_fp / \l__datatool_count_int ) }
Convert floating point variable and format result.
  \tl_set:Ne \l__datatool_result_tl
  { \fp_to_decimal:N \l__datatool_tmpa_fp }
  \__datatool_assign_result:N #3
Expand to the formatted value if store-datum = false.
  \bool_if:NF \l__datatool_db_store_datum_bool
  { \tl_set:Nx #3 { #3 } }
  }
End scope.
  \exp_args:NNNV
  \group_end: \tl_set:Nn #3 #3
}

```

```

    {
      \PackageError { datatool }
      {
        Database ~ `#1' ~ isn't ~ defined
      }
    }
  }
}

```

```

\DTLminforkeys[condition][assign list]{db list}
{key list}{cmd}

```

\DTLminforkeys

Determines the minimum over all entries for each key in *key list* over all databases in *db list*, and stores in *cmd*, which must be a control sequence. The first optional argument *condition* is the same as that for \DTLforeach. The second optional argument is an assignment list for \DTLforeach in the event that extra information is need for the condition. Version 3.0: changed to use \DTLmapdata

```

\NewDocumentCommand \DTLminforkeys { o o m m m }
{

```

Scope to prevent problems if nested.

```

\group_begin:
\fp_set_eq:NN \__datatool_min_fp \c_inf_fp
\tl_clear:N #5
\IfValueTF { #1 }
{
  \cs_set:Nn \__datatool_filter:n
  {
    \ifthenelse { #1 } { ##1 } { }
  }
}
{
  \cs_set_eq:NN \__datatool_filter:n \use:n
}

```

Iterate over all the listed data bases:

```

\clist_map_inline:nn { #3 }
{

```

Iterate over the current database (read only):

```

\DTLmapdata [ name = { ##1 }, read-only ]
{
  \IfValueT { #2 }
  {
    \DTLmapgetvalues { #2 }
  }
  \__datatool_filter:n
  {

```



```

    }
End scope.
  \exp_args:NNNV
  \group_end: \tl_set:Nn #5 #5
}

```

\@dtlminforkeys Version 3.0: removed.

```
\DTLminforcolumn{<db>}{<key>}{<cmd>}
```

\DTLminforcolumn

Quicker version of \DTLminforkeys that just finds the minimum value in one column (specified by <key>) for a single database (specified by <db>) and stores the result in <cmd>. Version 3.0: switched to using \DTLmapdata

```
\NewDocumentCommand \DTLminforcolumn { m m m }
{
```

Check data base exists

```
\DTLifdbexists{#1}%
{
```

Scope to prevent problems if nested.

```
\group_begin:
\fp_set_eq:NN \l__datatool_min_fp \c_inf_fp
\tl_clear:N #3
```

Iterate over the database (read only):

```
\DTLmapdata [ name = { #1 }, read-only ]
{
  \DTLmapget
  {
    key = { #2 },
    return = \l__datatool_item_value_tl
  }
  \datatool_if_null:NF \l__datatool_item_value_tl
  {
    \__datatool_parse:N
    \l__datatool_item_value_tl
  }
}
```

Check that the value is numerical.

```
\datatool_if_numeric_datum_type:nT { \@dtl@datatype }
{
  \datatool_set_fp:NV \l__datatool_datum_value_fp
  \l__datatool_item_value_tl
  \fp_compare:nNnT
  { \l__datatool_min_fp }
  >
  { \l__datatool_datum_value_fp }
}
\fp_set_eq:NN
```

```

        \l_datatool_min_fp
        \l_datatool_datum_value_fp
        \tl_set_eq:NN #3 \l_datatool_item_value_tl
    }
}
}
\if_empty:NTF #3
{
  \PackageError { datatool }
  {
    no ~ numeric ~ data ~ found ~ in ~ column ~ `#2' ~
    for ~ database ~ `#1'
  }
  {}
}
{
  \bool_if:NF \l_datatool_db_store_datum_bool
  {
    \tl_set:Nx #3 { #3 }
  }
}
}
End scope.
\exp_args:NNNV
\group_end: \tl_set:Nn #3 #3
}
data base doesn't exist
{
  \PackageError {datatool}
  { Database ~ `#1' ~ doesn't ~ exist}
  {}
}
}
}

```

```

\DTLmaxforkeys[condition][assign list]{db list}
{key list}{cmd}

```

\DTLmaxforkeys

Determines the maximum over all entries for each key in *key list* over all databases in *db list*, and stores in *cmd*, which must be a control sequence. The first optional argument (*condition*) is the same as that for \DTLforeach. The second optional argument is an assignment list to pass to \DTLforeach in the event that extra information is required in the condition. Version 3.0: changed to use \DTLmapdata

```

\NewDocumentCommand \DTLmaxforkeys { o o m m m }
{

```

Scope to prevent problems if nested.

```

\group_begin:

```

```

\fp_set_eq:NN \l__datatool_max_fp \c_minus_inf_fp
\tl_clear:N #5
\IfValueTF { #1 }
{
  \cs_set:Nn \__datatool_filter:n
  {
    \ifthenelse { #1 } { ##1 } { }
  }
}
{
  \cs_set_eq:NN \__datatool_filter:n \use:n
}

```

Iterate over all the listed data bases:

```

\clist_map_inline:nn { #3 }
{

```

Iterate over the current database (read only):

```

  \DTLmapdata [ name = { ##1 }, read-only ]
  {
    \IfValueT { #2 }
    {
      \DTLmapgetvalues { #2 }
    }
    \__datatool_filter:n
    {

```

Iterate through key list.

```

      \clist_map_variable:nNn
      { #4 }
      \l__datatool_item_key_tl
      {
        \DTLmapget
        {
          key = \l__datatool_item_key_tl,
          return = \l__datatool_item_value_tl
        }
        \datatool_if_null:NF \l__datatool_item_value_tl
        {
          \__datatool_parse:N
          \l__datatool_item_value_tl

```

Check that the value is numerical.

```

        \datatool_if_numeric_datum_type:nT { \@dtl@datatype }
        {
          \datatool_set_fp:NV \l__datatool_datum_value_fp
          \l__datatool_item_value_tl
          \fp_compare:nNnT
          { \l__datatool_max_fp }
          <
          { \l__datatool_datum_value_fp }

```



```

\fp_set_eq:NN \l_datatool_max_fp \c_minus_inf_fp
\tl_clear:N #3
Iterate over the database (read only):
\DTLmapdata [ name = { #1 }, read-only ]
{
  \DTLmapget
  {
    key = { #2 },
    return = \l_datatool_item_value_tl
  }
  \datatool_if_null:NF \l_datatool_item_value_tl
  {
    \__datatool_parse:N
    \l_datatool_item_value_tl
  }
  Check that the value is numerical.
  \datatool_if_numeric_datum_type:nT { \@dtl@datatype }
  {
    \datatool_set_fp:NV \l_datatool_datum_value_fp
    \l_datatool_item_value_tl
    \fp_compare:nNnT
    { \l_datatool_max_fp }
    <
    { \l_datatool_datum_value_fp }
    {
      \fp_set_eq:NN
      \l_datatool_max_fp
      \l_datatool_datum_value_fp
      \tl_set_eq:NN #3 \l_datatool_item_value_tl
    }
  }
}
}
\tl_if_empty:NTF #3
{
  \PackageError { datatool }
  {
    no ~ numeric ~ data ~ found ~ in ~ column ~ `#2' ~
    for ~ database ~ `#1'
  }
  { }
}
{
  \bool_if:NF \l_datatool_db_store_datum_bool
  {
    \tl_set:Nx #3 { #3 }
  }
}
}
End scope.

```

```

\exp_args:NNNV
\group_end: \tl_set:Nn #3 #3
}
data base doesn't exist
{
\PackageError {datatool}
{ Database ~ `#1' ~ doesn't ~ exist}
{}
}
}

```

```

\DTLcomputebounds[condition]{db list}{x key}{y
key}{minX cmd}{minY cmd}{maxX cmd}{maxY cmd}

```

\DTLcomputebounds

Computes the maximum and minimum x and y values over all the databases listed in $\langle db list \rangle$ where the x value is given by $\langle x key \rangle$ and the y value is given by $\langle y key \rangle$. The results are stored in $\langle minX cmd \rangle$, $\langle minY cmd \rangle$, $\langle maxX cmd \rangle$ and $\langle maxY cmd \rangle$ in plain decimal format. Version 3.0: switched to using \DTLmapdata

```

\NewDocumentCommand \DTLcomputebounds { o m m m m m m m }
{

```

Scope to prevent problems if nested.

```

\group_begin:
\fp_set_eq:NN \l__datatool_min_fp \c_inf_fp
\fp_set_eq:NN \l__datatool_min_ii_fp \c_inf_fp
\fp_set_eq:NN \l__datatool_max_fp \c_minus_inf_fp
\fp_set_eq:NN \l__datatool_max_ii_fp \c_minus_inf_fp
\tl_clear:N #5
\tl_clear:N #6
\tl_clear:N #7
\tl_clear:N #8
\IfValueTF { #1 }
{
\cs_set:Nn \__datatool_filter:n
{
\ifthenelse { #1 } { ##1 } { }
}
}
{
\cs_set_eq:NN \__datatool_filter:n \use:n
}

```

Iterate over all the listed data bases:

```

\clist_map_inline:nn { #2 }
{

```

Iterate over the current database (read only):

```

\DTLmapdata [ name = { ##1 }, read-only ]

```

```

{
  \DTLmapgetvalues
  {
    \DTLthisX = #3, \DTLthisY = #4
  }
  \__datatool_filter:n
  {

```

x key:

```

  \tl_set_eq:NN
    \l__datatool_item_value_tl \DTLthisX
  \datatool_if_null:NF \l__datatool_item_value_tl
  {
    \__datatool_parse:N
      \l__datatool_item_value_tl

```

Check that the value is numerical.

```

  \datatool_if_numeric_datum_type:nT { \@dtl@datatype }
  {
    \datatool_set_fp:NV \l__datatool_datum_value_fp
      \l__datatool_item_value_tl
    \fp_compare:nNnT
      { \l__datatool_min_fp }
      >
      { \l__datatool_datum_value_fp }
    {
      \fp_set_eq:NN
        \l__datatool_min_fp
        \l__datatool_datum_value_fp
      \tl_set_eq:Nx #5
      { \DTLdatumvalue { \l__datatool_item_value_tl } }
    }
    \fp_compare:nNnT
      { \l__datatool_max_fp }
      <
      { \l__datatool_datum_value_fp }
    {
      \fp_set_eq:NN
        \l__datatool_max_fp
        \l__datatool_datum_value_fp
      \tl_set_eq:Nx #7
      { \DTLdatumvalue { \l__datatool_item_value_tl } }
    }
  }
}
}

```

y key:

```

  \tl_set_eq:NN
    \l__datatool_item_value_tl \DTLthisY
  \datatool_if_null:NF \l__datatool_item_value_tl
  {

```



```

        \exp_not:N \tl_set:Nn \exp_not:N #7 { #7 }
        \exp_not:N \tl_set:Nn \exp_not:N #8 { #8 }
    }
    \l_datatool_tmpa_tl
}

```

Map over columns in the current row.

```
\dtlmapcurrentrow{<cs>}{<body>}
```

\dtlmapcurrentrow

```

\NewDocumentCommand \dtlmapcurrentrow { m m }
{
  \tl_if_empty:VTF \dtlcurrentrow
  {
    \PackageError { datatool }
    {
      Unable ~ to ~ map ~ current ~ row ~ (missing or empty)
    }
    {}
  }
  {
    \__datatool_map_current_row:Nn #1 { #2 }
  }
}

\cs_new:Nn \__datatool_map_current_row:Nn
{
  \cs_set:Nn \__datatool_map_row_loop_body:n
  {
    \tl_set:Nn #1 { ##1 }
    \exp_args:NV \tl_if_head_eq_meaning:nNT
    #1 \__datatool_datum:w
    {
      \__datatool_to_datum:N #1
    }
    #2
  }
  \exp_last_unbraced:NV \__datatool_map_row:w
  \dtlcurrentrow
  \db@col@id@w \q_recursion_tail \db@col@end@
  \db@col@elt@w \db@col@elt@end@
  \db@col@id@w \q_recursion_tail \db@col@end@
  \q_recursion_stop
  \prg_break_point:Nn \__datatool_map_row_break: { }
}

\ExplSyntaxOff

```

`\DTLgetvalueforkey`

```
\DTLgetvalueforkey{<cmd>}{<key>}{<db name>}{<ref
key>}{<ref value>}
```

This (globally) sets `<cmd>` (a control sequence) to the value of the key specified by `<key>` in the first row of the database called `<db name>` which contains the key `<ref key>` which has the value `<value>`. TODO

```
\newcommand*{\DTLgetvalueforkey}[5]{%
Get row containing referenced (key,value) pair
\DTLgetrowforkey{\@dtl@row}{#3}{#4}{#5}%
Get column number for <key>
\@sdtl@getcolumnindex{\@dtl@col}{#3}{#2}%
Get value for given column
{%
\dtlcurrentrow=\expandafter{\@dtl@row}%
\edef\@dtl@dogetval{\noexpand\dtlgetentryfromcurrentrow
{\noexpand\@dtl@val}{\@dtl@col}}%
\@dtl@dogetval
\global\let#1=\@dtl@val
}%
}
```

`\DTLgetrowforkey`

```
\DTLgetrowforkey{<cmd>}{<db name>}{<ref
key>}{<ref value>}
```

This (globally) sets `<cmd>` (a control sequence) to the first row of the database called `<db name>` which contains the key `<ref key>` that has the value `<value>`.

```
\newcommand*{\DTLgetrowforkey}[4]{%
\global\let#1=\@empty
\@sdtlforeach{#2}{\dtl@refvalue=#3}{%
\DTLifnull{\dtl@refvalue}%
{}%
{%
\ifthenelse{\equal{\dtl@refvalue}{#4}}{%
}%
\undef#1{\the\dtlcurrentrow}%
\dtlbreak
}%
{}%
}%
}%
}
```

12.10 Sorting Databases

The sorting commands have been rewritten in v3.0 to use `l3seq`.

\ExplSyntaxOn

The older `\dtlsort` has the following arguments:

- Replacement list (optional): comma-separated list of column keys to use as a replacement if the given value is null.
- Sort criteria: comma-separated list of $\langle key \rangle = \langle order \rangle$ items, where $\langle order \rangle$ may be `ascending` or `descending`. The order may be omitted, in which case ascending is assumed.
- Handler function: as for `\dtlsortlist`

The newer `\DTLsortdata` command works using a similar principle to `\DTLsortwordlist` but the items in the word list sequence need to include the row specs so the database can be reconstructed afterwards.

The sort criteria argument has a different syntax for the list where each criteria in the list is given by $\langle key \rangle = \{ \langle options \rangle \}$ where $\langle key \rangle$ is the column key. The options may be: `ascending`, `descending`, and `replacements = \{ \langle key list \rangle \}`. This means that a different set of replacements in the event of null can be supplied for each key.

The handler function is the same as for `\DTLsortwordlist`. Need a sequence to keep track of order options: `true` indicates ascending and `false` descending.

```
\seq_new:N \l__datatool_sort_order_seq
```

A sequence to keep track of whether the current sort criteria is for a numeric column. `True` for a numeric column, `false` otherwise.

```
\seq_new:N \l__datatool_sort_numeric_seq
```

A sequence to keep track of the replacement lists. Each item in the sequence will be the csv list.

```
\seq_new:N \l__datatool_replacement_indexes_seq
```

```
\bool_new:N \l__datatool_sort_order_bool
```

```
\clist_new:N \l__datatool_sort_replacements_clist
```

```
\keys_define:nn { datatool / sortdata / criteria }
```

```
{  
  ascending .bool_set:N = \l__datatool_sort_order_bool ,  
  descending .bool_set_inverse:N = \l__datatool_sort_order_bool ,  
  asc .code:n =  
  {  
    \bool_set_true:N \l__datatool_sort_order_bool  
  } ,  
  asc .value_forbidden:n = true ,  
  desc .code:n =  
  {  
    \bool_set_false:N \l__datatool_sort_order_bool  
  } ,  
  desc .value_forbidden:n = true ,  
  replacements .code:n =  
  {  
    \clist_set:No
```

```

        \l_datatool_sort_replacements_clist
        { #1 }
    } ,
}

```

Map function used for obtaining indexes of replacement columns:

```

\cs_new:Nn \__datatool_replacement_handler:n
{
  \tl_if_exist:cTF
  {
    dtl@ci
    @ \l_datatool_default_dbname_tl
    @ #1
  }
  {
    \clist_put_right:Nv \l_datatool_tmpa_clist
    {
      dtl@ci
      @ \l_datatool_default_dbname_tl
      @ #1
    }
  }
}
\__datatool_sortdata_missing_column:nn
{
  \token_to_str:N \DTLsortdata : ~ No ~ column ~ with ~ key ~
  ` #1 ' ~ in ~ database ~
  ` \l_datatool_default_dbname_tl ' ~
  in ~ replacement ~ list ~ for ~
  column ~ key ` #1 '. ~
  Ignoring ~ ` \l_datatool_item_key_tl '
}
{
  Check ~ that ~ you ~ have ~ correctly ~ spelt ~ the ~
  column ~ key ~ and ~ database ~ name ~
}
}
}

```

Parse the sort criteria list. This will set three sequences that correspond to each item in the list, so the $\langle i \rangle$ th item in each sequence corresponds to the $\langle i \rangle$ th item in the criteria list.

```

\cs_new:Nn \__datatool_parse_sort_criteria_list:n
{
  \seq_clear:N \l_datatool_sort_order_seq
  \seq_clear:N \l_datatool_sort_numeric_seq
  \seq_clear:N \l_datatool_column_indexes_seq
  \seq_clear:N \l_datatool_replacement_indexes_seq
  \clist_map_inline:nn { #1 }
  {

```

Parse optional criteria:

```
\keyval_parse:NNn
  \__datatool_parse_sort_criteria:n
  \__datatool_parse_sort_criteria:nn
  { ##1 }
\tl_if_exist:cTF
{
  dtl@ci
  @ \l__datatool_default_dbname_tl
  @ \l__datatool_item_key_tl
}
{
  \exp_args:Nnc
  \int_set:Nn \l__datatool_col_idx_int
  {
    dtl@ci
    @ \l__datatool_default_dbname_tl
    @ \l__datatool_item_key_tl
  }
}
```

Set the column index for this key.

```
\seq_put_right:Nx \l__datatool_column_indexes_seq
{ \int_use:N \l__datatool_col_idx_int }
```

Set the order for this key.

```
\bool_if:NTF \l__datatool_sort_order_bool
{
  \seq_put_right:Nn \l__datatool_sort_order_seq
  { \c_true_bool }
}
{
  \seq_put_right:Nn \l__datatool_sort_order_seq
  { \c_false_bool }
}
```

Get the column type.

```
\__datatool_get_col_type:vV
{ dtlkeys @ \l__datatool_default_dbname_tl }
\l__datatool_col_idx_int
```

Set the numeric flag for this key.

```
\datatool_if_numeric_datum_type:nTF
{ \l__datatool_item_type_int }
{ }
```

Numeric column.

```
\seq_put_right:Nn \l__datatool_sort_numeric_seq
{ \c_true_bool }
}
{ }
```

Not numeric column.

```
\seq_put_right:Nn \l__datatool_sort_numeric_seq
{ \c_false_bool }
}
```

Indexes of replacement columns.

```
\clist_clear:N \l__datatool_tmpa_clist
\clist_map_function:NN
  \l__datatool_sort_replacements_clist
  \__datatool_replacement_handler:n
\seq_put_right:Nx \l__datatool_replacement_indexes_seq
{ \l__datatool_tmpa_clist }
}
{
  \__datatool_sortdata_missing_column:nn
  {
    \token_to_str:N \DTLsortdata : ~ No ~ column ~ with ~ key ~
    ` \l__datatool_item_key_tl ' ~ in ~ database ~
    ` \l__datatool_default_dbname_tl ' . ~
    Ignoring ~ ` \l__datatool_item_key_tl '
  }
  {
    Check ~ that ~ you ~ have ~ correctly ~ spelt ~ the ~
    column ~ key ~ and ~ database ~ name ~
  }
}
}
```

Parse the sort criteria where only the column key is provided.

```
\cs_new:Nn \__datatool_parse_sort_criteria:n
{
```

Set defaults:

```
\bool_set_true:N \l__datatool_sort_order_bool
\clist_clear:N \l__datatool_sort_replacements_clist
\tl_set:Nn \l__datatool_item_key_tl { #1 }
}
```

Parse the sort criteria where the column key and option list are provided.

```
\cs_new:Nn \__datatool_parse_sort_criteria:nn
{
  \__datatool_parse_sort_criteria:n { #1 }
}
```

Parse the sort criteria options.

```
\keys_set:nn { datatool / sortdata / criteria } { #2 }
}
```

Syntax: $\langle handler-cs \rangle \{ \langle numeric\ bool\ var \rangle \} \{ \langle col-idx \rangle \} \{ \langle row-spec \rangle \} \langle replacement\ list \rangle$

The column index $\langle col-idx \rangle$ needs to be fully expanded. This will set $\l__datatool_content_tl$ to the sort value, using the fallback list in the event of a null value.

```
\cs_new:Nn \__datatool_set_sort_value:NnnN
```

```

{
Get the entry from the row specs.
  \__datatool_get_entry_from_row:Nnn
  \l__datatool_item_value_tl { #3 } { #4 }
Parse the value.
  \__datatool_if_replace:NTF \l__datatool_item_value_tl
  {
No value. Try column in the replacement list if available.
  \tl_set_eq:NN \l__datatool_content_tl \dtlnovalue
  \clist_if_empty:NF #5
  {
    \clist_pop:NN #5 \l__datatool_item_col_tl
    \__datatool_set_sort_value:NNVnN
      #1 #2 \l__datatool_item_col_tl
      { #4 } #5
  }
}
{
\cs_if_eq:NNF \__datatool_encap_sort:nnn \use_i:nnn
{
  \tl_set:Ne \l__datatool_item_value_tl
  {
    \__datatool_encap_sort:onn
      { \l__datatool_item_value_tl }
      { #3 } { \l__datatool_default_dbname_tl }
  }
}
\__datatool_parse:N \l__datatool_item_value_tl
\bool_if:NTF #2
{
Numeric column. Set sort to the numeric value.
  \datatool_if_numeric_datum_type:nTF { \@dtl@datatype }
  {
    \tl_set_eq:NN \l__datatool_content_tl
      \l__datatool_datum_value_tl
  }
}
If the column type is numeric but the value isn't, expand fully and try again.
  \tl_set:Nx \l__datatool_item_value_tl
    { \l__datatool_datum_original_value_tl }
  \__datatool_parse:N \l__datatool_item_value_tl
  \datatool_if_numeric_datum_type:nTF { \@dtl@datatype }
  {
    \tl_set_eq:NN \l__datatool_content_tl
      \l__datatool_datum_value_tl
  }
}
}

```

Value still isn't numeric so set to zero.

```
\tl_set:Nn \l__datatool_content_tl { 0 }
\tl_set:Nx \l__datatool_item_value_tl
{
  \exp_not:N \__datatool_datum:nnnn
  { \l__datatool_item_value_tl }
  { 0 } { }
  { \c_datatool_integer_int }
}
}
}
{
```

Not numeric column. Convert to byte sequence.

```
\exp_args:NV #1
  \l__datatool_datum_original_value_tl
  \l__datatool_content_tl
\tl_set:Nx \l__datatool_item_value_tl
{
  \exp_not:N \__datatool_datum:nnnn
  { \l__datatool_item_value_tl }
  { } { }
  { \c_datatool_string_int }
}
}
}
```

If null, treat as empty for strings and 0 for numbers.

```
\datatool_if_null:NT \l__datatool_content_tl
{
  \bool_if:NTF #2
  {
    \tl_set:Nn \l__datatool_content_tl { 0 }
  }
  {
    \tl_clear:N \l__datatool_content_tl
  }
}
\tl_set_eq:NN \l__datatool_item_value_tl \dtlnovalue
}
```

The sort value should now be in `\l__datatool_content_tl` and the actual value (or null) in `\l__datatool_item_value_tl`.

```
}
\cs_generate_variant:Nn
  \__datatool_set_sort_value:NNnnN
  { NNnVN , NNvN }
Options for \DTLsortdata. Handler function:
\cs_new:Nn \__datatool_default_sort_data_fn:nN
{
```

```

\DTLsortwordhandler { #1 } #2
}
\cs_set_eq:NN
  \__datatool_sort_data_fn:nN
  \__datatool_default_sort_data_fn:nN
If the sort value should be saved in a column. Index or key:
\int_new:N \__datatool_sort_data_sortcol_int
\tl_new:N \__datatool_sort_data_sortcol_tl
If the letter group should be saved in a column. Index or key:
\int_new:N \__datatool_sort_data_grpcol_int
\tl_new:N \__datatool_sort_data_grpcol_tl
Determines whether or not the value in the given token list variable should be replaced.
\cs_set_eq:NN
  \__datatool_if_replace:NTF
  \datatool_if_null_or_empty:NTF
Encapsulate non-numeric sort values:
\cs_new:Nn \__datatool_encap_sort:nnn { #1 }
\cs_generate_variant:Nn \__datatool_encap_sort:nnn { onn }
Allow user to choose between error, warning or ignore missing columns.
\cs_new:Nn \__datatool_sortdata_missing_column_err:nn
{
  \PackageError { datatool } { #1 } { #2 }
}
\cs_new:Nn \__datatool_sortdata_missing_column_warn:nn
{
  \PackageWarning { datatool } { #1 }
}
\cs_set_eq:NN
  \__datatool_sortdata_missing_column:nn
  \__datatool_sortdata_missing_column_err:nn
Define keys.
\keys_define:nn { datatool / sortdata }
{
  missing-column-action .choice: ,
  missing-column-action / error .code:n =
  {
    \cs_set_eq:NN
      \__datatool_sortdata_missing_column:nn
      \__datatool_sortdata_missing_column_err:nn
  } ,
  missing-column-action / warn .code:n =
  {
    \cs_set_eq:NN
      \__datatool_sortdata_missing_column:nn
      \__datatool_sortdata_missing_column_warn:nn
  } ,

```

```

missing-column-action / ignore .code:n =
{
  \cs_set_eq:NN
  \__datatool_sortdata_missing_column:nn
  \use_none:nn
},
function .code:n =
{
  \cs_set_eq:NN \__datatool_sort_data_fn:nN #1
},
encap .code:n =
{
  \tl_if_empty:nTF { #1 }
  {
    \cs_set_eq:NN \__datatool_encap_sort:nnn \use_i:nnn
  }
  {
    \cs_set:Nn \__datatool_encap_sort:nnn
    { #1 { ##1 } { ##2 } { ##3 } }
  }
},
replace .choice: ,
replace / null .code:n =
{
  \cs_set_eq:NN
  \__datatool_if_replace:NTF
  \datatool_if_null:NTF
},
replace / null ~ or ~ empty .code:n =
{
  \cs_set_eq:NN
  \__datatool_if_replace:NTF
  \datatool_if_null_or_empty:NTF
},
save-sort .code:n =
{
  \tl_set:Nn \__datatool_sort_data_sortcol_tl { sort }
  \int_zero:N \__datatool_sort_data_sortcol_int
},
save-sort .value_forbidden:n = true ,
save-group .code:n =
{
  \tl_set:Nn \__datatool_sort_data_grpcol_tl { group }
  \int_zero:N \__datatool_sort_data_grpcol_int
},
save-group .value_forbidden:n = true ,
save-sort-column .code:n =
{
  \int_set:Nn \__datatool_sort_data_sortcol_int { #1 }
  \tl_clear:N \__datatool_sort_data_sortcol_tl
}

```

```

    },
    save-sort-column .value_required:n = true ,
    save-sort-key .code:n =
    {
        \tl_set:Nn \__datatool_sort_data_sortcol_tl { #1 }
        \int_zero:N \__datatool_sort_data_sortcol_int
    },
    save-sort-key .value_required:n = true ,
    save-group-column .code:n =
    {
        \int_set:Nn \__datatool_sort_data_grpcol_int { #1 }
        \tl_clear:N \__datatool_sort_data_grpcol_tl
    },
    save-group-column .value_required:n = true ,
    save-group-key .code:n =
    {
        \tl_set:Nn \__datatool_sort_data_grpcol_tl { #1 }
        \int_zero:N \__datatool_sort_data_grpcol_int
    },
    save-group-key .value_required:n = true ,
}

```

\DTLsortdata[⟨options⟩]{⟨db-name⟩}{⟨sort criteria⟩}

\DTLsortdata

```

\NewDocumentCommand \DTLsortdata
{ o m m }
{
    \__datatool_db_sort:nnn { #1 } { #2 } { #3 }
}

```

This just makes it easier for the sort action to expand the arguments without the inconvenience of the optional syntax.

```

\cs_new:Nn \__datatool_db_sort:nnn
{

```

Initialise:

```

\cs_set_eq:NN
    \__datatool_sort_data_fn:nN
    \__datatool_default_sort_data_fn:nN
\cs_set_eq:NN
    \__datatool_if_replace:NTF
    \datatool_if_null_or_empty:NTF
\cs_set_eq:NN \__datatool_encap_sort:nnn \use_i:nnn
\int_zero:N \__datatool_sort_data_sortcol_int
\tl_clear:N \__datatool_sort_data_sortcol_tl
\int_zero:N \__datatool_sort_data_grpcol_int
\tl_clear:N \__datatool_sort_data_grpcol_tl
\IfValueT { #1 }
{

```

```

    \keys_set:nn { datatool / sortdata } { #1 }
  }
\tl_if_empty:nTF { #2 }
{
  \exp_args:No \__datatool_db_sort:nn
  { \l__datatool_default_dbname_tl }
  { #3 }
}
{
  \exp_args:Nx \__datatool_db_sort:nn
  { \text_purify:n { #2 } } { #3 }
}
}
\cs_generate_variant:Nn \__datatool_db_sort:nnn
{ VVV }

Syntax: {<db-name>}{<sort criteria>}
\cs_new:Nn \__datatool_db_sort:nn
{
  \datatool_db_state:nnnn { #1 }
  {
    \__datatool_sort_db_check_opts:n { #1 }
  }
}
Scope to localise the effect of the hook.
\group_begin:
\tl_set:Nx \l__datatool_default_dbname_tl { #1 }
\int_compare:nNnTF
  { \DTLrowcount { \l__datatool_default_dbname_tl } }
  >
  { 200 }
{
  \typeout
  {
    Sorting ~ database ~
    ` \l__datatool_default_dbname_tl ' ~ - ~
    this ~ may ~ take ~ a ~ while.
  }
}
{
  \dtl@message { Sorting ~ database ~ ` \l__datatool_default_dbname_tl ' }
}
\dtl@SortWordCommands@hook
\seq_clear:N \l__datatool_wordlist_seq
Parse the sort criteria. This will set the sequence variables: \l__datatool_sort_order_seq
\l__datatool_sort_numeric_seq\l__datatool_column_indexes_seq
  \__datatool_parse_sort_criteria_list:n { #2 }
\seq_if_empty:NTF \l__datatool_column_indexes_seq
{
  \PackageError { datatool }

```

```

    {
      \token_to_str:N \DTLsortdata : ~ missing ~ sort ~
      criteria
    }
    {
      The ~ final ~ argument ~ of ~ \token_to_str:N \DTLsortdata
      \c_space_tl ~ must ~ have ~ at ~ least ~ one ~ column ~ key
    }
  }
  {

```

For each row in the database, set the list of sort values for each specified column.

```

  \bool_set_true:N \l__datatool_sort_datum_bool
  \DTLmapdata [ read-only ]
  {
    \seq_clear:N \l__datatool_sorta_seq
    \seq_map_indexed_inline:Nn
      \l__datatool_column_indexes_seq
    {
      \exp_args:NNx
        \bool_set:Nn \l__datatool_sort_numeric_bool
        {
          \seq_item:Nn
            \l__datatool_sort_numeric_seq { ##1 }
        }
      \tl_set:Nx
        \l__datatool_sort_replacements_clist
        {
          \seq_item:Nn
            \l__datatool_replacement_indexes_seq { ##1 }
        }
    }

```

This will set `\l__datatool_content_tl` to the sort value, and the original value (or null) will be in `\l__datatool_item_value_tl`.

```

  \__datatool_set_sort_value:NNnVN
  \__datatool_sort_data_fn:nN
  \l__datatool_sort_numeric_bool
  { ##2 }
  \l__datatool_map_data_row_tl
  \l__datatool_sort_replacements_clist
  \bool_if:NTF \l__datatool_sort_numeric_bool
  {
    \dtl@message{ Row ~ \int_use:N \dtlrownum \c_space_tl ~
      numeric ~ sort ~ value ~ for ~ column ~ ##2 : ~
      \l__datatool_content_tl }
  }
  {
    \dtl@message{ Row ~ \int_use:N \dtlrownum \c_space_tl ~
      byte ~ sort ~ value ~ for ~ column ~ ##2 : ~
      \l__datatool_content_tl }
  }
}

```

Append to the word list:

```
\seq_put_right:Nx
  \l_datatool_sorta_seq
  {
    { \exp_not:V \l_datatool_content_tl }
    { \exp_not:V \l_datatool_item_value_tl }
  }
}
\exp_args:Noo \__datatool_sortword_append:nn
{ \l_datatool_sorta_seq }
{ \l_datatool_map_data_row_tl }
}
}
\exp_args:NVV
  \__datatool_start_datasortword_list:nn
  \l_datatool_wordlist_seq
  \l_datatool_sort_order_seq
  \__datatool_finish_sort_db:n { #1 }
}
{ }% empty
{
  \PackageError { datatool }
  {
    \token_to_str:N \DTLsortdata : ~ database ~
    `#1' ~ doesn't ~ exist
  }
  {
    Check ~ that ~ you ~ have ~ correctly ~ spelt ~
    the ~ database ~ name ~ or ~ set ~ the ~ default ~
    name, ~ as ~ applicable
  }
}
}
}
\cs_new:Nn \__datatool_start_datasortword_list:nn
{
  \group_end:
  \tl_set:Nn \l__datatool_wordlist_seq { #1 }
  \tl_set:Nn \l__datatool_sort_order_seq { #2 }
  \cs_set_eq:NN
  \__datatool_compare_sortitem:w
  \__datatool_compare_datasortitem:w
  \seq_sort:Nn \l__datatool_wordlist_seq
  {
    \__datatool_compare_sortitem:w ##1 ##2
  }
}
}
\seq_new:N \l__datatool_sorta_seq
\seq_new:N \l__datatool_sortb_seq
```

```

\cs_new:Npn \__datatool_compare_datasortitem:w
#1\q_mark#2\q_stop#3\q_mark#4\q_stop
{
  \tl_set:Nn \l__datatool_sorta_seq { #1 }
  \tl_set:Nn \l__datatool_sortb_seq { #3 }
  \seq_set_eq:NN
    \l__datatool_tmp_seq
    \l__datatool_sort_order_seq
  \__datatool_compare_datasortitem:
  \int_compare:nNnTF
    { \dtl@sortresult } < { \c_zero_int }
    {
      \sort_return_same:
    }
    {
      \int_compare:nNnTF
        { \dtl@sortresult } > { \c_zero_int }
        {
          \sort_return_swapped:
        }
        {
          \bool_lazy_or:nNTF
            { \seq_if_empty_p:N \l__datatool_sorta_seq }
            { \seq_if_empty_p:N \l__datatool_sortb_seq }
            {
              \sort_return_same:
            }
            {
              \tl_set:Nn \l__datatool_sorta_seq { #1 }
              \tl_set:Nn \l__datatool_sortb_seq { #3 }
              \seq_get_left:NN
                \l__datatool_sorta_seq
                \l__datatool_tmpa_tl
              \seq_get_left:NN
                \l__datatool_sortb_seq
                \l__datatool_tmpb_tl
              \tl_set:Nx \l__datatool_tmpa_tl
                {
                  \exp_last_unbraced:NV
                    \use_ii:nn \l__datatool_tmpa_tl
                }
              \tl_set:Nx \l__datatool_tmpb_tl
                {
                  \exp_last_unbraced:NV
                    \use_ii:nn \l__datatool_tmpb_tl
                }
              \bool_if:NTF \l__datatool_sort_reverse_bool
                {
                  \exp_args:NVV
                    \__datatool_fallback_action:n

```



```

    }
}

```

Arguments expected to be braced pairs.

```

\cs_new:Nn \__datatool_compare_sortitem:nn
{
  \__datatool_compare_sortitem:nnnn #1 #2
}

```

Check the options provided to \DTLsortdata

```

\cs_new:Nn \__datatool_sort_db_check_opts:n
{

```

Does the sort value or letter group need to be saved? Sort column:

```

\tl_if_empty:NF \__datatool_sort_data_sortcol_tl
{
  \tl_if_exist:cTF
  { dtl@ci@ #1 @ \__datatool_sort_data_sortcol_tl }
  {
    \int_set:Nn \__datatool_sort_data_sortcol_int
    {
      \use:c { dtl@ci@ #1 @ \__datatool_sort_data_sortcol_tl }
    }
  }
}

```

Doesn't exist so a new column needs to be created.

```

  \__datatool_add_column_with_header:nxxx
  { #1 }
  { \__datatool_sort_data_sortcol_tl }
  { \int_use:N \c_datatool_string_int }
  { \__datatool_sort_data_sortcol_tl }
  \int_set:Nn \__datatool_sort_data_sortcol_int
  { \DTLcolumncount { #1 } }
}
}

```

Letter group column:

```

\tl_if_empty:NF \__datatool_sort_data_grpcol_tl
{
  \tl_if_exist:cTF
  { dtl@ci@ #1 @ \__datatool_sort_data_grpcol_tl }
  {
    \int_set:Nn \__datatool_sort_data_grpcol_int
    {
      \use:c { dtl@ci@ #1 @ \__datatool_sort_data_grpcol_tl }
    }
  }
}

```

Doesn't exist so a new column needs to be created.

```

  \__datatool_add_column_with_header:nxxx

```

```

    { #1 }
    { \__datatool_sort_data_grpcol_tl }
    { \int_use:N \c_datatool_string_int }
    { \__datatool_sort_data_grpcol_tl }
    \int_set:Nn \__datatool_sort_data_grpcol_int
    { \DTLcolumncount { #1 } }
  }
}

```

If the column indexes were supplied rather than the keys, check if they exist. This needs to be done after the key check in case one was referenced by key and another by index. A reference by column index must exist otherwise it gets too complicated.

```

\int_compare:nNnT
{ \__datatool_sort_data_sortcol_int } > { \DTLcolumncount { #1 } }
{
  \PackageError { datatool }
  {
    save-sort-column ~ value ~
    \int_use:N \__datatool_sort_data_sortcol_int
    \c_space_tl ~ out ~ of ~ range. ~ Ignoring
  }
  {
    Database ~ ` #1 ' ~ only ~ has ~ \DTLcolumncount { #1 } ~
    columns. ~ Use ~ save-sort-key ~ instead ~ if ~ you ~
    want ~ to ~ create ~ a ~ new ~ column
  }
}
\int_zero:N \__datatool_sort_data_sortcol_int
}
\int_compare:nNnT
{ \__datatool_sort_data_grpcol_int } > { \DTLcolumncount { #1 } }
{
  \PackageError { datatool }
  {
    save-group-column ~ value ~
    \int_use:N \__datatool_sort_data_grpcol_int
    \c_space_tl ~ out ~ of ~ range. ~ Ignoring
  }
  {
    Database ~ ` #1 ' ~ only ~ has ~ \DTLcolumncount { #1 } ~
    columns. ~ Use ~ save-group-key ~ instead ~ if ~ you ~
    want ~ to ~ create ~ a ~ new ~ column
  }
}
\int_zero:N \__datatool_sort_data_grpcol_int
}
}

```

Reconstruct database after sorting.

```

\cs_new:Nn \__datatool_finish_sort_db:n
{
  \tl_clear:N \l__datatool_content_tl
}

```

```

\seq_map_indexed_inline:Nn \l__datatool_wordlist_seq
{
  \__datatool_finish_sort_db_parse:w ##2 { ##1 }
}
\bool_if:NTF \l__datatool_db_global_bool
{
  \__datatool_token_register_gset:cV
  { dtldb @ #1 }
  \l__datatool_content_tl
}
{
  \__datatool_token_register_set:cV
  { dtldb @ #1 }
  \l__datatool_content_tl
}
}

```

`\dtlsortdatavalue` Used to encapsulate the sort value when returned by the save-sort... settings. The first argument is the actual byte sequence. The second is the value used to form the byte sequence.

```
\newcommand{\dtlsortdatavalue}[2]{#2}
```

Obtain the original row markup.

```

\cs_new:Npn \__datatool_finish_sort_db_parse:w
#1 \q_mark #2 \q_stop #3
{
  \tl_set:Nn \l__datatool_tmp_seq { #1 }
  \tl_set:Nn \l__datatool_row_tl
  { #2 }
  \int_compare:nNnT
  { \__datatool_sort_data_sortcol_int } > { \c_zero_int }
  {

```

The sort value will be in the form `\dtlsortdatavalue{<sort>}{<datum>}`

```

  \tl_clear:N \l__datatool_tmpa_tl
  \seq_map_inline:Nn \l__datatool_tmp_seq
  {
    \tl_if_eq:nnF
    { ##1 } { { } } { \c_datatool_nullvalue_tl } }
    {
      \tl_set:Nn \l__datatool_tmpa_tl { ##1 }
    }
  }
  \tl_if_empty:NF \l__datatool_tmpa_tl
  {
    \seq_map_break:
  }
}
\tl_if_empty:NF \l__datatool_tmpa_tl
{
  \tl_put_left:Nn \l__datatool_tmpa_tl

```

```

    { \dtlsortdatavalue }
\exp_args:NVV
\__datatool_if_split_row:nnNNTF
\l__datatool_row_tl
\__datatool_sort_data_sortcol_int
\l__datatool_map_data_edit_before_tl
\l__datatool_map_data_edit_after_tl
{

```

Something already exists in this column, so replace it.

```

    \tl_set:Nx \l__datatool_row_tl
    {
      \exp_not:V \l__datatool_map_data_edit_before_tl
      \__datatool_row_element_markup:VV
      \__datatool_sort_data_sortcol_int
      \l__datatool_tmpa_tl
      \exp_not:V \l__datatool_map_data_edit_after_tl
    }
  }
  {
    \tl_put_right:Nx \l__datatool_row_tl
    {
      \__datatool_row_element_markup:VV
      \__datatool_sort_data_sortcol_int
      \l__datatool_tmpa_tl
    }
  }
}
\int_compare:nNnT
{ \__datatool_sort_data_grpcol_int } > { \c_zero_int }
{

```

Fetch the letter group corresponding to the first sort item.

```

\tl_clear:N \l__datatool_tmpa_tl
\seq_map_inline:Nn \l__datatool_tmp_seq
{
  \tl_if_eq:nnF
  { ##1 } { {} } { \c_datatool_nullvalue_tl } }
  {
    \tl_set:Nn \l__datatool_tmpa_tl { ##1 }
  }
\tl_if_empty:NF \l__datatool_tmpa_tl
{
  \seq_map_break:
}
\__datatool_sort_db_fetch_grp:N \l__datatool_tmpa_tl

```

Use hook to post-process the letter group token variable.

```

\datatool_post_process_lettergroup:N

```

```

    \l_datatool_tmpa_tl
  \exp_args:NVV
  \__datatool_if_split_row:nnNTF
  \l_datatool_row_tl
  \__datatool_sort_data_grpcol_int
  \l_datatool_map_data_edit_before_tl
  \l_datatool_map_data_edit_after_tl
  {

```

Something already exists in this column, so replace it.

```

    \tl_set:Nx \l_datatool_row_tl
    {
      \exp_not:V \l_datatool_map_data_edit_before_tl
      \__datatool_row_element_markup:VV
      \__datatool_sort_data_grpcol_int
      \l_datatool_tmpa_tl
      \exp_not:V \l_datatool_map_data_edit_after_tl
    }
  }
  {
    \tl_put_right:Nx \l_datatool_row_tl
    {
      \__datatool_row_element_markup:VV
      \__datatool_sort_data_grpcol_int
      \l_datatool_tmpa_tl
    }
  }
}

```

Add in the start and end row markers.

```

  \tl_put_right:Nx \l_datatool_content_tl
  {
    \__datatool_row_markup:nV
    { #3 } \l_datatool_row_tl
  }
}

```

Syntax: *<grp tl var>* The current row specs should be in `\l__datatool_row_tl`

```

\cs_new:Nn \__datatool_sort_db_fetch_grp:N
{
  \int_compare:nNnTF
  { \tl_count:N #1 } = { 2 }
  {
    \exp_after:wN \__datatool_sort_db_fetch_grp:nnN #1 #1
  }
  {
    \tl_clear:N #1
  }
}
\cs_new:Nn \__datatool_sort_db_fetch_grp:nnN
{

```

```

\tl_clear:N #3
\DTLassignlettergroup { #2 } { #1 } #3
}
Hook to post-process the letter group token variable.
\cs_new:Nn \datatool_post_process_lettergroup:N
{
}

```

\@dtl@list Version 3.0: removed \@dtl@list. Token register to store data when sorting.

```

\DTLsort[<replacement keys>]{<sort criteria>}{<db name>}

```

\DTLsort

Sorts database *<db name>* according to *{<sort criteria>}*, which must be a comma separated list of keys, and optionally =*<order>*, where *<order>* is either ascending or descending. The optional argument is a list of keys to uses if the given key has a null value. The starred version uses a case insensitive string comparison.

```

\newcommand*{\DTLsort}{\@ifstar\@sDTLsort\@DTLsort}

```

\@DTLsort Unstarred (case sensitive) version.

```

\newcommand{\@DTLsort}[3][[]]{%
\dtlsort[#1]{#2}{#3}{\dtlcompare}%
}

```

\@sDTLsort Starred (case insensitive) version.

```

\newcommand*\@sDTLsort}[3][[]]{%
\dtlsort[#1]{#2}{#3}{\dtlicompare}%
}

```

The \dtlsort macro uses some of the same sequences as \DTLsortdata: \l__datatool_replacement_indexes_seq (list of replacement columns), \l__datatool_sort_numeric_seq (boolean sort sequence), \l__datatool_column_indexes_seq (list of columns to sort by) and \l__datatool_sort_order_seq (sort order). The database rows will be temporarily stored in the following sequence, which will be sorted according to the handler.

```

\seq_new:N \l__datatool_dtl_sort_rows_seq
Temporary sort values.
\tl_new:N \l__datatool_sorta_tl
\tl_new:N \l__datatool_sortb_tl

```

```

\dtlsort[<replacement keys>]{<sort criteria>}{<db name>}{<handler>}

```

\dtlsort

More general version where user supplies a handler for the comparison.

```

\NewDocumentCommand \dtlsort { o m m m }
{
Check the database exists
  \DTLifdbexists { #3 }
  {
Scope.
  \group_begin:
  \tl_set:Nx \dtldbname { #3 }
List of replacement column indexes.
  \seq_clear:N \l__datatool_replacement_indexes_seq
  \IfValueT { #1 }
  {
    \clist_map_inline:nn { #1 }
    {
      \datatool_if_has_key:nnTF { #3 } { ##1 }
      {
        \seq_put_right:Nx \l__datatool_replacement_indexes_seq
        { \dtlcolumnindex { #3 } { ##1 } }
      }
      {
        \PackageWarning { datatool }
        { Ignoring ~ unknown ~ replacement ~ column ~ ##1 }
      }
    }
  }
}

List of sort column indexes. This also needs to keep track of the direction.
\seq_clear:N \l__datatool_column_indexes_seq
\seq_clear:N \l__datatool_sort_order_seq
\seq_clear:N \l__datatool_sort_numeric_seq
\keyval_parse:NNn
  \__datatool_dtlsort_col:n
  \__datatool_dtlsort_col:nn
  { #2 }
\seq_if_empty:NTF \l__datatool_column_indexes_seq
{
  \PackageError { datatool }
  {
    \token_to_str:N \dtlsort : ~ No ~ sort ~ columns
  }
  {
    Either ~ the ~ criteria ~ argument ~ is ~ empty ~ or ~
    all ~ listed ~ column ~ keys ~ are ~ undefined
  }
}
{
  \seq_clear:N \l__datatool_dtlsort_rows_seq
  \int_step_inline:nn { \DTLrowcount { #3 } }
}

```

```

    {
      \__datatool_get_row:vnN
      { dtldb@ #3 } { ##1 } \__datatool_sorta_tl
      \seq_put_right:NV \__datatool_dtlsort_rows_seq
      \__datatool_sorta_tl
    }
  \seq_sort:Nn \__datatool_dtlsort_rows_seq
  {
    \__datatool_dtlsort_compare:Nnn #4 { ##1 } { ##2 }
  }
}
\exp_args:NNV
\group_end:
\__datatool_dtlsort_reconstruct:nn
  \__datatool_dtlsort_rows_seq { #3 }
}
{
  \PackageError { datatool }
  { Database ~ ` #3 ' ~ doesn't ~ exist} { }
}
}
\cs_new:Nn \__datatool_dtlsort_reconstruct:nn
{
  \tl_set:Nn \__datatool_dtlsort_rows_seq { #1 }
  \__datatool_token_register_set:cn { dtldb@ #2 } { }
  \seq_map_indexed_inline:Nn \__datatool_dtlsort_rows_seq
  {
    \bool_if:NTF \__datatool_db_global_bool
    {
      \__datatool_token_register_gput_right:cx
      { dtldb@ #2 } { \__datatool_row_markup:nn { ##1 } { ##2 } }
    }
    {
      \__datatool_token_register_put_right:cx
      { dtldb@ #2 } { \__datatool_row_markup:nn { ##1 } { ##2 } }
    }
  }
}
}
\cs_new:Nn \__datatool_dtlsort_compare:Nnn
{
  \seq_map_indexed_inline:Nn \__datatool_column_indexes_seq
  {
    \bool_set:Nn \__datatool_sort_order_bool
    {
      \seq_item:Nn \__datatool_sort_order_seq { ##1 }
    }
  }
  \exp_args:NNx
  \bool_set:Nn \__datatool_sort_numeric_bool
  {

```

```

        \seq_item:Nn
          \l__datatool_sort_numeric_seq { ##1 }
      }
    \__datatool_dtl_sort_get_value:Nnn
      \l__datatool_sorta_tl { ##2 } { #2 }
    \__datatool_dtl_sort_get_value:Nnn
      \l__datatool_sortb_tl { ##2 } { #3 }
    \bool_if:NTF \l__datatool_sort_numeric_bool
      {
        \DTLnumcompare \dtl@sortresult { \l__datatool_sorta_tl } { \l__datatool_sortb_tl }
        \int_if_zero:nT { \dtl@sortresult }
        {
          \exp_args:NNVV #1 \dtl@sortresult \l__datatool_sorta_tl \l__datatool_sortb_tl
        }
      }
      {
        \exp_args:NNVV #1 \dtl@sortresult \l__datatool_sorta_tl \l__datatool_sortb_tl
      }
    \ifdtlverbose
      \dtl@message
      {
        \exp_not:V \l__datatool_sorta_tl' ~
        <=> ~ \exp_not:V \l__datatool_sortb_tl' ~ = ~ \int_use:N \dtl@sortresult
      }
    \fi
    \bool_if:NF \l__datatool_sort_order_bool
      {
        \int_set:Nn \dtl@sortresult { - \dtl@sortresult }
      }
    \int_if_zero:nTF { \dtl@sortresult }
      {
        \int_compare:nNnT
          { ##1 } = { \seq_count:N \l__datatool_column_indexes_seq }
          {
            \sort_return_same:
          }
      }
      {
        \int_compare:nNnTF { \dtl@sortresult } > { \c_zero_int }
        { \seq_map_break:n { \sort_return_swapped: } }
        { \seq_map_break:n { \sort_return_same: } }
      }
    }
  }
}
\cs_new:Nn \__datatool_dtl_sort_get_value:Nnn
{
  \__datatool_get_entry_from_row:Nnn
  #1 { #2 } { #3 }
  \bool_lazy_and:nnT

```

```

    { \tl_if_eq_p:NN #1 \dtlnvalue }
    { \bool_not_p:n { \seq_if_empty_p:N \l__datatool_replacement_indexes_seq } }
  {
    \seq_map_inline:Nn \l__datatool_replacement_indexes_seq
    {
      \__datatool_get_entry_from_row:Nnn
      #1 { ##1 } { #3 }
      \tl_if_eq:NNF #1 \dtlnvalue
      { \seq_map_break: }
    }
  }
}
\bool_if:NT \l__datatool_sort_numeric_bool
{
  \tl_if_eq:NNTF #1 \dtlnvalue
  {
    \DTLsetintegerdatum #1 { \c_datatool_nullvalue_tl } { 0 }
  }
  {
    \__datatool_parse:N #1
    \int_compare:nNnTF
      { \@dtl@datatype }
      <
      { \c_datatool_integer_int }
      {
        \bool_set_false:N \l__datatool_sort_numeric_bool
      }
  }
}
}
\cs_new:Nn \l__datatool_dtlsort_col:nN
{
  \datatool_if_has_key:nnTF { \dtldbname } { #1 }
  {
    \int_set:Nn \l__datatool_col_idx_int
      { \dtlcolumnindex { \dtldbname } { #1 } }
    \seq_put_right:NV \l__datatool_column_indexes_seq
      \l__datatool_col_idx_int
    \seq_put_right:Nn \l__datatool_sort_order_seq { #2 }
    \__datatool_get_col_type:vV
      { dtlkeys @ \dtldbname }
      \l__datatool_col_idx_int
    \datatool_if_numeric_datum_type:nTF
      { \l__datatool_item_type_int }
      {
        Numeric column.
        \seq_put_right:Nn \l__datatool_sort_numeric_seq
          { \c_true_bool }
      }
  }
}

```

Not numeric column.

```
\seq_put_right:Nn \l__datatool_sort_numeric_seq
  { \c_false_bool }
}
{
  \PackageWarning { datatool }
  { Ignoring ~ unknown ~ sort ~ column ~ #1 }
}
}
\cs_new:Nn \__datatool_dtlsort_col:n
{
  \__datatool_dtlsort_col:nN { #1 } \c_true_bool
}
\cs_new:Nn \__datatool_dtlsort_col:nn
{
  \tl_if_empty:nTF { #2 }
  {
    \__datatool_dtlsort_col:nN { #1 } \c_true_bool
  }
  {
    \tl_if_eq:nnTF { #2 } { descending }
    {
      \__datatool_dtlsort_col:nN { #1 } \c_false_bool
    }
    {
      \tl_if_eq:nnTF { #2 } { ascending }
      {
        \__datatool_dtlsort_col:nN { #1 } \c_true_bool
      }
      {
        \PackageError { datatool }
        {
          \token_to_str:N \dtlsort : ~ Invalid ~ sort ~ order ~ `#2' ~
          for ~ column ~ `#1'
        }
        {
          The ~ sort ~ order ~ may ~ be ~ either ~ `ascending' ~
          or ~ `descending'. ~ You ~ may ~ omit ~ the ~ order ~
          for ~ the ~ default ~ `ascending'
        }
      }
    }
  }
}
}
```

\@dtl@rowa Token register to store first row when sorting. Version 3.0: removed.

\@dtl@rowb Token register to store comparison row when sorting. Version 3.0: removed.

`\dtl@sortdata` `\dtl@sortdata{<db>}`
 Sorts the data in named database using an insertion sort algorithm. `\dtl@replacementkeys`, `\dtl@sortorder` and `\dtl@comparecs` must be set prior to use. Version 3.0: removed.

`\dtl@sortcriteria` `\dtl@sortcriteria{<row a toks>}{<row b toks>}`
`\dtl@dbname` and `\dtl@sortorder` must be set before use `\dtl@sortorder` is a comma separated list of either just keys or `<key>=<direction>`. (Check keys are valid before use.) Version 3.0: removed.

`\dtl@getsortdirection` Get the direction from either `<key>` or `<key>=<direction>`. Sets `\dtl@sortdirection` to either -1 (ascending) or 1 (descending). Version 3.0: removed.

`\dtl@get@sortdirection` Get direction (trims trailing = sign) Version 3.0: removed.

`\dtl@compare` `\dtl@compare{<key>}{<a toks>}{<b toks>}`
 Compares two values according to `<key>` of database given by `\dtl@dbname`. Sets `\dtl@sortresult`. `\dtl@comparecs` must be set to the required comparison macro. Version 3.0: removed.

`\dtl@compare@` `\dtl@compare@{<keyA>}{<keyB>}{<A toks>}{<B toks>}`
 Compare `<A>` and `` according `<keyA>` and `<keyB>` for database given by `\dtl@dbname`. Sets `\dtl@sortresult`. `\dtl@comparecs` must be set before use. Version 3.0: removed.

12.11 Saving a database to an external file

Version 3.0 provides a single command to save to the different types of files with an optional argument to specify the format.

```
\ior_new:N \g__datatool_in_stream
\iow_new:N \g__datatool_out_stream
```

Control whether or not the data should be expanded as it's written. The default doesn't expand.

```
\cs_new:Nn \__datatool_data:n { \exp_not:n { #1 } }
```

`\dtl@specialvalue` Elements starting with the special value marker will always be expanded.
`\newcommand{\dtl@specialvalue}[1]{#1}`

```

\cs_new:Nn \__datatool_data_value:n
{
  \tl_if_head_eq_meaning:nNTF { #1 } \dtlspecialvalue
  { #1 }
  { \__datatool_data:n { #1 } }
}
\cs_new:Nn \__datatool_save_data_no_expand:Nn
{
  \tl_set:Nx #1 { \tl_to_str:n { #2 } }
  \__datatool_save_data_postprocess:N #1
}
\cs_new:Nn \__datatool_save_data_protected_expand:Nn
{
  \protected@edef #1 { #2 }
  \@onelevel@sanitize #1
  \__datatool_save_data_postprocess:N #1
}
\cs_new:Nn \__datatool_save_data_full_expand:Nn
{
  \exp_args:NNx \__datatool_save_data_no_expand:Nn #1 { #2 }
}
\cs_set_eq:NN \__datatool_save_data:Nn \__datatool_save_data_no_expand:Nn

```

Escape delimiters:

```

\cs_new:Nn \__datatool_save_escape_delim_bksl:N
{
  \regex_replace_all:NnN \l__datatool_escape_delim_bksl_regex { \\1 } #1
}
\cs_new:Nn \__datatool_save_escape_delim:N
{
  \regex_replace_all:NnN \l__datatool_escape_delim_regex { \\1 } #1
}
\cs_new:Nn \__datatool_save_double_delim:N
{
  \regex_replace_all:NnN \l__datatool_escape_delim_regex { \1\1 } #1
}
\cs_set_eq:NN
  \__datatool_save_data_postprocess:N
  \__datatool_save_double_delim:N

```

Similarly unescape for reading data:

```

\cs_new:Nn \__datatool_load_unescape_delim_bksl:N
{
  \bool_if:NTF \l__datatool_csv_literal_content_bool
  {
    \regex_replace_all:NnN \l__datatool_unescape_str_delim_bksl_regex { \1 } #1
  }
  {
    \regex_replace_all:NnN \l__datatool_unescape_cs_delim_regex
    { \u{@dtl@delimiter} } #1
  }
}

```

```

    \regex_replace_all:nnN
      { \c{ \x{5c} } ( [[:^alpha:]] | [a-zA-Z]+ ) }
      { \c{ \1 } }
      #1
  }
}
\cs_new:Nn \__datatool_load_unescape_delim:N
{
  \bool_if:NTF \l__datatool_csv_literal_content_bool
  {
    \regex_replace_all:NnN \l__datatool_unescape_str_delim_regex { \1 } #1
  }
  {
    \regex_replace_all:NnN \l__datatool_unescape_cs_delim_regex
      { \u{@dtl@delimiter} } #1
  }
}
\cs_new:Nn \__datatool_load_unescape_double_delim:N
{
  \bool_if:NTF \l__datatool_csv_literal_content_bool
  {
    \regex_replace_all:NnN \l__datatool_unescape_str_double_delim_regex { \1 } #1
  }
  {
    \regex_replace_all:NnN \l__datatool_unescape_cs_double_delim_regex
      { \1 } #1
  }
}
\cs_set_eq:NN
  \__datatool_load_data_postprocess:N
  \__datatool_load_unescape_double_delim:N

```

The default format to save is CSV.

```
\cs_new:Nn \__datatool_save:n { \__datatool_save_csv:n { #1 } }
```

The default file extension.

```
\tl_new:N \l__datatool_default_ext_tl
\tl_set:Nn \l__datatool_default_ext_tl { .csv }
```

The default format to load is CSV.

```
\cs_new:Nn \__datatool_load: { \__datatool_load_csv: }
```

File overwrite.

```
\cs_new:Nn \__datatool_save_error_overwrite:nn
{
  \PackageError { datatool }
  { Can't ~ save ~ to ~ file ~ `#1': ~ overwrite ~ forbidden }
  {
    The ~ current ~ overwrite ~ setting ~ doesn't ~ allow ~ an ~
    existing ~ file ~ to ~ be ~ overwritten. ~ Use ~ `overwrite=allow' ~
    option ~ to ~ allow ~ overwrite.
  }
}
```

```

    }
  }
\cs_new:Nn \__datatool_save_warn_overwrite:nn
{
  \PackageWarning { datatool }
  { File ~ `#1' ~ already ~ exists. ~ Skipping ~ save}
}
\cs_new:Nn \__datatool_save_allow_overwrite:nn
{
  \dtl@message { Overwriting ~ `#1' }
  #2
}
\cs_set_eq:NN \__datatool_overwrite_action:nn
  \__datatool_save_error_overwrite:nn

```

Hook to run at the start of save/load CSV to allow for local catcode change for TSV format.

```
\tl_new:N \l__datatool_io_csv_init_tl
```

`\ifdtlnoheader` The `noheader` option indicates that the file doesn't have a header row.
`\newif\ifdtlnoheader`

`\ifdtlautokeys` Assign the default keys even if a header row is supplied (input only).
`\newif\ifdtlautokeys`
`\dtlautokeysfalse`

`\dtldefaultkey` Default key to use if none specified (column index will be appended).
`\newcommand*{\dtldefaultkey}{Column}`

`\ifDTLnewdbonload` [Deprecated] Governs whether or not the database should be defined by `\DTLloadadb` and `\DTLloadrawdb`.

```
\newif\ifDTLnewdbonload
```

Ensure compatibility with previous versions:

```
\DTLnewdbonloadtrue
```

Conditional set by format to indicate whether or not appending to a database is allowed.

```

\bool_new:N \l__datatool_append_allowed_bool
\bool_set_true:N \l__datatool_append_allowed_bool
\cs_new:Nn \__datatool_load_init_old_style:n
{
  \ifDTLnewdbonload
    \__datatool_load_init_create:n { #1 }
  \else
    \__datatool_load_init_append:n { #1 }
  \fi
}

```

Use old method as the default for backward-compatibility.

```
\cs_set_eq:NN \__datatool_load_init:n  
\__datatool_load_init_old_style:n
```

Error if database already exists with create setting.

```
\cs_new:Nn \__datatool_load_db_exists_error:n  
{  
  \PackageError { datatool }  
  {  
    \token_to_str:N \DTLread : ~ Database ~ `#1' ~  
    already ~ exists  
  }  
  {  
    Check ~ the ~ `name' ~ setting ~ in ~ the ~ optional ~  
    argument ~ of ~ \token_to_str:N \DTLread . ~  
    DBTEX ~ v2.0 ~ and ~ DTLTEX ~ v2.0 ~ formats ~ don't ~ allow ~ the ~  
    database ~ name ~ to ~ be ~ changed ~ if ~ it's ~  
    hard-coded ~ in ~ the ~ file. ~ DBTEX ~ v3.0 ~ and ~  
    DTLTEX ~ v3.0 ~ require ~ the ~ new ~ name ~ to ~  
    be ~ provided ~ with ~ the ~ `name' ~ option, ~ not ~  
    with ~ the ~ `default-name' ~ package-wide ~ setting  
  }  
}
```

Create database.

```
\cs_new:Nn \__datatool_load_init_create:n  
{  
  \cs_set_eq:NN \__datatool_csv_check_key:  
  \__datatool_csv_check_key_create:  
  \cs_set:Nn \__datatool_csv_check_col_idx: { }  
  \cs_set_eq:NN \__datatool_csv_check_col_count:  
  \__datatool_csv_check_col_count_create:  
  \DTLifdbexists { #1 }  
  {  
    \__datatool_load_db_exists_error:n { #1 }  
  }  
  {  
    \__datatool_new_db:n { #1 }  
  }  
}
```

```
\cs_new:Nn \__datatool_load_init_append:n  
{  
  \bool_if:NTF \l__datatool_append_allowed_bool  
  {  
    \cs_set_eq:NN \__datatool_csv_check_key:  
    \__datatool_csv_check_key_append:  
    \cs_set_eq:NN \__datatool_csv_check_col_idx:  
    \__datatool_csv_check_col_idx_append:  
    \cs_set:Nn \__datatool_csv_check_col_count: { }  
    \dtl@message { Appending ~ to ~ `#1' }
```

```

        \int_set:Nn \dtlrownum { \DTLrowcount { #1 } }
    }
    {
        \PackageError {datatool}
        { Appending ~ not ~ supported ~ for ~ the ~ given ~ format. ~
          Unexpected ~ results ~ may ~ occur}
        {}
    }
}
\cs_new:Nn \__datatool_load_init_overwrite:n
{
    \cs_set_eq:NN \__datatool_csv_check_key:
        \__datatool_csv_check_key_create:
    \cs_set:Nn \__datatool_csv_check_col_idx: { }
    \cs_set_eq:NN \__datatool_csv_check_col_count:
        \__datatool_csv_check_col_count_create:
    \DTLifdbexists { #1 }
    {
        \DTLgcleardb { #1 }
    }
    { \DTLnewdb { #1 } }
}
\cs_new:Nn \__datatool_load_init_append_or_create:n
{
    \DTLifdbexists { #1 }
    {
        \__datatool_load_init_append:n { #1 }
    }
    {
        \__datatool_load_init_create:n { #1 }
    }
}

```

When appending, need to map the column in the new data being parse to the corresponding column in the database to which the new data is being appended.

```

\prop_new:N \l__datatool_csv_colnew_to_colold_prop
\cs_new:Nn \__datatool_csv_check_key_create:
{
    \@sDTLifhaskey \l__datatool_io_name_tl \l__datatool_item_key_tl
    {
        \PackageError { datatool }
        { Duplicate ~ key ~ '\l__datatool_item_key_tl' ~ found ~ found }
        { Did ~ you ~ want ~ to ~ append ~ to ~ an ~ existing ~ database? }
    }
    { }
}

```

Appending so set up map.

```

\cs_new:Nn \__datatool_csv_check_key_append:
{

```

```

\@sDTLifhaskey \l__datatool_io_name_tl \l__datatool_item_key_tl
{

```

Get the existing column index.

```

\int_set:Nn \l__datatool_tmpa_int
  { \dtlcolumnindex \l__datatool_io_name_tl \l__datatool_item_key_tl }
\prop_put:NVV
  \l__datatool_csv_colnew_to_colold_prop
  \l__datatool_item_col_tl
  \l__datatool_tmpa_int
}
{
\int_gincr:c { dtlcols@ \l__datatool_io_name_tl }
\prop_put:NVx
  \l__datatool_csv_colnew_to_colold_prop
  \l__datatool_item_col_tl
  { \int_use:c { dtlcols@ \l__datatool_io_name_tl } }
}
}

```

With load-action=create, any extra columns can be detected if `\dtlcolumn` is greater than the column count for the database.

```

\cs_new:Nn \__datatool_csv_check_col_count_create:
{
\int_compare:nNnT
  { \int_use:c { dtlcols@ \l__datatool_io_name_tl } } < { \dtlcolumnnum}
{
\int_gset_eq:cN
  { dtlcols@ \l__datatool_io_name_tl }
  \dtlcolumnnum
}
}

```

With load-action=append, there's no need to do anything as the index check will increment the column count.

Update column index. Nothing needs to be done with load-action=create.

```

\cs_new:Nn \__datatool_csv_check_col_idx_append:
{
\prop_get:NVN
  \l__datatool_csv_colnew_to_colold_prop
  \l__datatool_item_col_tl
  \l__datatool_tmpb_tl
\quark_if_no_value:NTF \l__datatool_tmpb_tl
{
\int_gincr:c { dtlcols@ \l__datatool_io_name_tl }
\prop_put:NVx
  \l__datatool_csv_colnew_to_colold_prop
  \l__datatool_item_col_tl
  { \int_use:c { dtlcols@ \l__datatool_io_name_tl } }
\tl_set:Nv \l__datatool_item_col_tl
  { \int_use:c { dtlcols@ \l__datatool_io_name_tl } }
}
}

```

```

    }
    {
      \tl_set_eq:NN \l__datatool_item_col_tl \l__datatool_tmpb_tl
    }
  }
}

```

Default is for load-action=create

```

\cs_set_eq:NN \__datatool_csv_check_key: \__datatool_csv_check_key_create:
\cs_set_eq:NN \__datatool_csv_check_col_count:
  \__datatool_csv_check_col_count_create:
\cs_new:Nn \__datatool_csv_check_col_idx: { }
\tl_new:N \l__datatool_io_name_tl

```

`\dtllastloadedeb` This should be set at the end of DTLTEX v2.0 and DBTEX v2.0 files. Initialise to empty in case v1.0 file format loaded.

```
\tl_new:N \dtllastloadedeb
```

Does CSV/TSV source contain \LaTeX commands or should \TeX characters be considered literally?

```

\bool_new:N \l__datatool_csv_literal_content_bool
\bool_set_true:N \l__datatool_csv_literal_content_bool

```

Version 3.2: Does CSV/TSV source contain plain numbers or should content be parsed?

```

\bool_new:N \l__datatool_csv_plain_content_bool
\bool_set_false:N \l__datatool_csv_plain_content_bool

```

Default keys when reading CSV/TSV files.

```

\prop_new:N \l__datatool_csv_keys_prop
\prop_new:N \l__datatool_csv_headers_prop
\prop_new:N \l__datatool_csv_types_prop

```

Version 3.4: List of column indexes that shouldn't be parsed. (Columns explicitly identified as string in data-types shouldn't have items parsed.)

```

\seq_new:N \l__datatool_no_parse_cols_seq
\bool_new:N \l__datatool_csv_convert_bool
\bool_set_false:N \l__datatool_csv_convert_bool

```

`\dtl@omitlines` TODO replace with `l3int` variable?

```

\newcount{\dtl@omitlines}

\seq_new:N \l__datatool_csv_only_auto_reformat_seq
\cs_new:Nn \__datatool_csv_set_auto_reformat:
{
  \seq_if_empty:NF \l__datatool_csv_only_auto_reformat_seq
  {
    \seq_if_in:NVTF
      \l__datatool_csv_only_auto_reformat_seq
      \l__datatool_item_col_tl
    {
      \bool_set_true:N \l__datatool_reformat_numeric_bool
    }
  }
}

```

```

        \bool_set_true:N \l__datatool_reformat_datetime_bool
      }
    {
      \bool_set_false:N \l__datatool_reformat_numeric_bool
      \bool_set_false:N \l__datatool_reformat_datetime_bool
    }
  }
}

Options:
\keys_define:nn { datatool/io }
{
  keys .code:n =
  {
    \prop_clear_new:N \l__datatool_csv_keys_prop
    \clist_set:Nn \l__datatool_tmpa_clist { #1 }
    \int_zero:N \l__datatool_tmpa_int
    \clist_map_inline:Nn \l__datatool_tmpa_clist
    {
      \int_incr:N \l__datatool_tmpa_int
      \tl_if_empty:nF { ##1 }
      {
        \prop_put:NVn \l__datatool_csv_keys_prop
          \l__datatool_tmpa_int { ##1 }
      }
    }
    \prop_if_empty:NF \l__datatool_csv_keys_prop
    {
      \dtlautokeysfalse
    }
  },
  headers .code:n =
  {
    \prop_clear_new:N \l__datatool_csv_headers_prop
    \clist_set:Nn \l__datatool_tmpa_clist { #1 }
    \int_zero:N \l__datatool_tmpa_int
    \clist_map_inline:Nn \l__datatool_tmpa_clist
    {
      \int_incr:N \l__datatool_tmpa_int
      \prop_put:NVn \l__datatool_csv_headers_prop
        \l__datatool_tmpa_int { ##1 }
    }
  },
  data-types .code:n =
  {
    \seq_clear:N \l__datatool_no_parse_cols_seq
    \prop_clear_new:N \l__datatool_csv_types_prop
    \clist_set:Nn \l__datatool_tmpa_clist { #1 }
    \int_zero:N \l__datatool_tmpa_int
    \clist_map_inline:Nn \l__datatool_tmpa_clist

```

```

    {
      \int_incr:N \l__datatool_tmpa_int
      \int_if_exist:cTF { c_datatool_ ##1 _int }
      {
        \prop_put:Nv \l__datatool_csv_types_prop
          \l__datatool_tmpa_int { c_datatool_ ##1 _int }
        \int_compare:nNnT
          { \int_use:c { c_datatool_ ##1 _int } } = { \c_datatool_string_int }
          {
            \seq_put_right:Nv \l__datatool_no_parse_cols_seq
              \l__datatool_tmpa_int
          }
        }
      }
    {
      \PackageError { datatool }
        {
          unknown ~ data ~ type ~ identifier ~ ` ##1 '
        }
        {
          data-types ~ value ~ should ~ be ~ a ~
          comma-separated ~ list ~ of ~ data ~ type ~ identifiers ~
          such ~ as ~ `string' ~ for ~ strings or
          `decimal` for decimals
        }
    }
  }
},
only-reformat-columns .code:n =
{
  \seq_set_from_clist:Nn
    \l__datatool_csv_only_auto_reformat_seq { #1 }
} ,
separator .code:n =
{
  \DTLsetseparator { #1 }
  \tl_clear:N \l__datatool_io_csv_init_tl
},
separator .value_required:n = true,
delimiter .code:n =
{
  \DTLsetdelimiter { #1 }
},
delimiter .value_required:n = true,
convert-numbers .bool_set:N = \l__datatool_csv_convert_bool ,
trim .bool_set:N = \l__datatool_new_element_trim_bool ,
strict-quotes .choice:,
strict-quotes / true .code:n =
{
  \PackageWarning { datatool }
  {

```

```

        ignoring ~ option ~ `strict-quotes'. ~ This ~ setting ~
        is ~ only ~ supported ~ with ~ datatooltk ~ not ~ with ~
        datatool.sty
    }
},
strict-quotes / false .code:n = { },
strict-quotes .default:n = true ,
expand .choice:,
expand .default:n = protected,
expand / none .code:n =
{
    \cs_set_eq:NN
        \__datatool_save_data:Nn
        \__datatool_save_data_no_expand:Nn
    \cs_set_eq:NN \__datatool_data:n \tl_to_str:n
    \dtlnoexpandnewvalue
},
expand / protected .code:n =
{
    \cs_set_eq:NN
        \__datatool_save_data:Nn
        \__datatool_save_data_protected_expand:Nn
    \cs_set_eq:NN \__datatool_data:n \tl_to_str:n
    \dtlexpandnewvalue
},
expand / full .code:n =
{
    \cs_set_eq:NN
        \__datatool_save_data:Nn
        \__datatool_save_data_full_expand:Nn
    \cs_set_eq:NN \__datatool_data:n \use:n
    \dtlexpandnewvalue
},
format .choice:,
format .value_required:n = true,
format / csv .code:n =
{
    \tl_clear:N \l__datatool_io_csv_init_tl
    \cs_set_eq:NN \__datatool_save:n \__datatool_save_csv:n
    \cs_set_eq:NN \__datatool_load: \__datatool_load_csv:
    \tl_set:Nn \l__datatool_default_ext_tl { .csv }
    \bool_set_true:N \l__datatool_append_allowed_bool
},
format / tsv .code:n =
{
    \tl_set:Nn \l__datatool_io_csv_init_tl
        { \DTLsettabseparator }
    \cs_set_eq:NN \__datatool_save:n \__datatool_save_csv:n
    \cs_set_eq:NN \__datatool_load: \__datatool_load_csv:
    \tl_set:Nn \l__datatool_default_ext_tl { .tsv }
}

```

```

        \bool_set_true:N \l_datatool_append_allowed_bool
    },
format / dtltex-2 .code:n =
{
    \cs_set_eq:NN \__datatool_save:n \__datatool_save_dtltex_ii:n
    \cs_set_eq:NN \__datatool_load: \__datatool_load_tex:
    \tl_set:Nn \l__datatool_default_ext_tl { .dtltex }
    \bool_set_false:N \l_datatool_append_allowed_bool
},
format / dtltex-3 .code:n =
{
    \cs_set_eq:NN \__datatool_save:n \__datatool_save_dtltex_iii:n
    \cs_set_eq:NN \__datatool_load: \__datatool_load_tex:
    \tl_set:Nn \l__datatool_default_ext_tl { .dtltex }
    \bool_set_true:N \l_datatool_append_allowed_bool
},
format / dtltex .code:n =
{
    \cs_set_eq:NN \__datatool_save:n \__datatool_save_dtltex_iii:n
    \cs_set_eq:NN \__datatool_load: \__datatool_load_tex:
    \tl_set:Nn \l__datatool_default_ext_tl { .dtltex }
    \bool_set_true:N \l_datatool_append_allowed_bool
},
format / dbtex-2 .code:n =
{
    \cs_set_eq:NN \__datatool_save:n \__datatool_save_db_ii:n
    \cs_set_eq:NN \__datatool_load: \__datatool_load_tex:
    \tl_set:Nn \l__datatool_default_ext_tl { .dbtex }
    \bool_set_false:N \l_datatool_append_allowed_bool
},
format / dbtex-3 .code:n =
{
    \cs_set_eq:NN \__datatool_save:n \__datatool_save_db_iii:n
    \cs_set_eq:NN \__datatool_load: \__datatool_load_tex:
    \tl_set:Nn \l__datatool_default_ext_tl { .dbtex }
    \bool_set_false:N \l_datatool_append_allowed_bool
},
format / dbtex .code:n =
{
    \cs_set_eq:NN \__datatool_save:n \__datatool_save_db_iii:n
    \cs_set_eq:NN \__datatool_load: \__datatool_load_tex:
    \tl_set:Nn \l__datatool_default_ext_tl { .dbtex }
    \bool_set_false:N \l_datatool_append_allowed_bool
},
add-delimiter .choice;,
add-delimiter .value_required:n = true,
add-delimiter / always .code:n =
{
    \cs_set_eq:NN \__datatool_append_csv_item:n
        \__datatool_append_csv_item_always_delim:n
}

```

```

    },
    add-delimiter / detect .code:n =
    {
        \cs_set_eq:NN \__datatool_append_csv_item:n
        \__datatool_append_csv_item_detect_sep:n
    },
    add-delimiter / never .code:n =
    {
        \cs_set_eq:NN \__datatool_append_csv_item:n
        \__datatool_append_csv_item_no_delim:n
    },
    csv-escape-chars .choice:,
    csv-escape-chars .value_required:n = true,
    csv-escape-chars / none .code:n =
    {
        \cs_set:Nn \__datatool_save_data_postprocess:N { }
        \cs_set:Nn \__datatool_load_data_postprocess:N { }
    },
    csv-escape-chars / delim .code:n =
    {
        \cs_set_eq:NN \__datatool_save_data_postprocess:N
        \__datatool_save_escape_delim:N
        \cs_set_eq:NN \__datatool_load_data_postprocess:N
        \__datatool_load_unescape_delim:N
    },
    csv-escape-chars / delim + bksl .code:n =
    {
        \cs_set_eq:NN \__datatool_save_data_postprocess:N
        \__datatool_save_escape_delim_bksl:N
        \cs_set_eq:NN \__datatool_load_data_postprocess:N
        \__datatool_load_unescape_delim_bksl:N
    },
    csv-escape-chars / double-delim .code:n =
    {
        \cs_set_eq:NN \__datatool_save_data_postprocess:N
        \__datatool_save_double_delim:N
        \cs_set_eq:NN \__datatool_load_data_postprocess:N
        \__datatool_load_unescape_double_delim:N
    },
    csv-content .choice:,
    csv-content / literal .code:n =
    {
        \bool_set_true:N \l__datatool_csv_literal_content_bool
        \bool_set_false:N \l__datatool_csv_plain_content_bool
    },
    csv-content / tex .code:n =
    {
        \bool_set_false:N \l__datatool_csv_literal_content_bool
        \bool_set_false:N \l__datatool_csv_plain_content_bool
    },

```

Version 3.2: lines and cells are read as per `csv-content=tex` but the cell contents aren't parsed but are assumed to match the data type identified in the `data-type` option. Any numerical columns must have plain numbers (no currency symbol, no number group and a decimal point, regardless of localisation).

```

csv-content / no-parse .code:n =
  {
    \bool_set_false:N \l__datatool_csv_literal_content_bool
    \bool_set_true:N \l__datatool_csv_plain_content_bool
  },
csv-skip-lines .code:n =
  {
    \tl_if_eq:nnTF { #1 } { false }
    { \int_zero:N \dtl@omitlines }
    {
      \int_compare:nNnTF { #1 } < { 0 }
      {
        \PackageError {datatool}
        {csv-skip-lines ~ value ~ can't ~ be ~ negative}{ }
      }
      {
        \int_set:Nn \dtl@omitlines { #1 }
      }
    }
  },
omitlines .int_set:N = \dtl@omitlines,
csv-blank .choice:,
csv-blank / ignore .code:n =
  { \cs_set:Nn \__datatool_csv_blank: { } },
csv-blank / empty-row .code:n =
  { \cs_set:Nn \__datatool_csv_blank:
    { \int_incr:N \dtl@rownum \DTLdbNewRow }
  },
csv-blank / end .code:n =
  { \cs_set:Nn \__datatool_csv_blank: { \ior_map_break: } },
overwrite .choice:,
overwrite .value_required:n = true,
overwrite / error .code:n =
  {
    \cs_set_eq:NN \__datatool_overwrite_action:nn
    \__datatool_save_error_overwrite:nn
  },
overwrite / warn .code:n =
  {
    \cs_set_eq:NN \__datatool_overwrite_action:nn
    \__datatool_save_warn_overwrite:nn
  },
overwrite / allow .code:n =
  {
    \cs_set_eq:NN \__datatool_overwrite_action:nn

```

```

        \_datatool_save_allow_overwrite:nn
    },
noheader .legacy_if_set:n = dtlnoheader,
no-header .legacy_if_set:n = dtlnoheader,
autokeys .legacy_if_set:n = dtlautokeys,
auto-keys .legacy_if_set:n = dtlautokeys,
load-action .choice:,
load-action / create .code:n =
    {
        \cs_set_eq:NN \_datatool_load_init:n
        \_datatool_load_init_create:n
    },
load-action / append .code:n =
    {
        \cs_set_eq:NN \_datatool_load_init:n
        \_datatool_load_init_append:n
    },
load-action / overwrite .code:n =
    {
        \cs_set_eq:NN \_datatool_load_init:n
        \_datatool_load_init_overwrite:n
    },
load-action / detect .code:n =
    {
        \cs_set_eq:NN \_datatool_load_init:n
        \_datatool_load_init_append_or_create:n
    },
load-action / old-style .code:n =
    {
        \cs_set_eq:NN \_datatool_load_init:n
        \_datatool_load_init_old_style:n
    },
name .str_set_x:N = \l_datatool_io_name_tl,
}

```

Allow these options to be set in `\DTLsetup` and remove the separator and delimiter package options.

```

\keys_define:nn { datatool }
{
    io .code:n = { \keys_set:nn { datatool/io } { #1 } },
    display .code:n = { \keys_set:nn { datatool/display } { #1 } },
    separator .undefine:,
    delimiter .undefine:
}

```

`\DTLwrite`

`\DTLwrite[<options>]{<filename>}`

```

\NewDocumentCommand \DTLwrite { o m }

```

```

{
  \group_begin:
  \IfValueT { #1 } { \keys_set:nn { datatool/io } { #1 } }
  \tl_if_empty:NT \l__datatool_io_name_tl
  {
    \tl_set_eq:NN \l__datatool_io_name_tl \l__datatool_default_dbname_tl
  }
  \DTLifdbexists { \l__datatool_io_name_tl }
  {
    \__datatool_get_filename:n { #2 }
    \file_if_exist:nTF { \l__datatool_name_tl }
    {
      \__datatool_overwrite_action:nn { \l__datatool_name_tl }
      {
        \dtl@message { Writing ~ \l__datatool_name_tl }
        \iow_open:Nn \g__datatool_out_stream { \l__datatool_name_tl }
        \__datatool_save:n { \l__datatool_io_name_tl }
        \iow_close:N \g__datatool_out_stream
      }
    }
    {
      \iow_open:Nn \g__datatool_out_stream { \l__datatool_name_tl }
      \dtl@message { Writing ~ \l__datatool_name_tl }
      \__datatool_save:n { \l__datatool_io_name_tl }
      \iow_close:N \g__datatool_out_stream
    }
  }
  {
    \PackageError {datatool}
    { Can't ~ save ~ database ~ '\l__datatool_io_name_tl': ~
      no ~ such ~ database }
    {}
  }
}
\group_end:
}

```

Append default extension if omitted.

```

\tl_new:N \l__datatool_dir_tl
\tl_new:N \l__datatool_name_tl
\tl_new:N \l__datatool_ext_tl
\cs_new:Nn \__datatool_get_filename:n
{
  \file_parse_full_name:nNNN { #1 }
  \l__datatool_dir_tl \l__datatool_name_tl \l__datatool_ext_tl
  \tl_if_empty:NT \l__datatool_ext_tl
  {
    \tl_set_eq:NN \l__datatool_ext_tl \l__datatool_default_ext_tl
  }
  \tl_put_right:NV \l__datatool_name_tl \l__datatool_ext_tl
  \tl_if_empty:NF \l__datatool_dir_tl

```

```

    {
      \tl_if_eq:NnTF \l__datatool_dir_tl { / }
      {
        \tl_put_left:Nn \l__datatool_name_tl { / }
      }
      {
        \tl_put_left:Nx \l__datatool_name_tl { \l__datatool_dir_tl / }
      }
    }
  }
}

```

Wrapper function.

```

\cs_new:Nn \__datatool_write:n
{
  \iow_now:Nn \g__datatool_out_stream { #1 }
}
\cs_generate_variant:Nn \__datatool_write:n { x }
\cs_new:Nn \__datatool_write_wrap:n
{
  \iow_wrap:nnnN
  { #1 }
  { }
  { \dtl@init@write@wrap }
  \__datatool_write:n
}
\cs_generate_variant:Nn \__datatool_write_wrap:n { x }

```

\dtl@init@write@wrap

```

\ExplSyntaxOff
\newcommand{\dtl@init@write@wrap}{%
  \def\%{\string\}%
  \def\%{\string\}%
  \def\%{\string\}%
  \def\%{\string\}%
  \def\%{\string\}%
  \def\%{\string\}%
  \def\%{\string\}%
}
\ExplSyntaxOn

```

Save to CSV file.

```

\cs_new:Nn \__datatool_save_csv:n
{
  \l__datatool_io_csv_init_tl
  \tl_clear:N \l__datatool_row_tl
  \ifdtlnoheader
  \else
    \int_zero:N \l__datatool_col_idx_int
    \dtlforeachkey
    (

```

```

        \l__datatool_item_key_tl,
        \l__datatool_item_col_tl,
        \l__datatool_item_type_tl,
        \l__datatool_item_head_tl
    )
    \in { #1 } \do
  {
    \int_incr:N \l__datatool_col_idx_int
    \tl_if_empty:NTF \l__datatool_item_head_tl
      { \exp_args:NV \__datatool_append_csv_item:n \l__datatool_item_key_tl }
      { \exp_args:NV \__datatool_append_csv_item:n \l__datatool_item_head_tl }
  }
  \__datatool_write:x { \l__datatool_row_tl }
\fi
\int_step_inline:nn { \DTLrowcount { #1 } }
{
  \tl_clear:N \l__datatool_row_tl
  \dtlgetrow { #1 } { ##1 }
  \int_zero:N \l__datatool_col_idx_int
  \dtlforeachkey
  (
    \l__datatool_item_key_tl,
    \l__datatool_item_col_tl,
    \l__datatool_item_type_tl,
    \l__datatool_item_head_tl
  )
  \in { #1 } \do
  {
    \int_incr:N \l__datatool_col_idx_int
    \exp_args:NNx \dtlgetentryfromcurrentrow
      { \l__datatool_item_value_tl }
      { \l__datatool_item_col_tl }
    \__datatool_rm_datum:N \l__datatool_item_value_tl
    \datatool_if_null:NT \l__datatool_item_value_tl
    {
      \tl_clear:N \l__datatool_item_value_tl
    }
    \exp_args:NV \__datatool_append_csv_item:n \l__datatool_item_value_tl
  }
  \__datatool_write:x { \l__datatool_row_tl }
}
}

```

Append CSV entry to row token list. Only add delimiter if separator detected.

```

\cs_new:Nn \__datatool_append_csv_item_detect_sep:n
{
  \int_compare:nNnF
    { \l__datatool_col_idx_int } = { \c_one_int }
    { \tl_put_right:Nx \l__datatool_row_tl { \@dtl@separator } }
  \__datatool_save_data:Nn \l__datatool_tmpa_tl { #1 }
}

```

```

\exp_args:NNx
  \tl_if_in:NnTF \l__datatool_tmpa_tl { \token_to_str:N \@dtl@separator }
  {
    \tl_put_right:Nx \l__datatool_row_tl
      {
        \@dtl@delimiter \l__datatool_tmpa_tl \@dtl@delimiter
      }
  }
  {
    \tl_put_right:Nx \l__datatool_row_tl
      { \l__datatool_tmpa_tl }
  }
}

```

Always add delimiters.

```

\cs_new:Nn \__datatool_append_csv_item_always_delim:n
{
  \int_compare:nNnF
    { \l__datatool_col_idx_int } = { \c_one_int }
    { \tl_put_right:Nx \l__datatool_row_tl { \@dtl@separator } }
  \__datatool_save_data:Nn \l__datatool_tmpa_tl { #1 }
  \tl_put_right:Nx \l__datatool_row_tl
    {
      \@dtl@delimiter \l__datatool_tmpa_tl \@dtl@delimiter
    }
}

```

Don't add delimiters.

```

\cs_new:Nn \__datatool_append_csv_item_no_delim:n
{
  \int_compare:nNnF
    { \l__datatool_col_idx_int } = { \c_one_int }
    { \tl_put_right:Nx \l__datatool_row_tl { \@dtl@separator } }
  \__datatool_save_data:Nn \l__datatool_tmpa_tl { #1 }
  \tl_put_right:Nx \l__datatool_row_tl
    { \l__datatool_tmpa_tl }
}

```

Default:

```

\cs_set_eq:NN \__datatool_append_csv_item:n
  \__datatool_append_csv_item_detect_sep:n
\tl_new:N \l__datatool_save_version_comment_tl
\tl_set:Nn \l__datatool_save_version_comment_tl
{
  Created ~ by ~ datatool ~ \use:c { ver@datatool.sty } ~ on ~
  \cs_if_exist:NTF \DTMnow { \DTMnow } { \today }
}

```

Save to dltex v2 file.

```

\cs_new:Nn \__datatool_save_dltex_ii:n
{

```

```

__datatool_write:x
  { \c_percent_str \c_space_tl DTLTEX ~ 2.0 ~ \TrackLangEncodingName }
__datatool_write:x
  {
    \c_percent_str \c_space_tl \l_datatool_save_version_comment_tl
  }
__datatool_write:x
  { \token_to_str:N \DTLnewdb { #1 } \c_percent_str }

```

Content:

```

\int_step_inline:nn { \DTLrowcount { #1 } }
{
  __datatool_write:x
  { \token_to_str:N \DTLnewrow { #1 } \c_percent_str }
  \dtlgetrow { #1 } { ##1 }
  \dtlforeachkey
  (
    \l_datatool_item_key_tl,
    \l_datatool_item_col_tl,
    \l_datatool_item_type_tl,
    \l_datatool_item_head_tl
  )
  \in { #1 } \do
  {
    \exp_args:NNx \dtlgetentryfromcurrentrow
    { \l_datatool_item_value_tl }
    { \l_datatool_item_col_tl }
    \__datatool_rm_datum:N \l_datatool_item_value_tl
    \datatool_if_null:NF \l_datatool_item_value_tl
    {
      \exp_args:NNo \__datatool_save_data:Nn
      \l_datatool_item_value_tl
      { \l_datatool_item_value_tl }
      \__datatool_write_wrap:x
      {
        \token_to_str:N \DTLnewdbentry { #1 }
        { \l_datatool_item_key_tl }
        { \l_datatool_item_value_tl } \c_percent_str
      }
    }
  }
}

```

Headers (no check for headers option):

```

\dtlforeachkey
(
  \l_datatool_item_key_tl,
  \l_datatool_item_col_tl,
  \l_datatool_item_type_tl,
  \l_datatool_item_head_tl
)

```

```

\in { #1 } \do
{
  \exp_args:NNo \__datatool_save_data:Nn \l__datatool_item_head_tl
    { \l__datatool_item_head_tl }
  \__datatool_write:x
    {
      \token_to_str:N \DTLsetheader { #1 }
      { \l__datatool_item_key_tl }
      { \l__datatool_item_head_tl }
      \c_percent_str
    }
}
Trailer:
  \__datatool_write:x
    {
      \token_to_str:N \def
      \token_to_str:N \dtllastloadeddb { #1 }
      \c_percent_str
    }
}
Save to dtltex v3 file.
\cs_new:Nn \__datatool_save_dtltex_iii:n
{
  \__datatool_write:x
    { \c_percent_str \c_space_tl DTLTEX ~ 3.0 ~ \TrackLangEncodingName }
  \__datatool_write:x
    {
      \c_percent_str \c_space_tl \l__datatool_save_version_comment_tl
    }
  \__datatool_write:x
    { \token_to_str:N \DTLdbProvideData { #1 } \c_percent_str }
}
Content:
\int_step_inline:nn { \DTLrowcount { #1 } }
{
  \__datatool_write:x
    { \token_to_str:N \DTLdbNewRow }
  \dtlgetrow { #1 } { ##1 }
  \dtlforeachkey
    (
      \l__datatool_item_key_tl,
      \l__datatool_item_col_tl,
      \l__datatool_item_type_tl,
      \l__datatool_item_head_tl
    )
  \in { #1 } \do
  {
    \exp_args:NNx \dtlgetentryfromcurrentrow
      { \l__datatool_item_value_tl }
  }
}

```



```

\cs_set_eq:NN \__datatool_dbkeys_block:nnnn \__datatool_dbkeys_block_ii:nnnn
\__datatool_init_dbwrite:

```

Header:

```

\__datatool_write:x
{ \c_percent_str \c_space_tl DBTEX ~ 2.0 ~ \TrackLangEncodingName }
\__datatool_write:x
{
  \c_percent_str \c_space_tl \l__datatool_save_version_comment_tl
  \iow_newline:
  \token_to_str:N \DTLifdbexists { #1 } \c_percent_str \iow_newline:
  {
    \token_to_str:N \PackageError { datatool }
    { Database ~ `#1' ~ already ~ exists } { }
    \c_percent_str \iow_newline:
    \token_to_str:N \aftergroup
    \token_to_str:N \endinput
  }
  {} \c_percent_str \iow_newline:
  \token_to_str:N \bgroup
  \token_to_str:N \makeatletter
  \iow_newline:
  \token_to_str:N \dtl@message
  { Reconstructing ~ database ~ `#1' }
  \c_percent_str
}

```

Database Header:

```

\__datatool_write:x
{
  \token_to_str:N \expandafter
  \token_to_str:N \global
  \token_to_str:N \expandafter
  \iow_newline:
  \token_to_str:N \newtoks
  \token_to_str:N \csname \c_space_tl
  dtlkeys@#1
  \token_to_str:N \endcsname
  \iow_newline:
  \token_to_str:N \expandafter
  \token_to_str:N \global
  \iow_newline:
  \token_to_str:N \csname \c_space_tl
  dtlkeys@#1
  \token_to_str:N \endcsname =
  \iow_char:N \{ \c_percent_str
}
\exp_args:Nv \__datatool_write:x { dtlkeys@#1 }
\__datatool_write:x { \iow_char:N \} \c_percent_str }

```

Database Content:

```

\__datatool_write:x
{
  \token_to_str:N \expandafter
  \token_to_str:N \global
  \token_to_str:N \expandafter
  \iow_newline:
  \token_to_str:N \newtoks
  \token_to_str:N \csname \c_space_tl
    dtldb@#1
  \token_to_str:N \endcsname
  \iow_newline:
  \token_to_str:N \expandafter
  \token_to_str:N \global
  \iow_newline:
  \token_to_str:N \csname \c_space_tl
    dtldb@#1
  \token_to_str:N \endcsname =
  \iow_char:N \{ \c_percent_str
}
\exp_args:Nv \__datatool_write_wrap:x { dtldb@#1 }
\__datatool_write:x { \iow_char:N \} \c_percent_str }

```

Row and column count registers:

```

\__datatool_write:x
{

```

Number of Rows :

```

  \token_to_str:N \expandafter
  \token_to_str:N \global \iow_newline: \c_space_tl
  \token_to_str:N \expandafter
  \token_to_str:N \newcount
  \token_to_str:N \csname \c_space_tl
    dtlrows@#1
  \token_to_str:N \endcsname \iow_newline:
  \token_to_str:N \expandafter
  \token_to_str:N \global \iow_newline: \c_space_tl
  \token_to_str:N \csname \c_space_tl
    dtlrows@#1
  \token_to_str:N \endcsname
  = \DTLrowcount { #1 } \token_to_str:N \relax \iow_newline:

```

Number of Columns :

```

  \token_to_str:N \expandafter
  \token_to_str:N \global \iow_newline: \c_space_tl
  \token_to_str:N \expandafter
  \token_to_str:N \newcount
  \token_to_str:N \csname \c_space_tl
    dtlcols@#1
  \token_to_str:N \endcsname \iow_newline:
  \token_to_str:N \expandafter
  \token_to_str:N \global \iow_newline: \c_space_tl

```

```

        \token_to_str:N \csname \c_space_tl
          dtlcols@#1
        \token_to_str:N \endcsname
        = \DTLcolumncount { #1 } \token_to_str:N \relax
    }

```

Column label to index assignments:

```

\dtlforeachkey
(
  \l_datatool_item_key_tl,
  \l_datatool_item_col_tl,
  \l_datatool_item_type_tl,
  \l_datatool_item_head_tl
)
\in { #1 } \do
{
  \__datatool_write:x
  {
    \token_to_str:N \expandafter \iow_newline: \c_space_tl
    \token_to_str:N \gdef
      \token_to_str:N \csname \c_space_tl
        dtl@ci@#1@ \l_datatool_item_key_tl
      \token_to_str:N \endcsname
      { \l_datatool_item_col_tl }
    \c_percent_str
  }
}

```

Trailer:

```

\__datatool_write:n { \egroup }
\__datatool_write:x
{
  \token_to_str:N \def
  \token_to_str:N \dtllastloadeddb { #1 }
  \c_percent_str
}
}

```

Save to dbtex v3 file.

```

\cs_new:Nn \__datatool_save_db_iii:n
{

```

Initialise commands:

```

  \cs_set_eq:NN \__datatool_dbtex_row:nn \__datatool_dbtex_row_iii:nn
  \cs_set_eq:NN \__datatool_dbtex_value:nn \__datatool_dbtex_value_iii:nn
  \cs_set_eq:NN \__datatool_dbtex_datum:nnnn \__datatool_dbtex_datum_iii:nnnn
  \cs_set_eq:NN \__datatool_datum:w \__datatool_datum_use:w
  \cs_set_eq:NN \__datatool_dbkeys_block:nnnn \__datatool_dbkeys_block_iii:nnnn
  \cs_set_eq:NN \DTLtemporalvalue \__datatool_dbtex_temporal_value:nn
  \__datatool_init_dbwrite:

```

Header:

```

    \__datatool_write:x
      { \c_percent_str \c_space_tl DBTEX ~ 3.0 ~ \TrackLangEncodingName }
    \__datatool_write:x
      {
        \c_percent_str \c_space_tl \l__datatool_save_version_comment_tl
      }
    \__datatool_write:x
      { \token_to_str:N \DTLdbProvideData { #1 } \c_percent_str }
Database Construction:
    \__datatool_write:x { \token_to_str:N \DTLreconstructdatabase }
Number of rows and columns:
    \__datatool_write:x
      { { \DTLrowcount { #1 } } { \DTLcolumncount { #1 } } }
Database Header:
    \exp_args:Nv \__datatool_dbkeys_write_iii:n { dtlkeys@#1 }
Database Content:
    \exp_args:Nv \__datatool_dbtex_content_iii:n { dtldb@#1 }
Column label to index assignments:
    \__datatool_write:x
      { \iow_char:N \{ \c_percent_str \c_space_tl Key ~ to ~ index }
    \dtlforeachkey
      (
        \l__datatool_item_key_tl,
        \l__datatool_item_col_tl,
        \l__datatool_item_type_tl,
        \l__datatool_item_head_tl
      )
    \in { #1 } \do
  {
    \__datatool_write:x
      {
        \token_to_str:N \dtldbconstructkeyindex
        { \l__datatool_item_key_tl } { \l__datatool_item_col_tl }
        \c_percent_str
      }
  }
  \__datatool_write:x
    { \iow_char:N \} \c_percent_str \c_space_tl End ~ of ~ key ~ to ~ index }
}

```

When saving the contents of the database in a dbtex file, the datum markers need to be hidden as the \LaTeX 3 catcode changes won't be available.

DBTeX v2 writes all the internal marker tokens. Row:

```

\cs_new:Nn \__datatool_dbtex_row_ii:nn
{
  \c_percent_str \iow_newline:
  \c_percent_str \c_space_tl Start ~ of ~ Row ~ #1 \iow_newline:
}

```

```

\token_to_str:N \db@row@elt@w \c_space_tl
\c_percent_str \iow_newline:
\token_to_str:N \db@row@id@w \c_space_tl #1
\c_percent_str \iow_newline:
\token_to_str:N \db@row@id@end@ \c_space_tl
\c_percent_str \iow_newline:
#2
\c_percent_str \c_space_tl End ~ of ~ Row ~ #1 \iow_newline:
\token_to_str:N \db@row@id@w \c_space_tl #1
\c_percent_str \iow_newline:
\token_to_str:N \db@row@id@end@ \c_space_tl
\c_percent_str \iow_newline:
\token_to_str:N \db@row@elt@end@ \c_space_tl
}

```

Column value:

```

\cs_new:Nn \__datatool_dbtex_value_ii:nn
{
\c_percent_str \c_space_tl Column ~ #1 \iow_newline:
\token_to_str:N \db@col@id@w \c_space_tl #1
\c_percent_str \iow_newline:
\token_to_str:N \db@col@id@end@ \c_space_tl
\c_percent_str \iow_newline:
\token_to_str:N \db@col@elt@w \c_space_tl
\tl_if_head_eq_meaning:nNTF { #2 } \__datatool_datum:nnnn
{ #2 }
{
\tl_if_head_eq_meaning:nNTF { #2 } \__datatool_datum:w
{ #2 }
{
\__datatool_data_value:n { #2 }
}
}
\c_percent_str \iow_newline:
\token_to_str:N \db@col@elt@end@ \c_space_tl
\c_percent_str \iow_newline:
\token_to_str:N \db@col@id@w \c_space_tl #1
\c_percent_str \iow_newline:
\token_to_str:N \db@col@id@end@ \c_space_tl
\c_percent_str \c_space_tl End ~ of ~ Column ~ #1 \iow_newline:
}

```

DBTEX v2 doesn't support datum:

```

\cs_new:Nn \__datatool_dbtex_datum_ii:nnnn
{
\__datatool_data_value:n { #1 }
}

```

Header block:

```

\cs_new:Nn \__datatool_dbkeys_block_ii:nnnn
{

```

```

\c_percent_str \iow_newline:
\c_percent_str \c_space_tl Header ~ block ~ for ~ column ~ #1 \iow_newline:
\token_to_str:N \db@plist@elt@w \c_space_tl
  \c_percent_str \iow_newline:
\token_to_str:N \db@col@id@w \c_space_tl #1
  \c_percent_str \iow_newline:
\token_to_str:N \db@col@id@end@ \c_space_tl
  \c_percent_str \iow_newline:
\token_to_str:N \db@key@id@w \c_space_tl #2
  \c_percent_str \iow_newline:
\token_to_str:N \db@key@id@end@ \c_space_tl
  \c_percent_str \iow_newline:
\token_to_str:N \db@type@id@w \c_space_tl
  \__datatool_use_datatype:n { #3 }
  \c_percent_str \iow_newline:
\token_to_str:N \db@type@id@end@ \c_space_tl
  \c_percent_str \iow_newline:
\token_to_str:N \db@header@id@w \c_space_tl
  \__datatool_data_value:n { #4 }
  \c_percent_str \iow_newline:
\token_to_str:N \db@header@id@end@ \c_space_tl
  \c_percent_str \iow_newline:
\token_to_str:N \db@col@id@w \c_space_tl #1
  \c_percent_str \iow_newline:
\token_to_str:N \db@col@id@end@ \c_space_tl
  \c_percent_str \iow_newline:
\token_to_str:N \db@plist@elt@end@ \c_space_tl
}

```

DBTeX v3 hides the internal marker tokens.

```

\cs_new:Nn \__datatool_dbtex_content_iii:n
{
  \exp_args:Nx \__datatool_write_wrap:n
  {
    { \c_percent_str \c_space_tl Content \iow_newline:
      #1
    } \c_percent_str \c_space_tl End ~ of ~ Content
  }
}

```

Row:

```

\cs_new:Nn \__datatool_dbtex_row_iii:nn
{
  \c_percent_str \c_space_tl Row ~ #1 \iow_newline:
  \token_to_str:N \dtldbrowreconstruct
  { #1 } \c_percent_str
  \iow_newline: { \c_percent_str \c_space_tl Row ~ #1 ~ Content
  \iow_newline: #2
  } \c_percent_str \iow_newline:
}

```

Column value:

```
\cs_new:Nn \__datatool_dbtex_value_iii:nn
{
  \c_space_tl \c_space_tl \token_to_str:N \dtldbcolreconstruct
  { #1 } \c_percent_str \c_space_tl Column ~ #1 \iow_newline:
  \c_space_tl \c_space_tl
  {
    \tl_if_head_eq_meaning:nNTF { #2 } \__datatool_datum:nnnn
    { #2 }
    {
      \__datatool_data_value:n { #2 }
    }
  } \c_percent_str \iow_newline:
}
```

Datum:

```
\cs_new:Nn \__datatool_dbtex_datum_iii:nnnn
{
  \token_to_str:N \dtldbdatumreconstruct
  {
    \__datatool_data_value:n { #1 }
  }
  { #2 }
  { \__datatool_data_value:n { #3 } } { \number#4 }
}
```

Temporal value:

```
\cs_new:Nn \__datatool_dbtex_temporal_value:nn
{
  \token_to_str:N \DTLtemporalvalue { #1 } { #2 }
}
```

Headers:

```
\cs_new:Nn \__datatool_dbkeys_write_iii:n
{
  \exp_args:Nx \__datatool_write_wrap:n
  {
    { \c_percent_str \c_space_tl Header \iow_newline:
      #1
    } \c_percent_str \c_space_tl End ~ of ~ Header
  }
}
```

Header block:

```
\cs_new:Nn \__datatool_dbkeys_block_iii:nnnn
{
  \token_to_str:N \dtldbheaderreconstruct
  { #1 } { #2 } { #3 }
  {
    \__datatool_data_value:n { #4 }
  } \c_percent_str \iow_newline:
}
```

```
}
```

Default.

```
\cs_set_eq:NN \__datatool_dbtex_row:nn \__datatool_dbtex_row_iii:nn  
\cs_set_eq:NN \__datatool_dbtex_value:nn \__datatool_dbtex_value_iii:nn  
\cs_set_eq:NN \__datatool_dbtex_datum:nnnn \__datatool_dbtex_datum_iii:nnnn  
\cs_set_eq:NN \__datatool_dbkeys_block:nnnn \__datatool_dbkeys_block_iii:nnnn  
  
\cs_new:Nn \__datatool_init_dbwrite:  
{
```

Header markers:

```
\def \db@plist@elt@w  
  \db@col@id@w ##1 \db@col@id@end@ % ID  
  \db@key@id@w ##2 \db@key@id@end@ % label  
  \db@type@id@w ##3 \db@type@id@end@ % type  
  \db@header@id@w ##4 \db@header@id@end@ % title  
  \db@col@id@w ##5 \db@col@id@end@ % ID  
  \db@plist@elt@end@  
{  
  \__datatool_dbkeys_block:nnnn { ##1 } { ##2 } { ##3 } { ##4 }  
}
```

Content markers:

```
\def \db@row@elt@w  
  \db@row@id@w ##1 \db@row@id@end@  
  ##2  
  \db@row@id@w ##3 \db@row@id@end@  
  \db@row@elt@end@  
{  
  \__datatool_dbtex_row:nn { ##1 } { ##2 }  
}  
  
\def \db@col@id@w ##1 \db@col@id@end@  
  \db@col@elt@w ##2 \db@col@elt@end@  
  \db@col@id@w ##3 \db@col@id@end@  
{  
  \__datatool_dbtex_value:nn { ##1 } { ##2 }  
}  
  
\cs_set:Nn \__datatool_datum:nnnn  
{  
  \__datatool_dbtex_datum:nnnn { ##1 } { ##2 } { ##3 } { ##4 }  
}  
}
```

Reconstruction macros.

\dtldbrowreconstruct

```
\newcommand{\dtldbrowreconstruct}[2]{  
  \__datatool_row_markup_full:nn { #1 } { #2 }  
}
```

`\dtldbcolreconstruct` The second argument should be `\dtldbvaluereconstruct` or `\dtldbdatumreconstruct` in which case it can be allowed to expand, but if not prevent any further expansion.

```
\newcommand{\dtldbcolreconstruct}[2]{
  \__datatool_row_element_markup_full:n
  { #1 }
  {
    \tl_if_head_eq_meaning:nNTF
    { #2 } \dtldbvaluereconstruct
    { #2 }
    {
      \tl_if_head_eq_meaning:nNTF
      { #2 } \dtldbdatumreconstruct
      { #2 }
      { \exp_not:n { #2 } }
    }
  }
}
```

`\dtldbdatumreconstruct`

```
\newcommand{\dtldbdatumreconstruct}[4]{
  \__datatool_weird_datum:nnnn
  { #1 } { #2 } { #3 }
  {
    \int_case:nnF { #4 }
    {
      { \c_datatool_integer_int } { \exp_not:N \c_datatool_integer_int }
      { \c_datatool_decimal_int } { \exp_not:N \c_datatool_decimal_int }
      { \c_datatool_currency_int } { \exp_not:N \c_datatool_currency_int }
      { \c_datatool_datetime_int } { \exp_not:N \c_datatool_datetime_int }
      { \c_datatool_date_int } { \exp_not:N \c_datatool_date_int }
      { \c_datatool_time_int } { \exp_not:N \c_datatool_time_int }
      { \c_datatool_unknown_int } { \exp_not:N \c_datatool_unknown_int }
    }
    { \exp_not:N \c_datatool_string_int }
  }
}
```

`\dtldbvaluereconstruct`

```
\newcommand{\dtldbvaluereconstruct}[1]
{
  \exp_not:n { #1 }
}
```

`\dtldbheaderreconstruct`

```
\newcommand{\dtldbheaderreconstruct}[4]
{
  \exp_not:N \db@plist@elt@w
  \exp_not:N \db@col@id@w #1
  \exp_not:N \db@col@id@end@
```

```

\exp_not:N \db@key@id@w #2
\exp_not:N \db@key@id@end@
\exp_not:N \db@type@id@w #3
\exp_not:N \db@type@id@end@
\exp_not:N \db@header@id@w \exp_not:n { #4 }
\exp_not:N \db@header@id@end@
\exp_not:N \db@col@id@w #1
\exp_not:N \db@col@id@end@
\exp_not:N \db@plist@elt@end@
}

```

dtldbconstructkeyindex

```

\newcommand{\dtldbconstructkeyindex}[2]
{
\csgdef { dtl@ci@\dtllastloadeddb @ #1 } { #2 }
}

```

```

\dtl@reconstruct@data{<header>}{<content>}{<num rows>}
{<num cols>}
{<mappings>}

```

\dtl@reconstruct@data

```

\newcommand{\dtl@reconstruct@data}[5]{
\exp_args:Nxx \@dtl@reconstruct@data { #1 } {#2 }
{ #3 } { #4 } { #5 } { \dtllastloadeddb }
}
\newcommand{\@dtl@reconstruct@data}[6]{

```

Number of rows:

```

\expandafter\global
\expandafter\newcount\csname dtlrows@#6\endcsname
\expandafter\global
\csname dtlrows@#6\endcsname=#3\relax

```

Number of columns:

```

\expandafter\global
\expandafter\newcount\csname dtlcols@#6\endcsname
\expandafter\global
\csname dtlcols@#6\endcsname=#4\relax

```

Header:

```

\expandafter\global\expandafter
\newtoks\csname dtlkeys@#6\endcsname
\_datatool_token_register_gset:cn { dtlkeys@#6 } { #1 }

```

Content:

```

\expandafter\global\expandafter
\newtoks\csname dtldb@#6\endcsname
\_datatool_token_register_gset:cn { dtldb@#6 } { #2 }

```

Column label to index assignments:

```
#5  
}  
  
\ExplSyntaxOff
```

12.11.1 Deprecated Save Functions

`\@dtl@write` Used with the older functions, which are now deprecated, so `\@dtl@write` should only be defined if the older functions are used.

```
\@dtl@def@write  
  
\newcommand{\@dtl@def@write}{%  
  \newwrite\@dtl@write  
  \let\@dtl@def@write\relax  
}
```

```
\DTLsavedb{<db name>}{<filename>}
```

Save a database as an ASCII data file using the separator and delimiter given by `\@dtl@separator` and `\@dtl@delimiter`.

```
\newcommand*\DTLsavedb[2]{%  
  \DTLwrite[name={#1}, overwrite=warn, format=csv, expand=none, add-  
  delimiter=detect]{#2}%  
}
```

```
\DTLsavetexdb{<db name>}{<filename>}
```

Save a database as a \LaTeX file.

```
\newcommand*\DTLsavetexdb[2]{%  
  \DTLwrite[name={#1}, overwrite=warn, format=dtltex-2, expand=full]{#2}%  
}
```

```
\DTLsaverawdb
```

```
\newcommand*\DTLsaverawdb[2]{%  
  \DTLwrite[name={#1}, overwrite=warn, format=dbtex-2, expand=full]{#2}%  
}
```

```
\DTLprotectedsaverawdb
```

```
\newcommand*\DTLprotectedsaverawdb[2]{%  
  \DTLwrite[name={#1}, overwrite=warn, format=dbtex-2, expand=none]{#2}%  
}
```

12.12 Loading a database from an external file

\ExplSyntaxOn

\DTLdbProvideData Default definition changes the default-name option and defines \dtl\lastloadeddb. This is in case the file is simply \input instead of using \DTLread.

```
\newcommand{\DTLdbProvideData}[1]{%
  \tl_set:Nn \l__datatool_default_dbname_tl { #1 }
  \tl_set_eq:NN \dtl\lastloadeddb \l__datatool_default_dbname_tl
  \DTLifdbexists { #1 } { } { \DTLnewdb { #1 } }
}
```

\DTLreconstructdata Deprecated. Experimental version that changes category code of @ which is best avoided. TODO remove when a new rollback is provided after v3.0.

```
\newcommand{\DTLreconstructdata}{%
  \PackageWarning { datatool }
  {
    Experimental ~ command ~
    \token_to_str:N \DTLreconstructdata \c_space_tl ~
    deprecated. ~ Re-save ~ file
  }
  \DTLifdbexists{\dtl\lastloadeddb}%
  {%
    \PackageError{datatool}{Database ~ '\dtl\lastloadeddb' ~ already ~ exists}{}%
    \use_none:n
  }%
  {%
    \bgroup\makeatletter
    \let
      \dtl@db@header@reconstruct
      \dtldbheaderreconstruct
    \let
      \dtl@db@row@reconstruct
      \dtldbrowreconstruct
    \def
      \dtl@db@col@reconstruct
      ##1 ##2
    {
      \__datatool_row_element_markup_full:n
      { ##1 }
      {
        \tl_if_head_eq_meaning:nNTF
          { ##2 } \dtl@db@value@reconstruct
          { ##2 }
          {
            \tl_if_head_eq_meaning:nNTF
              { ##2 } \dtl@db@datum@reconstruct
              { ##2 }
              { \exp_not:n { ##2 } }
          }
      }
    }
  }
```

```

    }
  }
  \cs_set_eq:NN
  \dtl@db@datum@reconstruct
  \dtldbdatumreconstruct
  \cs_set_eq:NN
  \dtl@db@value@reconstruct
  \dtldbvaluereconstruct
  \cs_set_eq:NN
  \dtl@db@reconstruct@keyindex
  \dtldbreconstructkeyindex
  \@DTLreconstructdata
}
}
}

```

\@DTLreconstructdata

```

\newcommand{\@DTLreconstructdata}[5]{%
  \dtl@message{Reconstructing ~ database ~ `~\dtl@lastloadeddb'}%
  \dtl@reconstruct@data{#1}{#2}{#3}{#4}{#5}%
  \egroup
}

```

\DTLreconstructdbdata{<header>}{<content>}{<rows>}{<cols>}{<index>}

\DTLreconstructdbdata

Deprecated. Experimental command dropped in favour of \DTLreconstructdatabase, which has the number of rows and columns at the start.

```

\newcommand{\DTLreconstructdbdata}[5]{
  \DTLifdbexists {\dtl@lastloadeddb}
  {
    \PackageError{datatool}{Database ~ `~\dtl@lastloadeddb' ~ already ~ exists}{}
  }
  {
    \dtl@message{Reconstructing ~ database ~ `~\dtl@lastloadeddb'}
    \dtl@reconstruct@data{#1}{#2}{#3}{#4}{#5}%
  }
}

```

\DTLreconstructdatabase{<rows>}{<cols>}{<header>}{<content>}{<index>}

\DTLreconstructdatabase

This has the number of rows and columns in the first two arguments, which makes it easier for datatool to parse.

```

\newcommand{\DTLreconstructdatabase}[5]{
  \DTLifdbexists {\dtl@lastloadeddb}
  {

```

```

    \PackageError{datatool}{Database ~ `dtllastloadeddb' ~ already ~ exists}{}
  }
  {
    \dtl@message{Reconstructing ~ database ~ `dtllastloadeddb'}
    \dtl@reconstruct@data{#3}{#4}{#1}{#2}{#5}%
  }
}

```

Behaviour of \DTLdbProvideData within \DTLread:

```

\cs_new:Nn \__datatool_provide_data:n
{
  \tl_if_empty:NT \l__datatool_io_name_tl
  {
    \tl_set:Nn \l__datatool_io_name_tl { #1 }
  }
  \tl_set_eq:NN \dtllastloadeddb \l__datatool_io_name_tl
  \tl_set_eq:NN \l__datatool_default_dbname_tl \l__datatool_io_name_tl
}

```

Don't create the database for the dbtex formats as the database internals are created either explicitly (dbtex v2.0) or via \DTLreconstructdatabase.

```

  \tl_if_eq:NnF \l__datatool_default_ext_tl { .dbtex }
  { \__datatool_load_init:n { \dtllastloadeddb } }
}

```

Behaviour of \@sDTLsetheader within \DTLread if noheader on:

```

\cs_new:Nn \__datatool_set_no_header:nnn
{
  \@sDTLifhaskey { #1 } { #2 }
  {
    \int_set:Nn \dtlcolumnnum { \dtlcolumnindex { #1 } { #2 } }
    \prop_get:NVN \l__datatool_csv_headers_prop \dtlcolumnnum
      \l__datatool_tmpb_tl
    \quark_if_no_value:NTF \l__datatool_tmpb_tl
    {
      \dtl@message{Ignoring ~ header ~ for ~ column ~ `#2' ~ in ~
        database ~ `#1' ~ (no-header=true ~ and ~ no ~ corresponding ~
        key ~ in ~ headers ~ option)}
    }
    {
      \tl_set_eq:NN \l__datatool_item_head_tl \l__datatool_tmpb_tl
      \exp_args:Nnnx \@dtl@setheaderforindex { #1 } { \dtlcolumnnum }
        { \exp_not:o { \l__datatool_item_head_tl } }
    }
  }
}
{
  \dtl@message{Ignoring ~ header ~ for ~ column ~ `#2' ~ in ~
    database ~ `#1' ~ (no-header=true ~ and ~ no ~ column ~ with ~ that ~ key)}
}
}

```

\DTLread \DTLread[⟨options⟩]{⟨file⟩}

Reads a database from the given file according to the format option.

```

\NewDocumentCommand \DTLread { o m }
{
  \group_begin:
    \cs_set_eq:NN \DTLdbProvideData \__datatool_provide_data:n
    \IfValueT { #1 } { \keys_set:nn { datatool/io } { #1 } }
    \bool_set_true:N \l__datatool_db_global_bool
    \ifdtlnoheader
      \cs_set_eq:NN \@sDTLsetheader \__datatool_set_no_header:nnn
    \fi
    \__datatool_get_filename:n { #2 }
    \file_if_exist:nTF { \l__datatool_name_tl }
    {
      \__datatool_load:
      \tl_if_eq:NNTF
        \l__datatool_io_name_tl \dtllastloadeddb
      {
        \PackageWarning { datatool }
          { Database ~ name ~ '\l__datatool_io_name_tl' ~ requested ~
            but ~ name ~ hardcoded ~ in ~ file ~ as ~ '\dtllastloadeddb ' }
      }
    }
    {
      \PackageError { datatool }
        { Can't ~ open ~ file ~ '\l__datatool_name_tl' }
        {}
    }
    \global\let\dtllastloadeddb\dtllastloadeddb
  \group_end:
}
\int_new:N \l__datatool_line_int
  Load CSV/TSV file:
\cs_new:Nn \__datatool_load_csv:
{
  \tl_if_empty:NT \l__datatool_io_name_tl
  {
    \tl_set_eq:NN \l__datatool_io_name_tl \l__datatool_default_dbname_tl
  }
  \int_zero:N \dtlrownum
  \__datatool_load_init:n { \l__datatool_io_name_tl }
  \int_zero:N \l__datatool_line_int
  \l__datatool_io_csv_init_tl
  \exp_args:NV \char_set_catcode_other:N \@dtl@delimiter
  \exp_args:NV \char_set_catcode_other:N \@dtl@separator
  \char_set_catcode_other:n { \% }
  \ior_open:Nn \g__datatool_in_stream { \l__datatool_name_tl }
  \bool_if:NNTF \l__datatool_csv_literal_content_bool
  {

```

```

\ior_str_map_inline:Nn \g_datatool_in_stream
{
  \__datatool_parse_csv_line:nN { ##1 }
  \__datatool_parse_str_csv_process_item:n
}
}
{
\ior_map_inline:Nn \g_datatool_in_stream
{
  \__datatool_parse_csv_line:nN { ##1 }
  \__datatool_parse_csv_process_item:n
}
}

```

Headers need setting now that the data type has been found.

```

\int_step_function:nN
{ \int_use:c { dtlcols@ \l__datatool_io_name_tl } }
\__datatool_parse_csv_add_header:n

```

Close stream.

```

\ior_close:N \g_datatool_in_stream
\tl_set_eq:NN \dtllastloadeddb \l__datatool_io_name_tl
}

```

Add column header but check first if the key is already defined in case of load-action-append:

```

\cs_new:Nn \__datatool_parse_csv_add_header:n
{
  \prop_get:NnN
    \l__datatool_csv_types_prop { #1 }
    \l__datatool_tmpb_tl
  \quark_if_no_value:NTF \l__datatool_tmpb_tl
  {
    \tl_set:NV \l__datatool_item_type_tl \c_datatool_string_int
  }
  {
    \tl_set_eq:NN \l__datatool_item_type_tl \l__datatool_tmpb_tl
  }
}

```

Has a key has been provided for this column?

```

\prop_get:NnN
  \l__datatool_csv_keys_prop { #1 }
  \l__datatool_tmpb_tl
\quark_if_no_value:NTF \l__datatool_tmpb_tl
{

```

No key has been provided for this column, so create a default.

```

  \tl_set:Nx \l__datatool_item_key_tl
    { \dtldefaultkey #1 }
}
{

```

A key has been provided for this column, so use that.

```
\tl_set_eq:NN \l__datatool_item_key_tl \l__datatool_tmpb_tl
}
\@DTLifhaskey { \l__datatool_io_name_tl } \l__datatool_item_key_tl
{ }
{ }
```

Has a header has been provided for this column?

```
\prop_get:NnN \l__datatool_csv_headers_prop { #1 }
\l__datatool_tmpb_tl
\quark_if_no_value:NTF \l__datatool_tmpb_tl
{ }
```

No header has been provided for this column, so use the key.

```
\tl_set_eq:NN \l__datatool_item_head_tl \l__datatool_item_key_tl
}
{
\tl_set_eq:NN \l__datatool_item_head_tl \l__datatool_tmpb_tl
}
\tl_if_empty:NTF \l__datatool_item_type_tl
{
\tl_set_eq:NN \l__datatool_item_type_int
\c_datatool_unknown_int
}
{
\tl_set:Nn \l__datatool_item_type_int
{ \l__datatool_item_type_tl }
}
\__datatool_token_register_gput_right:cx
{ dtlkeys@ \l__datatool_io_name_tl }
{
\tl__datatool_column_markup:nVVV
{ #1 }
\tl__datatool_item_key_tl
\tl__datatool_item_type_int
\tl__datatool_item_head_tl
}
}
```

Define the key to column index mapping:

```
\tl_gset:cx
{ dtl@ci@ \l__datatool_io_name_tl @ \l__datatool_item_key_tl }
{ #1 }
}
}
```

Action for blank line:

```
\cs_new:Nn \__datatool_csv_blank: { }
```

The literal setting is awkward as letters still need to have the letter category code (or be active UTF-8).

```
\cs_new:Nn \__datatool_parse_csv_process_item:n
{ }
```

TODO replace with `__datatool_process_new_value:n?`

```
\@dtl@setnewvalue { #1 }
\tl_set:NV \l__datatool_item_value_tl \@dtl@toks
\__datatool_load_data_postprocess:N \l__datatool_item_value_tl
}

\tl_new:N \l__datatool_str_csv_regex_cases_tl
\tl_set:Nn \l__datatool_str_csv_regex_cases_tl
{
replace \n, \r and \f with a space
{ \x { 5C } [ nrf ] } { ~ }
replace \t with a tab character
{ \x { 5C } t } { \t }
replace \ with \textbackslash_
{ \c0(\x{5C}) } { \x{ 5C } textbackslash \cS\x{20} }
replace special character <c> with \<c> for # $ % & _ { and }
{ \c0(\x{23}|\x{24}|\x{25}|\x{26}|\x{5F}|\x{7B}|\x{7D}) } { \x{ 5C } \1 }
replace ^ with \textasciicircum_
{ \c0(\x{5E}) } { \x{ 5C } textasciicircum \cS\x{20} }
replace ~ with \textasciitilde_
{ \c0(\x{7E}) } { \x{ 5C } textasciitilde \cS\x{20} }
}

\cs_new:Nn \__datatool_parse_str_csv_process_item:n
{
\tl_set:Nn \l__datatool_item_value_tl { #1 }
\__datatool_load_data_postprocess:N \l__datatool_item_value_tl
\exp_args:NV \regex_replace_case_all:nN
\l__datatool_str_csv_regex_cases_tl
\l__datatool_item_value_tl
\exp_args:NNnV \tl_set_rescan:Nnn \l__datatool_item_value_tl { }
\l__datatool_item_value_tl
\dtl@domappings \l__datatool_item_value_tl
}
}
```

Test for blank line. Note that a blank line may be represented as a series of separator characters without anything else. This is checked for by the regex. This command may be redefined to omit the regular expression match if not appropriate, but the regular expression variable is private as it's redefined by `\DTLsetseparator`.

```
\cs_new:Nn \datatool_if_blank_line:nTF
{
\tl_if_blank:nTF { #1 }
{ #2 }
{
\tl_if_eq:nnTF { #1 } { \par }
{ #2 }
{
}
```

```

        \regex_match:NnTF \l__datatool_blank_row_regex { #1 }
        { #2 } { #3 }
    }
}
\cs_new:Nn \__datatool_parse_csv_line:nN
{
  \int_incr:N \l__datatool_line_int
  \int_compare:nNnT
    { \l__datatool_line_int } > { \dtl@omitlines }
  {
    \datatool_if_blank_line:nTF { #1 }
    {
      \__datatool_csv_blank:
    }
    {
      \tl_set:Nn \l__datatool_row_tl { #1 }
    }
  }
}

```

Split the line on the separator.

```

  \__datatool_split_line:
  \int_zero:N \dtlcolumnnum
  \dtlcurrentrow = { }

```

Iterate over each item in the row.

```

  \seq_map_inline:Nn \l__datatool_row_seq
  {
    \int_incr:N \dtlcolumnnum
    \tl_set:Nx \l__datatool_item_col_tl
      { \int_use:N \dtlcolumnnum }
    #2 { ##1 }
    \legacy_if:nTF { dtlnoheader }
    {

```

Row of data.

```

  \__datatool_csv_set_auto_reformat:
  \bool_if:nTF \l__datatool_csv_plain_content_bool
  {
    \__datatool_no_parse_csv_item:
  }
  {
    \__datatool_parse_csv_item:
  }
  \__datatool_csv_check_col_idx:

```

Append this item to the current row token register. This only needs a local assignment.

```

  \__datatool_token_register_put_right:Nx
  \dtlcurrentrow
  {
    \__datatool_row_element_markup:VV
    \l__datatool_item_col_tl
    \l__datatool_item_value_tl
  }

```

```

    }
  }
  {

```

Header row. Get the column label (key).

```

    \legacy_if:nTF { dtlautokeys }
  {

```

The autokeys setting is on so generate the default key.

```

    \tl_set:Nx \l__datatool_item_key_tl
      { \dtldefaultkey \l__datatool_item_col_tl }
    \prop_put:NVV \l__datatool_csv_keys_prop
      \l__datatool_item_col_tl \l__datatool_item_key_tl
  }
  {
    \prop_get:NVN
      \l__datatool_csv_keys_prop \l__datatool_item_col_tl
      \l__datatool_tmpb_tl
    \quark_if_no_value:nTF \l__datatool_tmpb_tl
      {

```

No key has been provided and autokeys is off so use the header as the key.

```

        \tl_set:Nx \l__datatool_item_key_tl
          { \tl_to_str:V \l__datatool_item_value_tl }
        \prop_put:NVV \l__datatool_csv_keys_prop
          \l__datatool_item_col_tl \l__datatool_item_key_tl
      }
    {
      \tl_set_eq:NN
        \l__datatool_item_key_tl
        \l__datatool_tmpb_tl
    }
  }
}

```

If a key already exists for this column then either we're appending or there's a duplicate key.

```

  \__datatool_csv_check_key:

```

Has a header been provided?

```

  \prop_if_in:NVF
    \l__datatool_csv_headers_prop
    \l__datatool_item_col_tl
  {

```

A header has not been provided for this column so use the value found on this line of the file.

```

    \prop_put:NVV
      \l__datatool_csv_headers_prop
      \l__datatool_item_col_tl
      \l__datatool_item_value_tl
  }
}

```

Unless data-types has been used, no information is currently available about the data type so header information needs to be saved (in the property map) and set later.

```

    }
  }
  \legacy_if:nTF { dtlnoheader }
  {

```

Globally append this row of data to the database token register.

```

    \int_incr:N \dtlrownum
    \__datatool_token_register_gput_right:cx
    { dtldb@ \l__datatool_io_name_tl }
    {
      \__datatool_row_markup:VV
      \dtlrownum
      \dtlcurrentrow
    }

```

Globally increment the row count.

```

    \int_gincr:c
    { dtlrows@ \l__datatool_io_name_tl }
  }
  {

```

Header has been found. The next row will be data.

```

    \legacy_if_set_true:n { dtlnoheader }
  }

```

If the number of columns is greater than the current column count for the database, update it.

```

    \__datatool_csv_check_col_count:
  }
}
}

```

Version 3.2: function for parsing CSV item:

```

\cs_new:Nn \__datatool_parse_csv_item:
{

```

Check if this column shouldn't be parsed:

```

  \seq_if_in:NVTF
  \l__datatool_no_parse_cols_seq
  \l__datatool_item_col_tl
  {
    \tl_if_empty:NTF \l__datatool_item_value_tl
    { \int_set_eq:NN \@dtl@datatype \c_datatool_unknown_int }
    { \int_set_eq:NN \@dtl@datatype \c_datatool_string_int }
  }
  {

```

Check if this column should be converted:

```

  \bool_if:NTF \l__datatool_csv_convert_bool
  {

```

Convert if number.

```
\prop_get:NVN
  \l__datatool_csv_types_prop \l__datatool_item_col_tl
  \l__datatool_tmpb_tl
\quark_if_no_value:NTF \l__datatool_tmpb_tl
{
  \int_set_eq:NN \@dtl@datatype \c_datatool_unknown_int
}
{
  \int_set:Nn \@dtl@datatype { \l__datatool_tmpb_tl }
}
\datatool_if_temporal_datum_type:nTF { \@dtl@datatype }
{
  \__datatool_parse:NV
  \l__datatool_tmpa_tl
  \l__datatool_item_value_tl
}
{
  \datatool_if_numeric_datum_type:nTF { \@dtl@datatype }
  {
    \int_compare:nNnTF
      { \@dtl@datatype } = { \c_datatool_currency_int }
      {
        \exp_args:NV \DTLdecimaltocurrency
        \l__datatool_item_value_tl
        \l__datatool_tmpa_tl
      }
      {
        \exp_args:NV \DTLdecimaltolocale
        \l__datatool_item_value_tl
        \l__datatool_tmpa_tl
      }
    }
  }
  {
    \__datatool_parse:NV
    \l__datatool_tmpa_tl
    \l__datatool_item_value_tl
  }
}
\int_set:Nn \@dtl@datatype { \DTLdatumtype \l__datatool_tmpa_tl }
\bool_if:NF \l__datatool_db_store_datum_bool
{
  \tl_set:Nc \l__datatool_item_value_tl
  { \l__datatool_tmpa_tl }
}
}
{
```

Parse to determine data type.

```
\__datatool_parse:NV
```

```

        \l__datatool_tmpa_tl
        \l__datatool_item_value_tl
    }
}

```

If store-datum option on, set the current item to its datum representation.

```

\bool_if:NT \l__datatool_db_store_datum_bool
{

```

Convert to weird datum.

```

    \__datatool_to_weird_datum:N \l__datatool_tmpa_tl
    \tl_set_eq:NN
        \l__datatool_item_value_tl
        \l__datatool_tmpa_tl
}

```

If the data type was determined (that is, the item isn't empty), update the column meta-data if applicable.

```

\int_compare:nNnF
{ \@dtl@datatype } = { \c_datatool_unknown_int }
{
    \prop_get:NVN
        \l__datatool_csv_types_prop \l__datatool_item_col_tl
        \l__datatool_tmpb_tl
    \quark_if_no_value:NTF \l__datatool_tmpb_tl
    {
        \prop_put:NVx
            \l__datatool_csv_types_prop
            \l__datatool_item_col_tl
            { \number\@dtl@datatype }
    }
}
{
    \tl_set_eq:NN
        \l__datatool_item_type_tl
        \l__datatool_tmpb_tl
    \int_compare:nNnT
        { \@dtl@datatype } > { \l__datatool_item_type_tl }
    {
        \prop_put:NVx
            \l__datatool_csv_types_prop \l__datatool_item_col_tl
            { \number\@dtl@datatype }
    }
}
}
}
}

```

Just for csv-content=no-parse:

```

\cs_new:Nn \__datatool_no_parse_csv_item:
{

```

Assume string if no information provided in data-types:

```

    \int_set_eq:NN

```

```

\@dtl@datatype
\c_datatool_string_int
\prop_if_empty:NTF \l__datatool_csv_types_prop
{
  \prop_put:NVx
  \l__datatool_csv_types_prop \l__datatool_item_col_tl
  { \number\@dtl@datatype }
}
{
  \prop_get:NVN
  \l__datatool_csv_types_prop
  \l__datatool_item_col_tl
  \l__datatool_tmpb_tl
  \quark_if_no_value:NTF \l__datatool_tmpb_tl
  {

```

Assume same as the final data type unless this is the first column:

```

  \prop_get:NeN
  \l__datatool_csv_types_prop
  { \int_eval:n { \l__datatool_item_col_tl - \c_one_int } }
  \l__datatool_tmpb_tl
  \quark_if_no_value:NF \l__datatool_tmpb_tl
  {
    \int_set:Nn \@dtl@datatype { \l__datatool_tmpb_tl }
  }
  \prop_put:NVx
  \l__datatool_csv_types_prop \l__datatool_item_col_tl
  { \number\@dtl@datatype }
}
{
  \int_set:Nn \@dtl@datatype { \l__datatool_tmpb_tl }
}
}
\tl_set_eq:NN
  \l__datatool_datum_original_value_tl
  \l__datatool_item_value_tl
\tl_clear:N \l__datatool_datum_value_tl
\tl_clear:N \l__datatool_datum_currency_tl
\datatool_if_numeric_datum_type:nT { \@dtl@datatype }
{
  \tl_set_eq:NN
  \l__datatool_datum_value_tl
  \l__datatool_item_value_tl

```

Column has been identified with a numeric type. Does it need converting?

```

\bool_if:NTF \l__datatool_csv_convert_bool
{
  \int_case:nn { \@dtl@datatype }
  {
    { \c_datatool_integer_int }
  }
}

```

```

        \exp_args:NV \DTLdecimaltolocale
        \l_datatool_datum_original_value_tl
        \l_datatool_item_value_tl
    }
}
{ \c_datatool_decimal_int }
{
    \exp_args:NV \DTLdecimaltolocale
    \l_datatool_datum_original_value_tl
    \l_datatool_item_value_tl
}
}
{ \c_datatool_currency_int }
{
    \exp_args:NV \DTLdecimaltocurrency
    \l_datatool_datum_original_value_tl
    \l_datatool_item_value_tl
}
}
{ \c_datatool_datetime_int }
{
    \datatool_decimal_to_temporal:NnV
    \l_datatool_item_value_tl
    { \c_datatool_datetime_int }
    \l_datatool_datum_original_value_tl
}
}
{ \c_datatool_date_int }
{
    \datatool_decimal_to_temporal:NnV
    \l_datatool_item_value_tl
    { \c_datatool_date_int }
    \l_datatool_datum_original_value_tl
}
}
{ \c_datatool_time_int }
{
    \datatool_decimal_to_temporal:NnV
    \l_datatool_item_value_tl
    { \c_datatool_time_int }
    \l_datatool_datum_original_value_tl
}
}
}

```

Bit strange to want conversion but not store as datum but allow it anyway.

```

\bool_if:NF \l_datatool_db_store_datum_bool
{
    \exp_args:NV \tl_if_head_eq_meaning:nNF
    \l_datatool_item_value_tl
    \__datatool_datum:nnnn
    {
        \tl_set:Ne \l_datatool_item_value_tl
        { \l_datatool_item_value_tl }
    }
}
}

```

```

}
{
  \int_compare:nNT { \@dtl@datatype } = { \c_datatool_currency_int }
  {

```

No conversion requested but markup currency.

```

    \tl_set:Nn
      \l__datatool_datum_currency_tl
      { \DTLcurr { \DTLCurrencyCode } }
    \tl_set:Ne \l__datatool_item_value_tl
      {
        \exp_not:N \DTLcurrency
        { \exp_not:V \l__datatool_datum_value_tl }
      }
    \tl_set_eq:NN
      \l__datatool_datum_original_value_tl
      \l__datatool_item_value_tl
  }
}
}
}

```

If store-datum option on, set the current item to its datum representation.

```

\bool_if:NT \l__datatool_db_store_datum_bool
{
  \exp_args:NV \tl_if_head_eq_meaning:nNF
    \l__datatool_item_value_tl
    \__datatool_datum:nnnn
  {
    \tl_set:Ne \l__datatool_item_value_tl
      {
        \exp_not:N \__datatool_datum:nnnn
        { \exp_not:V \l__datatool_datum_original_value_tl }
        { \l__datatool_datum_value_tl }
        { \exp_not:V \l__datatool_datum_currency_tl }
        { \int_use:N \@dtl@datatype }
      }
  }
}

```

Convert to weird datum.

```

  \__datatool_to_weird_datum_no_parse:N \l__datatool_item_value_tl
}
}

```

Splitting is awkward because the delimiter needs to be taken into account.

```

\cs_new:Nn \__datatool_split_line:n
{
  \tl_set:Nn \l__datatool_row_tl { #1 }
  \__datatool_split_line:
}
\seq_new:N \l__datatool_row_seq
\cs_new:Nn \__datatool_split_line:

```

```

{
  \exp_args:NNV \seq_set_split_keep_spaces:NnV \l__datatool_tmp_seq
    \@dtl@separator \l__datatool_row_tl
  \seq_clear:N \l__datatool_row_seq
  \tl_set:Nn \l__datatool_item_value_tl { \q_no_value }
  \__datatool_map_row_seq:
  \quark_if_no_value:NF \l__datatool_item_value_tl
  {
    \seq_put_right:NV \l__datatool_row_seq \l__datatool_item_value_tl
  }
}
\cs_new:Nn \__datatool_map_row_seq:
{
  \seq_pop_left:NN \l__datatool_tmp_seq \l__datatool_tmpb_tl
  \quark_if_no_value:NF \l__datatool_tmpb_tl
  {
    \quark_if_no_value:NTF \l__datatool_item_value_tl
    {
      \regex_replace_once:NnNTF \l__datatool_delim_both_regex { \1 }
        \l__datatool_tmpb_tl
      {
        \seq_put_right:NV \l__datatool_row_seq \l__datatool_tmpb_tl
      }
    }
    \regex_replace_once:NnNTF \l__datatool_delim_left_regex { }
      \l__datatool_tmpb_tl
    {
      \tl_set_eq:NN \l__datatool_item_value_tl \l__datatool_tmpb_tl
    }
    {
      \bool_if:NT \l__datatool_new_element_trim_bool
      {
        \tl_trim_spaces:N \l__datatool_tmpb_tl
      }
      \seq_put_right:NV \l__datatool_row_seq \l__datatool_tmpb_tl
    }
  }
}
}
{

```

Version 3.3: bug fix (middle part missing if multiple separators in delimited cell). If we've reached here, the cell is under construction. Only end the cell construction if the closing separator is found.

```

  \regex_replace_once:NnNTF \l__datatool_delim_right_regex { }
    \l__datatool_tmpb_tl
  {
    \tl_put_right:NV \l__datatool_item_value_tl \@dtl@separator
    \tl_put_right:NV \l__datatool_item_value_tl \l__datatool_tmpb_tl
    \seq_put_right:NV \l__datatool_row_seq \l__datatool_item_value_tl
    \tl_set:Nn \l__datatool_item_value_tl { \q_no_value }
  }

```

```

    }
    {
      \tl_put_right:NV \l__datatool_item_value_tl \@dtl@separator
      \tl_put_right:NV \l__datatool_item_value_tl \l__datatool_tmpb_tl
    }
  }
  \__datatool_map_row_seq:
}
}
Load DTLTEX or DBTEX file:
\cs_new:Nn \__datatool_load_tex:
{
  \tl_clear:N \dtllastloadeddb
  \file_input:n { \l__datatool_name_tl }
  \tl_if_empty:NT \l__datatool_io_name_tl
  {
    \tl_set_eq:NN \l__datatool_io_name_tl \dtllastloadeddb
  }
}
\ExplSyntaxOff

```

\DTLloaddbtex

`\DTLloaddbtex{<cs>}{<file>}`

Version 3.0: This now just uses \DTLread and assigns the control sequence.

```

\newcommand*{\DTLloaddbtex}[2]{%
  \DTLread[format=dbtex]{#2}%
  \let#1\dtllastloadeddb
}

```

\DTLloaddb

`\DTLloaddb[<options>]{<db name>}{<filename>}`

Version 3.0: rewritten to simply use \DTLread.

```

\NewDocumentCommand\DTLloaddb{0{mm}}{%
  \DTLread[name={#2},format=csv, csv-content=tex,#1]{#3}%
}

```

\DTLloadrawdb

`\DTLloadrawdb[<options>]{<db name>}{<filename>}`

```

\NewDocumentCommand\DTLloadrawdb{0{mm}}{%
  \DTLread[name={#2},format=csv, csv-content=literal,#1]{#3}%
}

```

\DTLrawmap

`\DTLrawmap{<string>}{<replacement>}`

Additional mappings to perform when reading a raw data file. Version 3.0: this is still supported for the literal CSV read.

```

\newcommand*\DTLrawmap}[2]{%
  \expandafter\@dtl@toks\expandafter{\@dtl@rawmappings}%
  \ifdefempty{\@dtl@rawmappings}%
  {%
    \def\@dtl@rawmappings{#1}{#2}%
  }%
  {%
    \def\@dtl@tmp{#1}{#2}%
    \protected@edef\@dtl@rawmappings{\the\@dtl@toks,\@dtl@tmp}%
  }%
}

```

\@dtl@rawmappings List of mappings.

```

\newcommand*\@dtl@rawmappings{}

```

\dtl@domappings

`\dtl@domappings{<cmd>}`

Do all mappings in string given by <cmd>.

```

\newcommand*\dtl@domappings}[1]{%
  \for\@dtl@map:=\@dtl@rawmappings\do{%
    \expandafter\DTLsubstituteall\expandafter#1\@dtl@map
  }%
}

```

12.13 Debugging commands

These commands are provided to assist debugging

\DTLdbLog

`\DTLdbLog{<db name>}`

Writes detailed information in the log file about the database structure. NB this uses a regex for convenience but it means that it can only be used for small database as l3regex can't handle more than 32732 tokens. For large databases, try saving as dbtex instead. This is here to debug the code to check for incorrect markup.

```

\ExplSyntaxOn
\NewDocumentCommand{\DTLdbLog} { m }
{
  \group_begin:
  \tl_set:Nv \__datatool_tmpa_tl { dtldb@#1 }
  \regex_replace_case_all:nN

```

```

{
  { \c{ db@row@elt@w } } { < ROW \ BLOCK \ START > ^^J }
  { \c{ db@row@elt@end@ } } { < ROW \ BLOCK \ END > ^^J }
  { \c{ db@row@id@w } } { \ < ROW \ ID \ DELIM \ START > }
  { \c{ db@row@id@end@ } } { < ROW \ ID \ DELIM \ END > ^^J }
  { \c{ db@col@id@w } } { \ \ < COL \ ID \ DELIM \ START > }
  { \c{ db@col@id@end@ } } { < COL \ ID \ DELIM \ END > ^^J }
  { \c{ db@col@elt@w } } { \ \ \ < ELEMENT \ START > }
  { \c{ db@col@elt@end@ } } { < ELEMENT \ END > ^^J }
}
__datatool_tmpa_tl
\PackageInfo { datatool }
{
  Details ~ of ~ database ~ `#1': ^^J
  Column ~ Count: ~ \DTLcolumncount{#1}. ~
  Row ~ Count: ~ \DTLrowcount{#1}. ^^J
  Correctly ~ formatted ~ database ~ content ~
  should ~ have ~ each ~ row ~ marked ~ up ~
  with: ^^J
  <ROW ~ BLOCK ~ START> ^^J
  <ROW ~ ID ~ DELIM ~ START> rowidx
  <ROW ~ ID ~ DELIM ~ END> ^^J
  column data ^^J
  <ROW ~ ID ~ DELIM ~ START> rowidx
  <ROW ~ ID ~ DELIM ~ END> ^^J
  <ROW ~ BLOCK ~ END>^^J
  Content ~ of ~ `#1':^^J
  \exp_not:V __datatool_tmpa_tl
}
\group_end:
}
\ExplSyntaxOff

```

\dtlshowdb

`\dtlshowdb{<db name>}`

Shows the database.

```

\newcommand*{\dtlshowdb}[1]{%
  \ifcsundef{dtldb@#1}%
  {\PackageError{datatool}{Database `#1' not defined}{}}%
  {\expandafter\showthe\csname dtldb@#1\endcsname}%
}

```

\dtlshowdbkeys

`\dtlshowdbkeys{<db name>}`

Shows the key list for the named database.

```

\newcommand*{\dtlshowdbkeys}[1]{%

```

```

\ifcsundef{dtlkeys@#1}%
{\PackageError{datatool}{Database `#1' not defined}{}}%
{\expandafter\showthe\csname dtlkeys@#1\endcsname}%
}

```

\dtlshowtype

```
\dtlshowtype{<db name>}{<key>}
```

Show the data type for given key in the named database. This should be an integer from 0 to 3.

```

\newcommand*{\dtlshowtype}[2]{%
\ifcsundef{dtldb@#1}%
{\PackageError{datatool}{Database `#1' not defined}{}}%
{\DTLgetdatatype{\@dtl@type}{#1}{#2}\show\@dtl@type}%
}

```

12.14 Deprecated

These commands are marked for removal.

\@dtl@construct@lopoff

```
\@dtl@construct@lopoff<separator char><delimiter char>
```

This defines

```
\@dtl@lopoff<first element><sep><rest of list>\to<cmd1><cmd2>
```

for the current separator and delimiter.

```

\edef\@dtl@construct@lopoff#1#2{%
\noexpand\long
\def\noexpand\@dtl@lopoff#1##1##2\noexpand\to##3##4{%
\noexpand\ifx##1\noexpand\relax
\noexpand\ifstrempy{##1}%
{\noexpand\@dtl@qlopoff#1{##2}\noexpand\to##3##4\relax}%
}%
\noexpand\dtl@ifsingle{##1}%
{\noexpand\@dtl@qlopoff#1##1##2\noexpand\to##3##4\relax}%
{\noexpand\@dtl@qlopoff#1{##1}##2\noexpand\to##3##4\relax}%
}%
\noexpand\else
\noexpand\ifstrempy{##1}%
{\noexpand\@dtl@lopoff#1{##2}\noexpand\to##3##4\relax}%
}%
\noexpand\dtl@ifsingle{##1}%
{\noexpand\@dtl@lopoff#1##1##2\noexpand\to##3##4\relax}%
}

```

```

        {\noexpand\@dtl@lop@ff#1{##1}##2\noexpand\to##3##4\relax}%
    }%
    \noexpand\fi
}
}
}

```

`\@dtl@construct@qlopoff<separator char><delimiter char>`

This constructs `\@dtl@qlopoff` to be used when the entry is surrounded by the current delimiter value.

```

\edef\@dtl@construct@qlopoff#1#2{%
  \noexpand\long
  \noexpand\def\noexpand\@dtl@qlopoff#1#2##1#2#1##2\noexpand\to##3##4{%
    \noexpand\def##4{##1}%
  }%
}

```

Replace any escaped delimiters

```

  \noexpand\DTLsubstituteall{##4}{#2#2}{#2}%
  \noexpand\edef\noexpand\@dtl@dosubs{%
    \noexpand\noexpand\noexpand\DTLsubstituteall{\noexpand\noexpand##4}%
    {\noexpand\expandafter\noexpand\noexpand\noexpand\csname#2\noexpand\endcsname#2}%
    {\noexpand\expandafter\noexpand\noexpand\noexpand\csname#2\noexpand\endcsname}%
  }%
  \noexpand\@dtl@dosubs
  \noexpand\def##3{#1##2}%
}
}
}

```

`\@dtl@construct@lop@ff<separator char>`

This constructs `\@dtl@lop@ff` to be used when the entry isn't surrounded by the delimiter.

```

\edef\@dtl@construct@lop@ff#1{%
  \noexpand\long
  \noexpand\def\noexpand\@dtl@lop@ff#1##1#1##2\noexpand\to##3##4{%
    \noexpand\def##4{##1}%
    \noexpand\def##3{#1##2}%
  }%
}
}

```

`\@dtl@construct@lopoffs`

This constructs all the lopoff macros using the given separator and delimiter characters.

```

\newcommand{\@dtl@construct@lopoffs}{%
  \edef\@dtl@chars{\@dtl@separator}\@dtl@delimiter}}%

```

```

\expandafter\@dtl@construct@lopoff\@dtl@chars
\expandafter\@dtl@construct@qlopoff\@dtl@chars
\expandafter\@dtl@construct@lopoff\expandafter{\@dtl@separator}%
}

```

13 datagidx.sty

This package provides a means to produce indices and glossaries without the need for an external indexing application, such as `makeindex` or `xindy`. However, the code here has been developed to implement the word order style described by the Oxford Style Manual. If you are not writing in English, this may not be applicable to your needs. You may be able to define your own comparison handler to use with `\dtl@sort`. If not, you'll need to use `xindy` with a package such as `glossaries`.

Declare package:

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```

\DeclareRelease{v2.32}{2019-09-27}{datagidx-2019-09-27.sty}
\DeclareCurrentRelease{v3.4}{2025-04-03}

```

Declare package:

```

\ProvidesPackage{datagidx}[2025/04/03 v3.4 (NLCT)]
\RequirePackage{etoolbox}

```

14 Default Settings

```
\ExplSyntaxOn
```

These commands need to be defined before the package options are used.

`\datagidx@columns` The number of columns to use for the index/glossary. Version 3.0: replaced `\datagidx@columns` with:

```

\int_new:N \l__datagidx_columns_int
\int_set:Nn \l__datagidx_columns_int { 2 }

```

Define commands used in package options.

`\DTLgidxSetColumns`

```

\NewDocumentCommand \DTLgidxSetColumns { m }
{
  \int_compare:nNnTF
    { #1 } < { \c_one_int }
  {
    \PackageError { datagidx }
    {
      \token_to_str:N \DTLgidxSetColumns \c_space_tl ~
      invalid ~ number ~ of ~ columns ~ #1
    }
  }
}

```

```

    {
      The ~ number ~ of ~ columns ~ must ~ be ~
      greater ~ than ~ 0
    }
  }
  {
    \int_set:Nn \l__datagidx_columns_int { #1 }
  }
}

```

`\DTLgidxChildStyle` Should the child name be displayed? (Default: show name.) If the name shouldn't be displayed, replace with a number.

```
\newcommand*\DTLgidxChildStyle}[1]{#1}
```

`\datagidx@setchildstyle` Version 3.0: removed.

```

\cs_new:Nn \__datagidx_set_child_style_named:
{
  \cs_set_eq:NN \DTLgidxChildStyle \use:n
}
\cs_new:Nn \__datagidx_set_child_style_noname:
{
  \renewcommand*\DTLgidxChildStyle}[1]{
    \DTLgidxChildCountLabel
  }
}

```

`\DTLgidxPostName` What to put after the name. (Defaults to space.)

```
\newcommand*\DTLgidxPostName}{ ~ }
```

`\DTLgidxPostChildName` What to put after the child name.

```
\newcommand*\DTLgidxPostChildName}{\DTLgidxPostName}
```

`\DTLgidxNameCase` Should the name have a case change in the index/glossary? (Default: no change.)

```
\newcommand*\DTLgidxNameCase}[1]{#1}
```

`\datagidx@setnamecase` Version 3.0: removed.

`\DTLgidxNameFont` The font to use for the name in the index/glossary. (Default: normal font.)

```
\newcommand*\DTLgidxNameFont}[1]{\textnormal{#1}}
```

`\DTLgidxPostDescription` What to put after the description. (Defaults to nothing.)

```
\newcommand*\DTLgidxPostDescription}{}
```

`\datagidx@setpostdesc` Version 3.0: removed.

`\DTLgidxPreLocation` What to put before the location list. (Defaults to en-space.)

```
\newcommand*\DTLgidxPreLocation}{\enspace}
```

`\DTLgidxPostLocation` What to put after the location list. (Defaults to space.)
`\newcommand*\DTLgidxPostLocation}{ ~ }`

`\datagidx@setprelocation` Version 3.0: removed.

`\DTLgidxLocation` How to display the location. (Defaults to show the location list.)
`\newcommand*\DTLgidxLocation}{\dtldolocationlist}`

`\datagidx@setlocation` Version 3.0: removed.

`\DTLgidxSee` How to display the cross-reference list.
`\newcommand*\DTLgidxSee}{`
`\datatool_if_null_or_empty:NF \See`
`{`
`\DTLgidxPreLocation`
`\DTLgidxFormatSee { \seename } { \See }`
`}`
`}`

`\DTLgidxSeeAlso` How to display the “see also” list.
`\newcommand*\DTLgidxSeeAlso}{%`
`\datatool_if_null_or_empty:NF \SeeAlso`
`{`
`\DTLgidxFormatSeeAlso`
`{ \seealsoname } { \SeeAlso }`
`}`
`}`

`\DTLgidxChildrenSeeAlso` Display the children and the see also attributes.
`\newcommand*\DTLgidxChildrenSeeAlso}{%`
`\DTLgidxChildren`
`\DTLgidxSeeAlso`
`}`

`\datagidx@setsee` Version 3.0: removed.

`\DTLgidxSymDescSep` Separator character between symbol and description if both are present.
`\newcommand*\DTLgidxSymDescSep}{\space}`

`\DTLgidxFormatDesc` How to format the description.
`\newcommand{\DTLgidxFormatDesc}[1]{#1}`

`\DTLgidxSymbolDescription` How to format the symbol and description fields.
`\newcommand*\DTLgidxSymbolDescription`
`{`
`\DTLgidxSymbolDescLeft`
`\DTLgidxSymbolDescRight`
`}`
`\newcommand*\DTLgidxSymbolDescLeft}`

```

{
  \tl_if_empty:NF \Symbol
  { ( \Symbol ) \DTLgidxSymDescSep }
}
\newcommand*{\DTLgidxSymbolDescRight}
{
  \tl_if_empty:NF \Description
  {
    \DTLgidxFormatDesc { \Description }
    \DTLgidxPostDescription
  }
}
}

```

\if@datagidxsymbolleft Identifies whether the symbol has been set to left or right. Version 3.0: replaced \if@datagidxsymbolleft with:

```

\bool_new:N \l__datagidx_symbol_left_bool
\bool_set_true:N \l__datagidx_symbol_left_bool

```

\datagidx@formatsymdesc Version 3.0: removed.

Only symbol

```

\cs_new:Nn \__datagix_set_symbol_only:
{
  \tl_set:Nn \DTLgidxSymbolDescLeft
  {
    \tl_if_empty:NF \Symbol { \Symbol }
  }
  \tl_clear:N \DTLgidxSymbolDescRight
  \bool_set_true:N \l__datagidx_symbol_left_bool
}

```

Only description

```

\cs_new:Nn \__datagix_set_desc_only:
{
  \tl_set:Nn \DTLgidxSymbolDescLeft
  {
    \tl_if_empty:NF \Description
    {
      \DTLgidxFormatDesc { \Description }
      \DTLgidxPostDescription
    }
  }
  \tl_clear:N \DTLgidxSymbolDescRight
  \bool_set_false:N \l__datagidx_symbol_left_bool
}

```

(symbol) description

```

\cs_new:Nn \__datagix_set_symbol_paren_desc:
{
  \tl_set:Nn \DTLgidxSymbolDescLeft

```

```

    {
      \tl_if_empty:NF \Symbol
      { ( \Symbol ) \DTLgidxSymDescSep }
    }
  \tl_set:Nn \DTLgidxSymbolDescRight
  {
    \tl_if_empty:NF \Description
    {
      \DTLgidxFormatDesc { \Description }
      \DTLgidxPostDescription
    }
  }
  \bool_set_true:N \l__datagidx_symbol_left_bool
}
description (symbol)
\cs_new:Nn \__datagix_set_desc_symbol_paren:
{
  \tl_set:Nn \DTLgidxSymbolDescLeft
  {
    \tl_if_empty:NF \Description
    {
      \DTLgidxFormatDesc { \Description }
      \DTLgidxPostDescription
      \DTLgidxSymDescSep
    }
  }
  \tl_set:Nn \DTLgidxSymbolDescRight
  {
    \tl_if_empty:NF \Symbol
    { ( \Symbol ) }
  }
  \bool_set_false:N \l__datagidx_symbol_left_bool
}
symbol description
\cs_new:Nn \__datagix_set_symbol_desc:
{
  \tl_set:Nn \DTLgidxSymbolDescLeft
  {
    \tl_if_empty:NF \Symbol
    { \Symbol \DTLgidxSymDescSep }
  }
  \tl_set:Nn \DTLgidxSymbolDescRight
  {
    \tl_if_empty:NF \Description
    {
      \DTLgidxFormatDesc { \Description }
      \DTLgidxPostDescription
    }
  }
}

```

```

    \bool_set_true:N \l__datagidx_symbol_left_bool
  }
description symbol
\cs_new:Nn \__datagix_set_desc_symbol:
{
  \tl_set:Nn \DTLgidxSymbolDescLeft
  {
    \tl_if_empty:NF \Description
    {
      \DTLgidxFormatDesc { \Description }
      \DTLgidxPostDescription
      \DTLgidxSymDescSep
    }
  }
  \tl_set:Nn \DTLgidxSymbolDescRight
  {
    \tl_if_empty:NF \Symbol { \Symbol }
  }
  \bool_set_false:N \l__datagidx_symbol_left_bool
}

```

\datagidx@compositor Version 3.0: replaced \datagidx@compositor with:
\l_new:N \l__datagidx_compositor_tl

\DTLgidxSetCompositor{<symbol>}

\DTLgidxSetCompositor

Set the location compositor.

```

\NewDocumentCommand \DTLgidxSetCompositor { m }
{
  \tl_set:Nn \l__datagidx_compositor_tl { #1 }
}

```

Set the default compositor to . (full stop).

```

\DTLgidxSetCompositor{.}

```

\DTLgidxCounter The counter used for the location lists.

```

\newcommand*{\DTLgidxCounter}{page}

```

```

\cs_new:Nn \__datagidx_set_counter:n

```

```

{
  \tl_if_empty:nTF { #1 }
  {
    \PackageError { datagidx }
    { Missing ~ counter ~ name }
    { The ~ argument ~ of ~ `counter' ~ must ~ be ~ a ~ counter ~ name }
  }
}

```

```

\tl_if_exist:cTF { the#1 }
{
  \tl_set:Nn \DTLgidxCnter { #1 }
}
{
  \PackageError { datagidx }
  { Invalid ~ counter ~ name ~ `#1' }
  {
    The ~ argument ~ of ~ `counter' ~ must ~ be ~ a ~
    counter ~ name ~ (or ~ \token_to_str:N \the#1 \c_space_tl
    must ~ be ~ defined)
  }
}
}
}

```

Sorting can take a long time (especially with large databases) but two \LaTeX runs are usually required to get the index or glossary up-to-date, so we usually don't need to worry about sorting on the first run (unless the order in some way affects the document, e.g. the group headings are to appear in the table of contents). It may also be that some modifications are done to the document that don't require a re-sort. The optimize setting tries to minimize the amount of sorting done to help speed up document compilation.

There are two optimization levels: low and high. The low level optimization just sorts every other \LaTeX run. This is done by writing to the aux file to determine whether or not the sort should be done next run. This is a cheap and easy hack that won't work if sorting makes the document out-of-date (for example, if the sorted index or glossary affects the table of contents by, say, making the group headings a sectional unit).

The high level optimization is more complicated and involves writing the sorted database to an external file and reading it in on the next run. This requires checks to see if the location lists have changed, in which case a new sort may be required.

The optimization function is only implemented when the sorting is specified via the sort key. Any explicit sorting done by the user via commands such as `\dlt sort` are not effected by the optimization setting.

`\datagidx@do@sort` Indicate what to do when it's time to sort the index/glossary. This defaults to un-optimised setting to avoid confusing users who don't like to read the manual.

```
\newcommand*{\datagidx@do@sort}{ \l__datagidx_sort_tl }
```

First deal with the low-level optimization as it's easier to implement.

`\datagidx@optimize@sort` The code to perform when the low optimize setting is on. If the command `\datagidx@do@optimize@sort` has been defined, do the sort. If it hasn't been defined, don't sort. If a sort isn't performed, the command definition is written to the aux file. If a sort is performed, the command definition isn't written to the aux file. This will do the sort every other run.

```
\newcommand*{\datagidx@optimize@sort}{%
```

First, has `\datagidx@do@optimize@sort` been defined?

```
\ifdef\datagidx@do@optimize@sort
{
```

It has been defined so go ahead and do the sort.

```
\l__datagidx_sort_tl
}
{
```

It hasn't been defined so don't sort. Write the command definition into the aux file for the next run.

```
\protected@write\@auxout{}{%
\string\gdef\string\datagidx@do@optimize@sort{%
}
}
```

Let the user know they need to recompile the document.

```
\cs_gset_eq:NN
\@datagidx@dorerun@warn@sort
\data@rerun@warn@sort
}
}
```

List of labels to check for re-run.

```
\seq_new:N \g__datagidx_refd_labels_seq
```

`\if@datagidx@warn` Provide a switch to allow warnings to be suppressed. Version 3.0: replaced `\if@datagidx@warn` with:

```
\bool_new:N \l__datagidx_warn_bool
\bool_set_true:N \l__datagidx_warn_bool
```

`\@datagidx@dorerun@warn`

```
\newcommand*\@datagidx@dorerun@warn{%
\seq_map_inline:Nn \g__datagidx_refd_labels_seq
{
\iftermexists { ##1 }
{
\DTLaction
[
name = { \__datagidx_term_database:n { ##1 } },
key = Label, value = { ##1 },
return =
{
```

Locations from previous run that may be a page out:

```
\UnsafeLocation = UnsafeLocation,
```

Locations from this run that may be a page out:

```
\CurrentLocation = CurrentLocation
```

If the document hasn't changed, they will both be out by the same amount so they can still be compared. However, protected expansion may cause extra spaces.

```

    }
  ]
  { select ~ row }
  \tl_set:Nx \UnsafeLocation
    { \text_purify:n { \UnsafeLocation } }
  \tl_set:Nx \CurrentLocation
    { \text_purify:n { \CurrentLocation } }
  \tl_remove_all:Nn \UnsafeLocation { ~ }
  \tl_remove_all:Nn \CurrentLocation { ~ }
  \tl_if_eq:NNF \UnsafeLocation \CurrentLocation
    {
      \@data@rerun@warn
      \seq_map_break:
    }
  }
  { }
}
}

```

datagidx@dorerun@warn@sort

```

\newcommand*\@datagidx@dorerun@warn@sort{}

\AtEndDocument
{
  \bool_if:NT \l__datagidx_warn_bool
  {
    \@datagidx@dorerun@warn
    \@datagidx@dorerun@warn@sort
  }
}

```

datagidx@rerun@warn@sort Warning issued when a rerun is required to sort the index or glossary.

```

\newcommand*\@data@rerun@warn@sort{
  \PackageWarningNoLine {datagidx}
  {
    Rerun ~ required ~ to ~ sort ~ the ~
    index/glossary ~ databases
  }
}

```

\@datagidx@rerun@warn Warning issued when a rerun is required to update the location lists.

```

\newcommand*\@data@rerun@warn{
  \PackageWarningNoLine {datagidx}
  {
    Rerun ~ required ~ to ~ ensure ~ the ~
    index/glossary ~ location ~ lists ~ are ~ up-to-date
  }
}

```

The high optimize setting is more complicated. This involves writing each database to an external file (named `\jobname-(db label).gidx`). The sort is only performed if new terms are added or used.

`gidx@do@highopt@optimize`

```
\newcommand*{\datagidx@do@highopt@optimize}{%
  \renewcommand*{\datagidx@do@sort}{%
```

Only sort if database has changed.

```
\ifcsdef{datagidx@do@highopt@sort@DTLgidxCurrentdb}%
  {%
    \csuse{datagidx@do@highopt@sort@DTLgidxCurrentdb}%
  }%
  {%
```

Do nothing

```
\dtl@message
  {
    Not ~ sorting ~ '\DTLgidxCurrentdb' : ~
    optimize=high ~ on ~ and ~ no ~ change ~
    detected
  }
}%
```

Save the database to file.

```
\group_begin:
```

Locally redefine `__datagidx_used:n` to expand to 0. Since this is encapsulated with `\dtlspecialvalue`, it will expand regardless of the `expand` setting. Similarly the location needs to expand to nothing.

```
\cs_set:Nn \__datagidx_used:n { 0 }
\cs_set_eq:NN \__datagidx_location:n \use_none:n
\cs_set_eq:NN
  \__datagidx_letter_group:n
  \__datagidx_write_letter_group:n
```

Write in latest dbtex format.

```
\DTLwrite
  [
    overwrite=allow,
    format = dbtex, expand=none,
    name = \DTLgidxCurrentdb
  ]
  { \datagidx@highoptfilename \DTLgidxCurrentdb }
\group_end:
}%
```

Change the behaviour of `\newgidx`

```
\def\newgidx{\datagidx@highopt@newgidx}%
```

Change the behaviour of `\newterm`

```
\def\newterm{\datagidx@highopt@newterm}%
}
```

`\@datagidx@db@col@id@w` Version 3.0: removed.

With the ‘highopt optimize’ setting, whenever a location is written to the aux file, if no location has been defined the database needs sorting.

`\datagidx@do@highopt@update` Default does nothing. (Argument is the entry’s label.)
`\newcommand*\@datagidx@do@highopt@update}[1]{}`

`\datagidxhighoptfilename` Expands to the name of the filename associated with the database identified by the argument for the ‘highopt’ setting.
`\newcommand*\@datagidxhighoptfilename}[1]{\jobname-#1.gidx}`

15 Package Options

These options govern the general layout of the glossary/index and may be passed as package options.

```
\keys_define:nn { datatool }
{
  columns .code:n = { \DTLgidxSetColumns { #1 } },
  child .choice: ,
  child / named .code:n = { \__datagidx_set_child_style_named: } ,
  child / noname .code:n = { \__datagidx_set_child_style_noname: } ,
  namecase .choice: ,
  namecase / nochange .code:n =
    { \let \DTLgidxNameCase \use:n } ,
  namecase / uc .code:n =
    { \renewcommand \DTLgidxNameCase [ 1 ] { \text_uppercase:n { ##1 } } } ,
  namecase / lc .code:n =
    { \renewcommand \DTLgidxNameCase [ 1 ] { \text_lowercase:n { ##1 } } } ,
  namecase / firstuc .code:n =
    { \renewcommand \DTLgidxNameCase [ 1 ] { \xmakefirstuc { ##1 } } } ,
  namecase / capitalise .code:n =
    { \renewcommand \DTLgidxNameCase [ 1 ] { \xcapitalisewords { ##1 } } } ,
  namefont .code:n =
    { \renewcommand \DTLgidxNameFont [ 1 ] { { #1 { ##1 } } } } ,
  postname .code:n =
    { \renewcommand \DTLgidxPostName { #1 } } ,
  postdesc .choice: ,
  postdesc / none .code:n =
    { \tl_clear:N \DTLgidxPostDescription } ,
  postdesc / dot .code:n =
    { \tl_set:Nn \DTLgidxPostDescription { . } } ,
  prelocation .choice: ,
  prelocation / none .code:n =
    { \tl_clear:N \DTLgidxPreLocation } ,
  prelocation / enspace .code:n =
    { \tl_set:Nn \DTLgidxPreLocation { \enspace } } ,
  prelocation / space .code:n =
```

```

    { \tl_set:Nn \DTLgidxPreLocation { ~ } } ,
prelocation / dotfill .code:n =
    { \tl_set:Nn \DTLgidxPreLocation { \dotfill } } ,
prelocation / hfill .code:n =
    { \tl_set:Nn \DTLgidxPreLocation { \hfill } } ,
location .choice: ,
location / hide .code:n =
    { \tl_clear:N \DTLgidxLocation },
location / list .code:n =
    { \tl_set:Nn \DTLgidxLocation { \dtldolocationlist } },
location / first .code:n =
    { \tl_set:Nn \DTLgidxLocation { \dtldofirstlocation } },
see .choice: ,
see / comma .code:n =
    {
    \renewcommand*\DTLgidxSee
    {
    \datatool_if_null_or_empty:NF \See
    {
    , ~ \DTLgidxFormatSee { \seename } { \See }
    }
    }
    } ,
see / brackets .code:n =
    {
    \renewcommand*\DTLgidxSee
    {
    \datatool_if_null_or_empty:NF \See
    {
    \space ( \DTLgidxFormatSee { \seename } { \See } )
    }
    }
    } ,
see / dot .code:n =
    {
    \renewcommand*\DTLgidxSee
    {
    \datatool_if_null_or_empty:NF \See
    {
    . ~
    \DTLgidxFormatSee
    { \xmakefirstuc { \seename } } { \See }
    }
    }
    } ,
see / space .code:n =
    {
    \renewcommand*\DTLgidxSee
    {
    \datatool_if_null_or_empty:NF \See

```

```

        {
            \space
            \DTLgidxFormatSee { \seename } { \See }
        }
    } ,
see / nosep .code:n =
    {
        \renewcommand*\DTLgidxSee
        {
            \datatool_if_null_or_empty:NF \See
            {
                \DTLgidxFormatSee { \seename } { \See }
            }
        }
    } ,
see / semicolon .code:n =
    {
        \renewcommand*\DTLgidxSee
        {
            \datatool_if_null_or_empty:NF \See
            {
                ; ~ \DTLgidxFormatSee { \seename } { \See }
            }
        }
    } ,
see / location .code:n =
    {
        \renewcommand*\DTLgidxSee
        {
            \datatool_if_null_or_empty:NF \See
            {
                \DTLgidxPreLocation
                \DTLgidxFormatSee { \seename } { \See }
            }
        }
    } ,
symboldesc .choice: ,
symboldesc / symbol .code:n =
    {
        \__datagix_set_symbol_only:
    } ,
symboldesc / desc .code:n =
    {
        \__datagix_set_desc_only:
    } ,
symboldesc / (symbol) ~ desc .code:n =
    {
        \__datagix_set_symbol_paren_desc:
    } ,

```

```

symboldesc / desc ~ (symbol) .code:n =
{
  \__datagix_set_desc_symbol_paren:
},
symboldesc / symbol ~ desc .code:n =
{
  \__datagix_set_symbol_desc:
},
symboldesc / desc ~ symbol .code:n =
{
  \__datagix_set_desc_symbol:
},
counter .code:n =
{
  \__datagidx_set_counter:n { #1 }
},
counter .value_required:n = true ,
compositor .tl_set:N = \l__datagidx_compositor_tl ,
compositor .value_required:n = true ,
final .code:n =
{ \cs_set_eq:NN \datagidxshowifdraft \use_none:n } ,
final .value_forbidden:n = true ,
draft .code:n =
{ \cs_set_eq:NN \datagidxshowifdraft \use:n } ,
draft .value_forbidden:n = true ,

```

optimize A boolean option indicating whether or not to optimize the sort. This is only available as a global option. If you want to optimize some glossaries but not others, switch on the `optimize` function and clear the sort key for the relevant glossaries and manually sort using `\dtlsort` before the glossary is displayed.

```

optimize .choice: ,
optimize / off .code:n =
{
  \renewcommand*\datagidx@do@sort{ \l__datagidx_sort_tl }
},
optimize / low .code:n =
{
  \renewcommand*\datagidx@do@sort{\datagidx@optimize@sort}
},
optimize / high .code:n =
{
  \datagidx@do@highopt@optimize
},
optimize .default:n = { high } ,
nowarn .bool_set_inverse:N = \l__datagidx_warn_bool ,
}

Set final as default:
\newcommand*\datagidxshowifdraft}[1]{}

```

```
\ExplSyntaxOff
```

Process package options and load `datatool` if not already loaded. This allows `datatool` package options to be supplied with `datagix`.

```
\IfPackageLoadedTF{datatool}
{
  \ProcessKeyOptions[datatool]
}
{
  \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{datatool}}
  \ProcessOptions
}
\RequirePackage{datatool}
```

Remove the package option keys so they can't be used with `\DTLsetup` directly.

```
\ExplSyntaxOn
\keys_define:nn { datatool }
{
  columns .undefine: ,
  child .undefine: ,
  namecase .undefine: ,
  postname .undefine: ,
  postdesc .undefine: ,
  prelocation .undefine: ,
  location .undefine: ,
  see .undefine: ,
  symboldesc .undefine: ,
  counter .undefine: ,
  compositor .undefine: ,
  final .undefine: ,
  draft .undefine: ,
  optimize .undefine: ,
  nowarn .undefine:
}
\ExplSyntaxOff
%
```

16 Initialisation

Required packages. Version 3.0: removed `xkeyval`

```
\RequirePackage{mfirstuc}[2022/10/14]
\RequirePackage{multicol}
```

```
\ExplSyntaxOn
```

Scratch variables:

```
\datagidx@child Version 3.0: replaced \datagidx@child with:
\__tl_new:N \l__datagidx_child_label_tl
\__clist_new:N \l__datagidx_child_clist
```

`\seq_new:N \l__datagidx_child_seq`

These labels are token list variables not strings as they may be set to another command that the user may want to redefine.

`\datagidx@parentdatabase` Version 3.0: replaced `\datagidx@parentdatabase` with:

`\tl_new:N \l__datagidx_parent_database_tl`

Temporary database, column and term labels.

`\tl_new:N \l__datagidx_database_tl`

`\tl_new:N \l__datagidx_label_tl`

`\datagidx@id` Version 3.0: replaced `\datagidx@id` with:

`\tl_new:N \l__datagidx_id_tl`

`\@datagidx@target` Version 3.0: replaced `\@datagidx@target` with:

`\tl_new:N \l__datagidx_target_tl`

`\datagidx@parent` Version 3.0: replaced `\datagidx@parent` with:

`\tl_new:N \l__datagidx_parent_tl`

`\datagidx@list` Version 3.0: replaced `\datagidx@list` with:

`\clist_new:N \l__datagidx_database_clist`

Temporary value:

`\tl_new:N \l__datagidx_value_tl`

`\datagidx@title` Database title. Replaced `\datagidx@title` with:

`\tl_new:N \l__datagidx_title_tl`

Location variables

`\datagidx@loc` Version 3.0: replaced `\datagidx@loc` with:

`\tl_new:N \l__datagidx_location_tl`

`\clist_new:N \l__datagidx_location_clist`

`\datagidx@sep` Version 3.0: replaced `\datagidx@sep` with:

`\tl_new:N \l__datagidx_sep_tl`

Database to keep track of all the defined terms.

`\DTLnewdb{datagidx}`

`DTLgidxChildCount` Child counter.

`\newcounter{DTLgidxChildCount}`

`\theHDTLgidxChildCount` Reduce duplicate identifier warnings if `hyperref` in use. `\Label` is a placeholder locally set while iterating.

`\def\theHDTLgidxChildCount{\Label.\arabic{DTLgidxChildCount}}`

`\DTLgidxChildCountLabel` Label for child counter.

```

\newcommand*{\DTLgidxChildCountLabel}{\theDTLgidxChildCount) ~ }

```

`\datagidx@foreachchild` Iterate through each child label in `\Children`, which should be a comma-separated list of labels. The current database should be in `\DTLgidxCurrentdb`.

```

\newcommand{\datagidx@foreachchild}[1]{%
  \bool_if:NTF \l__datagidx_childsort_bool
  {
    \seq_clear:N \l__datagidx_child_seq
    \clist_map_inline:Nn \Children
    {
      Get the row index only
      \__datatool_get_row_index:NnXn
      \l__datatool_row_idx_tl
      { \DTLgidxCurrentdb }
      { \dtlcolumnindex { \DTLgidxCurrentdb } { Label } }
      { ##1 }
      \datatool_if_null:NF \l__datatool_row_idx_tl
      {
        \seq_put_right:Nx \l__datagidx_child_seq
        { { \l__datatool_row_idx_tl } { ##1 } }
      }
    }
  }
  Sort by row index:
  \seq_sort:Nn \l__datagidx_child_seq
  {
    \int_compare:nNnTF
    { \use_i:nn ##1 } > { \use_i:nn ##2 }
    { \sort_return_swapped: }
    { \sort_return_same: }
  }
  \seq_map_inline:Nn \l__datagidx_child_seq
  {
    \tl_set:Nx \Label { \use_ii:nn ##1 }
    #1
  }
}
{
  \clist_map_variable:NNn \Children \Label
  { #1 }
}
}

```

`\datagidx@sortchildren` The list of child labels needs to be sorted so that the child list follows the same ordering as the database. Version 3.0: removed `\datagidx@sortchildren`.

`\tagidx@sort@foreachchild` Sorted iteration through all the child labels. Version 3.0: deprecated. Hierarchical sorting now implemented with `HierSort` column. Version 3.0: removed `\datagidx@sort@foreachchild`.

`\gidx@unsort@foreachchild` Unsorted iteration through all the child labels. Version 3.0: removed `\datagidx@unsort@foreachchild`.

`\datagidx@setchildsort` Version 3.0: removed `\datagidx@setchildsort`.

`\datagidxsymbolwidth` Space to allocate for the symbol. If zero or negative, symbol just occupies its natural space.

`\newlength\datagidxsymbolwidth`

`\datagidxlocationwidth` Space to allocate for the location list. If zero or negative, the list just occupies its natural space.

`\newlength\datagidxlocationwidth`

17 Glossary/Index Formatting

`\seename`

`\providecommand*\seename}{see}`

`\seealsoname`

```
\tl_if_exist:NF \seealsoname
{
  \tl_if_exist:NTF \alsoname
  {
    \tl_set:Nn \seealsoname { \alsoname }
  }
  {
    \tl_set:Nn \seealsoname { see ~ also }
  }
}
```

`\DTLgidxSeeTagFont`

`\newcommand*\DTLgidxSeeTagFont}[1]{\emph{#1}}`

`\DTLgidxFormatSee{<tag>}{<label list>}`

`\DTLgidxFormatSee`

```
\newcommand*\DTLgidxFormatSee}[2]{%
  \DTLgidxSeeTagFont{ #1 } ~ \DTLgidxSeeList{ #2 }
}
```

`\DTLgidxFormatSeeAlso{<tag>}{<label list>}`

`\DTLgidxFormatSeeAlso`

```
\NewDocumentCommand \DTLgidxFormatSeeAlso { m m }
{
```

```

\datagidxdoseealso
{
  \DTLgidxSeeTagFont{ #1 } ~ \DTLgidxSeeList { #2 }
}
}

```

\datagidxdoseealso

```

\NewDocumentCommand \datagidxdoseealso { m }
{
  \datagidxseealsostart
  #1
  \datagidxseealsoend
}

```

\DTLgidxSeeList{<label list>}

\DTLgidxSeeList

```

\NewDocumentCommand \DTLgidxSeeList { m }
{
  \group_begin:
  \tl_clear:N \l__datagidx_sep_tl
  \exp_args:NNo \seq_set_from_clist:Nn
    \l__datatool_tmp_seq { #1 }
  \int_set:Nn \l__datatool_count_int
    { \seq_count:N \l__datatool_tmp_seq }
  \seq_map_indexed_inline:Nn \l__datatool_tmp_seq
  {
    \tl_set:Nn \l__datatool_label_tl { ##2 }
    \int_compare:nNnTF
      { ##1 } = { \l__datatool_count_int }
      {

```

Last iteration.

```

  \tl_if_empty:NF \l__datagidx_sep_tl
  {

```

Not the only element in the list so separator needed.

```

    \DTLidxSeeLastSep
  }
}
{

```

Not last iteration

```

  \l__datagidx_sep_tl
  \tl_set_eq:NN \l__datagidx_sep_tl \DTLidxSeeSep
}
\DTLidxFormatSeeItem { \l__datatool_label_tl }
}
\group_end:
}

```

`\DTLidxFormatSeeItem{<label>}`

`\DTLidxFormatSeeItem`

```
\NewDocumentCommand \DTLidxFormatSeeItem { m }
{
  \group_begin:
  \DTLgidxFetchEntry
  \l__datagidx_value_tl { #1 } { Name }
  \datatool_if_null:NTF \l__datagidx_value_tl
  {
    \bool_if:NT \l__datagidx_warn_bool
    {
      \PackageWarning { datagidx }
      { Can't ~ find ~ cross-reference ~ `#1' }
    }
  }
  {
    \datagidxlink { #1 }
    { \l__datagidx_value_tl }
  }
  \group_end:
}
```

`\DTLidxSeeSep` Separator in cross-reference list.

```
\newcommand*{\DTLidxSeeSep}{ , ~ }
```

`\DTLidxSeeLastSep` Final separator in cross-reference list.

```
\newcommand*{\DTLidxSeeLastSep}{ ~ \& ~ }
```

`\DTLgidxDoSeeOrLocation` You shouldn't have both a "see" list and a location list. This checks if `\See` is null. If it isn't null, it does the "see" part, otherwise it deals with the location list.

```
\newrobustcmd* \DTLgidxDoSeeOrLocation
{
  \datatool_if_null_or_empty:NTF \See
  {
    \See is null. Do we have a location?
    \datatool_if_null_or_empty:NF \Location
    {
      \tl_if_empty:NF \DTLgidxLocation
      {
        \DTLgidxPreLocation
        \DTLgidxLocation
        \DTLgidxPostLocation
      }
    }
  }
}
```

`\See` is not null, so do the cross-reference.

```
    \DTLgidxSee
  }
}
```

`dtlgidxchildlist` (*env.*) Provided to allow for any font changes etc that might be required.

```
\newenvironment{dtlgidxchildlist}{}{}
```

`\DTLgidxChildren` How to display the children

```
\newcommand*{\DTLgidxChildren}{
  \begin { dtlgidxchildlist }
  \datatool_if_null_or_empty:NF \Children
  {
    \int_incr:N \datagidx@level
    \datagidxchildstart
    \let\Parent\Label
    \datagidx@foreachchild
    {
      \DTLaction
      [
        name = \DTLgidxCurrentdb ,
        key = Label,
        expand-value = \Label ,
        return =
        {
          \Location = Location ,
          \See = See ,
          \SeeAlso = SeeAlso
        }
      ]
      { select ~ row }
      \bool_lazy_all:nF
      {
        { \datatool_if_null_or_empty_p:N \Location }
        { \datatool_if_null_or_empty_p:N \See }
        { \datatool_if_null_or_empty_p:N \SeeAlso }
      }
      {
        \datagidx@displaychild
      }
    }
  }
  \datagidxchildend
}
\end { dtlgidxchildlist }
}
```

`\datagidxgetchildfields` Get the child fields from the current row.

```
\newcommand*{\datagidxgetchildfields}{%
  \dtlgetentryfromcurrentrow
```

```

    {\Name}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Name}}%
\dtlgetentryfromcurrentrow
    {\Description}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Description}}%
\dtlgetentryfromcurrentrow
    {\Symbol}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Symbol}}%
\dtlgetentryfromcurrentrow
    {\Long}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Long}}%
\dtlgetentryfromcurrentrow
    {\Short}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Short}}%
\dtlgetentryfromcurrentrow
    {\Text}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Text}}%
\dtlgetentryfromcurrentrow
    {\Plural}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Plural}}%
\dtlgetentryfromcurrentrow
    {\Used}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Used}}%
\dtlgetentryfromcurrentrow
    {\Children}%
    {\dtlcolumnindex{\DTLgidxCurrentdb}{Child}}%
}

```

`\datagidx@displaychild`

```

\newcommand*{\datagidx@displaychild}{%
  \datagidxgetchildfields
  \datagidxchilditem
}

```

`\datagidx@heading` Indicates how to format the heading in the glossary/index. Version 3.0: replaced `\datagidx@heading` with:

```

\tl_new:N \l__datagidx_heading_tl
\cs_if_exist:NTF \chapter
{
  \tl_set:Nn \l__datagidx_heading_tl { \chapter* }
}
{
  \tl_set:Nn \l__datagidx_heading_tl { \section* }
}

```

`\DTLgidxNoHeading` Allow user to suppress the heading. (So to suppress the heading do `heading=\DTLgidxNoHeading`).

```

\newcommand{\DTLgidxNoHeading}[1]{ }

```

`\datagidx@postheading` Indicates what to do immediately after the heading. Version 3.0: replaced `\datagidx@postheading` with:

```
\tl_new:N \l__datagidx_post_heading_tl
```

`\datagidx@multicols` Should we use multicols or multicols*? Version 3.0: replaced `\datagidx@multicols` with:

```
\tl_new:N \l__datagidx_multicols_tl
\tl_set:Nn \l__datagidx_multicols_tl { multicols }
```

`\datagidx@sort` Indicates how to sort the glossary/index. Defaults to word order. The expansion of this token list variable is added to the `datagidx` database (in the Sort column), so it needs to be expanded (and is therefore a token list variable not a function). Version 3.0: replaced `\dtl\sort` with `\DTL\sortdata` replaced `\datagidx@sort` with:

```
\tl_new:N \l__datagidx_sort_tl
\tl_set:Nn \l__datagidx_sort_tl
{
  \DTL\sortdata
  [ save-group-key = LetterGroup ]
  { \DTL\gidxCurrentdb }
  {HierSort={replacements=Sort},FirstId}
}
```

`\@idxitem` Some classes, such as `beamer`, don't define `\@idxitem` so if it's not already defined, define it here.

```
\providecommand{\@idxitem}{\par\hangindent 40\p@}
```

`\datagidxstart` Indicates what to do at the start of the glossary/index.

```
\newcommand* \datagidxstart
{
  \group_begin:
  \dim_zero:N \parindent
  \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
  \let\item\@idxitem
}
```

`\datagidxend` Indicates what to do at the end of the glossary/index.

```
\newcommand*{\datagidxend} { \datagidx_end: }
\cs_new:Nn \datagidx_end: { \expandafter \group_end: \if@endpe\@doendpe\fi }
```

`\datagidxtarget` Provide a means to add a hypertarget if `\hypertarget` has been defined.

```
\newcommand*{\datagidxtarget}{ \__datagidx_target:nn }
```

Version 3.0: replaced `\@datagidxtarget` with:

```
\cs_new:Nn \__datagidx_target:nn
{
  \cs_if_exist:NT \hypertarget
  {
    \group_begin:
    \datatool_measure_height:Nn
    \l__datatool_tmpa_dim { #2 }
  }
}
```

```

        \raisebox
        { \l__datatool_tmpa_dim }
        { \hypertarget { #1 } { } }
    \group_end:
}
#2
}

```

`\datagidxlink` Provide a means to add a link if `\hyperlink` has been defined.
`\newcommand*\datagidxlink{__datagidx_link:nn }`

Version 3.0: replaced `\@datagidxlink` with:

```

\cs_new:Nn \__datagidx_link:nn
{
  \cs_if_exist:NTF \hyperlink
  { \hyperlink { #1 } { #2 } }
  { #2 }
}

```

`\DTLgidxEnableHyper` Enable hyperlinks (if they are defined).
`\NewDocumentCommand \DTLgidxEnableHyper { }`
`{`
 `\cs_set_eq:NN \datagidxtarget __datagidx_target:nn`
 `\cs_set_eq:NN \datagidxlink __datagidx_link:nn`
`}`

`\DTLgidxDisableHyper` Disable hyperlinks (if they are defined).
`\NewDocumentCommand \DTLgidxDisableHyper { }`
`{`
 `\cs_set_eq:NN \datagidxtarget \use_ii:nn`
 `\cs_set_eq:NN \datagidxlink \use_ii:nn`
`}`

`\datagidxgroupsep` Indicates what to do between groups (after the previous group and before the header of the next group).
`\newcommand*\datagidxgroupsep{}`

`\datagidxgroupheader` Indicates what to do at the start of a group. (The current group label can be accessed via `\datagidxcurrentgroup` and the previous group label can be accessed via `\datagidxprevgroup`.)
`\newcommand*\datagidxgroupheader{}`

`\datagidxitem` Indicates what to do at the start of each item of the glossary/index.
`\newcommand*\datagidxitem{}`%

`\datagidxchildstart` Indicates what to do at the start of the child glossary/index.
`\newcommand*\datagidxchildstart{}`

`\datagidxchildend` Indicates what to do at the end of the child glossary/index.

```
\newcommand*\datagidxchildend{}
```

`\datagidxchilditem` Indicates what to do at the start of each item of the child glossary/index.

```
\newcommand*\datagidxchilditem{}
```

`\datagidxseealsostart` Indicates what to do at the start of the “see also” list.

```
\newcommand*\datagidxseealsostart{}
```

`\datagidxseealsoend` Indicates what to do at the end of the “see also” list.

```
\newcommand*\datagidxseealsoend{}
```

`\DTLgidxEndItem`

```
\newcommand{\DTLgidxEndItem}{\par\smallskip}
```

```
\datagidx@doifsymlocwidth{\langle indent \rangle}{\langle Name code \rangle}
{\langle Location code \rangle}
```

`\datagidx@doifsymlocwidth`

What to do if both the symbol width and the location width have been set. Version 3.0: replaced `\datagidx@doifsymlocwidth` with:

```
\cs_new:Nn \__datagidx_do_ifsymlocwidth:nnn
{
```

Calculate remaining space left for the description. If L is the linewidth, i is the `\langle indent \rangle`, w_N is the width of `\langle Name code \rangle`, w_S is the symbol width (`\datagidxsymbolwidth`), w_L is the location width (`\datagidxlocationwidth`), w_P is the width of `\DTLgidxPreLocation`, and w_D is the width of `\DTLgidxSymDescSep` then the available width is $L - i - w_N - w_S - w_L - w_P$.

```
\datatool_measure_width:Nn
  \__datatool_tmpa_dim
  { #2 \DTLgidxPreLocation \DTLgidxSymDescSep }
\dim_set:Nn \l__datatool_tmpa_dim
{
  \linewidth - #1
  - \__datatool_tmpa_dim
  - \datagidxsymbolwidth
  - \datagidxlocationwidth
}
\bool_if:NTF \l__datagidx_symbol_left_bool
{
  \begin{minipage} [t]
    { \datagidxsymbolwidth }
    \datagidxsymalign
    \tl_clear:N \DTLgidxSymDescSep
    \DTLgidxSymbolDescLeft
  \end{minipage}
  \DTLgidxSymDescSep
```

```

\begin{minipage} [t]
  { \l__datatool_tmpa_dim }
  \tl_clear:N \DTLgidxSymDescSep
  \DTLgidxSymbolDescRight
\end{minipage}
}
{
\begin{minipage} [t]
  { \l__datatool_tmpa_dim }
  \tl_clear:N \DTLgidxSymDescSep
  \DTLgidxSymbolDescRight
\end{minipage}
\DTLgidxSymDescSep
\begin{minipage} [t]
  { \datagidxsymbolwidth }
  \datagidxsymalign
  \tl_clear:N \DTLgidxSymDescSep
  \DTLgidxSymbolDescLeft
\end{minipage}
}
\DTLgidxPreLocation
\begin{minipage} [t]
  { \datagidxlocationwidth }
  \datagidxlocalign
  \tl_clear:N \DTLgidxPreLocation
  #3
\end{minipage}
}

```

```

\datagidx@doiflocwidth{<indent>}{<Name code>}
{<Location code>}

```

\datagidx@doiflocwidth

What to do if only the location width has been set. Version 3.0: replaced \datagidx@doiflocwidth with:

```

\cs_new:Nn \__datagidx_do_iflocwidth:nnn
{

```

Calculate remaining space left for the symbol and description.

```

\datatool_measure_width:Nn
  \l__datatool_tmpa_dim
  { #2 \DTLgidxPreLocation }
\dim_set:Nn \l__datatool_tmpa_dim
  {
    \linewidth - #1
    - \l__datatool_tmpa_dim
    - \datagidxlocationwidth
  }
\begin{minipage} [t]

```

```

        { \l__datatool_tmpa_dim }
        \DTLgidxSymbolDescription
    \end{minipage}
    \DTLgidxPreLocation
    \begin{minipage} [t]
        { \datagidxlocationwidth }
        \datagidxlocalign
        \tl_clear:N \DTLgidxPreLocation
        #3
    \end{minipage}
}

```

\datagidx@doifsymwidth TODO: what uses this?

```

\datagidx@doifsymwidth{<indent>}{<Name code>}
{<Location code>}

```

What to do if only the location width has been set. Version 3.0: replaced \datagidx@doifsymwidth with:

```

\cs_new:Nn \__datagidx_do_ifsymwidth:nnn
{

```

Calculate remaining space left for the description and location.

```

    \datatool_measure_width:Nn
    \l__datatool_tmpa_dim
    { #2 \DTLgidxSymDescSep }
    \dim_set:Nn \l__datatool_tmpa_dim
    {
        \linewidth -#1
        - \l__datatool_tmpa_dim
        - \datagidxsymbolwidth
    }
    \bool_if:NTF \l__datagidx_symbol_left_bool
    {
        \begin{minipage} [t]
            { \datagidxsymbolwidth }
            \datagidxsymalign
            \tl_clear:N \DTLgidxSymDescSep
            \DTLgidxSymbolDescLeft
        \end{minipage}
        \DTLgidxSymDescSep
        \begin{minipage} [t]
            { \l__datatool_tmpa_dim }
            \tl_clear:N \DTLgidxSymDescSep
            \DTLgidxSymbolDescRight
            #3
        \end{minipage}
    }
}

```

```

\begin{minipage} [t]
  { \l__datatool_tmpa_dim }
  \tl_clear:N \DTLgidxSymDescSep
  \DTLgidxSymbolDescRight
\end{minipage}
\DTLgidxSymDescSep
\begin{minipage} [t]
  { \datagidxsymbolwidth }
  \datagidxsymalign
  \tl_clear:N \DTLgidxSymDescSep
  \DTLgidxSymbolDescLeft

```

This arrangement may look a bit weird.

```

#3
\end{minipage}
}
}

```

`\datagidxlocalign` Alignment of the location when the location width has been set.

```
\newcommand*{\datagidxlocalign}{\raggedleft}
```

`\datagidxsymalign` Alignment of the symbol when the symbol width has been set.

```
\newcommand*{\datagidxsymalign}{\centering}
```

17.1 Predefined styles

`\datagidxsetstyle` Sets the current index/glossary style

```

\NewDocumentCommand \datagidxsetstyle { m }
{
  \cs_if_exist_use:cF {datagidx@style@#1}
  {
    \PackageError {datagidx} {Unknown ~ style ~ `#1'} {}
  }
}

```

`\datagidxnewstyle` Defines a new index/glossary style

```

\NewDocumentCommand \datagidxnewstyle { m +m }
{
  \cs_if_exist:cTF { datagidx@style@#1 }
  {
    \PackageError { datagidx }
    {
      Style ~ `#1 ' ~ already ~ exists
    }
  }
  {
    \cs_set:cpn { datagidx@style@#1 } { #2 }
  }
}

```

17.1.1 index

`\datagidx@style@index` Basic index style.

```
\datagidxnewstyle{index}
{
  \tl_set:Nn \datagidxstart
  {
    \group_begin:
    \dim_zero:N \parindent
    \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
```

Index columns are usually too narrow for fully justified text.

```
\raggedright
\cs_set_eq:NN \item \@idxitem
```

Have the symbol or location widths been set?

```
\dim_compare:nNnTF
{ \datagidxsymbolwidth } > { \c_zero_dim }
{
```

Symbol width has been set Has the location width been set?

```
\dim_compare:nNnTF
{ \datagidxlocationwidth } > { \c_zero_dim }
{
```

Both have been set.

```
\tl_set:Nn \datagidx@item@body
{
  \__datagidx_do_ifsymlocwidth:nnn
  { \c_zero_dim }
  {
    \DTLgidxNameFont { \DTLgidxNameCase { \Name } }
  }
  {
    \DTLgidxDoSeeOrLocation
  }
}
}
```

Location width hasn't been set.

```
\tl_set:Nn \datagidx@item@body
{
  \__datagidx_do_iflocwidth:nnn
  { \c_zero_dim }
  {
    \DTLgidxNameFont
    { \DTLgidxNameCase { \Name } }
  }
  {
    \DTLgidxDoSeeOrLocation
  }
}
```

```

    }
  }
}
{

```

Symbol width hasn't been set Has the location width been set?

```

\dim_compare:nNnTF
{ \datagidxlocationwidth } > { \c_zero_dim }
{

```

Location width has been set.

```

\tl_set:Nn \datagidx@item@body
{
  \__datagidx_do_iflocwidth:nnn
  { \c_zero_dim }
  {
    \DTLgidxNameFont
    { \DTLgidxNameCase { \Name } }
  }
  {
    \DTLgidxDoSeeOrLocation
  }
}
}
{

```

Neither have been set.

```

\tl_set:Nn \datagidx@item@body
{
  \DTLgidxSymbolDescription
  \DTLgidxDoSeeOrLocation
}
}
}
\tl_set:Nn \datagidxend { \datagidx_end: }
\tl_set:Nn \datagidxgroupsep
{ \ifdatagidxshowgroups \indexspace \fi }
\tl_set:Nn \datagidxgroupheader
{
  \legacy_if:nT { datagidxshowgroups }
  {
    \item
    \makebox [ \linewidth ]
    {
      \textbf
      {
        \DTLgidxGroupHeaderTitle { \datagidxcurrentgroup }
      }
    }
  }
  \DTLpar\nobreak\@afterheading

```

```

    }
  }
  \tl_set:Nn \datagidxitem
  {
    Is this the start of a new group?
    \tl_if_empty:NTF \datagidxprevgroup
    {
      First item of the list.
      \datagidxgroupheader
    }
    {
      Not the first item of the list. Is this item's group the same as the last item's group? Do
      nothing if the same.
      \tl_if_eq:NNF \datagidxcurrentgroup \datagidxprevgroup
      {
        Different, so do the separator and the header.
        \datagidxgroupsep
        \datagidxgroupheader
      }
    }
    Now get on with this item.
    \item
    \datagidxtarget { \Label }
    {
      \DTLgidxNameFont { \DTLgidxNameCase { \Name } }
    }
    \DTLgidxPostName
    \datagidx@item@body
    \DTLgidxChildrenSeeAlso
    \DTLgidxEndItem
  }
  \tl_set:Nn \datagidxchildstart
  {
    \group_begin:
    \dim_zero:N \parindent
    \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
    \cs_set_eq:NN \item \@idxitem
  }
  \tl_set:Nn \datagidxchildend { \group_end: }
  \tl_set:Nn \datagidxchilditem
  {
    \dim_set:Nn \l__datatool_tmpa_dim
    {
      \datagidx@level \datagidxindent
    }
    \@idxitem
    \hspace* { \l__datatool_tmpa_dim }
  }

```

```

\refstepcounter {DTLgidxChildCount}
\datagidxtarget { \Label }
{
  \DTLgidxChildStyle
  {
    \DTLgidxNameFont { \DTLgidxNameCase { \Name } }
    \DTLgidxPostChildName
  }
}
\DTLgidxSymbolDescription
\DTLgidxDoSeeOrLocation
\DTLgidxChildrenSeeAlso
}
\tl_set:Nn \datagidxseealsostart
{
  \group_begin:
  \dim_zero:N \parindent
  \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
  \int_incr:N \datagidx@level
  \dim_set:Nn \l__datatool_tmpa_dim
  {
    \datagidx@level \datagidxindent
  }
  \@idxitem
  \hspace* { \l__datatool_tmpa_dim }
}
\tl_set:Nn \datagidxseealsoend { \group_end: }
}

```

Make this the default style:

```

\datagidxsetstyle { index }
\dim_new:N \l__datagidx_childindent_dim

```

\datagidxmapdata

```

\NewDocumentCommand \datagidxmapdata { m }
{
  \DTLmapdata [ name = \DTLgidxCurrentdb , read-only ]
  {
    \exp_args:NV \__datatool_map_get_values_noerr:n
    \DTLgidxAssignList
    \__datagidx_filter:T
    {
      \__datagidx_unwrap_location:N \Location
      #1
    }
  }
}
}

```

17.1.2 indexalign

Similar to index style but aligns the descriptions.

atagidx@style@indexalign

```
\datagidxnewstyle { indexalign }
{
  \tl_set:Nn \datagidxstart
  {
    \group_begin:
    \dim_zero:N \parindent
    \dim_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
    \dim_zero:N \datagidxnamewidth
    \datagidxmapdata
    {
      \datatool_if_null:NT \Parent
      {
        \datagidx@doifdisplayed
        {
          \datatool_measure_width:Nn
            \l__datatool_tmpa_dim
            {
              \DTLgidxNameFont { \DTLgidxNameCase { \Name } }
            }
          \dim_compare:nNnT
            { \l__datatool_tmpa_dim }
            >
            { \datagidxnamewidth }
            {
              \dim_set_eq:NN
                \datagidxnamewidth
                \l__datatool_tmpa_dim
            }
        }
      }
    }
  }
  \datatool_measure_width:Nn
    \l__datatool_tmpa_dim { \DTLgidxPostName }
  \dim_add:Nn \datagidxnamewidth
    {
      \l__datatool_tmpa_dim
    }
  \dim_set:Nn \datagidxdescwidth
    {
      \linewidth - \datagidxnamewidth
    }
  \dim_compare:nNnT
    { \datagidxsymbolwidth } > { \c_zero_dim }
    {
      \datatool_measure_width:Nn
```

```

\l__datatool_tmpa_dim { \DTLgidxSymDescSep }
\dim_sub:Nn \datagidxdescwidth
{
  \datagidxsymbolwidth
  + \l__datatool_tmpa_dim
}
}
\dim_compare:nNnT
{ \datagidxlocationwidth } > { \c_zero_dim }
{
  \datatool_measure_width:Nn
  \l__datatool_tmpa_dim { \DTLgidxPreLocation }
  \dim_sub:Nn \datagidxdescwidth
  {
    \datagidxlocationwidth
    + \l__datatool_tmpa_dim
  }
}
}

```

Has the symbol width been set?

```

\dim_compare:nNnTF
{ \datagidxsymbolwidth } > { \c_zero_dim }
{

```

Yes, symbol width has been set. Has the location width been set?

```

\dim_compare:nNnTF
{ \datagidxlocationwidth } > { \c_zero_dim }
{

```

Both symbol and location widths have been set.

```

\bool_if:NTF \l__datagidx_symbol_left_bool
{

```

Symbol is on the left.

```

\tl_set:Nn \datagidx@item@body
{
  \begin{minipage} [t]
    { \datagidxsymbolwidth }
    \datagidxsymalign
    \tl_clear:N \DTLgidxSymDescSep
    \DTLgidxSymbolDescLeft
  \end{minipage}
  \DTLgidxSymDescSep
  \begin{minipage} [t]
    { \datagidxdescwidth }
    \tl_clear:N \DTLgidxSymDescSep
    \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
    \DTLgidxSymbolDescRight
  \end{minipage}
  \DTLgidxPreLocation
  \begin{minipage} [t]

```

```

        { \datagidxlocationwidth }
        \datagidxlocalign
        \tl_clear:N \DTLgidxPreLocation
        \DTLgidxDoSeeOrLocation
    \end{minipage}
}
}
{

```

Symbol is on the right.

```

\tl_set:Nn \datagidx@item@body
{
  \begin{minipage} [t]
    { \datagidxdescwidth }
    \tl_clear:N \DTLgidxSymDescSep
    \DTLgidxSymbolDescLeft
  \end{minipage}
  \DTLgidxSymDescSep
  \begin{minipage} [t]
    { \datagidxsymbolwidth }
    \datagidxsymalign
    \tl_clear:N \DTLgidxSymDescSep
    \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt}
    \DTLgidxSymbolDescRight
  \end{minipage}
  \DTLgidxPreLocation
  \begin{minipage} [t]
    { \datagidxlocationwidth }
    \datagidxlocalign
    \tl_clear:N \DTLgidxPreLocation
    \DTLgidxDoSeeOrLocation
  \end{minipage}
}
}
{

```

Location width hasn't been set. (Only symbol width has been set.)

```

\bool_if:NTF \l__datagidx_symbol_left_bool
{
  \tl_set:Nn \datagidx@item@body
  {
    \begin{minipage} [t]
      { \datagidxsymbolwidth }
      \datagidxsymalign
      \tl_clear:N \DTLgidxSymDescSep
      \DTLgidxSymbolDescLeft
    \end{minipage}
    \DTLgidxSymDescSep
    \begin{minipage} [t]
      { \datagidxdescwidth }

```

```

        \tl_clear:N \DTLgidxSymDescSep
        \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
        \DTLgidxSymbolDescRight
        \DTLgidxDoSeeOrLocation
    \end{minipage}
}
}
{

```

Symbol is on the right. This combination may look weird.

```

\tl_set:Nn \datagidx@item@body
{
  \begin{minipage} [t]
    { \datagidxdescwidth }
    \tl_clear:N \DTLgidxSymDescSep
    \DTLgidxSymbolDescLeft
  \end{minipage}
  \DTLgidxSymDescSep
  \begin{minipage} [t]
    { \datagidxsymbolwidth }
    \datagidxsymalign
    \tl_clear:N \DTLgidxSymDescSep
    \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
    \DTLgidxSymbolDescRight
    \DTLgidxDoSeeOrLocation
  \end{minipage}
}
}
}
}
{

```

Symbol width hasn't been set. Has the location width been set?

```

\dim_compare:nNnTF
{ \datagidxlocationwidth } > { \c_zero_dim }
{

```

Only location width has been set.

```

\tl_set:Nn \datagidx@item@body
{
  \begin{minipage} [t]
    { \datagidxdescwidth }
    \skip_set:Nn \parskip {0pt ~ plus ~ 0.3pt }
    \DTLgidxSymbolDescription
  \end{minipage}
  \DTLgidxPreLocation
  \begin{minipage} [t]
    { \datagidxlocationwidth }
    \datagidxlocalign
    \tl_clear:N \DTLgidxPreLocation
    \DTLgidxDoSeeOrLocation

```

```

    }
  }
  {

```

Neither location nor symbol widths have been set.

```

    \tl_set:Nn \datagidx@item@body
    {
      \begin{minipage} [t]
        { \datagidxdescwidth }
        \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
        \DTLgidxSymbolDescription
        \DTLgidxDoSeeOrLocation
      \end{minipage}
    }
  }
}
\tl_set:Nn \datagidxend { \datagidx_end: }
\tl_clear:N \datagidxgroupsep
\tl_clear:N \datagidxgroupheader
\tl_set:Nn \datagidxitem
{

```

Is this the start of a new group?

```

    \tl_if_empty:NTF \datagidxprevgroup
    {

```

First item of the list.

```

      \datagidxgroupheader
    }
  {

```

Not the first item of the list. Is this item's group the same as the last item's group? If the same, do nothing

```

    \tl_if_eq:NNF \datagidxcurrentgroup \datagidxprevgroup
    {

```

Different, so do the separator and the header.

```

      \datagidxgroupsep
      \datagidxgroupheader
    }
  }

```

Get on with this item

```

    \hangindent0pt\relax
    \parindent0pt\relax
    \makebox [ \datagidxnamewidth ] [l]
    {
      \datagidxtarget { \Label }
      {
        \DTLgidxNameFont
        { \DTLgidxNameCase { \Name } }

```

```

        \DTLgidxPostName
    }
}
\datagidx@item@body
\par
\DTLgidxChildrenSeeAlso
\DTLgidxEndItem
}
\tl_set:Nn \datagidxchildstart
{
  \group_begin:
  \dim_set:Nn \l__datatool_tmpa_dim
  { \datagidx@level \datagidxindent }
  \dim_set:Nn \l__datagidx_childindent_dim
  {
    \linewidth - \l__datatool_tmpa_dim
  }
  \dim_zero:N \parindent
  \dim_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
  \tl_set:Nx \item
  {
    \exp_not:N \parshape = \c_one_int
    \dim_use:N \l__datatool_tmpa_dim \c_space_tl ~
    \dim_use:N \l__datagidx_childindent_dim
  }
  \dim_zero:N \datagidxnamewidth
  \datagidxmapdata
  {
    \datatool_if_null:NT \Parent
    {
      \datagidx@doifdisplayed
      {
        \datatool_measure_width:Nn
        \l__datatool_tmpa_dim
        {
          \DTLgidxChildStyle
          {
            \DTLgidxNameFont
            { \DTLgidxNameCase { \Name } }
          }
        }
      }
      \dim_compare:nNNT
      { \l__datatool_tmpa_dim }
      >
      { \datagidxnamewidth }
      {
        \dim_set_eq:NN
        \datagidxnamewidth
        \l__datatool_tmpa_dim
      }
    }
  }
}

```

```

    }
  }
}
\datatool_measure_width:Nn
  \l_datatool_tmpa_dim
  { \DTLgidxChildStyle \DTLgidxPostChildName }
\dim_add:Nn \datagidxnamewidth
  {
    \l_datatool_tmpa_dim
  }
\dim_set:Nn \datagidxdescwidth
  {
    \l_datagidx_childindent_dim
    - \datagidxnamewidth
  }
}
\tl_set:Nn \datagidxchildend { \group_end: }
\tl_set:Nn \datagidxchilditem
  {
    \item
    \refstepcounter {DTLgidxChildCount}
    \makebox [ \datagidxnamewidth ] [l]
    {
      \datagidxtarget { \Label }
      {
        \DTLgidxChildStyle
        {
          \DTLgidxNameFont
          { \DTLgidxNameCase {\Name} }
          \DTLgidxPostChildName
        }
      }
    }
  }
\begin{minipage} [t]
  { \datagidxdescwidth }
  \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
  \DTLgidxSymbolDescription
  \DTLgidxDoSeeOrLocation
  \DTLgidxChildrenSeeAlso
\end{minipage}
\par
}
}

```

`\datagidxindent` Indent used by `index` and `indexalign` styles.

```

\newlength\datagidxindent
\dim_set:Nn \datagidxindent { 10pt }

```

17.1.3 align

`\datagidxnamewidth` Length used by `align` and `indexalign` style name.
`\newlength\datagidxnamewidth`

`\datagidxdescwidth` Length used by `align` and `indexalign` style description.
`\newlength\datagidxdescwidth`

`\datagidx@style@align`

```
\datagidxnewstyle { align }
{
  \tl_set:Nn \datagidxstart
  {
    \group_begin:
    \dim_zero:N \parindent
    \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
    \dim_zero:N \datagidxnamewidth
    \datagidxmapdata
    {
      \datatool_if_null:NT \Parent
      {
        \datagidx@doifdisplayed
        {
          \datatool_measure_width:Nn
          \l__datatool_tmpa_dim
          {
            \DTLgidxNameFont
            { \DTLgidxNameCase { \Name } }
          }
          \dim_compare:nNnT
          { \l__datatool_tmpa_dim }
          >
          { \datagidxnamewidth }
          {
            \dim_set_eq:NN
            \datagidxnamewidth
            \l__datatool_tmpa_dim
          }
        }
      }
    }
  }
  \datatool_measure_width:Nn
  \l__datatool_tmpa_dim
  { \DTLgidxPostName }
  \dim_add:Nn \datagidxnamewidth
  {
    \l__datatool_tmpa_dim
  }
  \dim_set:Nn \datagidxdescwidth
  {
```

```

    \linewidth - \datagidxnamewidth
  }
\dim_compare:nNNT
  { \datagidxsymbolwidth } > { \c_zero_dim }
  {
    \datatool_measure_width:Nn
    \l__datatool_tmpa_dim
    { \DTLgidxSymDescSep }
    \dim_sub:Nn \datagidxdescwidth
    {
      \datagidxsymbolwidth
      + \l__datatool_tmpa_dim
    }
  }
}
\dim_compare:nNNT
  { \datagidxlocationwidth } > { \c_zero_dim }
  {
    \datatool_measure_width:Nn
    \l__datatool_tmpa_dim
    { \DTLgidxPreLocation }
    \dim_sub:Nn \datagidxdescwidth
    {
      \datagidxlocationwidth
      + \l__datatool_tmpa_dim
    }
  }
}

```

Has the symbol width been set?

```

\dim_compare:nNNTF
  { \datagidxsymbolwidth } > { \c_zero_dim }
  {

```

Yes, symbol width has been set. Has the location width been set?

```

\dim_compare:nNNTF
  { \datagidxlocationwidth } > { \c_zero_dim }
  {

```

Both symbol and location widths have been set.

```

\bool_if:NTF \l__datagidx_symbol_left_bool
  {

```

Symbol is on the left.

```

\tl_set:Nn \datagidx@item@body
  {
    \begin{minipage} [t]
      { \datagidxsymbolwidth }
    \datagidxsymalign
    \tl_clear:N \DTLgidxSymDescSep
    \DTLgidxSymbolDescLeft
    \end{minipage}
    \DTLgidxSymDescSep
  }

```

```

\begin{minipage} [t]
  { \datagidxdescwidth }
\tl_clear:N \DTLgidxSymDescSep
\skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
\DTLgidxSymbolDescRight
\end{minipage}
\DTLgidxPreLocation
\begin{minipage} [t]
  { \datagidxlocationwidth }
  \datagidxlocalign
  \tl_clear:N \DTLgidxPreLocation
  \DTLgidxDoSeeOrLocation
  \DTLgidxChildrenSeeAlso
\end{minipage}
}
}
{

```

Symbol is on the right.

```

\tl_set:Nn \datagidx@item@body
{
  \begin{minipage} [t]
    { \datagidxdescwidth }
    \tl_clear:N \DTLgidxSymDescSep
    \DTLgidxSymbolDescLeft
  \end{minipage}
  \DTLgidxSymDescSep
  \begin{minipage} [t]
    { \datagidxsymbolwidth }
    \datagidxsymalign
    \tl_clear:N \DTLgidxSymDescSep
    \skip_set:N \parskip { 0pt ~ plus ~ 0.3pt }
    \DTLgidxSymbolDescRight
  \end{minipage}
  \DTLgidxPreLocation
  \begin{minipage} [t]
    { \datagidxlocationwidth }
    \datagidxlocalign
    \tl_clear:N \DTLgidxPreLocation
    \DTLgidxDoSeeOrLocation
    \DTLgidxChildrenSeeAlso
  \end{minipage}
}
}
}
{

```

Location width hasn't been set. (Only symbol width has been set.)

```

\bool_if:NTF \l__datagidx_symbol_left_bool
{
  \tl_set:Nn \datagidx@item@body

```

```

{
  \begin{minipage} [t]
    { \datagidxsymbolwidth }
    \datagidxsymalign
    \tl_clear:N \DTLgidxSymDescSep
    \DTLgidxSymbolDescLeft
  \end{minipage}
  \DTLgidxSymDescSep
  \begin{minipage} [t]
    { \datagidxdescwidth }
    \tl_clear:N \DTLgidxSymDescSep
    \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
    \DTLgidxSymbolDescRight
    \DTLgidxDoSeeOrLocation
    \DTLgidxChildrenSeeAlso
  \end{minipage}
}
}
{

```

Symbol is on the right. This combination may look weird.

```

\tl_set:Nn \datagidx@item@body
{
  \begin{minipage} [t]
    { \datagidxdescwidth }
    \tl_clear:N \DTLgidxSymDescSep
    \DTLgidxSymbolDescLeft
  \end{minipage}
  \DTLgidxSymDescSep
  \begin{minipage} [t]
    { \datagidxsymbolwidth }
    \datagidxsymalign
    \tl_clear:N \DTLgidxSymDescSep
    \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
    \DTLgidxSymbolDescRight
    \DTLgidxDoSeeOrLocation
    \DTLgidxChildrenSeeAlso
  \end{minipage}
}
}
}
{

```

Symbol width hasn't been set. Has the location width been set?

```

\dim_compare:nNnTF
{ \datagidxlocationwidth } > { \c_zero_dim }
{

```

Only location width has been set.

```

\tl_set:Nn \datagidx@item@body

```

```

    {
      \begin{minipage} [t]
        { \datagidxdescwidth }
        \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
        \DTLgidxSymbolDescription
      \end{minipage}
      \DTLgidxPreLocation
      \begin{minipage} [t]
        { \datagidxlocationwidth }
        \datagidxlocalign
        \tl_clear:N \DTLgidxPreLocation
        \DTLgidxDoSeeOrLocation
        \DTLgidxChildrenSeeAlso
      \end{minipage}
    }
  }
  {
    Neither location nor symbol widths have been set.
    \tl_set:Nn \datagidx@item@body
      {
        \begin{minipage} [t]
          { \datagidxdescwidth }
          \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
          \DTLgidxSymbolDescription
          \DTLgidxDoSeeOrLocation
          \DTLgidxChildrenSeeAlso
        \end{minipage}
      }
    }
  }
  \tl_set:Nn \datagidxend { \datagidx_end: }
  \tl_set:Nn \datagidxgroupsep
    { \ifdatagidxshowgroups \indexspace \fi }
  \tl_set:Nn \datagidxgroupheader
    {
      \ifdatagidxshowgroups
        \item
        \makebox [ \linewidth ]
        {
          \textbf
          {
            \DTLgidxGroupHeaderTitle
            { \datagidxcurrentgroup }
          }
        }
      }
    }
  \DTLpar\nobreak\@afterheading
\fi
}

```

```

\tl_set:Nn \datagidxitem
{
Is this the start of a new group?
\tl_if_empty:NTF \datagidxprevgroup
{
First item of the list.
\datagidxgroupheader
}
{
Not the first item of the list. Is this item's group the same as the last item's group? If
the same, do nothing.
\tl_if_eq:NNF \datagidxcurrentgroup \datagidxprevgroup
{
Different, so do the separator and the header.
\datagidxgroupsep
\datagidxgroupheader
}
}
\hangindent \c_zero_dim
\parindent \c_zero_dim
\makebox [ \datagidxnamewidth ] [l]
{
\datagidxtarget { \Label }
{
\DTLgidxNameFont
{ \DTLgidxNameCase {\Name} }
\DTLgidxPostName
}
}
\datagidx@item@body
\DTLgidxEndItem
}
\tl_set:Nn \datagidxchildstart
{
\group_begin:
\dim_zero:N \parindent
\skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
\dim_zero:N \datagidxnamewidth
\datagidxmapdata
{
\datatool_if_null:NT \Parent
{
\datagidx@doifdisplayed
{
\datatool_measure_width:Nn
\l__datatool_tmpa_dim
{

```

```

        \DTLgidxChildStyle
        {
            \DTLgidxNameFont
            { \DTLgidxNameCase {\Name} }
        }
    }
\dim_compare:nNnT
{ \l__datatool_tmpa_dim }
>
{ \datagidxnamewidth }
{
    \dim_set_eq:NN
    \datagidxnamewidth
    \l__datatool_tmpa_dim
}
}
}
}
\datatool_measure_width:Nn
\l__datatool_tmpa_dim
{
    \DTLgidxChildStyle \DTLgidxPostChildName
}
\dim_add:Nn \datagidxnamewidth
{ \l__datatool_tmpa_dim }
\dim_set:Nn \datagidxdescwidth
{
    \linewidth - \datagidxnamewidth
}
}
\tl_set:Nn \datagidxchildend { \group_end: }
\tl_set:Nn \datagidxchilditem
{
    \hangindent \c_zero_dim
    \parindent \c_zero_dim
    \refstepcounter {DTLgidxChildCount}
    \makebox [ \datagidxnamewidth ] [l]
    {
        \datagidxtarget {\Label}
        {
            \DTLgidxChildStyle
            {
                \DTLgidxNameFont
                { \DTLgidxNameCase {\Name} }
                \DTLgidxPostChildName
            }
        }
    }
}
\begin{minipage} [t]
{ \datagidxdescwidth }

```

```

\skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
\DTLgidxSymbolDescription
\DTLgidxDoSeeOrLocation
\DTLgidxChildrenSeeAlso
\end{minipage}
\par
}
}

```

17.1.4 gloss

\datagidx@style@gloss

```

\datagidxnewstyle { gloss }
{
\tl_set:Nn \datagidxstart
{
\group_begin:
\dim_zero:N \parindent
\skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
\dim_zero:N \datagidxnamewidth
\datagidxmapdata
{
\datatool_if_null:NT \Parent
{
\datagidx@doifdisplayed
{
\datatool_measure_width:Nn
\l__datatool_tmpa_dim
{
\DTLgidxNameFont
{ \DTLgidxNameCase {\Name} }
}
\dim_compare:nNnT
{ \l__datatool_tmpa_dim }
>
{ \datagidxnamewidth }
{
\dim_set_eq:NN
\datagidxnamewidth
\l__datatool_tmpa_dim
}
}
}
}
\datatool_measure_width:Nn
\l__datatool_tmpa_dim
{ \DTLgidxPostName }
\dim_add:Nn \datagidxnamewidth
{ \l__datatool_tmpa_dim }
}
}

```

```

\dim_set:Nn \datagidxdescwidth
{
  \linewidth - \datagidxnamewidth
}
}
\tl_set:Nn \datagidxend { \datagidx_end: }
\tl_set:Nn \datagidxgroupsep
{
  \ifdatagidxshowgroups \indexspace \fi
}
\tl_set:Nn \datagidxgroupheader
{
  \ifdatagidxshowgroups
  \item
  \makebox [ \linewidth ]
  {
    \textbf
    {
      \DTLgidxGroupHeaderTitle
      { \datagidxcurrentgroup }
    }
  }
  \DTLpar\nobreak\@afterheading
\fi
}
\tl_set:Nn \datagidxitem
{
  Is this the start of a new group?
  \tl_if_empty:NTF \datagidxprevgroup
  {
    First item of the list.
    \datagidxgroupheader
  }
  {
    Not the first item of the list. Is this item's group the same as the last item's group? If
    the same, do nothing.
    \tl_if_eq:NMF \datagidxcurrentgroup\datagidxprevgroup
    {
      Different, so do the separator and the header.
      \datagidxgroupsep
      \datagidxgroupheader
    }
  }
  \dim_zero:N \hangindent
  \dim_zero:N \parindent
  \makebox [ \datagidxnamewidth ] [l]
  {

```

```

\datagidxtarget {\Label}
{
  \DTLgidxNameFont
  { \DTLgidxNameCase {\Name} }
  \DTLgidxPostName
}
}
\begin{minipage} [t]
{ \datagidxdescwidth }
\skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
\bool_lazy_all:nTF
{
  { \tl_if_empty_p:N \Description }
  { \tl_if_empty_p:N \Symbol }
  { \tl_if_empty_p:N \Location }
}
{
  \mbox { }
}
{
  \DTLgidxSymbolDescription
  \DTLgidxDoSeeOrLocation
}
\DTLgidxChildrenSeeAlso
\end{minipage}
\DTLgidxEndItem
}
\tl_set:Nn \datagidxchildstart
{
  \group_begin:
  \tl_clear:N \datagidx@childsep
  \setcounter {DTLgidxChildCount} { 0 }
}
\tl_set:Nn \datagidxchildend
{ \DTLgidxPostChild \group_end: }
\tl_set:Nn \datagidxchilditem
{
  \datagidx@childsep
  \refstepcounter {DTLgidxChildCount}
  \datagidxtarget {\Label}
  {
    \DTLgidxChildStyle
    {
      \DTLgidxNameFont
      { \DTLgidxNameCase {\Name} }
      \DTLgidxPostChildName
    }
  }
}
\DTLgidxSymbolDescription

```

```

        \DTLgidxDoSeeOrLocation
        \DTLgidxChildrenSeeAlso
        \tl_set_eq:NN \datagidx@childsep \DTLgidxChildSep
    }
}

```

`\DTLgidxChildSep` Separator between child entries for gloss style.

```
\newcommand*\DTLgidxChildSep}{ ~ }
```

`\DTLgidxPostChild` What to put at the end of child entries for gloss style.

```
\newcommand*\DTLgidxPostChild}{ }
```

`\DTLgidxDictHead` Group header for dict style.

```

\cs_if_exist:NTF \chapter
{
  \newcommand \DTLgidxDictHead
  {
    \chapter
    {
      \DTLgidxGroupHeaderTitle { \datagidxcurrentgroup }
    }
  }
}
{
  \newcommand \DTLgidxDictHead
  {
    \section
    {
      \DTLgidxGroupHeaderTitle { \datagidxcurrentgroup }
    }
  }
}

```

`\DTLgidxCategoryNameFont` Font used for ‘category’ entries with ‘dict’ style.

```
\newcommand*\DTLgidxCategoryNameFont}[1]{#1}
```

`\DTLgidxCategorySep` Separator used with ‘dict’ style.

```
\newcommand*\DTLgidxCategorySep}{\space}
```

`\DTLgidxSubCategorySep` Separator used with ‘dict’ style.

```
\newcommand*\DTLgidxSubCategorySep}{\space}
```

`\datagidxdictindent` Indent used by ‘dict’ style.

```
\newcommand*\datagidxdictindent}{1em}
```

`\DTLgidxDictPostItem` What to do at the end of each item in the ‘dict’ style.

```
\newcommand{\DTLgidxDictPostItem}{\DTLgidxEndItem}
```

`\datagidx@style@dict` Dictionary style. This assumes a hierarchical structure where the top level entries have a name. The next level is used to indicate a category, such as “adjective” or “noun”. If there is only one meaning this level also has a description. If there is more than one meaning, each meaning should be a child of the category entry. Only third level entries are numbered. The `child` key is ignored in this style. The symbol is ignored. The location and symbols widths are also ignored.

```

\datagidxnewstyle { dict }
{
  \tl_set:Nn \datagidxstart
  {
    \group_begin:
    \dim_zero:N \parindent
    \dim_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
    \dim_set:Nn \l__datatool_tmpa_dim
    {
      \linewidth - \datagidxdictindent
    }
    \dim_set:Nn \l__datagidx_childindent_dim
    { \datagidxdictindent }
    \tl_set:Nx \datagidxdictparshape
    {
      \exp_not:N \parshape=2 ~ 0pt ~
      \dim_use:N \linewidth \c_space_tl ~
      \dim_use:N \l__datagidx_childindent_dim
      \c_space_tl ~
      \dim_use:N \l__datatool_tmpa_dim
    }
    \int_set_eq:NN \datagidx@level \c_one_int
  }
}

```

Index columns are usually too narrow for fully justified text.

```

\raggedright
}
\tl_set:Nn \datagidxend { \datagidx_end: }
\tl_clear:N \datagidxgroupsep
\tl_set:Nn \datagidxgroupheader
{
  \ifdatagidxshowgroups
  \datagidxend
  \datagidx@postend
  \DTLgidxDictHead
  \l__datagidx_prestart_tl
  \datagidxstart
  \fi
}
\tl_set:Nn \datagidxitem
{

```

Is this the start of a new group?

```

\tl_if_empty:NTF \datagidxprevgroup
{

```

First item of the list.

```
\datagidxgroupheader  
}  
{
```

Not the first item of the list. Is this item's group the same as the last item's group? If the same, do nothing.

```
\tl_if_eq:NNF \datagidxcurrentgroup \datagidxprevgroup  
{
```

Different, so do the separator and the header.

```
\datagidxgroupsep  
\datagidxgroupheader  
}  
}
```

Now get on with this item.

```
\datagidxdictparshape  
\datagidxtarget {\Label}  
{  
  \DTLgidxNameFont  
  { \DTLgidxNameCase {\Name} }  
}  
\DTLgidxPostName
```

Initialise category separator to do nothing.

```
\tl_clear:N \datagidx@catsep  
\tl_clear:N \datagidx@subcatsep  
\DTLgidxSymbolDescription
```

No location list.

```
\DTLgidxChildrenSeeAlso  
\DTLgidxDictPostItem  
}  
\tl_set:Nn \datagidxchildstart  
{ \group_begin: }  
\tl_set:Nn \datagidxchildend { \group_end: }  
\tl_set:Nn \datagidxchilditem  
{
```

Which level are we on?

```
\int_compare:nNnTF  
{ \datagidx@level } = { 2 }  
{
```

Category entry

```
\datagidx@catsep  
\tl_set_eq:NN  
  \datagidx@catsep  
  \DTLgidxCategorySep  
\tl_clear:N \datagidx@subcapsep  
\datagidxtarget { \Label }
```

```

    {
      \DTLgidxChildStyle
      {
        \DTLgidxCategoryNameFont
        { \DTLgidxNameCase{\Name} }
        \DTLgidxPostChildName
      }
    }
  \setcounter {DTLgidxChildCount} {0}
}
{
Sub Category entry
  \datagidx@subcatsep
  \tl_set_eq:NN
  \datagidx@subcatsep
  \DTLgidxSubCategorySep
  \refstepcounter {DTLgidxChildCount}
  \DTLgidxChildCountLabel
  \DTLgidxPostChildName
}
\DTLgidxSymbolDescription
\DTLgidxDoSeeOrLocation
\DTLgidxChildrenSeeAlso
}
\tl_set:Nn \datagidxseealsostart
{
  \group_begin:
  \dim_zero:N \parindent
  \skip_set:Nn \parskip { 0pt ~ plus ~ 0.3pt }
  \int_incr:N \datagidx@level
  \dim_set:Nn \l__datatool_tmpa_dim
  {
    \datagidx@level \datagidxindent
  }
  \@idxitem
  \hspace* { \l__datatool_tmpa_dim }
}
\tl_set:Nn \datagidxseealsoend { \group_end: }
}

```

17.2 Location Lists

`\dtldofirstlocation` Only display the first location in the list.

```

\newcommand*{\dtldofirstlocation}{%
  \group_begin:
  \__datagidx_unwrap_location:N \Location
  \clist_map_inline:Nn \Location
  {
    \tl_if_empty:nF { ##1 }

```

```

{
  \tl_if_head_eq_meaning:nNTF { ##1 } [
    {
      \__datagidx_getlocation:wnn ##1
    }
    {
      \__datagidx_getlocation:wnn [ ] { } { }
    }
  ]
  \datagidxlink
  { \datagidx@current@target }
  {
    \__datagidx_formatlocation:VV
    \datagidx@current@format
    \datagidx@current@locationstring
  }
}

```

Only interested in the first item, so break out of loop.

```

  \clist_map_break:
}
}
\group_end:
}

```

`\datagidx@formatlocation` Version 3.0: replaced `\datagidx@formatlocation` with:

```

\cs_new:Nn \__datagidx_formatlocation:nn
{
  \tl_if_empty:nTF { #1 }
  { #2 }
  {
    \cs_if_exist:cTF { #1 }
    {
      \use:c { #1 } { #2 }
    }
    {
      \PackageWarning {datagidx}
      { Unknown ~ format ~ `#1' }
      #2
    }
  }
}
\cs_generate_variant:Nn
  \__datagidx_formatlocation:nn
  { VV }

```

`\dtldolocationlist` Display the location list.

```

\NewDocumentCommand \dtldolocationlist { }
{
  \datatool_if_null_or_empty:NF \Location
  {
    \group_begin:

```

```

\int_set:Nn \l__datagidx_prevloc_int {-1}
\tl_clear:N \datagidx@prev@locationstring
\tl_clear:N \datagidx@prev@format
\tl_clear:N \datagidx@prev@locationformat
\tl_clear:N \datagidx@prev@prefix
\tl_clear:N \datagidx@prev@target
\tl_clear:N \datagidx@location@sep
\int_set:Nn \l__datagidx_startloc_int {-1}
\__datagidx_unwrap_location:N \Location
\clist_map_function:NN
  \Location \datagidx@parse@location
  \__datagidx_do_prev_location: % tidy up loose ends
  \group_end:
}
}

```

\if@dtl@sequential Conditional to keep track of sequences. Version 3.0: replaced \if@dtl@sequential with:

```
\bool_new:N \l__datagidx_sequential_bool
```

\datagidx@getlocdo Handler for \datagidx@docompllist Version 3.0: removed

Assign a numeric value to a location:

```

\regex_const:Nn \c__datagidx_location_int_regex
{ ( \d+ ) \Z }
\regex_const:Nn \c__datagidx_location_roman_regex
{ ( [ I V X L C D M ]+ | [ i v x l c d m ]+ ) \Z }
\regex_const:Nn \c__datagidx_location_alph_regex
{ ( [ a-z A-Z ] ) \Z }
\cs_new:Nn \__datagidx_get_location_num:Nn
{
  \DTLifint { #2 }
  {
    \int_set:Nn #1 { \l__datatool_datum_value_tl }
  }
  {
    \regex_extract_once:NnNTF
      \c__datagidx_location_int_regex { #2 }
      \l__datatool_tmpb_seq
    {
      \exp_args:NNx \int_set:Nn #1
        { \seq_item:Nn \l__datatool_tmpb_seq { 2 } }
    }
  }
  {
    \regex_extract_once:NnNTF
      \c__datagidx_location_roman_regex { #2 }
      \l__datatool_tmpb_seq
    {
      \exp_args:NNx \tl_set:Nn
        \l__datatool_tmpb_tl

```

```

        {
            \exp_not:N \int_from_roman:n
            {
                \seq_item:Nn \l__datatool_tmpb_seq { 2 }
            }
        }
    \int_set:Nn #1 { \l__datatool_tmpb_tl }
}
{
\regex_extract_once:NnNTF
\c__datagidx_location_alph_regex { #2 }
\l__datatool_tmpb_seq
{
\exp_args:NNx \tl_set:Nn
\l__datatool_tmpb_tl
{
\exp_not:N \int_from_alph:n
{
\seq_item:Nn \l__datatool_tmpb_seq { 2 }
}
}
\int_set:Nn #1 { \l__datatool_tmpb_tl }
}
{
\int_set:Nn #1 { -1 }
}
}
}
}
\cs_generate_variant:Nn \__datagidx_get_location_num:Nn
{ NV }
\int_new:N \l__datagidx_prevloc_int
\int_new:N \l__datagidx_currentloc_int

```

\datagidx@location@start Version 3.0: replaced \datagidx@location@start with:

```
\int_new:N \l__datagidx_startloc_int
```

\datagidx@getlocation Syntax: [*format*]{*location*}{*anchor*} Get the location and store in \current@location:

```
\cs_new:Npn \__datagidx_getlocation:wnn
[ #1 ] #2 #3
{
```

Store the original value.

```
\tl_set:Nn \datagidx@current@locationstring { #2 }
```

Store the format:

```
\tl_set:Nn \datagidx@current@format { #1 }
```

Store the target:

```

\l_set:Nn \datagidx@current@target { #3 }
\l_if_empty:nTF { #2 }
{
  \l_clear:N \datagidx@current@prefix
  \l_clear:N \datagidx@current@location
}
{

```

If the location contains a compositor, we need to get the final element and store the rest as a prefix:

```

\seq_set_split:NVn \l__datatool_tmpa_seq
  \l__datagidx_compositor_tl
  { #2 }
\seq_pop_right:NN \l__datatool_tmpa_seq
  \datagidx@current@location
\l_set:Nx \datagidx@current@prefix
  {
    \seq_use:Nn \l__datatool_tmpa_seq
      \l__datagidx_compositor_tl
  }
}
}

```

`\datagidx@parse@location` Parses the location list (given in the argument).

```

\newcommand*{\datagidx@parse@location}[1]{
  \l_set:Nn \l__datagidx_location_tl { #1 }
  \__datagidx_unwrap_location:N
  \l__datagidx_location_tl

```

Parse location format.

```

\exp_args:NV \l_if_head_eq_meaning:nNTF
  \l__datagidx_location_tl [
  {
    \exp_after:wN \__datagidx_getlocation:wnn
      \l__datagidx_location_tl
  }
  {
    \__datagidx_getlocation:wnn [ ] { } { }
  }
}

```

If this is the same as the previous location, do nothing.

```

\l_if_eq:NNTF
  \datagidx@prev@locationstring
  \datagidx@current@locationstring
{

```

If the format is different, let the non-empty format over-ride the empty format.

```

\l_if_eq:NNF
  \datagidx@prev@format
  \datagidx@current@format
{

```

```

\ifempty\datagidx@current@format
{
\ifempty\datagidx@prev@format
{
Previous format is empty, so update.
\seteq\datagidx@prev@format
\datagidx@current@format
}
{
\PackageWarning{datagidx}
{
Conflicting ~ location ~ formats ~
\datagidx@prev@format' ~ and ~
\datagidx@current@format' ~ for ~
location ~ \datagidx@current@location'
}
}
}
}
}
{
\@datagidx@parse@location
}
}

```

@datagidx@parse@location

```

\newcommand*\@datagidx@parse@location}{
Get a numeric value for this location.
\__datagidx_get_location_num:NV
\l__datagidx_currentloc_int
\datagidx@current@location
Check if we have a sequence.
\bool_set_true:N \l__datagidx_sequential_bool
A change in font format breaks the sequence.
\ifeq\datagidx@prev@format \datagidx@current@format
{
A change in location format breaks the sequence.
\ifeq\datagidx@prev@locationformat
\datagidx@current@locationformat
{
A change in prefix breaks the sequence.
\ifeq\datagidx@prev@prefix \datagidx@current@prefix
{

```

Prefixes are different, so not a sequence.

```
    \bool_set_false:N \l__datagidx_sequential_bool
  }
}
```

Formats are different, so not a sequence.

```
    \bool_set_false:N \l__datagidx_sequential_bool
  }
}
```

Formats are different, so not a sequence.

```
    \bool_set_false:N \l__datagidx_sequential_bool
  }
\bool_if:NT \l__datagidx_sequential_bool
{
```

Is this location one more than the previous location?

```
\int_compare:nNnTF
{ \l__datagidx_prevloc_int + 1 }
=
{ \l__datagidx_currentloc_int }
{
```

It is one more than previous value. Is this location the same type as the previous location?

```
\tl_if_eq:NNTF
\datagidx@current@locationformat
\datagidx@prev@locationformat
{
```

They are the same, so we have a sequence.

```
    \bool_set_true:N \l__datagidx_sequential_bool
  }
}
```

They aren't the same, so we don't have a sequence.

```
    \bool_set_false:N \l__datagidx_sequential_bool
  }
}
{
  \bool_set_false:N \l__datagidx_sequential_bool
}
}
```

Has the sequence flag been set?

```
\bool_if:NNTF \l__datagidx_sequential_bool
{
```

Yes, we have a sequence. Has the start of the sequence been set?

```
\int_compare:nNnT
{ \l__datagidx_startloc_int } = { -1 }
```

```

    {
No it hasn't, so set it
    \int_set_eq:NN
    \l__datagidx_startloc_int
    \l__datagidx_prevloc_int
    \let\datagidx@location@startval\datagidx@prev@locationstring
    \let\datagidx@location@format\datagidx@prev@format
    \let\datagidx@location@target\datagidx@prev@target
    }
}
{

```

We don't have a sequence, so do the previous location.

```

    \__datagidx_do_prev_location:
}

```

Update previous location macros to this location.

```

    \let\datagidx@prev@location\datagidx@current@location
    \let\datagidx@prev@format\datagidx@current@format
    \let\datagidx@prev@prefix\datagidx@current@prefix
    \let\datagidx@prev@locationformat\datagidx@current@locationformat
    \let\datagidx@prev@locationstring\datagidx@current@locationstring
    \let\datagidx@prev@target\datagidx@current@target
    \int_set_eq:NN
    \l__datagidx_prevloc_int
    \l__datagidx_currentloc_int
}

```

`\DTLgidxLocationSep` Separator between locations.

```

\newcommand*\DTLgidxLocationSep}{, ~ }

```

`\DTLgidxLocationF` How to format a location list consisting of only two locations.

```

\newcommand*\DTLgidxLocationF}[2]{%
#1\DTLgidxLocationSep#2%
}

```

`\DTLgidxLocationFF` How to format a location list consisting of three or more locations.

```

\newcommand*\DTLgidxLocationFF}[2]{%
#1- -#2%
}

```

`\do@prevlocation` Do the previous location in the current list. Version 3.0: replaced `\do@prevlocation` with:

```

\cs_new:Nn \__datagidx_do_prev_location:
{

```

Have we come to the end of a sequence?

```

\int_compare:nNnTF
{ \l__datagidx_startloc_int } = { -1 }
{

```

Not the end of a sequence.

```
\tl_if_empty:NF \datagidx@prev@locationstring
{
  \datagidx@location@sep
  \datagidxlink{\datagidx@prev@target}%
  {
    \__datagidx_formatlocation:VV
    \datagidx@prev@format
    \datagidx@prev@locationstring
  }
  \def\datagidx@location@sep{\DTLgidXLocationSep}%
}
}
```

At the end of a sequence.

```
\datagidx@location@sep
\do@locrange
\def\datagidx@location@sep{\DTLgidXLocationSep}%
\int_set:Nn \l__datagidx_startloc_int { -1 }
}%
}
```

`\do@locrange` Format the location range.

```
\newcommand*{\do@locrange}{%
Are the start and end locations 2 or more apart?
\int_compare:nNnTF
{\l__datagidx_prevloc_int}
>
{ \l__datagidx_startloc_int + 1}%
}%
```

Yes, they are, so form a range:

```
\DTLgidXLocationFF
{%
  \datagidxlink{\datagidx@location@target}%
  {%
    \__datagidx_formatlocation:VV
    \datagidx@location@format
    \datagidx@location@startval
  }%
}%
{%
  \datagidxlink{\datagidx@prev@target}%
  {%
    \__datagidx_formatlocation:VV
    \datagidx@prev@format
    \datagidx@prev@locationstring
  }%
}%
```

```

    }%
    {%
No, they aren't so don't form a range:
    \DTLgidxLocationF
    {%
        \datagidxlink{\datagidx@location@target}%
        {%
            \__datagidx_formatlocation:VV
            \datagidx@location@format
            \datagidx@location@startval
        }%
    }%
    {%
        \datagidxlink{\datagidx@prev@target}%
        {%
            \__datagidx_formatlocation:VV
            \datagidx@prev@format
            \datagidx@prev@locationstring
        }%
    }%
}
}

```

18 Defining New Glossary/Index Databases

`\datagidx@defaultdatabase` The default database to which terms should be added. Version 3.0: replaced `\datagidx@defaultdatabase` with:

```
\tl_new:N \l__datagidx_default_database_tl
```

`\DTLgidxSetDefaultDB` Allow user to set the default database. Note that the name isn't expanded yet to allow for a placeholder command.

```
\newcommand*{\DTLgidxSetDefaultDB}[1]{%
  \tl_set:Nn \l__datagidx_default_database_tl { #1 }
}
```

`\ifdatagidxbalance`

```
\newif\ifdatagidxbalance
\datagidxbalancetrue
```

Default style is 'index':

```
\newcommand*{\datagidx@style}{index}
```

Define conditional to determine whether or not to show group headers and do sep. (Default is false.)

`\ifdatagidxshowgroups`

```
\newif\ifdatagidxshowgroups
\newcommand*{\datagidx@showgroups}{false}
```

```
\newgloss[options]{database name}{title}
```

\newgidx

Define \newgidx if it hasn't already been defined by the 'highopt' optimize setting.

```
\ifundef\newgidx
{%
  \newcommand*\newgidx{\datagidx@newgidx}
}%
{}
```

May only be used in the preamble (otherwise the entries will be undefined when their locations are read from the aux file).

```
\@onlypreamble\newgidx
```

\datagidx@highopt@newgidx The behaviour of \newgidx when the 'highopt' optimize option has been set.

```
\NewDocumentCommand \datagidx@highopt@newgidx { o m m }
{
```

Get the file name:

```
  \tl_set:Nx \datagidx@indexfilename
    { \text_purify:n { \datagidx@highoptfilename{ #2 } } }
```

Has the file been created?

```
  \IfFileExists{\datagidx@indexfilename}%
  {%
```

File does exist. Load it.

```
    \DTLread[format=dbtex] { \datagidx@indexfilename }
```

If the file was created pre v3.0, the new columns will be missing.

```
    __datagidx_update_loaded_data:n { #2 }
```

Update the 'datagidx' database.

```
    \group_begin:
      \IfValueT { #1 }
      {
        \keys_set_groups:nnn
          { datatool / index } { newgloss } { #1 }
      }
      \datagidx@newgidx@update {#2} {#3}
    \group_end:
  }
{
```

File doesn't exist. Behave as normal.

```
  \datagidx@newgidx[#1]{#2}{#3}
}
}
```

```
\loadgidx[options]{filename}{title}
```

\loadgidx

Loads a datagidx database.

```
\NewDocumentCommand \loadgidx { 0{} m m }
{%
```

Load database:

```
\DTLread [ format = dbtex ] { #2 }
```

Update the 'datagidx' database. (Assume database is already sorted.)

```
\__datagidx_update_loaded_data:n { \dtllastloadeddb }
\bgroup
  \keys_set_groups:nnn
  { datatool / index } { newgloss }
  { sort = {} , #1 }
  \expandafter\datagidx@newgidx@update\expandafter
  {\dtllastloadeddb}{#3}%
\egroup
```

Set this as the default database:

```
\tl_set_eq:NN
  \__datagidx_default_database_tl
  \dtllastloadeddb
```

Assign labels to this database.

```
\dtlforcolumn{\Label}{\dtllastloadeddb}{Label}%
{%
  \__datagidx_assign_label_db:nn
  { \Label } { \dtllastloadeddb }
}%
}
```

May only be used in the preamble (otherwise the entries will be undefined when their locations are read from the aux file).

```
\@onlypreamble\loadgidx
```

Marker for Used field:

```
\cs_new:Nn \__datagidx_used:n { #1 }
```

Marker for LetterGroup field:

```
\cs_new:Nn \__datagidx_letter_group:n { #1 }
```

Make sure the letter group doesn't expand.

```
\cs_new:Nn \__datagidx_write_letter_group:n
{
  \tl_to_str:n { #1 }
}
```

Marker for Location field:

```
\cs_new:Nn \__datagidx_location:n { \exp_not:n { #1 } }
```

Extract the location from the special markers.

```
\cs_new:Nn \__datagidx_unwrap_location:N
{
  \exp_args:NV
```

```

\l_if_head_eq_meaning:nNT #1
{ \dtlspecialvalue }
{
\group_begin:
\cs_set_eq:NN \__datagidx_location:n \exp_not:n
\cs_set_eq:NN \dtlspecialvalue \use:n
\exp_args:NNNx
\group_end:
\l_set:Nn #1 { #1 }
}
}

```

\datagidx@newgidx The normal behaviour of \newgidx

```

\NewDocumentCommand \datagidx@newgidx { o m m }
{
\bggroup
\IfValueT { #1 }
{

```

NB \keys_set_filter:nnnN is being deprecated in favour of \keys_set_exclude_groups:nnn (l3kernel 2024-01-22).

```

\keys_set_filter:nnnN
{ datatool / index } { general , print-only } { #1 }
\l_datagidx_remainder_tl
\l_if_empty:NF \l_datagidx_remainder_tl
{
\PackageError { datagidx }
{
Invalid ~ \token_to_str:N \newgidx \c_space_tl option(s): ~
\l_to_str:N \l_datagidx_remainder_tl
}
{
The ~ listed ~ option ~ or ~ options ~ can't ~ be ~ passed ~
to ~ \token_to_str:N \newgidx . \MessageBreak
Try ~ \token_to_str:N \DTLsetup
{ index = { \l_to_str:N \l_datagidx_remainder_tl } } ~
or ~ pass ~ the ~ option(s) ~ to ~
\token_to_str:N \printterms \c_space_tl instead
}
}
}
}

```

If no default database has been identified, set the default to this database.

```

\l_if_empty:NT \l__datagidx_default_database_tl
{
\l_gset:Nx \l__datagidx_default_database_tl { #2 }
}
\DTLgnewdb{#2}%
\__datagidx_add_column:nn {#2} {Label}
\__datagidx_add_column:nnn

```

```

    {#2} {Used} { \c_datatool_integer_int }
  \__datagidx_add_column:nn {#2} {Location}
  \__datagidx_add_column:nn {#2} {UnsafeLocation}
  \__datagidx_add_column:nn {#2} {CurrentLocation}
  \__datagidx_add_column:nnn {#2} {FirstId} { \c_datatool_integer_int }
  \__datagidx_add_column:nn {#2} {Name}
  \__datagidx_add_column:nn {#2} {Text}
  \__datagidx_add_column:nn {#2} {Plural}
  \__datagidx_add_column:nn {#2} {Parent}
  \__datagidx_add_column:nn {#2} {Child}
  \__datagidx_add_column:nn {#2} {Description}
  \__datagidx_add_column:nn {#2} {HierSort}
  \__datagidx_add_column:nn {#2} {Sort}
  \__datagidx_add_column:nn {#2} {LetterGroup}
  \__datagidx_add_column:nn {#2} {Symbol}
  \__datagidx_add_column:nn {#2} {Long}
  \__datagidx_add_column:nn {#2} {LongPlural}
  \__datagidx_add_column:nn {#2} {Short}
  \__datagidx_add_column:nn {#2} {ShortPlural}
  \__datagidx_add_column:nn {#2} {See}
  \__datagidx_add_column:nn {#2} {SeeAlso}
  \datagidx@newgidx@update{#2}{#3}%
\egroup
}

```

Assume all columns contain strings.

```

\cs_new:Nn \__datagidx_add_column:nn
{
  \__datagidx_add_column:nnn
  { #1 } { #2 } { \c_datatool_string_int }
}
\cs_new:Nn \__datagidx_add_column:nnn
{
  \__datatool_add_column_with_header:nxxx
  { #1 } { #2 } { \int_eval:n { #3 } } { #2 }
}
Add new fields in the event a pre v3.0 database has been loaded:
\cs_new:Nn \__datagidx_update_loaded_data:n
{
  \datatool_if_has_key:nnF { #1 } { HierSort }
  {
    \__datagidx_add_column:nn { #1 } { HierSort }
  }
  \datatool_if_has_key:nnF { #1 } { LetterGroup }
  {
    \__datagidx_add_column:nn { #1 } { LetterGroup }
  }
  \datatool_if_has_key:nnF { #1 } { UnsafeLocation }
  {

```

```

    \__datagidx_add_column:nn {#1 } { UnsafeLocation }
  }
}

```

`\datagidx@newgidx@update` Update the ‘datagidx’ database.

```

\newcommand*{\datagidx@newgidx@update}[2]{%
  \group_begin:
  \bool_set_true:N \l__datatool_db_global_bool
  \dtlexpandnewvalue
  \DTLnewrow {datagidx}
  \DTLnewdbentry {datagidx} {Glossary}
  { \exp_not:n { #1 } }
  \DTLnewdbentry {datagidx} {Title}
  { \exp_not:n { #2 } }
  \DTLnewdbentry {datagidx} {Heading}
  { \exp_not:V \l__datagidx_heading_tl }
  \DTLnewdbentry{datagidx}{PostHeading}
  { \exp_not:V \l__datagidx_post_heading_tl }
  \DTLnewdbentry {datagidx} {MultiCols}
  { \exp_not:V \l__datagidx_multicols_tl }
  \DTLnewdbentry{datagidx}{Sort}
  { \exp_not:V \l__datagidx_sort_tl }
  \DTLnewdbentry{datagidx}{Style}{\expandonce\datagidx@style}%
  \DTLnewdbentry{datagidx}{ShowGroups}{\expandonce\datagidx@showgroups}%
  \group_end:
}

```

`\printterms@condition` Version 3.0: replaced `\printterms@condition` with a function instead.

```

\cs_new:Npn \__datagidx_filter:T #1 { #1 }

\bool_new:N \l__datagidx_childsort_bool
\bool_set_true:N \l__datagidx_childsort_bool

```

19 General Options

```

\clist_new:N \l__datagidx_styles_clist

```

Define options for use in the `index` setting in `\DTLsetup`:

```

\keys_define:nn { datatool / index }
{

```

The default index database name:

```

  database .tl_set:N =
    \l__datagidx_default_database_tl ,
  database .groups:n = { print-only },

```

Number of columns in the index:

```

  columns .code:n =
    { \DTLgidxSetColumns { #1 } },
  columns .groups:n = { print-only },

```

Symbol width:

```
symbolwidth .dim_set:N =
  \datagidxsymbolwidth ,
symbolwidth .groups:n = { print-only },
```

Synonym:

```
symbol-width .dim_set:N =
  \datagidxsymbolwidth ,
symbol-width .groups:n = { print-only },
```

Location width:

```
locationwidth .dim_set:N =
  \datagidxlocationwidth ,
locationwidth .groups:n = { print-only },
```

Synonym:

```
location-width .dim_set:N =
  \datagidxlocationwidth ,
location-width .groups:n = { print-only },
```

Child style (should the child's name be shown):

```
child .choice: ,
child .groups:n = { print-only },
child / named .code:n =
  { \__datagidx_set_child_style_named: } ,
child / noname .code:n =
  { \__datagidx_set_child_style_noname: } ,
```

Child sort. NB the child entries will be sorted by HierSort by default, along with all the parent entries. This option Governs whether or not `\datagidx@foreachchild` follows the ordering from the database (which will in the sort order, if the database has been sorted.)

```
childsort .bool_set:N = \l__datagidx_childsort_bool ,
childsort .groups:n = { print-only } ,
```

Synonym.

```
child-sort .bool_set:N = \l__datagidx_childsort_bool ,
child-sort .groups:n = { print-only } ,
```

Should a case change be applied to the name?

```
namecase .choice: ,
namecase .groups:n = { print-only },
namecase / nochange .code:n =
  { \let \DTLgidxNameCase \use:n } ,
namecase / uc .code:n =
  { \renewcommand \DTLgidxNameCase [ 1 ] { \text_uppercase:n { ##1 } } } ,
namecase / lc .code:n =
  { \renewcommand \DTLgidxNameCase [ 1 ] { \text_lowercase:n { ##1 } } } ,
namecase / firstuc .code:n =
  { \renewcommand \DTLgidxNameCase [ 1 ] { \xmakefirstuc { ##1 } } } ,
namecase / capitalise .code:n =
  { \renewcommand \DTLgidxNameCase [ 1 ] { \xcapitalisewords { ##1 } } } ,
```

Synonym:

```
name-case .choice: ,
```

```

name-case .groups:n = { print-only },
name-case / nochange .code:n =
  { \let \DTLgidxNameCase \use:n } ,
name-case / uc .code:n =
  { \renewcommand \DTLgidxNameCase [ 1 ] { \text_uppercase:n { ##1 } } } ,
name-case / lc .code:n =
  { \renewcommand \DTLgidxNameCase [ 1 ] { \text_lowercase:n { ##1 } } } ,
name-case / firstuc .code:n =
  { \renewcommand \DTLgidxNameCase [ 1 ] { \xmakefirstuc { ##1 } } } ,
name-case / capitalise .code:n =
  { \renewcommand \DTLgidxNameCase [ 1 ] { \xcapitalisewords { ##1 } } } ,

Font to apply to the name:
namefont .code:n =
  { \renewcommand*\DTLgidxNameFont [ 1 ] { { #1 { ##1 } } } } ,
namefont .groups:n = { print-only },

Synonym:
name-font .code:n =
  { \renewcommand*\DTLgidxNameFont [ 1 ] { { #1 { ##1 } } } } ,
name-font .groups:n = { print-only },

Content to be placed after the name:
postname .code:n =
  { \renewcommand \DTLgidxPostName { #1 } } ,
postname .groups:n = { print-only },

Synonym:
post-name .code:n =
  { \renewcommand \DTLgidxPostName { #1 } } ,
post-name .groups:n = { print-only },

Content to be placed after the description:
postdesc .choice: ,
postdesc / none .code:n =
  { \tl_clear:N \DTLgidxPostDescription } ,
postdesc / dot .code:n =
  { \tl_set:Nn \DTLgidxPostDescription { . } } ,
postdesc .groups:n = { print-only },

Synonym:
post-desc .choice: ,
post-desc / none .code:n =
  { \tl_clear:N \DTLgidxPostDescription } ,
post-desc / dot .code:n =
  { \tl_set:Nn \DTLgidxPostDescription { . } } ,
post-desc .groups:n = { print-only },

Content to be placed before the location:
prelocation .choice: ,
prelocation .groups:n = { print-only },
prelocation / none .code:n =
  { \tl_clear:N \DTLgidxPreLocation } ,
prelocation / enspace .code:n =

```

```

    { \tl_set:Nn \DTLgidXPreLocation { \enspace } } ,
prelocation / space .code:n =
    { \tl_set:Nn \DTLgidXPreLocation { ~ } } ,
prelocation / dotfill .code:n =
    { \tl_set:Nn \DTLgidXPreLocation { \dotfill } } ,
prelocation / hfill .code:n =
    { \tl_set:Nn \DTLgidXPreLocation { \hfill } } ,

```

Synonym:

```

pre-location .choice: ,
pre-location .groups:n = { print-only },
pre-location / none .code:n =
    { \tl_clear:N \DTLgidXPreLocation } ,
pre-location / enspace .code:n =
    { \tl_set:Nn \DTLgidXPreLocation { \enspace } } ,
pre-location / space .code:n =
    { \tl_set:Nn \DTLgidXPreLocation { ~ } } ,
pre-location / dotfill .code:n =
    { \tl_set:Nn \DTLgidXPreLocation { \dotfill } } ,
pre-location / hfill .code:n =
    { \tl_set:Nn \DTLgidXPreLocation { \hfill } } ,

```

Location style (don't show, only show first, or show list):

```

location .choice: ,
location .groups:n = { print-only },
location / hide .code:n =
    { \tl_clear:N \DTLgidXLocation },
location / list .code:n =
    { \tl_set:Nn \DTLgidXLocation { \dtldolocationlist } },
location / first .code:n =
    { \tl_set:Nn \DTLgidXLocation { \dtldofirstlocation } },

```

Cross-reference (see) style:

```

see .choice: ,
see .groups:n = { print-only },
see / comma .code:n =
    {
    \renewcommand \DTLgidXSee
    {
    \datatool_if_null_or_empty:NF \See
    {
    , ~ \DTLgidXFormatSee { \seename } { \See }
    }
    }
    } ,
see / brackets .code:n =
    {
    \renewcommand \DTLgidXSee
    {
    \datatool_if_null_or_empty:NF \See
    {
    \space ( \DTLgidXFormatSee { \seename } { \See } )
    }
    }
    }

```

```

    }
  }
},
see / dot .code:n =
{
  \renewcommand \DTLgidxSee
  {
    \datatool_if_null_or_empty:NF \See
    {
      . ~
      \DTLgidxFormatSee
      { \xmakefirstuc { \seename } } { \See }
    }
  }
},
see / space .code:n =
{
  \renewcommand \DTLgidxSee
  {
    \datatool_if_null_or_empty:NF \See
    {
      \space
      \DTLgidxFormatSee { \seename } { \See }
    }
  }
},
see / nosep .code:n =
{
  \renewcommand \DTLgidxSee
  {
    \datatool_if_null_or_empty:NF \See
    {
      \DTLgidxFormatSee { \seename } { \See }
    }
  }
},
see / semicolon .code:n =
{
  \renewcommand \DTLgidxSee
  {
    \datatool_if_null_or_empty:NF \See
    {
      ; ~ \DTLgidxFormatSee { \seename } { \See }
    }
  }
},
see / location .code:n =
{
  \renewcommand \DTLgidxSee
  {

```

```

        \datatool_if_null_or_empty:NF \See
        {
          \DTLgidxPreLocation
          \DTLgidxFormatSee { \seename } { \See }
        }
      } ,

```

Style of the symbol and description:

```

symboldesc .choice: ,
symboldesc .groups:n = { print-only },
symboldesc / symbol .code:n =
{
  \__datagix_set_symbol_only:
} ,
symboldesc / desc .code:n =
{
  \__datagix_set_desc_only:
} ,
symboldesc / (symbol) ~ desc .code:n =
{
  \__datagix_set_symbol_paren_desc:
} ,
symboldesc / desc ~ (symbol) .code:n =
{
  \__datagix_set_desc_symbol_paren:
} ,
symboldesc / symbol ~ desc .code:n =
{
  \__datagix_set_symbol_desc:
} ,
symboldesc / desc ~ symbol .code:n =
{
  \__datagix_set_desc_symbol:
} ,

```

Synonym:

```

symbol-desc .choice: ,
symbol-desc .groups:n = { print-only },
symbol-desc / symbol .code:n =
{
  \__datagix_set_symbol_only:
} ,
symbol-desc / desc .code:n =
{
  \__datagix_set_desc_only:
} ,
symbol-desc / (symbol) ~ desc .code:n =
{
  \__datagix_set_symbol_paren_desc:
} ,

```

```

symbol-desc / desc ~ (symbol) .code:n =
{
  \__datagix_set_desc_symbol_paren:
},
symbol-desc / symbol ~ desc .code:n =
{
  \__datagix_set_symbol_desc:
},
symbol-desc / desc ~ symbol .code:n =
{
  \__datagix_set_desc_symbol:
},
Compositor:
compositor .tl_set:N = \l__datagidx_compositor_tl ,
compositor .value_required:n = true ,
compositor .groups:n = { general } ,
Counter:
counter .code:n =
{
  \__datagidx_set_counter:n { #1 }
},
counter .value_required:n = true ,
counter .groups:n = { general } ,
Switch warnings on or off:
warn .bool_set:N = \l__datagidx_warn_bool ,
warn .groups:n = { general } ,
Index heading:
heading .code:n =
{
  \clist_put_right:Nn \l__datagidx_styles_clist
  { heading = { #1 } }
  \tl_set:Nn \l__datagidx_heading_tl { #1 }
},
heading .groups:n = { newgloss, print } ,
After index heading:
postheading .code:n =
{
  \clist_put_right:Nn \l__datagidx_styles_clist
  { postheading = { #1 } }
  \tl_set:Nn \l__datagidx_post_heading_tl { #1 }
},
postheading .groups:n = { newgloss, print } ,
Synonym:
post-heading .code:n =
{
  \clist_put_right:Nn \l__datagidx_styles_clist
  { postheading = { #1 } }
  \tl_set:Nn \l__datagidx_post_heading_tl { #1 }
}

```

```

    },
    post-heading .groups:n = { newgloss, print } ,
Balance columns:
    balance .choice: ,
    balance .groups:n = { newgloss, print } ,
    balance / true .code:n =
    {
        \clist_put_right:Nn \l__datagidx_styles_clist
        { balance = true }
        \tl_set:Nn \l__datagidx_multicols_tl { multicols }
        \datagidxbalancetrue
    } ,
    balance / false .code:n =
    {
        \clist_put_right:Nn \l__datagidx_styles_clist
        { balance = false }
        \tl_set:Nn \l__datagidx_multicols_tl { multicols* }
        \datagidxbalancefalse
    } ,
    balance .default:n = { true } ,
Sort. The value should be the code to sort the glossary/index database. The database
should be referenced with \DTLgidxCurrentdb:
    sort .code:n =
    {
        \clist_put_right:Nn \l__datagidx_styles_clist
        { sort = { #1 } }
        \tl_set:Nn \l__datagidx_sort_tl { #1 }
    } ,
    sort .groups:n = { newgloss, print } ,
Style:
    style .code:n =
    {
        \clist_put_right:Nn \l__datagidx_styles_clist
        { style = { #1 } }
        \tl_set:Nn \datagidx@style { #1 }
    } ,
    style .groups:n = { newgloss, print } ,
Show groups:
    showgroups .choice: ,
    showgroups .groups:n = { newgloss, print } ,
    showgroups / true .code:n =
    {
        \clist_put_right:Nn \l__datagidx_styles_clist
        { showgroups = true }
        \tl_set:Nn \datagidx@showgroups { true }
    } ,
    showgroups / false .code:n =
    {

```

```

\clist_put_right:Nn \l__datagidx_styles_clist
{ showgroups = false }
\tl_set:Nn \datagidx@showgroups { false }
} ,
showgroups .default:n = { true } ,

```

Synonym:

```

show-groups .choice: ,
show-groups .groups:n = { newgloss, print } ,
show-groups / true .code:n =
{
\clist_put_right:Nn \l__datagidx_styles_clist
{ showgroups = true }
\tl_set:Nn \datagidx@showgroups { true }
} ,
show-groups / false .code:n =
{
\clist_put_right:Nn \l__datagidx_styles_clist
{ showgroups = false }
\tl_set:Nn \datagidx@showgroups { false }
} ,
show-groups .default:n = { true } ,

```

Condition:

```

condition .code:n =
{
\cs_set:Npn \__datagidx_filter:T ##1
{
\ifthenelse { #1 } { ##1 } { }
}
} ,
condition .groups:n = { print-only } ,
include-if .cs_set:Np = \__datagidx_filter:T #1,
include-if .groups:n = { print-only } ,
include-if-fn .code:n =
{
\cs_set_eq:NN \__datagidx_filter:T #1
},
include-if-fn .groups:n = { print-only } ,
}

```

NB package options draft, final and optimize not available.

Allow these keys to be set in `\DTLsetup{index={...}}`

```

\keys_define:nn { datatool }
{
index .code:n = { \keys_set:nn { datatool / index } { #1 } }
}

```

Used to store filtered settings:

```

\tl_new:N \l__datagidx_remainder_tl

```

20 Defining New Terms

20.1 Options

Options for `\newterm`:

The internal commands all need to be in the form `\l__datagidx_term_⟨key⟩_tl` to work with `\newtermfield`

`\newterm@label` Version 3.0: replaced `\newterm@label` with:
`\tl_new:N \l__datagidx_term_label_tl`

`\newterm@parent` Version 3.0: replaced `\newterm@parent` with:
`\tl_new:N \l__datagidx_term_parent_tl`

`\newterm@name` Version 3.0: replaced `\newterm@name` with: This doesn't have a corresponding option since the name is the mandatory argument of `\newterm`:
`\tl_new:N \l__datagidx_term_name_tl`

`\newterm@text` Version 3.0: replaced `\newterm@text` with:
`\tl_new:N \l__datagidx_term_text_tl`

`\newterm@description` Version 3.0: replaced `\newterm@description` with:
`\tl_new:N \l__datagidx_term_description_tl`

`\newterm@plural` Version 3.0: replaced `\newterm@plural` with:
`\tl_new:N \l__datagidx_term_plural_tl`

`\newterm@sort` Version 3.0: replaced `\newterm@sort` with:
`\tl_new:N \l__datagidx_term_sort_tl`

`\newterm@symbol` Version 3.0: replaced `\newterm@symbol` with:
`\tl_new:N \l__datagidx_term_symbol_tl`

`\newterm@database` Version 3.0: replaced `\newterm@database` with:
`\tl_new:N \l__datagidx_term_database_tl`

`\newterm@long` Version 3.0: replaced `\newterm@long` with:
`\tl_new:N \l__datagidx_term_long_tl`

`\newterm@short` Version 3.0: replaced `\newterm@short` with:
`\tl_new:N \l__datagidx_term_short_tl`

`\newterm@longplural` Version 3.0: replaced `\newterm@longplural` with:
`\tl_new:N \l__datagidx_term_longplural_tl`

`\newterm@shortplural` Version 3.0: replaced `\newterm@shortplural` with:
`\tl_new:N \l__datagidx_term_shortplural_tl`

`\newterm@see` “see” should not be used with a location list. If you have a location list and want a cross-reference use “see also” instead. Version 3.0: replaced `\newterm@see` with:

```
\tl_new:N \l__datagidx_term_see_tl
```

`\newterm@seealso` “see also” should be used with a location list (or with child entries with location lists). If an entry has no location list and not child entries use “see” instead. Version 3.0: replaced `\newterm@seealso` with:

```
\tl_new:N \l__datagidx_term_seealso_tl
```

The following commands allow users to, say, specify the name as $\langle name \rangle \backslash g l s a d d \{ \langle other label \rangle \}$ without having to specify the label when defining a term. Assign the label token list variable:

```
\cs_new:Nn \__datagidx_create_label:n
{
  \group_begin:
    \cs_set_eq:NN \glsadd \DTLgidxGobble
```

Strip common formatting commands. NB v3.0: `\text_purify:n` should now deal with these.

```
\cs_set_eq:NN \MakeUppercase \DTLgidxNoFormat
\cs_set_eq:NN \MakeTextUppercase \DTLgidxNoFormat
\cs_set_eq:NN \MakeLowercase \DTLgidxNoFormat
\cs_set_eq:NN \MakeTextLowercase \DTLgidxNoFormat
\cs_set_eq:NN \acronymfont \DTLgidxNoFormat
\cs_set_eq:NN \textrm \DTLgidxNoFormat
\cs_set_eq:NN \texttt \DTLgidxNoFormat
\cs_set_eq:NN \textsf \DTLgidxNoFormat
\cs_set_eq:NN \textsc \DTLgidxNoFormat
\cs_set_eq:NN \textbf \DTLgidxNoFormat
\cs_set_eq:NN \textmd \DTLgidxNoFormat
\cs_set_eq:NN \textit \DTLgidxNoFormat
\cs_set_eq:NN \textsl \DTLgidxNoFormat
\cs_set_eq:NN \emph \DTLgidxNoFormat
\cs_set_eq:NN \textsuperscript \DTLgidxNoFormat
```

Convert character commands like `\&`.

```
\datagidxconvertchars
```

Strip `\ensuremath`.

```
\cs_set_eq:NN \ensuremath \DTLgidxNoFormat
```

Ensure that inversions are dealt with for the label.

```
\cs_set_eq:NN \DTLgidxParen \use_none:n
\cs_set_eq:NN \DTLgidxName \use_ii:n
\cs_set_eq:NN \DTLgidxPlace \datagidx@invert
\cs_set_eq:NN \DTLgidxSubject \datagidx@invert
\cs_set_eq:NN \DTLgidxOffice \use_ii:n
\cs_set_eq:NN \DTLgidxParticle \datagidx@bothoftwo
\cs_set_eq:NN \__datagidx_punc:n \use_none:n
```

Convert Greek maths (such as `\alpha`) to text.

```
\datagidxwordifygreek
```

Allow user to hook into this.

```
\newtermlabelhook
```

Using protected expansion first allows for the localised change to `\ensuremath`:

```
\protected@edef \l__datagidx_term_label_tl { #1 }
```

Strip punctuation characters that are likely to cause a problem for syntax parsing.

```
\regex_replace_all:nnN
  { [,=] } { } \l__datagidx_term_label_tl
\l_set:Nx \l__datagidx_term_label_tl
  {
  \text_purify:n { \l__datagidx_term_label_tl }
  }
\exp_args:NNNV
\group_end:
  \l_set:Nn
    \l__datagidx_term_label_tl
    \l__datagidx_term_label_tl
}
```

Assign the sort token list variable:

```
\cs_new:Nn \__datagidx_create_sort:n
{
  \group_begin:
    \cs_set_eq:NN \glsadd \use_none:n
```

Strip common formatting commands. NB v3.0: `\text_purify:n` should now deal with these.

```
\cs_set_eq:NN \MakeUppercase \DTLgidxNoFormat
\cs_set_eq:NN \MakeTextUppercase \DTLgidxNoFormat
\cs_set_eq:NN \MakeLowercase \DTLgidxNoFormat
\cs_set_eq:NN \MakeTextLowercase \DTLgidxNoFormat
\cs_set_eq:NN \acronymfont \DTLgidxNoFormat
\cs_set_eq:NN \textrm \DTLgidxNoFormat
\cs_set_eq:NN \texttt \DTLgidxNoFormat
\cs_set_eq:NN \textsf \DTLgidxNoFormat
\cs_set_eq:NN \textsc \DTLgidxNoFormat
\cs_set_eq:NN \textbf \DTLgidxNoFormat
\cs_set_eq:NN \textmd \DTLgidxNoFormat
\cs_set_eq:NN \textit \DTLgidxNoFormat
\cs_set_eq:NN \textsl \DTLgidxNoFormat
\cs_set_eq:NN \emph \DTLgidxNoFormat
\cs_set_eq:NN \textsuperscript \DTLgidxNoFormat
```

Convert character commands like `\&`.

```
\datagidxconvertchars
```

Strip `\ensuremath`.

```
\cs_set_eq:NN \ensuremath \DTLgidxNoFormat
```

These commands behave differently for the sort key:

```
\cs_set_eq:NN \__datagidx_punc:n \exp_not:n
\cs_set_eq:NN \DTLgidxName \datagidx@person
\cs_set_eq:NN \DTLgidxPlace \datagidx@place
\cs_set_eq:NN \DTLgidxSubject \datagidx@subject
\cs_set_eq:NN \DTLgidxOffice \datagidx@person
\cs_set_eq:NN \DTLgidxParen \datagidx@paren
\cs_set_eq:NN \DTLgidxMac \datagidx@mac
\cs_set_eq:NN \DTLgidxSaint \datagidx@saint
\cs_set_eq:NN \DTLgidxIgnore \@gobble
\cs_set_eq:NN \DTLgidxRank \datagidx@rank
\cs_set_eq:NN \DTLgidxParticle \datagidx@particle
\cs_set_eq:NN \DTLgidxNameNum \datagidx@namenum
```

Convert Greek maths (such as α) to text.

```
\datagidxwordifygreek
```

Allow user to hook into this.

```
\newtermsorthook
```

Using protected expansion first allows for the localised change to \ensuremath :

```
\protected@edef \__datagidx_term_sort_tl { #1 }
\exp_args:NNNV
\group_end:
\tl_set:Nn
  \__datagidx_term_sort_tl
  \__datagidx_term_sort_tl
}
```

Variable to store hierarchical sort value.

```
\tl_new:N \__datagidx_term_hiersort_tl
\keys_define:nn { datatool / index / newterm }
{
```

Labels:

```
  database .code:n =
  {
    \tl_set:Nx \__datagidx_term_database_tl
      { #1 }
  },
  label .code:n =
  {
    \__datagidx_create_label:n { #1 }
  },
  parent .code:n =
  {
    \tl_set:Nx \__datagidx_term_parent_tl
      { #1 }
  },
```

Token lists:

```
text .code:n =
  {
    \tl_set:Nn \l__datagidx_term_text_tl { #1 }
    \tl_if_eq:NnT \l__datagidx_term_plural_tl { \c_novalue_tl }
    {
      \tl_set:Nn \l__datagidx_term_plural_tl { #1 s }
    }
  } ,
description .tl_set:N = \l__datagidx_term_description_tl ,
plural .tl_set:N = \l__datagidx_term_plural_tl ,
sort .code:n =
  {
    \__datagidx_create_sort:n { #1 }
  } ,
symbol .tl_set:N = \l__datagidx_term_symbol_tl ,
long .code:n =
  {
    \tl_set:Nn \l__datagidx_term_long_tl { #1 }
    \tl_if_eq:NnT \l__datagidx_term_longplural_tl { \c_novalue_tl }
    {
      \tl_set:Nn \l__datagidx_term_longplural_tl { #1 s }
    }
  } ,
short .code:n =
  {
    \tl_set:Nn \l__datagidx_term_short_tl { #1 }
    \tl_if_eq:NnT \l__datagidx_term_shortplural_tl { \c_novalue_tl }
    {
      \tl_set:Nn \l__datagidx_term_shortplural_tl { #1 s }
    }
  } ,
longplural .tl_set:N = \l__datagidx_term_longplural_tl ,
shortplural .tl_set:N = \l__datagidx_term_shortplural_tl ,
see .tl_set:N = \l__datagidx_term_see_tl ,
seealso .tl_set:N = \l__datagidx_term_seealso_tl ,
}
```

20.2 New Terms

`\newterm@defaultshook` Version 3.0: replaced `\newterm@defaultshook` with:
`\tl_new:N \g__datagidx_newterm_defaults_tl`

`\newterm@extrafields` Version 3.0: replaced `\newterm@extrafields` with
`\tl_new:N \g__datagidx_extra_fields_tl`

`\DTLgidxAssignList` Assignment list used by `\printterms`
`\newcommand*{\DTLgidxAssignList}{`
`\Name=Name,`

```

\Description=Description,
\Used=Used,
\Symbol=Symbol,
\Long=Long,
\Short=Short,
\LongPlural=LongPlural,
\ShortPlural=ShortPlural,
\Location=Location,
\See=See,
\SeeAlso=SeeAlso,
\Text=Text,
\Plural=Plural,
\CurrentLocation=CurrentLocation,
\Label=Label,
\Parent=Parent,
\Children=Child,
\FirstId=FirstId,
\HierSort=HierSort,
\Sort=Sort,
\datagidxcurrentgroup=LetterGroup
}

```

`\datagidxtermkeys` Keys defined for `\newterm` corresponding to fields.

```
\newcommand*{\datagidxtermkeys}{}

```

Access keys corresponding to given fields.

Syntax: `{\langle column key \rangle}{\langle term key \rangle}`

Add term key to list and define mapping:

```

\cs_new:Nn \__datagidx_add_field:nn
{
  \clist_gput_right:Nn \datagidxtermkeys { #2 }
  \tl_gset:cn { g__datagidx_fieldkey_ #1 } { #2 }
  \tl_clear_new:c { l__datagidx_term_ #2 _tl }
}

```

Syntax: `{\langle column key \rangle}{\langle term key \rangle}{\langle default val \rangle}` Add term key to list, define mapping and provide the key as an option:

```

\cs_new:Nn \__datagidx_add_field_option:nnnN
{
  \__datagidx_add_field:nn { #1 } { #2 }
  \keys_define:nn { datatool / index / newterm }
  {
    #2 .tl_set:N = #4
  }
  \tl_put_right:Nn \g__datagidx_newterm_defaults_tl
  {
    \tl_if_eq:NnT #4 { \c_novalue_tl }
    {
      \tl_set:Nx #4 { #3 }
    }
  }
}

```

```

    }
  }
  \cs_generate_variant:Nn
  \__datagidx_add_field_option:nnnN
  { xxnc }

```

Predefined fields:

```

\__datagidx_add_field:nn { Name } { name }
\__datagidx_add_field:nn { Description } { description }
\__datagidx_add_field:nn { Symbol } { symbol }
\__datagidx_add_field:nn { Long } { long }
\__datagidx_add_field:nn { Short } { short }
\__datagidx_add_field:nn { See } { see }
\__datagidx_add_field:nn { SeeAlso } { seealso }
\__datagidx_add_field:nn { Text } { text }
\__datagidx_add_field:nn { Plural } { plural }
\__datagidx_add_field:nn { Label } { label }
\__datagidx_add_field:nn { Parent } { parent }
\__datagidx_add_field:nn { Sort } { sort }

```

```

\newtermaddfield[<db list>]{<column key>
[<placeholder cs>]{<new term
key>}[<data type>]{<default value>}

```

\newtermaddfield

The default value may contain \field{<key>} to get the value of another field.

```

\NewDocumentCommand \newtermaddfield
  { 0 } m o m O { \c_datatool_string_int } m }
{
  \__datagidx_set_label:Nn \l__datagidx_label_tl { #2 }

```

If optional argument not specified, iterate over all defined glossaries/indices.

```

\tl_if_empty:nTF { #1 }
{
  \dtlforcolumn
  \l__datagidx_database_tl { datagidx } { Glossary }
  {
    \datatool_if_has_key:nnF
    { \l__datagidx_database_tl } { \l__datagidx_label_tl }
    {
      \__datagidx_add_column:nnn
      { \l__datagidx_database_tl }
      { \l__datagidx_label_tl }
      { #5 }
    }
  }
}
}
{
  \clist_map_inline:nn { #1 }
  {

```

```

\datatool_if_has_key:nnF
  { ##1 } { \l__datagidx_label_tl }
  {
    \__datagidx_add_column:nnn
      { ##1 }
      { \l__datagidx_label_tl }
      { #5 }
  }
}
}
\__datagidx_add_field_option:xxnc
  { \l__datagidx_label_tl } { #4 } { #6 }
  { l__datagidx_term_#4_tl }
\__datagidx_append_extra_field:cV
  { l__datagidx_term_#4_tl }
  \l__datagidx_label_tl
\IfValueTF { #3 }
{
  \tl_if_blank:n { #3 }
  {
    \__datagidx_add_placeholder:cV
      { \l__datagidx_label_tl }
      \l__datagidx_label_tl
  }
  {
    \__datagidx_add_placeholder:NV
      #3
      \l__datagidx_label_tl
  }
}
}
{
  \__datagidx_add_placeholder:cV
    { \l__datagidx_label_tl }
    \l__datagidx_label_tl
}
}
}

```

Append to extra fields hook.

```

\cs_new:Nn \__datagidx_append_extra_field:Nn
  {
    \tl_gput_right:Nn \g__datagidx_extra_fields_tl
      {
        \__datagidx_append_element_with_check:Nn
          #1 { #2 }
      }
  }
\cs_generate_variant:Nn
  \__datagidx_append_extra_field:Nn
  { cV }

```

```

\cs_new:Nn \__datagidx_add_placeholder:Nn
{
  \tl_if_exist:NTF #1
  {
    {
      \PackageError { datagidx }
      {
        \token_to_str: \newtermaddfield : ~ placeholder ~
        \token_to_str #1 \c_space_tl ~ already ~ exists
      }
    }
    {
      Choose ~ a ~ different ~ command ~ name ~ in
      \token_to_str: \newtermaddfield [ ... ]
      { #2 } [ \token_to_str #1 ] { ... }
    }
  }
  {
    \clist_gput_right:Nn \DTLgidxAssignList
    {
      #1 = #2
    }
    \tl_gput_right:Nn \datagidxgetchildfields
    {
      \datatool_if_has_key:nnTF
      { \DTLgidxCurrentdb } { #2 }
      {
        \dtlgetentryfromcurrentrow { #1 }
        { \dtlcolumnindex { \DTLgidxCurrentdb } { #2 } }
      }
      {
        \tl_set_eq:NN #1 \dtlnovalue
      }
    }
  }
}
\cs_generate_variant:Nn \__datagidx_add_placeholder:Nn
{ cn, cV, NV }

```

\newtermlabelhook Hook used to provide local redefinitions to adjust the label.

```
\newcommand*{\newtermlabelhook}{}
```

\newtermsorthook Hook used to provide local redefinitions to adjust the sort.

```
\newcommand*{\newtermsorthook}{}
```

\DTLgidxNoFormat

```
\newcommand*{\DTLgidxNoFormat}[1]{#1}
```

\DTLgidxGobble

```
\newcommand*{\DTLgidxGobble}[1]{}

```

`\DTLgidxStripBackslash` Argument must be a control sequence. This is stringified and the backslash is removed).
`\newcommand*\DTLgidxStripBackslash}[1]{ \cs_to_str:N #1 }`

`\DTLgidxName`

`\DTLgidxName{\langle forenames \rangle}{\langle surname \rangle}`

How to format a person's name in the text.

`\newcommand*\DTLgidxName}[2]{ #1 \c_space_tl #2 }`

`\DTLgidxNameNum`

`\DTLgidxNameNum{\langle n \rangle}`

The argument $\langle n \rangle$ should be a number applied to a name (e.g. James₁`\DTLgidxNameNum1`). This is converted to a two-digit number for sorting but a Roman numeral for the label and in the text.

`\newcommand*\DTLgidxNameNum}[1]{ \@Roman{#1} }`

`\datagidx@namenum` Conversion for sort key.

`\newcommand*\datagidx@namenum}[1]{ \two@digits{#1} }`

`\DTLgidxPlace`

`\DTLgidxPlace{\langle country \rangle}{\langle town/city \rangle}`

How to format a place in the text.

`\newcommand*\DTLgidxPlace}[2]{ #2 }`

`\DTLgidxSubject`

`\DTLgidxSubject{\langle main \rangle}{\langle category \rangle}`

How to format a subject in the text. Ignore the main part in the text.

`\newcommand*\DTLgidxSubject}[2]{ #2 }`

`\DTLgidxOffice`

`\DTLgidxOffice{\langle office \rangle}{\langle name \rangle}`

Put the office in parentheses in the document text.

`\newcommand*\DTLgidxOffice}[2]{ #2 ~ (#1) }`

`\DTLgidxIgnore` Show argument in document text, but disregard in the sort and label.

`\newcommand*\DTLgidxIgnore}[1]{ #1 }`

`\DTLgidxMac`

`\DTLgidxMac{\langle text \rangle}`

In the document, just does *<text>*, but gets converted to “Mac” in the sort key. (Unless overridden by the user.)

```
\newcommand*\DTLgidxMac}[1]{#1}
```

`\datagidx@mac` `\DTLgidxMac` gets temporarily redefined to `\datagidx@mac` when constructing the sort key.

```
\newcommand*\datagidx@mac}[1]{Mac}
```

`\DTLgidxSaint`

```
\DTLgidxSaint{<text>}
```

In the document, just does *<text>*, but gets converted to “Saint” in the sort key. (Unless overridden by the user.)

```
\newcommand*\DTLgidxSaint}[1]{#1}
```

`\datagidx@saint` `\DTLgidxMac` gets temporarily redefined to `\datagidx@saint` when constructing the sort key.

```
\newcommand*\datagidx@saint}[1]{Saint}
```

```
\ExplSyntaxOff
```

`\DTLgidxRank`

```
\DTLgidxRank{<rank>}{<forenames>}
```

A person’s title, rank or sanctity should be ignored when sorting. This has a non-breakable space separator.

```
\newcommand*\DTLgidxRank}[2]{#1~#2}
```

`\datagidx@rank` `\DTLgidxRank` gets temporarily redefined to `\datagidx@rank` when constructing the sort key. An extra dot is added to the end to ensure names without a rank are sorted before identical names with a rank.

```
\newcommand*\datagidx@rank}[2]{#2.}
```

`\DTLgidxParticle`

```
\DTLgidxParticle{<particle>}{<surname>}
```

A particle such as “of”, “de” or “von” should be ignored when sorting. This has a non-breakable space separator.

```
\newcommand*\DTLgidxParticle}[2]{#1~#2}
```

```
\ExplSyntaxOn
```

`\datagidx@particle` `\DTLgidxParticle` gets temporarily redefined to `\datagidx@particle` when constructing the sort key. An extra dot is added to the end to ensure names without a particle are sorted before identical names with a particle.

```
\newcommand*\datagidx@particle}[2]{#2.}
```

`\datagidx@bothoftwo`
`\newcommand*\datagidx@bothoftwo}[2]{#1#2}`
`\cs_new:Nn __datagidx_punc:n { #1 }`

`\datagidx@person` Used when constructing the sort key for a name.
`\newcommand*\datagidx@person}[2]{`
`#2 __datagidx_punc:n { \datatoolpersoncomma } #1`
`}`

`\datagidx@place` Used when constructing the sort key for a place.
`\newcommand*\datagidx@place}[2]{`
`#2 __datagidx_punc:n { \datatoolplacecomma } #1`
`}`

`\datagidx@subject` Used when constructing the sort key for a place.
`\newcommand*\datagidx@subject}[2]{`
`#2 __datagidx_punc:n { \datatoolsubjectcomma } #1`
`}`

`\datagidx@paren` Used when constructing the sort key for a parenthesis.
`\newcommand*\datagidx@paren}[1]{`
`__datagidx_punc:n { \datatoolparenstart } #1`
`}`

`\datagidx@invert`
`\newcommand*\datagidx@invert}[2]{`
`#2 __datagidx_punc:n { , } ~ #1`
`}`

`\DTLgidxParen` Parenthetical material.
`\newcommand*\DTLgidxParen}[1]{ \c_space_tl (#1) }`

`\datagidxwordifygreek` Convert commands like `\alpha` into words for indexing and labelling purposes.
`\newcommand*\datagidxwordifygreek}{%`
`\def\alpha{alpha}%`
`\def\beta{beta}%`
`\def\gamma{gamma}%`
`\def\delta{delta}%`
`\def\epsilon{epsilon}%`
`\def\varepsilon{epsilon}%`
`\def\zeta{zeta}%`
`\def\eta{eta}%`
`\def\theta{theta}%`
`\def\vartheta{theta}%`
`\def\iota{iota}%`
`\def\kappa{kappa}%`
`\def\lambda{lambda}%`
`\def\mu{mu}%`

```

\def\nu{nu}%
\def\xi{xi}%
\def\pi{pi}%
\def\varpi{pi}%
\def\rho{rho}%
\def\varrho{rho}%
\def\sigma{sigma}%
\def\varsigma{sigma}%
\def\tau{tau}%
\def\upsilon{upsilon}%
\def\phi{phi}%
\def\varphi{phi}%
\def\chi{chi}%
\def\psi{psi}%
\def\omega{omega}%
\def\Gamma{Gamma}%
\def\Delta{Delta}%
\def\Theta{Theta}%
\def\Lambda{Lambda}%
\def\Xi{Xi}%
\def\Pi{Pi}%
\def\Sigma{Sigma}%
\def\Upsilon{Upsilon}%
\def\Phi{Phi}%
\def\Psi{Psi}%
\def\Omega{Omega}%
}

```

`\datagidxextendedtoascii` Convert commands like `\aa` into the closest ASCII equivalent. Version 3.0: Deprecated (use localisation)

```

\newcommand{\datagidxextendedtoascii}{%
\def\AE{AE}%
\def\ae{ae}%
\def\OE{OE}%
\def\oe{oe}%
\def\AA{AA}%
\def\aa{aa}%
\def\L{L}%
\def\l{l}%
\def\O{O}%
\def\o{o}%
\def\SS{SS}%
\def\ss{ss}%
\def\th{th}%
\def\TH{TH}%
\def\dh{dh}%
\def\DH{DH}%
}

```

```
\ExplSyntaxOff
```

`\datagidxconvertchars` Convert commands like `\&`. This can mostly be done with the new kernel commands and v3.0 localisation support but maintained for backward compatibility.

```
\newcommand*{\datagidxconvertchars}{%
  \let~\space
  \ifdef\andname
  {%
    \let\&\andname
  }%
  {%
    \def\&{\expandafter\@gobble\string\&}%
  }%
  \def\_ {\string_}%
  \def\$ {\string$}%
  \def\# {\expandafter\@gobble\string\#}%
  \def\% {\expandafter\@gobble\string\}%
  \def\{ {\expandafter\@gobble\string\{}%
  \def\} {\expandafter\@gobble\string\}%
}

\ExplSyntaxOn
```

`\datagidxstripaccents` Strip accents so they don't interfere with the label and sort. If you want to write your own comparison handler macro, you'll need to redefine this if you want accented letters to be sorted differently from the unaccented version. This command should only be used within a scope. Need to test kernel version. The new 2019/10/01 version has a different definition of `\UTFviii@two@octets` which won't expand UTF-8 characters to `\IeC` in the required context. (This is really useful if you want extended characters in labels but not if they need to be stripped.) If you don't want accents stripped then redefine `\datagidxstripaccents` to do nothing.

Version 3.0: deprecated. This may not work with modern L^AT_EX kernels.

```
\newcommand*{\datagidxstripaccents}{%
  \PackageWarning { datagidx }
  {
    \token_to_str:N \datagidxstripaccents \c_space_tl ~
    is ~ deprecated
  }
}
```

These redefinitions will only work with `\edef` or `\xdef`:

```
\let\add@accent@\@secondoftwo
\let\@text@composite@\@secondoftwo
\let\@tabacckludge@\@secondoftwo
```

The following are need with `\protected@edef` or `\protected\xdef`:

```
\expandafter\def\csname \encodingdefault-cmd\endcsname##1##2##3{##3}%
\expandafter\def\csname OT1-cmd\endcsname##1##2##3{##3}%
\expandafter\def\csname T1-cmd\endcsname##1##2##3{##3}%
\expandafter\def\csname PD1-cmd\endcsname##1##2##3{##3}%
\def\IeC##1{\@gobbletwo##1}%
\let\UTFviii@two@octets\UTFviii@two@octets@combine
}%
```

```
\newterm[options]name
```

\newterm

Defaults to normal behaviour.

```
\providecommand{\newterm}{\datagidx@newterm}
```

May only be used in the preamble. (Terms must be defined before the aux file is read.)

```
\@onlypreamble\newterm
```

Set `\l__datagidx_term_label_tl` to the given label:

```
\cs_new:Nn \__datagidx_set_label:n
{
  \__datagidx_set_label:Nn
  \l__datagidx_term_label_tl { #1 }
}
\cs_new:Nn \__datagidx_set_label:Nn
{
  \tl_set:Nx #1 { \text_purify:n { #2 } }
}
```

\datagidx@setfieldvalues Syntax: `{options}{name}`

Sets the values for all the field.

Version 3.0: replaced `\datagidx@setfieldvalues` with:

```
\cs_new:Nn \__datagidx_set_field_values:nn
{
```

Initialise all token list variables to null to begin with:

```
\clist_map_inline:Nn \datagidxtermkeys
{
  \tl_set:cn { l__datagidx_term_ ##1 _ tl } { \c_novalue_tl }
}
```

Now set non-null defaults.

```
\tl_set:Nx \l__datagidx_term_database_tl
{ \l__datagidx_default_database_tl }
\tl_clear:N \l__datagidx_term_parent_tl
```

Predefined field values:

```
\tl_set:Nn \l__datagidx_term_name_tl { #2 }
\tl_set:Nn \l__datagidx_term_text_tl { #2 }
\tl_clear:N \l__datagidx_term_description_tl
\tl_clear:N \l__datagidx_term_symbol_tl
\tl_set:Nn \l__datagidx_term_short_tl { #2 }
\tl_set:Nn \l__datagidx_term_long_tl { #2 }
\tl_clear:N \l__datagidx_term_see_tl
\tl_clear:N \l__datagidx_term_seealso_tl
```

Assign values given in optional argument.

```
\keys_set:nn { datatool / index / newterm } { #1 }
```

Allow hook to access other fields.

```
\cs_set_eq:NN \__datagidx_org_field:n \field
\def \field ##1
  { \exp_not:v { l__datagidx_term_ ##1 _tl } }
```

Hook to make it easier to add extra fields.

```
\g__datagidx_newterm_defaults_tl
\let \field \__datagidx_org_field:n
```

Set label if not provided in the options:

```
\tl_if_eq:NnT \l__datagidx_term_label_tl { \c_novalue_tl }
{
  \__datagidx_create_label:n { #2 }
}
\exp_args:NV \tl_if_blank:nT \l__datagidx_term_label_tl
{
  \PackageError { datagidx }
  {
    Blank ~ label ~ not ~ permitted ~
    ( for ~ term ~ ` \tl_to_str:n { #2 } ')
  }
  {
    Use ~ label={...} ~ in ~ options ~
    to ~ set ~ the ~ label ~ to ~ a ~ non-blank ~ value. ~
    Bear ~ in ~ mind ~ that ~ commas ~ (,) ~ and ~
    equals ~ (=) ~ and ~ other ~ problematic ~
    content ~ will ~ be ~ stripped
  }
}
\tl_if_eq:NnT \l__datagidx_term_sort_tl { \c_novalue_tl }
{
  \__datagidx_create_sort:n { #2 }
}
}
```

`\datagidx@add@term` The argument is the term's name. Add term (once all fields have been set. Argument is the name field. The column label should be in `\l__datagidx_term_label_tl` and the database label should be in `\l__datagidx_term_database_tl` Version 3.0: replaced `\datagidx@add@term` with:

```
\cs_new:Nn \__datagidx_add_term:n
{
  \__datagidx_assign_label_db:nn
  { \l__datagidx_term_label_tl }
  { \l__datagidx_term_database_tl }
}
```

Build the row. Don't use datum for labels, clists.

```
\tl_clear:N \l__datatool_row_tl
\tl_put_right:Nx \l__datatool_row_tl
{
  \__datatool_row_element_markup:vV
```

```

    { dtl@ci@ \l__datagidx_term_database_tl @ Label }
    \l__datagidx_term_label_tl
  }

```

Markup Used with \dtlspecialvalue

```

\tl_put_right:Nx \l__datatool_row_tl
{
  \__datatool_row_element_markup:vn
  { dtl@ci@ \l__datagidx_term_database_tl @ Used }
  {
    \dtlspecialvalue { \__datagidx_used:n { 0 } }
  }
}
\__datagidx_append_element:nn { Name } { #1 }
\__datagidx_append_element:nV
{ Text } \l__datagidx_term_text_tl
\__datagidx_append_element:nV
{ Description } \l__datagidx_term_description_tl
\__datagidx_append_element:nV
{ Sort } \l__datagidx_term_sort_tl
\__datagidx_append_element:nV
{ Symbol } \l__datagidx_term_symbol_tl
\__datagidx_append_element:nV
{ Short } \l__datagidx_term_short_tl
\__datagidx_append_element:nV
{ Long } \l__datagidx_term_long_tl
\tl_if_eq:NnTF \l__datagidx_term_plural_tl { \c_novalue_tl }
{
  \__datagidx_append_element:no
  { Plural }
  { \l__datagidx_term_text_tl s }
}
{
  \__datagidx_append_element:nV
  { Plural } \l__datagidx_term_plural_tl
}
\tl_if_eq:NnTF \l__datagidx_term_shortplural_tl { \c_novalue_tl }
{
  \__datagidx_append_element:no
  { ShortPlural }
  { \l__datagidx_term_short_tl s }
}
{
  \__datagidx_append_element:nV
  { ShortPlural }
  \l__datagidx_term_shortplural_tl
}
\tl_if_eq:NnTF \l__datagidx_term_longplural_tl { \c_novalue_tl }
{
  \__datagidx_append_element:no

```

```

        { LongPlural }
        { \l__datagidx_term_long_tl s }
    }
    {
        \__datagidx_append_element:nV
        { LongPlural }
        \l__datagidx_term_longplural_tl
    }
\__tl_if_empty:NF \l__datagidx_term_see_tl
{
    \__tl_put_right:Nx \l__datatool_row_tl
    {
        \__datatool_row_element_markup:vV
        { dtl@ci@ \l__datagidx_term_database_tl @ See }
        \l__datagidx_term_see_tl
    }
}
\__tl_if_empty:NF \l__datagidx_term_seealso_tl
{
    \__tl_put_right:Nx \l__datatool_row_tl
    {
        \__datatool_row_element_markup:vV
        { dtl@ci@ \l__datagidx_term_database_tl @ SeeAlso }
        \l__datagidx_term_see_tl
    }
}
}

```

Hook to make it easier to add extra fields.

```
\g__datagidx_extra_fields_tl
```

Add parent, if supplied.

```

\__tl_if_empty:NF \l__datagidx_term_parent_tl
{
    \iftermexists { \l__datagidx_term_parent_tl }
    {
        \__tl_set:Nx \l__datagidx_parent_database_tl
        {
            \__datagidx_term_database:n
            { \l__datagidx_term_parent_tl }
        }
    }
}

```

Parent entry is required to belong to same database as child entry.

```

\__tl_if_eq:NNTF
    \l__datagidx_parent_database_tl
    \l__datagidx_term_database_tl
{
    \__tl_put_right:Nx \l__datatool_row_tl
    {
        \__datatool_row_element_markup:vV
        { dtl@ci@ \l__datagidx_term_database_tl @ Parent }
        \l__datagidx_term_parent_tl
    }
}

```

```

}
\__datagidx_add_child:xxx
{ \l__datagidx_term_database_tl }
{ \l__datagidx_term_parent_tl }
{ \l__datagidx_term_label_tl }

```

Add the hierarchical sort.

```

\tl_set:Nn \l__datagidx_term_hiersort_tl { \c_novalue_tl }
\__datagidx_set_hiersort:
\tl_if_eq:NnF
  \l__datagidx_term_hiersort_tl { \c_novalue_tl }
  {
    \__datagidx_append_element:nV
      { HierSort } \l__datagidx_term_hiersort_tl
  }
}
{
  \PackageError{datagidx}
  {
    Parent ~ entry ~ ` \l__datagidx_term_parent_tl ' ~ must ~
    belong ~ to ~ the ~ same ~ database ~ as ~
    child ~ entry ~ ` \l__datagidx_term_label_tl '
  }
  {
    Parent ~ entry ~ is ~ in ~ database ~
    ` \l__datagidx_parent_database_tl ' ~ and ~
    child ~ entry ~ is ~ in ~
    database ~ ` \l__datagidx_term_database_tl '
  }
}
}
{
  \PackageError {datagidx}
  {
    Can't ~ assign ~ parent ~ to ~
    ` \l__datagidx_term_label_tl ': ~
    ` \l__datagidx_term_parent_tl ' ~ doesn't ~ exist
  }
  {}
}
}

```

Add the row to the database. Increment total number of rows:

```
\int_gincr:c { dtlrows@ \l__datagidx_term_database_tl }
```

Append row markup to the database's internal token register.

```

\__datatool_token_register_gput_right:cx
{ dtldb@ \l__datagidx_term_database_tl }
{
  \__datatool_row_markup:vV
  { dtlrows@ \l__datagidx_term_database_tl }
}

```

```

        \l__datatool_row_tl
    }
Provide user with a means to access the label of the latest defined term:
    \tl_gset:Nx \datagidxlastlabel
    { \l__datagidx_term_label_tl }
Allow user to hook in here:
    \postnewtermhook
}
\cs_new:Nn \__datagidx_set_hiersort:
{
    \group_begin:
    \DTLaction
    [
        key = Label,
        expand-value = \l__datagidx_term_parent_tl ,
        name = \l__datagidx_term_database_tl ,
        return = { \Sort = Sort, \HierSort = HierSort}
    ]
    { select ~ row }
    \datatool_if_null_or_empty:NTF \HierSort
    {
        \datatool_if_null_or_empty:NF \Sort
        {
            \tl_set:Nx \l__datagidx_term_hiersort_tl
            {
                \exp_not:V \Sort
                \exp_not:N \datatoolctrlboundary
                \exp_not:N \datatoolasciistart
                \exp_not:V \l__datagidx_term_sort_tl
            }
        }
    }
    {
        \tl_set:Nx \l__datagidx_term_hiersort_tl
        {
            \exp_not:V \HierSort
            \exp_not:N \datatoolctrlboundary
            \exp_not:N \datatoolasciistart
            \exp_not:V \l__datagidx_term_sort_tl
        }
    }
    \exp_args:NNNV
    \group_end:
    \tl_set:Nn \l__datagidx_term_hiersort_tl
    \l__datagidx_term_hiersort_tl
}

```

Append an element to the current row token list variable, taking the current expansion setting into account. Syntax: `{<column key>}{<value>}`

```

\cs_new:Nn \__datagidx_append_element:nn
{
  \tl_if_exist:cTF
  { dtl@ci@ \l__datagidx_term_database_tl @ #1 }
  {
    \__datatool_process_new_value:n { #2 }
    \tl_put_right:Nx \l__datatool_row_tl
    {
      \__datatool_row_element_markup:vV
      { dtl@ci@ \l__datagidx_term_database_tl @ #1 }
      \l__datatool_item_value_tl
    }
  }
}
{
  \PackageError { datagidx }
  {
    Column ~ ` #1' ~ hasn't ~ been ~ defined ~ in ~
    database ~ ` \l__datagidx_term_database_tl '
  }
  {
    A ~ new ~ term ~ can't ~ be ~ added ~ to ~
    database ~ ` \l__datagidx_term_database_tl '. ~
    Has ~ the ~ database ~ been ~ defined ~ with ~
    \token_to_str:N \newgidx ? ~ If ~ this ~ is ~
    a ~ custom ~ field, ~ was ~
    \token_to_str:N \newtermaddfield \c_space_tl ~
    used ~ after ~ ` \l__datagidx_term_database_tl ' ~
    was ~ defined?
  }
}
}
\cs_generate_variant:Nn
  \__datagidx_append_element:nn
  { nV , no, nv }
  Syntax: <value tl var>{<col-key>}
\cs_new:Nn \__datagidx_append_element_with_check:Nn
{
  \datatool_if_null:NF #1
  {
    \datatool_if_has_key:nnT
    { \l__datagidx_term_database_tl } { #2 }
    {
      \__datagidx_append_element:nV
      { #2 } #1
    }
  }
}
}

```

\postnewtermhook

```
\newcommand*\postnewtermhook{}
```

`\newtermfield` Expandable access to field name. (No check for existence of the field. Expands to an empty string if the field is undefined.)

```
\newcommand*\newtermfield}[1]{
  \use:c { \__datagidx_term_ #1 _ t1 }
}
```

`\ifnewtermfield` If the named field (given in first argument) is empty or undefined do third argument, otherwise do second argument.

```
\newcommand{\ifnewtermfield}[3]{%
  \tl_if_exist:cTF { \__datagidx_term_ #1 _ t1 }
  {
    \tl_if_empty:cTF { \__datagidx_term_ #1 _ t1 }
    { #3 } { #2 }
  }
  { #3 }
}
```

`\datagidx@newterm` Normal behaviour for `\newterm`

```
\NewDocumentCommand \datagidx@newterm { 0{} m }
{
```

Assign values to all the fields.

```
  \__datagidx_set_field_values:nn { #1 } { #2 }
```

Check if database exists.

```
  \DTLifdbexists { \__datagidx_term_database_t1 }
  {
```

Database exists. Check if term already exists.

```
  \iftermexists { \__datagidx_term_label_t1 }
  {
    \PackageError {datagidx}
    {
      Term ~ ` \__datagidx_term_label_t1 ' ~
      already ~ exists ~ in ~ database ~
      ` \__datagidx_term_database_t1 '
    }
  }
  { }
}
```

Add this entry to the database.

```
  \__datagidx_add_term:n { #2 }
  \dtl@message
  {
    Added ~ term ~ ` \__datagidx_term_label_t1 ' ~
    to ~ database ~ ` \__datagidx_term_database_t1 ' ~
    (name: ~ ` \tl_to_str:N \__datagidx_term_name_t1 ' , ~
    sort: ~ ` \tl_to_str:N \__datagidx_term_sort_t1 ')
  }
```

```

    }
  }
}
{
Database doesn't exist.
  \PackageError {datagidx}
  {
    Glossary/index ~ database ~ '\l__datagidx_term_database_tl' ~
    doesn't ~ exist
  }
  {
    You ~ must ~ define ~ the ~ glossary/index ~
    database ~ with \token_to_str:N \newgidx \c_space_tl ~
    before ~ you ~ can ~ add ~ any ~ terms ~ to ~ it.
  }
}
}%
}

```

datagidx@highopt@newterm Used when high optimized setting enabled. This setting must be switched off if the user wants to modify the database.

```

\NewDocumentCommand \datagidx@highopt@newterm { 0{} m }
{

```

Assign values to all the fields.

```

  \__datagidx_set_field_values:nn { #1 } { #2 }

```

Check if database exists.

```

  \DTLifdbexists { \l__datagidx_term_database_tl }
  {

```

Database exists. If this is the first run, we need to add the term as usual, otherwise we just need to define the mapping from the term label to the database label

```

  \__datatool_get_row_index:Nxxx
  \l__datatool_row_idx_tl
  { \l__datagidx_term_database_tl }
  {
    \dtlcolumnindex
    { \l__datagidx_term_database_tl } {Label}
  }
  { \l__datagidx_term_label_tl }
  \datatool_if_null:NTF \l__datatool_row_idx_tl
  {

```

Hasn't been defined so add.

```

  \__datagidx_add_term:n { #2 }

```

Database will need to be sorted.

```

  \tl_set:cx
  {
    datagidx@do@highopt@sort@
    \l__datagidx_term_database_tl
  }

```

```

    }
    { \exp_not:V \l__datagidx_sort_tl }
  }
  {

```

Has been defined, so just define the mapping and \datagidxlastlabel

```

    \__datagidx_assign_label_db:nn
    \l__datagidx_term_label_tl
    \l__datagidx_term_database_tl
    \tl_set:Nx \datagidxlastlabel
    { \l__datagidx_term_label_tl }
  }
}%
{%

```

Database doesn't exist.

```

\PackageError {datagidx}
{
  Glossary/index ~ database ~
  '\l__datagidx_term_database_tl' ~ doesn't ~ exist
}
{
  You ~ must ~ define ~ the ~ glossary/index ~
  database ~ before ~ you ~ can ~
  add ~ any ~ terms ~ to ~ it.
}
}
}
}

```

\datagidx@addchild Version 3.0: replaced \datagidx@addchild with:

```

\cs_new:Nn \__datagidx_add_child:nnn
{
  \__datatool_get_row_for_value:xxn
  { #1 }
  { \dtlcolumnindex { #1 } { Label } }
  { #2 }
  \dtlgetentryfromcurrentrow
  \l__datagidx_child_clist
  { \dtlcolumnindex { #1 } { Child } }
  \datatool_if_null:NT \l__datagidx_child_clist
  {
    \clist_clear:N \l__datagidx_child_clist
  }
  \clist_put_right:Nx \l__datagidx_child_clist
  { #3 }
  \exp_args:NnV
  \dtlupdateentryincurrentrow
  {Child} \l__datagidx_child_clist
  \dtlrecombine
}
}

```

```

\cs_generate_variant:Nn
  \__datagidx_add_child:nnn
  { xxx }

```

20.3 Defining Acronyms

```
\newacro[<options>]{<short>}{<long>}
```

\newacro

Shortcut command for acronyms.

```

\NewDocumentCommand \newacro { 0{} m m }
{
  \exp_args:Nno \datagidx_new_acro:nnnn { #1 }
  { \text_uppercase:n { #2 } } { #2 } { #3 }
}

\cs_new:Nn \datagidx_new_acro:nnnn
{
  \bool_if:NTF \l__datatool_new_element_expand_bool
  {
    \newterm
    [
      description = { \exp_not:N \capitalisewords { #4 } },
      short = { \exp_not:N \acronymfont { #3 } },
      long = { #4 },
      text =
      {
        \exp_not:N \DTLgidxAcrStyle
        { #4 } { \exp_not:N \acronymfont { #3 } }
      },
      plural =
      {
        \exp_not:N \DTLgidxAcrStyle
        { #4 s } { \exp_not:N \acronymfont { #3 s } }
      },
      sort = { #3 }, label = { #3 },
      #1
    ]
    { #2 }
  }
  {
    \newterm
    [
      description = { \capitalisewords { #4 } },
      short = { \acronymfont { #3 } },
      long = { #4 },
      text = { \DTLgidxAcrStyle { #4 } { \acronymfont { #3 } } },
      plural = { \DTLgidxAcrStyle { #4 s } { \acronymfont { #3 s } } },
      sort = { #3 }, label = { #3 },

```

```

        #1
      ]
    { #2 }
  }
}

```

`\acronymfont` The font to use for the acronym.
`\newcommand*{\acronymfont}[1]{#1}`

`\DTLgidxAcrStyle`

```
\DTLgidxAcrStyle{<long>}{<short>}
```

```
\newcommand*{\DTLgidxAcrStyle}[2]{#1 ~ (#2)}
```

21 Conditionals

`\iftermexists`

```
\iftermexists{<label>}{<true part>}{<>false part>}
```

Check if term with given label exists. This uses the term to database mapping to avoid a database lookup.

```
\newcommand{\iftermexists}[3]{%
  \tl_if_exist:cTF
    { g__datagidxentry_ #1 _ tl }
    { #2 } { #3 }
}
```

Term label to database assignment.

```
\cs_new:Nn \__datagidx_assign_label_db:nn
{
  \tl_if_exist:cTF
    { g__datagidxentry_ #1 _ tl }
    {
      \exp_args:Nxx \tl_if_eq:nnF
        { #2 } { \tl_use:c { g__datagidxentry_ #1 _ tl } }
      {
        \PackageError { datagidx }
        {
          Can't ~ associated ~ label ~ `#1 ' ~
          with ~ database ~ `#2'. ~ Label ~
          already ~ associated ~ with ~ database ~
          ` \tl_use:c { g__datagidxentry_ #1 _ tl } '
        }
      }
    }
  { }
}
}
{
  \tl_gset:cx { g__datagidxentry_ #1 _ tl } { #2 }
}
```

```

    }
  }
  Expands to the database label the given term is in.
  \cs_new:Nn \__datagidx_term_database:n
  {
    \csuse { g__datagidxentry_ #1 _ tl }
  }

```

`\datagidxdb` Gets the label of database containing the given entry. No check is made for the existence of the entry. Expands to empty if label is undefined.

```

\newcommand*{\datagidxdb}[1]{
  \__datagidx_term_database:n { #1 }
}

```

`\dtlunknowntag`

```

\newcommand{\dtlunknowntag}{??}

Fetch the row from the index/glossary database associated with the given term.
The term's label should be in \l__datagidx_term_label_tl. This will set
\l__datagidx_term_database_tl to the database label and \dtlcurrentrow
if successful.
\cs_new:Nn \__datagidx_fetch_row_for_label:NT
{
Fetch the name of the database with which this entry is associated.
  \tl_set:Nx \l__datagidx_term_database_tl
  {
    \__datagidx_term_database:n
    { \l__datagidx_term_label_tl }
  }
  \tl_if_empty:NTF \l__datagidx_term_database_tl
  {
    \dtlunknowntag
    \PackageError {datagidx}
    {
      \token_to_str:N #1 : ~
      No ~ term ~ ` \l__datagidx_term_label_tl ' ~ defined
    }
    {
      Check ~ that ~ you ~ have ~ correctly ~ spelt ~ the ~
      label. ~ If ~ you ~ defined ~ a ~ term ~ containing ~
      commands ~ and ~ you ~ didn't ~ explicitly ~ set ~
      the ~ label, ~
      \legacy_if:nF { dtlverbose } { switch ~ on ~ verbose ~
      mode ~ and ~ } examine ~ the ~ transcript ~
      messages ~ (Added ~ term ~ ` [...] ' ~ to ~
      database ~ ` [...] ') ~ to ~ check ~ the ~ label
    }
  }
}

```

Get the row associated with this label and make it the current row.

```
\tl_set:Nx \l__datatool_item_col_tl
{
  \dtlcolumnindex
  { \l__datagidx_term_database_tl } {Label}
}
\tl_if_empty:NTF \l__datatool_item_col_tl
{
  \PackageError { datagidx }
  {
    \token_to_str:N #1 : ~
    No ~ column ~ `Label' ~ found ~ in ~ database ~
    ` \l__datagidx_term_database_tl '
  }
  {
    Something ~ has ~ gone ~ wrong. ~ The ~
    index/glossary ~ database
    ` \l__datagidx_term_database_tl ' ~
    is ~ associated ~ with ~ the ~ term ~
    label ~ ` \l__datagidx_term_label_tl ' ~
    but ~ it ~ doesn't ~ have ~ a ~ column ~ with ~
    the ~ key ~ `Label'
  }
}
{
  \exp_args:NNVV
  \__datatool_get_row_for_value:nnnTF
  \l__datagidx_term_database_tl
  \l__datatool_item_col_tl
  \l__datagidx_term_label_tl
}
```

Found it.

```
#2
}
```

Not found. Something has gone wrong.

```
\PackageError { datagidx }
{
  \token_to_str:N #1 : ~
  No ~ row ~ found ~ in ~ database ~
  ` \l__datagidx_term_database_tl ' ~ in ~ column ~
  ` Label ' ~ matching ~ ` \l__datagidx_term_label_tl '
}
{
  Something ~ has ~ gone ~ wrong. ~ Term ~ with ~
  label ~ ` \l__datagidx_term_label_tl ' ~ was ~
  assigned ~ to ~ database ~
  ` \l__datagidx_term_database_tl ' ~ but ~
```



```

    {
      \dtlcolumnindex { \l__datagidx_term_database_tl } {Used}
    }

```

Current row has been edited, so we need to merge the current row back into the database.

```

    \dtlrecombine
  }
}
\MFUexcl { \glsreset }

```

```
\glsunset{<label>}
```

\glsunset

Mark as used without affecting location.

```

\NewDocumentCommand \glsunset { m }
{
  \__datagidx_set_label:n { #1 }
  \__datagidx_fetch_row_for_label:NT \glsunset
  {

```

Update the Used field.

```

    \dtlreplaceentryincurrentrow
    {
      \dtlspecialvalue { \__datagidx_used:n { 1 } }
    }
    {
      \dtlcolumnindex
        { \l__datagidx_term_database_tl } {Used}
    }

```

Current row has been edited, so we need to merge the current row back into the database.

```

    \dtlrecombine
  }
}
\MFUexcl { \glsunset }

```

```
\glsresetall{<db>}
```

\glsresetall

Resets all entries in the given database.

```

\NewDocumentCommand \glsresetall { m }
{
  \dtlforcolumn \l__datagidx_label_tl { #1 } { Label }
  {
    \exp_args:NV \glsreset \l__datagidx_label_tl
  }
}
\MFUexcl { \glsresetall }

```

`\glsunsetall`

`\glsunsetall{<db>}`

Resets all entries in the given database.

```
\NewDocumentCommand \glsunsetall { m }
{
  \dtlforcolumn \l__datagidx_label_tl { #1 } { Label }
  {
    \exp_args:NV \glsunset \l__datagidx_label_tl
  }
}
\MFUexcl { \glsunsetall }
```

23 Accessing Entry Information

`\datagidx@anchorcount` Register to make unique anchors. Version 3.0: replaced `\datagidx@anchorcount` with:

```
\int_new:N \g__datagidx_anchor_count_int
```

`\datagidx@formatanchor` Format number using six digits. Version 3.0: replaced `\datagidx@formatanchor` with:

```
\cs_new:Nn \__datagidx_format_anchor:n
{
  \int_compare:nNnT { #1 } < { 10000 }
  {
    0
    \int_compare:nNnT { #1 } < { 1000 }
    {
      0
      \int_compare:nNnT { #1 } < { 100 }
      {
        0
        \int_compare:nNnT { #1 } < { 10 }
        { 0 }
      }
    }
  }
}
\int_eval:n { #1 }
}
```

Append `FirstId` to current row.

```
\cs_new:Nn \__datagidx_append_firstid:n
{
  \exp_args:Nnx \dtlappendentrytocurrentrow
  {FirstId} { \__datagidx_format_anchor:n { #1 } }
}
```

Syntax: `<tl var>{<db-name>}`

Gets the FirstId from the current row:

```
\cs_new:Nn \__datagidx_get_firstid:Nn
{
  \dtlgetentryfromcurrentrow #1
  {
    \dtlcolumnindex { #2 } {FirstId}
  }
}
```

\@datagidx@escloc

```
\newcommand*\@datagidx@escloc}[2]
{
  \token_to_str:c { #1 } { \exp_not:N \int_eval:n { #2 } }
}
```

\datagidx@escapelocation Version 3.0: removed \datagidx@escapelocation

\datagidx@escapelocationformat Version 3.0: removed \datagidx@escapelocationformat

\datagidx@clearlocationformat Version 3.0: removed \datagidx@clearlocationformat

\DTLgidxAddLocationType Allow user to add their own location type. Argument must be control sequence name without initial backslash. Version 3.0: deprecated

```
\newcommand*\DTLgidxAddLocationType}[1]{%
  \PackageWarning { datagidx }
  {
    \token_to_str:N \DTLgidxAddLocationType \c_space_tl ~
    deprecated. ~ Ignoring
  }
}

\tl_put_right:Nn \l_datatool_measure_hook_tl
{
  \cs_set_eq:NN \glsadd \use_none:n
}
```

\datagidx@target

`\datagidx@target{<label>}{<format>}{<location>}{<text>}`

Make a target if `\hypertarget` has been defined, but only write content in the document environment. Ignore the location in the preamble (the aux file isn't open at this point, but increment the anchor count). Version 3.0: replaced `\datagidx@target` with:

```
\cs_new:Nn \__datagidx_target:nnnn
{
  \__datagidx_target_create_anchor:nnn
  { #1 } { #2 } { }
}
```

```

\AtBeginDocument
{
  \cs_set_eq:NN
  \__datagidx_target:nnnn
  \__datagidx_target_doc:nnnn
}

```

Create just the anchor information.

```

\cs_new:Nn \__datagidx_target_create_anchor:nnn
{
  \int_gincr:N \g__datagidx_anchor_count_int
  \tl_set:Nx \l__datagidx_target_tl
  {
    datagidx .
    \__datagidx_format_anchor:n { \g__datagidx_anchor_count_int }
  }
  \tl_if_empty:nTF { #3 }
  {
    \exp_args:Nx \datagidx@write@usedentry
    { #1 } { }
  }
  {
    \__datagidx_write_used_entry:xxnx
    { #1 } { #2 } { #3 } { \l__datagidx_target_tl }
  }
}

```

Document environment version:

```

\cs_new:Nn \__datagidx_target_doc:nnnn
{
  \__datagidx_target_create_anchor:nnn
  { #1 } { #2 } { #3 }
  \cs_if_exist:NT \hypertarget
  {

```

Make sure the current line doesn't scroll off the top of the screen.

```

  \datagidxshowifdraft
  {
    [ \l__datagidx_target_tl ]
    \discretionary {} {} {}
  }
  \group_begin:
  \datatool_measure_height:Nn
  \l__datatool_tmpa_dim { #4 }
  \raisebox { \l__datatool_tmpa_dim }
  {
    \datagidxtarget { \l__datagidx_target_tl } { }
  }
  \group_end:
}
\datagidxshowifdraft

```

```

    { [ #1 ] \discretionary {} {} {} }
#4
}

```

\glsdispenry

`\glsdispenry{<label>}{<field>}`

Short cut that fetches and displays a value.

```

\NewDocumentCommand \glsdispenry { m m }
{
  \DTLgidxFetchEntry \l__datagidx_value_tl { #1 } { #2 }
  \datatool_if_null:NF \l__datagidx_value_tl
  {
    \l__datagidx_value_tl
  }
}

```

\Glsdispenry

`\Glsdispenry{<label>}{<field>}`

As previous but makes the first letter upper case.

```

\NewDocumentCommand \Glsdispenry { m m }
{
  \DTLgidxFetchEntry \l__datagidx_value_tl { #1 } { #2 }
  \datatool_if_null:NF \l__datagidx_value_tl
  {
    \xmakefirstuc \l__datagidx_value_tl
  }
}
\MFUaddmap { \glsdispenry } { \Glsdispenry }

```

\DTLgidxFetchEntry

`\DTLgidxFetchEntry<tl var>{<label>}{<field>}`

Fetch value for the given field for the term identified by <label> and store the value in <cs> (a control sequence). Triggers an error and sets <tl var> to null if not found.

```

\NewDocumentCommand \DTLgidxFetchEntry { m m m }
{
  \__datagidx_set_label:n { #2 }
  \tl_set_eq:NN #1 \dtlnovalue

```

Does this entry exist?

```

  \iftermexists { \l__datagidx_term_label_tl }
  {
    \tl_set:Nx \l__datagidx_term_database_tl
    {
      \__datagidx_term_database:n
      { \l__datagidx_term_label_tl }
    }
  }
}

```

```

}
\datatool_if_has_key:nnTF
{ \l__datagidx_term_database_tl }
{ #3 }
{
  \__datagidx_fetch_row_for_label:NT \DTLgidxFetchEntry
  {
    Get the entry for the given field in the current row and store in <cs>.
    \dtlgetentryfromcurrentrow
    #1
    {
      \dtlcolumnindex { \l__datagidx_term_database_tl } { #3 }
    }
  }
}
{
  \PackageError { datagidx }
  {
    Database ~ ` \l__datagidx_term_database_tl ' ~
    doesn't ~ have ~ a ~ column ~ labelled ~ `#3'
  }
  {
    Check ~ that ~ you ~ have ~ correctly ~ spelt ~
    the ~ column ~ label ~ (key)
  }
}
}
{
  \PackageError { datagidx }
  {
    No ~ term ~ ` \l__datagidx_term_label_tl ' ~ defined
  }
  {
    Check ~ that ~ you ~ have ~ spelt ~ the ~ label ~
    correctly ~ and ~ that ~ the ~ term ~ was ~ added ~
    to ~ the ~ database ~ with ~ \token_to_str:N \newterm
    \c_space_tl ~ or ~ \token_to_str:N \newacro
  }
}
}
}

```

\datagidx@format Version 3.0: replaced \datagidx@format with:
 \tl_new:N \l__datagidx_format_tl

\parse@format label{[<format>]label}

tagidx@parse@format label

Separate format and label from argument.

```

\newcommand*\datagidx@parse@format@label@[1]{%
  \datagidx@parse@format@label@#1\@endparse@format@label@
}
\newcommand*\datagidx@parse@format@label@{%
  \@ifnextchar[{\datagidx@parse@format@label@}{\datagidx@parse@format@label@[]}%
}
\def\datagidx@parse@format@label@[#1]#2\@endparse@format@label@{%
  \tl_set:Nn \l__datagidx_format_tl { #1 }
  \__datagidx_set_label:n { #2 }
}

```

```
\@datagidx@use@entry{<link text>}
```

\@datagidx@use@entry

The label and format should have been stored in `\l__datagidx_term_label_tl` and `\l__datagidx_format_tl` before calling this macro. Version 3.0: replaced `\@datagidx@use@entry` with:

Syntax: *<calling-cs>* {<link text>}

```

\cs_new:Nn \__datagidx_use_entry:Nn
{
  \__datagidx_fetch_row_for_label:NT #1
  {

```

Get the entry for the `FirstId` field and store in `\l__datagidx_id_tl`

```

  \__datagidx_get_firstid:Nn
  \l__datagidx_id_tl
  { \l__datagidx_term_database_tl }

```

If it hasn't been defined set it.

```

  \datatool_if_null:NT \l__datagidx_id_tl
  {

```

Count register hasn't been updated yet so add 1.

```

    \exp_args:Nx \__datagidx_append_firstid:n
    {
      \int_eval:n
      { \g__datagidx_anchor_count_int + \c_one_int }
    }
  }

```

Update the `Used` field.

```

  \dtlreplaceentryincurrentrow
  {
    \dtlspecialvalue { \__datagidx_used:n { 1 } }
  }
  {
    \dtlcolumnindex
    { \l__datagidx_term_database_tl } {Used}
  }
}

```

Get the parent entry label (if one exists).

```
\dtlgetentryfromcurrentrow
  \l__datagidx_parent_tl
  {
    \dtlcolumnindex
      { \l__datagidx_term_database_tl }{Parent}
  }
```

Current row has been edited, so we need to merge the current row back into the database.

```
\dtlrecombine
```

If parent hasn't be used, give it an empty location.

```
\__datagidx_mark_parent:NN
  \l__datagidx_term_database_tl \l__datagidx_parent_tl
```

Write the location to the auxiliary file and display value of field.

```
\__datagidx_target:nnnn
  { \l__datagidx_term_label_tl }
  { \l__datagidx_format_tl }
  { \csuse { the\DTLgidXCounter } }
  { #2 }
}
}
```

`\datagidx@markparent` Syntax: $\langle db-tl-var \rangle \langle parent-tl-var \rangle$ Assign empty location to parent, if location of that parent is null. (Recursive). Version 3.0: replaced `\datagidx@markparent` with:

```
\cs_new:Nn \__datagidx_mark_parent:NN
{
  \datatool_if_null:NF #2
  {
```

Write empty location to the auxiliary file.

```
\__datagidx_target:nnnn { #2 } { } { } { }
```

Fetch this parent's parent entry. Get the row associated with this and make it the current row.

```
\__datatool_get_row_for_value:xxx
{ #1 }
{ \dtlcolumnindex { #1 } { Label } }
{ #2 }
```

Get the entry for the `FirstId` field and store in `\l__datagidx_id_tl`

```
\__datagidx_get_firstid:Nn
  \l__datagidx_id_tl
  { \l__datagidx_term_database_tl }
```

If it hasn't been defined set it.

```
\datatool_if_null:NT \l__datagidx_id_tl
{
  \__datagidx_append_firstid:n
  {
    \g__datagidx_anchor_count_int
```

```

    }
  }

```

Get the parent

```

    \dtlgetentryfromcurrentrow
    \l__datagidx_parent_tl
    {\dtlcolumnindex{#1}{Parent}}%

```

Current row has been edited, so we need to merge the current row back into the database.

```

    \dtlrecombine

```

Recurse

```

    \__datagidx_mark_parent:NN #1 \l__datagidx_parent_tl
  }
}

```

Syntax: $\langle label \rangle \langle format \rangle \langle location \rangle \langle target \rangle$

```

\cs_new:Nn \__datagidx_write_used_entry:nxxx
{
  \datagidx@write@usedentry
  { #1 }
  { [ #2 ] { #3 } { #4 } }
}
\cs_generate_variant:Nn
  \__datagidx_write_used_entry:nxxx
  { xxx }

```

`\datagidx@write@usedentry` Write out location to aux file and add location to the location list for the current run.

```

  \newcommand*{\datagidx@write@usedentry}[2]{%

```

Do update if ‘highopt optimize’ setting is on.

```

  \datagidx@do@highopt@update{#1}%
  \protected@edef \l__datagidx_location_tl { #2 }

```

Write out location to aux file.

```

  \protected@write{\@auxout}{}%
  {%
    \token_to_str:N \datagidx@aux@usedentry
    { #1 } { #2 }
    { \tl_to_str:N \l__datagidx_location_tl }
  }%

```

This may be a page off if indexing occurs by a page break, so it should be checked with `UnsafeLocation` rather than `Location`.

```

  \__datagidx_used_entry:nxx
  { CurrentLocation } { #1 }
  { \tl_to_str:N \l__datagidx_location_tl }
}

```

`\datagidx@xusedentry`

```
\datagidx@usedentry{<location tag>}{<label>}
{<location>}
```

Like `\datagidx@usedentry` but expands the location. Unlike `\datagidx@usedentry` the first argument isn't optional. Version 3.0: replaced `\datagidx@xusedentry` with:

```
\cs_new:Nn \__datagidx_used_entry:nnn
{
  \datagidx@usedentry [ #1 ] { #2 } { #3 }
}
\cs_generate_variant:Nn
  \__datagidx_used_entry:nnn
  { xxx, nxx }
```

`\datagidx@usedentry`

```
\datagidx@usedentry[<location tag>]{<label>}
{<location>}
```

Add to the location list for the given entry.

```
\newcommand*{\datagidx@usedentry}[3][Location]{%
```

Check if label exists. (It may have been deleted or had a label change.)

```
\iftermexists { #2 }
{%
```

Fetch the name of the database with which this entry is associated.

```
\tl_set:Nx \l__datagidx_term_database_tl
{ \__datagidx_term_database:n { #2 } }
```

Get the row associated with this label and make it the current row.

```
\__datatool_get_row_for_value:xxx
{ \l__datagidx_term_database_tl }
{ \dtlcolumnindex{\l__datagidx_term_database_tl}{Label} }
{ #2 }
```

Get the entry for the `<location tag>` field in the current row and store in `\l__datagidx_location_tl`.

```
\dtlgetentryfromcurrentrow
  \l__datagidx_location_tl
  { \dtlcolumnindex { \l__datagidx_term_database_tl } { #1 } }
\__datagidx_unwrap_location:N
  \l__datagidx_location_tl
```

Check the success of the previous command.

```
\datatool_if_null:NTF \l__datagidx_location_tl
{
```

There's no `<location tag>` field in the current row, so add one with the given location.

```
\tl_set:Nn \l__datagidx_location_tl { #3 }
\__datagidx_unwrap_location:N
  \l__datagidx_location_tl
```

```

\exp_args:Nne \dtlappendentrytocurrentrow
{ #1 }
{
  \exp_not:N \dtlspecialvalue
  {
    \exp_not:N \__datagidx_location:n
    {
      \exp_not:V \l__datagidx_location_tl
    }
  }
}
}
{

```

There is a *location tag* field in the current row, so append the given location to the list, unless one or the other is empty.

```

\clist_clear:N \l__datagidx_location_clist
\tl_if_empty:NTF \l__datagidx_location_tl
{
  \clist_put_right:Nn \l__datagidx_location_clist {#3}
}
{
  \clist_set:NV \l__datagidx_location_clist
  \l__datagidx_location_tl
  \tl_if_empty:nF { #3 }
  {
    \clist_put_right:Nn \l__datagidx_location_clist { #3 }
  }
}

```

and update the entry in the current row.

```

\exp_args:Nx \dtlreplaceentryincurrentrow
{
  \exp_not:N \dtlspecialvalue
  {
    \exp_not:N \__datagidx_location:n
    {
      \clist_use:Nn \l__datagidx_location_clist { , }
    }
  }
}
{ \dtlcolumnindex { \l__datagidx_term_database_tl } {#1} }
}

```

Current row has been edited, so we need to merge the current row back into the database.

```

\dtlrecombine
}
{
  \PackageWarning{datagidx}{No ~ term ~ `#2' ~ defined. ~ Ignoring}
}
}

```

```
\datagidx@aux@usedentry{\langle label \rangle}{\langle location \rangle}{\langle unsafe location \rangle}
```

\datagidx@aux@usedentry

This command is for the aux file. The unsafe location is a location that may be off due to the delayed shipout. The value is used to compare with the current location to determine if a rerun is required.

```
\newcommand*{\datagidx@aux@usedentry}[3]
{
```

Check if label exists. (It may have been deleted or had a label change.)

```
\iftermexists { #1 }
{
```

Fetch the name of the database with which this entry is associated.

```
\tl_set:Nx \l__datagidx_term_database_tl
{ \__datagidx_term_database:n { #1 } }
```

Get the row associated with this label and make it the current row.

```
\__datatool_get_row_for_value:xxxT
{ \l__datagidx_term_database_tl }
{ \dtlcolumnindex{\l__datagidx_term_database_tl}{Label} }
{ #1 }
{
```

Get the entry for the Location field in the current row and store in \l__datagidx_location_tl.

```
\dtlgetentryfromcurrentrow
\l__datagidx_location_tl
{ \dtlcolumnindex { \l__datagidx_term_database_tl } { Location } }
\__datagidx_unwrap_location:N
\l__datagidx_location_tl
```

Check the success of the previous command.

```
\datatool_if_null:NTF \l__datagidx_location_tl
{
```

There's no Location field in the current row, so add one with the given location.

```
\tl_set:Nn \l__datagidx_location_tl { #2 }
\__datagidx_unwrap_location:N
\l__datagidx_location_tl
\exp_args:Nne \dtlappendentrytocurrentrow
{ Location }
{
\exp_not:N \dtlspecialvalue
{
\exp_not:N \__datagidx_location:n
{
\exp_not:V \l__datagidx_location_tl
}
}
}
}
}
```

```
{
```

There is a Location field in the current row, so append the given location to the list, unless one or the other is empty.

```
\clist_clear:N \l__datagidx_location_clist
\tl_if_empty:NTF \l__datagidx_location_tl
{
  \clist_put_right:Nn \l__datagidx_location_clist
  { #2 }
}
{
  \clist_set:NV \l__datagidx_location_clist
  \l__datagidx_location_tl
  \tl_if_empty:nF { #2 }
  {
    \clist_put_right:Nn \l__datagidx_location_clist
    { #2 }
  }
}
```

and update the entry in the current row.

```
\exp_args:Nx \dtlreplaceentryincurrentrow
{
  \exp_not:N \dtlspecialvalue
  {
    \exp_not:N \__datagidx_location:n
    {
      \clist_use:Nn \l__datagidx_location_clist { , }
    }
  }
}
{
  \dtlcolumnindex
  { \l__datagidx_term_database_tl }
  { Location }
}
}
```

Get the entry for the UnsafeLocation field in the current row and store in \l__datagidx_location_tl.

```
\dtlgetentryfromcurrentrow
\l__datagidx_location_tl
{
  \dtlcolumnindex
  { \l__datagidx_term_database_tl }
  { UnsafeLocation }
}
\__datagidx_unwrap_location:N
\l__datagidx_location_tl
```

Check the success of the previous command.

```
\datatool_if_null:NTF \l__datagidx_location_tl
{
```

There's no UnsafeLocation field in the current row, so add one with the given location.

```

\tl_set:Nn \l__datagidx_location_tl { #3 }
\__datagidx_unwrap_location:N
  \l__datagidx_location_tl
\exp_args:Nne \dtlappendentrytocurrentrow
  { UnsafeLocation }
  {
    \exp_not:N \dtlspecialvalue
    {
      \exp_not:N \__datagidx_location:n
      {
        \tl_to_str:N \l__datagidx_location_tl
      }
    }
  }
}
{

```

There is an UnsafeLocation field in the current row, so append the given location to the list, unless one or the other is empty.

```

\clist_clear:N \l__datagidx_location_clist
\tl_if_empty:NTF \l__datagidx_location_tl
{
  \tl_set:Nn \l__datagidx_location_tl { #3 }
  \__datagidx_unwrap_location:N
    \l__datagidx_location_tl
\clist_put_right:Nx \l__datagidx_location_clist
  { \tl_to_str:N \l__datagidx_location_tl }
}
{
  \clist_set:NV \l__datagidx_location_clist
    \l__datagidx_location_tl
\tl_if_empty:nF { #3 }
  {
    \tl_set:Nn \l__datagidx_location_tl { #3 }
    \__datagidx_unwrap_location:N
      \l__datagidx_location_tl
\clist_put_right:Nx \l__datagidx_location_clist
    { \tl_to_str:N \l__datagidx_location_tl }
  }
}

```

and update the entry in the current row.

```

\exp_args:Nx \dtlreplaceentryincurrentrow
  {
    \exp_not:N \dtlspecialvalue
    {
      \exp_not:N \__datagidx_location:n
      {
        \clist_use:Nn \l__datagidx_location_clist { , }

```

```

    }
  }
}
{
  \dtlcolumnindex
  { \l__datagidx_term_database_tl }
  { UnsafeLocation }
}
}

```

Current row has been edited, so we need to merge the current row back into the database.

```

  \dtlrecombine
}
}
{
  \PackageWarning{datagidx}{No ~ term ~ `#1' ~ defined. ~ Ignoring}
}
}

```

\datagidx@save@loc Store the current location from the previous run. Version 3.0: no longer used but still defined until next version as it may be in the aux file of existing documents. TODO: remove

```

  \newcommand*{\datagidx@save@loc}[2]{%
}

```

\glsadd

```
\glsadd{<[<format>]label}
```

```

\NewDocumentCommand \glsadd { m }
{
  \group_begin:

```

Check term has been defined.

```

  \iftermexists { \l__datagidx_term_label_tl }
  {

```

```

    \datagidx@parse@formatlabel{#1}%

```

Write the location to the auxiliary file.

```

  \__datagidx_target:nnnn
  { \l__datagidx_term_label_tl }
  { \l__datagidx_format_tl }
  { \csuse{the\DTLgidxCounter} }
  { }

```

Fetch the name of the database with which this entry is associated.

```

  \tl_set:Nx \l__datagidx_term_database_tl
  { \__datagidx_term_database:n { \l__datagidx_term_label_tl } }

```

Get the row associated with this label and make it the current row.

```

  \__datatool_get_row_for_value:xxxTF

```

```

{ \l_datagidx_term_database_tl }
{ \dtlcolumnindex { \l_datagidx_term_database_tl } {Label} }
{ \l_datagidx_term_label_tl }
{

```

Update the Used field.

```

\dtlreplaceentryincurrentrow
{
  \dtlspecialvalue { \__datagidx_used:n { 1 } }
}
{
  \dtlcolumnindex { \l_datagidx_term_database_tl } {Used}
}

```

Get the entry for the FirstId field and store in \l__datagidx_id_tl

```

\__datagidx_get_firstid:Nn
  \l_datagidx_id_tl
  { \l_datagidx_term_database_tl }

```

If it hasn't been defined set it.

```

\datatool_if_null:NT \l_datagidx_id_tl
{
  \__datagidx_append_firstid:n
  { \g_datagidx_anchor_count_int }
}

```

Current row has been edited, so we need to merge the current row back into the database.

```

\dtlrecombine
}
{

```

The label to database mapping has been found but the label can't be found in the database.

```

\PackageError { datagidx }
{
  No ~ row ~ found ~ for ~ label ~
  ` \l_datagidx_term_label_tl ' ~ in ~
  database ~ ` \l_datagidx_term_database_tl '
}
{
  Something ~ has ~ gone ~ wrong ~ with ~ the ~ underlying ~
  structure. ~ Did ~ you ~ define ~ ` \l_datagidx_term_label_tl ' ~
  using ~ \token_to_str:N \newterm \c_space_tl or
  \token_to_str:N \newacro ? ~ Has ~ the ~ database ~
  ` \l_datagidx_term_database_tl ' ~ been ~ modified ~
  outside ~ of ~ datagidx.sty ~ commands?
}
}

```

```

}
{
  \PackageError {datagidx}
  { Term ~ ` \l_datagidx_term_label_tl ' ~ doesn't ~ exist }

```

```

    {
      Check ~ the ~ spelling ~ of ~ the ~ label. ~ Verbose ~ mode ~
      will ~ show ~ the ~ labels ~ in ~ the ~ transcript ~ for ~
      each ~ new ~ term
    }
  }
\group_end:
}
\MFUexcl { \glsadd }

```

\datagidx@count Version 3.0: Removed \datagidx@count

\glsaddall

\glsaddall{<db>}

Adds all entries in the given database.

```

\NewDocumentCommand \glsaddall { m }
{
  \DTLifdbexists{#1}%
  {
    \int_step_inline:nn
      { \DTLrowcount { #1 } }
    {
      \datatool_get_row:nnT { #1 } { ##1 }
      {

```

Get the label for this row.

```

        \dtlgetentryfromcurrentrow
          \l__datagidx_term_label_tl
          { \dtlcolumnindex { #1 } {Label} }

```

Write blank location to the auxiliary file but temporarily change \hypertarget as it doesn't make sense to have a target here.

```

        \group_begin:
          \cs_set_eq:NN \hypertarget \use_ii:nn
          \__datagidx_target:nnnn
            { \l__datagidx_term_label_tl }{}{}{}
        \group_end:

```

Update the Used field.

```

        \dtlreplaceentryincurrentrow
          {
            \dtlspecialvalue { \__datagidx_used:n { 1 } }
          }
          { \dtlcolumnindex { #1 } {Used} }

```

Get the entry for the FirstId field and store in \l__datagidx_id_tl

```

        \__datagidx_get_firstid:Nn
          \l__datagidx_id_tl { #1 }

```

If it hasn't been defined set it.

```
\datatool_if_null:NT \l_datagidx_id_tl
{
  \__datagidx_append_firstid:n
  { \g_datagidx_anchor_count_int }
}
```

Current row has been edited, so we need to merge the current row back into the database.

```
\dtlrecombine
}
}
}
{
  \PackageError {datagidx}
  {
    \token_to_str:N \glsaddall : ~
    Database ~ `#1' ~ doesn't ~ exist
  }
  {
    Check ~ that ~ you ~ have ~ correctly ~ spelt ~ the ~ database
    ~ name ~ in ~ the ~ argument ~ of \token_to_str:N \glsaddall
  }
}
}
}
\MFUexcl { \glsaddall }
```

Version 3.0 has added grouping to the following to prevent leakage of scratch token list variables.

```
\glslink{<label>}{<text>}
```

\glslink

Use given entry but user supplies text.

```
\NewDocumentCommand \glslink { m m }
{
  \group_begin:
  \datagidx@parse@formatlabel {#1}
  \datagidxlink { \l_datagidx_term_label_tl }
  {
    \__datagidx_use_entry:Nn \glslink { #2 }
  }
  \group_end:
}
\NewDocumentCommand \Glslink { m m }
{
  \glslink { #1 } { \makefirststuc { #2 } }
}
\MFUaddmap { \glslink } { \Glslink }
```

`\useentry`

`\useentry{<label>}{<field>}`

Fetch and use the given field for the given entry.

```
\NewDocumentCommand \useentry { m m }
{
  \group_begin:
  \datagidx@parse@formatlabel { #1 }
  \DTLgidxFetchEntry
  \l__datagidx_value_tl
  { \l__datagidx_term_label_tl } { #2 }
```

Just test for null, `\DTLgidxFetchEntry` will have already triggered an error.

```
\datatool_if_null:NF \l__datagidx_value_tl
{
  \datagidxlink { \l__datagidx_term_label_tl }
  {
    \__datagidx_use_entry:Nn \useentry
    { \l__datagidx_value_tl }
  }
}
\group_end:
}
```

`\Useentry`

`\Useentry{<label>}{<field>}`

As `\useentry`, but capitalise the first word.

```
\NewDocumentCommand \Useentry { m m }
{
  \group_begin:
  \datagidx@parse@formatlabel { #1 }
  \DTLgidxFetchEntry
  \l__datagidx_value_tl
  { \l__datagidx_term_label_tl } { #2 }
  \datatool_if_null:NF \l__datagidx_value_tl
  {
    \datagidxlink { \l__datagidx_term_label_tl }
    {
      \__datagidx_use_entry:Nn \Useentry
      { \xmakefirstuc { \l__datagidx_value_tl } }
    }
  }
}
\group_end:
}
\MFUaddmap { \useentry } { \Useentry }
```

`\USEentry`

`\USEentry{<label>}{<field>}`

As `\useentry`, but make the whole term upper case.

```
\NewDocumentCommand \USEEntry { m m }
{
  \group_begin:
  \datagidx@parse@formatlabel { #1 }
  \DTLgidxFetchEntry
  \l__datagidx_value_tl
  { \l__datagidx_term_label_tl } { #2 }
  \datatool_if_null:NF \l__datagidx_value_tl
  {
    \datagidxlink { \l__datagidx_term_label_tl }
    {
      \__datagidx_use_entry:Nn \USEEntry
      { \text_uppercase:n { \l__datagidx_value_tl } }
    }
  }
  \group_end:
}
\MFUexcl { \USEEntry }
```

`\useentrynl`

`\useentrynl{<label>}{<field>}`

Fetch and use the given field for the given entry without creating a hyperlink.

```
\NewDocumentCommand \useentrynl { m m }
{
  \group_begin:
  \datagidx@parse@formatlabel { #1 }
  \DTLgidxFetchEntry
  \l__datagidx_value_tl
  { \l__datagidx_term_label_tl } { #2 }
  \datatool_if_null:NF \l__datagidx_value_tl
  {
    \__datagidx_use_entry:Nn \useentrynl
    { \l__datagidx_value_tl }
  }
  \group_end:
}
```

`\Useentrynl`

`\Useentrynl{<label>}{<field>}`

As `\useentry`, but capitalise the first word.

```
\NewDocumentCommand \Useentrynl { m m }
{
  \group_begin:
  \datagidx@parse@formatlabel { #1 }
  \DTLgidxFetchEntry
```

```

    \l_datagidx_value_tl
    { \l_datagidx_term_label_tl } { #2 }
\datatool_if_null:NF \l_datagidx_value_tl
{
  \__datagidx_use_entry:Nn \Useentrynl
  { \xmakefirstuc { \l_datagidx_value_tl } }
}
\group_end:
}
\MFUaddmap { \useentrynl } { \Useentrynl }

```

`\USEentrynl{<label>}{<field>}`

`\USEentrynl`

As `\useentry`, but make the whole term upper case.

```

\NewDocumentCommand \USEentrynl { m m }
{
  \group_begin:
  \datagidx@parse@formatlabel { #1 }
  \DTLgidxFetchEntry
  \l_datagidx_value_tl
  { \l_datagidx_term_label_tl } { #2 }
  \datatool_if_null:NF \l_datagidx_value_tl
  {
    \__datagidx_use_entry:Nn \USEentrynl
    { \text_uppercase:n { \l_datagidx_value_tl } }
  }
  \group_end:
}
\MFUexcl { \USEentrynl }

```

Short cuts to common fields.

`\gls`

```
\newrobustcmd*{\gls}[1]{\useentry{#1}{Text}}
```

`\glspl`

```
\newrobustcmd*{\glspl}[1]{\useentry{#1}{Plural}}
```

`\Gls`

```
\newrobustcmd*{\Gls}[1]{\Useentry{#1}{Text}}
\MFUaddmap { \gls } { \Gls }

```

`\Glspl`

```
\newrobustcmd*{\Glspl}[1]{\Useentry{#1}{Plural}}
\MFUaddmap { \glspl } { \Glspl }

```

`\glsnl`

```
\newrobustcmd*{\glsnl}[1]{\useentrynl{#1}{Text}}
```

```

\glsplnl
\newrobustcmd*{\glsplnl}[1]{\useentrynl{#1}{Plural}}

\Glsnl
\newrobustcmd*{\Glsnl}[1]{\Useentrynl{#1}{Text}}
\MFUaddmap { \glsnl } { \Glsnl }

\Glsplnl
\newrobustcmd*{\Glsplnl}[1]{\Useentrynl{#1}{Plural}}
\MFUaddmap { \glsplnl } { \Glsplnl }

\glssym
\newrobustcmd*{\glssym}[1]{\useentry{#1}{Symbol}}

\Glsym
\newrobustcmd*{\Glsym}[1]{\Useentry{#1}{Symbol}}
\MFUaddmap { \glssym } { \Glsym }

```

23.1 Using Acronyms

```

\DTLgidxFormatAcr{<label>}{<long field>}{<short
field>}

```

```

\DTLgidxFormatAcr
\newcommand*{\DTLgidxFormatAcr}[3]{%
\DTLgidxAcrStyle{\glsdispenry{#1}{#2}}{\useentry{#1}{#3}}%
}

```

```

\DTLgidxFormatAcr{<label>}{<long field>}{<short
field>}

```

```

\DTLgidxFormatAcrUC
As previous but capitalise first word.
\newcommand*{\DTLgidxFormatAcrUC}[3]{%
\DTLgidxAcrStyle{\Glsdispenry{#1}{#2}}{\useentry{#1}{#3}}%
}

```

```

\acr
\newrobustcmd*{\acr}[1]{%
\ifentryused{#1}%
{\useentry{#1}{Short}}%
{\DTLgidxFormatAcr{#1}{Long}{Short}}%
}

```

```

\acrpl
\newrobustcmd*{\acrpl}[1]{%
\ifentryused{#1}%
}

```

```

        {\useentry{#1}{ShortPlural}}%
        {\DTLgidxFormatAcr{#1}{LongPlural}{ShortPlural}}%
    }

\Acr
\newrobustcmd*{\Acr}[1]{%
  \ifentryused{#1}%
  {\Useentry{#1}{Short}}%
  {\DTLgidxFormatAcrUC{#1}{Long}{Short}}%
}
\MFUaddmap { \acr } { \Acr }

\Acrpl
\newrobustcmd*{\Acrpl}[1]{%
  \ifentryused{#1}%
  {\Useentry{#1}{ShortPlural}}%
  {\DTLgidxFormatAcrUC{#1}{LongPlural}{ShortPlural}}%
}
\MFUaddmap { \acrpl } { \Acrpl }

```

24 Displaying Glossaries, Lists of Acronyms, Indices

```

\printtermsstartpar
  \newcommand{\printtermsstartpar}{\par}

\datagidx@prestart Version 3.0: replaced \datagidx@prestart with:
  \tl_new:N \l__datagidx_prestart_tl

printterms@setupmulticol
\newcommand*{\printterms@setupmulticol}{
  \tl_if_empty:NTF \l__datagidx_post_heading_tl
  {
    \tl_set:Nx \l__datagidx_prestart_tl
    {
      \exp_not:N \l__datagidx_heading_tl
      { \exp_not:N \l__datagidx_title_tl }
      \exp_not:N \begin
      { \l__datagidx_multicols_tl }
      { \int_use:N \l__datagidx_columns_int }
    }
  }
}

```

```

        [ \exp_not:N \l__datagidx_post_heading_tl ]
    }
}
\l_set:Nx \datagidx@end
{
    \exp_not:N \end { \l__datagidx_multicols_tl }
}
}

```

\printterms@setuptwocol

```

\newcommand*{\printterms@setuptwocol}{
    \l_set:Nn \l__datagidx_prestart_tl
    {
        \twocolumn
        [
            \l__datagidx_heading_tl
            { \l__datagidx_title_tl }
            \l__datagidx_post_heading_tl
        ]
    }
    \if@twocolumn
        \l_clear:N \datagidx@end
    \else
        \l_set:Nn \datagidx@end
        { \printtermsrestoreonecolumn }
    \fi
}

```

inttermsrestoreonecolumn

```

\newcommand{\printtermsrestoreonecolumn}{\onecolumn}

```

\printterms[options]

\printterms

Print the list of terms

```

\NewDocumentCommand \printterms { o }
{
    \group_begin:

```

Ensure that sorting has a global effect:

```

    \bool_set_true:N \l__datatool_db_global_bool

```

Initialise key list for style:

```

    \clist_clear:N \l__datagidx_styles_clist

```

Set options. If the database key is used, this will set \l__datagidx_default_database_tl

```

    \IfValueT { #1 }
    {
        \keys_set_filter:nnn
            { datatool / index } { general } { #1 }
    }

```

```

    \l_datagidx_remainder_tl
\tl_if_empty:NF \l_datagidx_remainder_tl
{
  \PackageError { datagidx }
  {
    Invalid ~ \token_to_str:N \printterms \c_space_tl option(s): ~
    \tl_to_str:N \l_datagidx_remainder_tl
  }
  {
    The ~ listed ~ option ~ or ~ options ~ can't ~ be ~ passed ~
    to ~ \token_to_str:N \printterms . \MessageBreak
    Try ~ \token_to_str:N \DTLsetup
    { index = { \tl_to_str:N \l_datagidx_remainder_tl } }
  }
}

```

Set the database.

```

\tl_set_eq:NN
  \l_datagidx_term_database_tl
  \l_datagidx_default_database_tl

```

Check if database exists.

```

\DTLifdbexists { \l_datagidx_term_database_tl }
{

```

Provide user the means to access the current database name.

```

\tl_set_eq:NN
  \DTLgidxCurrendb
  \l_datagidx_term_database_tl

```

Get the fields from datagidx:

```

\__datatool_get_row_for_value:xxxTF
{ datagidx }
{ \dtlcolumnindex{datagidx}{Glossary} }
{ \l_datagidx_term_database_tl }
{
  \dtlgetentryfromcurrentrow
  \l_datagidx_title_tl
  {\dtlcolumnindex{datagidx}{Title}}%
  \dtlgetentryfromcurrentrow
  \l_datagidx_heading_tl
  {\dtlcolumnindex{datagidx}{Heading}}%
  \dtlgetentryfromcurrentrow
  \l_datagidx_post_heading_tl
  { \dtlcolumnindex {datagidx} {PostHeading} }
  \dtlgetentryfromcurrentrow
  \l_datagidx_multicols_tl
  { \dtlcolumnindex {datagidx} {MultiCols} }
  \dtlgetentryfromcurrentrow
  \l_datagidx_sort_tl

```

```

    { \dtlcolumnindex {datagidx} {Sort} }
\dtlgetentryfromcurrentrow
  {\datagidx@style}%
  {\dtlcolumnindex{datagidx}{Style}}%
\dtlgetentryfromcurrentrow
  {\datagidx@showgroups}%
  {\dtlcolumnindex{datagidx}{ShowGroups}}%

```

Allow user to override style here.

```

\keys_set_groups:nnV { datatool / index } { print }
  \l__datagidx_styles_clist

```

Do we need to use multicols?

```

\int_case:nnF { \l__datagidx_columns_int }
{
  { \c_one_int }
  {
    \tl_clear:N \l__datagidx_post_heading_tl
    \tl_clear:N \datagidx@postend
  }
  { 2 }
  {
    \ifdatagidxbalance
      \printterms@setupmulticol
    \else
      \printterms@setuptwocol
    \fi
  }
}
{
  \printterms@setupmulticol
}
\tl_set_eq:NN \@dtl@dbname \DTLgidxCurrentdb

```

Set the style

```

\csuse{datagidxshowgroups\datagidx@showgroups}%
\datagidxsetstyle{\datagidx@style}%

```

Now display the glossary/index:

```

\int_compare:nNnT
  { \l__datagidx_columns_int } = { \c_one_int }
{
  \l__datagidx_heading_tl
  { \l__datagidx_title_tl }
  \l__datagidx_post_heading_tl
}
\datagidx@do@sort
\l__datagidx_prestart_tl

```

:

```

\printtermsstartpar
\datagidxstart

```

```

\let\DTLgidName\datagidx@invert
\let\DTLgidPlace\datagidx@invert
\let\DTLgidSubject\datagidx@invert
\let\DTLgidOffice\datagidx@invert
\DTLgidxForeachEntry
{
  \datagidxitem
}
\datagidxend
\datagidx@postend
}
{
  \PackageError { datagidx }
  {
    \token_to_str:N \printterms : ~
    Unable ~ to ~ access ~ `Glossary' ~
    column ~ in ~ ` datagidx ' ~
    database ~ matching ~ ` \l__datagidx_term_database_tl '
  }
  { }
}
}
}
{

```

Database doesn't exist.

```

\PackageError{datagidx}%
{
  Glossary/index ~ database ~
  ` \l__datagidx_term_database_tl ' ~ doesn't ~ exist
}
{
  You ~ must ~ define ~ the ~ glossary/index ~
  database ~ before ~ you ~ can ~ use ~ it.
}
}
\expandafter \group_end: \if@endpe \@doendpe \fi
}

```

\datagidx@getgroup Version 3.0: removed \datagidx@getgroup

\DTLgidxGroupHeaderTitle Produce the group title from the group label.

```

\newcommand*{\DTLgidxGroupHeaderTitle}[1]{%
  \cs_if_exist_use:CF
  { datagidx #1 name }
  { #1 }
}

```

\DTLgidxForeachEntry

\DTLgidxForeachEntry{<body>}

Iterate through the current database, but only do *<body>* if there is a location or cross-reference.

```
\NewDocumentCommand \DTLgidxForeachEntry { m }
{
  \tl_clear:N \datagidxprevgroup
  \DTLmapdata [ name = \DTLgidxCurrentdb , read-only ]
  {
```

Don't trigger an error if a column key is undefined. This may simply mean that the column was only added for some glossary/index databases and not others. The return value will be null in that case.

```
    \exp_args:NV \__datatool_map_get_values_noerr:n
    \DTLgidxAssignList
    \__datagidx_filter:T
  {
```

Iterate through top-level entries.

```
    \datatool_if_null:NT \Parent
  {
```

The letter group needs to be expanded to allow non-letter groups to merge if they expand to a word (such as Symbols) regardless of their argument.

```
    \legacy_if:nT { datagidxshowgroups }
    {
      \tl_set:Ne \datagidxcurrentgroup
      { \datagidxcurrentgroup }
    }
  \datagidx@doifdisplayed
  {
    \seq_gput_right:NV
    \g__datagidx_refd_labels_seq
    \Label
```

Initialise level.

```
    \int_set_eq:NN \datagidx@level \c_one_int
    #1
    \cs_gset_eq:NN \datagidxprevgroup \datagidxcurrentgroup
  }
}
}
}
```

gidx@checklocationchange Version 3.0: Removed \dtlgidx@checklocationchange

`\datagidx@doifdisplayed{<body>}`

`\datagidx@doifdisplayed`

Do *<body>* if entry should appear in the glossary/index. `\Location`, `\See` and `\SeeAlso` must be set before use.

```

\newcommand{\datagidx@doifdisplayed}[1]{
  \__datagidx_unwrap_location:N \Location
  \DTLifnull \Location
  {
    \datatool_if_null_or_empty:NTF \See
    {
      \datatool_if_null_or_empty:NF \SeeAlso { #1 }
    }
  }
}

```

See is not null, but have any of the cross-referenced items been used?

```

\clist_map_inline:Nn \See
{

```

Does the cross-referenced term exist?

```

  \iftermexists { ##1 }
  {

```

Has it been used?

```

    \ifentryused { ##1 }
    {
      #1

```

Break out of loop.

```

      \clist_map_break:
    }
  { }
}
{ }
}
}
}
{ #1 }
}

```

```

\datagidx@level Keep track of current level
\newcount\datagidx@level

\ExplSyntaxOff

```

25 databib.sty

25.1 Package Declaration

```

\NeedsTeXFormat{LaTeX2e}

```

Rollback releases:

```

\DeclareRelease{v2.32}{2019-09-27}{databib-2019-09-27.sty}
\DeclareCurrentRelease{v3.4}{2025-04-03}

```

Declare package:

\ProvidesPackage{databib}[2025/04/03 v3.4 (NLCT)]

Version 3.0: no longer using xkeyval.

\andname Version 3.0: removed definition of \andname (datatool-base now provides \DTLandname)

25.2 Package Options

\ExplSyntaxOn

\dtlibib@style The default bib style. Version 3.0 replaced \dtlibib@style with

```
\tl_new:N \l__databib_style_tl
\tl_set:Nn \l__databib_style_tl { plain }
```

Provide option to run bibtex from the shell escape. Off by default.

```
\bool_new:N \l__databib_auto_build_bool
\bool_set_false:N \l__databib_auto_build_bool
\cs_new:Nn \__databib_auto_build:n
{
  \bool_if:NT \l__databib_auto_build_bool
  {
    \sys_if_shell:TF
    {
      \IfFileExists { #1.aux }
      {
        \sys_shell_now:e { bibtex ~ #1 }
      }
      {
        \PackageWarning { databib }
        {
          File ~ `#1' ~ does ~ not ~ exist. ~
          Rerun ~ may ~ be ~ required
        }
      }
    }
  }
  {
    \PackageWarning { databib }
    {
      Can't ~ run ~ `bibtex #1`: shell ~ not ~ enabled
    }
  }
}
}
\keys_define:nn { datatool }
{
  style .choices:nn = { plain, abbrev, alpha }
  { \tl_set_eq:NN \l__databib_style_tl \l_keys_choice_tl } ,
  auto .bool_set:N = \l__databib_auto_build_bool ,
}
```

Switch off \LaTeX 3 syntax to prevent interference with package loading.

```
\ExplSyntaxOff
  Process options:
\IfPackageLoadedTF{datatool}
{
  \ProcessKeyOptions[datatool]
}
{
  \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{datatool}}
  \ProcessOptions
}
\RequirePackage{datatool}
```

Switch \LaTeX 3 syntax back on.

```
\ExplSyntaxOn
```

Remove the package option keys so they can't be used with `\DTLsetup` (otherwise they may conflict with `databar` etc).

```
\keys_define:nn { datatool }
{
  style .undefine: ,
  auto .undefine: ,
}
```

25.3 Loading BBL file

`\DTLloadbbl`

```
\DTLloadbib[<bbl file>]{<db name>}{<bib list>}
```

```
\NewDocumentCommand \DTLloadbbl { O{\jobname.bbl} m m }
{
  \bibliographystyle {databib}
```

The code below that writes to the aux file is adapted from the definition of `\bibliographystyle`.

```
\ifx \@begindocumenthook \@undefined
  \bool_if:NT \l_databib_auto_build_bool
  {
    \PackageError { databib }
    {
      \token_to_str:N \DTLloadbbl \c_space_tl
      may ~ only ~ be ~ used ~ in ~ the ~ preamble ~
      with `auto=true'
    }
    {
      Move ~ \token_to_str:N \DTLloadbbl \c_space_tl
      to ~ the ~ preamble ~ or ~ switch ~ off ~ the ~
      `auto' ~ option
    }
  }
```

```

    }
  }
\else
  \__databib_auto_build:n { \c_sys_jobname_str }
  \expandafter \AtBeginDocument \fi
  {
    \if@filesw
      \immediate \write \@auxout { \string \bibdata { #3 } }
    \fi
  }

```

Version 3.0: allow empty name to indicate the default database.

```

\__tl_if_blank:nTF { #2 }
{
  \tl_set_eq:NN \DTLBIBdbname \l_datatool_default_dbname_tl
}
{
  \tl_set:Nx \DTLBIBdbname { \tl_trim_spaces:n { #2 } }
}
\DTLnewdb { \DTLBIBdbname }
\@input@ { #1 }
}

```

`\DTLnewbibrow` `\DTLnewbibrow` adds a new row to the bibliography database. (`\DTLBIBdbname` must be set prior to use to the name of the `datatool` database which must exist. Any check to determine its existence should be performed when `\DTLBIBdbname` is set.)

```

\NewDocumentCommand \DTLnewbibrow { }
{
  \@sDTLnewrow { \DTLBIBdbname }
}

```

`\DTLnewbibitem`

```
\DTLnewbibitem{<key>}{<value>}
```

Adds a new database entry with the given key and value.

```

\NewDocumentCommand \DTLnewbibitem { m m }
{
  \@sDTLnewdbentry { \DTLBIBdbname } { #1 } { #2 }
}

```

`\DTLnewbibliteralitem`

```
\DTLnewbibliteralitem{<key>}{<value>}
```

For use with fields where the value needs detokenizing. The percent is the most awkward. The rest can be detokenize with `\detokenize` but it will need balanced braces if any occur.

```
\NewDocumentCommand \DTLnewbibliteralitem { m }
```

```

{
  \group_begin:
  \char_set_catcode_other:N \%
  \__databib_literal_item:nn { #1 }
}
\cs_new:Nn \__databib_literal_item:nn
{
  \exp_args:NNne
  \group_end:
  \DTLnewbibitem { #1 } { \detokenize { #2 } }
}

```

`\DTLbibsetlongestlabel`

```

\NewDocumentCommand \DTLbibsetlongestlabel { 0 { \DTLBIBdbname } m }
{
  \tl_set:cn { __databib_longest_label_ #1 _ tl } { #2 }
}

```

`\DTLbibgetlongestlabel`

```

\newcommand{\DTLbibgetlongestlabel}[1]{
  \tl_if_exist:cT { __databib_longest_label_ #1 _ tl }
  { \tl_use:c { __databib_longest_label_ #1 _ tl } }
}

\tl_new:N \__databib_longest_label_tl

```

25.4 Predefined text

`\ofname`

```
\providecommand*\ofname}{of}
```

`\inname`

```
\providecommand*\inname}{in}
```

`\etalname`

```
\providecommand*\etalname}{et ~ al.}
```

`\editorname`

```
\providecommand*\editorname}{editor}
```

`\editorsname`

```
\providecommand*\editorsname}{editors}
```

`\volumename`

```
\providecommand*\volumename}{volume}
```

`\numbername`

```
\providecommand*\numbername}{number}
```

`\pagesname`
`\providecommand*\pagesname}{pages}`

`\pagename`
`\providecommand*\pagename}{page}`

`\editionname`
`\providecommand*\editionname}{edition}`

`\techreportname`
`\providecommand*\techreportname}{Technical ~ report}`

`\mscthesishname`
`\providecommand*\mscthesishname}{Master's ~ thesis}`

`\phdthesishname`
`\providecommand*\phdthesishname}{PhD ~ thesis}`

25.5 Displaying the bibliography

`\DTLbibliography{<bib dbname>}`

Displays the bibliography for the database `<bib dbname>` which must have previously been loaded using `\DTLloadbbL`.

```

\DTLbibliography Version 3.0: switched to read-only loop.
\NewDocumentCommand \DTLbibliography { 0{\boolean{true}} m }
{
  \begin{DTLthebibliography} [ #1 ] { #2 }
  \DTLforeachbibentry * [ #1 ] { #2 }
  {
    \DTLbibitem \DTLformatbibentry \DTLendbibitem
  }
  \end{DTLthebibliography}
}

\cs_new:Nn \databib_check_fmt:nT
{
  \tl_if_exist:cTF { DTLformat #1 }
  { #2 }
  {
    \PackageError { databib }
    {
      Don't ~ know ~ how ~ to ~ format ~ bibliography ~
      entries ~ of ~ type ~ ` #1 '
    }
    {
      The ~ current ~ bibliography ~ format ~ doesn't ~ seem ~ to ~

```

```

        support ~ the ~ given ~ entry ~ type
    }
}

```

\DTLformatbibentry

\DTLformatbibentry

Formats the current bib entry.

```

\NewDocumentCommand \DTLformatbibentry { }
{

```

Check format for this type is defined.

```

\datbib_check_fmt:nT { \DBIBentrytype }
{

```

Print information to terminal and log file if in verbose mode.

```

\dtl@message { [ \DBIBcitekey ] }

```

Initialise:

```

\legacy_if_set_false:n { DTLstartsentence }
\legacy_if_set_false:n { DTLmidsentence }
\legacy_if_set_false:n { DTLperiod }

```

Format this entry

```

\tl_use:c { DTLformat \DBIBentrytype }
}
}

```

\gDTLformatbibentry

\gDTLformatbibentry

Global version.

```

\NewDocumentCommand \gDTLformatbibentry { }
{

```

Check format for this type is defined.

```

\datbib_check_fmt:nT { \DBIBentrytype }
{

```

Print information to terminal and log file if in verbose mode.

```

\dtl@message { [ \DBIBcitekey ] }

```

Initialise:

```

\legacy_if_gset_false:n { DTLstartsentence }
\legacy_if_gset_false:n { DTLmidsentence }
\legacy_if_gset_false:n { DTLperiod }

```

Format this entry

```

\tl_use:c { DTLformat \DBIBentrytype }
}
}

```

`\DTLformatthisbibentry`

`\DTLformatthisbibentry{<db>}{<cite key>}`

Just does `\DTLformatbibentry` for a given entry.

```

\NewDocumentCommand \DTLformatthisbibentry { m m }
{
  \tl_set:Nc \DBIBname { \exp_args:Nc \tl_to_str:n { #1 } }
  \tl_set:Nc \DBIBcitekey { \exp_args:Nc \tl_to_str:n { #2 } }
  \edtlgetrowforvalue { \DBIBname }
    { \dtlcolumnindex { \DBIBname } { CiteKey } }
    { \DBIBcitekey }
  \dtl@gathervalues { \DBIBname } { \dtlcurrentrow }
  \tl_set_eq:Nc \DBIBentrytype { @dtl@key@EntryType }
  \DTLformatbibentry
}

```

`\DTLendbibitem` Hook to add extra information at the end of a bibliography item. This does nothing by default.

```
\newcommand*{\DTLendbibitem}{}
```

`\dtl@widest` Define a length to store the widest bib entry label. Version 3.0 replaced `\dtl@widest` with:

```
\dim_new:N \l__databib_widest_dim
```

`\DTLcomputewidestbibentry`

`\DTLcomputewidestbibentry{<conditions>}{<db name>}{<bib label>}{<tl var>}`

Computes the widest bibliography entry over all entries satisfying `<condition>` for the database called `<db name>`, where the bibliography label is formatted according to `<bib label>` and stores the result in the token list variable `<tl var>`. Version 3.0: switched to read-only loop.

```

\NewDocumentCommand \DTLcomputewidestbibentry { m m m m }
{
  \dim_zero:N \l__databib_widest_dim
  \tl_clear:N #4
  \DTLforeachbibentry * [ #1 ] { #2 }
  {
    \datatool_measure_width:Nn \dtl@tmplength { #3 }
    \dim_compare:nNnT
      { \dtl@tmplength } > { \l__databib_widest_dim }
    {
      \dim_set_eq:NN \l__databib_widest_dim \dtl@tmplength
      \tl_set:Nc #4 { #3 }
    }
  }
}

```

\DTLforeachbibentry

```
\DTLforeachbibentry[<condition>]{<db name>}{<body>}
```

```
\DTLforeachbibentry*[<condition>]{<db name>}{<body>}
```

Iterates through the database called *<db name>* and does *<text>* if *<condition>* is met. As with \DTLforeach, the starred version is read only. Version 3.0 bug fix: only locally assign \DBIBCitekey and \DBIBentrytype.

```
\NewDocumentCommand \DTLforeachbibentry { s o m m }
{
  \IfBooleanTF { #1 }
  {
```

Iterate through the database (read only).

```
  \__databib_foreach_entry:Nnnn
  \@sDTLforeach { #2 } { #3 } { #4 }
  }
  {
```

Unstarred version (edits allowed).

```
  \__databib_foreach_entry:Nnnn
  \@DTLforeach { #2 } { #3 } { #4 }
  }
}
```

```
\cs_new:Nn \__databib_foreach_entry:Nnnn
{
```

Store database name.

```
  \tl_set:Nc \DBIBname { \exp_args:Nc \tl_to_str:n { #3 } }
```

Reset row counter.

```
  \int_zero:c { c@DTLbibrow }
```

Condition.

```
  \IfValueTF { #2 }
  {
    \tl_if_empty:nTF { #2 }
    {
      \cs_set_eq:NN \__databib_do_foreach:n \use:n
    }
    {
      \cs_set:Nn \__databib_do_foreach:n
      {
        \ifthenelse { #2 } { ##1 } { }
      }
    }
  }
  {
    \cs_set_eq:NN \__databib_do_foreach:n \use:n
```

```

    }
    #1 { #3 } { }
    {
        \dtl@gathervalues { #3 } { \dtlcurrentrow }
        \tl_set_eq:Nc \DBIBCitekey { @dtl@key@CiteKey }
        \tl_set_eq:Nc \DBIBEntrytype { @dtl@key@EntryType }
        \__databib_do_foreach:n
        {
            \refstepcounter{DTLbibrow}
            #4
        }
    }
}

```

\@DTLforeachbibentry Version 3.0: removed \@DTLforeachbibentry

\@sDTLforeachbibentry Version 3.0: removed \@sDTLforeachbibentry

\gDTLforeachbibentry

\gDTLforeachbibentry[*<condition>*]{*<db name>*}{*<body>*}

\gDTLforeachbibentry* [*<condition>*] { *<db name>* } { *<body>* }

Global version.

```

\NewDocumentCommand \gDTLforeachbibentry { s O{\boolean{true}} m m }
{
  \IfBooleanTF { #1 }
  {
    \__databib_gforeach_entry:Nnnn
    \@sDTLforeach { #2 } { #3 } { #4 }
  }
  {
    \__databib_gforeach_entry:Nnnn
    \@DTLforeach { #2 } { #3 } { #4 }
  }
}

\cs_new:Nn \__databib_gforeach_entry:Nnnn
{

```

Store database name.

```

  \tl_gset:Ne \DBIBname { \exp_args:Ne \tl_to_str:n { #3 } }

```

Reset row counter.

```

  \int_gzero:c { c@DTLbibrow }

```

Iterate through the database.

```

  #1 { #3 }
  { \DBIBCitekey = CiteKey , \DBIBEntrytype = EntryType }

```

```

    {
      \dtl@g@gathervalues { #3 } { \dtlcurrentrow }
      \ifthenelse { #2 }
      {
        \refstepcounter{DTLbibrow}
        #4
      }
      { }
    }
  }
}

```

`\@gDTLforeachbibentry` Version 3.0: removed `\@gDTLforeachbibentry`

`\@sgDTLforeachbibentry` Version 3.0: removed `\@sgDTLforeachbibentry`

DTLbibrow The counter `DTLbibrow` keeps track of the current row in the body of `\DTLforeachbibentry`. (You can't rely on `DTLrowi`, `DTLrowii` and `DTLrowiii`, as `\DTLforeachbibentry` pass the conditions to the optional argument of `\DTLforeach`, but instead uses `\ifthenelse`, which means that `DTLrowi` etc will be incremented, even when the given condition is not met.)

```
\newcounter{DTLbibrow}
```

`\theHDTLbibrow` Keep hyperref happy:

```
\def\theHDTLbibrow{\theHDTLrow.bib.\arabic{DTLbibrow}}%
```

`\DTLbibfield`

```
\DTLbibfield{<field name>}
```

Gets the value assigned to the field `<field name>` for the current row of `\DTLforeachbibentry`. This should be expandable but not fully in case the field contains fragile commands.

```

\newcommand*{\DTLbibfield}[1]{
  \tl_if_exist:cT { @dtl@key@#1 }
  {
    \exp_not:v { @dtl@key@#1 }
  }
}

```

`\DTLbibdatefield`

```
\DTLbibdatefield{<field name>}
```

Used for fields that have dates (Date and UrlDate). This may be redefined to format the date.

```

\newcommand*{\DTLbibdatefield}[1]{
  \DTLbibfield { #1 }
}

```

Provide a means of passing the actual field value to another command. This may be needed for commands that require their argument in a specific format.

\DTLencapbibfield

`\DTLencapbibfield{<cs>}{<field>}`

```
\newcommand*\DTLencapbibfield}[2]{
  \tl_if_exist:cT { @dtl@key@#2 }
  {
    \exp_args:Nv #1 { @dtl@key@#2 }
  }
}
```

\DTLbibfieldlet

`\DTLbibfield{<cs>}{<field name>}`

Gets the value assigned to the field *<field name>* for the current row of `\DTLforeachbibentry` and assigns it to the control sequence *<cs>*. (Doesn't check if the field exists, or if it is being used within `\DTLforeachbibentry`.)

```
\NewDocumentCommand \DTLbibfieldlet { m m }
{
  \tl_set_eq:Nc #1 { @dtl@key@#2 }
}
```

\DTLifbibfieldexists

`\DTLifbibfieldexists{<field name>}{<true part>}{<>false part>}`

Determines whether the given field name exists for the current row of `\DTLforeachbibentry`.

```
\newcommand*\DTLifbibfieldexists}[3]{%
  \tl_if_exist:cTF { @dtl@key@#1 }
  {
    \datatool_if_null:cTF { @dtl@key@ #1 }
    { #3 } { #2 }
  }
  { #3 }
}
```

\DTLifanybibfieldexists

`\DTLifanybibfieldexists{<list of field names>}{<true part>}{<>false part>}`

Determines whether any of the listed fields exist for the current row of `\DTLforeachbibentry`.

```
\NewDocumentCommand \DTLifanybibfieldexists { m m m }
{
  \cs_set_eq:NN \__databib_do:nn \use_ii:nn
  \clist_map_inline:nn { #1 }
  {
```

```

\DTLifbibfieldexists { ##1 }
{
  \cs_set_eq:NN \__databib_do:nn \use_i:nn
  \clist_map_break:
}
{ }
}
\__databib_do:nn { #2 } { #3 }
}

```

`\ifDTLperiod` The conditional `\ifDTLperiod` is used to keep track of any abbreviations ending with a period, this is to ensure that abbreviations aren't followed by a full stop if they already have a full stop terminating the abbreviation.

```

\newif\ifDTLperiod

\regex_new:N \l_databib_end_sentence_regex
\regex_set:Nn \l_databib_end_sentence_regex
{ [\.\?!] \Z }

```

`\DTLcheckendperiod{<string>}`

`\DTLcheckendsperiod`

Checks if `<string>` ends with an end of sentence punctuation mark. This sets `\ifDTLperiod`.

```

\NewDocumentCommand \DTLcheckendsperiod { m }
{
  \regex_match:NnTF \l_databib_end_sentence_regex { #1 }
  { \legacy_if_gset_true:n { DTLperiod } }
  { \legacy_if_gset_false:n { DTLperiod } }
}

```

`\DTLcheckbibfielddendperiod{<label>}`

`\DTLcheckbibfielddendsperiod`

Checks if the bib field `<label>` ends with a full stop. This sets `\ifDTLperiod`.

```

\NewDocumentCommand \DTLcheckbibfielddendsperiod { m }
{
  \exp_args:Ne \DTLcheckendsperiod { \DTLbibfield { #1 } }
}

\cs_new:Nn \databib_do_and_check:n
{
  \legacy_if:nTF { DTLmidsentence }
  { #1 }
  {
    \DTLstartsentencespace
    \text_titlecase:n { #1 }
  }
}

```

```

\DTLcheckendsperiod { #1 }
}
\cs_generate_variant:Nn \databib_do_and_check:n { e }

```

\ifDTLmidsentence

\ifDTLmidsentence

Determine whether we are in the middle of a sentence.
\newif\ifDTLmidsentence

\ifDTLstartsentence

\ifDTLstartsentence

Determine whether we are at the start of a sentence.
\newif\ifDTLstartsentence

\DTLaddperiod

\DTLaddperiod

Adds a full stop and sets \DTLmidsentencefalse, \DTLstartsentencetrue and \DTLperiodfalse.

```

\newcommand*{\DTLaddperiod}{
\ifDTLperiod\else.\fi
\DTLmidsentencefalse
\DTLperiodfalse
\DTLstartsentencetrue
}

```

\DTLaddcomma

\DTLaddcomma

Adds a comma and sets \DTLmidsentencetrue, \DTLperiodfalse and \DTLstartsentencefalse

```

\newcommand*{\DTLaddcomma}{
,~
\DTLmidsentencetrue
\DTLperiodfalse
\DTLstartsentencefalse
}

```

\ExplSyntaxOff

\DTLstartsentencespace Adds a space if at the start of the sentence, otherwise does nothing. (The space between sentences is added this way, rather than in \DTLaddperiod otherwise spurious extra space can occur at the end of the bib item. The spacefactor needs to be set manually, because there's stuff in the way of the previous sentence's full stop and this space which

confuses the inter sentence spacing (and, of course, the previous sentence could have ended with a capital letter.)

```
\newcommand*{\DTLstartsentencespace}{%
\ifDTLstartsentence\spacefactor=\sfcode`\.\relax\space
\fi\DTLstartsentencefalse}
```

`\DTLtwoand` In a list of only two author (or editor) names, the text between the two names is given by `\DTLtwoand`:

```
\newcommand*{\DTLtwoand}{\ \DTLlistand \ }
```

`\DTLlandlast` In a list of author (or editor) names, the text between the penultimate and last name is given by `\DTLlandlast`:

```
\newcommand*{\DTLlandlast}{, \DTLlistand \ }
```

```
\ExplSyntaxOn
```

`\DTLlandnotlast` In a list of author (or editor) names, the text between the names (except the penultimate and last name) is given by `\DTLlandnotlast`:

```
\newcommand*{\DTLlandnotlast}{, ~ }
```

`\dtl@authorcount` Define a integer variable to keep track of the number of authors. Version 3.0: replaced `\dtl@authorcount` with:

```
\int_new:N \l__databib_author_count_int
```

`DTLmaxauthors` The counter `DTLmaxauthors` indicates the maximum number of author names to display, if there are more than that number, `\etalname` is used.

```
\newcounter{DTLmaxauthors}
\setcounter{DTLmaxauthors}{10}
```

`\DTLformatbibnamelist` `\DTLformatbibnamelist{<clist>}{<max>}{<formatting cmd>}`

Generic formatting command for list of names.

```
\NewDocumentCommand \DTLformatbibnamelist { m m m }
{
\int_set:Nn \l__databib_author_count_int
{ \clist_count:n { #1 } }
\int_zero:N \l__datatool_count_int
\int_compare:nNnTF
{ \l__databib_author_count_int } > { #2 }
{
\clist_map_inline:nn { #1 }
{
\int_incr:N \l__datatool_count_int
\int_compare:nNnTF
{ \l__datatool_count_int } = { \c_one_int }
{
\__databib_format_name:Nn #3 { ##1 }
}
}
}
```



```

\DTLstartsentencespace
\exp_args:NV \DTLformatbibnamelist \@dtl@key@Author
{ \c@DTLmaxauthors } { \DTLformatauthor }
}
{ }
}

```

`DTLmaxeditors` The counter `DTLmaxeditors` indicates the maximum number of editor names to display, if there are more than that number, `\etalname` is used.

```

\newcounter{DTLmaxeditors}
\setcounter{DTLmaxeditors}{10}

```

`\DTLformateditorlist` Format a list of editor names (the list is stored in `\@dtl@key@Editor`):

```

\newcommand*{\DTLformateditorlist}{%
\DTLifbibfieldexists {Editor}
{
\DTLstartsentencespace
\exp_args:NV \DTLformatbibnamelist \@dtl@key@Editor
{ \c@DTLmaxeditors } { \DTLformateditor }
, ~
\int_compare:nNnTF
{ \l__datbib_author_count_int } = { \c_one_int }
{
\editorname
\exp_args:NV \DTLcheckendsperiod \editorname
}
{
\editorsname
\exp_args:NV \DTLcheckendsperiod \editorsname
}
}
{ }
}
\ExplSyntaxOff

```

`\DTLpostvon` Space to insert after *(von part)*.

```

\newcommand{\DTLpostvon}{~}

```

`\DTLpostvolnum`

```

\newcommand{\DTLpostvolnum}{:}

```

`\DTLpostpagename`

```

\newcommand{\DTLpostpagename}{~}

```

`\DTLpostvolumename`

```

\newcommand{\DTLpostvolumename}{~}

```

`\DTLpostchaptername`

```

\newcommand{\DTLpostchaptername}{~}

```

```

\DTLpostnumbername
\newcommand{\DTLpostnumbername}{~}

\DTLprecite
\newcommand{\DTLprecite}{~}

\DTLofseries
\newcommand{\DTLofseries}[1]{%
  \ \ofname\ \DTLofseriesfmt{#1}%
}

\DTLofseriesfmt
\newcommand{\DTLofseriesfmt}[1]{\emph{#1}}

\DTLinseries
\newcommand{\DTLinseries}[1]{%
  \ \inname\ #1%
}

\DTLjournalfmt
\newcommand{\DTLjournalfmt}[1]{\emph{#1}}

\DTLinbooktitlefmt
\newcommand{\DTLinbooktitlefmt}[1]{\emph{#1}}

\DTLmanualtitlefmt
\newcommand{\DTLmanualtitlefmt}[1]{\emph{#1}}

\DTLthesistitlefmt
\newcommand{\DTLthesistitlefmt}[1]{\emph{#1}}

\DTLproceedingstitlefmt
\newcommand{\DTLproceedingstitlefmt}[1]{\emph{#1}}

\ExplSyntaxOn

```

```

\DTLformatsurnameonly{<von part>}{<surname>}{<jr
part>}{<forenames>}

```

This is used when only the surname should be displayed. (The final argument, *<forenames>*, is ignored.)

```

\NewDocumentCommand \DTLformatsurnameonly { m m m m }
{
  \tl_if_empty:nF { #1 }
  { #1 \DTLpostvon }
  #2
  \tl_if_empty:nTF { #3 }

```

```

    {
      \DTLcheckendsperiod { #2 }
    }
    {
      , ~ #3
      \DTLcheckendsperiod { #3 }
    }
  }
}

```

\DTLformatforenames

`\DTLformatforenames{<forenames>}`

The format of an author/editor’s forenames. If the forenames occur at the start of sentence, a new sentence space is added. The argument is checked to determine whether it ends with a full stop (sometimes the forenames may include initials.)

```

\NewDocumentCommand \DTLformatforenames { m }
{
  #1
  \DTLcheckendsperiod { #1 }
}

```

\DTLformatabbrvforenames

`\DTLformatabbrvforenames{<forenames>}`

The format of an author/editor’s abbreviated forenames. The initials may or may not end in a full stop depending on the commands governing the format of `\DTLstoreinitials`, so the initials need to be check using `\DTLcheckendsperiod`.

```

\NewDocumentCommand \DTLformatabbrvforenames { m }
{
  \DTLstoreinitials { #1 } \@dtl@tmp
  \@dtl@tmp
  \exp_args:NV \DTLcheckendsperiod \@dtl@tmp
}

```

\DTLformatvon

`\DTLformatvon{<von part>}`

The format of the “von” part. This does nothing if the argument is empty, otherwise it does the argument followed by a non-breakable space.

```

\NewDocumentCommand \DTLformatvon { m }
{
  \tl_if_empty:nF { #1 }
  {
    #1 \DTLpostvon
  }
}

```

`\DTLformatsurname`

`\DTLformatsurname{<surname>}`

The format of an author/editor's surname.

```
\NewDocumentCommand \DTLformatsurname { m }
{
  #1
  \DTLcheckendsperiod { #1 }
}
```

`\DTLformatjr`

`\DTLformatjr{<jr part>}`

The format of the “jr” part. This does nothing if the argument is empty.

```
\NewDocumentCommand \DTLformatjr { m }
{
  \tl_if_empty:nF { #1 }
  {
    , ~ #1
    \DTLcheckendsperiod { #1 }
  }
}
```

`\DTLformatcrossrefeditor` Format cross reference editors:

```
\NewDocumentCommand \DTLformatcrossrefeditor { }
{
  \DTLifbibfieldexists {Editor}
  {
    \DTLstartsencespace
    \int_set:Nn \l__databib_author_count_int
      { \clist_count:N \@dtl@key@Editor }
    \int_zero:N \l__datatool_count_int
    \clist_map_inline:Nn \@dtl@key@Editor
      {
        \int_compare:nNnTF
          { \l__databib_author_count_int } = { \c_one_int }
          {
            \__databib_format_name:Nn
              \DTLformatsurnameonly { ##1 }
          }
      }
    {
      \int_incr:N \l__datatool_count_int
      \int_compare:nNnTF
        { \l__datatool_count_int } = { \c_one_int }
        {
          \__databib_format_name:Nn
            \DTLformatsurnameonly { ##1 }
        }
      }
  }
}
```



```

    }
    \DTLbibfield {Pages}
    \DTLperiodfalse
  }
  { }
}

```

\DTLformatbvolume Format book volume.

```

\NewDocumentCommand \DTLformatbvolume { }
{
  \DTLifbibfieldexists {Volume}
  {
    \legacy_if:nTF { DTLmidsentence }
    {
      \volumename
    }
    {
      \DTLstartsentencespace
      \text_titlecase_first:n { \volumename }
    }
    \DTLpostvolumename
    \DTLbibfield {Volume}
    \DTLifbibfieldexists {Series}
    {
      \DTLofseries { \DTLbibfield{Series} }
      \DTLcheckbibfieldendsperiod {Series}
    }
    {
      \DTLcheckbibfieldendsperiod {Volume}
    }
  }
  { }
}

```

\DTLformatchapterpages Format chapter and pages:

```

\NewDocumentCommand \DTLformatchapterpages { }
{
  \DTLifbibfieldexists {Chapter}
  {
    \DTLifbibfieldexists {Type}
    {
      \DTLstartsentencespace
      \DTLbibfield {Type}
    }
    {
      \DTLstartsentencespace
      \chaptername
    }
  }
  \DTLpostchaptername
  \DTLbibfield {Chapter}
}

```

```

\DTLifbibfieldexists {Pages}
{ \DTLaddcomma }
{
  \DTLcheckbibfieldendsperiod {Chapter}
}
}
{ }
\DTLstartsentencespace
\DTLformatpages
}

```

\DTLformatpages Format pages:

```

\NewDocumentCommand \DTLformatpages { }
{
  \DTLifbibfieldexists{Pages}
  {
    \DTLstartsentencespace
    \exp_args:Ne \DTLifnumerical { @\DTLbibfield{Pages} }
    { \pagename } { \pagesname }
    \DTLpostpagename
    \DTLbibfield {Pages}
    \DTLcheckbibfieldendsperiod {Pages}
  }
  { }
}

```

\DTLformatnumberseries Format number and series (of book)

```

\NewDocumentCommand \DTLformatnumberseries { }
{
  \DTLifbibfieldexists {Volume}
  { }
  {
    \DTLifbibfieldexists {Number}
    {
      \legacy_if:nTF { DTLmidsentence }
      {
        \numbername
      }
      {
        \DTLstartsentencespace
        \text_titlecase_first:n { \numbername }
      }
    }
    \DTLpostnumbername
    \DTLbibfield {Number}
    \DTLifbibfieldexists {Series}
    {
      \DTLinseries { \DTLbibfield {Series} }
      \DTLcheckbibfieldendsperiod {Series}
    }
    {

```

```

        \DTLcheckbibfieldendsperiod {Number}
      }
    }
  {
    \DTLifbibfieldexists {Series}
    {
      \DTLstartsencespace
      \DTLbibfield {Series}
      \DTLcheckbibfieldendsperiod {Series}
    }
    { }
  }
}
}
}

```

\DTLformatbookcrossref Format a book cross reference.

```

\NewDocumentCommand \DTLformatbookcrossref { }
{
  \DTLifbibfieldexists {Volume}
  {
    \legacy_if:nTF { DTLmidsentence }
    {
      \volumename
    }
    {
      \DTLstartsencespace
      \text_titlecase:n { \volumename }
    }
    \DTLpostvolumename
    \DTLbibfield {Volume}
    \c_space_tl \ofname \c_space_tl
  }
  {
    \legacy_if:nTF { ifDTLmidsentence }
    {
      \inname
    }
    {
      \DTLstartsencespace
      \text_titlecase:n { \inname }
    }
    \c_space_tl
  }
  \DTLifbibfieldexists {Editor}
  {
    \DTLformatcrossrefeditor
  }
  {
    \DTLifbibfieldexists {Key}
    {

```

```

        \DTLbibfield {Key}
    }
    {
        \DTLifbibfieldexists {Series}
        {
            \DTLofseriesfmt { \DTLbibfield {Series} }
        }
        { }
    }
}
\DTLprecite
\DTLpcite { \DTLbibfield{CrossRef} }
}

```

formatincollproccrossref Format 'incollections' cross reference.

```

\NewDocumentCommand \DTLformatincollproccrossref { }
{
    \DTLifbibfieldexists {Editor}
    {
        \legacy_if:nTF { DTLmidsentence }
        {
            \inname
        }
        {
            \DTLstartsencespace
            \text_titlecase:n { \inname }
        }
        \c_space_tl
        \DTLformatcrossrefeditor
    }
    {
        \DTLifbibfieldexists {Key}
        {
            \legacy_if:nTF { DTLmidsentence }
            {
                \inname
            }
            {
                \DTLstartsencespace
                \text_titlecase_first:n { \inname }
            }
            \c_space_tl
            \DTLbibfield {Key}
        }
        {
            \DTLifbibfieldexists {BookTitle}
            {
                \legacy_if:nTF { DTLmidsentence }
                {
                    \inname
                }
            }
        }
    }
}

```

```

    }
    {
      \DTLstartsentencespace
      \text_titlecase_first:n { \inname }
    }
    \c_space_tl
    \DTLformatbooktitle { \DTLbibfield {BookTitle} }
  }
  { }
}
}
\DTLprecite
\DTLpcite { \DTLbibfield {CrossRef} }
}

```

\DTLformatinedbooktitle Format editor and booktitle:

```

\NewDocumentCommand \DTLformatinedbooktitle { }
{
  \DTLifbibfieldexists {BookTitle}
  {
    \legacy_if:nTF { DTLmidsentence }
    {
      \inname
    }
    {
      \DTLstartsentencespace
      \text_titlecase_first:n { \inname }
    }
  }
  \c_space_tl
  \DTLifbibfieldexists {Editor}
  {
    \DTLformatteditorlist
    \DTLaddcomma
    \DTLformatbooktitle { \DTLbibfield {BookTitle} }
    \DTLcheckbibfieldendsperiod {BookTitle}
  }
  {
    \DTLformatbooktitle { \DTLbibfield {BookTitle} }
    \DTLcheckbibfieldendsperiod {BookTitle}
  }
}
{ }
}

```

\DTLformatdate Format date.

```

\NewDocumentCommand \DTLformatdate { }
{
  \DTLifbibfieldexists {Date}
  {
    \DTLstartsentencespace

```

```

    \DTLbibdatefield {Date}
  }
  {
  \DTLifbibfieldexists {Year}
  {
    \DTLifbibfieldexists {Month}
    {
      \legacy_if:nTF { DTLmidsentence }
      {
        \DTLbibfield {Month}
      }
      {
        \DTLstartsentencespace
        \text_titlecase:n { \DTLbibfield {Month} }
      }
      \c_space_tl
      \DTLmidsentencefalse
    }
    { }
    \DTLstartsentencespace
    \DTLbibfield {Year}
  }
  {
  \DTLifbibfieldexists {Month}
  {
    \legacy_if:nTF { DTLmidsentence }
    {
      \DTLbibfield {Month}
    }
    {
      \DTLstartsentencespace
      \text_titlecase_first:n { \DTLbibfield {Month} }
    }
    \DTLcheckbibfieldendsperiod {Month}
  }
  { }
  }
}
}

```

DTLformatarticlecrossref Format article cross reference.

```

\NewDocumentCommand \DTLformatarticlecrossref { }
{
  \DTLifbibfieldexists {Key}
  {
    \legacy_if:nTF { DTLmidsentence }
    {
      \inname
    }
    {

```

```

        \DTLstartsentencespace
        \text_titlecase_first:n { \iname }
    }
    \c_space_tl
    \DTLjournalfmt { \DTLbibfield {Key} }
}
{
    \DTLifbibfieldexists {Journal}
    {
        \legacy_if:nTF { DTLmidsentence }
        {
            \iname
        }
        {
            \DTLstartsentencespace
            \text_titlecase_first:n { \iname }
        }
        \c_space_tl
        \DTLjournalfmt { \DTLbibfield{Journal} }
    }
    { }
}
}
\DTLprecite
\DTLpcite { \DTLbibfield{CrossRef} }
}

\DTLpcite
\NewDocumentCommand \DTLpcite { m }
{
    \exp_args:Ne \cite { #1 }
}

\ExplSyntaxOff

\DTLbibdoihome
\newcommand{\DTLbibdoihome}{https://doi.org/}

\DTLbibpubmedhome
\newcommand{\DTLbibpubmedhome}{https://pubmed.ncbi.nlm.nih.gov/}

\DTLbibdoitag
\newcommand{\DTLbibdoitag}{\textsc{doi}: }

\DTLbibpubmedtag
\newcommand{\DTLbibpubmedtag}{\textsc{pmid}: }

\DTLbiburldate{\DTLbiburldate{\<date>}}
\DTLbiburldate

```

Used for UrlDate field.

```
\newcommand*{\DTLbiburldate}[1]{%  
  \space (\DTLbibaccessedname : #1)%  
}
```

\DTLbibprints

```
\DTLbibprints{eprint}{eprint-type}
```

Used for Eprints field.

```
\newcommand*{\DTLbibprints}[2]{%  
  \ifdef\href  
    {\href{#1}{#2}}%  
    {%  
      #2: % space intended  
      \ifdef\url{\url{#1}}{\texttt{#1}}%  
    }%  
  }  
  
\ExplSyntaxOn
```

\DTLbibdoi

```
\DTLbibdoi{doi}
```

Used for DOI field, which should now have its content sanitized.

```
\newcommand*{\DTLbibdoi}[1]{  
  \DTLbibdoitag  
  \cs_if_exist:NTF \href  
  {  
    \exp_args:Ne \href { \DTLbibdoihome #1 } { \nolinkurl { #1 } }  
  }  
  {  
    \cs_if_exist:NTF \url  
    { \url { #1 } } { \texttt { #1 } }  
  }  
}
```

\DTLbiburl

```
\DTLbiburl{url}
```

Used for Url field, which should now have its content sanitized.

```
\newcommand*{\DTLbiburl}[1]{  
  \cs_if_exist:NTF \url  
  { \url { #1 } }  
  { \texttt { #1 } }  
}
```

\DTLbibaccessedname

```
\newcommand*{\DTLbibaccessedname}{accessed}
```

`\DTLbibpubmed{<id>}`

`\DTLbibpubmed`

Used for PubMed field.

```
\newcommand*{\DTLbibpubmed}[1]{
  \DTLbibpubmedtag
  \cs_if_exist:NTF \href
    { \exp_args:Ne \href { \DTLbibpubmedhome #1 } { #1 } }
    { #1 }
}
```

`\DTLbibformatdigital` Format the digital elements.

```
\NewDocumentCommand \DTLbibformatdigital { }
{
  \DTLifbibfieldexists {PubMed}
  {
    \exp_args:Ne \DTLbibpubmed { \DTLbibfield { PubMed } }
    \legacy_if_set_true:n { DTLmidsentence }
  }
  { }
  \DTLifbibfieldexists {DOI}
  {
    \legacy_if:nT { DTLmidsentence }
    {
      \DTLaddcomma
    }
    \exp_args:Ne \DTLbibdoi { \DTLbibfield { DOI } }
    \legacy_if_set_true:n { DTLmidsentence }
  }
  { }
  \DTLifbibfieldexists {Url}
  {
    \legacy_if:nT { DTLmidsentence }
    {
      \DTLaddcomma
    }
    \exp_args:Ne \DTLbiburl { \DTLbibfield { Url } }
    \DTLifbibfieldexists {UrlDate}
    {
      \DTLbiburldate { \DTLbibdatefield { UrlDate } }
    }
    { }
    \legacy_if_set_true:n { DTLmidsentence }
  }
  { }
  \DTLifbibfieldexists {Eprints}
  {
    \legacy_if:nT { DTLmidsentence }
    {
      \DTLaddcomma
    }
  }
}
```

```

    }
    \exp_args:Nee \DTLbibprints
    { \DTLbibfield { Eprints } }
    {
      \tl_if_exist:NTF \@dtl@key@EprintType
      { \exp_not:V \@dtl@key@EprintType } { eprint }
    }
    \legacy_if_set_true:n { DTLmidsentence }
  }
  { }
}

```

25.5.1 ifthen conditionals

The conditionals defined in this section may be used in the optional argument of `\DTLforeachbibentry`. They may also be used in the first argument of `\ifthenelse`, but only if the command occurs within the body of `\DTLforeachbibentry`. NB these commands need to expand.

```
\DTLbibfieldexists{<field label>}
```

`\DTLbibfieldexists`

Checks if named bib field exists for current entry

```

\newcommand*{\DTLbibfieldexists}[1]{%
  \TE@throw
  \noexpand \dtl@testbibfieldexists {#1}
  \noexpand \if@dtl@condition
}

```

`\dtl@testbibfieldexists`

```

\newcommand*{\dtl@testbibfieldexists}[1]{%
  \DTLifbibfieldexists {#1}
  { \@dtl@conditiontrue }
  { \@dtl@conditionfalse }
}

```

```
\DTLbibfieldiseq{<field label>}{<value>}
```

`\DTLbibfieldiseq`

Checks if the value of the bib field given by `<field label>` is equal to `<value>`. (Uses `\dtlcompare` to determine if the values are equal. If the bib field doesn't exist, the condition is false.)

```

\newcommand*{\DTLbibfieldiseq}[2]{%
  \TE@throw
  \noexpand
  \dtl@testbibfieldiseq {#1} {#2}
  \noexpand\if@dtl@condition
}

```

`\dtl@testbibfieldiseq`

```
\newcommand*\dtl@testbibfieldiseq}[2]{%
\DTLifbibfieldexists {#1}
{
  \exp_args:NNv \dtlcompare
  \@dtl@tmpcount
  { @dtl@key@ #1 } { #2 }
  \int_if_zero:nTF { \@dtl@tmpcount }
  {
    \@dtl@conditiontrue
  }
  {
    \@dtl@conditionfalse
  }
}
{
  \@dtl@conditionfalse
}
}
```

`\DTLbibfieldislt{<field label>}{<value>}`

`\DTLbibfieldislt`

Checks if the value of the bib field given by *<field label>* is less than *<value>*. (If the bib field doesn't exist, the condition is false.)

```
\newcommand*\DTLbibfieldislt}[2]{%
\TE@throw
\noexpand \dtl@testbibfieldislt { #1 } { #2 }
\noexpand \if@dtl@condition
}
```

`\dtl@testbibfieldislt`

```
\newcommand*\dtl@testbibfieldislt}[2]{%
\DTLifbibfieldexists {#1}
{
  \exp_args:NNv \dtlcompare
  \@dtl@tmpcount
  { @dtl@key@ #1 } { #2 }
  \int_compare:nNnTF { \@dtl@tmpcount } = { -1 }
  {
    \@dtl@conditiontrue
  }
  {
    \@dtl@conditionfalse
  }
}
{
  \@dtl@conditionfalse
}
}
```

```
}
```

```
\DTLbibfieldisle{<field label>}{<value>}
```

```
\DTLbibfieldisle
```

Checks if the value of the bib field given by *<field label>* is less than or equal to *<value>*. (If the bib field doesn't exist, the condition is false.)

```
\newcommand*\DTLbibfieldisle[2]{%  
  \TE@throw  
  \noexpand \dtl@testbibfieldisle { #1 } { #2 }  
  \noexpand \if@dtl@condition  
}
```

```
\dtl@testbibfieldisle
```

```
\newcommand*\dtl@testbibfieldisle[2]{%  
  \DTLifbibfieldexists {#1}  
  {  
    \exp_args:NNv \dtlcompare  
    \@dtl@tmpcount  
    { @dtl@key@ #1 } { #2 }  
    \int_compare:nNnTF { \@dtl@tmpcount } < { \c_one_int }  
    {  
      \@dtl@conditiontrue  
    }  
    {  
      \@dtl@conditionfalse  
    }  
  }  
  {  
    \@dtl@conditionfalse  
  }  
}
```

```
\DTLbibfieldisgt{<field label>}{<value>}
```

```
\DTLbibfieldisgt
```

Checks if the value of the bib field given by *<field label>* is greater than *<value>*. (If the bib field doesn't exist, the condition is false.)

```
\newcommand*\DTLbibfieldisgt[2]{%  
  \TE@throw  
  \noexpand \dtl@testbibfieldisgt { #1 } { #2 }  
  \noexpand \if@dtl@condition  
}
```

```
\dtl@testbibfieldisgt
```

```
\newcommand*\dtl@testbibfieldisgt[2]{%  
  \DTLifbibfieldexists {#1}  
  {
```

```

\exp_args:NNv \dtlcompare
  \@dtl@tmpcount
  { @dtl@key@ #1 } { #2 }
\int_compare:nNnTF { \@dtl@tmpcount } = { \c_one_int }
  {
    \@dtl@conditiontrue
  }
  {
    \@dtl@conditionfalse
  }
}
{
  \@dtl@conditionfalse
}
}

```

`\DTLbibfieldisge{<field label>}{<value>}`

`\DTLbibfieldisge`

Checks if the value of the bib field given by *<field label>* is less than or equal to *<value>*. (If the bib field doesn't exist, the condition is false.)

```

\newcommand*{\DTLbibfieldisge}[2]{%
  \TE@throw
  \noexpand \dtl@testbibfieldisge { #1 } { #2 }
  \noexpand \if@dtl@condition
}

```

`\dtl@testbibfieldisge`

```

\newcommand*{\dtl@testbibfieldisge}[2]{%
  \DTLifbibfieldexists {#1}
  {
    \exp_args:NNv \dtlcompare
      \@dtl@tmpcount
      { @dtl@key@ #1 } { #2 }
    \int_compare:nNnTF { \@dtl@tmpcount } > { -1 }
      {
        \@dtl@conditiontrue
      }
      {
        \@dtl@conditionfalse
      }
  }
  {
    \@dtl@conditionfalse
  }
}

```

```
\DTLbibfieldcontains{<field label>}{<sub string>}
```

\DTLbibfieldcontains

Checks if the value of the bib field given by *<field label>* contains *<sub string>*. (If the bib field doesn't exist, the condition is false.)

```
\newcommand*\DTLbibfieldcontains[2]{%
  \TE@throw
  \noexpand \dtl@testbibfieldcontains { #1 } { #2 }
  \noexpand \if@dtl@condition
}
```

dtl@testbibfieldcontains

```
\newcommand*\dtl@testbibfieldcontains[2]{%
  \DTLifbibfieldexists { #1 }
  {
    \exp_args:Nc \dtl@testifsubstring
      { @dtl@key@ #1 } { #2 }
  }
  { \@dtl@conditionfalse }
}
```

25.6 Bibliography Style Macros

The macros defined in this section should be redefined by bibliography styles.

DTLthebibliography (*env.*) How to format the entire bibliography:

```
\NewDocumentEnvironment { DTLthebibliography }
  { 0{\boolean{true}} m }
{
  \tl_clear:N \__databib_longest_label_tl
  \tl_if_eq:nnT { #1 } { \boolean{true} }
  {
    \tl_if_exist:cT { __databib_longest_label_ #1 _ tl }
    {
      \tl_set_eq:Nc
        \__databib_longest_label_tl
        { __databib_longest_label_ #1 _ tl }
    }
  }
  \tl_if_empty:NT \__databib_longest_label_tl
  {
    \int_zero:N \__datatool_count_int
    \@sDTLforeach [ #1 ] { #2 } { }
    { \int_incr:N \__datatool_count_int }
    \tl_set:NV \__databib_longest_label_tl
      \__datatool_count_int
  }
  \exp_args:NnV \begin { thebibliography }
    \__databib_longest_label_tl
}
```

```
}  
{ \end {thebibliography} }
```

`\DTLmonthname` The monthname style. The argument must be a number from 1 to 12. By default, uses `\dtl@monthname`.

```
\newcommand*{\DTLmonthname}[1]{%  
  \dtl@monthname{#1}}
```

Ensure the value is the numeric argument if sorting by month.

```
\dtlSortWordCommands{\let\DTLmonthname\@firstofone}
```

`\dtl@monthname` Full month names:

```
\newcommand*{\dtl@monthname}[1]{%  
  \ifcase#1%  
  \or January%  
  \or February%  
  \or March%  
  \or April%  
  \or May%  
  \or June%  
  \or July%  
  \or August%  
  \or September%  
  \or October%  
  \or November%  
  \or December%  
  \fi  
}
```

`\dtl@abbrvmonthname` Abbreviated months:

```
\newcommand*{\dtl@abbrvmonthname}[1]{%  
  \ifcase#1%  
  \or Jan.%  
  \or Feb.%  
  \or Mar.%  
  \or Apr.%  
  \or May%  
  \or June%  
  \or July%  
  \or Aug.%  
  \or Sept.%  
  \or Oct.%  
  \or Nov.%  
  \or Dec.%  
  \fi  
}
```

`\DTLbibitem` Define how to start a new bibitem:

```
\newcommand*{\DTLbibitem}{\bibitem{\DBIBcitekey}}
```

`\DTLmbibitem` As `\DTLbibitem` but for `\DTLmbibliography`
`\newcommand*\DTLmbibitem}[1]{\bibitem{#1@DBIBCitekey}}`

`\DTLcustombibitem{<item code>}{<ref text>}{<cite key>}`

`\DTLcustombibitem`

As `\DTLbibitem` but user provides *<item code>* to use in place of `\item`. This code can access the cite key using `\DBIBCitekey`. The *<ref text>* is the text associated with this bib item. (For example, if used in an enumerate environment, *<ref text>* might be `\theenumi`.)

```
\NewDocumentCommand \DTLcustombibitem { m m m }
{%
  #1%
  \if@filesw
    \immediate\write\@auxout{\string\bibcite{#3}{#2}}%
  \fi
  \ignorespaces
}
```

`\DTLformatauthor{<von part>}{<surname>}{<junior part>}{<forenames>}`

`\DTLformatauthor`

The format of an author's name.

```
\newcommand*\DTLformatauthor}[4]{%
  \DTLformatforenames { #4 } ~
  \DTLformatvon { #1 }
  \DTLformatsurname { #2 }
  \DTLformatjr { #3 }
}
```

Syntax: `<cs> {<name specs>}` where *<name specs>* is in the form `{<von>}{<surname>}{<jr>}{<forename>}`

```
\cs_new:Nn \__datbib_format_name:Nn
{
  #1 #2
}
```

`\DTLformateditor` The format of an editor's name.

```
\newcommand*\DTLformateditor}[4]{%
  \DTLformatforenames { #4 } ~
  \DTLformatvon { #1 }
  \DTLformatsurname { #2 }
  \DTLformatjr { #3 }
}
```

`\DTLformatedition` The format of an edition:

```
\newcommand*\DTLformatedition}[1]{#1 ~ \editionname}
```

The following will be redefined by the style.

```
\DTLformatarticle The format of an article:
    \newcommand{\DTLformatarticle}{}

\DTLformatbook The format of a book:
    \newcommand{\DTLformatbook}{}

\DTLformatbooklet The format of a booklet:
    \newcommand{\DTLformatbooklet}{}

\DTLformatinbook The format of an “inbook” type:
    \newcommand{\DTLformatinbook}{}

\DTLformatincollection The format of an “incollection” type:
    \newcommand{\DTLformatincollection}{}

\DTLformatinproceedings The format of an “inproceedings” type:
    \newcommand{\DTLformatinproceedings}{}

\DTLformatmanual The format of a manual:
    \newcommand{\DTLformatmanual}{}

\DTLformatmastersthesis The format of a master’s thesis:
    \newcommand{\DTLformatmastersthesis}{}

\DTLformatmisc The format of a miscellaneous entry:
    \newcommand{\DTLformatmisc}{}

\DTLformatphdthesis The format of a Ph.D. thesis:
    \newcommand{\DTLformatphdthesis}{}

\DTLformatproceedings The format of a proceedings:
    \newcommand{\DTLformatproceedings}{}

\DTLformattechreport The format of a technical report:
    \newcommand{\DTLformattechreport}{}

\DTLformatunpublished The format of an unpublished work:
    \newcommand{\DTLformatunpublished}{}

\ExplSyntaxOff
```

Predefined names (these correspond to the standard Bib_TE_X predefined strings of the same name without the leading \DTL):

```
\DTLacmcs
    \newcommand*{\DTLacmcs}{ACM Computing Surveys}
```

```

\DTLacta
\newcommand*\DTLacta}{Acta Informatica}

\DTLcacm
\newcommand*\DTLcacm}{Communications of the ACM}

\DTLibmjrd
\newcommand*\DTLibmjrd}{IBM Journal of Research and Development}

\DTLibmsj
\newcommand*\DTLibmsj}{IBM Systems Journal}

\DTLIEEESE
\newcommand*\DTLIEEESE}{IEEE Transactions on Software Engineering}

\DTLIEEECT
\newcommand*\DTLIEEECT}{IEEE Transactions on Computers}

\DTLIEEECTAD
\newcommand*\DTLIEEECTAD}{IEEE Transactions on Computer-Aided Design
of Integrated Circuits}

\DTLipl
\newcommand*\DTLipl}{Information Processing Letters}

\DTLjacm
\newcommand*\DTLjacm}{Journal of the ACM}

\DTLjcss
\newcommand*\DTLjcss}{Journal of Computer and System Sciences}

\DTLscp
\newcommand*\DTLscp}{Science of Computer Programming}

\DTLsicomp
\newcommand*\DTLsicomp}{SIAM Journal on Computing}

\DTLtocs
\newcommand*\DTLtocs}{ACM Transactions on Computer Systems}

\DTLtods
\newcommand*\DTLtods}{ACM Transactions on Database Systems}

\DTLtog
\newcommand*\DTLtog}{ACM Transactions on Graphics}

\DTLtoms
\newcommand*\DTLtoms}{ACM Transactions on Mathematical Software}

```

`\DTLtoois`

```
\newcommand*\DTLtoois}{ACM Transactions on Office Information  
Systems}
```

`\DTLtoplas`

```
\newcommand*\DTLtoplas}{ACM Transactions on Programming Languages  
and Systems}
```

`\DTLtcs`

```
\newcommand*\DTLtcs}{Theoretical Computer Science}
```

`\DTLresetpredefined`

```
\newcommand*\DTLresetpredefined}{%  
  \renewcommand*\DTLacmcs}{ACM Computing Surveys}  
  \renewcommand*\DTLacta}{Acta Informatica}  
  \renewcommand*\DTLcacm}{Communications of the ACM}  
  \renewcommand*\DTLibmjrd}{IBM Journal of Research and Development}  
  \renewcommand*\DTLibmsj}{IBM Systems Journal}  
  \renewcommand*\DTLIEEEese}{IEEE Transactions on Software Engineering}  
  \renewcommand*\DTLIEEEetc}{IEEE Transactions on Computers}  
  \renewcommand*\DTLIEEEetcad}{IEEE Transactions on Computer-Aided Design  
of Integrated Circuits}  
  \renewcommand*\DTLipl}{Information Processing Letters}  
  \renewcommand*\DTLjacm}{Journal of the ACM}  
  \renewcommand*\DTLjcss}{Journal of Computer and System Sciences}  
  \renewcommand*\DTLscp}{Science of Computer Programming}  
  \renewcommand*\DTLsicomp}{SIAM Journal on Computing}  
  \renewcommand*\DTLtocs}{ACM Transactions on Computer Systems}  
  \renewcommand*\DTLtods}{ACM Transactions on Database Systems}  
  \renewcommand*\DTLtog}{ACM Transactions on Graphics}  
  \renewcommand*\DTLtoms}{ACM Transactions on Mathematical Software}  
  \renewcommand*\DTLtoois}{ACM Transactions on Office Information  
Systems}  
  \renewcommand*\DTLtoplas}{ACM Transactions on Programming Languages  
and Systems}  
  \renewcommand*\DTLtcs}{Theoretical Computer Science}  
}
```

`\DTLresetpredefinedabbrv`

```
\newcommand*\DTLresetpredefinedabbrv}{%  
  \renewcommand*\DTLacmcs}{ACM Comput.\ Surv.}%  
  \renewcommand*\DTLacta}{Acta Inf.}%  
  \renewcommand*\DTLcacm}{Commun.\ ACM}%  
  \renewcommand*\DTLibmjrd}{IBM J.\ Res.\ Dev.}%  
  \renewcommand*\DTLibmsj}{IBM Syst.-J.}%  
  \renewcommand*\DTLIEEEese}{IEEE Trans. Softw.\ Eng.}%  
  \renewcommand*\DTLIEEEetc}{IEEE Trans.\ Comput.}%  
  \renewcommand*\DTLIEEEetcad}{IEEE Trans.\ Comput.-Aided Design  
Integrated Circuits}%
```

```

\renewcommand*\DTLipl}{Inf.\ Process.\ Lett.}%
\renewcommand*\DTLjacm}{J.~ACM}%
\renewcommand*\DTLjcscs}{J.~Comput.\ Syst.\ Sci.}%
\renewcommand*\DTLscp}{Sci.\ Comput.\ Programming}%
\renewcommand*\DTLsicomp}{SIAM J.~Comput.}%
\renewcommand*\DTLtocs}{ACM Trans.\ Comput.\ Syst.}%
\renewcommand*\DTLtods}{ACM Trans.\ Database Syst.}%
\renewcommand*\DTLtog}{ACM Trans.\ Gr.}%
\renewcommand*\DTLtoms}{ACM Trans.\ Math. Softw.}%
\renewcommand*\DTLtoois}{ACM Trans. Office Inf.\ Syst.}%
\renewcommand*\DTLtoplas}{ACM Trans.\ Prog. Lang.\ Syst.}%
\renewcommand*\DTLtcs}{Theoretical Comput.\ Sci.}%
}

\ExplSyntaxOn

```

25.7 Bibliography Styles

Each bibliography style is set by the command `\dtlbst@<style>`, where `<style>` is the name of the bibliography style.

`\dtlbst@plain` The ‘plain’ style:

```
\newcommand{\dtlbst@plain}{%
```

Set how to format the entire bibliography:

```

\RenewDocumentEnvironment { DTLthebibliography }
{ 0{\boolean{true}} m }
{
  \int_zero:N \l__datatool_count_int
  \@sDTLforeach [ ##1 ] { ##2 } { }
  { \int_incr:N \l__datatool_count_int }
  \exp_args:NnV \begin { thebibliography }
  \l__datatool_count_int
}
{ \end {thebibliography} }

```

Set how to start the bibliography entry:

```

\renewcommand*\DTLbibitem}{\bibitem{\DBIBCitekey}}%
\renewcommand*\DTLmbibitem}[1]{\bibitem{##1@\DBIBCitekey}}%

```

Sets the author name format.

```

\renewcommand*\DTLformatauthor}[4]{
  \DTLformatforenames {##4} ~
  \DTLformatvon {##1}
  \DTLformatsurname {##2}
  \DTLformatjr {##3}
}

```

Sets the editor name format.

```

\renewcommand*\DTLformateditor}[4]{
  \DTLformatforenames {##4} ~

```

```

\DTLformatvon {##1}
\DTLformatsurname {##2}
\DTLformatjr {##3}
}

```

Sets the edition format.

```
\renewcommand*{\DTLformatedition}[1]{##1 ~ \editionname}%
```

Sets the monthname format.

```
\let\DTLmonthname\dtl@monthname
```

Sets other predefined names:

```
\DTLresetpredefined
```

The format of an article.

```

\renewcommand*{\DTLformatarticle}{%
\DTLformatauthorlist
\DTLifbibfieldexists {Author}
{ \DTLaddperiod } { }
\DTLifbibfieldexists {Title}
{
\DTLstartsentencespace
\DTLbibfield {Title}
\DTLcheckbibfieldendsperiod {Title}
\DTLaddperiod
}
{ }
\DTLifbibfieldexists{CrossRef}
{

```

Cross ref field

```

\DTLformatarticlecrossref
\DTLifbibfieldexists {Pages}
{ \DTLaddcomma } { }
\DTLformatpages
\DTLaddperiod
}
{

```

No cross ref field

```

\DTLifbibfieldexists {Journal}
{
\DTLstartsentencespace
\DTLjournalfmt { \DTLbibfield{Journal} }
\DTLcheckbibfieldendsperiod {Journal}
\DTLifanybibfieldexists {Number,Volume,Pages,Month,Year}
{ \DTLaddcomma }
{ \DTLaddperiod }
}
{ }
\DTLformatvolnumpages
\DTLifanybibfieldexists {Volume,Number,Pages}

```

```

    {
      \DTLifanybibfieldexists {Year,Month}
      { \DTLaddcomma }
      { \DTLaddperiod }
      \DTLmidsentencefalse
    }
    { }
    \DTLformatdate
    \DTLifanybibfieldexists {Year,Month}
    { \DTLaddperiod } { }
  }
  \DTLifbibfieldexists {Note}
  {
    \DTLstartsencespace
    \DTLbibfield {Note}
    \DTLcheckbibfieldendsperiod {Note}
    \DTLaddperiod
  }
  { }
}

```

The format of a book.

```

\renewcommand*\DTLformatbook){
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  {
    \DTLformateditorlist
    \DTLifbibfieldexists {Editor}
    {
      \DTLaddperiod
    }
  }
}
\DTLifbibfieldexists {Title}
{
  \DTLstartsencespace
  \DTLformatbooktitle { \DTLbibfield {Title} }
  \DTLcheckbibfieldendsperiod {Title}
}
{ }
\DTLifbibfieldexists{CrossRef}
{

```

Cross ref field

```

  \DTLifbibfieldexists {Title}
  { \DTLaddperiod } { }
  \DTLformatbookcrossref
  \DTLifanybibfieldexists {Edition,Month,Year}

```

```

    { \DTLaddcomma }
    { \DTLaddperiod }
  }
  {
no cross ref field
  \DTLifbibfieldexists {Title}
  {
    \DTLifbibfieldexists {Volume}
    { \DTLaddcomma }
    { \DTLaddperiod }
  }
  { }
  \DTLformatbvolume
  \DTLformatnumberseries
  \DTLifanybibfieldexists {Number, Series, Volume}
  { \DTLaddperiod } { }
  \DTLifbibfieldexists {Publisher}
  {
    \DTLstartsentencespace
    \DTLbibfield {Publisher}
    \DTLcheckbibfieldendsperiod {Publisher}
    \DTLifbibfieldexists {Address}
    { \DTLaddcomma }
    {
      \DTLifanybibfieldexists {Month, Year}
      { \DTLaddcomma }
      { \DTLaddperiod }
    }
  }
  { }
  \DTLifbibfieldexists{Address}
  {
    \DTLstartsentencespace
    \DTLbibfield {Address}
    \DTLcheckbibfieldendsperiod {Address}
    \DTLifanybibfieldexists {Month, Year}
    { \DTLaddcomma }
    { \DTLaddperiod }
  }
  { }
  }
  \DTLifbibfieldexists{Edition}
  {
    \databib_do_and_check:e
    { \DTLformattedition { \DTLbibfield {Edition} } }
    \DTLifanybibfieldexists { Month, Year }
    { \DTLaddcomma } { \DTLaddperiod }
  }
  { }

```

```

\DTLformatdate
\DTLifanybibfieldexists {Year,Month}
  { \DTLaddperiod } { }
\DTLifbibfieldexists {Note}
  {
    \DTLstartsentencespace
    \DTLbibfield {Note}
    \DTLcheckbibfieldendsperiod{Note}
    \DTLaddperiod
  }
  { }
}

```

The format of a booklet.

```

\renewcommand*{\DTLformatbooklet}{
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  { }
\DTLifbibfieldexists {Title}
  {
    \DTLstartsentencespace
    \DTLbibfield {Title}
    \DTLcheckbibfieldendsperiod {Title}
    \DTLaddperiod
  }
  { }
\DTLifbibfieldexists {HowPublished}
  {
    \DTLstartsentencespace
    \DTLbibfield {HowPublished}
    \DTLcheckbibfieldendsperiod {HowPublished}
    \DTLifanybibfieldexists {Address,Month,Year}
    { \DTLaddcomma } { \DTLaddperiod }
  }
  { }
\DTLifbibfieldexists {Address}
  {
    \DTLstartsentencespace
    \DTLbibfield {Address}
    \DTLcheckbibfieldendsperiod {Address}
    \DTLifanybibfieldexists {Month,Year}
    { \DTLaddcomma } { \DTLaddperiod }
  }
  { }
\DTLformatdate
\DTLifanybibfieldexists {Year,Month}
  { \DTLaddperiod } { }
}

```

```

\DTLifbibfieldexists {Note}
{
  \DTLstartsencespace
  \DTLbibfield{Note}
  \DTLcheckbibfieldendsperiod {Note}
  \DTLaddperiod
}
{ }
}

```

The format of an 'inbook' entry.

```

\renewcommand*\DTLformatinbook
{
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  {
    \DTLifbibfieldexists {Editor}
    {
      \DTLformateditorlist
      \DTLaddperiod
    }
    { }
  }
  \DTLifbibfieldexists {Title}
  {
    \DTLstartsencespace
    \DTLinbooktitlefmt { \DTLbibfield{Title} }
    \DTLcheckbibfieldendsperiod {Title}
  }
  { }
  \DTLifbibfieldexists {CrossRef}
  {

```

Cross ref entry

```

  \DTLifbibfieldexists {Title}
  {
    \DTLifbibfieldexists {Chapter}
    { \DTLaddcomma } { \DTLaddperiod }
  }
  { }
  \DTLformatchapterpages
  \DTLifanybibfieldexists {Chapter,Pages}
  { \DTLaddperiod } { }
  \DTLformatbookcrossref
}
{

```

No cross ref

```

\DTLifbibfieldexists {Title}
{
  \DTLifanybibfieldexists {Chapter,Volume}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatbvvolume
\DTLifanybibfieldexists {Volume,Series}
{
  \DTLifanybibfieldexists {Chapter,Pages}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatchapterpages
\DTLifanybibfieldexists {Chapter,Pages}
{ \DTLaddperiod } { }
\DTLifbibfieldexists {Publisher}
{
  \DTLstartsentencespace
  \DTLbibfield {Publisher}
  \DTLcheckbibfieldendsperiod {Publisher}
  \DTLifbibfieldexists {Address}
  { \DTLaddcomma } { }
}
{ }
\DTLifbibfieldexists{Address}
{
  \DTLstartsentencespace
  \DTLbibfield {Address}
  \DTLcheckbibfieldendsperiod {Address}
}
{ }
}
\DTLifanybibfieldexists {Edition,Month,Year}
{ \DTLaddcomma } { \DTLaddperiod }
\DTLifbibfieldexists {Edition}
{
  \databib_do_and_check:e
  { \DTLformatedition { \DTLbibfield{Edition} } }
  \DTLifanybibfieldexists {Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatdate
\DTLifanybibfieldexists {Month,Year}
{ \DTLaddperiod } { }
\DTLifbibfieldexists {Note}
{
  \DTLstartsentencespace
  \DTLbibfield {Note}
}

```

```

        \DTLcheckbibfieldendsperiod {Note}
        \DTLaddperiod
    }
    { }
}

```

The format of an 'incollection' entry.

```

\renewcommand*{\DTLformatincollection}
{
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  { }
  \DTLifbibfieldexists {Title}
  {
    \DTLstartsentencespace
    \DTLbibfield {Title}
    \DTLcheckbibfieldendsperiod {Title}
    \DTLaddperiod
  }
  { }
  \DTLifbibfieldexists {CrossRef}
  {

```

Cross ref entry

```

    \DTLformatincolprocrossref
    \DTLifanybibfieldexists {Chapter,Pages}
    { \DTLaddcomma } { }
    \DTLformatchapterpages
    \DTLaddperiod
  }
  {

```

No cross ref entry

```

    \DTLformatinedbooktitle
    \DTLifbibfieldexists {BookTitle}
    {
      \DTLifanybibfieldexists
      {Volume, Series, Chapter, Pages, Number}
      { \DTLaddcomma } { \DTLaddperiod }
    }
    { }
    \DTLformatbvvolume
    \DTLifbibfieldexists {Volume}
    {
      \DTLifanybibfieldexists
      {Number, Series, Chapter, Pages}
      { \DTLaddcomma } { \DTLaddperiod }
    }
  }

```

```

    { }
\DTLformatnumberseries
\DTLifanybibfieldexists {Number, Series}
{
  \DTLifanybibfieldexists {Chapter, Pages}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatchapterpages
\DTLifanybibfieldexists {Chapter, Pages}
{ \DTLaddperiod } { }
\DTLifbibfieldexists {Publisher}
{
  \DTLstartsencespace
  \DTLbibfield {Publisher}
  \DTLcheckbibfieldendsperiod {Publisher}
  \DTLifanybibfieldexists {Address, Edition, Month, Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLifbibfieldexists{Address}
{
  \DTLstartsencespace
  \DTLbibfield {Address}
  \DTLcheckbibfieldendsperiod {Address}
  \DTLifanybibfieldexists {Edition, Month, Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLifbibfieldexists {Edition}
{
  \databib_do_and_check:e
  { \DTLformatedition { \DTLbibfield {Edition} } }
  \DTLifanybibfieldexists {Month, Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatdate
\DTLifanybibfieldexists {Month, Year}
{ \DTLaddperiod } { }
}
\DTLifbibfieldexists {Note}
{
  \DTLstartsencespace
  \DTLbibfield {Note}
  \DTLcheckbibfieldendsperiod {Note}
  \DTLaddperiod
}
{ }
}%

```

The format of an 'inproceedings' entry.

```
\renewcommand*{\DTLformatinproceedings}
{
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  { }
  \DTLifbibfieldexists {Title}
  {
    \DTLstartsentencespace
    \DTLbibfield {Title}
    \DTLcheckbibfieldendsperiod {Title}
    \DTLaddperiod
  }
  { }
  \DTLifbibfieldexists {CrossRef}
  {
```

Cross ref entry

```
\DTLformatincollproccrossref
\DTLifbibfieldexists {Pages}
{ \DTLaddcomma } { \DTLaddperiod }
\DTLformatpages
\DTLifbibfieldexists {Pages}
{ \DTLaddperiod } { }
}
{
```

No cross ref

```
\DTLformatinedbooktitle
\DTLifbibfieldexists {BookTitle}
{
  \DTLifanybibfieldexists
  { Volume, Series, Pages, Number, Address, Month, Year }
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatbvvolume
\DTLifbibfieldexists {Volume}
{
  \DTLifanybibfieldexists
  { Number, Series, Pages, Address, Month, Year }
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatnumberseries
\DTLifanybibfieldexists {Number, Series}
{
```

```

\DTLifanybibfieldexists
  {Pages,Address,Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatpages
\DTLifbibfieldexists {Pages}
{
  \DTLifanybibfieldexists {Address,Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLifbibfieldexists {Address}
{
  \DTLstartsentencespace
  \DTLbibfield {Address}
  \DTLcheckbibfieldendsperiod {Address}
  \DTLifanybibfieldexists {Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
  \DTLformatdate
  \DTLifanybibfieldexists {Month,Year}
  { \DTLaddperiod } { }
  \DTLifbibfieldexists {Organization}
  {
    \DTLstartsentencespace
    \DTLbibfield {Organization}
    \DTLcheckbibfieldendsperiod {Organization}
    \DTLifbibfieldexists {Publisher}
    { \DTLaddcomma } { \DTLaddperiod }
  }
  { }
  \DTLifbibfieldexists {Publisher}
  {
    \DTLstartsentencespace
    \DTLbibfield {Publisher}
    \DTLcheckbibfieldendsperiod {Publisher}
    \DTLaddperiod
  }
  { }
}
{
  \DTLifanybibfieldexists {Publisher,Organization}
  { \DTLaddperiod } { }
  \DTLifbibfieldexists {Organization}
  {
    \DTLstartsentencespace
    \DTLbibfield {Organization}
    \DTLcheckbibfieldendsperiod {Organization}
    \DTLifanybibfieldexists {Publisher,Month,Year}
    { \DTLaddcomma } { }
  }
}

```

```

    }
    { }
    \DTLifbibfieldexists {Publisher}
    {
      \DTLstartsentencespace
      \DTLbibfield{Publisher}
      \DTLcheckbibfieldendsperiod {Publisher}
      \DTLifanybibfieldexists {Month,Year}
      { \DTLaddcomma } { \DTLaddperiod }
    }
    { }
    \DTLformatdate
    \DTLifanybibfieldexists {Month,Year}
    { \DTLaddperiod } { }
  }
}
\DTLifbibfieldexists{Note}
{
  \DTLstartsentencespace
  \DTLbibfield {Note}
  \DTLcheckbibfieldendsperiod {Note}
  \DTLaddperiod
}
{ }
}

```

The format of a manual.

```

\renewcommand*{\DTLformatmanual}
{
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  {
    \DTLifbibfieldexists {Organization}
    {
      \DTLstartsentencespace
      \DTLbibfield {Organization}
      \DTLcheckbibfieldendsperiod {Organization}
      \DTLifbibfieldexists {Address}
      {
        \DTLaddcomma
        \DTLbibfield {Address}
        \DTLcheckbibfieldendsperiod {Address}
      }
      { }
    }
    \DTLaddperiod
  }
  { }
}

```

```

}
\DTLifbibfieldexists {Title}
{
  \DTLstartsentencespace
  \DTLmanualtitlefmt { \DTLbibfield{Title} }
  \DTLcheckbibfieldendsperiod {Title}
  \DTLifbibfieldexists {Author}
  {
    \DTLifanybibfieldexists {Organization,Address}
    { \DTLaddperiod } { \DTLaddcomma }
  }
  {
    \DTLifanybibfieldexists
    {Organization,Address,Edition,Month,Year}
    { \DTLaddcomma } { \DTLaddperiod }
  }
}
{ }
\DTLifbibfieldexists {Author}
{
  \DTLifbibfieldexists {Organization}
  {
    \DTLstartsentencespace
    \DTLbibfield{Organization}%
    \DTLcheckbibfieldendsperiod{Organization}%
    \DTLifanybibfieldexists {Address,Edition,Month,Year}
    { \DTLaddcomma } { \DTLaddperiod }
  }
  { }
\DTLifbibfieldexists {Address}
{
  \DTLstartsentencespace
  \DTLbibfield {Address}
  \DTLcheckbibfieldendsperiod {Address}
  \DTLifanybibfieldexists
  {Edition,Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
}
{
  \DTLifbibfieldexists {Organization} { }
  {
    \DTLifbibfieldexists {Address}
    {
      \DTLstartsentencespace
      \DTLbibfield {Address}
      \DTLcheckbibfieldendsperiod {Address}
      \DTLifanybibfieldexists
      {Edition,Month,Year}
    }
  }
}

```

```

        { \DTLaddcomma } { \DTLaddperiod }
      }
    { }
  }
}
\DTLifbibfieldexists {Edition}
{
  \databib_do_and_check:e
  { \DTLformattedition { \DTLbibfield {Edition} } }
  \DTLifanybibfieldexists {Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatdate
\DTLifanybibfieldexists {Month,Year}
{ \DTLaddperiod } { }
\DTLifbibfieldexists {Note}
{
  \DTLstartsentencespace
  \DTLbibfield {Note}
  \DTLcheckbibfieldendsperiod {Note}
  \DTLaddperiod
}
{ }
}

```

The format of a master's thesis.

```

\renewcommand*{\DTLformatmastersthesis}
{
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  { }
  \DTLifbibfieldexists {Title}
  {
    \DTLstartsentencespace
    \DTLbibfield {Title}
    \DTLcheckbibfieldendsperiod {Title}
    \DTLaddperiod
  }
  { }
  \DTLifbibfieldexists{Type}
  {
    \DTLstartsentencespace
    \DTLbibfield {Type}
    \DTLcheckbibfieldendsperiod {Type}
    \DTLifanybibfieldexists
    {School,Address,Month,Year}
  }
}

```

```

    { \DTLaddcomma } { \DTLaddperiod }
  }
  { }
\DTLifbibfieldexists {School}
{
  \DTLstartsentencespace
  \DTLbibfield {School}
  \DTLcheckbibfieldendsperiod {School}
  \DTLifanybibfieldexists
  {Address,Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLifbibfieldexists {Address}
{
  \DTLstartsentencespace
  \DTLbibfield {Address}
  \DTLcheckbibfieldendsperiod {Address}
  \DTLifanybibfieldexists {Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatdate
\DTLifanybibfieldexists {Month,Year}
{ \DTLaddperiod } { }
\DTLifbibfieldexists {Note}
{
  \DTLstartsentencespace
  \DTLbibfield {Note}
  \DTLcheckbibfieldendsperiod {Note}
  \DTLaddperiod
}
{ }
}

```

The format of a miscellaneous entry.

```

\renewcommand*{\DTLformatmisc}
{
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  { }
  \DTLifbibfieldexists {Title}
  {
    \DTLstartsentencespace
    \DTLbibfield {Title}
    \DTLcheckbibfieldendsperiod {Title}
    \DTLifbibfieldexists {HowPublished}
  }
}

```

```

    {
      \DTLaddperiod
    }
    {
      \DTLifanybibfieldexists {Month,Year}
        { \DTLaddcomma } { \DTLaddperiod }
    }
  \DTLmidsentencefalse
}
{ }
\DTLifbibfieldexists {HowPublished}
{
  \DTLstartsentencespace
  \DTLbibfield {HowPublished}
  \DTLcheckbibfieldendsperiod {HowPublished}
  \DTLifanybibfieldexists {Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatdate
\DTLifanybibfieldexists {Month,Year}
{ \DTLaddperiod } { }
\DTLifbibfieldexists {Note}
{
  \DTLstartsentencespace
  \DTLbibfield {Note}
  \DTLcheckbibfieldendsperiod {Note}
  \DTLaddperiod
}
{ }
}

```

The format of a PhD thesis.

```

\renewcommand*{\DTLformatphdthesis}
{
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  { }
  \DTLifbibfieldexists {Title}
  {
    \DTLstartsentencespace
    \DTLthesistitlefmt { \DTLbibfield{Title} }
    \DTLcheckbibfieldendsperiod {Title}
    \DTLaddperiod
  }
  { }
  \DTLifbibfieldexists {Type}
}

```

```

{
  \DTLstartsentencespace
  \DTLbibfield {Type}
  \DTLcheckbibfieldendsperiod {Type}
  \DTLifanybibfieldexists {School,Address,Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLifbibfieldexists {School}
{
  \DTLstartsentencespace
  \DTLbibfield {School}
  \DTLcheckbibfieldendsperiod {School}
  \DTLifanybibfieldexists {Address,Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLifbibfieldexists {Address}
{
  \DTLstartsentencespace
  \DTLbibfield {Address}
  \DTLcheckbibfieldendsperiod {Address}
  \DTLifanybibfieldexists {Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatdate
\DTLifanybibfieldexists {Month,Year}
{ \DTLaddperiod } { }
\DTLifbibfieldexists {Note}
{
  \DTLstartsentencespace
  \DTLbibfield {Note}
  \DTLcheckbibfieldendsperiod {Note}
  \DTLaddperiod
}
{ }
}

```

The format of a proceedings.

```

\renewcommand*\DTLformatproceedings}
{
  \DTLifbibfieldexists {Editor}
  {
    \DTLformateditorlist
    \DTLaddperiod
  }
  {
    \DTLifbibfieldexists {Organization}
    {

```

```

        \DTLstartsencespace
        \DTLbibfield {Organization}
        \DTLcheckbibfieldendsperiod {Organization}
        \DTLaddperiod
    }
    { }
}
\DTLifbibfieldexists {Title}
{
    \DTLstartsencespace
    \DTLproceedingstitlefmt { \DTLbibfield{Title} }
    \DTLcheckbibfieldendsperiod {Title}
    \DTLifanybibfieldexists
    {
        Volume,Number,Address,Editor,Publisher,
        Month,Year
    }
    { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatbvolume
\DTLifbibfieldexists {Volume}
{
    \DTLifanybibfieldexists
    {
        Number,Address,Editor,Publisher,
        Month,Year
    }
    { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatnumberseries
\DTLifbibfieldexists {Number}
{
    \DTLifanybibfieldexists
    {
        Address,Editor,Publisher,Month,Year
    }
    { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLifbibfieldexists {Address}
{
    \DTLstartsencespace
    \DTLbibfield {Address}
    \DTLcheckbibfieldendsperiod {Address}
    \DTLifanybibfieldexists {Month,Year}
    { \DTLaddcomma } { \DTLaddperiod }
    \DTLformatdate
    \DTLifanybibfieldexists {Month,Year}
}

```

```

    { \DTLaddperiod } { }
\DTLifbibfieldexists {Editor}
{
  \DTLifbibfieldexists {Organization}
  {
    \DTLstartsentencespace
    \DTLbibfield {Organization}
    \DTLcheckbibfieldendsperiod {Organization}
    \DTLifbibfieldexists {Publisher}
    { \DTLaddcomma } { \DTLaddperiod }
  }
  { }
}
{ }
\DTLifbibfieldexists {Publisher}
{
  \DTLstartsentencespace
  \DTLbibfield {Publisher}
  \DTLcheckbibfieldendsperiod {Publisher}
  \DTLaddperiod
}
{ }
}
{
no address
\DTLifbibfieldexists {Editor}
{
  \DTLifbibfieldexists {Organization}
  {
    \DTLstartsentencespace
    \DTLbibfield {Organization}
    \DTLcheckbibfieldendsperiod {Organization}
    \DTLifanybibfieldexists {Publisher,Month,Year}
    { \DTLaddcomma } { \DTLaddperiod }
  }
  { }
}
{ }
\DTLifbibfieldexists {Publisher}
{
  \DTLstartsentencespace
  \DTLbibfield {Publisher}
  \DTLcheckbibfieldendsperiod {Publisher}
  \DTLifanybibfieldexists {Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatdate
\DTLifanybibfieldexists {Month,Year}

```

```

    { \DTLaddperiod } { }
  }
\DTLifbibfieldexists {Note}
{
  \DTLstartsencespace
  \DTLbibfield {Note}
  \DTLcheckbibfieldendsperiod {Note}
  \DTLaddperiod
}
{ }
}

```

The format of a technical report.

```

\renewcommand*{\DTLformattechreport}
{
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  { }
\DTLifbibfieldexists {Title}
{
  \DTLstartsencespace
  \DTLbibfield {Title}
  \DTLcheckbibfieldendsperiod {Title}
  \DTLaddperiod
}
{ }
\DTLifbibfieldexists {Type}
{
  \DTLstartsencespace
  \DTLbibfield {Type}
  \DTLcheckbibfieldendsperiod {Type}
  \DTLifbibfieldexists {Number}
  { \DTLpostnumbername } { }
}
{ }
\DTLifbibfieldexists {Number}
{
  \DTLstartsencespace
  \DTLbibfield {Number}
  \DTLcheckbibfieldendsperiod {Number}
}
{ }
\DTLifanybibfieldexists {Type,Number}
{
  \DTLifanybibfieldexists
  {Institution,Address,Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}

```

```

}
{ }
\DTLifbibfieldexists {Institution}
{
  \DTLstartsencespace
  \DTLbibfield {Institution}
  \DTLcheckbibfieldendsperiod {Institution}
  \DTLifanybibfieldexists {Address,Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLifbibfieldexists {Address}
{
  \DTLstartsencespace
  \DTLbibfield {Address}
  \DTLcheckbibfieldendsperiod {Address}
  \DTLifanybibfieldexists {Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatdate
\DTLifanybibfieldexists {Month,Year}
{ \DTLaddperiod } { }
\DTLifbibfieldexists {Note}
{
  \DTLstartsencespace
  \DTLbibfield {Note}
  \DTLcheckbibfieldendsperiod {Note}
  \DTLaddperiod
}
{ }
}

```

The format of an unpublished work.

```

\renewcommand*{\DTLformatunpublished}
{
  \DTLifbibfieldexists {Author}
  {
    \DTLformatauthorlist
    \DTLaddperiod
  }
  { }
  \DTLifbibfieldexists {Title}
  {
    \DTLstartsencespace
    \DTLbibfield {Title}
    \DTLcheckbibfieldendsperiod {Title}
    \DTLaddperiod
  }
  { }
}

```

```

\DTLifbibfieldexists {Note}
{
  \DTLstartsentencespace
  \DTLbibfield {Note}
  \DTLcheckbibfieldendsperiod {Note}
  \DTLifanybibfieldexists {Month,Year}
  { \DTLaddcomma } { \DTLaddperiod }
}
{ }
\DTLformatdate
\DTLifanybibfieldexists {Month,Year}
{ \DTLaddperiod } { }
}

```

End of ‘plain’ style.

```
}

```

`\DTLformatbooktitle`

```
\newcommand*{\DTLformatbooktitle}[1]{\emph{#1}}
```

`\dtlbst@abbrv` Define ‘abbrv’ style. This is similar to ‘plain’ except that some of the values are abbreviated

```
\newcommand{\dtlbst@abbrv}{%
```

Base this style on ‘plain’:

```
\dtlbst@plain
```

Sets the author name format.

```
\renewcommand*{\DTLformatauthor}[4]{
  \DTLformatabbrvforenames { ##4 } ~
  \DTLformatvon { ##1 }
  \DTLformatsurname { ##2 }
  \DTLformatjr { ##3 }
}

```

Sets the editor name format.

```
\renewcommand*{\DTLformateditor}[4]{
  \DTLformatabbrvforenames { ##4 } ~
  \DTLformatvon { ##1 }
  \DTLformatsurname { ##2 }
  \DTLformatjr { ##3 }
}

```

Sets the monthname format.

```
\let\DTLmonthname\dtl@abbrvmonthname
```

Sets other predefined names:

```
\DTLresetpredefinedabbrv
```

End of ‘abbrv’ style.

```
}

```

`\dtl@alpha` Define ‘alpha’ style. This is similar to ‘plain’ except that the labels are strings rather than numerical.

```
\newcommand{\dtl@alpha}{%
```

Base this style on ‘plain’:

```
\dtl@plain
```

Set how to format the entire bibliography:

```
\RenewDocumentEnvironment { DTLthebibliography }
{ 0{\boolean{true}} m }
{
  \dtl@createalphabiblabels { ##1 } { ##2 }
  \exp_args:NnV \begin { thebibliography }
    \g__databib_widest_label_tl
  }
{ \end {thebibliography} }
```

Set how to start the bibliography entry:

```
\renewcommand* \DTLbibitem
{
  \exp_last_unbraced:NNf
  \bibitem
  [
    { \tl_use:c { dtl@biblabel@ \DBIBCitekey } }
  ]
  { \DBIBCitekey }
}
\renewcommand* \DTLmbibitem [1]
{
  \exp_last_unbraced:NNf
  \bibitem
  [
    { \tl_use:c { dtl@biblabel@ \DBIBCitekey } }
  ]
  { ##1 @ \DBIBCitekey }
}
```

End of ‘alpha’ style.

```
}
```

`\@dtl@widestlabel` Version 3.0: replaced `\@dtl@widestlabel` with:

```
\tl_new:N \g__databib_widest_label_tl
```

`\@dtl@thislabel` Version 3.0: replaced `\@dtl@thislabel` with:

```
\tl_new:N \l__databib_label_tl
```

```
\dtl@createalphabiblabels{<condition>}{<db name>}
```

`\dtl@createalphabiblabels`

Constructs the alpha style bib labels for the given database. (Labels are stored in the control sequence `\dtl@biblabel@<citekey>`.) This also sets the widest label.

```
\newcommand*\dtl@createalphabiblabels}[2]{
  \dtl@message { Creating ~ bib ~ labels }
  \group_begin:
    \tl_gclear:N \g__databib_widest_label_tl
    \dim_zero:N \l__databib_widest_dim
```

Version 3.0: switched to read-only loop.

```
\DTLforeachbibentry * [ #1 ] { #2 }
{
  \dtl@message { \DBIBCitekey }
  \DTLifbibfieldexists {Author}
  {
    \__databib_get_alpha_label:NV
    \l__databib_label_tl \@dtl@key@Author
  }
  {
    \DTLifbibfieldexists {Editor}
    {
      \__databib_get_alpha_label:NV
      \l__databib_label_tl \@dtl@key@Editor
    }
    {
      \DTLifbibfieldexists {Key}
      {
        \__databib_get_first_three:Nn
        \l__databib_label_tl { \@dtl@key@Key }
      }
      {
        \DTLifbibfieldexists {Organization}
        {
          \__databib_get_first_three:Nn
          \l__databib_label_tl
          { \@dtl@key@Organization }
        }
        {
          \__databib_get_first_three:Nn
          \l__databib_label_tl
          { \DBIBentrytype }
        }
      }
    }
  }
}
\DTLifbibfieldexists {Year}
{ }
{
  \DTLifbibfieldexists {CrossRef}
  {
    \DTLgetvalueforkey
```

```

        \@dtl@key@Year
        { Year } { #2 } { CiteKey }
        { \@dtl@key@CrossRef }
    }
    { }
}
\DTLifbibfieldexists {Year}
{
    \__databib_get_year_suffix:V \@dtl@key@Year
    \tl_put_right:Ne \l__databib_label_tl
    { \l__databib_year_tl }
}
{ }

```

Version 3.0: replaced `\c@biblabel@{label}` with `\g__databib_label_<label>_int`,
replaced `\@dtl@bibfirst@{label}` with `\g__databib_first_<label>_tl`
and replaced `\dtl@biblabel@{key}` with `\g__databib_key_<key>_tl`

```

\int_if_exist:cTF
{ g__databib_label_ \l__databib_label_tl _int }
{
    \int_compare:nNnT
    { \int_use:c { g__databib_label_ \l__databib_label_tl _int } }
    =
    { \c_one_int }
    {
        \tl_gset:ce
        {
            g__databib_key_
            \tl_use:c { g__databib_first_ \l__databib_label_tl _tl }
            _tl
        }
        { \l__databib_label_tl a }
    }
}
\int_gincr:c
{ g__databib_label_ \l__databib_label_tl _int }
\tl_gset:ce
{ g__databib_key_ \DBIBCitekey _tl }
{
    \l__databib_label_tl
    \int_to_alph:n
    { \int_use:c { g__databib_label_ \l__databib_label_tl _int } }
}
}
{
    \int_new:c { g__databib_label_ \l__databib_label_tl _int }
    \int_gset_eq:cN
    { g__databib_label_ \l__databib_label_tl _int }
    \c_one_int
    \tl_gset_eq:cN
    { g__databib_first_ \l__databib_label_tl _tl }
}

```

```

        \DBIBCitekey
        \tl_gset_eq:cN
          { g__databib_key_ \DBIBCitekey _tl }
          \l__databib_label_tl
      }
\datatool_measure_width:Nn \dtl@tmplength
{ \tl_use:c { g__databib_key_ \DBIBCitekey _tl } }
\dim_compare:nNnT
{ \dtl@tmplength } > { \l__databib_widest_dim }
{
  \dim_set_eq:NN
  \l__databib_widest_dim \dtl@tmplength
  \tl_gset_eq:Nc \g__databib_widest_label_tl
  { g__databib_key_ \DBIBCitekey _tl }
}
}
\group_end:
}

```

`\dtl@listgetalphalabel` Determine the alpha style label from a list of authors/editors (the first argument must be a control sequence (in which the label is stored), the second argument must be the list of names.) Version 3.0: replaced `\dtl@listgetalphalabel` with:

```

\cs_new:Nn \__databib_get_alpha_label:Nn
{
  \group_begin:
  \tl_clear:N \DTLafterinitials
  \tl_clear:N \DTLbetweeninitials
  \tl_clear:N \DTLafterinitialbeforehyphen
  \tl_clear:N \DTLinitialhyphen
  \int_set:Nn \l__databib_author_count_int
  { \clist_count:n { #2 } }
  \int_compare:nNnTF
  { \l__databib_author_count_int } = { \c_one_int }
  {
    \int_compare:nNnTF
    { \tl_count:o { #2 } } = { 4 }
    {
      \exp_last_unbraced:No
      \databib_get_solo_author_initials:nnnnN
      #2 #1
    }
  }
  {
    \exp_args:No \DTLstoreinitials { #2 } #1
  }
}
{
  \tl_clear:N #1
  \int_zero:N \l__datatool_count_int
  \clist_map_inline:nn { #2 }
  {

```

```

\int_compare:nNnTF
  { \tl_count:n { ##1 } } = { 4 }
  {
    \databib_get_author_initials:nnnnN
      ##1 \l__databib_author_initials_tl
    }
  {
    \DTLstoreinitials
      { ##1 } \l__databib_author_initials_tl
    }
\l__put_right:NV #1 \l__databib_author_initials_tl
\int_incr:N \l__datatool_count_int
\int_compare:nNnT
  { \l__datatool_count_int } > { 2 }
  {
    \clist_map_break:
  }
}
}
\exp_args:NNNV
  \group_end:
  \tl_set:Nn #1 #1
}
\cs_generate_variant:Nn \__databib_get_alpha_label:Nn { NV }

```

\dtl@getauthorinitial Get author's initial:

```

\l__new:N \l__databib_author_initials_tl
\cs_new:Nn \databib_get_author_initials:nnnnN
{
  \tl_if_empty:nTF { #1 }
  {
    \DTLstoreinitials { #2 } #5
  }
  {
    \DTLstoreinitials { #1 ~ #2 } #5
  }
}

```

Get label for single author (last argument is control sequence in which to store the label):

```

\cs_new:Nn \databib_get_solo_author_initials:nnnnN
{
  \tl_if_empty:nTF { #1 }
  {
    \DTLstoreinitials { #2 } #5
  }
  {
    \DTLstoreinitials { #1 ~ #2 } #5
  }
}
\int_compare:nNnT
  { \tl_count:N #5 } < { 2 }

```

```

    {
      \__databib_get_first_three:Nn #5 { #1 #2 }
    }
  }

```

`\dtl@get@firstthree` Get first three letters from the given string. Version 3.0: replaced `\dtl@get@firstthree` with:

```

\cs_new:Nn \__databib_get_first_three:Nn
{
  \tl_clear:N #1
  \int_zero:N \l__datatool_count_int
  \exp_args:Nx \text_map_inline:nn { \text_purify:n { #2 } }
  {
    \tl_put_right:Nn #1 { ##1 }
    \int_incr:N \l__datatool_count_int
    \int_compare:nNnT
      { \l__datatool_count_int } = { 3 }
      {
        \text_map_break:
      }
  }
}

```

`\dtl@get@yearsuffix` Get year suffix. Version 3.0: replaced `\dtl@get@yearsuffix` with:

```

\cs_new:Nn \__databib_get_year_suffix:n
{
  \regex_extract_once:NnNF \c_databib_year_suffix_regex
    \l__datatool_tmp_seq
  {
    \seq_get_left:NN
      \l__datatool_tmp_seq
      \l__databib_year_tl
  }
  {
    \tl_clear:N \l__databib_year_tl
  }
}
\cs_generate_variant:Nn \__databib_get_year_suffix:n { V }
\regex_const:Nn \c_databib_year_suffix_regex
{ ( \d \d ) \Z }

```

`\@dtl@year` Version 3.0: replaced `\@dtl@year` with:

```

\tl_new:N \l__databib_year_tl

```

`\DTLbibliographystyle{<style>}`

`\DTLbibliographystyle`

Sets the bibliography style.

```

\NewDocumentCommand \DTLbibliographystyle { m }

```

```

{
  \tl_if_exist:cTF { dtlbst@ #1 }
  {
    \tl_use:c { dtlbst@ #1 }
  }
  {
    \PackageError {databib}
    {
      Unknown ~ bibliography ~ style ~ `#1'
    }
    {}
  }
}
}
%
```

Set the default bibliography style:

```
\DTLbibliographystyle { \l__databib_style_tl }
```

25.8 Multiple Bibliographies

In order to have multiple bibliographies, there needs to be an aux file for each bibliography. The main bibliography is in `\jobname.aux`, but need to provide a means of creating additional aux files.

```
\DTLmultibibs{<list>}
```

`\DTLmultibibs`

This creates an auxiliary file for each name in `<list>`. For example, `\DTLmultibibs{foo,bar}` will create the files `foo.aux` and `bar.aux`.

```

\NewDocumentCommand \DTLmultibibs { m }
{
  \clist_map_inline:nn { #1 }
  {
    \__databib_auto_build:n { ##1 }
    \iow_new:c { g__databib_aux_ ##1 _iow }
    \iow_open:cn { g__databib_aux_ ##1 _iow } { ##1 .aux }
    \tl_new:c { b@ ##1 @ * }
  }
}
}
```

Can only be used in the preamble:

```
\@onlypreamble { \DTLmultibibs }
```

`\@dtl@cite@write`

```

\newcommand{\@dtl@cite@write}[2]{%
  \if@filesw
    \tl_if_exist:cTF { g__databib_aux_ #1 _iow }
    {
      \iow_now:ce { g__databib_aux_ #1 _iow } { #2 }
    }
  }
}
```

```

    }
    {
      \PackageError {databib}
        { multibib ~ `#1' ~ not ~ defined }
        {
          You ~ need ~ to ~ define ~ `#1' ~ in ~
          \token_to_str:N \DTLmultibibs
        }
    }
  \fi
}
\ExplSyntaxOff

```

```
\DTLcite[⟨text⟩]{⟨mbib⟩}{⟨labels⟩}
```

\DTLcite

This is similar to `\cite[⟨text⟩]{⟨labels⟩}`, except 1) the cite information is written to the auxiliary file associated with the multi-bib `⟨mbib⟩` (which must be named in `\DTLmultibibs`) and 2) the cross referencing label is constructed from `⟨mbib⟩` and `⟨label⟩` to allow for the same citation to appear in multiple bibliographies.

```
\newcommand*{\DTLcite}{\@ifnextchar[{\@tempswatrue \dtl@citex}
{\@tempswafalse \dtl@citex[]}}
```

\dtl@citex Adapted from \@citex

```

\def\dtl@citex[#1]#2#3{%
\leavevmode\let\@citea\@empty
\@cite{\@for\@citeb:=#3\do{\@citea
\def\@citea{\penalty \@m \ }%
\edef\@citeb{\expandafter\@firstofone\@citeb\@empty}%
\dtl@cite@write{#2}{\string\citation{\@citeb}}%
\ifundefined{b@#2@\@citeb}{%
\hbox{\reset@font\bfseries ?}}%
\G@refundefinedtrue
\PackageWarning{databib}{Citation ` \@citeb ' for multibib `#2'
undefined}%
}{%
\@cite@ofmt{\csname b@#2@\@citeb \endcsname }%
}%
}}{#1}%
}

```

```
\DTLnocite{⟨mbib⟩}{⟨key list⟩}
```

\DTLnocite

As `\nocite` but uses the aux file associated with `⟨mbib⟩` which must have been defined using `\DTLmultibibs`.

```
\newcommand*{\DTLnocite}[2]{%
```

```

\@bsphack
\ifx\@onlypreamble\document
  \@for\@citeb:=#2\do{%
    \edef\@citeb{\expandafter\@firstofone\@citeb}%
    \@dtl@cite@write{#1}{\string\citation{\@citeb}}%
    \@ifundefined{b@#1@\@citeb}{%
      \G@refundefinedtrue
      \PackageWarning{datbib}{Citation '\@citeb ' undefined for
        multibib `#1'}}{%
    }%
  }%
\else
  \@latex@error{Cannot be used in preamble}\@eha
\fi
\@esphack
}

\ExplSyntaxOn

```

```
\DTLloadmbib{<mbib>}{<db name>}{<bib list>}
```

\DTLloadmbbl

```

\NewDocumentCommand \DTLloadmbbl { m m m }
{
  \@dtl@cite@write { #1 }
  {
    \token_to_str:N \bibstyle { datbib }
    \iow_newline:
    \token_to_str:N \bibdata { #3 }
  }
  \DTLnewdb { #2 }
  \tl_set:Nx \DTLBIBdbname { \exp_args:Ne \tl_to_str:n { #2 } }
  \@input@ { #1 .bib }
}

```

```
\DTLmbibliography[<condition>]{<mbib name>}{<bib dbname>}
```

\DTLmbibliography

Displays the bibliography for the database *<bib dbname>* which must have previously been loaded using `\DTLloadmbbl`, where *<mbib name>* must be listed in `\DTLmultibibs`.

```

\NewDocumentCommand \DTLmbibliography
{ O{\boolean{true}} m m }
{
  \begin {DTLthebibliography} [ #1 ] { #3 }
  \DTLforeachbibentry * [ #1 ] { #3 }
  {

```

```

        \DTLmbibitem { #2 }
        \DTLformatbibentry
        \DTLendbibitem
    }
\end {DTLthebibliography}
}

```

25.9 Sort Support

The author and editor columns will be comma-separated lists with each item in the form `{\von}{\surname}{\jr}{\forenames}`. This means that if the database is sorted by author or editor, the names will be munged together. If it's not sufficient to sort by this, a command is provided for use with the `encap` sort option.

```
\DTLbibsorentencap{<value>}{<col-idx>}{<db-name>}
```

\DTLbibsorentencap

```

\newcommand \DTLbibsorentencap [3]
{
  \bool_lazy_or:nnTF
    { \int_compare_p:nNn { #2 } = { \dtlcolumnindex { #3 } { Author } } }
    { \int_compare_p:nNn { #2 } = { \dtlcolumnindex { #3 } { Editor } } }
  {
    \exp_not:N \DTLbibsorentname
    \clist_use:nn { #1 } { \DTLbibsorentnamesep \DTLbibsorentname }
  }
  { \exp_not:n { #1 } }
}

```

\DTLbibsorentname

```

\newcommand{\DTLbibsorentname}[4]{
  \tl_if_empty:nF { #1 } { #1 ~ }
  #2
  \tl_if_empty:nF { #3 } { , ~ #3 }
  \datatoolpersoncomma
  #4
}

```

\DTLbibsorentnamesep

```

\newcommand{\DTLbibsorentnamesep}{ \datatoolasciend }
\ExplSyntaxOff

```

25.10 Localisation Support

Version 3.0: added localisation support.

```

\RequireDataBibDialect
  \newcommand*\RequireDataBibDialect}[1]{%
  \TrackLangRequireDialect{databib}{#1}%
  }
  \datatool@load@locales{%
  \AnyTrackedLanguages
  {%
  \ForEachTrackedDialect{\@dtl@thisdialect}%
  {%
  \RequireDataBibDialect{\@dtl@thisdialect}%
  }%
  }%
  }%
  }

```

26 databar.sty

Declare package:

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```
\DeclareRelease{v2.32}{2019-09-27}{databar-2019-09-27.sty}
```

```
\DeclareCurrentRelease{v3.4}{2025-04-03}
```

Declare package:

```
\ProvidesPackage{databar}[2025/04/03 v3.4 (NLCT)]
```

Version 3.0: no longer using xkeyval.

`\ifDTLcolorbarchart` The conditional `\ifDTLcolorbarchart` is used to determine whether to use colour or grey scale. NB may be removed or deprecated.

```

\newif\ifDTLcolorbarchart
\DTLcolorbarcharttrue

```

`\ifDTLverticalbars` Define boolean keys to govern bar chart orientation.

```
\newif\ifDTLverticalbars
```

Set defaults:

```
\DTLverticalbarstrue
```

`\DTLbarXlabelalign` Alignment for lower bar labels.

```

\newcommand\DTLbarXlabelalign{%
  \ifDTLverticalbars left,rotate=-90\else right\fi
}

```

`\DTLbarXupperlabelalign` Alignment for upper bar labels.

```

\newcommand\DTLbarXupperlabelalign{%
  \ifDTLverticalbars bottom,center\else left\fi
}

```

`\DTLbarXneglabelalign` Alignment for lower label on negative bars.

```

\newcommand\DTLbarXneglabelalign{%
  \ifDTLverticalbars right,rotate=-90\else left\fi
}

```

`\DTLbarXnegupperlabelalign` Alignment for upper bar labels on negative bars.

```

\newcommand\DTLbarXnegupperlabelalign{%
  \ifDTLverticalbars top,center\else right\fi
}

```

`\DTLbarYticklabelalign` Alignment for *y* tick labels.

```

\newcommand\DTLbarYticklabelalign{%
  \ifDTLverticalbars right\else top,center\fi
}

```

The package options have been changed to use l3keys.

Define package options:

```

\ExplSyntaxOn
\keys_define:nn { datatool }
{
  color .legacy_if_set:n = DTLcolorbarchart,
  gray .legacy_if_set_inverse:n = DTLcolorbarchart,
  verticalbars .legacy_if_set:n = DTLverticalbars ,
  vertical .code:n =
  {
    \DTLverticalbarstrue
  },
  horizontal .code:n =
  {
    \DTLverticalbarsfalse
  },
}
\ExplSyntaxOff

```

Process options:

```

\IfPackageLoadedTF{datatool}
{
  \ProcessKeyOptions[datatool]
}
{
  \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{datatool}}
  \ProcessOptions
}
\RequirePackage{datatool}

```

Remove the package option keys so they can't be used with `\DTLsetup` (otherwise they may conflict with `datapie` etc).

```

\ExplSyntaxOn
\keys_define:nn { datatool }
{

```

```

    color .undefine: ,
    gray .undefine: ,
    verticalbars .undefine: ,
    vertical .undefine: ,
    horizontal .undefine: ,
  }
  \ExplSyntaxOff
  Require dataplot package. Note that this also loads tikz.
  \RequirePackage{dataplot}

```

26.1 Scratch Variables

```
\ExplSyntaxOn
```

Token list to construct content:

```
\tl_new:N \l__databar_content_tl
```

`\DTLtotalbars` Used to store the total number of bars.

```
\tl_new:N \DTLtotalbars
```

`\DTLbartotalvariables` Used to store the total number of variables for multi charts.

```
\tl_new:N \DTLbartotalvariables
```

`\DTLtotalbargroups` Used to store the total number of bar groups for multi charts.

```
\tl_new:N \DTLtotalbargroups
```

`\DTLbarchartwidth` Used to store the total width of the x -axis. This doesn't include the y tick marks or labels.

```
\tl_new:N \DTLbarchartwidth
```

```
\dim_new:N \l__databar_miny_dim
```

```
\dim_new:N \l__databar_maxy_dim
```

`\DTLbarvariable` The bar chart variable.

```
\tl_new:N \DTLbarvariable
```

`\dtlbar@variables` Token list variables used to create the multi bar chart are now stored in a sequence.

Version 3.0: changed `\dtlbar@variables` to:

```
\seq_new:N \l__databar_variables_seq
```

`\@dtl@start` Lower bar labels. Version 3.0: renamed `\@dtl@start` to:

```
\fp_new:N \l__databar_start_fp
```

Consider a bar as a thick line (of one bar width). This is anchored to the x axis at the line's start `\DTLstartpt` and extends to the line's end `\DTLendpt`. Half-way along this line is the mid point `\DTLmidpt`. The x -coordinate for all these points is the same and will be stored in:

```
\tl_new:N \l__databar_mid_tl
```

```
\dim_new:N \l__databar_mid_dim
```

The extent is the current bar's y value converted to a dimension:

`\dim_new:N \l__databar_extent_dim`

The y point of the starting point will be 0. The y point of the ending point will be the variable value. But we also need the starting point of the rectangle and the end point in order to draw the bar so that the line passes through the middle. The x co-ordinate of the start of the rectangle is stored in:

`\tl_new:N \l__databar_start_tl`

The x co-ordinate of the end of the rectangle is stored in:

`\tl_new:N \l__databar_end_tl`

Four points of the rectangle are obtained with those x co-ordinates for $y = 0$ and $y = v$, where v is the bar variable's value.

Offset for group label.

`\dim_new:N \l__databar_group_label_offset_dim`

`\dtl@extent` Bar extent. Version 3.0: renamed `\dtl@extent` to:

`\fp_new:N \l__databar_extent_fp`

`\dtl@unit` Lower bar labels. Version 3.0: renamed `\dtl@unit` to:

`\fp_new:N \l__databar_unit_fp`

Current label offset and alignment:

`\tl_new:N \l__databar_label_current_offset_tl`

`\tl_new:N \l__databar_label_current_align_tl`

`\dtl@barlabel` Lower bar labels. Version 3.0: renamed `\dtl@barlabel` to:

`\tl_new:N \l__databar_barlabel_tl`

Lower bar label in multi-bar chart.

`\tl_new:N \l__databar_lowerbarlabel_tl`

`\dtl@multibarlabels` Lower bar labels for multi-bar charts. Version 3.0: changed `\dtl@multibarlabels` to:

`\seq_new:N \l__databar_multibarlabels_seq`

`\dtlbar@groupgap` Gap between groups in multi-bar charts (This should be in x units where 1 x unit is the width of a bar.) Version 3.0: changed `\dtlbar@groupgap` to:

`\tl_new:N \l__databar_groupgap_tl`

`\tl_set:Nn \l__databar_groupgap_tl { 1 }`

Gap between bars.

`\tl_new:N \l__databar_bargap_tl`

`\tl_set:Nn \l__databar_bargap_tl { 0 }`

`\dtl@upperbarlabel` Upper bar labels. Version 3.0: changed `\dtl@upperbarlabel` to:

`\tl_new:N \l__databar_upperbarlabel_tl`

```

\dtl@uppermultibarlabels Upper bar labels for multi-bar charts. Version 3.0: changed \dtl@uppermultibarlabels
to:
  \seq_new:N \l__databar_uppermultibarlabels_seq

dtlbar@yticlist Define list of points for y tics. (Must be a comma separated list of decimal numbers.)
Version 3.0: changed from \dtlbar@yticlist to a sequence.
  \clist_new:N \l__databar_yticpoints_clist
  \seq_new:N \l__databar_yticpoints_seq

\dtlbar@yticgap The y tick gap. Version 3.0: changed \dtlbar@yticgap to:
  \tl_new:N \l__databar_yticgap_tl
  \fp_new:N \l__databar_yticgap_fp

dtlbar@yticlabels Define list of points for y tick labels. Version 3.0: changed from \dtlbar@yticlabels
to a sequence.
  \seq_new:N \l__databar_yticlabels_seq

\dtlbar@ylabel y axis label. Version 3.0: changed \dtlbar@ylabel to:
  \tl_new:N \l__databar_ylabel_tl

\DTLyAxisLabelStyle y-axis label style.
  \newcommand{\DTLyAxisLabelStyle}{%
    bottom, center \ifDTLverticalbars , rotate = 90 \fi
  }

  \tl_new:N \l__databar_ylabel_offset_tl
  \tl_set:Nn \l__databar_ylabel_offset_tl
    { \baselineskip }

  \tl_new:N \l__databar_ylabel_pos_tl
  \tl_set:Nn \l__databar_ylabel_pos_tl
    { \c__databar_ylabel_pos_centred_tl }

  Centred along the y axis:
  \tl_const:Nn \c__databar_ylabel_pos_centred_tl
    {
      \ifDTLverticalbars
        \exp_not:N \pgfpoint
        {
          - \exp_not:N \l__dataplot_y_tic_label_width_dim
        }
        {
          \dim_eval:n
            {
              0.5 \DTLbarchartlength + \l__databar_miny_dim
            }
        }
      }
    \else
      \exp_not:N \pgfpoint

```

```

        {
          \dim_eval:n
          {
            0.5 \DTLbarchartlength + \l__databar_miny_dim
          }
        }
        {
          - \exp_not:N \l__dataplot_y_tic_label_width_dim
        }
      \fi
    }
  }
  At the minimum end of the y axis:
  \tl_const:Nn \c__databar_ylabel_pos_min_tl
  {
    \ifDTLverticalbars
      \exp_not:N \pgfpoint
      {
        - \exp_not:N \l__dataplot_y_tic_label_width_dim
      }
      { \exp_not:N \l__databar_miny_dim }
    \else
      \exp_not:N \pgfpoint
      { \exp_not:N \l__databar_miny_dim }
      {
        - \exp_not:N \l__dataplot_y_tic_label_width_dim
      }
    \fi
  }
  }
  At the maximum end:
  \tl_const:Nn \c__databar_ylabel_pos_max_tl
  {
    \ifDTLverticalbars
      \exp_not:N \pgfpoint
      {
        - \exp_not:N \l__dataplot_y_tic_label_width_dim
      }
      { \exp_not:N \l__databar_maxy_dim }
    \else
      \exp_not:N \pgfpoint
      { \exp_not:N \l__databar_maxy_dim }
      {
        - \exp_not:N \l__dataplot_y_tic_label_width_dim
      }
    \fi
  }
  }
  At the origin:
  \tl_const:Nn \c__databar_ylabel_pos_zero_tl
  {

```

```

\ifDTLverticalbars
  \exp_not:N \pgfpoint
  {
    - \exp_not:N \l__dataplot_y_tic_label_width_dim
  }
  { \exp_not:N \c_zero_dim }
\else
  \exp_not:N \pgfpoint
  { \exp_not:N \c_zero_dim }
  {
    - \exp_not:N \l__dataplot_y_tic_label_width_dim
  }
\fi
}

```

`\@dtl@barcount` Version 3.0: integer register `\@dtl@barcount` removed.

`\DTLbarindex` May be used in hooks to access the bar index.
`\newcommand{\DTLbarindex}{0}`

`\DTLbargroupindex` May be used in hooks to access the bar group index.
`\newcommand{\DTLbargroupindex}{0}`

26.2 Settings

Define some variables that govern the appearance of the bar chart.

`\DTLbargrouplabelalign` Alignment for group label.
`\newcommand\DTLbargrouplabelalign{\DTLbarxlabelalign}`

`\DTLbarchartlength` The total height of the bar chart is given by `\DTLbarchartheight`
`\newlength\DTLbarchartlength`
`\DTLbarchartlength=3in`

`\DTLbarwidth` The width of each bar is given by `\DTLbarwidth`.
`\newlength\DTLbarwidth`
`\DTLbarwidth=1cm`

`\DTLbarmax` The maximum value of the *y* axis.
`\tl_new:N \DTLbarmax`

Set the maximum, with a check to make sure that the value isn't negative:

```

\cs_new:Nn \__databar_set_max:n
{
  \tl_if_empty:nTF { #1 }
  {
    \tl_clear:N \DTLbarmax
  }
}

```

```

\fp_compare:nNnTF
{ #1 } < { \c_zero_fp }
{
  \PackageError { databar }
  {
    max ~ must ~ be ~ zero ~ or ~ positive ~ (or ~
    empty ~ for ~ the ~ default)
  }
  { }
}
{
  \tl_set:Nn \DTLbarmax { #1 }
}
}

```

`\DTLnegextent` The negative extent.

```
\tl_new:N \DTLnegextent
```

Set the negative extent, with a check to make sure that the value isn't positive:

```

\cs_new:Nn \__databar_set_max_depth:n
{
  \tl_if_empty:nTF { #1 }
  {
    \tl_clear:N \DTLnegextent
  }
  {
    \fp_compare:nNnTF
    { #1 } > { \c_zero_fp }
    {
      \PackageError { databar }
      {
        maxdepth ~ must ~ be ~ zero ~ or ~ negative ~ (or ~
        empty ~ for ~ the ~ default)
      }
      { }
    }
  }
  {
    \tl_set:Nn \DTLnegextent { #1 }
  }
}

```

`\DTLbarlabeloffset` The offset from the x axis to the bar label is given by `\DTLbarlabeloffset`.

```

\newlength\DTLbarlabeloffset
\setlength\DTLbarlabeloffset{10pt}

```

The offset from the upper edge of the bar to the upper label.

```
\tl_new:N \l__databar_upper_label_offset_tl
```

`\tl_set:Nn \l__databar_upper_label_offset_tl`
`{ \DTLbarlabeloffset }`

Label offsets depend on the label-style setting. Lower labels:

`\tl_new:N \l__databar_label_pos_offset_tl`
`\tl_set:Nn \l__databar_label_pos_offset_tl`
`{ \dim_to_decimal:n { -\DTLbarlabeloffset } pt }`
`\tl_new:N \l__databar_label_neg_offset_tl`
`\tl_set:Nn \l__databar_label_neg_offset_tl`
`{ \dim_to_decimal:n { \DTLbarlabeloffset } pt }`

Upper labels:

`\tl_new:N \l__databar_upper_label_pos_offset_tl`
`\tl_set:Nn \l__databar_upper_label_pos_offset_tl`
`{ \dim_to_decimal:n { \l__databar_upper_label_offset_tl } pt }`
`\tl_new:N \l__databar_upper_label_neg_offset_tl`
`\tl_set:Nn \l__databar_upper_label_neg_offset_tl`
`{ \dim_to_decimal:n { -\l__databar_upper_label_offset_tl } pt }`

`\DTLBarXAxisStyle` The style of the x axis is given by `\DTLBarXAxisStyle`
`\newcommand*\DTLBarXAxisStyle}{-}`

`\DTLBarYAxisStyle` The style of the y axis is given by `\DTLBarYAxisStyle`.
`\newcommand*\DTLBarYAxisStyle}{-}`

`\DTLBarStyle` Any additional styling for each bar.
`\newcommand*\DTLBarStyle}{}`

`DTLbarroundvar` `DTLbarroundvar` is a counter governing the number of digits to round to for the label.
`\newcounter{DTLbarroundvar}`
`\setcounter{DTLbarroundvar}{1}`

Number of digits to round the y tick label:

`\tl_new:N \l__databar_ytic_round_tl`
`\tl_set:Nn \l__databar_ytic_round_tl { \int_use:N \c@DTLbarroundvar }`

`\DTLbardisplayYticklabel` `\DTLbardisplayYticklabel` governs how the y tick labels appear.
`\newcommand*\DTLbardisplayYticklabel}[1]{#1}`

`\DTLdisplaylowerbarlabel` `\DTLdisplaylowerbarlabel` governs how the lower bar labels appear.
`\newcommand*\DTLdisplaylowerbarlabel}[1]{#1}`

`\DTLdisplaybargrouplabel` `\DTLdisplaybargrouplabel` governs how the bar group labels appear.
`\newcommand*\DTLdisplaybargrouplabel}[1]{#1}`

`\DTLdisplaylowermultibarlabel` `\DTLdisplaylowermultibarlabel` governs how the lower multi bar labels appear.
`\newcommand*\DTLdisplaylowermultibarlabel}[1]{#1}`

`\DTLdisplayupperbarlabel` `\DTLdisplayupperbarlabel` governs how the upper bar labels appear.
`\newcommand*{\DTLdisplayupperbarlabel}[1]{#1}`

`\DTLdisplayuppermultibarlabel` `\DTLdisplayuppermultibarlabel` governs how the upper multi bar labels appear.
`\newcommand*{\DTLdisplayuppermultibarlabel}[1]{#1}`

`\DTLbaratbegintikz` `\DTLbaratbegintikz` specifies any commands to apply at the start of the `tikzpicture` environment. By default it does nothing.
`\newcommand*{\DTLbaratbegintikz}{}`

`\DTLbaratendtikz` `\DTLbaratendtikz` specifies any commands to apply at the end of the `tikzpicture` environment. By default it does nothing.
`\newcommand*{\DTLbaratendtikz}{}`

`\ifDTLbarxaxis` The conditional `\ifDTLbarxaxis` is used to determine whether or not to display the x axis
`\newif\ifDTLbarxaxis`

`\ifDTLbaryaxis` The conditional `\ifDTLbaryaxis` is used to determine whether or not to display the y axis.
`\newif\ifDTLbaryaxis`

`\ifDTLbarytics` The conditional `\ifDTLbarytics` to determine whether or not to display the y tick marks.
`\newif\ifDTLbarytics`

No-op command:
`\cs_new:Npn __databar_noop:N #1`
`{`
`\PackageError { databar }`
`{`
`Can't ~ use ~ \token_to_str:N #1 \c_space_tl ~ outside ~`
`\token_to_str:N \DTLbarchart \c_space_tl ~ or ~`
`\token_to_str:N \DTLmultibarchart`
`}`
`{ }`
`}`

There are two colour lists: the default colour list and the negative bar list. If a bar value is negative, the colour will first be looked up in the negative bar list. If missing, the default colour list will be used. Bars with positive values will just use the default colour list.

`\int_new:N \l__databar_max_colors_int`
`\int_new:N \l__databar_max_neg_colors_int`

`\DTLsetbarcolor{<n>}{<color>}`

`\DTLsetbarcolor`

Assigns colour name *<color>* to the *<n>*th bar.

```
\NewDocumentCommand \DTLsetbarcolor { m m }
{
  \tl_set:cn { dtlbar@col\romannumeral#1 } { #2 }
  \int_compare:nNnT { #1 } > { \l_databar_max_colors_int }
  {
    \int_set:Nn \l_databar_max_colors_int { #1 }
  }
}
```

`\DTLclearbarcolors`

`\DTLclearbarcolors`

Clears all bar colours.

```
\NewDocumentCommand \DTLclearbarcolors { }
{
  \int_step_inline:nn { \l_databar_max_colors_int }
  {
    \cs_undefine:c { dtlbar@col\romannumeral##1 }
  }
  \int_zero:N \l_databar_max_colors_int
}
```

`\DTLsetnegbarcolor{<n>}{<color>}`

`\DTLsetnegbarcolor`

Assigns colour name *<color>* to the *<n>*th bar for negative bar values.

```
\NewDocumentCommand \DTLsetnegbarcolor { m m }
{
  \tl_set:cn { dtlbar@negcol\romannumeral#1 } { #2 }
  \int_compare:nNnT { #1 } > { \l_databar_max_neg_colors_int }
  {
    \int_set:Nn \l_databar_max_neg_colors_int { #1 }
  }
}
```

`\DTLclearnegbarcolors`

`\DTLclearnegbarcolors`

Clears all negative bar colours.

```
\NewDocumentCommand \DTLclearnegbarcolors { }
{
  \int_step_inline:nn { \l_databar_max_neg_colors_int }
  {
    \cs_undefine:c { dtlbar@negcol\romannumeral##1 }
  }
}
```

```

}
\int_zero:N \l__databar_max_neg_colors_int
}

```

Provide an option to cycle round the bar colours. This is a token list variable rather than an integer to allow it to be set to `\l__databar_max_colors_int` which can then take into account any extra colours added afterwards.

```

\tl_new:N \l__databar_color_max_index_tl
\tl_set:Nn \l__databar_color_max_index_tl { \c_zero_int }
\tl_new:N \l__databar_neg_color_max_index_tl
\tl_set:Nn \l__databar_neg_color_max_index_tl
  { \l__databar_color_max_index_tl }
\cs_new:Nn \__databar_cycle_index:nn
{
  \int_eval:n
  {
    \__databar_cycle_index_adjust:on
    {
      \int_mod:nn { #1 } { \l__databar_color_max_index_tl }
    }
    { \l__databar_color_max_index_tl }
  }
}
\cs_new:Nn \__databar_cycle_index_adjust:nn
{
  \int_if_zero:nTF { #1 } { #2 } { #1 }
}
\cs_generate_variant:Nn \__databar_cycle_index_adjust:nn { on }

```

`\DTLgetbarcolor{<n>}`

`\DTLgetbarcolor`

Gets the colour specification for the $\langle n \rangle$ th bar.

```

\newcommand*{\DTLgetbarcolor}[1]{%
  \int_compare:nNnTF
    { \l__databar_color_max_index_tl } > { \c_zero_int }
  {
    \__databar_get_bar_col:n
    {
      \__databar_cycle_index:nn
      { #1 } { \l__databar_color_max_index_tl }
    }
  }
  {
    \__databar_get_bar_col:n { #1 }
  }
}
\cs_new:Nn \__databar_get_bar_col:n

```

```
{
  \cs_if_exist_use:cF { dtlbar@col\romannumeral#1 } { white }
}
```

\DTLgetnegbarcolor{<n>}

\DTLgetnegbarcolor

Gets the negative bar colour specification for the <n>th bar.

```
\newcommand*\DTLgetnegbarcolor}[1]{%
  \int_compare:nNnTF
    { \l_databar_neg_color_max_index_tl } > { \c_zero_int }
  {
    \__databar_get_neg_bar_col:n
    {
      \__databar_cycle_index:nn
      { #1 } { \l_databar_neg_color_max_index_tl }
    }
  }
  {
    \__databar_get_neg_bar_col:n { #1 }
  }
}
\cs_new:Nn \__databar_get_neg_bar_col:n
{
  \cs_if_exist_use:cF { dtlbar@negcol\romannumeral#1 }
  { \__databar_get_bar_col:n { #1 } }
}
```

\DTLdobarcolor[<value>]{<n>}

\DTLdobarcolor

Sets the colour to that for the <n>th bar. The value determines whether to use the default colour set or the negative set.

```
\NewDocumentCommand \DTLdobarcolor { o m }
{
  \IfValueTF { #1 }
  {
    \fp_compare:nNnTF { #1 } < { \c_zero_fp }
    {
      \__databar_do_col_or_nothing:x { \DTLgetnegbarcolor { #2 } }
    }
    {
      \__databar_do_col_or_nothing:x { \DTLgetbarcolor { #2 } }
    }
  }
  {
    \__databar_do_col_or_nothing:x { \DTLgetbarcolor { #2 } }
  }
}
```

```

}
\cs_new:Nn \__databar_do_col_or_nothing:n
{
  \tl_if_empty:nF { #1 } { \color { #1 } }
}
\cs_generate_variant:Nn \__databar_do_col_or_nothing:n { x }

```

`\DTLdocurrentbarcolor` `\DTLdocurrentbarcolor` sets the colour to that of the current bar. NB this only consults the default colour list unless `\DTLbarvalue` is defined and `__databar_index_int` is greater than 0. In which case, the bar value will be tested to determine if the negative bar colour list should be used.

```

\NewDocumentCommand \DTLdocurrentbarcolor { }
{
  \int_compare:nNnTF
    { \int_use:N \l__databar_index_int } > { \c_zero_int }
  {
    \tl_if_exist:N \DTLbarvalue
    {
      \exp_args:NV \tl_if_head_eq_meaning:nNTF
        \DTLbarvalue \__datatool_datum:n
        {
          \fp_compare:nNnTF
            { \DTLdatumvalue \DTLbarvalue } < { \c_zero_int }
            {
              \__databar_do_col_or_nothing:x
                { \DTLgetnegbarcolor { \l__databar_index_int } }
            }
            {
              \__databar_do_col_or_nothing:x
                { \DTLgetbarcolor { \l__databar_index_int } }
            }
          }
        }
      {
        \fp_compare:nNnTF
          { \DTLbarvalue } < { \c_zero_int }
          {
            \__databar_do_col_or_nothing:x
              { \DTLgetnegbarcolor { \l__databar_index_int } }
          }
          {
            \__databar_do_col_or_nothing:x
              { \DTLgetbarcolor { \l__databar_index_int } }
          }
        }
      }
    }
  {
    \__databar_do_col_or_nothing:x
      { \DTLgetbarcolor { \l__databar_index_int } }
  }
}

```

```

{
  \int_compare:nNnTF
    { \l_datatool_row_idx_int } > { \c_zero_int }
  {
    \exp_args:Nv \DTLdobarcolor \l_datatool_row_idx_int
  }
  {
    \int_compare:nNnTF { \dtlforeachlevel } > { 0 }
    {
      \exp_args:Nv \DTLdobarcolor
        { c@DTLrow\romannumeral\dtlforeachlevel }
    }
    {
      \__databar_noop:N \DTLdocurrentbarcolor
    }
  }
}
}
}

```

`\DTLbaroutlinecolor` `\DTLbaroutlinecolor` specifies what colour to draw the outline.
`\newcommand*{\DTLbaroutlinecolor}{black}`

`\DTLbaroutlinewidth` `\DTLbaroutlinewidth` specifies the line width of the outline: Outline is only drawn if the linewidth is greater than 0pt.
`\newlength\DTLbaroutlinewidth`
`\DTLbaroutlinewidth=0pt`

Set the default colours. If there are more than eight bars, more colours will need to be defined.

```

\ifDTLcolorbarchart
  \DTLsetbarcolor{1}{red}
  \DTLsetbarcolor{2}{green}
  \DTLsetbarcolor{3}{blue}
  \DTLsetbarcolor{4}{yellow}
  \DTLsetbarcolor{5}{magenta}
  \DTLsetbarcolor{6}{cyan}
  \DTLsetbarcolor{7}{orange}
  \DTLsetbarcolor{8}{white}
\else
  \DTLsetbarcolor{1}{black!15}
  \DTLsetbarcolor{2}{black!25}
  \DTLsetbarcolor{3}{black!35}
  \DTLsetbarcolor{4}{black!45}
  \DTLsetbarcolor{5}{black!55}
  \DTLsetbarcolor{6}{black!65}
  \DTLsetbarcolor{7}{black!75}
  \DTLsetbarcolor{8}{black!85}
\fi

```

`\DTLeverybarhook` Code to apply at every bar after the bar has been drawn.

```
\newcommand*\DTLeverybarhook{}
```

`\DTLeveryprebarhook` Code to apply at every bar before the bar has been drawn.

```
\newcommand*\DTLeveryprebarhook{}
```

`\DTLeverybargrouphook` Hook at the end of every bar group for `\DTLmultibar chart`.

```
\newcommand*\DTLeverybargrouphook{}
```

`DTLbarsetupperlabelalign`

```
\NewDocumentCommand \DTLbarsetupperlabelalign { o m }
{
  \IfValueT { #1 }
  {
    \tl_set:Nn \DTLbarXnegupperlabelalign { #1 }
  }
  \tl_set:Nn \DTLbarXupperlabelalign { #2 }
}
```

Used by `upper-label-align` to allow for missing braces around mandatory part (e.g. `upper-label-align=[left]right` or `upper-label-align=right`).

```
\cs_new:Npn \__databar_set_upper_align:w #1 \q_stop
```

```
{
  \tl_if_head_eq_charcode:nNTF { #1 } [
  {
    \__databar_set_upper_align_both:w #1 \q_stop
  }
  {
    \tl_if_single:NTF { #1 }
    {
      \DTLbarsetupperlabelalign #1
    }
    {
      \DTLbarsetupperlabelalign { #1 }
    }
  }
}
```

```
\cs_new:Npn \__databar_set_upper_align_both:w [ #1 ] #2 \q_stop
```

```
{
  \tl_if_single:NTF { #2 }
  {
    \DTLbarsetupperlabelalign [ #1 ] #2
  }
  {
    \DTLbarsetupperlabelalign [ #1 ] { #2 }
  }
}
```

Initialisation code after options have been parsed:

```
\tl_new:N \l__databar_init_tl
```

Initialisation code before options have been parsed:

```
\tl_new:N \l__databar_pre_init_tl
\keys_define:nn { datatool/bar }
{
```

Variable used to create the bar chart. (Must be a control sequence.)

```
variable .code:n =
{
  \tl_if_single:nTF { #1 }
  {
    \tl_set:Nn \DTLbarvariable { #1 }
  }
  {
    \PackageError { databar }
    {
      Invalid ~ value ~ in ~ `variable = \tl_to_str:n { #1 }'
    }
    {
      A ~ single ~ control ~ sequence ~ expected ~ as ~ the ~
      value ~ for ~ the ~ `variable' ~ setting
    }
  }
}
},
```

Variables used to create the multi bar chart. (Must be a comma separated list of control sequences.)

```
variables .code:n =
{
  \seq_set_from_clist:Nn
  \l__databar_variables_seq { #1 }
},
```

Rounding:

```
round .int_set:N = \c@DTLbarroundvar ,
y-tick-round .code:n =
{
  \tl_if_empty:nTF { #1 }
  {
    \tl_set:Nn \l__databar_ytic_round_tl
    { \int_use:N \c@DTLbarroundvar }
  }
  {
    \tl_set:Nn \l__databar_ytic_round_tl { #1 }
  }
}
},
y-tick-round .default:n = { } ,
```

Synonym:

```
ytic-round .code:n =
{
```

```

\tl_if_empty:nTF { #1 }
  {
    \tl_set:Nn \l__databar_ytic_round_tl
      { \int_use:N \c@DTLbarroundvar }
  }
  {
    \tl_set:Nn \l__databar_ytic_round_tl { #1 }
  }
},
ytic-round .default:n = { } ,

```

Bar width:

```

barwidth .dim_set:N = \DTLbarwidth,
bar-width .dim_set:N = \DTLbarwidth,

```

Lower bar labels

```

barlabel .tl_set:N = \l__databar_barlabel_tl ,
bar-label .tl_set:N = \l__databar_barlabel_tl ,

```

Lower bar labels for multi-bar charts:

```

multibarlabels .code:n =
  {
    \seq_set_from_clist:Nn
      \l__databar_multibarlabels_seq { #1 }
  },
multi-bar-labels .code:n =
  {
    \seq_set_from_clist:Nn
      \l__databar_multibarlabels_seq { #1 }
  },

```

Gap between bars:

```

bargap .tl_set:N = \l__databar_bargap_tl ,
bar-gap .tl_set:N = \l__databar_bargap_tl ,

```

Gap between groups in multi-bar charts:

```

groupgap .tl_set:N = \l__databar_groupgap_tl ,
group-gap .tl_set:N = \l__databar_groupgap_tl ,

```

Upper bar labels:

```

upperbarlabel .tl_set:N = \l__databar_upperbarlabel_tl ,
upper-bar-label .tl_set:N = \l__databar_upperbarlabel_tl ,

```

Upper bar labels for multi-bar charts:

```

uppermultibarlabels .code:n =
  {
    \seq_set_from_clist:Nn
      \l__databar_uppermultibarlabels_seq { #1 }
  },
upper-multi-bar-labels .code:n =
  {
    \seq_set_from_clist:Nn

```

```

        \l__databar_uppermultibarlabels_seq { #1 }
    },
Define list of points for y tics:
yticpoints .code:n =
{
    \clist_set:Nn
        \l__databar_yticpoints_clist { #1 }
    \DTLbaryticstrue
    \DTLbaryaxistrue
},
y-tick-points .code:n =
{
    \clist_set:Nn
        \l__databar_yticpoints_clist { #1 }
    \DTLbaryticstrue
    \DTLbaryaxistrue
},
Set the y tick gap:
yticgap .code:n =
{
    \tl_set:Nn \l__databar_yticgap_tl { #1 }
    \DTLbaryticstrue
    \DTLbaryaxistrue
},
y-tick-gap .code:n =
{
    \tl_set:Nn \l__databar_yticgap_tl { #1 }
    \DTLbaryticstrue
    \DTLbaryaxistrue
},
List of labels for y tics.
yticlabels .code:n =
{
    \seq_set_from_clist:Nn
        \l__databar_yticlabels_seq { #1 }
    \DTLbaryticstrue
    \DTLbaryaxistrue
},
y-tick-labels .code:n =
{
    \seq_set_from_clist:Nn
        \l__databar_yticlabels_seq { #1 }
    \DTLbaryticstrue
    \DTLbaryaxistrue
},
y axis label:
ylabel .tl_set:N = \l__databar_ylabel_tl ,

```

y axis label position: *y* axis label:

```
ylabel-position .choice: ,
ylabel-position / center .code:n =
{
  \tl_set:Nn \l__databar_ylabel_pos_tl
  { \c__databar_ylabel_pos_centred_tl }
},
ylabel-position / min .code:n =
{
  \tl_set:Nn \l__databar_ylabel_pos_tl
  { \c__databar_ylabel_pos_min_tl }
},
ylabel-position / max .code:n =
{
  \tl_set:Nn \l__databar_ylabel_pos_tl
  { \c__databar_ylabel_pos_max_tl }
},
ylabel-position / zero .code:n =
{
  \tl_set:Nn \l__databar_ylabel_pos_tl
  { \c__databar_ylabel_pos_zero_tl }
},
```

Vertical bars:

```
vertical .code:n =
{
  \DTLverticalbarstrue
},
```

Horizontal:

```
horizontal .code:n =
{
  \DTLverticalbarsfalse
},
```

Option that takes a value:

```
verticalbars .legacy_if_set:n = DTLverticalbars ,
```

Label alignment:

```
upper-label-align .code:n =
{
  \tl_if_empty:nTF { #1 }
  {
    \tl_set:Nn \DTLbarXupperlabelalign
    {
      \ifDTLverticalbars
        bottom, center
      \else
        left
      \fi
    }
  }
}
```

```

\l_set:Nn \DTLbarXnegupperlabelalign
{
  \ifDTLverticalbars
    top, center
  \else
    right
  \fi
}
}
{
  \__databar_set_upper_align:w #1 \q_stop
}
},
upper-label-align .default:n = { } ,
lower-label-style .choice: ,
lower-label-style / below .code:n =
{
  \l_set:Nn \DTLbarXlabelalign
  {
    \ifDTLverticalbars
      left, rotate=-90
    \else
      right
    \fi
  }
  \l_set:Nn \DTLbarXneglabelalign
  {
    \ifDTLverticalbars
      left, rotate=-90
    \else
      right
    \fi
  }
  \l_set:Nn \l__databar_label_pos_offset_tl
  { \dim_to_decimal:n { -\DTLbarlabeloffset } pt }
  \l_set:Nn \l__databar_label_neg_offset_tl
  { \dim_to_decimal:n { -\DTLbarlabeloffset } pt }
} ,
lower-label-style / above .code:n =
{
  \l_set:Nn \DTLbarXlabelalign
  {
    \ifDTLverticalbars
      right, rotate=-90
    \else
      left
    \fi
  }
  \l_set:Nn \DTLbarXneglabelalign
  {

```

```

        \ifDTLverticalbars
            right, rotate=-90
        \else
            left
        \fi
    }
    \tl_set:Nn \l__databar_label_pos_offset_tl
    { \dim_to_decimal:n { \DTLbarlabeloffset } pt }
    \tl_set:Nn \l__databar_label_neg_offset_tl
    { \dim_to_decimal:n { \DTLbarlabeloffset } pt }
} ,
lower-label-style / same .code:n =
{
    \tl_set:Nn \DTLbarXlabelalign
    {
        \ifDTLverticalbars
            right, rotate=-90
        \else
            left
        \fi
    }
    \tl_set:Nn \DTLbarXneglabelalign
    {
        \ifDTLverticalbars
            left, rotate=-90
        \else
            right
        \fi
    }
    \tl_set:Nn \l__databar_label_pos_offset_tl
    { \dim_to_decimal:n { \DTLbarlabeloffset } pt }
    \tl_set:Nn \l__databar_label_neg_offset_tl
    { \dim_to_decimal:n { -\DTLbarlabeloffset } pt }
} ,
lower-label-style / opposite .code:n =
{
    \tl_set:Nn \DTLbarXneglabelalign
    {
        \ifDTLverticalbars
            right, rotate=-90
        \else
            left
        \fi
    }
    \tl_set:Nn \DTLbarXlabelalign
    {
        \ifDTLverticalbars
            left, rotate=-90
        \else
            right
        \fi
    }
}

```

```

        \fi
    }
    \tl_set:Nn \l__databar_label_pos_offset_tl
      { \dim_to_decimal:n { -\DTLbarlabeloffset } pt }
    \tl_set:Nn \l__databar_label_neg_offset_tl
      { \dim_to_decimal:n { \DTLbarlabeloffset } pt }
  } ,

```

Maximum value of the y axis:

```

max .code:n =
  {
    \__databar_set_max:n { #1 }
  } ,
max .default:n = { } ,

```

The total length of the bar chart

```
length .dim_set:N = \DTLbarchartlength,
```

The maximum depth (negative extent):

```

maxdepth .code:n =
  {
    \__databar_set_max_depth:n { #1 }
  } ,
maxdepth .default:n = { } ,
max-depth .code:n =
  {
    \__databar_set_max_depth:n { #1 }
  } ,
max-depth .default:n = { } ,

```

Determine which axes should be shown:

```

axes .choice: ,
axes .default:n = { both } ,
axes / both .code:n =
  {
    \DTLbarxaxistrue
    \DTLbaryaxistrue
    \DTLbaryticstrue
  } ,
axes / x .code:n =
  {
    \DTLbarxaxistrue
    \DTLbaryaxisfalse
    \DTLbaryticsfalse
  } ,
axes / y .code:n =
  {
    \DTLbaraxisfalse
    \DTLbaryaxistrue
    \DTLbaryticstrue
  } ,

```

```

axes / none .code:n =
{
  \DTLbaraxisfalse
  \DTLbaryaxisfalse
  \DTLbaryticsfalse
},
yaxis .legacy_if_set:n = DTLbaryaxis,
y-axis .legacy_if_set:n = DTLbaryaxis,
y-ticks .choice: ,
y-ticks / true .code:n =
{
  \DTLbaryaxistrue
  \DTLbaryticstrue
},
y-ticks / false .code:n =
{
  \DTLbaryticsfalse
},
y-ticks .default:n = true,

```

Synonym:

```

ytics .choice: ,
ytics / true .code:n =
{
  \DTLbaryaxistrue
  \DTLbaryticstrue
},
ytics / false .code:n =
{
  \DTLbaryticsfalse
},
ytics .default:n = true,

```

Axis style:

```

x-axis-style .tl_set:N = \DTLBarXAxisStyle ,
y-axis-style .tl_set:N = \DTLBarYAxisStyle ,

```

Bar colours:

```

color-style .choice: ,
color-style / cycle .code:n =
{
  \tl_set:Nn \l__databar_color_max_index_tl
  { \l__databar_max_colors_int }
},
color-style / single .code:n =
{
  \tl_set:Nn \l__databar_color_max_index_tl
  { \c_one_int }
},
color-style / default .code:n =
{

```

```

\ctl_set:Nn \l__databar_color_max_index_tl
  { \c_zero_int }
},
bar-colors .code:n =
{
  \seq_set_from_clist:Nn \l__datatool_tmp_seq { #1 }
  \seq_map_indexed_function:NN
    \l__datatool_tmp_seq
    \DTLsetbarcolor
},
bar-default-colors .code:n =
{
  \DTLcolorbarcharttrue
  \DTLsetbarcolor{1}{red}
  \DTLsetbarcolor{2}{green}
  \DTLsetbarcolor{3}{blue}
  \DTLsetbarcolor{4}{yellow}
  \DTLsetbarcolor{5}{magenta}
  \DTLsetbarcolor{6}{cyan}
  \DTLsetbarcolor{7}{orange}
  \DTLsetbarcolor{8}{white}
},
bar-default-colors .value_forbidden:n = true,
bar-default-gray .code:n =
{
  \DTLcolorbarchartfalse
  \DTLsetbarcolor{1}{black!15}
  \DTLsetbarcolor{2}{black!25}
  \DTLsetbarcolor{3}{black!35}
  \DTLsetbarcolor{4}{black!45}
  \DTLsetbarcolor{5}{black!55}
  \DTLsetbarcolor{6}{black!65}
  \DTLsetbarcolor{7}{black!75}
  \DTLsetbarcolor{8}{black!85}
},
bar-default-gray .value_forbidden:n = true,
Colours for bars with negative values.
negative-bar-colors .code:n =
{
  \seq_set_from_clist:Nn \l__datatool_tmp_seq { #1 }
  \seq_map_indexed_function:NN
    \l__datatool_tmp_seq
    \DTLsetnegbarcolor
},
negative-color-style .choice: ,
negative-color-style / cycle .code:n =
{
  \ctl_set:Nn \l__databar_neg_color_max_index_tl
    { \l__databar_max_neg_colors_int }

```

```

    },
    negative-color-style / single .code:n =
    {
        \tl_set:Nn \l__databar_neg_color_max_index_tl
        { \c_one_int }
    },

```

Default negative-color-style matches color-style.

```

    negative-color-style / default .code:n =
    {
        \tl_set:Nn \l__databar_neg_color_max_index_tl
        { \l__databar_color_max_index_tl }
    },

```

Bar outline colour:

```

    outline-color .tl_set:N = \DTLbaroutlinecolor,
    outline-width .dim_set:N = \DTLbaroutlinewidth,

```

Distance from the bar to the bar label:

```

    label-offset .dim_set:N = \DTLbarlabeloffset ,

```

Distance from the outer edge of the bar to the upper bar label:

```

    upper-label-offset .tl_set:N = \l__databar_upper_label_offset_tl ,

```

group label alignment:

```

    group-label-align .tl_set:N = \DTLbargrouplabelalign ,

```

y tick label alignment:

```

    y-tick-label-align .tl_set:N = \DTLbarYticklabelalign ,
    y-tic-label-align .tl_set:N = \DTLbarYticklabelalign ,
    ytic-label-align .tl_set:N = \DTLbarYticklabelalign ,

```

Initialisation code:

```

    init .tl_set:N = \l__databar_init_tl ,
    pre-init .tl_set:N = \l__databar_pre_init_tl ,
    pre-init .groups:n = { pre-parse },

```

Filter:

```

    include-if .cs_set:Np = \__databar_filter:T #1,
    include-if-fn .code:n =
    {
        \cs_set_eq:NN \__databar_filter:T #1
    },

```

Deprecated experimental setting. TODO remove

```

    condition .code:n =
    {
        \PackageWarning{databar}{Deprecated ~ option ~ `condition'. ~
        Use ~ `include-if' ~ instead}
        \cs_set:Npn = \__databar_filter:T ##1 { #1 }
    }
}

```

```

Allow these keys to be set in \DTLsetup{bar={...}}
\keys_define:nn { datatool }
{
  bar .code:n = { \keys_set:nn { datatool/bar } { #1 } }
}

```

Provide a filter function:

```
\cs_new:Npn \__databar_filter:T #1 { #1 }
```

\@dtl@bar Current filtered row number. Version 3.0: replaced \@dtl@bar with:

```

\int_new:N \l__databar_index_int

\cs_new:Npn \__databar_filtered_map:nn #1 #2
{
  \int_zero:N \l__databar_index_int
  \DTLmapdata
  {
    \DTLmapgetvalues { #1 }
    \__databar_filter:T
    {
      \int_incr:N \l__databar_index_int
      #2
    }
  }
}

```

Boolean to check the current chart type.

```

\bool_new:N \l__databar_multi_bars_bool
\bool_set_false:N \l__databar_multi_bars_bool

```

```

\DTLbarchart[conditions]{option list}{db name}
{assign list}

```

\DTLbarchart

Make a bar chart from data given in data base *db name*, where *assign list* is a comma-separated list of *cmd*=*key* pairs. *option list* must include `variable=cmd`, where *cmd* is included in *assign list*. The optional argument *conditions* is the same as that for \DTLforeach.

```

\NewDocumentCommand \DTLbarchart { o m m m }
{
  \group_begin:
  \bool_set_false:N \l__databar_multi_bars_bool
  \tl_set:Nn \DTLbargroupindex { 0 }
  \IfValueT { #1 }
  {
    \cs_set:Npn \__databar_filter:T ##1
    {
      \ifthenelse { #1 } { ##1 } { }
    }
  }
}

```

```

}
\tl_if_blank:nF { #3 }
{
  \DTLsetup { default-name = { #3 } }
}
\keys_set_groups:nnn { datatool/bar } { pre-parse } { #2 }
\l__databar_pre_init_tl
\keys_set:nn { datatool/bar } { #2 }
\l__databar_init_tl
\cs_set_eq:NN \__databar_do:n \use:n
\tl_if_empty:NT \DTLbarvariable
{
  \cs_set_eq:NN \__databar_do:n \use_none:n
  \seq_if_empty:NTF \l__databar_variables_seq
  {
    \PackageError { databar }
    {
      \token_to_str:N \DTLbarchart \c_space_tl ~ missing ~ variable
    }
    {
      You ~ need ~ to ~ set ~ the ~ `variable' ~
      key ~ to ~ the ~ placeholder ~ command
    }
  }
}
{
  \PackageError { databar }
  {
    \token_to_str:N \DTLbarchart \c_space_tl ~ missing ~ variable
  }
  {
    Remember ~ that ~ you ~ need ~ to ~ use ~ `variable' ~
    not ~ `variables' ~ with ~ \token_to_str:N \DTLbarchart
  }
}
}
\tl_if_empty:NF \l__databar_yticgap_tl
{
  \fp_set:Nn \l__databar_yticgap_fp
  { \l__databar_yticgap_tl }
  \fp_compare:nNnT { \l__databar_yticgap_fp } < { \c_zero_fp }
  {
    \PackageError { databar }
    {
      y-tick ~ gap ~ \tl_to_str:o { \l__databar_yticgap_tl } ' ~
      is ~ negative
    }
    {
      The ~ y ~ tick ~ gap ~ specification ~ evaluates ~ to ~
      a ~ negative ~ number ~ ( \fp_to_decimal:N \l__databar_yticgap_fp ) ~
      so ~ the ~ yticgap ~ setting ~ will ~ be ~ ignored
    }
  }
}

```

```

    }
    \tl_clear:N \l__databar_yticgap_tl
    \fp_zero:N \l__databar_yticgap_fp
  }
}
\__databar_do:n
{
  \__databar_do_chart:n { #4 }
}
\group_end:
}

```

```

\cs_new:Nn \__databar_do_chart:n
{

```

Clear the underlying placeholder command used to reference the variable.

```

  \exp_args:NV \tl_clear:N \DTLbarvariable
  \tl_clear:N \DTLtotalbars
  \__datatool_calc_bar_lengths:n { #1 }

```

Calculate the total number of bars if not already found.

```

  \tl_if_empty:NT \DTLtotalbars
  {
    \__databar_filtered_map:nn { #1 } { }
    \tl_set:NV \DTLtotalbars \l__databar_index_int
  }

```

A bar width is one unit so the chart width is the number of bars.

```

  \tl_set_eq:NN \DTLbarchartwidth \DTLtotalbars

```

Add on the inter bar gaps:

```

  \tl_if_eq:NnF \l__databar_bargap_tl { 0 }
  {
    \tl_set:Nx \DTLbarchartwidth
    {
      \fp_eval:n
      {
        \DTLbarchartwidth
        + \l__databar_bargap_tl
        * (\DTLtotalbars - \c_one_fp )
      }
    }
  }

```

```

  \__databar_calc_scale:
  \__databar_construct_ytics:

```

Draw the chart.

```

  \__databar_chart:n { #1 }
}

```

Action 'bar chart':

```

\cs_new:cn { __datatool_action_bar ~ chart : }

```

```

{
  \group_begin:
  \tl_if_empty:NF \l__datatool_action_name_tl
  {
    \tl_set_eq:NN
      \l__datatool_default_dbname_tl
      \l__datatool_action_name_tl
  }
  \bool_set_false:N \l_databar_multi_bars_bool
  \cs_set_eq:NN \__databar_do:n \use:n
  \tl_set:Nn \DTLbargroupindex { 0 }

```

If the ‘key’ or ‘column’ has been set, then that provides the variable, unless it’s overridden by the variable setting in the options.

```

  \__datatool_optional_key_xor_column_get_key:nTF
  {

```

No key or column. The variable will need to be provided in the options list instead (or may have already been set with `\DTLsetup`).

```

  }
  {

```

Key or column provided.

```

  \tl_set:Nn \DTLbarvariable
  { \l__databar_action_variable_tl }
  \clist_put_right:Nx \l__datatool_action_assign_clist
  {
    \exp_not:N \l__databar_action_variable_tl =
    \l__datatool_action_key_tl
  }
}
{

```

Invalid syntax.

```

  \cs_set_eq:NN \__databar_do:n \cs_none:n
}
\__databar_do:n
{

```

Parse options if set.

```

  \clist_if_empty:NTF \l__datatool_action_options_clist
  {
    \l__databar_pre_init_tl
  }
  {
    \keys_set_groups:nnV { datatool/bar } { pre-parse }
    \l__datatool_action_options_clist
    \l__databar_pre_init_tl
    \keys_set:nV { datatool/bar }
    \l__datatool_action_options_clist
  }
  \l__databar_init_tl

```

Check variable has been set.

```
\tl_if_empty:NT \DTLbarvariable
{
  \cs_set_eq:NN \__databar_do:n \use_none:n
  \seq_if_empty:NTF \l__databar_variables_seq
  {
    \__datatool_action_error:nnn { databar }
    {
      \token_to_str:N \DTLbarchart \c_space_tl ~ missing ~ variable
    }
    {
      You ~ need ~ to ~ either ~ use ~ `key' ~ or ~ `column' ~
      to ~ identify ~ the ~ variable ~ column ~ or ~ set ~
      the ~ `variable' ~ key ~ to ~ the ~ placeholder ~
      command ~ within ~ `options'
    }
  }
  {
    \__datatool_action_error:nnn { databar }
    {
      missing ~ variable ~ (either ~ use ~ `key' ~ or ~ `column' ~
      to ~ identify ~ the ~ variable ~ column ~ or ~ set ~
      the ~ `variable' ~ key ~ to ~ the ~ placeholder ~
      command ~ within ~ `options')
    }
    {
      Remember ~ that ~ you ~ need ~ to ~ use ~ `variable' ~
      not ~ `variables' ~ for ~ a ~ single ~ variable ~ bar ~ chart
    }
  }
}
\tl_if_empty:NF \l__databar_yticgap_tl
{
  \fp_set:Nn \l__databar_yticgap_fp
  { \l__databar_yticgap_tl }
  \fp_compare:nNnT { \l__databar_yticgap_fp } < { \c_zero_fp }
  {
    \__datatool_action_error:nnn { databar }
    {
      y-tick ~ gap ~ \tl_to_str:o { \l__databar_yticgap_tl } ' ~
      is ~ negative
    }
    {
      The ~ y ~ tick ~ gap ~ specification ~ evaluates ~ to ~
      a ~ negative ~ number ~ ( \fp_to_decimal:N \l__databar_yticgap_fp) ~
      so ~ the ~ yticgap ~ setting ~ will ~ be ~ ignored
    }
  }
  \tl_clear:N \l__databar_yticgap_tl
  \fp_zero:N \l__databar_yticgap_fp
}
```

```

    }
  }
  \__databar_do:n
  {
    \exp_args:NV \__databar_do_chart:n
    \l_datatool_action_assign_clist
  }
}
\group_end:
}
Scratch placeholder for action if key or column given instead of variable:
\tl_new:N \l__databar_action_variable_tl
\cs_new:Nn \__databar_single_update:
{
  \exp_args:NNV \tl_set_eq:NN
  \l_dataplot_y_tl \DTLbarvariable
  \__databar_update_bounds:
}
\cs_new:Nn \__databar_do_update:
{
  \__databar_single_update:
}
\cs_new:Nn \__databar_multi_variables_update:
{
  \seq_map_inline:Nn \l__databar_variables_seq
  {
    \tl_set_eq:NN \l_dataplot_y_tl ##1
    \__databar_update_bounds:
  }
}
\cs_new:Nn \__databar_multi_columns_update:
{
  \seq_map_inline:Nn \l_datatool_action_columns_seq
  {
    \exp_args:NNno
    \dtl@getentryfromrow
    \l_dataplot_y_tl
    { ##1 }
    \l_datatool_map_data_row_tl
    \__databar_update_bounds:
  }
}
}
\cs_new:Nn \__datatool_calc_bar_lengths:n
{
  \bool_lazy_or:nnTF

```

Compute the bar heights unless `\DTLbarmax` has been set and negative extent unless `\DTLnegextent` has been set. This needs to take into account number formatting.


```

        { \fp_to_decimal:N \l__dataplot_min_y_fp }
\tl_if_empty:NF \l__databar_yticgap_tl
    {
        \fp_set:Nn \l__dataplot_y_fp { - \l__databar_yticgap_fp }
        \fp_while_do:nNnn { \l__dataplot_y_fp } > { \l__dataplot_min_y_fp }
        {
            \fp_sub:Nn \l__dataplot_y_fp { \l__databar_yticgap_fp }
        }
        \tl_set:Nx \DTLnegextent { \fp_to_decimal:N \l__dataplot_y_fp }
    }
}
{
    \tl_set:Nn \DTLnegextent { 0 }
}
}
{
    \fp_set:Nn \l__dataplot_min_y_fp { \DTLnegextent }
}
}
{
    \tl_if_empty:NF \DTLbarmax
    {
        \fp_set:Nn \l__dataplot_max_y_fp { \DTLbarmax }
    }
    \tl_if_empty:NF \DTLnegextent
    {
        \fp_set:Nn \l__dataplot_min_y_fp { \DTLnegextent }
    }
}
}

```

Update max and min values. The current value from the database column should be in `\l__dataplot_y_tl`.

```

\cs_new:Nn \__databar_update_bounds:
{
    \tl_if_empty:NF \l__dataplot_y_tl
    {
        \datatool_set_fp:Nn \l__dataplot_y_fp
        { \l__dataplot_y_tl }
        \tl_if_empty:NT \DTLbarmax
        {
            \fp_compare:nNnT
            { \l__dataplot_y_fp }
            >
            { \l__dataplot_max_y_fp }
            {
                \fp_set_eq:NN
                \l__dataplot_max_y_fp
                \l__dataplot_y_fp
            }
        }
    }
}

```

```

    }
    \tl_if_empty:NT \DTLnegextent
    {
      \fp_compare:nNnT
        { \l_dataplot_y_fp }
        <
        { \l_dataplot_min_y_fp }
      {
        \fp_set_eq:NN
          \l_dataplot_min_y_fp
          \l_dataplot_y_fp
      }
    }
  }
}

Calculate the scaling factor.
\cs_new:Nn \__databar_calc_scale:
{
  \fp_set:Nn \l__databar_extent_fp
    { \DTLbarmax - \DTLnegextent }
  \fp_set:Nn \l__databar_unit_fp
    {
      \dim_to_decimal_in_sp:n { \DTLbarchartlength }
      / \l__databar_extent_fp
    }
  \dim_set:Nn \l__databar_miny_dim
    {
      \fp_eval:n
        {
          \DTLnegextent * \l__databar_unit_fp
        }
      sp
    }
  \dim_set:Nn \l__databar_maxy_dim
    {
      \fp_eval:n
        {
          \DTLbarmax * \l__databar_unit_fp
        }
      sp
    }
}

Construct y tick list if required.
\cs_new:Nn \__databar_construct_ytics:
{
  \dim_zero:N \l__dataplot_y_tic_label_width_dim
  \ifDTLbarytics
    \clist_if_empty:NTF \l__databar_yticpoints_clist
    {

```

```

\tl_if_empty:NTF \l__databar_yticgap_tl
{
  \fp_set:Nn \l__databar_min_gap_fp
  {
    \dim_to_decimal_in_sp:n { \DTLmintickgap }
    / \l__databar_unit_fp
  }
  \__dataplot_construct_tick_list:NNNN
  \l__dataplot_min_y_fp
  \l__dataplot_max_y_fp
  \l__databar_min_gap_fp
  \l__databar_yticpoints_seq
}
{
  \__dataplot_construct_tick_list_with_gap_excl:NNNN
  \l__dataplot_min_y_fp
  \l__dataplot_max_y_fp
  \l__databar_yticpoints_seq
  \l__databar_yticgap_fp
}
}
{
  \__dataplot_to_fp_seq:NNnn
  \l__databar_yticpoints_seq
  \l__databar_y_tic_clist
  \l__dataplot_min_y_fp
  \l__dataplot_max_y_fp
}
\seq_if_empty:NT \l__databar_yticlabels_seq
{
  \seq_map_inline:Nn \l__databar_yticpoints_seq
  {
    \tl_set:Nn \l__dataplot_y_fp { ##1 }
    \__dataplot_get_default_tic_label:Nx
    \l__dataplot_y_fp { \l__databar_ytic_round_tl }
    \seq_put_right:Nx \l__databar_yticlabels_seq
    {
      \exp_not:V \l__dataplot_tic_label_tl
    }
  }
}
}
\fi
}
Do the bar chart
\cs_new:Nn \__databar_chart:n
{
  \begin{tikzpicture}
Set unit vectors
  \ifDTLverticalbars

```

```

\pgfsetyvec
{
  \pgfpoint
  { 0pt } { \fp_to_int:N \l__databar_unit_fp ~ sp }
}
\pgfsetxvec
{
  \pgfpoint { \DTLbarwidth } { 0pt }
}
\else
\pgfsetxvec
{
  \pgfpoint
  { \fp_to_int:N \l__databar_unit_fp ~ sp } { 0pt }
}
\pgfsetyvec
{
  \pgfpoint { 0pt } { \DTLbarwidth }
}
\fi
Begin hook
\DTLbaratbegintikz
Initialise the start point. This is the y co-ordinate for the first corner of the bar along
the y axis. The end point is the start point plus one unit (which will be the same as the
bar index).
\fp_zero:N \l__databar_start_fp
Iterate through data
\__databar_filtered_map:nn { #1 }
{
The bar index is the same as the value of \l__databar_index_int:
\tl_set:Nx \DTLbarindex { \int_use:N \l__databar_index_int }
Draw the current bar.
\__databar_draw_bar:
}
Clear content token list variable.
\tl_clear:N \l__dataplot_content_tl
Add axes drawing code to content:
\__databar_draw_axes:
Add y tick marks if required
\seq_map_indexed_function:NN
\l__databar_yticpoints_seq
\__databar_draw_y_tics_fn:nn
Do any pending content and clear token list variable.
\l__dataplot_content_tl
\tl_clear:N \l__dataplot_content_tl

```

Add the y label if required

```
\__databar_plot_ylabel:
```

Do any pending content and clear token list variable.

```
\l__dataplot_content_tl  
\tl_clear:N \l__dataplot_content_tl
```

End hook

```
\DTLbaratendtikz  
\end{tikzpicture}
```

```
}
```

Draw bar:

```
\cs_new:Nn \__databar_draw_bar:  
{
```

`\DTLbarvariable` should be defined to the actual placeholder command.

```
\__databar_draw_bar:Nvxx \DTLbarvariable  
\l__databar_index_int  
{  
  \tl_if_empty:NF \l__databar_barlabel_tl  
  {  
    \exp_not:N \DTLdisplaylowerbarlabel  
    { \exp_not:V \l__databar_barlabel_tl }  
  }  
}  
{  
  \tl_if_empty:NF \l__databar_upperbarlabel_tl  
  {  
    \exp_not:N \DTLdisplayupperbarlabel  
    { \exp_not:V \l__databar_upperbarlabel_tl }  
  }  
}
```

Update start.

```
\fp_add:Nn \l__databar_start_fp { \c_one_fp }  
}
```

`__databar_draw_bar:Nnnn<tl-var>{<bar index>}{<lower label>}{<upper label>}` Draw bar for the given variable. The starting point `\l__databar_start_int` should already be set. For multi bar charts, the bar index is the index within the group (that is, it's reset to 1 at the start of each group).

```
\cs_new:Nn \__databar_draw_bar:Nnnn  
{
```

Add the inter bar gap if this isn't the first bar.

```
\tl_if_eq:NnF \l__databar_bargap_tl { 0 }  
{  
  \int_compare:nNnT  
  { #2 } > { \c_one_int }  
  {  
    \fp_add:Nn \l__databar_start_fp
```

```

        { \l__databar_bargap_tl }
    }
}
\tl_set:Nx \l__databar_start_tl
{ \fp_to_decimal:N \l__databar_start_fp }

```

Content token list variable is reset for each bar to allow the hook to access the current bar settings.

```
\tl_clear:N \l__dataplot_content_tl
```

Get the variable. The original variable data is stored in `\l__dataplot_y_tl` but this will be a formatted number that needs converting to a decimal. This is stored twice: as a floating point variable `\l__dataplot_y_fp` to avoid repeated parsing where calculations are required, and as a token list variable `\l__dataplot_decimal_y_tl` where the value needs expanding for the `pgf` parser.

```

\tl_set_eq:NN \l__dataplot_y_tl #1
\tl_if_empty:NTF \l__dataplot_y_tl
{

```

Missing data for this row so assume 0.

```

    \fp_zero:N \l__dataplot_y_fp
    \tl_set:Nn \l__dataplot_decimal_y_tl { 0 }
    \tl_set:Nn \DTLbarvalue
        { \__datatool_datum:nnnn { 0 } { 0 } { } { \c_datatool_decimal_int } }
}
{
    \datatool_set_fp:NV \l__dataplot_y_fp
        \l__dataplot_y_tl
    \tl_set:Nx \l__dataplot_decimal_y_tl
        { \fp_to_tl:N \l__dataplot_y_fp }

```

Set `\DTLbarvalue` to the rounded formatted value for use in the labels or hook.

```

\tl_set:Nx \l__datatool_result_tl
{
    \fp_to_decimal:n
        { round ( \l__dataplot_y_fp, \c@DTLbarroundvar ) }
}
\datatool_pad_trailing_zeros:Nn
    \l__datatool_result_tl \c@DTLbarroundvar
\exp_args:NV \DTLdecimaltolocale
    \l__datatool_result_tl \l__datatool_tmpa_tl
\tl_set:Nx \DTLbarvalue
{
    \exp_not:N \__datatool_datum:nnnn
    { \exp_not:V \l__datatool_tmpa_tl }
    { \exp_not:V \l__datatool_result_tl }
    { }
    { \exp_not:N \c_datatool_decimal_int }
}
}

```

Mid point of bar (along the y axis).

```

\tl_set:Nx \l__databar_mid_tl
  { \fp_eval:n { \l__databar_start_fp + 0.5 } }
\dim_set_eq:NN \l__databar_mid_dim \DTLbarwidth
\dim_set:Nn \l__databar_mid_dim
  {
    \l__databar_mid_tl \DTLbarwidth
  }
\dim_set:Nn \l__databar_extent_dim
  {
    \fp_eval:n
      {
        \l__dataplot_y_fp * \l__databar_unit_fp
      }
    sp
  }

```

End point.

```

\tl_set:Nx \l__databar_end_tl
  { \fp_eval:n { \l__databar_start_fp + \c_one_fp } }

```

Set placeholder commands `\DTLstartpt`, `\DTLmidpt` and `\DTLendpt`. These are the start, middle and end of the bar along the bar's mid axis.

```

\ifDTLverticalbars
  \tl_set:Nx \DTLstartpt
    {
      \exp_not:N \pgfpointxy
        { \l__databar_mid_tl } { 0 }
    }
  \tl_set:Nx \DTLmidpt
    {
      \exp_not:N \pgfpointxy
        { \l__databar_mid_tl }
        { \fp_to_decimal:n { 0.5 \l__dataplot_y_fp } }
    }
  \tl_set:Nx \DTLendpt
    {
      \exp_not:N \pgfpointxy
        { \l__databar_mid_tl }
        { \l__dataplot_decimal_y_tl }
    }
\else
  \tl_set:Nx \DTLstartpt
    {
      \exp_not:N \pgfpointxy
        { 0 } { \l__databar_mid_tl }
    }
  \tl_set:Nx \DTLmidpt
    {
      \exp_not:N \pgfpointxy

```

```

        { \fp_to_decimal:n { 0.5 \l__dataplot_y_fp } }
        { \l__databar_mid_tl }
    }
    \tl_set:Nx \DTLendpt
    {
        \exp_not:N \pgfpointxy
        { \l__dataplot_decimal_y_tl }
        { \l__databar_mid_tl }
    }
\fi
Draw bar.
\tl_put_right:Nn \l__dataplot_content_tl
{
    \begin{scope}
Every pre bar hook
\tl_put_right:Nn \l__dataplot_content_tl
{ \DTLeveryprebarhook }
\fp_compare:nNnTF { \l__dataplot_y_fp } < { \c_zero_fp }
{
    \tl_set:Nx \l__datatool_tmpa_tl
    {
        \DTLgetnegbarcolor { #2 }
    }
}
{
    \tl_set:Nx \l__datatool_tmpa_tl
    {
        \DTLgetbarcolor { #2 }
    }
}
\tl_put_right:Nn \l__dataplot_content_tl
{
    \path ~ [
\tl_if_empty:NF \l__datatool_tmpa_tl
{
    \tl_put_right:Nx \l__dataplot_content_tl
    {
        fill = \l__datatool_tmpa_tl ,
    }
}
}
\bool_lazy_and:nnT
{
    \tl_if_empty_p:N \DTLbaroutlinecolor
}
{
    \dim_compare_p:nNn
    { \DTLbaroutlinewidth } > { \c_zero_dim }

```

```

}
{
\tl_put_right:Nx \l__dataplot_content_tl
{
draw = \DTLbaroutlinecolor ,
line ~ width = \exp_not:N \DTLbaroutlinewidth ,
}
}
\tl_put_right:Nx \l__dataplot_content_tl
{
\DTLBarStyle ]
}
\ifDTLverticalbars
\tl_put_right:Nx \l__dataplot_content_tl
{
( \l__databar_start_tl , ~ 0 ) ~
-- ~
(
\l__databar_start_tl , ~
\l__dataplot_decimal_y_tl
) ~
-- ~
(
\l__databar_end_tl , ~
\l__dataplot_decimal_y_tl
) ~
-- ~
( \l__databar_end_tl , ~ 0 )
}
\else
\tl_put_right:Nx
\l__dataplot_content_tl
{
( 0 , ~ \l__databar_start_tl ) ~
-- ~
(
\l__dataplot_decimal_y_tl , ~
\l__databar_start_tl
) ~
-- ~
(
\l__dataplot_decimal_y_tl , ~
\l__databar_end_tl
) ~
-- ~
( 0 , ~ \l__databar_end_tl )
}
\fi
\tl_put_right:Nn \l__dataplot_content_tl
{

```

```

-- ~ cycle; ~
\end{scope}
}

```

Draw lower bar label.

```

\fp_compare:nNnTF { \l__dataplot_y_fp } < { \c_zero_fp }
{
  \tl_set_eq:NN \l__databar_label_current_offset_tl
  \l__databar_label_neg_offset_tl
  \tl_set:Nx \l__databar_label_current_align_tl
  { \DTLbarXneglabelalign }
}
{
  \tl_set_eq:NN \l__databar_label_current_offset_tl
  \l__databar_label_pos_offset_tl
  \tl_set:Nx \l__databar_label_current_align_tl
  { \DTLbarXlabelalign }
}
\tl_if_empty:nF { #3 }
{
  \tl_put_right:Nn \l__dataplot_content_tl
  {
    \pgftext [ at =
  ]
  \ifDTLverticalbars
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    {
      \exp_not:N \pgfpoint
      { \l__databar_mid_dim }
      { \l__databar_label_current_offset_tl }
    }
  }
  \else
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    {
      \exp_not:N \pgfpoint
      { \l__databar_label_current_offset_tl }
      { \l__databar_mid_dim }
    }
  }
  \fi
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    , \exp_not:N \l__databar_label_current_align_tl
  ]
  }
  \tl_put_right:Nn \l__dataplot_content_tl
  {

```

```

        { #3 }
    }
    \bool_lazy_and:nnT
    { \bool_if_p:N \l_databar_multi_bars_bool }
    { ! \tl_if_empty_p:N \l__databar_barlabel_tl }
    {
        \tl_put_right:Nn \l__dataplot_content_tl
        { \__databar_update_group_offset: }
    }
}

Draw upper bar label
\tl_if_empty:nF { #4 }
{
    \tl_put_right:Nn \l__dataplot_content_tl
    {
        \pgftext [ at =
    }
    \ifDTLverticalbars
Vertical bars.
    \fp_compare:nNnTF
    { \l__dataplot_y_fp } < { \c_zero_fp }
    {
        \tl_put_right:Nx \l__dataplot_content_tl
        {
            {
                \exp_not:N \pgfpoint
                { \l__databar_mid_dim }
                {
                    \dim_eval:n
                    {
                        \l__databar_extent_dim
                        + \l__databar_upper_label_neg_offset_tl
                    }
                }
            }
        }
        , ~ \DTLbarXnegupperlabelalign
    }
}
{
    \tl_put_right:Nx \l__dataplot_content_tl
    {
        {
            \exp_not:N \pgfpoint
            { \l__databar_mid_dim }
            {
                \dim_eval:n
                {
                    \l__databar_extent_dim
                    + \l__databar_upper_label_pos_offset_tl
                }
            }
        }
    }
}

```

```

    }
  }
  , ~ \DTLbarXupperlabelalign
}
\else
Horizontal bars.
\fp_compare:nNnTF
{ \l__dataplot_y_fp } < { \c_zero_fp }
{
\tl_put_right:Nx \l__dataplot_content_tl
{
{
\exp_not:N \pgfpoint
{
\dim_eval:n
{
\l__databar_extent_dim
+ \l__databar_upper_label_neg_offset_tl
}
}
{ \l__databar_mid_dim }
}
, ~ \DTLbarXnegupperlabelalign
}
}
\tl_put_right:Nx \l__dataplot_content_tl
{
{
\exp_not:N \pgfpoint
{
\dim_eval:n
{
\l__databar_extent_dim
+ \l__databar_upper_label_pos_offset_tl
}
}
{ \l__databar_mid_dim }
}
, ~ \DTLbarXupperlabelalign
}
}
\fi
\tl_put_right:Nn \l__dataplot_content_tl
{
}
{ #4 }

```

```

    }
  }
Every bar hook
  \tl_put_right:Nn \l__dataplot_content_tl
  { \DTLeverybarhook }
Do content and clear token list variable.
  \l__dataplot_content_tl
  \tl_clear:N \l__dataplot_content_tl
}
\cs_generate_variant:Nn \__databar_draw_bar:Nnnn
{ NVxx , NnVV }
Draw axes if applicable.
\cs_new:Nn \__databar_draw_axes:
{
Draw x axis
  \ifDTLbarxaxis
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw [ \DTLBarXAxisStyle ] ~
    (0,0) ~ -- ~
  }
  \ifDTLverticalbars
  \tl_put_right:Nn \l__dataplot_content_tl
  {
    ( \DTLbarchartwidth, 0 );
  }
  \else
  \tl_put_right:Nn \l__dataplot_content_tl
  {
    ( 0, \DTLbarchartwidth );
  }
  \fi
\fi
Draw y axis
  \ifDTLbaryaxis
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw [ \DTLBarYAxisStyle ] ~
  }
  \ifDTLverticalbars
  \tl_put_right:Nn \l__dataplot_content_tl
  {
    ( 0, \DTLnegextent ) ~ -- ~ ( 0, \DTLbarmax );
  }
  \else
  \tl_put_right:Nn \l__dataplot_content_tl
  {

```

```

        ( \DTLnegextent, 0) ~ -- ~ ( \DTLbarmax, 0 );
    }
    \fi
\fi
}
\cs_new:Nn \__databar_draw_y_tics_fn:nn
{
  \tl_set:Nn \l__dataplot_y_fp { #2 }
  \tl_set:Nx \l__dataplot_decimal_y_tl
    { \fp_to_decimal:N \l__dataplot_y_fp }
  \dim_set:Nn \l__databar_extent_dim
    {
      \fp_eval:n
      {
        \l__dataplot_y_fp * \l__databar_unit_fp
      }
      sp
    }
  \ifDTLverticalbars
    \tl_put_right:Nx \l__dataplot_content_tl
    {
      \exp_not:N \pgfpathmoveto
      {
        \exp_not:N \pgfpointxy
        { 0 } { \l__dataplot_decimal_y_tl }
      }
      \exp_not:N \pgfpathlineto
      {
        \exp_not:N \pgfpoint
        { \dim_to_decimal:n { - \DTLticklength } pt }
        { \l__databar_extent_dim }
      }
    }
  }
\else
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \pgfpathmoveto
    {
      \exp_not:N \pgfpointxy
      { \l__dataplot_decimal_y_tl } { 0 }
    }
    \exp_not:N \pgfpathlineto
    {
      \exp_not:N \pgfpoint
      { \l__databar_extent_dim }
      { \dim_to_decimal:n { - \DTLticklength } pt }
    }
  }
}
\fi

```

```

\tl_put_right:Nn \l__dataplot_content_tl
{
  \pgfusepath{stroke}
}
\int_compare:nNnTF
{ #1 } > { \seq_count:N \l__databar_yticlabels_seq }
{
  \__dataplot_get_default_tic_label:Nx
  \l__dataplot_y_fp { \l__databar_ytic_round_tl }
}
{
  \tl_set:Nx \l__dataplot_tic_label_tl
  { \seq_item:Nn \l__databar_yticlabels_seq { #1 } }
}
\tl_put_right:Nx \l__dataplot_content_tl
{
  \exp_not:N \pgftext [ \DTLbarYticklabelalign , at=
}
\ifDTLverticalbars
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    {
      \exp_not:N \pgfpoint
      { \dim_to_decimal:n { -\DTLticklabeloffset } pt }
      { \l__databar_extent_dim }
    }
  }
\else
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    {
      \exp_not:N \pgfpoint
      { \l__databar_extent_dim }
      { \dim_to_decimal:n { -\DTLticklabeloffset } pt }
    }
  }
\fi
\tl_put_right:Nx \l__dataplot_content_tl
{
  ]
  {
    \exp_not:N \DTLbardisplayYticklabel
    { \exp_not:N \l__dataplot_tic_label_tl }
  }
}
\tl_if_empty:NF \l__databar_ylabel_tl
{
  \tl_put_right:Nn \l__dataplot_content_tl
  { \__databar_update_ylabel_offset: }
}

```

```

\l_dataplot_content_tl
\tl_clear:N \l_dataplot_content_tl
}
\cs_new:Nn \__databar_update_ylabel_offset:
{
\ifDTLverticalbars
\dim_set:Nn
\l_dataplot_y_tic_label_width_dim
{
\dim_max:nn
{ \l_dataplot_y_tic_label_width_dim }
{ \dim_abs:n { \pgf@pathminx } }
}
\else
\dim_set:Nn
\l_dataplot_y_tic_label_width_dim
{
\dim_max:nn
{ \l_dataplot_y_tic_label_width_dim }
{ \dim_abs:n { \pgf@pathminy } }
}
\fi
}
\cs_new:Nn \__databar_plot_ylabel:
{
\tl_if_empty:NF \l__databar_ylabel_tl
{
\dim_add:Nn \l_dataplot_y_tic_label_width_dim
{ \l__databar_ylabel_offset_tl }
\tl_put_right:Nx \l_dataplot_content_tl
{
\exp_not:N \pgftext
[
at = { \l__databar_ylabel_pos_tl } ,
\DTLAxisLabelStyle
]
{ \exp_not:V \l__databar_ylabel_tl }
}
}
}
}

```

`\DTLmultibarchart[conditions]{option list}{db name}{assign list}`

`\DTLmultibarchart`

Make a multi-bar chart from data given in data base *db name*, where *assign list* is a comma-separated list of *cmd*=*key* pairs. *option list* must include the variables key which must be a comma separated list of commands, where each command is

included in *<assign list>*. The optional argument *<conditions>* is the same as that for `\DTLforeach`.

```

\NewDocumentCommand \DTLmultibarchart { o m m m }
{
  \group_begin:
  \bool_set_true:N \l_databar_multiBars_bool
  \IfValueT { #1 }
  {
    \cs_set:Npn \__databar_filter:T ##1
    {
      \ifthenelse { #1 } { ##1 } { }
    }
  }
  \tl_if_blank:nF { #3 }
  {
    \DTLsetup { default-name = { #3 } }
  }
  \keys_set_groups:nnn { datatool/bar } { pre-parse } { #2 }
  \l__databar_pre_init_tl
  \keys_set:nn { datatool/bar } { #2 }
  \l__databar_init_tl
  \cs_set_eq:NN \__databar_do:n \use:n
  \seq_if_empty:NT \l__databar_variables_seq
  {
    \cs_set_eq:NN \__databar_do:n \use_none:n
    \tl_if_empty:NTF \DTLbarvariable
    {
      \PackageError { databar }
      {
        \token_to_str:N \DTLmultibarchart \c_space_tl ~ missing ~ variables
      }
      {
        You ~ need ~ to ~ set ~ the ~ `variables' ~
        key ~ to ~ the ~ list ~ of ~ placeholder ~ commands
      }
    }
  }
  {
    \PackageError { databar }
    {
      \token_to_str:N \DTLmultibarchart \c_space_tl ~ missing ~
      variables ~ (`variable' ~ setting ~ not ~ applicable ~
      for ~ multibar ~ charts)
    }
    {
      Remember ~ that ~ you ~ need ~ to ~ use ~ `variables' ~
      not ~ `variable' ~ with ~ \token_to_str:N \DTLmultibarchart
    }
  }
}
}

```

```

\tl_if_empty:NF \l__databar_yticgap_tl
{
  \fp_set:Nn \l__databar_yticgap_fp
  { \l__databar_yticgap_tl }
  \fp_compare:nNnT { \l__databar_yticgap_fp } < { \c_zero_fp }
  {
    \PackageError { databar }
    {
      y-tick ~ gap ~ ``\tl_to_str:o { \l__databar_yticgap_tl } ' ~
      is ~ negative
    }
    {
      The ~ y ~ tick ~ gap ~ specification ~ evaluates ~ to ~
      a ~ negative ~ number ~ ( \fp_to_decimal:N \l__databar_yticgap_fp) ~
      so ~ the ~ yticgap ~ setting ~ will ~ be ~ ignored
    }
  }
  \tl_clear:N \l__databar_yticgap_tl
  \fp_zero:N \l__databar_yticgap_fp
}
}
\__databar_do:n
{
  \cs_set_eq:NN
  \__databar_do_update:
  \__databar_multi_variables_update:
  \cs_set_eq:NN
  \__databar_drawBars:
  \__databar_variables_drawBars:
  \tl_set:Nx \DTLbartotalvariables
  { \seq_count:N \l__databar_variables_seq }
  \__databar_do_multi_chart:n { #4 }
}
\group_end:
}
Action 'multibar chart':
\cs_new:cn { __datatool_action_multibar ~ chart : }
{
  \group_begin:
  \tl_if_empty:NF \l__datatool_action_name_tl
  {
    \tl_set_eq:NN
    \l__datatool_default_dbname_tl
    \l__datatool_action_name_tl
  }
  \bool_set_true:N \l__databar_multiBars_bool
  \cs_set_eq:NN \__databar_do:n \use:n
  \__datatool_optional_columns:
  \clist_if_empty:NTF \l__datatool_action_options_clist
  {

```

```

    \l_databar_pre_init_tl
  }
  {
    \keys_set_groups:nnV { datatool/bar } { pre-parse }
      \l_datatool_action_options_clist
    \l_databar_pre_init_tl
    \keys_set:nV { datatool/bar }
      \l_datatool_action_options_clist
  }
\l_databar_init_tl
\seq_if_empty:NTF \l_datatool_action_columns_seq
{
  \seq_if_empty:NTF \l_databar_variables_seq
  {
    \__datatool_action_error:nn
    {
      missing ~ variables
    }
    {
      You ~ need ~ to ~ either ~ set ~ the ~ `keys' ~
      or ~ `columns' ~ action ~ settings ~ or ~ set ~
      `variables' ~ within ~ the ~ `options' ~
      action ~ setting ~ in ~
      \token_to_str:N \DTLaction [...]{ \l_datatool_action_tl }
    }
    \cs_set_eq:NN \__databar_do:n \cs_none:n
  }
  {
    \tl_set:Nx \DTLbartotalvariables
    { \seq_count:N \l_databar_variables_seq }
    \cs_set_eq:NN
      \__databar_do_update:
      \__databar_multi_variables_update:
    \cs_set_eq:NN
      \__databar_drawBars:
      \__databar_variables_drawBars:
  }
}
{
  \tl_set:Nx \DTLbartotalvariables
  { \seq_count:N \l_datatool_action_columns_seq }
  \cs_set_eq:NN
    \__databar_do_update:
    \__databar_multi_columns_update:
  \cs_set_eq:NN
    \__databar_drawBars:
    \__databar_columns_drawBars:
}
\__databar_do:n
{

```

```

        \exp_args:NV
        \__databar_do_multi_chart:n
        \l_datatool_action_assign_clist
    }
\group_end:
}
\cs_new:Nn \__databar_do_multi_chart:n
{
    \tl_clear:N \DTLtotalbars
    \__datatool_calc_bar_lengths:n { #1 }
}
Calculate the total number of bar groups if not already found.
\tl_if_empty:NT \DTLtotalbars
{
    \__databar_filtered_map:nn { #1 } { }
    \tl_set:NV \DTLtotalbars \l__databar_index_int
}
\tl_set_eq:NN \DTLtotalbargroups \DTLtotalbars
Calculate the overall total number of bars.
\tl_set:Nx \DTLtotalbars
{ \int_eval:n { \DTLtotalbargroups * \DTLbartotalvariables } }
Calculate the bar group width, which needs to take into account the bar gap, but first
set it to just the total number of bars in a group.
\tl_set:Nx \DTLbargroupwidth
{ \DTLbartotalvariables }
Add on the inter bar gaps to the group width.
\tl_if_eq:NnF \l__databar_bargap_tl { 0 }
{
    \tl_set:Nx \DTLbargroupwidth
    {
        \fp_eval:n
        {
            \DTLbargroupwidth
            + \l__databar_bargap_tl
            * ( \DTLbargroupwidth - \c_one_fp )
        }
    }
}
Calculate the bar chart width (x-axis length).
\tl_set:Nx \DTLbarchartwidth
{
    \fp_eval:n
    {
        \DTLtotalbargroups * \DTLbargroupwidth
        + \l__databar_groupgap_tl
        * ( \DTLtotalbargroups - \c_one_fp )
    }
}

```

```

    }
    \__databar_calc_scale:
    \__databar_construct_ytics:
    \__databar_multi_chart:n { #1 }
  }
Code that loops through each variable:
\cs_new:Nn \__databar_draw_bars:
{
  \__databar_variables_draw_bars:
}
Draw bars if variables option used:
\cs_new:Nn \__databar_variables_draw_bars:
{
  \seq_map_indexed_function:NN
    \l__databar_variables_seq
    \__databar_draw_bar:nn
}
Draw bars if columns or keys action setting used:
\cs_new:Nn \__databar_columns_draw_bars:
{
  \seq_map_indexed_inline:Nn
    \l__datatool_action_columns_seq
    {
      \exp_args:NNno
        \dtl@getentryfromrow
        \l__databar_action_variable_tl
        { ##2 }
        \l__datatool_map_data_row_tl
        \__databar_draw_bar:nn
        { ##1 }
        \l__databar_action_variable_tl
    }
}
\cs_new:Nn \__databar_multi_chart:n
{
  \begin{tikzpicture}
Set unit vectors
  \ifDTLverticalbars
    \pgfsetyvec
    {
      \pgfpoint
      { 0pt } { \fp_to_int:N \l__databar_unit_fp ~ sp }
    }
  \pgfsetxvec
  {
    \pgfpoint { \DTLbarwidth } { 0pt }
  }
}

```

```

\else
  \pgfsetxvec
  {
    \pgfpoint
    { \fp_to_int:N \l__databar_unit_fp ~ sp } { 0pt }
  }
  \pgfsetyvec
  {
    \pgfpoint { 0pt } { \DTLbarwidth }
  }
\fi

Begin hook
  \DTLbaratbegintikz

Initialise:
  \fp_zero:N \l__databar_start_fp

Iterate through data
  \__databar_filtered_map:nn { #1 }
  {

Initialise bar group label offset.
  \dim_zero:N \l__databar_group_label_offset_dim

Draw each bar in the group.
  \__databar_draw_bars:

Do the bar group label, if set.
  \tl_if_empty:NF \l__databar_barlabel_tl
  {
    \dim_add:Nn
      \l__databar_group_label_offset_dim
      { \DTLbarlabeloffset }
    \tl_put_right:Nn \l__dataplot_content_tl
      { \pgftext [ at = \pgfpoint ]
        \ifDTLverticalbars
          \tl_put_right:Nx \l__dataplot_content_tl
          {
            {
              \fp_eval:n
              {
                \l__databar_start_fp
                - 0.5 * \DTLbargroupwidth
              }
              \exp_not:N \DTLbarwidth
            }
            {
              - \exp_not:N \l__databar_group_label_offset_dim
            }
          }
        }
      }
  }
\else

```

```

\l_dataplot_content_tl
{
  {
    - \exp_not:N \l_databar_group_label_offset_dim
  }
  {
    \fp_eval:n
    {
      \l_databar_start_fp
      - 0.5 * \DTLbargroupwidth
    }
    \exp_not:N \DTLbarwidth
  }
}
\fi
\l_dataplot_content_tl
{
  , ~ \DTLbargrouplabelalign ] ~
  {
    \exp_not:N \DTLdisplaybargrouplabel
    { \exp_not:N \l_databar_barlabel_tl }
  }
}
\l_dataplot_content_tl
\l_clear:N \l_dataplot_content_tl
}

```

Bar group hook

```

\DTLeverybargrouphook
\fp_add:Nn \l_databar_start_fp { \l_databar_groupgap_tl }
}

```

Add axes drawing code to content:

```
\__databar_draw_axes:
```

Add *y* tick marks if required

```

\seq_map_indexed_function:NN
  \l_databar_yticpoints_seq
  \__databar_draw_y_tics_fn:nn

```

Do any pending content and clear token list variable.

```

\l_dataplot_content_tl
\l_clear:N \l_dataplot_content_tl

```

Add the *y* label if required

```
\__databar_plot_ylabel:
```

Do any pending content and clear token list variable.

```

\l_dataplot_content_tl
\l_clear:N \l_dataplot_content_tl

```

End hook

```

\DTLbaratendtikz
\end{tikzpicture}
}
Draw all bars in the current group.
\cs_new:Nn \__databar_draw_bar:nn
{
The bar group index is the same as the value of \l__databar_index_int:
\tl_set:Nx \DTLbargroupindex
{ \int_use:N \l__databar_index_int }
\tl_set:Nn \DTLbarindex { #1 }
Set the lower label
\tl_set:Nx \l__databar_lowerbarlabel_tl
{ \seq_item:Nn \l__databar_multibarlabels_seq { #1 } }
\tl_if_empty:NF \l__databar_lowerbarlabel_tl
{
\tl_set:Nx \l__databar_lowerbarlabel_tl
{
\exp_not:N \DTLdisplaylowermultibarlabel
{ \exp_not:V \l__databar_lowerbarlabel_tl }
}
}
Set the upper label
\tl_set:Nx \l__databar_upperbarlabel_tl
{ \seq_item:Nn \l__databar_uppermultibarlabels_seq { #1 } }
\tl_if_empty:NF \l__databar_upperbarlabel_tl
{
\tl_set:Nx \l__databar_upperbarlabel_tl
{
\exp_not:N \DTLdisplayuppermultibarlabel
{ \exp_not:V \l__databar_upperbarlabel_tl }
}
}
\__databar_draw_bar:NnVV #2 { #1 }
\l__databar_lowerbarlabel_tl
\l__databar_upperbarlabel_tl
\fp_add:Nn \l__databar_start_fp { \c_one_fp }
}
Update group offset.
\cs_new:Nn \__databar_update_group_offset:
{
\ifDTLverticalbars
\dim_compare:nNnT
{ \pgf@pathminy } < { \c_zero_dim }
{
\dim_set:Nn
\l__databar_group_label_offset_dim
{

```

```

        \dim_max:nn
        { \l_databar_group_label_offset_dim }
        { \dim_abs:n { \pgf@pathminy} }
    }
}
\else
\dim_compare:nNT
{ \pgf@pathminx } < { \c_zero_dim }
{
\dim_set:Nn
\l_databar_group_label_offset_dim
{
\dim_max:nn
{ \l_databar_group_label_offset_dim }
{ \dim_abs:n { \pgf@pathminx} }
}
}
}
\fi
}
\ExplSyntaxOff

```

27 datapie.sty

Declare package:

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```
\DeclareRelease{v2.32}{2019-09-27}{datapie-2019-09-27.sty}
\DeclareCurrentRelease{v3.4}{2025-04-03}
```

Declare package:

```
\ProvidesPackage{datapie}[2025/04/03 v3.4 (NLCT)]
```

Version 3.0: no longer using xkeyval.

`\ifDTLcolorpiechart` The conditional `\ifDTLcolorpiechart` is to determine whether to use colour or grey scale. NB may be removed or deprecated.

```
\newif\ifDTLcolorpiechart
\DTLcolorpiecharttrue
```

`\ifDTLrotateinner` Define boolean keys to govern label rotations.

```
\newif\ifDTLrotateinner
\DTLrotateinnerfalse
```

`\ifDTLrotateouter`

```
\newif\ifDTLrotateouter
\DTLrotateouterfalse
```

The package options have been changed to use l3keys.

Define package options:

```
\ExplSyntaxOn
\keys_define:nn { datatool }
{
  color .legacy_if_set:n = DTLcolorpiechart,
  gray .legacy_if_set_inverse:n = DTLcolorpiechart,
  rotateinner .legacy_if_set:n = DTLrotateinner,
  norotateinner .legacy_if_set_inverse:n = DTLrotateinner,
  rotateouter .legacy_if_set:n = DTLrotateouter,
  norotateouter .legacy_if_set_inverse:n = DTLrotateouter,
}
\ExplSyntaxOff
  Process options:
\IfPackageLoadedTF{datatool}
{
  \ProcessKeyOptions[datatool]
}
{
  \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{datatool}}
  \ProcessOptions
}
\RequirePackage{datatool}
```

Remove the package option keys so they can't be used with `\DTLsetup` (otherwise they may conflict with `databar` etc).

```
\ExplSyntaxOn
\keys_define:nn { datatool }
{
  color .undefine: ,
  gray .undefine: ,
  rotateinner .undefine: ,
  norotateinner .undefine: ,
  rotateouter .undefine: ,
  norotateouter .undefine: ,
}
\ExplSyntaxOff
```

Required packages:

```
\RequirePackage{tikz}
```

Define some variables that govern the appearance of the pie chart.

```
\ExplSyntaxOn
  The pie chart variable.
\tl_new:N \DTLpievariable
```

`\DTLradius` The radius of the pie chart is given by `\DTLradius`.

```
\newlength\DTLradius
\DTLradius=2cm
```

`\DTLinnerratio` The inner label offset ratio is given by `\DTLinnerratio`
`\newcommand*\DTLinnerratio}{0.5}`

`\DTLouterratio` The outer label offset ratio is given by `\DTLouterratio`.
`\newcommand*\DTLouterratio}{1.25}`

`\DTLcutawayratio` The cutaway offset ratio is given by `\DTLcutawayratio`.
`\newcommand*\DTLcutawayratio}{0.2}`

`\DTLstartangle` The angle of the first segment is given by `\DTLstartangle`.
`\newcommand*\DTLstartangle}{0}`

`\dtl@inneroffset` Version 3.0: replaced `\dtl@inneroffset` with:
`\dim_new:N \l__datapie_inner_offset_dim`
`\dim_set:Nn \l__datapie_inner_offset_dim`
`{ \DTLinnerratio \DTLradius }`

`\dtl@outeroffset` Version 3.0: replaced `\dtl@outeroffset` with:
`\dim_new:N \l__datapie_outer_offset_dim`
`\dim_set:Nn \l__datapie_outer_offset_dim`
`{ \DTLouterratio \DTLradius }`

`\dtl@cutawayoffset` Version 3.0: replaced `\dtl@cutawayoffset` with:
`\dim_new:N \l__datapie_cutaway_offset_dim`
`\dim_set:Nn \l__datapie_cutaway_offset_dim`
`{ \DTLcutawayratio \DTLradius }`

`\dtl@piecutaways` A comma separated list of segments that need to be cut away from the pie chart. This now uses a clist variable.
`\clist_new:N \l__datapie_cutaways_clist`

`\dtl@innerlabel` `\dtl@innerlabel` specifies the label to appear inside the segment. By default this is the variable used to create the pie chart.
Version 3.0: renamed `\l__datatool_pie_inner_label_tl`
`\tl_new:N \l__datapie_inner_label_tl`
`\tl_set:Nn \l__datapie_inner_label_tl { \DTLpievariable }`

`\dtl@outerlabel` Version 3.0: renamed `\l__datatool_pie_outer_label_tl`
`\tl_new:N \l__datapie_outer_label_tl`

`DTLpieroundvar` `DTLpieroundvar` is a counter governing the number of digits to round to (for display).
`\newcounter{DTLpieroundvar}`
`\setcounter{DTLpieroundvar}{1}`

`\DTLdisplayinnerlabel{<label>}`

`\DTLdisplayinnerlabel`

This is used to format the inner label. This just does the label by default.
`\newcommand*\DTLdisplayinnerlabel}[1]{#1}`

```
\DTLdisplayouterlabel{\label}
```

\DTLdisplayouterlabel

This is used to format the outer label. This just does the label by default.

```
\newcommand*\DTLdisplayouterlabel}[1]{#1}
```

No-op command:

```
\cs_new:Nn \__datapie_noop:N
```

```
{
```

```
  \PackageError { datapie }
```

```
  {
```

```
    Can't ~ use ~ \token_to_str:N #1 \c_space_tl ~ outside ~
```

```
    \token_to_str:N \DTLpiechart
```

```
  }
```

```
{
```

```
  Certain ~ datapie.sty ~ commands ~ may ~ only ~ be ~ used ~
```

```
  within ~ pie ~ chart ~ hooks ~ or ~ option ~ values
```

```
}
```

```
}
```

\DTLpiepercent \DTLpiepercent returns the percentage value of the current segment.

```
\newcommand*\DTLpiepercent}{%
```

```
  \__datapie_noop:N \DTLpiepercent
```

```
}
```

```
\cs_new:Nn \__datapie_percent:
```

```
{
```

```
  \use:c
```

```
  {
```

```
    dtl@piepercent@
```

```
    \romannumeral \l__datapie_segment_int
```

```
  }
```

```
}
```

```
\DTLpieatsegment{\segment index}{\total}{\start angle}{\mid angle}{\end angle}{\shift offset}{\inner offset}{\outer offset}
```

\DTLpieatsegment

Hook at each segment.

```
\newcommand*\DTLpieatsegment}[9]{}
```

\DTLpieatbegintikz \DTLpieatbegintikz specifies any commands to apply at the start of the tikzpicture environment. By default it does nothing.

```
\newcommand*\DTLpieatbegintikz{}
```

\DTLpieatendtikz \DTLpieatendtikz specifies any commands to apply at the end of the tikzpicture environment. By default it does nothing.

```
\newcommand*\DTLpieatendtikz{}
```

```
\DTLsetpiesegmentcolor{<n>}{<color>}
```

\DTLsetpiesegmentcolor

Assign colour name *<color>* to the *<n>*th segment.

```
\newcommand*{\DTLsetpiesegmentcolor}[2]{%
  \tl_set:cn { dtlpie@segcol\romannumeral#1 } { #2 }
}
```

```
\DTLgetpiesegmentcolor{<n>}
```

\DTLgetpiesegmentcolor

Get the colour specification for segment *<n>*

```
\newcommand*{\DTLgetpiesegmentcolor}[1]{%
  \cs_if_exist_use:cF { dtlpie@segcol\romannumeral#1 } { white }
}
```

```
\DTLdopiesegmentcolor{<n>}
```

\DTLdopiesegmentcolor

Set the colour to that for segment *<n>*

```
\newcommand*{\DTLdopiesegmentcolor}[1]{
  \cs_if_exist:cTF { dtlpie@segcol\romannumeral#1 }
  {
    \exp_args:Nc \color { dtlpie@segcol\romannumeral#1 }
  }
  {
    \PackageWarning{datapie}{No ~ colour ~ assigned ~ to ~ segment ~ \number#1}
  }
}
```

\DTLdopiesegmentcolor

\DTLdopiesegmentcolor sets the colour to that of the current segment. Allow it to also be used within \DTLmapdata or \DTLforeach.

```
\NewDocumentCommand \DTLdopiesegmentcolor { }
{
  \int_compare:nNnTF
    { \l_datapie_segment_int } > { \c_zero_int }
  {
    \exp_args:NV \DTLdopiesegmentcolor \l_datapie_segment_int
  }
  {
    \int_compare:nNnTF
      { \l_datatool_row_idx_int } > { \c_zero_int }
    {
      \exp_args:NV \DTLdopiesegmentcolor \l_datatool_row_idx_int
    }
  }
  {
    \int_compare:nNnTF
      { \dtlforeachlevel } > { \c_zero_int }
  }
}
```

```

    {
      \exp_args:Nv \DTLdopiesegmentcolor { c@DTLrow\romannumeral\dtlforeachlevel }
    }
    {
      \__datapie_noop:N \DTLdocurrentpiesegmentcolor
    }
  }
}
}
}

```

`\DTLpieoutlinecolor` `\DTLpieoutlinecolor` specifies what colour to draw the outline.

```
\newcommand*{\DTLpieoutlinecolor}{black}
```

`\DTLpieoutlinewidth` `\DTLpieoutlinewidth` specifies the line width of the outline: Outline is only drawn if the linewidth is greater than 0pt.

```
\newlength\DTLpieoutlinewidth
\DTLpieoutlinewidth=0pt
```

Set the default colours. If there are more than eight segments, more colours will need to be defined.

```

\ifDTLcolorpiechart
  \DTLsetpiesegmentcolor{1}{red}
  \DTLsetpiesegmentcolor{2}{green}
  \DTLsetpiesegmentcolor{3}{blue}
  \DTLsetpiesegmentcolor{4}{yellow}
  \DTLsetpiesegmentcolor{5}{magenta}
  \DTLsetpiesegmentcolor{6}{cyan}
  \DTLsetpiesegmentcolor{7}{orange}
  \DTLsetpiesegmentcolor{8}{white}
\else
  \DTLsetpiesegmentcolor{1}{black!15}
  \DTLsetpiesegmentcolor{2}{black!25}
  \DTLsetpiesegmentcolor{3}{black!35}
  \DTLsetpiesegmentcolor{4}{black!45}
  \DTLsetpiesegmentcolor{5}{black!55}
  \DTLsetpiesegmentcolor{6}{black!65}
  \DTLsetpiesegmentcolor{7}{black!75}
  \DTLsetpiesegmentcolor{8}{black!85}
\fi

```

Provide key=value for pie option in `\DTLsetup`

```

\keys_define:nn { datatool/pie }
{
  rotateinner .legacy_if_set:n = DTLrotateinner,
  rotate-inner .legacy_if_set:n = DTLrotateinner,
  rotateouter .legacy_if_set:n = DTLrotateouter,
  rotate-outer .legacy_if_set:n = DTLrotateouter,
}

```

Inner ratio:

```
innerratio .code:n =
```

```

    {
      \tl_set:Nn \DTLinnerratio { #1 }
      \dim_set:Nn \l__datapie_inner_offset_dim
        { \DTLinnerratio \DTLradius }
    },
inner-ratio .code:n =
    {
      \tl_set:Nn \DTLinnerratio { #1 }
      \dim_set:Nn \l__datapie_inner_offset_dim
        { \DTLinnerratio \DTLradius }
    },
Outer ratio:
outerratio .code:n =
    {
      \tl_set:Nn \DTLouterratio { #1 }
      \dim_set:Nn \l__datapie_outer_offset_dim
        { \DTLouterratio \DTLradius }
    },
outer-ratio .code:n =
    {
      \tl_set:Nn \DTLouterratio { #1 }
      \dim_set:Nn \l__datapie_outer_offset_dim
        { \DTLouterratio \DTLradius }
    },
Cutaway ratio:
cutawayratio .code:n =
    {
      \tl_set:Nn \DTLcutawayratio { #1 }
      \dim_set:Nn \l__datapie_cutaway_offset_dim
        { \DTLcutawayratio \DTLradius }
    },
cutaway-ratio .code:n =
    {
      \tl_set:Nn \DTLcutawayratio { #1 }
      \dim_set:Nn \l__datapie_cutaway_offset_dim
        { \DTLcutawayratio \DTLradius }
    },
Sets the inner offset as an absolute value (not dependent on the radius):
inneroffset .dim_set:N = \l__datapie_inner_offset_dim ,
inner-offset .dim_set:N = \l__datapie_inner_offset_dim ,
Sets the outer offset as an absolute value (not dependent on the radius):
outeroffset .dim_set:N = \l__datapie_outer_offset_dim ,
outer-offset .dim_set:N = \l__datapie_outer_offset_dim ,
Sets the cutaway offset as an absolute value (not dependent on the radius):
cutawayoffset .dim_set:N = \l__datapie_cutaway_offset_dim ,
cutaway-offset .dim_set:N = \l__datapie_cutaway_offset_dim ,

```

Starting angle:

```
start-angle .tl_set:N = \DTLstartangle,  
start .tl_set:N = \DTLstartangle,
```

Set the radius of the pie chart.

```
radius .code:n =  
{  
  \dim_set:Nn \DTLradius { #1 }  
  \dim_set:Nn \l__datapie_inner_offset_dim  
    { \DTLinnerratio \DTLradius }  
  \dim_set:Nn \l__datapie_outer_offset_dim  
    { \DTLouterratio \DTLradius }  
  \dim_set:Nn \l__datapie_cutaway_offset_dim  
    { \DTLcutawayratio \DTLradius }  
},
```

Set the radius of the pie chart without adjusting the offsets.

```
radius* .dim_set:N = \DTLradius ,
```

Rounding:

```
round .int_set:N = \c@DTLpieroundvar,  
segment-colors .code:n =  
{  
  \seq_set_from_clist:Nn \l__datatool_tmp_seq { #1 }  
  \seq_map_indexed_function:NN  
    \l__datatool_tmp_seq  
    \DTLsetpiesegmentcolor  
},  
segment-default-colors .code:n =  
{  
  \DTLcolorpiecharttrue  
  \DTLsetpiesegmentcolor{1}{red}  
  \DTLsetpiesegmentcolor{2}{green}  
  \DTLsetpiesegmentcolor{3}{blue}  
  \DTLsetpiesegmentcolor{4}{yellow}  
  \DTLsetpiesegmentcolor{5}{magenta}  
  \DTLsetpiesegmentcolor{6}{cyan}  
  \DTLsetpiesegmentcolor{7}{orange}  
  \DTLsetpiesegmentcolor{8}{white}  
},  
segment-default-colors .value_forbidden:n = true,  
segment-default-gray .code:n =  
{  
  \DTLcolorpiechartfalse  
  \DTLsetpiesegmentcolor{1}{black!15}  
  \DTLsetpiesegmentcolor{2}{black!25}  
  \DTLsetpiesegmentcolor{3}{black!35}  
  \DTLsetpiesegmentcolor{4}{black!45}  
  \DTLsetpiesegmentcolor{5}{black!55}  
  \DTLsetpiesegmentcolor{6}{black!65}  
  \DTLsetpiesegmentcolor{7}{black!75}
```

```

        \DTLsetpiesegmentcolor{8}{black!85}
    },
    segment-default-gray .value_forbidden:n = true,
    outline-color .tl_set:N = \DTLpieoutlinecolor,
    outline-width .dim_set:N = \DTLpieoutlinewidth,
List of cut away segments.
    cutaway .clist_set:N = \__datapie_cutaways_clist,
Variable used to create the pie chart. (Must be a control sequence.)
    variable .tl_set:N = \DTLpievariable,
Inner label:
    innerlabel .tl_set:N = \__datapie_inner_label_tl,
    inner-label .tl_set:N = \__datapie_inner_label_tl,
Outer label:
    outerlabel .tl_set:N = \__datapie_outer_label_tl,
    outer-label .tl_set:N = \__datapie_outer_label_tl,
Filter:
    include-if .cs_set:Np = \__datapie_filter:T #1,
    include-if-fn .code:n =
    {
        \cs_set_eq:NN \__datapie_filter:T #1
    },
Deprecated experimental setting. TODO remove
    condition .code:n =
    {
        \PackageWarning{datapie}{Deprecated ~ option ~ `condition'. ~
        Use ~ `include-if' ~ instead}
        \cs_set:Nn = \__datapie_filter:T { #1 }
    }
}
}
Allow these keys to be set in \DTLsetup{pie={...}}
\keys_define:nn { datatool }
{
    pie .code:n = { \keys_set:nn { datatool/pie } { #1 } }
}
Provide a filter function:
\cs_new:Nn \__datapie_filter:T { #1 }
\cs_new:Nn \__datapie_filtered_map:nn
{
    \DTLmapdata
    {
        \DTLmapgetvalues { #1 }
        \__datapie_filter:T { #2 }
    }
}
}

```

Floating point variables.

```
\fp_new:N \l_datapie_x_fp  
\fp_new:N \l_datapie_total_fp  
\fp_new:N \l_datapie_start_fp  
\fp_new:N \l_datapie_end_fp  
\fp_new:N \l_datapie_extent_fp  
\fp_new:N \l_datapie_angle_fp  
\fp_new:N \l_datapie_mid_fp
```

Constants:

```
\fp_const:Nn \c_datapie_whole_circle_fp { 360 }  
\fp_const:Nn \c_datapie_half_circle_fp { 180 }  
\fp_const:Nn \c_datapie_minus_half_circle_fp { -180 }  
\fp_const:Nn \c_datapie_quarter_circle_fp { 90 }  
\fp_const:Nn \c_datapie_three_quarter_circle_fp { 270 }  
\fp_const:Nn \c_datapie_minus_quarter_circle_fp { -90 }
```

Define integer variable to keep track of segments

`\@dtl@seg` Version 3.0 replaced `\@dtl@seg` with:

```
\int_new:N \l_datapie_segment_int
```

Token lists containing values to write to content token list.

`\@dtl@start` Version 3.0: replaced `\@dtl@start` with:

```
\tl_new:N \l_datapie_start_tl
```

`\dtl@midangle` Version 3.0: replaced `\dtl@midangle` with:

```
\tl_new:N \l_datapie_mid_tl
```

`\dtl@endangle` Version 3.0: replaced `\dtl@endangle` with:

```
\tl_new:N \l_datapie_end_tl
```

`\dtl@extent` Version 3.0: replaced `\dtl@extent` with:

```
\tl_new:N \l_datapie_extent_tl
```

`\dtl@angle` Version 3.0: replaced `\dtl@angle` with:

```
\tl_new:N \l_datapie_angle_tl
```

`\dtl@cutlen` Version 3.0: replaced `\dtl@cutlen` with:

```
\tl_new:N \l_datapie_cut_length_tl
```

`\dtl@innernodeopt` Version 3.0: replaced `\dtl@innernodeopt` with:

```
\tl_new:N \l_datapie_inner_node_opt_tl
```

`\dtl@outernodeopt` Version 3.0: replaced `\dtl@outernodeopt` with:

```
\tl_new:N \l_datapie_outer_node_opt_tl
```

Calculate the total (filtered column sum).

```
\cs_new:Nn \__datapie_compute_total:n
{
  \fp_zero:N \l__datapie_total_fp
  \__datapie_filtered_map:nn { #1 }
  {
    \datatool_set_fp:NV \l__datapie_x_fp \DTLpievariable
    \fp_add:Nn \l__datapie_total_fp { \l__datapie_x_fp }
  }
}
```

Calculate the angles for each segment.

```
\cs_new:Nn \__datapie_compute_angles:n
{
  \datatool_set_fp:NV \l__datapie_start_fp \DTLstartangle
  \tl_set:Nn \l__datapie_start_tl
  { \fp_to_decimal:N \l__datapie_start_fp }
  \int_zero:N \l__datapie_segment_int
  \__datapie_filtered_map:nn { #1 }
  {
    \int_incr:N \l__datapie_segment_int
    \datatool_set_fp:NV
      \l__datapie_x_fp \DTLpievariable
    \__datapie_compute_angles:nN
      { \l__datapie_segment_int }
      \l__datapie_x_fp
    \fp_set:Nn \l__datapie_x_fp
      {
        round
        (
          ( 100 * \l__datapie_x_fp ) / \l__datapie_total_fp,
          \c@DTLpieroundvar
        )
      }
    \tl_set:cx
      {
        dtl@piepercent@
        \romannumeral \l__datapie_segment_int
      }
      { \fp_to_decimal:N \l__datapie_x_fp }
    \datatool_pad_trailing_zeros:cn
      {
        dtl@piepercent@
        \romannumeral \l__datapie_segment_int
      }
      { \c@DTLpieroundvar }
  }
}
```

Compute angles for segment. Syntax: $\{\langle segment\ index\rangle\}\langle x\text{-var}\rangle$

```

\cs_new:Nn \__datapie_compute_angles:nN
{
  \fp_compare:nNnTF
    { \l__datapie_start_fp } > { \c_datapie_half_circle_fp }
    {
      if startangle > 180
        \fp_sub:Nn \l__datapie_start_fp
          { \c_datapie_whole_circle_fp }
        }
      {
        \fp_compare:nNnT
          { \l__datapie_start_fp } < { \c_datapie_minus_half_circle_fp }
          {
            if startangle < -180
              \fp_add:Nn \l__datapie_start_fp
                { \c_datapie_whole_circle_fp }
              }
            }
        \tl_set:cx
          { dtl@sang@ \romannumeral #1 }
          { \fp_to_decimal:N \l__datapie_start_fp }
        \fp_set:Nn \l__datapie_tmpa_fp
          { ( #2 * \c_datapie_whole_circle_fp ) / \l__datapie_total_fp }
        \tl_set:cx
          { dtl@angle@ \romannumeral #1 }
          { \fp_to_decimal:N \l__datapie_tmpa_fp }
        \fp_add:Nn \l__datapie_start_fp
          { \l__datapie_tmpa_fp }
        \tl_set:cx { dtl@cut@angle@ \romannumeral #1 } { 0 }
        \tl_set:cx { dtl@cut@len@ \romannumeral #1 } { 0cm }
        \tl_set:Nx \l__datapie_start_tl
          { \fp_to_decimal:N \l__datapie_start_fp }
      }
    }
}

```

The new version of tikz doesn't seem to like command names in certain contexts, so use a token list variable to build up the content of the tikzpicture.

```

\tl_new:N \l__datapie_content_tl
\tl_new:N \l__datapie_hook_tl

```

This has only partially been converted to L^AT_EX3:

```

\cs_new:Nn \__datapie_draw:n
{
  Set the starting angle
  \tl_set:Nx \l__datapie_start_tl { \DTLstartangle }
  \int_zero:N \l__datapie_segment_int
  \int_zero:N \l__datatool_row_idx_int
  \begin{tikzpicture}
  \DTLpieatbegintikz
  \__datapie_filtered_map:nn { #1 }

```

```

{
Clear the content token list used for this segment.
\tl_clear:N \l__datapie_content_tl
\int_incr:N \l__datapie_segment_int
Set the start angle.
\tl_set:Nx \l__datapie_start_tl
{
\tl_use:c
{
dtl@sang@ \romannumeral \l__datapie_segment_int
}
}
\fp_set:Nn \l__datapie_start_fp
{ \l__datapie_start_tl }
Set the extent
\tl_set:Nx \l__datapie_extent_tl
{
\tl_use:c
{
dtl@angle@
\romannumeral \l__datapie_segment_int
}
}
\fp_set:Nn \l__datapie_extent_fp
{ \l__datapie_extent_tl }
Compute the end angle
\fp_set:Nn \l__datapie_end_fp
{ \l__datapie_start_fp + \l__datapie_extent_fp }
\tl_set:Nx \l__datapie_end_tl
{ \fp_to_decimal:N \l__datapie_end_fp }
Compute the shift.
\tl_set:Nx \l__datapie_angle_tl
{
\tl_use:c
{
dtl@cut@angle@
\romannumeral \l__datapie_segment_int
}
}
\fp_set:Nn \l__datapie_angle_fp
{ \l__datapie_angle_tl }
\fp_compare:nNnT
{ \l__datapie_angle_fp } > { \c_datapie_half_circle_fp }
{
\fp_sub:Nn \l__datapie_angle_fp
{ \c_datapie_whole_circle_fp }
\tl_set:Nx \l__datapie_angle_tl

```

```

        { \fp_to_decimal:N \l_datapie_angle_fp }
    }
\l_set:Nx \l_datapie_cut_length_tl
{
  \tl_use:c
  {
    dtl@cut@len@
    \romannumeral \l_datapie_segment_int
  }
}
\l_put_right:Nn \l_datapie_content_tl
{ \begin { scope} }
\l_set:Nx \l_datapie_hook_tl
{ { \l_datapie_angle_tl } { \l_datapie_cut_length_tl } }
\l_put_right:Nx \l_datapie_content_tl
{
  [ shift =
  {
    (
      \l_datapie_angle_tl \c_colon_str
      \l_datapie_cut_length_tl
    )
  } ]
}

```

Compute the mid way angle.

```

\fp_set:Nn \l_datapie_mid_fp
{ 0.5 * \l_datapie_extent_fp + \l_datapie_start_fp }
\l_set:Nx \l_datapie_mid_tl
{ \fp_to_decimal:N \l_datapie_mid_fp }

```

Draw the segment.

```

\l_put_right:Nn \l_datapie_content_tl { \fill }
\l_put_right:Nx \l_datapie_content_tl
{
  [color= \DTLgetpiesegmentcolor \l_datapie_segment_int ]
  (0,0) ~ -- ~
  ( \l_datapie_start_tl \c_colon_str \DTLradius) ~
  arc
  (
    \l_datapie_start_tl \c_colon_str
    \l_datapie_end_tl \c_colon_str
    \DTLradius
  ) ~
  -- ~ cycle;
}

```

Draw the outline if required:

```

\dim_compare:nNnT
{ \DTLpieoutlinewidth } > { \c_zero_dim }
{

```

```

\tl_put_right:Nn \l_datapie_content_tl { \draw }
\tl_put_right:Nx \l_datapie_content_tl
{
  [color=\DTLpieoutlinecolor,
   line ~ width=\DTLpieoutlinewidth]
  (0,0) ~ -- ~
  (
    \l_datapie_start_tl \c_colon_str \DTLradius
  ) ~
  arc
  (
    \l_datapie_start_tl \c_colon_str
    \l_datapie_end_tl \c_colon_str
    \DTLradius
  ) ~
  -- ~ cycle;
}
}

```

Continue constructing segment hook:

```

\tl_put_left:Nx \l_datapie_hook_tl
{
  \exp_not:N \DTLpieatsegment
  { \int_use:N \l_datapie_segment_int }
  { \fp_to_decimal:N \l_datapie_total_fp }
  { \l_datapie_start_tl }
  { \l_datapie_mid_tl }
  { \l_datapie_end_tl }
}

```

Determine whether to rotate inner labels

```

\legacy_if:nTF { DTLrotateinner }
{

```

If the mid way angle is between 90 and 270, the text will look upside-down, so adjust accordingly.

```

\fp_compare:nTF
{
  \c_datapie_quarter_circle_fp
  < \l_datapie_mid_fp
  < \c_datapie_three_quarter_circle_fp
}
{
  \cs_set_eq:NN \__datapie_next:nn \use_i:nn
}
{
  \fp_compare:nNnTF
  { \l_datapie_mid_fp }
  < { \c_datapie_minus_quarter_circle_fp }
  {
    \cs_set_eq:NN \__datapie_next:nn \use_i:nn
  }
}

```

```

    }
    {
      \cs_set_eq:NN \__datapie_next:nn \use_ii:nn
    }
  }
  \__datapie_next:nn
  {
    \tl_set:Nx \l__datapie_inner_node_opt_tl
    {
      anchor = east ,
      rotate =
        \fp_eval:n
        { \l__datapie_mid_fp - \c_datapie_half_circle_fp }
    }
  }
  {
    \tl_set:Nx \l__datapie_inner_node_opt_tl
    {
      anchor = west ,
      rotate = \l__datapie_mid_tl
    }
  }
}

```

Don't rotate inner labels

```

}
{
  \tl_set:Nn \l__datapie_inner_node_opt_tl
  { anchor = center }
}

```

Determine whether to rotate outer labels

```

\legacy_if:nTF { DTLrotateouter }
{

```

If the mid way angle is between 90 and 270, the text will look upside-down, so adjust accordingly.

```

  \fp_compare:nTF
  {
    \c_datapie_quarter_circle_fp
    < \l__datapie_mid_fp
    < \c_datapie_three_quarter_circle_fp
  }
  {
    \cs_set_eq:NN \__datapie_next:nn \use_i:nn
  }
  {
    \fp_compare:nNnTF
    { \l__datapie_mid_fp } < { \c_datapie_minus_quarter_circle_fp }
    {
      \cs_set_eq:NN \__datapie_next:nn \use_i:nn
    }
  }
}

```

```

    {
      \cs_set_eq:NN \__datapie_next:nn \use_ii:nn
    }
  }
  \__datapie_next:nn
  {
    \tl_set:Nx \l__datapie_outer_node_opt_tl
    {
      anchor = east ,
      rotate =
        \fp_eval:n
        { \l__datapie_mid_fp - \c_datapie_half_circle_fp }
    }
  }
  {
    \tl_set:Nx \l__datapie_outer_node_opt_tl
    {
      anchor = west ,
      rotate = \l__datapie_mid_tl
    }
  }
}
}
{

```

Don't rotate outer labels if $(\theta > -45 \text{ and } \theta < 45)$ or $\theta = 45$ or $\theta > 315$

```

  \fp_compare:nNnTF
  { \l__datapie_mid_fp } > { 315 }
  {
    \cs_set_eq:NN \__datapie_next:nn \use_i:nn
  }
  {
    \fp_compare:nTF
    { -45 < \l__datapie_mid_fp <= 45 }
    {
      \cs_set_eq:NN \__datapie_next:nn \use_i:nn
    }
    {
      \cs_set_eq:NN \__datapie_next:nn \use_ii:nn
    }
  }
}
\__datapie_next:nn
{

```

East quadrant

```

  \tl_set:Nn \l__datapie_outer_node_opt_tl
  { anchor = west }
}
{
  \fp_compare:nTF
  { 45 < \l__datapie_mid_fp <= 135 }
  {

```

```

        \cs_set_eq:NN \__datapie_next:nn \use_i:nn
      }
    {
      \cs_set_eq:NN \__datapie_next:nn \use_ii:nn
    }
  \__datapie_next:nn
  {
    North quadrant
      \tl_set:Nn \l__datapie_outer_node_opt_tl
        { anchor = south }
      }
    {
      If ( $\theta > 135$  and  $\theta < 225$ ) or  $\theta = 225$  or  $\theta = -135$  or  $\theta < -135$ 
        \fp_compare:nTF
          { 135 <= \l__datapie_mid_fp <= 225 }
          {
            \cs_set_eq:NN \__datapie_next:nn \use_i:nn
          }
          {
            \fp_compare:nNnTF
              { \l__datapie_mid_fp } > { -135 }
              {
                \cs_set_eq:NN \__datapie_next:nn \use_ii:nn
              }
              {
                \cs_set_eq:NN \__datapie_next:nn \use_i:nn
              }
            }
          }
        \__datapie_next:nn
      {
        West quadrant
          \tl_set:Nn \l__datapie_outer_node_opt_tl
            { anchor = east }
          }
        {
          \tl_set:Nn \l__datapie_outer_node_opt_tl
            { anchor = north }
          }
        }
      }
    }
  Inner label drawing code:
    \tl_put_right:Nx \l__datapie_content_tl
    {
      \exp_not:N \draw
      (
        \l__datapie_mid_tl

```

```

        \c_colon_str
        \dim_use:N \l_datapie_inner_offset_dim
    ) ~
    node [ \l_datapie_inner_node_opt_tl ] ~
    {
        \exp_not:N \DTLdisplayinnerlabel
        { \exp_not:V \l_datapie_inner_label_tl }
    };
}
Outer label drawing code:
\tl_put_right:Nx \l_datapie_content_tl
{
    \exp_not:N \draw
    (
        \l_datapie_mid_tl \c_colon_str
        \dim_use:N \l_datapie_outer_offset_dim
    ) ~
    node [ \l_datapie_outer_node_opt_tl ] ~
    {
        \exp_not:N \DTLdisplayouterlabel
        { \exp_not:V \l_datapie_outer_label_tl }
    };
}
\tl_put_right:Nn \l_datapie_hook_tl
{
    { \l_datapie_inner_offset_dim }
    { \l_datapie_outer_offset_dim }
}
\tl_put_right:Nn \l_datapie_content_tl
{
    \l_datapie_hook_tl
    \end { scope }
}
\l_datapie_content_tl
}
\int_zero:N \l_datapie_segment_int
\int_zero:N \l_datapie_tool_row_idx_int
\DTLpieatendtikz
\end{tikzpicture}
}

```

```

\DTLpiechart[<conditions>]{<option list>}{<db name>}
<assign list>

```

\DTLpiechart

Make a pie chart from data given in data base *<db name>*, where *<assign list>* is a comma-separated list of *<cmd>*=*<key>* pairs. *<option list>* must include `variable=<cmd>`, where *<cmd>* is included in *<assign list>*. The optional argument *<conditions>* is the same as that for \DTLforeach.

Version 3.0 now uses `\DTLmapdata`. The condition can now be passed as an argument in *(option list)* but the optional argument is retained for backward compatibility. The condition in the option list will override the optional argument.

```
\NewDocumentCommand \DTLpiechart { o m m m }
{
  \group_begin:
  \IfValueT { #1 }
  {
    \cs_set:Nn \__datapie_filter:T
    {
      \ifthenelse { #1 } { ##1 } { }
    }
  }
  \tl_if_blank:nF { #3 }
  {
    \DTLsetup { default-name = { #3 } }
  }
  \keys_set:nn { datatool/pie } { #2 }
  \tl_if_empty:NTF \DTLpievariable
  {
    \PackageError { datapie }
    {
      \token_to_str:N \DTLpiechart \c_space_tl ~ missing ~ variable
    }
    {
      You ~ need ~ to ~ set ~ the ~ `variable' ~ key ~ in ~ the ~
      first ~ mandatory ~ argument ~ of ~
      \token_to_str:N \DTLpiechart \c_space_tl ~ to ~ the ~
      applicable ~ placeholder ~ command ~ listed ~ in ~ the ~
      final ~ argument
    }
  }
  }
  {
    \__datapie_do_chart:n { #4 }
  }
  \group_end:
}
```

Do the chart. The argument is the assignment list.

```
\cs_new:Nn \__datapie_do_chart:n
{
```

Enable commands that may only be used within `\DTLpiechart`:

```
\cs_set_eq:NN \DTLpiepercent \__datapie_percent:
```

Compute the total. This needs to take into account number formatting.

```
\__datapie_compute_total:n { #1 }
\__datapie_compute_angles:n { #1 }
```

Compute the offsets for each cut away segment

```

\clist_map_inline:Nn \l__datapie_cutaways_clist
{
  \__datapie_set_offset:nw ##1 - \q_stop
}
\__datapie_draw:n { #1 }
}

```

Scratch placeholder for action if key or column given instead of variable:

```

\tl_new:N \l__datapie_action_variable_tl
Action 'pie chart':
\cs_new:cn { __datatool_action_pie ~ chart : }
{
  \group_begin:
  \tl_if_empty:NF \l__datatool_action_name_tl
  {
    \tl_set_eq:NN
      \l__datatool_default_dbname_tl
      \l__datatool_action_name_tl
  }
  \cs_set_eq:NN \__datapie_do:n \use:n

```

If the 'key' or 'column' has been set, then that provides the variable, unless it's overridden by the variable setting in the options.

```

  \__datatool_optional_key_xor_column_get_key:nTF
  {

```

No key or column. The variable will need to be provided in the options list instead (or may have already been set with `\DTLsetup`).

```

  }
  {

```

Key or column provided.

```

  \tl_set:Nn \DTLpievariable
  { \l__datapie_action_variable_tl }
  \clist_put_right:Nx \l__datatool_action_assign_clist
  {
    \exp_not:N \l__datapie_action_variable_tl =
    \l__datatool_action_key_tl
  }
}
{

```

Invalid syntax.

```

  \cs_set_eq:NN \__datapie_do:n \cs_none:n
}
\__datapie_do:n
{

```

Parse options if set.

```

  \clist_if_empty:NF \l__datatool_action_options_clist
  {

```

```

\keys_set:nV { datatool/pie }
\l_datatool_action_options_clist
}

```

Check variable has been set.

```

\tl_if_empty:NT \DTLpievariable
{
\cs_set_eq:NN \__datapie_do:n \use_none:n
\__datatool_action_error:nnn { datapie }
{
\token_to_str:N \DTLpiechart \c_space_tl ~ missing ~ variable
}
{
You ~ need ~ to ~ either ~ use ~ `key' ~ or ~ `column' ~
to ~ identify ~ the ~ variable ~ column ~ or ~ set ~
the ~ `variable' ~ key ~ to ~ the ~ placeholder ~
command ~ within ~ `options'
}
}
\__datapie_do:n
{
\exp_args:NV \__datapie_do_chart:n
\l_datatool_action_assign_clist
}
}

```

\group_end:

}

Set the offset angles.

\@dtl@set@off Version 3.0: replaced \@dtl@set@off with:

```

\cs_new:Npn \__datapie_set_offset:nw
#1 - #2 \q_stop
{
\tl_if_empty:nTF { #2 }
{
\__datapie_set_offset:n { #1 }
}
{
\__datapie_set_offset_range:nw #1 - #2 \q_stop
}
}

```

Set offset for individual segment:

\@@dtl@set@off

```

\cs_new:Nn \__datapie_set_offset:n
{
\tl_set:cx { dtl@cut@angle@ \romannumeral #1 }
{
\fp_eval:n

```

```

    {
      0.5 * \tl_use:c { dtl@angle@ \romannumeral #1 }
      + \tl_use:c { dtl@sang@ \romannumeral #1 }
    }
  }
\l_set:cx
{ dtl@cut@len@ \romannumeral #1 }
{ \dim_use:N \l__datapie_cutaway_offset_dim }
}

```

\@@dtl@setoffr Set offset for a range of segments. Version 3.0: replaced \@@dtl@setoffr with:

```

\cs_new:Npn \__datapie_set_offset_range:nw
#1 - #2 - \q_stop
{
  \int_compare:nNnTF { #1 } > { #2 }
  {
    \PackageError {datapie}
    {
      Segment ~ ranges ~ must ~ go ~ in ~ ascending ~ order
    }
    {
      Try ~ #2 - #1 ~ instead of ~ #1 - #2
    }
  }
}
{
  \fp_zero:N \l__datapie_angle_fp
  \int_step_inline:nnn { #1 } { #2 }
  {
    \fp_add:Nn \l__datapie_angle_fp
    {
      \tl_use:c { dtl@angle@ \romannumeral ##1 }
    }
  }
  \tl_set:Nx \l__datapie_angle_tl
  {
    \fp_eval:n
    {
      0.5 * \l__datapie_angle_fp
      + \tl_use:c { dtl@sang@\romannumeral#1 }
    }
  }
  \int_step_inline:nnn { #1 } { #2 }
  {
    \tl_set_eq:cN { dtl@cut@angle@\romannumeral ##1 }
    \l__datapie_angle_tl
    \tl_set:cx
    { dtl@cut@len@\romannumeral ##1 }
    { \dim_use:N \l__datapie_cutaway_offset_dim }
  }
}
}

```

```
}
\ExplSyntaxOff
```

28 dataplot.sty

Declare package:

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```
\DeclareRelease{v2.32}{2019-09-27}{dataplot-2019-09-27.sty}
\DeclareCurrentRelease{v3.4}{2025-04-03}
```

Declare package:

```
\ProvidesPackage{dataplot}[2025/04/03 v3.4 (NLCT)]
```

Version 3.0: no longer using xkeyval.

```
\IfPackageLoadedTF{datatool}
{
  \DeclareOption*{\expandafter\DTLsetup\expandafter{\CurrentOption}}
}
{
  \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{datatool}}
}
\ProcessOptions
  Required packages
\RequirePackage{datatool}
\RequirePackage{tikz}
Load TikZ plot libraries
\usetikzlibrary{plotmarks}
\usetikzlibrary{plohandlers}
Load calc library
\usetikzlibrary{calc}
\ExplSyntaxOn
```

28.1 Scratch variables.

List of x keys:

```
\clist_new:N \l__dataplot_x_keys_clist
\seq_new:N \l__dataplot_x_keys_seq
\int_new:N \l__dataplot_x_key_int
```

List of y keys:

```
\seq_new:N \l__dataplot_y_keys_seq
\int_new:N \l__dataplot_y_key_int
```

Any extra assignments that need to be made in the loop. For example, to assist filtering.

```
\tl_new:N \l__dataplot_extra_assign_tl
```

`\dtl@xkey` The database key for the x value. Version 3.0 replaced `\dtl@xkey` with:
`\tl_new:N \l__dataplot_x_key_tl`

`\dtl@ykey` The database key for the y value. Version 3.0 replaced `\dtl@ykey` with:
`\tl_new:N \l__dataplot_y_key_tl`

Placeholders for x and y obtained from database:

`\dtl@x` Version 3.0 replaced `\dtl@x` with:
`\tl_new:N \l__dataplot_x_tl`

`\dtl@decx` Version 3.0 replaced `\dtl@decx` with:
`\tl_new:N \l__dataplot_decimal_x_tl`

`\dtl@y` Version 3.0 replaced `\dtl@y` with:
`\tl_new:N \l__dataplot_y_tl`

`\dtl@decy` Version 3.0 replaced `\dtl@decy` with:
`\tl_new:N \l__dataplot_decimal_y_tl`

Floating point values:

`\fp_new:N \l__dataplot_x_fp`
`\fp_new:N \l__dataplot_y_fp`

Plot bounds.

`\fp_new:N \l__dataplot_min_x_fp`
`\fp_new:N \l__dataplot_min_y_fp`
`\fp_new:N \l__dataplot_max_x_fp`
`\fp_new:N \l__dataplot_max_y_fp`

Support for extending the axes beyond the plot bounds:

`\fp_new:N \l__dataplot_extend_min_x_axis_fp`
`\fp_new:N \l__dataplot_extend_max_x_axis_fp`
`\fp_new:N \l__dataplot_extend_min_y_axis_fp`
`\fp_new:N \l__dataplot_extend_max_y_axis_fp`

Extended plot bounds.

`\fp_new:N \l__dataplot_extended_min_x_fp`
`\fp_new:N \l__dataplot_extended_min_y_fp`
`\fp_new:N \l__dataplot_extended_max_x_fp`
`\fp_new:N \l__dataplot_extended_max_y_fp`

Tick gaps:

`\fp_const:Nn \c_dataplot_smallest_gap_fp { 0.000001 }`

`\@dtl@neggap` Version 3.0 replaced `\@dtl@neggap` with:
`\fp_new:N \l__dataplot_neg_gap_fp`

`\@dtl@posgap` Version 3.0 replaced `\@dtl@posgap` with:
`\fp_new:N \l__dataplot_pos_gap_fp`

`\@dtl@gap` Version 3.0 replaced `\@dtl@gap` with:
`\fp_new:N \l__dataplot_gap_fp`
`\fp_new:N \l__dataplot_min_minor_gap_fp`
Scale factors and offsets.

`\dtl@scale@x` Version 3.0 replaced `\dtl@scale@x` with:
`\fp_new:N \l__dataplot_scale_x_fp`
`\fp_set_eq:NN \l__dataplot_scale_x_fp \c_one_fp`

`\dtl@scale@y` Version 3.0 replaced `\dtl@scale@y` with:
`\fp_new:N \l__dataplot_scale_y_fp`
`\fp_set_eq:NN \l__dataplot_scale_y_fp \c_one_fp`

Inverse scale factors:
`\fp_new:N \l__dataplot_inv_scale_x_fp`
`\fp_set_eq:NN \l__dataplot_inv_scale_x_fp \c_one_fp`
`\fp_new:N \l__dataplot_inv_scale_y_fp`
`\fp_set_eq:NN \l__dataplot_inv_scale_y_fp \c_one_fp`

`\dtl@offset@x` Version 3.0 replaced `\dtl@offset@x` with:
`\fp_new:N \l__dataplot_offset_x_fp`

`\dtl@offset@y` Version 3.0 replaced `\dtl@offset@y` with:
`\fp_new:N \l__dataplot_offset_y_fp`

`\dtl@dx` Version 3.0 replaced `\dtl@dx` with:
`\fp_new:N \l__dataplot_x_extent_fp`

`\dtl@dy` Version 3.0 replaced `\dtl@dy` with:
`\fp_new:N \l__dataplot_y_extent_fp`

`\dtl@ticklength` Tick length in terms of canvas co-ordinates. Version 3.0 replaced `\dtl@ticklength` with:
`\fp_new:N \l__dataplot_tick_length_fp`

`\@dtl@width` Version 3.0 replaced `\@dtl@width` with:
`\fp_new:N \l__dataplot_width_fp`
`\fp_new:N \l__dataplot_height_fp`

`\dtl@xticlabelheight` The height of the x tick labels. Version 3.0: replaced `\dtl@xticlabelheight` with:
`\dim_new:N \l__dataplot_x_tic_label_height_dim`

`\dtl@yticlabelwidth` Dimension used to store the width of the y tick labels. Version 3.0 replaced `\dtl@yticlabelwidth` with:
`\dim_new:N \l__dataplot_y_tic_label_width_dim`

`\dtl@ticlabeloffset` The offset of the label. Version 3.0: replaced `\dtl@ticlabeloffset` with:
`\fp_new:N \l__dataplot_tic_label_offset_fp`

Tick label:

`\tl_new:N \l__dataplot_tic_label_tl`

List of database names:

`\seq_new:N \l__dataplot_dbnames_seq`

List of plot marks (obtained from `\DTLplotmarks`):

`\seq_new:N \l__dataplot_mark_seq`

`\dtl@mark` Current mark. Version 3.0: replaced `\dtl@mark` with:

`\tl_new:N \l__dataplot_current_mark_tl`

Boolean to determine whether to cycle marks for each database or for each (x, y) pair.

`\bool_new:N \l__dataplot_mark_group_bool`

`\bool_set_false:N \l__dataplot_mark_group_bool`

List of plot mark colours (obtained from `\DTLplotmarkcolors`):

`\seq_new:N \l__dataplot_mark_colors_seq`

`\dtl@thisplotmarkcolor` Current mark colour. Version 3.0: replaced `\dtl@thisplotmarkcolor` with:

`\tl_new:N \l__dataplot_current_mark_color_tl`

Boolean to determine whether to cycle mark colour for each database or for each (x, y) pair.

`\bool_new:N \l__dataplot_mark_color_group_bool`

`\bool_set_false:N \l__dataplot_mark_color_group_bool`

Current mark style and colour combination:

`\tl_new:N \l__dataplot_current_mark_style_tl`

List of line styles (obtained from `\DTLplotlines`):

`\seq_new:N \l__dataplot_line_seq`

`\dtl@linestyle` Current line. Version 3.0: replaced `\dtl@linestyle` with:

`\tl_new:N \l__dataplot_current_line_tl`

Boolean to determine whether to cycle line style for each database or for each (x, y) pair.

`\bool_new:N \l__dataplot_line_group_bool`

`\bool_set_false:N \l__dataplot_line_group_bool`

List of line colours (obtained from `\DTLplotlinecolors`):

`\seq_new:N \l__dataplot_line_colors_seq`

`\dtl@thisplotlinecolor` Current line colour. Version 3.0: replace `\dtl@thisplotlinecolor` with:

`\tl_new:N \l__dataplot_current_line_color_tl`

Boolean to determine whether to cycle line colour for each database or for each (x, y) pair.

```
\bool_new:N \l__dataplot_line_color_group_bool  
\bool_set_false:N \l__dataplot_line_color_group_bool
```

Current line style and colour combination:

```
\tl_new:N \l__dataplot_current_line_style_tl
```

Boolean to determine whether to reset or cycle if group setting not on.

```
\bool_new:N \l__dataplot_no_group_mark_reset_bool  
\bool_set_false:N \l__dataplot_no_group_mark_reset_bool  
\bool_new:N \l__dataplot_no_group_mark_color_reset_bool  
\bool_set_false:N \l__dataplot_no_group_mark_color_reset_bool  
\bool_new:N \l__dataplot_no_group_line_reset_bool  
\bool_set_false:N \l__dataplot_no_group_line_reset_bool  
\bool_new:N \l__dataplot_no_group_line_color_reset_bool  
\bool_set_false:N \l__dataplot_no_group_line_color_reset_bool
```

`\dtl@xminorticlist` List of minor x ticks. Version 3.0: replaced `\dtl@xminorticlist` with:

```
\seq_new:N \l__dataplot_x_minor_tic_seq
```

`\dtl@yminorticlist` List of minor y ticks. Version 3.0: replaced `\dtl@yminorticlist` with:

```
\seq_new:N \l__dataplot_y_minor_tic_seq
```

`\dtl@stream` Plot stream token list. Version 3.0: replaced `\dtl@stream` with:

```
\tl_new:N \l__dataplot_stream_tl
```

`\dtl@legend` Plot legend token list. This is a public temporary variable as it needs to be referenced in `\DTLaddtoplotlegend`, which may be redefined by the user. Version 3.0: replaced `\dtl@legend` with:

```
\tl_new:N \l__dataplot_legend_tl
```

`\dtl@bounds` The bounds of the graph may be given as a four-element list $\langle \min x \rangle, \langle \min y \rangle, \langle \max x \rangle, \langle \max y \rangle$. Version 3.0 replaced `\dtl@bounds` comma-separated list with the sequence variable:

```
\seq_new:N \l__dataplot_bounds_seq
```

Token list to contain the plot code:

```
\tl_new:N \l__dataplot_content_tl
```

28.2 Settings

`\DTLplotmarks` `\DTLplotmarks` contains a list of plot marks used by `\DTLplot`. This will be converted to the sequence `\l__dataplot_marks_seq` in `\DTLplot`.

```
\newcommand*{\DTLplotmarks}{%  
  \pgfuseplotmark{o},%  
  \pgfuseplotmark{x},%  
  \pgfuseplotmark{+},%
```

```

\pgfuseplotmark{square},%
\pgfuseplotmark{triangle},%
\pgfuseplotmark{diamond},%
\pgfuseplotmark{pentagon},%
\pgfuseplotmark{asterisk},%
\pgfuseplotmark{star}%
}

```

`\DTLplotmarkcolors` `\DTLplotmarkcolors` contains a list of the plot mark colours. This will be converted to the sequence `\l__dataplot_mark_colors_seq` in `\DTLplot`.

```

\newcommand*\DTLplotmarkcolors{%
red,%
green,%
blue,%
yellow,%
magenta,%
cyan,%
orange,%
black,%
gray}

```

`\DTLplotlines` `\DTLplotlines` contains a list of dash patterns used by `\DTLplot`. This will be converted to the sequence `\l__dataplot_line_seq` in `\DTLplot`.

```

\newcommand*\DTLplotlines{%
\pgfsetdash{}{0pt},% solid line
\pgfsetdash{{10pt}{5pt}}{0pt},%
\pgfsetdash{{5pt}{5pt}}{0pt},%
\pgfsetdash{{1pt}{5pt}}{0pt},%
\pgfsetdash{{5pt}{5pt}{1pt}{5pt}}{0pt},%
\pgfsetdash{{1pt}{3pt}}{0pt}%
}

```

`\DTLplotlinecolors` `\DTLplotlinecolors` contains a list of the plot line colours. This will be converted to the sequence `\l__dataplot_line_colors_seq` in `\DTLplot`.

```

\newcommand*\DTLplotlinecolors{%
red,%
green,%
blue,%
yellow,%
magenta,%
cyan,%
orange,%
black,%
gray}

```

`\DTLplotwidth` The default total plot width is stored in the length `\dtlplotwidth`

```

\newlength\DTLplotwidth
\setlength\DTLplotwidth{4in}

```

`\DTLplotheight` The default total plot height is stored in the length `\dtlplotheight`
`\newlength\DTLplotheight`
`\setlength\DTLplotheight{4in}`

`\DTLticklength` The length of the tick marks is given by `\DTLticklength`
`\newlength\DTLticklength`
`\setlength\DTLticklength{5pt}`

`\DTLminorticklength` The length of the minor tick marks is given by `\DTLminorticklength`.
`\newlength\DTLminorticklength`
`\setlength\DTLminorticklength{2pt}`

`\DTLticklabeloffset` The offset from the axis to the tick label is given by `\DTLticklabeloffset`.
`\newlength\DTLticklabeloffset`
`\setlength\DTLticklabeloffset{8pt}`

`\DTLmintickgap` `\DTLmintickgap` stores the suggested minimum distance between tick marks where the gap is not specified.
`\newlength\DTLmintickgap`
`\setlength\DTLmintickgap{20pt}`

`\DTLminminortickgap` The suggested minimum distance between minor tick marks where the gap is not specified is given by `\DTLminminortickgap`.
`\newlength\DTLminminortickgap`
`\setlength\DTLminminortickgap{5pt}`

`DTLplotroundXvar` Round x tick labels to the number of digits given by the counter `DTLplotroundXvar`.
`\newcounter{DTLplotroundXvar}`
`\setcounter{DTLplotroundXvar}{2}`

`DTLplotroundYvar` Round y tick labels to the number of digits given by the counter `DTLplotroundYvar`.
`\newcounter{DTLplotroundYvar}`
`\setcounter{DTLplotroundYvar}{2}`

`\ifDTLxaxis` The conditional `\ifDTLxaxis` is used to determine whether or not to display the x axis.
`\newif\ifDTLxaxis`
`\DTLxaxistrue`

`\DTLXaxisStyle` The style of the x axis is given by `\DTLXaxisStyle`. This is just a solid line by default.
`\newcommand*\DTLXaxisStyle{-}`

`\ifDTLyaxis` The conditional `\ifDTLyaxis` is used to determine whether or not to display the y axis
`\newif\ifDTLyaxis`
`\DTLyaxistrue`

`\DTLYAxisStyle` The style of the y axis is given by `\DTLYAxisStyle`. This is just a solid line by default.

```
\newcommand*\DTLYAxisStyle{-}
```

`\DTLmajorgridstyle` The style of the major grid lines is given by `\DTLmajorgridstyle`.

```
\newcommand*\DTLmajorgridstyle{color=gray, -}
```

`\DTLminorgridstyle` The style of the minor grid lines is given by `\DTLminorgridstyle`.

```
\newcommand*\DTLminorgridstyle{color=lightgray, very ~ thin}
```

`\ifDTLxticsin` The conditional `\ifDTLxticsin` is used to determine whether the x tics should point in or out.

```
\newif\ifDTLxticsin
\DTLxticsintrue
```

`\ifDTLyticsin` The conditional `\ifDTLyticsin` is used to determine whether the y tics should point in or out.

```
\newif\ifDTLyticsin
\DTLyticsintrue
```

`\DTLlegendxoffset` The gap between the border of plot and legend is given by the lengths `\DTLlegendxoffset` and `\DTLlegendyoffset`

```
\newlength\DTLlegendxoffset
\setlength\DTLlegendxoffset{10pt}
```

`\DTLlegendyoffset`

```
\newlength\DTLlegendyoffset
\setlength\DTLlegendyoffset{10pt}
```

`\DTLformatlegend`

```
\DTLformatlegend{\legend}
```

This formats the legend.

```
\newcommand*\DTLformatlegend[1]{%
\setlength{\fboxrule}{1.1pt}%
\fcolorbox{black}{white}{#1}}
```

`\DTLcustomlegend`

```
\DTLcustomlegend{\legend}
```

Used with the custom legend setting. This should be redefined to place the legend at the desired position.

```
\newcommand{\DTLcustomlegend}[1]{
\node { \DTLformatlegend { #1 } } ;
}
```

Adds the begin tabular code for the legend:

```
\cs_new:Nn \dataplot_legend_add_begin:
{
  \tl_put_left:Nn \l_dataplot_legend_tl
  { \begin { tabular } { c l } }
}
```

Adds the end tabular code for the legend:

```
\cs_new:Nn \dataplot_legend_add_end:
{
  \tl_put_right:Nn \l_dataplot_legend_tl
  { \end { tabular } }
}
```

`\ifDTLshowmarkers` The conditional `\ifDTLshowmarkers` is used to specify whether or not to use markers.

```
\newif\ifDTLshowmarkers
\DTLshowmarkerstrue
```

`\ifDTLshowlines` The conditional `\ifDTLshowlines` is used to specify whether or not to use lines.

```
\newif\ifDTLshowlines
\DTLshowlinesfalse
```

`\ifDTLbox` Enclose plot in a box

```
\newif\ifDTLbox
\DTLboxfalse
```

`\ifDTLxticstrue` Condition to determine whether to show the x tick marks

```
\newif\ifDTLxtics
\DTLxticstrue
```

`\ifDTLyticstrue` Condition to determine whether to show the y tick marks

```
\newif\ifDTLytics
\DTLyticstrue
```

`\ifDTLxminortics` Condition to determine whether to show the x minor tick marks

```
\newif\ifDTLxminortics
\DTLxminorticsfalse
```

`\ifDTLyminortics` Condition to determine whether to show the y minor tick marks

```
\newif\ifDTLyminortics
\DTLyminorticsfalse
```

`\ifDTLgrid` Determine whether to draw the grid

```
\newif\ifDTLgrid
```

`\DTLplotdisplayticklabel`

`\DTLplotdisplayticklabel{<text>}`

Formatting used for default x tick labels.

`\newcommand{\DTLplotdisplayticklabel}[1]{#1}`

`\DTLplotdisplayXticklabel`

`\DTLplotdisplayXticklabel{<text>}`

Formatting used for default x tick labels.

`\newcommand{\DTLplotdisplayXticklabel}[1]{\DTLplotdisplayticklabel{#1}}`

x tick label node style:

`\tl_new:N \l__dataplot_x_tick_label_style_tl`

`\DTLplotdisplayYticklabel`

`\DTLplotdisplayYticklabel{<text>}`

Formatting used for default y tick labels.

`\newcommand{\DTLplotdisplayYticklabel}[1]{\DTLplotdisplayticklabel{#1}}`

y tick label node style:

`\tl_new:N \l__dataplot_y_tick_label_style_tl`

`\tl_set:Nn \l__dataplot_y_tick_label_style_tl { anchor=east }`

`\dtl@minx` The lower x bound. Version 3.0: replaced `\dtl@minx` with:

`\tl_new:N \l__dataplot_min_x_tl`

`\dtl@maxx` The upper x bound: Version 3.0: replaced `\dtl@maxx` with:

`\tl_new:N \l__dataplot_max_x_tl`

`\dtl@miny` The lower y bound: Version 3.0: replaced `\dtl@miny` with:

`\tl_new:N \l__dataplot_min_y_tl`

`\dtl@maxy` The upper y bound: Version 3.0: replaced `\dtl@maxy` with:

`\tl_new:N \l__dataplot_max_y_tl`

`\dtl@xticlist` The list of floating point values for x ticks. Version 3.0: replaced `\dtl@xticlist` with:

`\clist_new:N \l__dataplot_x_tic_clist`

`\seq_new:N \l__dataplot_x_tic_seq`

`\dtl@yticlist` The list of decimal values for y ticks. Version 3.0: replaced `\dtl@yticlist` with:

`\clist_new:N \l__dataplot_y_tic_clist`

`\seq_new:N \l__dataplot_y_tic_seq`

`\dtl@xticgap` The gap between x tick marks (`xticpoints` overrides `xticgap`) Version 3.0: replaced `\dtl@xticgap` with:

```
\tl_new:N \l__dataplot_xtic_gap_tl
```

`\dtl@yticgap` The gap between y tick marks (`ycticpoints` overrides `yticgap`) Version 3.0: replaced `\dtl@yticgap` with:

```
\tl_new:N \l__dataplot_ytic_gap_tl
```

`\dtl@xticlabels` A comma separated list of labels for x ticks. Version 3.0 replaced `\dtl@xticlabels` with a sequence variable:

```
\seq_new:N \l__dataplot_xtic_labels_seq
```

`\dtl@yticlabels` A comma separated list of labels for y ticks. Version 3.0 replaced `\dtl@yticlabels` with a sequence variable:

```
\seq_new:N \l__dataplot_ytic_labels_seq
```

`\dtl@xlabel` x axis label Version 3.0 replaced `\dtl@xlabel` with:

```
\tl_new:N \l__dataplot_xlabel_tl
```

`\dtl@ylabel` y axis label Version 3.0 replaced `\dtl@ylabel` with:

```
\tl_new:N \l__dataplot_ylabel_tl
```

Labels at either end of axes and their style:

```
\tl_new:N \l__dataplot_x_min_label_tl
```

```
\tl_new:N \l__dataplot_x_min_label_style_tl
```

```
\tl_set:Nn \l__dataplot_x_min_label_style_tl { left }
```

```
\tl_new:N \l__dataplot_x_max_label_tl
```

```
\tl_new:N \l__dataplot_x_max_label_style_tl
```

```
\tl_set:Nn \l__dataplot_x_max_label_style_tl { right }
```

```
\tl_new:N \l__dataplot_y_min_label_tl
```

```
\tl_new:N \l__dataplot_y_min_label_style_tl
```

```
\tl_set:Nn \l__dataplot_y_min_label_style_tl { below }
```

```
\tl_new:N \l__dataplot_y_max_label_tl
```

```
\tl_new:N \l__dataplot_y_max_label_style_tl
```

```
\tl_set:Nn \l__dataplot_y_max_label_style_tl { above }
```

`\dtl@legendlabels` Legend labels (comma separated list). If empty, the database name is used. Version 3.0 replaced `\dtl@legendlabels` with the sequence:

```
\seq_new:N \l__dataplot_legend_labels_seq
```

`\dtl@legendsetting` Integer variable corresponding to the legend setting: none (0, don't show it), north (1), northeast (2), east (3), southeast (4), south (5), southwest (6), west (7), northwest (8) or custom (9). The custom setting will use `\DTLcustomlegend` to position the legend which should be redefined as applicable. Version 3.0 replaced `\dtl@legendsetting` with:

```
\int_new:N \l__dataplot_legend_setting_int
```

Provide a filter function:

```
\cs_new:Nn \__dataplot_filter:T { #1 }
```

Convert a list of numbers to a sequence containing floating point markup (so that the numbers don't have to keep being reparsed). Only include numbers in the given range (inclusive) Syntax: $\langle seq \rangle \{ \langle clist \rangle \} \{ \langle min \rangle \} \{ \langle max \rangle \}$

```
\cs_new:Nn \__dataplot_to_fp_seq:NNnn
{
  \seq_clear:N #1
  \clist_map_inline:Nn { #2 }
  {
    \datatool_set_fp:Nn \l__datatool_tmpa_fp { ##1 }
    \fp_compare:nT
      { #3 <= \l__datatool_tmpa_fp <= #4 }
      {
        \seq_put_right:NV #1 \l__datatool_tmpa_fp
      }
  }
}
```

```
\cs_new:Nn \__dataplot_filtered_map:nnn
{
  \int_zero:N \l__dataplot_x_key_int
  \int_zero:N \l__dataplot_y_key_int
  \seq_set_from_clist:NN \l__dataplot_x_keys_seq
  \l__dataplot_x_keys_clist
}
```

Iterate over the (x, y) coordinate pairs:

```
\seq_map_inline:Nn \l__dataplot_y_keys_seq
{
  \int_incr:N \l__dataplot_y_key_int
}
```

The y key is the sequence iteration value:

```
\tl_set:Nn \l__dataplot_y_key_tl { ##1 }
```

Get the x key:

```
\seq_if_empty:NT \l__dataplot_x_keys_seq
{
  \int_zero:N \l__dataplot_x_key_int
  \seq_set_from_clist:NN \l__dataplot_x_keys_seq
  \l__dataplot_x_keys_clist
}
\seq_pop_left:NN \l__dataplot_x_keys_seq
\l__dataplot_x_key_tl
\int_incr:N \l__dataplot_x_key_int
```

Both the x and y key must exist for the current database for this plot stream. If either doesn't exist, skip this iteration. Check the y key exists for the current database:

```
\datatool_if_has_key:nnTF
{ \l__datatool_default_dbname_tl }
{ \l__dataplot_y_key_tl }
{ }
```

Check the x key exists for the current database:

```
\datatool_if_has_key:nnTF
  { \l__datatool_default_dbname_tl }
  { \l__dataplot_x_key_tl }
}
```

Pre map code:

```
#1
```

Iterate over all rows in this database:

```
\DTLmapdata
{
  \tl_if_empty:NF \l__dataplot_extra_assign_tl
  {
    \exp_args:NV \DTLmapgetvalues
    \l__dataplot_extra_assign_tl
  }
}
```

Get the x coordinate:

```
\DTLmapget
{
  return = \l__dataplot_x_tl ,
  key = \l__dataplot_x_key_tl
}
```

Get the y coordinate:

```
\DTLmapget
{
  return = \l__dataplot_y_tl ,
  key = \l__dataplot_y_key_tl
}
\__dataplot_filter:T { #2 }
```

Post map code:

```
#3
}
{
```

The y key isn't defined for the current database.

```
\dataplot_skipping_key_msg:nnnn
{ \seq_count:N \l__dataplot_dbnames_seq }
{ x } { \l__dataplot_x_key_tl }
{ \l__datatool_default_dbname_tl }
}
}
```

The y key isn't defined for the current database.

```
\dataplot_skipping_key_msg:nnnn
{ \seq_count:N \l__dataplot_dbnames_seq }
{ y } { \l__dataplot_y_key_tl }
```

```

        { \l__datatool_default_dbname_tl }
    }
}
\cs_new:Nn \__dataplot_filtered_map:n
{
    \__dataplot_filtered_map:nnn { } { #1 } { }
}
Syntax: {<num databases>}{<x/y>}{<key>}{<db-name>} Warn or verbose message if
skipping key:
\cs_new:Nn \dataplot_skipping_key_msg:nnnn
{
    \int_compare:nNnTF { #1 } = { \c_one_int }
    {
        \PackageWarning { dataplot }
        {
            \token_to_str:N \DTLplot : ~ skipping ~ #2 ~ key ~
            ` #3 ' ~ for ~ database ~ ` \l__datatool_default_dbname_tl ' ~
            (column ~ not ~ defined)
        }
    }
    {
        \dtl@message
        {
            \token_to_str:N \DTLplot : ~ skipping ~ #2 ~ key ~
            ` #3 ' ~ for ~ database ~ ` \l__datatool_default_dbname_tl ' ~
            (column ~ not ~ defined)
        }
    }
}
}

```

If the side axes boolean is on, the axes will always be draw on the left and bottom. If the setting is off and there are negative values, the axes will pass through 0 otherwise they will be drawn on the side.

```

\bool_new:N \l__dataplot_side_axes_bool
\bool_set_false:N \l__dataplot_side_axes_bool

```

Booleans set after computing the bounds. True if x axis includes 0. That is, the y axis should intersect at x=0:

```

\bool_new:N \l__dataplot_zero_x_axis_bool

```

True if y axis includes 0. That is, the x axis should intersect at y=0:

```

\bool_new:N \l__dataplot_zero_y_axis_bool

```

Omit tick label at $x = 0$ or $y = 0$ if true:

```

\bool_new:N \l__dataplot_omit_zero_x_label_bool
\bool_new:N \l__dataplot_omit_zero_y_label_bool

```

Setting to determine whether or not to omit zero labels: 1 (auto), 2 (omit both), 3 (omit x), 4 (omit y), 5 (don't omit)

```

\int_new:N \l__dataplot_omit_zero_label_action_int

```

Determines whether to show ticks on the box if `box=true`. Values: 1=match axes, 2=in, 3=out, 0=none. Any other value is treated as 0.

```
\int_new:N \l__dataplot_box_ticks_int
\int_set_eq:NN \l__dataplot_box_ticks_int \c_one_int
\keys_define:nn { dataplot/plot }
{
```

Plot settings. The database key for the x value is given by the `x` setting:

```
x .clist_set:N = \l__dataplot_x_keys_clist ,
```

The database key for the y value is given by the `y` setting:

```
y .code:n =
{
  \seq_set_from_clist:Nn \l__dataplot_y_keys_seq { #1 }
},
```

Any extra assignments that need to be made in `\DTLmapdata`:

```
extra-assign .tl_set:N = \l__dataplot_extra_assign_tl ,
```

The list of plot mark colours is given by the `markcolors` setting. (This should be a comma separated list of colour names.)

```
markcolors .clist_set:N = \DTLplotmarkcolors,
mark-colors .clist_set:N = \DTLplotmarkcolors,
```

The list of plot line colours is given by the `linecolors` setting. (This should be a comma separated list of colour names.)

```
linecolors .clist_set:N = \DTLplotlinecolors,
line-colors .clist_set:N = \DTLplotlinecolors,
```

The list of plot mark and line colours is given by the `colors` setting. (This should be a comma separated list of colour names.)

```
colors .code:n =
{
  \clist_set:Nn \DTLplotmarkcolors { #1 }
  \clist_set:Nn \DTLplotlinecolors { #1 }
},
```

The list of plot marks is given by the `marks` setting. (This should be a comma separated list of code that generates pgf plot marks.)

```
marks .clist_set:N = \DTLplotmarks ,
```

The list of plot line styles is given by the `lines` setting. (This should be a comma separated list of code that sets the line style.) An empty set will create solid lines.

```
lines .clist_set:N = \DTLplotlines ,
```

Determine whether or not styles not enabled with group-styles should continue cycling or reset at the start of each database.

```
style-resets .multichoice: ,
style-resets .default:n = { all },
style-resets / mark-style .code:n =
{
  \bool_set_true:N \l__dataplot_no_group_mark_reset_bool
```

```

    } ,
style-resets / mark-color .code:n =
{
  \bool_set_true:N \l__dataplot_no_group_mark_color_reset_bool
} ,
style-resets / line-style .code:n =
{
  \bool_set_true:N \l__dataplot_no_group_line_reset_bool
} ,
style-resets / line-color .code:n =
{
  \bool_set_true:N \l__dataplot_no_group_line_color_reset_bool
} ,
style-resets / all .code:n =
{
  \bool_set_true:N \l__dataplot_no_group_mark_reset_bool
  \bool_set_true:N \l__dataplot_no_group_mark_color_reset_bool
  \bool_set_true:N \l__dataplot_no_group_line_reset_bool
  \bool_set_true:N \l__dataplot_no_group_line_color_reset_bool
} ,
style-resets / none .code:n =
{
  \bool_set_false:N \l__dataplot_no_group_mark_reset_bool
  \bool_set_false:N \l__dataplot_no_group_mark_color_reset_bool
  \bool_set_false:N \l__dataplot_no_group_line_reset_bool
  \bool_set_false:N \l__dataplot_no_group_line_color_reset_bool
} ,

```

Determine whether to cycle mark and line styles for each database or for each (x, y) pair.

```

group-styles .multichoice: ,
group-styles .default:n = { all } ,
group-styles / mark-style .code:n =
{
  \bool_set_true:N \l__dataplot_mark_group_bool
} ,
group-styles / mark-color .code:n =
{
  \bool_set_true:N \l__dataplot_mark_color_group_bool
} ,
group-styles / line-style .code:n =
{
  \bool_set_true:N \l__dataplot_line_group_bool
} ,
group-styles / line-color .code:n =
{
  \bool_set_true:N \l__dataplot_line_color_group_bool
} ,
group-styles / all .code:n =
{

```

```

        \bool_set_true:N \l__dataplot_mark_group_bool
        \bool_set_true:N \l__dataplot_mark_color_group_bool
        \bool_set_true:N \l__dataplot_line_group_bool
        \bool_set_true:N \l__dataplot_line_color_group_bool
    } ,
group-styles / none .code:n =
{
    \bool_set_false:N \l__dataplot_mark_group_bool
    \bool_set_false:N \l__dataplot_mark_color_group_bool
    \bool_set_false:N \l__dataplot_line_group_bool
    \bool_set_false:N \l__dataplot_line_color_group_bool
} ,

```

The total width of the plot is given by the `width` setting.

```
width .dim_set:N = \DTLplotwidth ,
```

The total height of the plot is given by the `height` setting.

```
height .dim_set:N = \DTLplotheight ,
```

Tick label offset.

```
tick-label-offset .dim_set:N = \DTLticklabeloffset ,
```

Determine whether to show lines, markers or both

```

style .choice:,
style / both .code:n =
{
    \DTLshowlinestrue
    \DTLshowmarkerstrue
},
style / lines .code:n =
{
    \DTLshowlinestrue
    \DTLshowmarkersfalse
},
style / markers .code:n =
{
    \DTLshowmarkerstrue
    \DTLshowlinesfalse
},

```

Determine whether or not to display the axes

```

axes .choice:,
axes / both .code:n =
{
    \DTLxaxistrue
    \DTLxticstrue
    \DTLyaxistrue
    \DTLyticstrue
},
axes / x .code:n =
{
    \DTLxaxistrue

```

```

\DTLxticstrue
\DTLyaxisfalse
\DTLyticsfalse
},
axes / y .code:n =
{
\DTLxaxisfalse
\DTLxticsfalse
\DTLyaxistrue
\DTLyticstrue
},
axes / none .code:n =
{
\DTLxaxisfalse
\DTLxticsfalse
\DTLyaxisfalse
\DTLyticsfalse
},

```

Axis drawing style:

```

x-axis-style .tl_set:N = \DTLXAxisStyle ,
y-axis-style .tl_set:N = \DTLYAxisStyle ,
axis-style .code:n =
{
\tl_set:Nn \DTLXAxisStyle { #1 }
\tl_set:Nn \DTLYAxisStyle { #1 }
},

```

Major and minor grid drawing style:

```

major-grid-style .tl_set:N = \DTLmajorgridstyle ,
minor-grid-style .tl_set:N = \DTLminorgridstyle ,

```

Indicate whether or not the plot should be enclosed in a box:

```

box .legacy_if_set:n = DTLbox ,

```

Indicate if the box should also have tick marks:

```

box-ticks .choices:nn=
{ none, match-axes, in , out }
{
\int_set:Nn \l_dataplot_box_ticks_int
{ \l_keys_choice_int - \c_one_int }
} ,
box-ticks .default:n = { match-axes },
box-ticks .initial:n = { match-axes },

```

Rounding for default tick labels:

```

round-x .int_set:N = \c@DTLplotroundXvar ,
round-y .int_set:N = \c@DTLplotroundYvar ,
round .code:n =
{
\int_set:Nn \c@DTLplotroundXvar { #1 }
\int_set:Nn \c@DTLplotroundYvar { #1 }
}

```

```
},
```

Indicates whether to show the x tick marks:

```
xtics .legacy_if_set:n = DTLxtics ,  
x-ticks .legacy_if_set:n = DTLxtics ,
```

Indicates whether to show the y tick marks:

```
ytics .legacy_if_set:n = DTLytics ,  
y-ticks .legacy_if_set:n = DTLytics ,
```

Indicates whether to show the x and y tick marks:

```
tics .code:n =  
{  
  \setbool{DTLxtics}{#1}  
  \setbool{DTLytics}{#1}  
},  
ticks .code:n =  
{  
  \setbool{DTLxtics}{#1}  
  \setbool{DTLytics}{#1}  
},
```

Indicates whether to show the x minor tick marks:

```
xminortics .choice: ,  
xminortics / true .code:n =  
{  
  \DTLxminorticstrue  
  \DTLxticstrue  
},  
xminortics / false .code:n =  
{  
  \DTLxminorticsfalse  
},  
xminortics .default:n = true,
```

Synonym:

```
x-minor-ticks .choice: ,  
x-minor-ticks / true .code:n =  
{  
  \DTLxminorticstrue  
  \DTLxticstrue  
},  
x-minor-ticks / false .code:n =  
{  
  \DTLxminorticsfalse  
},  
x-minor-ticks .default:n = true,
```

Indicates whether to show the y minor tick marks:

```
yminortics .choice:,  
yminortics / true .code:n =  
{
```

```

        \DTLyminorticstrue
        \DTLyticstrue
    } ,
yminortics / false .code:n =
    {
        \DTLyminorticsfalse
    } ,
yminortics .default:n = true,

```

Synonym:

```

y-minor-ticks .choice:,
y-minor-ticks / true .code:n =
    {
        \DTLyminorticstrue
        \DTLyticstrue
    } ,
y-minor-ticks / false .code:n =
    {
        \DTLyminorticsfalse
    } ,
y-minor-ticks .default:n = true,

```

Indicates whether to show the x and y minor tick marks:

```

minor-ticks .choice: ,
minor-ticks / true .code:n =
    {
        \DTLxminorticstrue
        \DTLxticstrue
        \DTLyminorticstrue
        \DTLyticstrue
    } ,
minor-ticks / false .code:n =
    {
        \DTLxminorticsfalse
        \DTLyminorticsfalse
    } ,
minor-ticks .default:n = true,

```

Synonym:

```

minortics .choice: ,
minortics / true .code:n =
    {
        \DTLxminorticstrue
        \DTLxticstrue
        \DTLyminorticstrue
        \DTLyticstrue
    } ,
minortics / false .code:n =
    {
        \DTLxminorticsfalse
        \DTLyminorticsfalse
    }

```

```

    } ,
    minortics .default:n = true,
Determine whether to draw the grid:
    grid .legacy_if_set:n = DTLgrid ,
Determine whether the x tick marks should point in or out:
    xtictdir .choice: ,
    xtictdir / in .code:n =
    {
        \DTLxticsintrue
    },
    xtictdir / out .code:n =
    {
        \DTLxticsinfalse
    },
Synonym:
    x-tick-dir .choice: ,
    x-tick-dir / in .code:n =
    {
        \DTLxticsintrue
    },
    x-tick-dir / out .code:n =
    {
        \DTLxticsinfalse
    },
Determine whether the y tick marks should point in or out:
    yticdir .choice: ,
    yticdir / in .code:n =
    {
        \DTLyticintrue
    },
    yticdir / out .code:n =
    {
        \DTLyticinfalse
    },
Synonym:
    y-tick-dir .choice: ,
    y-tick-dir / in .code:n =
    {
        \DTLyticintrue
    },
    y-tick-dir / out .code:n =
    {
        \DTLyticinfalse
    },
Determine whether the x and y tick marks should point in or out:
    ticdir .choice: ,

```

```

ticdir / in .code:n =
  {
    \DTLxticsintrue
    \DTLyticsintrue
  },
ticdir / out .code:n =
  {
    \DTLxticsinfalse
    \DTLyticsinfalse
  },

```

Synonym:

```

tick-dir .choice: ,
tick-dir / in .code:n =
  {
    \DTLxticsintrue
    \DTLyticsintrue
  },
tick-dir / out .code:n =
  {
    \DTLxticsinfalse
    \DTLyticsinfalse
  },

```

Set the bounds of the graph (value must be in the form $\langle \min x \rangle, \langle \min y \rangle, \langle \max x \rangle, \langle \max y \rangle$). Version 3.0: bounds no longer overrides minx, miny, maxx and maxy settings. Set to empty to cancel.

```

bounds .code:n =
  {
    \seq_set_from_clist:Nn \l__dataplot_bounds_seq { #1 }
    \seq_if_empty:NF \l__dataplot_bounds_seq
    {
      \int_compare:nNnTF
        { \seq_count:N \l__dataplot_bounds_seq } = { 4 }
      {
        \tl_set:Nx \l__dataplot_min_x_tl
          { \seq_item:Nn \l__dataplot_bounds_seq { 1 } }
        \tl_set:Nx \l__dataplot_min_y_tl
          { \seq_item:Nn \l__dataplot_bounds_seq { 2 } }
        \tl_set:Nx \l__dataplot_max_x_tl
          { \seq_item:Nn \l__dataplot_bounds_seq { 3 } }
        \tl_set:Nx \l__dataplot_max_y_tl
          { \seq_item:Nn \l__dataplot_bounds_seq { 4 } }
      }
    }
    {
      \PackageError {dataplot}
      {
        Invalid ~ syntax ~ in ~ bounds=#1 ~
        (expected ~ empty ~ or ~ four ~ items, ~ found ~
        \seq_count:N \l__dataplot_bounds_seq)
      }
    }
  }

```

```

    }
    {
    The ~ bounds ~ must ~ be ~ specified ~ as ~ minX,minY,maxX,maxY
    }
  }
},

```

Set only the lower x bound

```

minx .tl_set:N = \l__dataplot_min_x_tl ,
min-x .tl_set:N = \l__dataplot_min_x_tl ,

```

Set only the upper x bound

```

maxx .tl_set:N = \l__dataplot_max_x_tl ,
max-x .tl_set:N = \l__dataplot_max_x_tl ,

```

Set only the lower y bound

```

miny .tl_set:N = \l__dataplot_min_y_tl ,
min-y .tl_set:N = \l__dataplot_min_y_tl ,

```

Set only the upper y bound

```

maxy .tl_set:N = \l__dataplot_max_y_tl ,
max-y .tl_set:N = \l__dataplot_max_y_tl ,

```

Define list of points for x ticks. (Must be a comma separated list of decimal numbers.)

These need to be converted to a sequence containing the floating point representation.

```

xticpoints .code:n =
{
  \tl_if_empty:nTF { #1 }
  {
    \clist_clear:N \l__dataplot_x_tic_clist
  }
  {
    \clist_set:Nn \l__dataplot_x_tic_clist { #1 }
    \DTLxticstrue
    \DTLxaxistrue
  }
}

```

```

},
x-tick-points .code:n =
{
  \tl_if_empty:nTF { #1 }
  {
    \clist_clear:N \l__dataplot_x_tic_clist
  }
  {
    \clist_set:Nn \l__dataplot_x_tic_clist { #1 }
    \DTLxticstrue
    \DTLxaxistrue
  }
}

```

Define list of points for y ticks. (Must be a comma separated list of decimal numbers.)

```

yticpoints .code:n =
{
  \tl_if_empty:nTF { #1 }
  {
    \clist_clear:N \l__dataplot_y_tic_clist
  }
  {
    \clist_set:Nn \l__dataplot_y_tic_clist { #1 }
    \DTLyticstrue
    \DTLyaxistrue
  }
},
y-tick-points .code:n =
{
  \tl_if_empty:nTF { #1 }
  {
    \clist_clear:N \l__dataplot_y_tic_clist
  }
  {
    \clist_set:Nn:Nn \l__dataplot_y_tic_clist { #1 }
    \DTLyticstrue
    \DTLyaxistrue
  }
},

```

Define the gap between x tick marks (xticpoints overrides xticgap)

```

xticgap .code:n =
{
  \tl_set:Nn \l__dataplot_xtic_gap_tl { #1 }
  \tl_if_empty:NF \l__dataplot_xtic_gap_tl
  {
    \DTLxticstrue
    \DTLxaxistrue
  }
},
x-tick-gap .code:n =
{
  \tl_set:Nn \l__dataplot_xtic_gap_tl { #1 }
  \tl_if_empty:NF \l__dataplot_xtic_gap_tl
  {
    \DTLxticstrue
    \DTLxaxistrue
  }
},

```

Define the gap between y tick marks (yticpoints overrides yticgap)

```

yticgap .code:n =
{
  \tl_set:Nn \l__dataplot_ytic_gap_tl { #1 }
  \tl_if_empty:NF \l__dataplot_ytic_gap_tl
  {

```

```

        \DTLyticstrue
        \DTLyaxistrue
    }
},
y-tick-gap .code:n =
{
    \tl_set:Nn \l__dataplot_ytic_gap_tl { #1 }
    \tl_if_empty:NF \l__dataplot_ytic_gap_tl
    {
        \DTLyticstrue
        \DTLyaxistrue
    }
},

```

Define the gap between x and y tick marks:

```

ticgap .code:n =
{
    \tl_set:Nn \l__dataplot_xtic_gap_tl { #1 }
    \tl_set:Nn \l__dataplot_ytic_gap_tl { #1 }
    \tl_if_empty:NF \l__dataplot_xtic_gap_tl
    {
        \DTLxticstrue
        \DTLxaxistrue
        \DTLyticstrue
        \DTLyaxistrue
    }
},
tick-gap .code:n =
{
    \tl_set:Nn \l__dataplot_xtic_gap_tl { #1 }
    \tl_set:Nn \l__dataplot_ytic_gap_tl { #1 }
    \tl_if_empty:NF \l__dataplot_xtic_gap_tl
    {
        \DTLxticstrue
        \DTLxaxistrue
        \DTLyticstrue
        \DTLyaxistrue
    }
},

```

Define comma separated list of labels for x ticks.

```

xticlabels .code:n =
{
    \tl_if_empty:nTF { #1 }
    {
        \seq_clear:N \l__dataplot_xtic_labels_seq
    }
    {
        \seq_set_from_clist:Nn \l__dataplot_xtic_labels_seq { #1 }
        \DTLxticstrue
        \DTLxaxistrue
    }
}

```

```

    }
  },
  x-tick-labels .code:n =
  {
    \tl_if_empty:nTF { #1 }
    {
      \seq_clear:N \l__dataplot_xtic_labels_seq
    }
    {
      \seq_set_from_clist:Nn \l__dataplot_xtic_labels_seq { #1 }
      \DTLxticstrue
      \DTLxaxistrue
    }
  },

```

Define comma separated list of labels for *y* ticks.

```

  yticlabels .code:n =
  {
    \tl_if_empty:nTF { #1 }
    {
      \seq_clear:N \l__dataplot_ytic_labels_seq
    }
    {
      \seq_set_from_clist:Nn \l__dataplot_ytic_labels_seq { #1 }
      \DTLyticstrue
      \DTLyaxistrue
    }
  },
  y-tick-labels .code:n =
  {
    \tl_if_empty:nTF { #1 }
    {
      \seq_clear:N \l__dataplot_ytic_labels_seq
    }
    {
      \seq_set_from_clist:Nn \l__dataplot_ytic_labels_seq { #1 }
      \DTLyticstrue
      \DTLyaxistrue
    }
  },

```

Define *x* axis label:

```

  xlabel .tl_set:N = \l__dataplot_xlabel_tl ,
  x-label .tl_set:N = \l__dataplot_xlabel_tl ,

```

Define *y* axis label:

```

  ylabel .tl_set:N = \l__dataplot_ylabel_tl ,
  y-label .tl_set:N = \l__dataplot_ylabel_tl ,

```

The legend setting may be one of: none (don't show it), north, northeast, east, southeast, south, southwest, west, or northwest. These set the count reg-

ister \dtl@legendsetting.

```
legend .choices:nn =
{
  none, north, northeast, east, southeast,
  south, southwest, west, northwest, custom
}
{
  \int_set:Nn \l__dataplot_legend_setting_int
  { \l_keys_choice_int - 1 }
},
legend .default:n = { northeast },
```

Legend labels (comma separated list). If omitted, the default is used.

```
legendlabels .code:n =
{
  \seq_set_from_clist:Nn
  \l__dataplot_legend_labels_seq { #1 }
} ,
legend-labels .code:n =
{
  \seq_set_from_clist:Nn
  \l__dataplot_legend_labels_seq { #1 }
} ,
```

Legend offset may be a single value, in which case it applies to both x and y offsets, or two values.

```
legend-offset .code:n =
{
  \seq_set_from_clist:Nn
  \l__datatool_tmp_seq { #1 }
  \int_case:nnF { \seq_count:N \l__datatool_tmp_seq }
  {
    { 1 }
    {
      \dim_set:Nn \DTLlegendxoffset
      { \seq_item:Nn \l__datatool_tmp_seq { 1 } }
      \dim_set_eq:Nn \DTLlegendyoffset \DTLlegendxoffset
    }
    { 2 }
    {
      \dim_set:Nn \DTLlegendxoffset
      { \seq_item:Nn \l__datatool_tmp_seq { 1 } }
      \dim_set:Nn \DTLlegendyoffset
      { \seq_item:Nn \l__datatool_tmp_seq { 2 } }
    }
  }
}
{
  \PackageError { dataplot }
  {
    Invalid ~ legend-offset ~ value ~ `#1': one ~ or ~ two ~
```

```

        dimensions ~ required
    }
    {
    The ~ legend-offset ~ value ~ must ~ be ~ either ~ a ~
    single ~ dimension ~ or ~ two ~ comma-separated ~ dimensions
    }
}
},

```

Set whether or not to enforce side axes:

```
side-axes .bool_set:N = \l_dataplot_side_axes_bool ,
```

Should the zero labels be omitted:

```
omit-zero-label .choices:nn =
{ auto , both , x , y , false }
{
\int_set_eq:NN
\l_dataplot_omit_zero_label_action_int
\l_keys_choice_int
} ,
omit-zero-label .initial:n = { auto } ,
omit-zero-label .default:n = { both } ,
```

Allow the x axis to be extended beyond the plot bounds:

```
extend-x-axis .code:n =
{
\int_case:nnF
{ \clist_count:n { #1 } }
{
{ \c_one_int }
{
\exp_args:NNx \datatool_set_fp:Nn
\l_dataplot_extend_min_x_axis_fp
{ \clist_item:nn { #1 } { 1 } }
\fp_set_eq:NN
\l_dataplot_extend_max_x_axis_fp
\l_dataplot_extend_min_x_axis_fp
}
}
{ 2 }
{
\exp_args:NNx \datatool_set_fp:Nn
\l_dataplot_extend_min_x_axis_fp
{ \clist_item:nn { #1 } { 1 } }
\exp_args:NNx \datatool_set_fp:Nn
\l_dataplot_extend_max_x_axis_fp
{ \clist_item:nn { #1 } { 2 } }
}
}
}
{
\PackageError { dataplot }
{

```

```

        Invalid ~ extend-x-axis ~ value ~ `#1': one ~ or ~ two ~
        numbers ~ required
    }
    {
        The ~ extend-x-axis ~ value ~ must ~ be ~ either ~ a ~
        single ~ number ~ or ~ two ~ comma-separated ~ numbers
    }
}
},
Allow the y axis to be extended beyond the plot bounds:
extend-y-axis .code:n =
{
    \int_case:nnF
    { \clist_count:n { #1 } }
    {
        { \c_one_int }
        {
            \exp_args:NNx \datatool_set_fp:Nn
            \l_dataplot_extend_min_y_axis_fp
            { \clist_item:nn { #1 } { 1 } }
            \fp_set_eq:NN
            \l_dataplot_extend_max_y_axis_fp
            \l_dataplot_extend_min_y_axis_fp
        }
        { 2 }
        {
            \exp_args:NNx \datatool_set_fp:Nn
            \l_dataplot_extend_min_y_axis_fp
            { \clist_item:nn { #1 } { 1 } }
            \exp_args:NNx \datatool_set_fp:Nn
            \l_dataplot_extend_max_y_axis_fp
            { \clist_item:nn { #1 } { 2 } }
        }
    }
}
{
    \PackageError { dataplot }
    {
        Invalid ~ extend-y-axis ~ value ~ `#1': one ~ or ~ two ~
        numbers ~ required
    }
    {
        The ~ extend-y-axis ~ value ~ must ~ be ~ either ~ a ~
        single ~ number ~ or ~ two ~ comma-separated ~ numbers
    }
}
},
Set the extension for both x and y axes:
extend-axes .code:n =
{

```

```

\int_case:nnF
  { \clist_count:n { #1 } }
  {
    { \c_one_int }
      {
        \exp_args:NNx \datatool_set_fp:Nn
          \l__dataplot_extend_min_x_axis_fp
          { \clist_item:nn { #1 } { 1 } }
        \fp_set_eq:NN
          \l__dataplot_extend_max_x_axis_fp
          \l__dataplot_extend_min_x_axis_fp
      }
    { 2 }
      {
        \exp_args:NNx \datatool_set_fp:Nn
          \l__dataplot_extend_min_x_axis_fp
          { \clist_item:nn { #1 } { 1 } }
        \exp_args:NNx \datatool_set_fp:Nn
          \l__dataplot_extend_max_x_axis_fp
          { \clist_item:nn { #1 } { 2 } }
      }
    }
  }
  {
    \PackageError { dataplot }
    {
      Invalid ~ extend-x-axis ~ value ~ `#1': one ~ or ~ two ~
      numbers ~ required
    }
    {
      The ~ extend-x-axis ~ value ~ must ~ be ~ either ~ a ~
      single ~ number ~ or ~ two ~ comma-separated ~ numbers
    }
  }
}
\fp_set_eq:NN
  \l__dataplot_extend_min_y_axis_fp
  \l__dataplot_extend_min_x_axis_fp
\fp_set_eq:NN
  \l__dataplot_extend_max_y_axis_fp
  \l__dataplot_extend_max_x_axis_fp
},

```

Label minimum end of the x axis:

```

min-x-label .tl_set:N = \l__dataplot_x_min_label_tl ,
min-x-label-style .tl_set:N = \l__dataplot_x_min_label_style_tl ,

```

Label maximum end of the x axis:

```

max-x-label .tl_set:N = \l__dataplot_x_max_label_tl ,
max-x-label-style .tl_set:N = \l__dataplot_x_max_label_style_tl ,

```

Label minimum end of the y axis:

```

min-y-label .tl_set:N = \l__dataplot_y_min_label_tl ,

```

```

min-y-label-style .tl_set:N = \l_dataplot_y_min_label_style_tl ,
Label maximum end of the y axis:
max-y-label .tl_set:N = \l_dataplot_y_max_label_tl ,
max-y-label-style .tl_set:N = \l_dataplot_y_max_label_style_tl ,
Style for x tick labels:
x-tick-label-style .tl_set:N = \l_dataplot_x_tick_label_style_tl ,
x-tic-label-style .tl_set:N = \l_dataplot_x_tick_label_style_tl ,
Style for y tick labels:
y-tick-label-style .tl_set:N = \l_dataplot_y_tick_label_style_tl ,
y-tic-label-style .tl_set:N = \l_dataplot_y_tick_label_style_tl ,
Shortcut for both:
tick-label-style .code:n =
{
\tl_set:Nn \l_dataplot_x_tick_label_style_tl { #1 }
\tl_set:Nn \l_dataplot_y_tick_label_style_tl { anchor=east, #1 }
},
tic-label-style .code:n =
{
\tl_set:Nn \l_dataplot_x_tick_label_style_tl { #1 }
\tl_set:Nn \l_dataplot_y_tick_label_style_tl { anchor=east, #1 }
},
Filter:
include-if .cs_set:Np = \__dataplot_filter:T #1,
include-if-fn .code:n =
{
\cs_set_eq:NN \__dataplot_filter:T #1
},
Deprecated experimental setting. TODO remove
condition .code:n =
{
\PackageWarning{dataplot}{Deprecated ~ option ~ `condition'. ~
Use ~ `include-if' ~ instead}
\cs_set:Nn = \__dataplot_filter:T { #1 }
}
}
Allow these keys to be set in \DTLsetup{plot={...}}
\keys_define:nn { datatool }
{
plot .code:n = { \keys_set:nn { datatool/plot } { #1 } }
}

```

29 Plotting Commands and Hooks

Calculate the transformation matrix and extent based on `\DTLminX`, `\DTLminY`, `\DTLmaxX`, `\DTLmaxY`, `\DTLplotwidth` and `\DTLplotheight`. Note that this

doesn't take the labels and axis extensions into account. The x -scale factor is given by:

$$s_x = \frac{W}{x_{\max} - x_{\min}}$$

where W is the plot width. The x offset is $-s_x x_{\min}$. Similarly for y .

```
\cs_new:Nn \dataplot_calc_transform:
{
  \fp_set:Nn \l__dataplot_x_extent_fp
  { \DTLmaxX - \DTLminX }
  \fp_set:Nn \l__dataplot_scale_x_fp
  {
```

The width as points:

```
  \dim_to_decimal:n \DTLplotwidth / \l__dataplot_x_extent_fp
  }
  \fp_set:Nn \l__dataplot_offset_x_fp
  {
    - \l__dataplot_scale_x_fp * \DTLminX
  }
  \fp_set:Nn \l__dataplot_y_extent_fp
  { \DTLmaxY - \DTLminY }
  \fp_set:Nn \l__dataplot_scale_y_fp
  {
```

The height as points:

```
  \dim_to_decimal:n \DTLplotheight / \l__dataplot_y_extent_fp
  }
  \fp_set:Nn \l__dataplot_offset_y_fp
  {
    - \l__dataplot_scale_y_fp * \DTLminY
  }
}
```

Calculate the inverse scale factors:

```
\fp_set:Nn \l__dataplot_inv_scale_x_fp
{ 1 / \l__dataplot_scale_x_fp }
\fp_set:Nn \l__dataplot_inv_scale_y_fp
{ 1 / \l__dataplot_scale_y_fp }
}
```

Transform data co-ordinates using the scales and offsets calculated above.

```
\cs_new:Nn \dataplot_transform_data_coords:NN
{
  \fp_set:Nn \l__dataplot_x_fp
  {
    \l__dataplot_scale_x_fp * #1 + \l__dataplot_offset_x_fp
  }
  \fp_set:Nn \l__dataplot_y_fp
  {
    \l__dataplot_scale_y_fp * #2 + \l__dataplot_offset_y_fp
  }
}
```

```

\tl_set:Nx #1 { \fp_to_tl:N \l__dataplot_x_fp }
\tl_set:Nx #2 { \fp_to_tl:N \l__dataplot_y_fp }
}

```

Apply pgf transform using the scales and offsets calculated above.

```

\cs_new:Nn \dataplot_apply_pgfttransform:
{
  \pgftransformcm
  { \fp_use:N \l__dataplot_scale_x_fp } { 0 }
  { 0 } { \fp_use:N \l__dataplot_scale_y_fp }
  {
    \pgfpoint
    { \fp_to_decimal:N \l__dataplot_offset_x_fp pt }
    { \fp_to_decimal:N \l__dataplot_offset_y_fp pt }
  }
}
}

```

Apply inverse pgf transform.

```

\cs_new:Nn \dataplot_apply_inverse_pgfttransform:
{
  \pgftransformcm
  { \fp_use:N \l__dataplot_inv_scale_x_fp } { 0 }
  { 0 } { \fp_use:N \l__dataplot_inv_scale_y_fp }
  {
    \pgfpoint
    {
      \fp_to_decimal:n
      { - \l__dataplot_offset_x_fp * \l__dataplot_inv_scale_x_fp }
      pt
    }
    {
      \fp_to_decimal:n
      { - \l__dataplot_offset_y_fp * \l__dataplot_inv_scale_y_fp }
      pt
    }
  }
}
}

```

```

\DTLplotstream[condition]{db name}{x key}{y key}

```

\DTLplotstream

Add points to a stream from the database called *db name* where the *x* co-ordinates are given by the key *x key* and the *y* co-ordinates are given by the key *y key*. The optional argument *condition* is the same as that for \DTLforeach

```

\NewDocumentCommand \DTLplotstream { o m m m }
{
  \DTLmapdata [ name = { #2 } ]
  {
    \DTLmapgetvalues { \l__dataplot_x_tl = #3 , \l__dataplot_y_tl = #4 }
  }
}

```

```

\IfValueTF { #1 }
{
  \ifthenelse { #1 } { \__dataplot_stream: } { }
}
{
  \__dataplot_stream:
}
}
}
\cs_new:Nn \__dataplot_stream:
{
  \DTLconverttodecimal
  { \l__dataplot_x_tl } { \l__dataplot_decimal_x_tl }
  \DTLconverttodecimal
  { \l__dataplot_y_tl } { \l__dataplot_decimal_y_tl }
  \dataplot_transform_data_coords:NN
  \l__dataplot_decimal_x_tl
  \l__dataplot_decimal_y_tl
  \pgfplotstreampoint
  {
    \pgfpointxy
    { \l__dataplot_decimal_x_tl }
    { \l__dataplot_decimal_y_tl }
  }
}
}

```

`\DTLplotatbegintikz` `\DTLplotatbegintikz` is a hook to insert stuff at the start of the `tikzpicture` environment (after the unit vectors have been set).

```
\newcommand*\DTLplotatbegintikz{}
```

`\dtlpllothandlermark`

```

\newcommand*\dtlpllothandlermark}[1]{
  \PackageWarning { dataplot }
  {
    \string \dtlpllothandlermark \space ~
    found ~ outside ~ \string \DTLplot
  }
  \pgfpllothandlermark { #1 }
}

```

`\@dtlpllothandlermark`

```

\newcommand*\@dtlpllothandlermark}[1]{
  \pgftransformreset
  \tl_set:Nn \__dataplot_post_at_begin_tl
  {
    \dataplot_apply_pgftransform:
  }
  \pgfpllothandlermark { #1 }
}

```

```
\tl_new:N \__dataplot_post_at_begin_tl
```

`\DTLplotatendtikz` `\DTLplotatendtikz` is a hook to insert stuff at the end of the `tikzpicture` environment.

```
\newcommand*{\DTLplotatendtikz}{}
```

Obtain the plot bounds, either from the settings (if provided) or calculate from the data. This will set token list variables `\DTLminX`, `\DTLminY`, `\DTLmaxX` and `\DTLmaxY` as well as floating point variables: `\l__dataplot_min_x_fp`, `\l__dataplot_min_y_fp`, `\l__dataplot_max_x_fp`, `\l__dataplot_max_y_fp` to avoid repeatedly converting between the two representations. The arguments are the column keys for the x and y data.

```
\cs_new:Nn \__dataplot_update_bounds:
```

```
{
  \bool_lazy_all:nTF
  {
    { \bool_not_p:n { \tl_if_empty_p:N \l__dataplot_min_x_tl } }
    { \bool_not_p:n { \tl_if_empty_p:N \l__dataplot_min_y_tl } }
    { \bool_not_p:n { \tl_if_empty_p:N \l__dataplot_max_x_tl } }
    { \bool_not_p:n { \tl_if_empty_p:N \l__dataplot_max_y_tl } }
  }
}
```

Store the numbers as floating point variables to save repeated parsing.

```
\datatool_set_fp:Nn \l__dataplot_min_x_fp { \l__dataplot_min_x_tl }
\datatool_set_fp:Nn \l__dataplot_min_y_fp { \l__dataplot_min_y_tl }
\datatool_set_fp:Nn \l__dataplot_max_x_fp { \l__dataplot_max_x_tl }
\datatool_set_fp:Nn \l__dataplot_max_y_fp { \l__dataplot_max_y_tl }
```

Placeholders for use in hooks.

```
\tl_set:Nx \DTLminX { \fp_to_tl:N \l__dataplot_min_x_fp }
\tl_set:Nx \DTLminY { \fp_to_tl:N \l__dataplot_min_y_fp }
\tl_set:Nx \DTLmaxX { \fp_to_tl:N \l__dataplot_max_x_fp }
\tl_set:Nx \DTLmaxY { \fp_to_tl:N \l__dataplot_max_y_fp }
}
{
  \tl_set_eq:NN \l__dataplot_min_x_fp \c_novalue_tl
  \tl_set_eq:NN \l__dataplot_min_y_fp \c_novalue_tl
  \tl_set_eq:NN \l__dataplot_max_x_fp \c_novalue_tl
  \tl_set_eq:NN \l__dataplot_max_y_fp \c_novalue_tl
  \seq_map_inline:Nn \l__dataplot_dbnames_seq
  {
    \DTLsetup{ default-name = { ##1 } }
    \__dataplot_filtered_map:n
    {
      \datatool_set_fp:Nn \l__dataplot_x_fp
        { \l__dataplot_x_tl }
      \datatool_set_fp:Nn \l__dataplot_y_fp
        { \l__dataplot_y_tl }
      \exp_args:NV \tl_if_novalue:nTF \l__dataplot_min_x_fp
```

```

{
  \tl_if_empty:NT \l__dataplot_min_x_tl
  {
    \fp_set_eq:NN
      \l__dataplot_min_x_fp
      \l__dataplot_x_fp
  }
}
{
  \fp_set:Nn \l__dataplot_min_x_fp
    { min ( \l__dataplot_min_x_fp , \l__dataplot_x_fp ) }
}
\exp_args:NV \tl_if_novalue:nTF \l__dataplot_min_y_fp
{
  \tl_if_empty:NT \l__dataplot_min_y_tl
  {
    \fp_set_eq:NN
      \l__dataplot_min_y_fp
      \l__dataplot_y_fp
  }
}
{
  \fp_set:Nn \l__dataplot_min_y_fp
    { min ( \l__dataplot_min_y_fp , \l__dataplot_y_fp ) }
}
\exp_args:NV \tl_if_novalue:nTF \l__dataplot_max_x_fp
{
  \tl_if_empty:NT \l__dataplot_max_x_tl
  {
    \fp_set_eq:NN
      \l__dataplot_max_x_fp
      \l__dataplot_x_fp
  }
}
{
  \fp_set:Nn \l__dataplot_max_x_fp
    { max ( \l__dataplot_max_x_fp , \l__dataplot_x_fp ) }
}
\exp_args:NV \tl_if_novalue:nTF \l__dataplot_max_y_fp
{
  \tl_if_empty:NT \l__dataplot_max_y_tl
  {
    \fp_set_eq:NN
      \l__dataplot_max_y_fp
      \l__dataplot_y_fp
  }
}
{
  \fp_set:Nn \l__dataplot_max_y_fp
    { max ( \l__dataplot_max_y_fp , \l__dataplot_y_fp ) }
}

```

```

    }
  }
}
Update \DTLminX
\exp_args:NV \tl_if_novalue:nT \l__dataplot_min_x_fp
{
  \tl_if_empty:NTF \l__dataplot_min_x_tl
  {
    \PackageError { dataplot }
    { No ~ minimum ~ X ~ available! }
    {
      Check ~ that ~ your ~ filter ~ criteria ~
      hasn't ~ excluded ~ all ~ data
    }
    \fp_zero:N \l__dataplot_min_x_fp
    \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n
  }
  {
    \datatool_set_fp:Nn \l__dataplot_min_x_fp
    { \l__dataplot_min_x_tl }
  }
}
\tl_set:Nx \DTLminX { \fp_to_tl:N \l__dataplot_min_x_fp }
Update \DTLminY
\exp_args:NV \tl_if_novalue:nT \l__dataplot_min_y_fp
{
  \tl_if_empty:NTF \l__dataplot_min_y_tl
  {
    \PackageError { dataplot }
    { No ~ minimum ~ Y ~ available! }
    {
      Check ~ that ~ your ~ filter ~ criteria ~
      hasn't ~ excluded ~ all ~ data
    }
    \fp_zero:N \l__dataplot_min_y_fp
    \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n
  }
  {
    \datatool_set_fp:Nn \l__dataplot_min_y_fp
    { \l__dataplot_min_y_tl }
  }
}
\tl_set:Nx \DTLminY { \fp_to_tl:N \l__dataplot_min_y_fp }
Update \DTLmaxX
\exp_args:NV \tl_if_novalue:nT \l__dataplot_max_x_fp
{
  \tl_if_empty:NTF \l__dataplot_max_x_tl
  {

```

```

\PackageError { dataplot }
{ No ~ maximum ~ X ~ available! }
{
  Check ~ that ~ your ~ filter ~ criteria ~
  hasn't ~ excluded ~ all ~ data
}
\fp_zero:N \l_dataplot_max_x_fp
\cs_set_eq:NN \__dataplot_do_plot:n \use_none:n
}
{
  \datatool_set_fp:Nn \l_dataplot_max_x_fp
  { \l_dataplot_max_x_tl }
}
}
\tl_set:Nx \DTLmaxX { \fp_use:N \l_dataplot_max_x_fp }
Update \DTLmaxY
\exp_args:NV \tl_if_novalue:nT \l_dataplot_max_y_fp
{
  \tl_if_empty:NTF \l_dataplot_max_y_tl
  {
    \PackageError { dataplot }
    { No ~ maximum ~ Y ~ available! }
    {
      Check ~ that ~ your ~ filter ~ criteria ~
      hasn't ~ excluded ~ all ~ data
    }
    \fp_zero:N \l_dataplot_max_y_fp
    \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n
  }
  {
    \datatool_set_fp:Nn \l_dataplot_max_y_fp
    { \l_dataplot_max_y_tl }
  }
}
\tl_set:Nx \DTLmaxY { \fp_use:N \l_dataplot_max_y_fp }
}
Don't bother checking if an error has already occurred.
\__dataplot_do_plot:n
{
  \fp_compare:nNnT
  { \l_dataplot_min_x_fp } > { \l_dataplot_max_x_fp }
  {
    \PackageError {dataplot}
    {
      Min ~ X ~ ( \fp_use:N \l_dataplot_min_x_fp ) ~
      > ~ Max ~ X ~ ( \fp_use:N \l_dataplot_min_x_fp )
    }
  }
  {
    If ~ you ~ have ~ used ~ the ~ `bounds' ~ setting ~, check ~

```

```

        that ~ it ~ is ~ specified ~ as ~ minX,minY,maxX,maxY
    }
    \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n
}
\fp_compare:nNnT
{ \l__dataplot_min_y_fp } > { \l__dataplot_max_y_fp }
{
    \PackageError {dataplot}
    {
        Min ~ Y ~ ( \fp_use:N \l__dataplot_min_y_fp ) ~
        > ~ Max ~ Y ~ ( \fp_use:N \l__dataplot_min_y_fp )
    }
    {
        If ~ you ~ have ~ used ~ the ~ `bounds' ~ setting ~, check ~
        that ~ it ~ is ~ specified ~ as ~ minX,minY,maxX,maxY
    }
}
\cs_set_eq:NN \__dataplot_do_plot:n \use_none:n
}
}
}
}
}

```

```

\__dataplot_x_y_bounded:nnnnnnTF
{<x>}{<min x>}{<max x>}
{<y>}{<min y>}{<max y>}
{<true>}{<false>}

```

Test if x is between min x and max x and y is between min y and max y

```

\cs_new:Nn \__dataplot_x_y_bounded:nnnnnnTF
{
    \bool_lazy_any:nTF
    {
        { \fp_compare_p:n { #1 < #2 } }
        { \fp_compare_p:n { #1 > #3 } }
        { \fp_compare_p:n { #4 < #5 } }
        { \fp_compare_p:n { #4 > #6 } }
    }
    { #8 } { #7 }
}
\cs_new:Nn \__dataplot_x_y_bounded:nnnnnnT
{
    \__dataplot_x_y_bounded:nnnnnnTF
    { #1 } { #2 } { #3 } { #4 } { #5 } { #6 } { #7 } { }
}

```

Tick lists.

```
\fp_new:N \l__dataplot_min_gap_fp
```

Calculate x tick gap or construct tick list if x tics required.

```
\cs_new:Nn \__dataplot_calc_x_tics:
```

```

{
  \legacy_if:nT { DTLxtics }
  {
    \clist_if_empty:NTF \l__dataplot_x_tic_clist
    {
      \seq_clear:N \l__dataplot_x_tic_seq
      \tl_if_empty:NTF \l__dataplot_xtic_gap_tl
      {
        No tick list or gap set by user. Get the min tick gap in data co-ordinates
        \fp_set:Nn \l__dataplot_min_gap_fp
        {
          (
            ( \DTLmintickgap - \l__dataplot_offset_x_fp )
            / \l__dataplot_scale_x_fp
          )
          / 65536
        }
        construct tick list
        \__dataplot_construct_tick_list:NNNN
        \l__dataplot_min_x_fp
        \l__dataplot_max_x_fp
        \l__dataplot_min_gap_fp
        \l__dataplot_x_tic_seq
      }
      {
        Gap set by user
        \fp_set:Nn
        \l__dataplot_min_gap_fp
        { \l__dataplot_xtic_gap_tl }
        \fp_compare:nTF
        { \l__dataplot_min_x_fp < \c_zero_fp < \l__dataplot_max_x_fp }
        {
          \__dataplot_construct_tick_list_over_zero:NNNN
          \l__dataplot_min_x_fp
          \l__dataplot_max_x_fp
          \l__dataplot_x_tic_seq
          \l__dataplot_min_gap_fp
        }
        {
          \__dataplot_construct_tick_list_with_gap:NNNN
          \l__dataplot_min_x_fp
          \l__dataplot_max_x_fp
          \l__dataplot_x_tic_seq
          \l__dataplot_min_gap_fp
        }
      }
    }
  }
}

```

Check that the provided tick marks are within the bounds and save to sequence.

```

    \__dataplot_to_fp_seq:NNnn
    \l__dataplot_x_tic_seq
    \l__dataplot_x_tic_clist
    \l__dataplot_min_x_fp
    \l__dataplot_max_x_fp
  }
  \__dataplot_calc_minor_x_ticks:
  \__dataplot_calc_x_label_dim:
}
}
Minor x ticks:
\cs_new:Nn \__dataplot_calc_minor_x_ticks:
{
  \dim_zero:N \l__dataplot_x_tic_label_height_dim
Construct a list of  $x$  minor tick points if required
  \seq_clear:N \l__dataplot_x_minor_tic_seq
  \legacy_if:nT { DTLxminorotics }
  {
    \__dataplot_construct_minor_ticks:NNNNN
    \l__dataplot_x_tic_seq
    \l__dataplot_min_x_fp
    \l__dataplot_max_x_fp
    \l__dataplot_scale_x_fp
    \l__dataplot_x_minor_tic_seq
  }
}

```

```

\__dataplot_get_default_tic_label:NN
<fp-var><int-var>

```

Get the default tic label for position $\langle fp-var \rangle$ and rounding value $\langle int-var \rangle$

```

\cs_new:Nn \__dataplot_get_default_tic_label:Nn
{
  \fp_set:Nn \l__datatool_tmpa_fp
  {
    round ( #1 , #2 )
  }
  \tl_set:Nx \l__dataplot_tic_label_tl
  { \fp_to_decimal:N \l__datatool_tmpa_fp }
  \datatool_pad_trailing_zeros:Nn
  \l__dataplot_tic_label_tl { #2 }
  \exp_args:NV \DTLdecimaltolocale \l__dataplot_tic_label_tl
  \l__dataplot_tmpa_tl
  \tl_set:Nx \l__dataplot_tic_label_tl
  {
    \exp_not:N \__datatool_datum:nnnn
  }
}

```

```

    { \exp_not:V \l__dataplot_tic_label_tl }
    { \exp_not:V \l__dataplot_tmpa_tl }
    { }
    { \c_datatool_decimal_int }
  }
}
\cs_generate_variant:Nn \__dataplot_get_default_tic_label:Nn
{ NV , Nx }
Determine the height of the  $x$  tick labels and save default tick labels if required.
\cs_new:Nn \__dataplot_calc_x_label_dim:
{
  \seq_if_empty:NTF \l__dataplot_xtic_labels_seq
  {
    \seq_map_inline:Nn \l__dataplot_x_tic_seq
    {
Tick label not provided, use the  $x$  value. Reconstruct the floating point variable:
      \tl_set:Nn \l__datatool_tmpa_fp { ##1 }
Obtain the default label:
      \__dataplot_get_default_tic_label:NV
      \l__datatool_tmpa_fp \c@DTLplotroundXvar
Save for later:
      \seq_put_right:NV \l__dataplot_xtic_labels_seq
      \l__dataplot_tic_label_tl
Calculate height:
      \settoheight \dtl@tmplength
      { \l__dataplot_tic_label_tl }
Compare with current max height:
      \dim_compare:nNnT
      { \dtl@tmplength }
      >
      { \l__dataplot_x_tic_label_height_dim }
      {
        \dim_set_eq:NN
        \l__dataplot_x_tic_label_height_dim \dtl@tmplength
      }
    }
  }
}
\seq_map_inline:Nn \l__dataplot_xtic_labels_seq
{
  \datatool_measure_height:Nn \dtl@tmplength
  { \DTLplotdisplayXticklabel { ##1 } }
  \dim_compare:nNnT
  { \dtl@tmplength } > { \l__dataplot_x_tic_label_height_dim }
  {
    \dim_set_eq:NN \l__dataplot_x_tic_label_height_dim \dtl@tmplength
  }
}

```

```

    }
  }
}

```

Calculate y tick gap or construct tick list if y tics required.

```

\cs_new:Nn \__dataplot_calc_y_tics:
{
  \dim_zero:N \l__dataplot_y_tic_label_width_dim
  \legacy_if:nT { DTLytics }
  {
    \clist_if_empty:NTF \l__dataplot_y_tic_clist
    {
      \seq_clear:N \l__dataplot_y_tic_seq

```

List of y tics not provided.

```

      \tl_if_empty:NTF \l__dataplot_ytic_gap_tl
      {

```

No y tic gap not provided. Get the min tick gap in data co-ordinates.

```

      \fp_set:Nn \l__dataplot_min_gap_fp
      {
        (
          ( \DTLmintickgap - \l__dataplot_offset_y_fp )
          / \l__dataplot_scale_y_fp
        )
        / 65536
      }

```

Construct tick list

```

      \__dataplot_construct_tick_list:NNNN
      \l__dataplot_min_y_fp
      \l__dataplot_max_y_fp
      \l__dataplot_min_gap_fp
      \l__dataplot_y_tic_seq
    }
  {

```

Gap set by user

```

      \fp_set:Nn
      \l__dataplot_min_gap_fp
      { \l__dataplot_ytic_gap_tl }
      \fp_compare:nTF
      { \l__dataplot_min_y_fp < \c_zero_fp < \l__dataplot_max_y_fp }
      {
        \__dataplot_construct_tick_list_over_zero:NNNN
        \l__dataplot_min_y_fp
        \l__dataplot_max_y_fp
        \l__dataplot_y_tic_seq
        \l__dataplot_min_gap_fp
      }
    {

```

```

        \__dataplot_construct_tick_list_with_gap:NNNN
        \l__dataplot_min_y_fp
        \l__dataplot_max_y_fp
        \l__dataplot_y_tic_seq
        \l__dataplot_min_gap_fp
    }
}
{

```

Check that the provided tick marks are within the bounds and save to sequence.

```

    \__dataplot_to_fp_seq:NNnn
    \l__dataplot_y_tic_seq
    \l__dataplot_y_tic_clist
    \l__dataplot_min_y_fp
    \l__dataplot_max_y_fp
}
\__dataplot_calc_minor_y_tics:
\__dataplot_calc_y_label_dim:
}
}
Minor y ticks:
\cs_new:Nn \__dataplot_calc_minor_y_tics:
{
\seq_clear:N \l__dataplot_y_minor_tic_seq
\legacy_if:nT { DTLyminortics }
{
    \__dataplot_construct_minor_ticks:NNNNN
    \l__dataplot_y_tic_seq
    \l__dataplot_min_y_fp
    \l__dataplot_max_y_fp
    \l__dataplot_scale_y_fp
    \l__dataplot_y_minor_tic_seq
}
}

```

Determine the width of the *y* tick labels and save default tick labels if required.

```

\cs_new:Nn \__dataplot_calc_y_label_dim:
{
    \seq_if_empty:NTF\l__dataplot_ytic_labels_seq
    {
        \seq_map_inline:Nn \l__dataplot_y_tic_seq
        {

```

Tick label not provided, use the *y* value. Reconstruct the floating point variable:

```

        \tl_set:Nn \l__datatool_tmpa_fp { ##1 }

```

Obtain the default label:

```

        \__dataplot_get_default_tic_label:NV
        \l__datatool_tmpa_fp \c@DTLplotroundYvar

```

Save for later:

```
\seq_put_right:NV \l__dataplot_ytic_labels_seq
\l__dataplot_tic_label_tl
```

Calculate width:

```
\settowidth \dtl@tmplength
{ \l__dataplot_tic_label_tl }
```

Compare with current max width:

```
\dim_compare:nNnT
{ \dtl@tmplength }
>
{ \l__dataplot_y_tic_label_width_dim }
{
\dim_set_eq:NN \l__dataplot_y_tic_label_width_dim \dtl@tmplength
}
}
}
{
\seq_map_inline:Nn \l__dataplot_ytic_labels_seq
{
\datatool_measure_width:Nn \dtl@tmplength
{ \DTLplotdisplayYticklabel { ##1 } }
\dim_compare:nNnT
{ \dtl@tmplength }
>
{ \l__dataplot_y_tic_label_width_dim }
{
\dim_set_eq:NN \l__dataplot_y_tic_label_width_dim \dtl@tmplength
}
}
}
}
}
```

Do the plot:

```
\cs_new:Nn \__dataplot_do_plot:
{
```

Initialise:

```
\tl_clear:N \l__dataplot_content_tl
\tl_clear:N \l__dataplot_legend_tl
```

Enable `\dtlpllothandlermark` for the begin and end hooks.

```
\tl_clear:N \__dataplot_post_at_begin_tl
\tl_set_eq:NN \dtlpllothandlermark \@dtlpllothandlermark
```

Start the picture.

```
\begin{tikzpicture}
```

Set the x and y unit vectors.

```
\pgfsetxvec{\pgfpoint{1pt}{0pt}}%
\pgfsetyvec{\pgfpoint{0pt}{1pt}}%
```

```

Set the transformation matrix.
    \dataplot_apply_pgfttransform:
Initial hook.
    \DTLplotatbegintikz
    \__dataplot_post_at_begin_tl
Plot grid if required
    \__dataplot_add_grid:
Plot box or axes:
    \__dataplot_add_axes:
Plot x tics if required.
    \__dataplot_add_x_tics:
Plot x label if required.
    \__dataplot_add_x_label:
Plot the x minor ticks if required
    \__dataplot_add_minor_x:
Plot y tics if required.
    \__dataplot_add_y_tics:
Plot y label if required.
    \__dataplot_add_y_label:
Plot the y minor ticks if required
    \__dataplot_add_minor_y:
Do the accumulated plot instructions if any remaining:
    \l__dataplot_content_tl
    \tl_clear:N \l__dataplot_content_tl
Reset transformation matrix. (Don't want marker shapes to be scaled or skewed.)
    \begin{scope}
    \pgfttransformreset
Draw marks and lines for each database and the legend:
    \__dataplot_plot_data:
Retain local assignments after scope:
    \tl_put_right:Nx \l__dataplot_content_tl
    {
End current scope:
    \exp_not:N \end{scope}
    \exp_not:N \tl_set:Nn \exp_not:N \DTLminX { \DTLminX }
    \exp_not:N \tl_set:Nn \exp_not:N \DTLminY { \DTLminY }
    \exp_not:N \tl_set:Nn \exp_not:N \DTLmaxX { \DTLmaxX }
    \exp_not:N \tl_set:Nn \exp_not:N \DTLmaxY { \DTLmaxY }
    \exp_not:N \int_set:Nn
    \exp_not:N \l__dataplot_stream_index_int
    { \int_use:N \l__dataplot_stream_index_int }

```

```

    }
    \l_dataplot_content_tl
    \tl_clear:N \l_dataplot_content_tl
End hook
    \DTLplotatendtikz
Retain local assignments after scope:
    \tl_put_right:Nx \l_dataplot_content_tl
    {
End tikzpicture environment:
    \exp_not:N \end{tikzpicture}
    \exp_not:N \tl_set:Nn \exp_not:N \DTLminX { \DTLminX }
    \exp_not:N \tl_set:Nn \exp_not:N \DTLminY { \DTLminY }
    \exp_not:N \tl_set:Nn \exp_not:N \DTLmaxX { \DTLmaxX }
    \exp_not:N \tl_set:Nn \exp_not:N \DTLmaxY { \DTLmaxY }
    \exp_not:N \int_set:Nn
    \exp_not:N \l_dataplot_stream_index_int
    { \int_use:N \l_dataplot_stream_index_int }
    }
    \l_dataplot_content_tl
    \tl_clear:N \l_dataplot_content_tl
}
Add box or axes:
    \cs_new:Nn \__dataplot_add_axes:
    {
Determine whether to put a box around the plot
    \legacy_if:nT { DTLbox }
    {
        \tl_put_right:Nx \l_dataplot_content_tl
        {
            \exp_not:N \draw
            (
                \fp_to_decimal:N \l__dataplot_extended_min_x_fp ,
                \fp_to_decimal:N \l__dataplot_extended_min_y_fp
            ) ~
            -- ~
            (
                \fp_to_decimal:N \l__dataplot_extended_max_x_fp ,
                \fp_to_decimal:N \l__dataplot_extended_min_y_fp
            ) ~
            -- ~
            (
                \fp_to_decimal:N \l__dataplot_extended_max_x_fp ,
                \fp_to_decimal:N \l__dataplot_extended_max_y_fp
            ) ~
            -- ~
            (
                \fp_to_decimal:N \l__dataplot_extended_min_x_fp ,

```

```

        \fp_to_decimal:N \l__dataplot_extended_max_y_fp
      ) ~
      -- ~ cycle ; ~
    }
  }
}
Plot x axis if required.
\legacy_if:nT { DTLxaxis }
{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw [ \exp_not:V \DTLXAxisStyle ]
  }
  \bool_if:NTF \l__dataplot_zero_y_axis_bool
  {
x axis passes through  $y = 0$ .
    \tl_put_right:Nx \l__dataplot_content_tl
    {
      (
        \fp_to_decimal:N \l__dataplot_extended_min_x_fp ,
        0 )
      }
    \tl_if_empty:NF \l__dataplot_x_min_label_tl
    {
      \tl_put_right:Nx \l__dataplot_content_tl
      {
        ~ node [ \exp_not:V \l__dataplot_x_min_label_style_tl ]
        { \exp_not:V \l__dataplot_x_min_label_tl }
      }
    }
    \tl_put_right:Nx \l__dataplot_content_tl
    {
      --
      (
        \fp_to_decimal:N \l__dataplot_extended_max_x_fp ,
        0 )
      }
    }
  }
}
x axis passes through  $y = \min_y$ .
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    (
      \fp_to_decimal:N \l__dataplot_extended_min_x_fp ,
      \DTLminY
    )
  }
  \tl_if_empty:NF \l__dataplot_x_min_label_tl
  {

```

```

\tl_put_right:Nx \l__dataplot_content_tl
{
  ~ node [ \exp_not:V \l__dataplot_x_min_label_style_tl ]
  { \exp_not:V \l__dataplot_x_min_label_tl }
}
\tl_put_right:Nx \l__dataplot_content_tl
{
  --
  (
    \fp_to_decimal:N \l__dataplot_extended_max_x_fp ,
    \DTLminY
  )
}
\tl_if_empty:NF \l__dataplot_x_max_label_tl
{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    ~ node [ \exp_not:V \l__dataplot_x_max_label_style_tl ]
    { \exp_not:V \l__dataplot_x_max_label_tl }
  }
}
\tl_put_right:Nn \l__dataplot_content_tl
{ ; ~ }
}

```

Plot y axis if required.

```

\legacy_if:nT { DTLyaxis }
{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw [ \exp_not:V \DTLYAxisStyle ]
  }
  \bool_if:NTF \l__dataplot_zero_x_axis_bool
  {

```

y axis passes through $x = 0$.

```

\tl_put_right:Nx \l__dataplot_content_tl
{
  (0,
    \fp_to_decimal:N \l__dataplot_extended_min_y_fp
  )
}
\tl_if_empty:NF \l__dataplot_y_min_label_tl
{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    ~ node [ \exp_not:V \l__dataplot_y_min_label_style_tl ]
    { \exp_not:V \l__dataplot_y_min_label_tl }
  }
}

```

```

    }
    \tl_put_right:Nx \l__dataplot_content_tl
    {
      --
      (0,
        \fp_to_decimal:N \l__dataplot_extended_max_y_fp
      )
    }
  }
}
{
y axis passes through  $x = \min_x$ .
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    (\DTLminX,
      \fp_to_decimal:N \l__dataplot_extended_min_y_fp
    )
  }
  \tl_if_empty:NF \l__dataplot_y_min_label_tl
  {
    \tl_put_right:Nx \l__dataplot_content_tl
    {
      ~ node [ \exp_not:V \l__dataplot_y_min_label_style_tl ]
      { \exp_not:V \l__dataplot_y_min_label_tl }
    }
  }
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    --
    (\DTLminX,
      \fp_to_decimal:N \l__dataplot_extended_max_y_fp
    )
  }
}
\l__dataplot_y_max_label_tl
{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    ~ node [ \exp_not:V \l__dataplot_y_max_label_style_tl ]
    { \exp_not:V \l__dataplot_y_max_label_tl }
  }
}
\l__dataplot_content_tl
{ ; ~ }
}
\l__dataplot_content_tl
\l__clear:N \l__dataplot_content_tl
}
Plot grid if required:
\cs_new:Nn \l__dataplot_add_grid:

```

```

{
  \legacy_if:nT { DTLgrid }
  {
    Draw minor grid lines if minor ticks enabled and if there is a line style set.
    \tl_if_empty:NF \DTLminorgridstyle
    {
      \legacy_if:nT { DTLxminorotics }
      {
        Iterate through minor x ticks.
        \seq_map_inline:Nn \l__dataplot_x_minor_tic_seq
        {
          Reconstruct floating point variable.
          \tl_set:Nn \l__dataplot_x_fp { ##1 }
          \tl_set:Nx \l__dataplot_x_tl
            { \fp_to_decimal:N \l__dataplot_x_fp }
          Draw minor grid line.
          \tl_put_right:Nx \l__dataplot_content_tl
          {
            {
              \exp_not:N \draw [ \exp_not:V \DTLminorgridstyle ]
              ( \l__dataplot_x_tl ,
                \fp_to_decimal:N \l__dataplot_extended_min_y_fp
              )
              --
              ( \l__dataplot_x_tl,
                \fp_to_decimal:N \l__dataplot_extended_max_y_fp
              ); ~
            }
          }
        }
      }
    }
  }
  \legacy_if:nT { DTLyminorotics }
  {
    Iterate through minor y ticks.
    \seq_map_inline:Nn \l__dataplot_y_minor_tic_seq
    {
      Reconstruct floating point variable.
      \tl_set:Nn \l__dataplot_y_fp { ##1 }
      \tl_set:Nx \l__dataplot_y_tl
        { \fp_to_decimal:N \l__dataplot_y_fp }
      Draw minor grid line.
      \tl_put_right:Nx \l__dataplot_content_tl
      {
        {
          \exp_not:N \draw [ \exp_not:V \DTLminorgridstyle ]
          (
            \fp_to_decimal:N \l__dataplot_extended_min_x_fp ,
            \l__dataplot_y_tl
          )
        }
      }
    }
  }
}

```



```

    }
  }
Plot x tics if required:
\cs_new:Nn \__dataplot_add_x_tics:
{
  \legacy_if:nT { DTLxtics }
  {
Get tick length in terms of canvas co-ordinates
    \fp_set:Nn \l__dataplot_tick_length_fp
    {
      (
        (
          \dim_to_decimal_in_sp:n { \DTLticklength }
          - \l__dataplot_offset_y_fp
        ) / \l__dataplot_scale_y_fp
      )
    } / 65536
  }
Get tick label offset in terms of canvas co-ordinates
    \dim_add:Nn \l__dataplot_x_tic_label_height_dim
    { \DTLticklabeloffset }
    \fp_set:Nn \l__dataplot_tic_label_offset_fp
    {
      (
        (
          \dim_to_decimal_in_sp:n
            { \l__dataplot_x_tic_label_height_dim }
          + \l__dataplot_offset_y_fp
        ) / \l__dataplot_scale_y_fp
      ) / 65536
    }
Iterate through tick list. The default tick labels should have already been added in
\__dataplot_calc_x_label_dim:
    \seq_map_indexed_inline:Nn \l__dataplot_x_tic_seq
    {
Reconstruct the floating point variable:
      \tl_set:Nn \l__dataplot_x_fp { ##2 }
      \tl_set:Nn \l__dataplot_x_tl
      { \fp_use:N \l__dataplot_x_fp }
Fetch current tick label:
      \tl_set:Nx \l__dataplot_tic_label_tl
      {
        \seq_item:Nn \l__dataplot_xtic_labels_seq { ##1 }
      }
Draw tick.

```

```

\legacy_if:nTF { DTLxticsin }
{
Tick above the  $x$ -axis. (Tick in)
\bool_if:nTF \l__dataplot_zero_y_axis_bool
{
Enforce  $x$  axis to pass through  $y = 0$ .
\fp_set_eq:NN \l__dataplot_y_fp
\l__dataplot_tick_length_fp
\tl_put_right:Nx \l__dataplot_content_tl
{
\exp_not:N \draw
( \l__dataplot_x_tl , 0 )
--
( \l__dataplot_x_tl ,
\fp_to_decimal:N \l__dataplot_y_fp ) ; ~
}
\fp_set:Nn \l__dataplot_y_fp
{ - \l__dataplot_tic_label_offset_fp }
}
}
{
Don't enforce  $x$  axis to pass through  $y = 0$  (but this will occur if  $\min y = 0$ ).
\fp_set:Nn \l__dataplot_y_fp
{
\l__dataplot_min_y_fp
+ \l__dataplot_tick_length_fp
}
\tl_put_right:Nx \l__dataplot_content_tl
{
\exp_not:N \draw
( \l__dataplot_x_tl , \DTLminY )
--
( \l__dataplot_x_tl ,
\fp_to_decimal:N \l__dataplot_y_fp ) ; ~
}
\fp_set:Nn \l__dataplot_y_fp
{
\l__dataplot_min_y_fp
- \l__dataplot_tic_label_offset_fp
}
}
}
Draw the label unless 0 and omit zero label on.
\bool_lazy_and:nnF
{ \l__dataplot_omit_zero_x_label_bool }
{
\fp_compare_p:nNn
{ \l__dataplot_x_fp } = { \c_zero_fp }
}
}

```

```

{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw
      ( \l__dataplot_x_tl ,
        \fp_to_decimal:N \l__dataplot_y_fp ) ~
      node [ \exp_not:V \l__dataplot_x_tick_label_style_tl ]
      {
        \exp_not:N \DTLplotdisplayxticklabel
        { \exp_not:V \l__dataplot_tic_label_tl }
      } ; ~
  }
}
}
{
Tick below the  $x$ -axis. (Tick out)
\bool_if:NTF \l__dataplot_zero_y_axis_bool
{
  \fp_set:Nn \l__dataplot_y_fp
    { - \l__dataplot_tick_length_fp }
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw
      ( \l__dataplot_x_tl , 0 )
      --
      ( \l__dataplot_x_tl ,
        \fp_to_decimal:N \l__dataplot_y_fp ) ; ~
  }
  \fp_sub:Nn \l__dataplot_y_fp
    { \l__dataplot_tic_label_offset_fp }
}
{
Don't enforce  $x$  axis to pass through  $y = 0$  (but this will occur if min  $y = 0$ ).
\fp_set:Nn \l__dataplot_y_fp
{
  \l__dataplot_min_y_fp
  - \l__dataplot_tick_length_fp
}
\tl_put_right:Nx \l__dataplot_content_tl
{
  \exp_not:N \draw
    ( \l__dataplot_x_tl , \DTLminY )
    --
    ( \l__dataplot_x_tl ,
      \fp_to_decimal:N \l__dataplot_y_fp ) ;
}
\fp_sub:Nn \l__dataplot_y_fp
{ \l__dataplot_tic_label_offset_fp }
}

```

Draw the label unless 0 and omit zero label on.

```

\bool_lazy_and:nnF
{ \l_dataplot_omit_zero_x_label_bool }
{ \fp_compare_p:nNn { \l_dataplot_x_fp } = { \c_zero_fp } }
{
  \tl_put_right:Nx \l_dataplot_content_tl
  {
    \exp_not:N \draw
    ( \l_dataplot_x_tl ,
      \fp_to_decimal:N \l_dataplot_y_fp ) ~
    node [ \exp_not:V \l_dataplot_x_tick_label_style_tl ]
    {
      \exp_not:N \DTLplotdisplayXticklabel
      { \exp_not:V \l_dataplot_tic_label_tl }
    } ; ~
  }
}

```

Draw box ticks, if box setting is on.

```

\legacy_if:nT { DTLbox }
{

```

If min y isn't 0 and the box setting is on, need to draw tick on the bottom of the box according to the box setting.

```

  \__dataplot_draw_box_ticks_lower_x:n
  {
    \int_case:nnT { \l_dataplot_box_ticks_int }
    {
      { \c_one_int } % match
      {
        \legacy_if:nTF { DTLxticsin }
        {
          \fp_set:Nn \l_dataplot_y_fp
          {
            \l_dataplot_extended_min_y_fp
            + \l_dataplot_tick_length_fp
          }
        }
        {
          \fp_set:Nn \l_dataplot_y_fp
          {
            \l_dataplot_extended_min_y_fp
            - \l_dataplot_tick_length_fp
          }
        }
      }
    }
  }
  { 2 } % in
  {
    \fp_set:Nn \l_dataplot_y_fp

```

```

        {
          \l__dataplot_extended_min_y_fp
          + \l__dataplot_tick_length_fp
        }
      }
    { 3 } % out
    {
      \fp_set:Nn \l__dataplot_y_fp
      {
        \l__dataplot_extended_min_y_fp
        - \l__dataplot_tick_length_fp
      }
    }
  }
  {
    \tl_put_right:Nx \l__dataplot_content_tl
    {
      \exp_not:N \draw
      ( \l__dataplot_x_tl ,
        \fp_to_decimal:N \l__dataplot_extended_min_y_fp )
      --
      ( \l__dataplot_x_tl ,
        \fp_to_decimal:N \l__dataplot_y_fp ) ; ~
    }
  }
}

```

Draw the ticks on the opposite side of the box.

```

\int_case:nnT { \l__dataplot_box_ticks_int }
{
  { \c_one_int } % match
  {
    \legacy_if:nTF { DTLxticsin }
    {
      \fp_set:Nn \l__dataplot_y_fp
      {
        \l__dataplot_extended_max_y_fp
        - \l__dataplot_tick_length_fp
      }
    }
    {
      \fp_set:Nn \l__dataplot_y_fp
      {
        \l__dataplot_extended_max_y_fp
        + \l__dataplot_tick_length_fp
      }
    }
  }
}
{ 2 } % in
{

```

```

\fp_set:Nn \l__dataplot_y_fp
{
  \l__dataplot_extended_max_y_fp
  - \l__dataplot_tick_length_fp
}
}
{ 3 } % out
{
  \fp_set:Nn \l__dataplot_y_fp
  {
    \l__dataplot_extended_max_y_fp
    + \l__dataplot_tick_length_fp
  }
}
}
{
\tl_put_right:Nx \l__dataplot_content_tl
{
  \exp_not:N \draw
  ( \l__dataplot_x_tl ,
    \fp_to_decimal:N \l__dataplot_extended_max_y_fp )
  --
  ( \l__dataplot_x_tl ,
    \fp_to_decimal:N \l__dataplot_y_fp ) ; ~
}
}
}
}
\l__dataplot_content_tl
\tl_clear:N \l__dataplot_content_tl
}
}
Plot x label if required.
\cs_new:Nn \__dataplot_add_x_label:
{
  \tl_if_empty:NF \l__dataplot_xlabel_tl
  {
Get baseline in terms of canvas co-ordinates
\fp_add:Nn \l__dataplot_tic_label_offset_fp
{
  (
    (
      \dim_to_decimal_in_sp:n { \baselineskip }
      + \l__dataplot_offset_y_fp
    ) / \l__dataplot_scale_y_fp
  ) / 65536
}
}
Get halfway position

```

```

\fp_set:Nn \l__dataplot_x_fp
  { \l__dataplot_min_x_fp + 0.5 * \l__dataplot_x_extent_fp }
\bool_if:NTF \l__dataplot_zero_y_axis_bool
  {
    \fp_set:Nn \l__dataplot_y_fp
      { - \l__dataplot_tic_label_offset_fp }
  }
  {
    \fp_set:Nn \l__dataplot_y_fp
      { \l__dataplot_min_y_fp - \l__dataplot_tic_label_offset_fp }
  }
\l__put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw
      ( \fp_to_decimal:N \l__dataplot_x_fp ,
        \fp_to_decimal:N \l__dataplot_y_fp ) ~
      node[anchor=north] { \exp_not:V \l__dataplot_xlabel_tl }; ~
  }
\l__dataplot_content_tl
\l__clear:N \l__dataplot_content_tl
}
}
Plot the  $x$  minor ticks if required
\cs_new:Nn \__dataplot_add_minor_x:
  {
    \legacy_if:nT { DTLxminortics }
    {
      Get tick length in terms of canvas co-ordinates
      \fp_set:Nn \l__dataplot_tick_length_fp
        {
          (
            (
              \dim_to_decimal_in_sp:n { \DTLminorticklength }
              + \l__dataplot_offset_y_fp
            ) / \l__dataplot_scale_y_fp
          ) / 65536
        }
      Iterate through minor ticks.
      \seq_map_inline:Nn \l__dataplot_x_minor_tic_seq
        {
          Reconstruct floating point variable.
          \tl_set:Nn \l__dataplot_x_fp { ##1 }
          \tl_set:Nx \l__dataplot_x_tl
            { \fp_to_decimal:N \l__dataplot_x_fp }
          Draw tick.
          \legacy_if:nTF { DTLxticsin }
            {

```

Tick above the x -axis. (Tick in)

```
\bool_if:NTF \l__dataplot_zero_y_axis_bool
{
  Enforce  $x$  axis to pass through  $y = 0$ .
  \fp_set_eq:NN \l__dataplot_y_fp
    \l__dataplot_tick_length_fp
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw
      ( \l__dataplot_x_tl , 0 )
      --
      ( \l__dataplot_x_tl ,
        \fp_to_decimal:N \l__dataplot_y_fp ); ~
  }
}
```

Don't enforce x axis to pass through $y = 0$ (but this will occur if $\min y = 0$).

```
\fp_set:Nn \l__dataplot_y_fp
{
  \l__dataplot_min_y_fp
  + \l__dataplot_tick_length_fp
}
\tl_put_right:Nx \l__dataplot_content_tl
{
  \exp_not:N \draw
    ( \l__dataplot_x_tl , \DTLminY )
    --
    ( \l__dataplot_x_tl ,
      \fp_to_decimal:N \l__dataplot_y_fp ); ~
}
}
```

Tick below the x -axis. (Tick out)

```
\bool_if:NTF \l__dataplot_zero_y_axis_bool
{
  \fp_set:Nn \l__dataplot_y_fp
    { - \l__dataplot_tick_length_fp }
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw
      ( \l__dataplot_x_tl , 0 )
      --
      ( \l__dataplot_x_tl ,
        \fp_to_decimal:N \l__dataplot_y_fp ); ~
  }
}
```

Don't enforce x axis to pass through $y = 0$ (but this will occur if $\min y = 0$).

```

\fp_set:Nn \l__dataplot_y_fp
{
  \l__dataplot_min_y_fp
  - \l__dataplot_tick_length_fp
}
\tl_put_right:Nx \l__dataplot_content_tl
{
  \exp_not:N \draw
  ( \l__dataplot_x_tl , \DTLminY )
  --
  ( \l__dataplot_x_tl ,
    \fp_to_decimal:N \l__dataplot_y_fp ); ~
}
}
}

```

Draw box ticks, if box setting is on.

```

\legacy_if:nT { DTLbox }
{

```

If $\min y$ isn't 0 and the box setting is on, need to draw tick on the bottom of the box according to the box setting.

```

\__dataplot_draw_box_ticks_lower_x:n
{
  \int_case:nnT { \l__dataplot_box_ticks_int }
  {
    { \c_one_int } % match
    {
      \legacy_if:nTF { DTLxticsin }
      {
        \fp_set:Nn \l__dataplot_y_fp
        {
          \l__dataplot_extended_min_y_fp
          + \l__dataplot_tick_length_fp
        }
      }
      {
        \fp_set:Nn \l__dataplot_y_fp
        {
          \l__dataplot_extended_min_y_fp
          - \l__dataplot_tick_length_fp
        }
      }
    }
  }
  { 2 } % in
  {
    \fp_set:Nn \l__dataplot_y_fp
    {
      \l__dataplot_extended_min_y_fp

```

```

        + \l__dataplot_tick_length_fp
      }
    }
  { 3 } % out
  {
    \fp_set:Nn \l__dataplot_y_fp
    {
      \l__dataplot_extended_min_y_fp
      - \l__dataplot_tick_length_fp
    }
  }
}
{
\tl_put_right:Nx \l__dataplot_content_tl
{
\exp_not:N \draw
( \l__dataplot_x_tl ,
\fp_to_decimal:N \l__dataplot_extended_min_y_fp )
--
( \l__dataplot_x_tl ,
\fp_to_decimal:N \l__dataplot_y_fp ); ~
}
}
}
}

```

Draw the ticks on the opposite side of the box.

```

\int_case:nnT { \l__dataplot_box_ticks_int }
{
{ \c_one_int } % match
{
\legacy_if:nTF { DTLxticsin }
{
\fp_set:Nn \l__dataplot_y_fp
{
\l__dataplot_extended_max_y_fp
- \l__dataplot_tick_length_fp
}
}
}
{
\fp_set:Nn \l__dataplot_y_fp
{
\l__dataplot_extended_max_y_fp
+ \l__dataplot_tick_length_fp
}
}
}
}
{ 2 } % in
{
\fp_set:Nn \l__dataplot_y_fp
{

```

```

        \l__dataplot_extended_max_y_fp
        - \l__dataplot_tick_length_fp
    }
}
{ 3 } % out
{
  \fp_set:Nn \l__dataplot_y_fp
  {
    \l__dataplot_extended_max_y_fp
    + \l__dataplot_tick_length_fp
  }
}
}
{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw
    ( \l__dataplot_x_tl ,
      \fp_to_decimal:N \l__dataplot_extended_max_y_fp )
    --
    ( \l__dataplot_x_tl ,
      \fp_to_decimal:N \l__dataplot_y_fp ); ~
  }
}
}
}
\l__dataplot_content_tl
\tl_clear:N \l__dataplot_content_tl
}
}
Plot y tics if required:
\cs_new:Nn \__dataplot_add_y_tics:
{
  \legacy_if:nT { DTLytics }
  {
    Get tick length in terms of canvas co-ordinates
    \fp_set:Nn \l__dataplot_tick_length_fp
    {
      (
        (
          \dim_to_decimal_in_sp:n { \DTLticklength }
          + \l__dataplot_offset_x_fp
        ) / \l__dataplot_scale_x_fp
      )
      / 65536
    }
    Get tick label offset in terms of canvas co-ordinates
    \fp_set:Nn \l__dataplot_tic_label_offset_fp

```

```

{
  (
    (
      \dim_to_decimal_in_sp:n { \DTLticklabeloffset }
      + \l__dataplot_offset_x_fp
    ) / \l__dataplot_scale_x_fp
  ) / 65536
}

```

Iterate through tick list. The default tick labels should have already been added in `__dataplot_calc_y_label_dim`:

```

\seq_map_indexed_inline:Nn \l__dataplot_y_tic_seq
{

```

Reconstruct the floating point variable:

```

\tl_set:Nn \l__dataplot_y_fp { ##2 }
\tl_set:Nn \l__dataplot_y_tl
{ \fp_use:N \l__dataplot_y_fp }

```

Fetch current tick label:

```

\tl_set:Nx \l__dataplot_tic_label_tl
{
  \seq_item:Nn \l__dataplot_ytic_labels_seq { ##1 }
}

```

Draw tick.

```

\legacy_if:nTF { DTLyticsin }
{

```

Tick to the right of the y -axis. (Tick in)

```

\bool_if:NTF \l__dataplot_zero_x_axis_bool
{

```

Enforce y axis to pass through $x = 0$.

```

\fp_set_eq:NN \l__dataplot_x_fp
\l__dataplot_tick_length_fp
\tl_put_right:Nx \l__dataplot_content_tl
{
  \exp_not:N \draw
  ( 0, \l__dataplot_y_tl )
  --
  ( \fp_to_decimal:N \l__dataplot_x_fp,
    \l__dataplot_y_tl ); ~
}
\fp_set:Nn \l__dataplot_x_fp
{ - \l__dataplot_tic_label_offset_fp }
}
{

```

Don't enforce y axis to pass through $x = 0$ (but this will occur if $\min x = 0$).

```

\fp_set:Nn \l__dataplot_x_fp
{

```

```

        \l_dataplot_min_x_fp
        + \l_dataplot_tick_length_fp
    }
\tl_put_right:Nx \l_dataplot_content_tl
{
    \exp_not:N \draw
    (
        \DTLminX , \l_dataplot_y_tl
    )
    --
    ( \fp_to_decimal:N \l_dataplot_x_fp,
      \l_dataplot_y_tl ); ~
}
\fp_set:Nn \l_dataplot_x_fp
{
    \l_dataplot_min_x_fp
    - \l_dataplot_tic_label_offset_fp
}
}
}

```

Draw the label unless 0 and omit zero label on.

```

\bool_lazy_and:nnF
{ \l_dataplot_omit_zero_y_label_bool }
{
    \fp_compare_p:nNn
    { \l_dataplot_y_fp } = { \c_zero_fp }
}
{
\tl_put_right:Nx \l_dataplot_content_tl
{
    \exp_not:N \draw
    ( \fp_to_decimal:N \l_dataplot_x_fp,
      \l_dataplot_y_tl ) ~
    node [ \exp_not:V \l_dataplot_y_tick_label_style_tl ]
    {
        \exp_not:N \DTLplotdisplayYticklabel
        { \exp_not:V \l_dataplot_tic_label_tl }
    }; ~
}
}
}
}

```

Tick to the left of the y -axis. (Tick out)

```

\bool_if:NTF \l_dataplot_zero_x_axis_bool
{
    \fp_set:Nn \l_dataplot_x_fp
    { - \l_dataplot_tick_length_fp }
\tl_put_right:Nx \l_dataplot_content_tl
{
    \exp_not:N \draw

```

```

        ( 0 , \l_dataplot_y_tl )
        --
        ( \fp_to_decimal:N \l_dataplot_x_fp,
          \l_dataplot_y_tl ) ; ~
    }
}
{

```

Don't enforce y axis to pass through $x = 0$ (but this will occur if $\min x = 0$).

```

\fp_set:Nn \l_dataplot_x_fp
{
  \l_dataplot_min_x_fp
  - \l_dataplot_tick_length_fp
}
\tl_put_right:Nx \l_dataplot_content_tl
{
  \exp_not:N \draw
  (
    \DTLminX , \l_dataplot_y_tl
  )
  --
  ( \fp_to_decimal:N \l_dataplot_x_fp,
    \l_dataplot_y_tl ) ; ~
}
}

```

Draw the label unless 0 and omit zero label on.

```

\bool_lazy_and:nnF
{ \l_dataplot_omit_zero_y_label_bool }
{
  \fp_compare_p:nNn
  { \l_dataplot_y_fp } = { \c_zero_fp }
}
{
  \fp_sub:Nn \l_dataplot_x_fp
  { \l_dataplot_tic_label_offset_fp }
  \tl_put_right:Nx \l_dataplot_content_tl
  {
    \exp_not:N \draw
    ( \fp_to_decimal:N \l_dataplot_x_fp,
      \l_dataplot_y_tl ) ~
    node [ \exp_not:N \l_dataplot_y_tick_label_style_tl ]
    {
      \exp_not:N \DTLplotdisplayYticklabel
      { \exp_not:N \l_dataplot_tic_label_tl }
    } ; ~
  }
}
}
}

```

Draw box ticks, if box setting is on.

```

\legacy_if:nT { DTLbox }
{

```

If min x isn't 0 and the box setting is on, need to draw tick on the left of the box according to the box setting.

```

\__dataplot_draw_box_ticks_lower_y:n
{
  \int_case:nnT { \l__dataplot_box_ticks_int }
  {
    { \c_one_int } % match
    {
      \legacy_if:nTF { DTlyticsin }
      {
        \fp_set:Nn \l__dataplot_x_fp
        {
          \l__dataplot_extended_min_x_fp
          + \l__dataplot_tick_length_fp
        }
      }
      {
        \fp_set:Nn \l__dataplot_x_fp
        {
          \l__dataplot_extended_min_x_fp
          - \l__dataplot_tick_length_fp
        }
      }
    }
  }
  { 2 } % in
  {
    \fp_set:Nn \l__dataplot_x_fp
    {
      \l__dataplot_extended_min_x_fp
      + \l__dataplot_tick_length_fp
    }
  }
  { 3 } % out
  {
    \fp_set:Nn \l__dataplot_x_fp
    {
      \l__dataplot_extended_min_x_fp
      - \l__dataplot_tick_length_fp
    }
  }
}
{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw
    (
      \fp_to_decimal:N \l__dataplot_extended_min_x_fp ,

```



```

    {
      \exp_not:N \draw
      ( \fp_use:N \l__dataplot_x_fp,
        \fp_use:N \l__dataplot_y_fp ) ~
      node[rotate=90,anchor=south]
      { \exp_not:V \l__dataplot_ylabel_tl }; ~
    }
    \l__dataplot_content_tl
    \tl_clear:N \l__dataplot_content_tl
  }
}
}
Plot the y minor ticks if required
\cs_new:Nn \__dataplot_add_minor_y:
{
  \legacy_if:nT { DTLyminortics }
  {
    Get tick length in terms of canvas co-ordinates
    \fp_set:Nn \l__dataplot_tick_length_fp
    {
      (
        (
          \dim_to_decimal_in_sp:n { \DTLminorticklength }
          + \l__dataplot_offset_x_fp
        ) / \l__dataplot_scale_x_fp
      ) / 65536
    }
  }
}
Iterate through minor ticks.
\seq_map_inline:Nn \l__dataplot_y_minor_tic_seq
{
  \tl_set:Nn \l__dataplot_y_fp { ##1 }
  \tl_set:Nx \l__dataplot_y_tl
  { \fp_to_decimal:N \l__dataplot_y_fp }
  \legacy_if:nTF { DTLyticsin }
  {
    Tick right of the y-axis. (Tick in)
    \bool_if:NTF \l__dataplot_zero_x_axis_bool
    {
      Enforce y axis to pass through  $x = 0$ .
      \fp_set_eq:NN \l__dataplot_x_fp
      \l__dataplot_tick_length_fp
      \tl_put_right:Nx \l__dataplot_content_tl
      {
        \exp_not:N \draw
        ( 0 , \l__dataplot_y_tl )
        --
        ( \fp_to_decimal:N \l__dataplot_x_fp,
          \l__dataplot_y_tl ); ~
      }
    }
  }
}

```

```

    }
  }
  {
Don't enforce  $y$  axis to pass through  $x = 0$  (but this will occur if  $\min x = 0$ ).
    \fp_set:Nn \l__dataplot_x_fp
      { \l__dataplot_min_x_fp + \l__dataplot_tick_length_fp }
    \tl_put_right:Nx \l__dataplot_content_tl
      {
        \exp_not:N \draw
          ( \DTLminX, \l__dataplot_y_tl )
          --
          ( \fp_to_decimal:N \l__dataplot_x_fp,
            \l__dataplot_y_tl ); ~
      }
    }
  }
}
{
Tick left of the  $y$ -axis. (Tick out)
    \bool_if:NTF \l__dataplot_zero_x_axis_bool
      {
        \fp_set:Nn \l__dataplot_x_fp
          { - \l__dataplot_tick_length_fp }
        \tl_put_right:Nx \l__dataplot_content_tl
          {
            \exp_not:N \draw
              ( 0 , \l__dataplot_y_tl )
              --
              ( \fp_to_decimal:N \l__dataplot_x_fp ,
                \l__dataplot_y_tl ); ~
          }
        }
      }
    }
}
Don't enforce  $y$  axis to pass through  $x = 0$  (but this will occur if  $\min x = 0$ ).
    \fp_set:Nn \l__dataplot_x_fp
      { \l__dataplot_min_x_fp - \l__dataplot_tick_length_fp }
    \tl_put_right:Nx \l__dataplot_content_tl
      {
        \exp_not:N \draw
          ( \DTLminX, \l__dataplot_y_tl )
          --
          ( \fp_to_decimal:N \l__dataplot_x_fp ,
            \l__dataplot_y_tl ); ~
      }
    }
  }
}
Draw box ticks, if box setting is on.
    \legacy_if:nT { DTLbox }
      {

```

If min x isn't 0 and the box setting is on, need to draw tick on the left of the box according to the box setting.

```

\__dataplot_draw_box_ticks_lower_y:n
{
  \int_case:nnT { \l__dataplot_box_ticks_int }
  {
    { \c_one_int } % match
    {
      \legacy_if:nTF { DTlyticsin }
      {
        \fp_set:Nn \l__dataplot_x_fp
        {
          \l__dataplot_extended_min_x_fp
          + \l__dataplot_tick_length_fp
        }
      }
      {
        \fp_set:Nn \l__dataplot_x_fp
        {
          \l__dataplot_extended_min_x_fp
          - \l__dataplot_tick_length_fp
        }
      }
    }
  }
  { 2 } % in
  {
    \fp_set:Nn \l__dataplot_x_fp
    {
      \l__dataplot_extended_min_x_fp
      + \l__dataplot_tick_length_fp
    }
  }
  { 3 } % out
  {
    \fp_set:Nn \l__dataplot_x_fp
    {
      \l__dataplot_extended_min_x_fp
      - \l__dataplot_tick_length_fp
    }
  }
}
{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw
    (
      \fp_to_decimal:N \l__dataplot_extended_min_x_fp ,
      \l__dataplot_y_tl
    )
  }
}

```

```

--
      ( \fp_to_decimal:N \l__dataplot_x_fp,
        \l__dataplot_y_tl ); ~
    }
  }
}
Draw opposite tick.
\int_case:nnT { \l__dataplot_box_ticks_int }
{
  { \c_one_int } % match
  {
    \legacy_if:nTF { DTLyticsin }
    {
      \fp_set:Nn \l__dataplot_x_fp
      {
        \l__dataplot_extended_max_x_fp
        - \l__dataplot_tick_length_fp
      }
    }
    {
      \fp_set:Nn \l__dataplot_x_fp
      {
        \l__dataplot_extended_max_x_fp
        + \l__dataplot_tick_length_fp
      }
    }
  }
}
{ 2 } % in
{
  \fp_set:Nn \l__dataplot_x_fp
  {
    \l__dataplot_extended_max_x_fp
    - \l__dataplot_tick_length_fp
  }
}
{ 3 } % out
{
  \fp_set:Nn \l__dataplot_x_fp
  {
    \l__dataplot_extended_max_x_fp
    + \l__dataplot_tick_length_fp
  }
}
}
{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw
    (

```

```

        \fp_to_decimal:N \l__dataplot_extended_max_x_fp ,
        \l__dataplot_y_tl
    )
    --
    ( \fp_to_decimal:N \l__dataplot_x_fp,
      \l__dataplot_y_tl); ~
  }
}
}
\l__dataplot_content_tl
\tl_clear:N \l__dataplot_content_tl
}
}

```

Used to count the total number of plot streams. Primarily provided for use as a return value for the `plot` action, but may also be used in the legend hook to access the stream index.

```
\int_new:N \l__dataplot_stream_index_int
```

Plot marks and draw lines for each database.

```
\cs_new:Nn \__dataplot_plot_data:
```

```
{
```

Initialise:

```

\tl_clear:N \l__dataplot_current_mark_tl
\tl_clear:N \l__dataplot_current_mark_color_tl
\tl_clear:N \l__dataplot_current_line_tl
\tl_clear:N \l__dataplot_current_line_color_tl
\int_zero:N \l__dataplot_stream_index_int

```

Iterate through each database

```

\seq_map_indexed_inline:Nn \l__dataplot_dbnames_seq
{

```

Reset styles at the start of each database unless corresponding group by setting on:

```

\bool_if:NTF \l__dataplot_mark_group_bool
{
  \__dataplot_get_style:NNN
  \l__dataplot_mark_seq \DTLplotmarks
  \l__dataplot_current_mark_tl
}
{
  \bool_if:NT \l__dataplot_no_group_mark_reset_bool
  {
    \__dataplot_set_style_from_clist:NN
    \l__dataplot_mark_seq \DTLplotmarks
  }
  \tl_clear:N \l__dataplot_current_mark_tl
}
\bool_if:NTF \l__dataplot_mark_color_group_bool
{

```

```

    \__dataplot_get_style:NNN
      \l__dataplot_mark_colors_seq \DTLplotmarkcolors
      \l__dataplot_current_mark_color_tl
    }
  {
    \bool_if:NT \l__dataplot_no_group_mark_color_reset_bool
      {
        \__dataplot_set_style_from_clist:NN
          \l__dataplot_mark_colors_seq \DTLplotmarkcolors
        }
      \tl_clear:N \l__dataplot_current_mark_color_tl
    }
  \bool_if:NTF \l__dataplot_line_group_bool
  {
    \__dataplot_get_style:NNN
      \l__dataplot_line_seq \DTLplotlines
      \l__dataplot_current_line_tl
    }
  {
    \bool_if:NT \l__dataplot_no_group_line_reset_bool
      {
        \__dataplot_set_style_from_clist:NN
          \l__dataplot_line_seq \DTLplotlines
        }
      \tl_clear:N \l__dataplot_current_line_tl
    }
  \bool_if:NTF \l__dataplot_line_color_group_bool
  {
    \__dataplot_get_style:NNN
      \l__dataplot_line_colors_seq \DTLplotlinecolors
      \l__dataplot_current_line_color_tl
    }
  {
    \bool_if:NT \l__dataplot_no_group_line_color_reset_bool
      {
        \__dataplot_set_style_from_clist:NN
          \l__dataplot_line_colors_seq \DTLplotlinecolors
        }
      \tl_clear:N \l__dataplot_current_line_color_tl
    }
  }
  \DTLsetup{ default-name = { ##2 } }
  \__dataplot_filtered_map:nnn
  {

```

Pre-map code.

```
\int_incr:N \l__dataplot_stream_index_int
```

Current mark setting.

```
\legacy_if:nT { DTLshowmarkers }
{
```

Get the current plot mark if applicable.

```
\bool_if:NF \l__dataplot_mark_group_bool
{
  \__dataplot_get_style:NNN
  \l__dataplot_mark_seq \DTLplotmarks
  \l__dataplot_current_mark_tl
}
```

Get the current plot mark colour.

```
\bool_if:NF \l__dataplot_mark_color_group_bool
{
  \__dataplot_get_style:NNN
  \l__dataplot_mark_colors_seq \DTLplotmarkcolors
  \l__dataplot_current_mark_color_tl
}
```

Save the current marker and mark colour.

```
\tl_if_empty:NTF \l__dataplot_current_mark_tl
{
  \tl_clear:N \l__dataplot_current_mark_style_tl
}
{
  \tl_set_eq:NN
  \l__dataplot_current_mark_style_tl
  \l__dataplot_current_mark_tl
  \tl_if_empty:NF \l__dataplot_current_mark_color_tl
  {
    \tl_put_left:Nx \l__dataplot_current_mark_style_tl
    {
      \exp_not:N \pgfsetstrokecolor
      { \l__dataplot_current_mark_color_tl }
    }
  }
}
```

Current line setting.

```
\legacy_if:nT { DTLshowlines }
{
```

Get the current plot line.

```
\bool_if:NF \l__dataplot_line_group_bool
{
  \__dataplot_get_style:NNN
  \l__dataplot_line_seq \DTLplotlines
  \l__dataplot_current_line_tl
}
```

Get the current plot line colour.

```
\bool_if:NF \l__dataplot_line_color_group_bool
{
```

```

    \__dataplot_get_style:NNN
      \l__dataplot_line_colors_seq \DTLplotlinecolors
      \l__dataplot_current_line_color_tl
    }

```

Save the current marker and mark colour.

```

\__tl_if_empty:NTF \l__dataplot_current_line_tl
{
  \__tl_clear:N \l__dataplot_current_line_style_tl
}
{
  \__tl_set_eq:NN
    \l__dataplot_current_line_style_tl
    \l__dataplot_current_line_tl
  \__tl_if_empty:NF \l__dataplot_current_line_color_tl
  {
    \__tl_put_left:Nx \l__dataplot_current_line_style_tl
    {
      \exp_not:N \pgfsetstrokecolor
      { \l__dataplot_current_line_color_tl }
    }
  }
}
}

```

Append this plot setting to the legend if applicable.

```

\__int_if_zero:NF \l__dataplot_legend_setting_int
{

```

Get legend label.

```

  \__seq_pop_left:NNF
    \l__dataplot_legend_labels_seq
    \l__datatool_tmpa_tl
  {
    \__tl_clear:N \l__datatool_tmpa_tl
    \exp_args:NNx
      \dataplot_get_default_legend:Nnnnn
      \l__datatool_tmpa_tl
      { ##1 } { ##2 }
      { \l__dataplot_x_key_tl }
      { \l__dataplot_y_key_tl }
  }
}

```

Only add to the legend if the label isn't empty.

```

\__tl_if_empty:NF \l__datatool_tmpa_tl
{
  \exp_args:Noox
    \DTLaddtoplotlegend
    { \l__dataplot_current_mark_style_tl }
    { \l__dataplot_current_line_style_tl }
    { \l__datatool_tmpa_tl }
}

```

```

    }
}

```

Store stream in `\l__dataplot_stream_tl`:

```

\tl_set:Nn \l__dataplot_stream_tl
{ \pgfplotstreamstart }

```

Only plot points that lie inside bounds.

```

}
{
\datatool_set_fp:Nn \l__dataplot_x_fp
{
\l__dataplot_x_tl
}
\datatool_set_fp:Nn \l__dataplot_y_fp
{
\l__dataplot_y_tl
}
\tl_set:Nx \l__dataplot_decimal_x_tl
{ \fp_to_tl:N \l__dataplot_x_fp }
\tl_set:Nx \l__dataplot_decimal_y_tl
{ \fp_to_tl:N \l__dataplot_y_fp }
\_dataplot_x_y_bounded:nnnnnT
{ \l__dataplot_x_fp }
{ \l__dataplot_min_x_fp } { \l__dataplot_max_x_fp }
{ \l__dataplot_y_fp }
{ \l__dataplot_min_y_fp } { \l__dataplot_max_y_fp }
}

```

Apply transformation to co-ordinates

```

\fp_set:Nn \l__dataplot_x_fp
{
\l__dataplot_x_fp * \l__dataplot_scale_x_fp
+ \l__dataplot_offset_x_fp
}
\tl_set:Nx \l__dataplot_x_tl
{ \fp_to_tl:N \l__dataplot_x_fp }
\fp_set:Nn \l__dataplot_y_fp
{
\l__dataplot_y_fp * \l__dataplot_scale_y_fp
+ \l__dataplot_offset_y_fp
}
\tl_set:Nx \l__dataplot_y_tl
{ \fp_to_tl:N \l__dataplot_y_fp }
\tl_put_right:Nx \l__dataplot_stream_tl
{
\exp_not:N \pgfplotstreampoint
{
\exp_not:N \pgfpointxy
{ \l__dataplot_x_tl }
{ \l__dataplot_y_tl }
}
}

```

```

    }
  }
}
{

```

Add end of plot stream.

```

\l_dataplot_stream_tl
{ \pgfplotstreamend }

```

Draw path if applicable.

```

\l_dataplot_current_line_style_tl
{
  \begin{scope}
    \l_dataplot_current_line_style_tl
    \pgfplotshandlerlineto
    \l_dataplot_stream_tl
    \pgfusepath{stroke}
  \end{scope}
}
\l_dataplot_current_mark_style_tl
{
  \begin{scope}
    \exp_args:NV \pgfplotshandlermark
    \l_dataplot_current_mark_style_tl
    \l_dataplot_stream_tl
    \pgfusepath{stroke}
  \end{scope}
}
}
}

```

Plot legend if required.

```

\l_dataplot_legend_setting_int
{

```

Prior to v3.0, `\DTLaddtoplotlegend` appended to `\dtl@legend` so allow for backward-compatibility (this may be removed in future):

```

\bool_lazy_and:nnT
{ \l_dataplot_legend_tl }
{ \dtl@legend }
{
  \l_dataplot_legend_tl \dtl@legend
}
}
\l_dataplot_legend_tl
{
  \__dataplot_do_legend:
}
}

```

Do the legend:

```

\cs_new:Nn \__dataplot_do_legend:
{
  \tl_clear:N \l__dataplot_content_tl
  \dataplot_legend_add_begin:
  \dataplot_legend_add_end:
  \int_case:nnTF { \l__dataplot_legend_setting_int }
  {
    { 1 } % north
    {
      \fp_set:Nn \l__dataplot_x_fp
      {
        \l__dataplot_scale_x_fp *
        ( \l__dataplot_min_x_fp + 0.5 * \l__dataplot_x_extent_fp )
        + \l__dataplot_offset_x_fp
      }
      \fp_set:Nn \l__dataplot_y_fp
      {
        \l__dataplot_max_y_fp * \l__dataplot_scale_y_fp
        + \l__dataplot_offset_y_fp
        - \DTLlegendyoffset
      }
      If the y offset is negative anchor at the south otherwise anchor north.
      \fp_compare:nNnTF
      { \DTLlegendyoffset } < { \c_zero_fp }
      {
        \tl_put_right:Nn \l__dataplot_content_tl
        {
          node [ anchor = south ]
        }
      }
      {
        \tl_put_right:Nn \l__dataplot_content_tl
        {
          node [ anchor = north ]
        }
      }
    }
  }
  { 2 } % northeast
  {
    \fp_set:Nn \l__dataplot_x_fp
    {
      \l__dataplot_max_x_fp * \l__dataplot_scale_x_fp
      + \l__dataplot_offset_x_fp
      - \DTLlegendxoffset
    }
    \fp_set:Nn \l__dataplot_y_fp
    {
      \l__dataplot_max_y_fp * \l__dataplot_scale_y_fp
      + \l__dataplot_offset_y_fp
    }
  }
}

```

```

        - \DTLlegendyoffset
    }
    \tl_put_right:Nn \l__dataplot_content_tl
    {
        node [ anchor =
    }
    If the y offset is negative anchor at the south otherwise anchor north.
    \fp_compare:nNnTF
    { \DTLlegendyoffset } < { \c_zero_fp }
    {
        \tl_put_right:Nn \l__dataplot_content_tl { south ~ }
    }
    {
        \tl_put_right:Nn \l__dataplot_content_tl { north ~ }
    }
    If the x offset is negative anchor at the west otherwise anchor east.
    \fp_compare:nNnTF
    { \DTLlegendxoffset } < { \c_zero_fp }
    {
        \tl_put_right:Nn \l__dataplot_content_tl { west }
    }
    {
        \tl_put_right:Nn \l__dataplot_content_tl { east }
    }
    \tl_put_right:Nn \l__dataplot_content_tl
    {
        ]
    }
}
{ 3 } % east
{
    \fp_set:Nn \l__dataplot_x_fp
    {
        \l__dataplot_max_x_fp * \l__dataplot_scale_x_fp
        + \l__dataplot_offset_x_fp
        - \DTLlegendxoffset
    }
    \fp_set:Nn \l__dataplot_y_fp
    {
        \l__dataplot_offset_y_fp
        + \l__dataplot_scale_y_fp
        * ( \l__dataplot_min_y_fp + 0.5 * \l__dataplot_y_extent_fp )
    }
    If the x offset is negative anchor at the west otherwise anchor east.
    \fp_compare:nNnTF
    { \DTLlegendxoffset } < { \c_zero_fp }
    {
        \tl_put_right:Nn \l__dataplot_content_tl

```

```

    {
      node [ anchor = west ]
    }
  }
  {
    \tl_put_right:Nn \l__dataplot_content_tl
    {
      node [ anchor = east ]
    }
  }
}
{ 4 } % southeast
{
  \fp_set:Nn \l__dataplot_x_fp
  {
    \l__dataplot_max_x_fp * \l__dataplot_scale_x_fp
    + \l__dataplot_offset_x_fp
    - \DTLlegendxoffset
  }
  \fp_set:Nn \l__dataplot_y_fp
  {
    \l__dataplot_min_y_fp * \l__dataplot_scale_y_fp
    + \l__dataplot_offset_y_fp
    + \DTLlegendyoffset
  }
  \tl_put_right:Nn \l__dataplot_content_tl
  {
    node [ anchor =
  }
}
If the y offset is negative anchor at the north otherwise anchor south.
\fp_compare:nNnTF
{ \DTLlegendyoffset } < { \c_zero_fp }
{
  \tl_put_right:Nn \l__dataplot_content_tl { north ~ }
}
{
  \tl_put_right:Nn \l__dataplot_content_tl { south ~ }
}
}
If the x offset is negative anchor at the west otherwise anchor east.
\fp_compare:nNnTF
{ \DTLlegendxoffset } < { \c_zero_fp }
{
  \tl_put_right:Nn \l__dataplot_content_tl { west }
}
{
  \tl_put_right:Nn \l__dataplot_content_tl { east }
}
\tl_put_right:Nn \l__dataplot_content_tl
{

```

```

    ]
  }
}
{ 5 } % south
{
  \fp_set:Nn \l__dataplot_x_fp
  {
    \l__dataplot_scale_x_fp
    * ( \l__dataplot_min_x_fp + 0.5 * \l__dataplot_x_extent_fp )
    + \l__dataplot_offset_x_fp
  }
  \fp_set:Nn \l__dataplot_y_fp
  {
    \l__dataplot_min_y_fp * \l__dataplot_scale_y_fp
    + \l__dataplot_offset_y_fp
    + \DTLlegendyoffset
  }
}

```

If the y offset is negative anchor at the north otherwise anchor south.

```

  \fp_compare:nNnTF
  { \DTLlegendyoffset } < { \c_zero_fp }
  {
    \tl_put_right:Nn \l__dataplot_content_tl
    {
      node [ anchor = north ]
    }
  }
  {
    \tl_put_right:Nn \l__dataplot_content_tl
    {
      node [ anchor = south ]
    }
  }
}
{ 6 } % southwest
{
  \fp_set:Nn \l__dataplot_x_fp
  {
    \l__dataplot_min_x_fp * \l__dataplot_scale_x_fp
    + \l__dataplot_offset_x_fp
    + \DTLlegendxoffset
  }
  \fp_set:Nn \l__dataplot_y_fp
  {
    \l__dataplot_min_y_fp * \l__dataplot_scale_y_fp
    + \l__dataplot_offset_y_fp
    + \DTLlegendyoffset
  }
  \tl_put_right:Nn \l__dataplot_content_tl
  {

```

```

        node [ anchor =
    }
If the y offset is negative anchor at the north otherwise anchor south.
\fp_compare:nNnTF
{ \DTLlegendyoffset } < { \c_zero_fp }
{
  \tl_put_right:Nn \l__dataplot_content_tl { north ~ }
}
{
  \tl_put_right:Nn \l__dataplot_content_tl { south ~ }
}
If the x offset is negative anchor at the east otherwise anchor west.
\fp_compare:nNnTF
{ \DTLlegendxoffset } < { \c_zero_fp }
{
  \tl_put_right:Nn \l__dataplot_content_tl { east }
}
{
  \tl_put_right:Nn \l__dataplot_content_tl { west }
}
\tl_put_right:Nn \l__dataplot_content_tl
{
  ]
}
}
{ 7 } % west
{
  \fp_set:Nn \l__dataplot_x_fp
  {
    \l__dataplot_offset_x_fp
    + \l__dataplot_min_x_fp * \l__dataplot_scale_x_fp
    + \DTLlegendxoffset
  }
  \fp_set:Nn \l__dataplot_y_fp
  {
    \l__dataplot_scale_y_fp
    * ( \l__dataplot_min_y_fp + 0.5 * \l__dataplot_y_extent_fp )
    + \l__dataplot_offset_y_fp
  }
}
If the x offset is negative anchor at the east otherwise anchor west.
\fp_compare:nNnTF
{ \DTLlegendxoffset } < { \c_zero_fp }
{
  \tl_put_right:Nn \l__dataplot_content_tl
  {
    node [ anchor = east ]
  }
}
}

```

```

    {
      \tl_put_right:Nn \l__dataplot_content_tl
      {
        node [ anchor = west ]
      }
    }
  }
{ 8 } % northwest
{
  \fp_set:Nn \l__dataplot_x_fp
  {
    \l__dataplot_offset_x_fp
    + \l__dataplot_min_x_fp * \l__dataplot_scale_x_fp
    + \DTLlegendxoffset
  }
  \fp_set:Nn \l__dataplot_y_fp
  {
    \l__dataplot_offset_y_fp
    + \l__dataplot_max_y_fp * \l__dataplot_scale_y_fp
    - \DTLlegendyoffset
  }
  \tl_put_right:Nn \l__dataplot_content_tl
  {
    node [ anchor =
  }
}
If the y offset is negative anchor at the south otherwise anchor north.
\fp_compare:nNnTF
{ \DTLlegendyoffset } < { \c_zero_fp }
{
  \tl_put_right:Nn \l__dataplot_content_tl { south ~ }
}
{
  \tl_put_right:Nn \l__dataplot_content_tl { north ~ }
}
}
If the x offset is negative anchor at the east otherwise anchor west.
\fp_compare:nNnTF
{ \DTLlegendxoffset } < { \c_zero_fp }
{
  \tl_put_right:Nn \l__dataplot_content_tl { east }
}
{
  \tl_put_right:Nn \l__dataplot_content_tl { west }
}
\tl_put_right:Nn \l__dataplot_content_tl
{
  ]
}
}
}
}

```

```

{
  \tl_put_left:Nx \l__dataplot_content_tl
  {
    \exp_not:N \draw
      ( \fp_to_decimal:N \l__dataplot_x_fp,
        \fp_to_decimal:N \l__dataplot_y_fp ) ~
  }
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    ~ {
      \exp_not:N \DTLformatlegend
      {
        \exp_not:V \l_dataplot_legend_tl
      }
    }; ~
  }
}
{
  \tl_put_right:Nx \l__dataplot_content_tl
  {
    \exp_not:N \DTLcustomlegend
    {
      \exp_not:V \l_dataplot_legend_tl
    }
  }
}
\l__dataplot_content_tl
\tl_clear:N \l__dataplot_content_tl
}

```

Syntax: *<seq var>* *<clist var>* *<tl var>*
 Get style setting from sequence, and reset *<seq var>* from *<clist var>* if empty:

```

\cs_new:Nn \__dataplot_get_style:NNN
{
  \seq_if_empty:NT #1
  {
    \__dataplot_set_style_from_clist:NN #1 #2
  }
  \seq_pop_left:NN #1 #3

```

Check for `\relax` to indicate no mark for the current set.

```

\tl_if_eq:NnT #3 { \relax }
{
  \tl_clear:N #3
}
}

```

\DTLplot

`\DTLplot[<condition>]{<db list>}{<settings>}`

Creates a plot (inside a tikzpicture environment) of all the data given in the databases listed in *(db list)*.

```
\NewDocumentCommand \DTLplot { o m m }
{
  \group_begin:
```

Initialise command to encapsulate plot code. Any errors should change this to do nothing.

```
\cs_set_eq:NN \__dataplot_do_plot:n \use:n
```

Parse options:

```
\keys_set:nn { datatool / plot } { #3 }
```

Check optional argument:

```
\IfValueT { #1 }
{
```

The optional argument overrides the condition setting:

```
\cs_set:Nn \__dataplot_filter:T
{
  \ifthenelse { #1 } { ##1 } { }
}
}
```

Store the list of database names in a sequence variable:

```
\exp_args:NNx \seq_set_from_clist:Nn
\l__dataplot_dbnames_seq { #2 }
```

Check that all the databases exist.

```
\seq_map_inline:Nn \l__dataplot_dbnames_seq
{
  \DTLifdbexists { ##1 } { }
  {
    \PackageError { dataplot }
    {
      Database ~ `##1' ~ doesn't ~ exist
    }
    {
      Check ~ you ~ have ~ spelt ~ the ~ database ~ name ~
      correctly ~ in ~ the ~ argument ~ of ~
      \token_to_str:N \DTLplot { \exp_not:n { #2 } } { ... }
    }
  }
  \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n
}
}
\__dataplot_do_plot:n
{
```

Convert the minor gap dimension to user co-ordinates:

```
\fp_set:Nn \l__dataplot_min_minor_gap_fp
{ \DTLminminortickgap / 65536 }
```

Save the plot marks comma-separated list as a sequence:

```
\__dataplot_set_style_from_clist:NN  
\l__dataplot_mark_seq \DTLplotmarks
```

Save the plot lines comma-separated list as a sequence:

```
\__dataplot_set_style_from_clist:NN  
\l__dataplot_line_seq \DTLplotlines
```

Save the plot mark colours comma-separated list as a sequence:

```
\__dataplot_set_style_from_clist:NN  
\l__dataplot_mark_colors_seq \DTLplotmarkcolors
```

Save the plot line colours comma-separated list as a sequence:

```
\__dataplot_set_style_from_clist:NN  
\l__dataplot_line_colors_seq \DTLplotlinecolors
```

Clear the legend token list:

```
\tl_clear:N \l__dataplot_legend_tl
```

Check the user has supplied at least one x variable:

```
\clist_if_empty:NT \l__dataplot_x_keys_clist  
{  
  \PackageError { dataplot }  
  {Missing ~ x ~ setting ~ for ~ \token_to_str:N \DTLplot}  
  {}  
  \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n  
}
```

Check the user has supplied at least one y variable:

```
\seq_if_empty:NTF \l__dataplot_y_keys_seq  
{  
  \PackageError { dataplot }  
  {Missing ~ y ~ setting ~ for ~ \token_to_str:N \DTLplot}  
  {}  
  \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n  
}  
{
```

Check that there aren't more x than y variables:

```
\int_compare:nNnT  
  { \clist_count:N \l__dataplot_x_keys_clist }  
  >  
  { \seq_count:N \l__dataplot_y_keys_seq }  
{  
  \PackageError { dataplot }  
  { Too ~ many ~ x ~ keys ~ listed ~ in ~ \token_to_str:N \DTLplot }  
  {  
    The ~ number ~ of ~ x ~ keys ~ must ~ be ~ less ~ than ~  
    or ~ equal ~ to ~ the ~ number ~ of ~ y ~ keys  
  }  
  \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n  
}
```

```

    }
    \__dataplot_init_and_do_plot:
  }
\group_end:
}

```

Initialisation code:

```

\cs_new:Nn \__dataplot_init_and_do_plot:
{

```

If user didn't specified bounds, compute the maximum and minimum x and y values over all the databases listed.

```

  \__dataplot_do_plot:n
  {
    \__dataplot_update_bounds:
  }

```

Do the plot code:

```

  \__dataplot_do_plot:n
  {

```

Calculate the extended bounds for the axes and box:

```

  \fp_set:Nn \l__dataplot_extended_min_x_fp
  {
    \l__dataplot_min_x_fp
    - \l__dataplot_extend_min_x_axis_fp
  }
  \fp_set:Nn \l__dataplot_extended_min_y_fp
  {
    \l__dataplot_min_y_fp
    - \l__dataplot_extend_min_y_axis_fp
  }
  \fp_set:Nn \l__dataplot_extended_max_x_fp
  {
    \l__dataplot_max_x_fp
    + \l__dataplot_extend_max_x_axis_fp
  }
  \fp_set:Nn \l__dataplot_extended_max_y_fp
  {
    \l__dataplot_max_y_fp
    + \l__dataplot_extend_max_y_axis_fp
  }

```

Determine whether to set the zero axis booleans:

```

  \bool_set_false:N \l__dataplot_zero_x_axis_bool
  \bool_set_false:N \l__dataplot_zero_y_axis_bool
  \bool_if:NF \l__dataplot_side_axes_bool
  {
    \fp_compare:nT
    {
      \l__dataplot_extended_min_x_fp

```

```

        < \c_zero_fp
        < \l_dataplot_extended_max_x_fp
    }
}

```

X axis includes 0. That is, the y axis should intersect at x=0:

```

    \bool_set_true:N \l_dataplot_zero_x_axis_bool
}
\fp_compare:nT
{
    \l_dataplot_extended_min_y_fp
    < \c_zero_fp
    < \l_dataplot_extended_max_y_fp
}
}

```

Y axis includes 0. That is, the x axis should intersect at y=0:

```

    \bool_set_true:N \l_dataplot_zero_y_axis_bool
}
}

```

Check the omit zero label setting:

```

\int_case:nnF { \l_dataplot_omit_zero_label_action_int }
{
    { 2 } % omit both
    {
        \bool_set_true:N \l_dataplot_omit_zero_x_label_bool
        \bool_set_true:N \l_dataplot_omit_zero_y_label_bool
    }
    { 3 } % omit x
    {
        \bool_set_true:N \l_dataplot_omit_zero_x_label_bool
        \bool_set_false:N \l_dataplot_omit_zero_y_label_bool
    }
    { 4 } % omit y
    {
        \bool_set_false:N \l_dataplot_omit_zero_x_label_bool
        \bool_set_true:N \l_dataplot_omit_zero_y_label_bool
    }
    { 5 } % don't omit
    {
        \bool_set_false:N \l_dataplot_omit_zero_x_label_bool
        \bool_set_false:N \l_dataplot_omit_zero_y_label_bool
    }
}
}% auto
\bool_set_eq:NN
    \l_dataplot_omit_zero_x_label_bool
    \l_dataplot_zero_x_axis_bool
\bool_set_eq:NN
    \l_dataplot_omit_zero_y_label_bool

```

```

    \l__dataplot_zero_y_axis_bool
  }

```

Determine whether or not to draw ticks along the minimum box edges.

```

\bool_lazy_all:nTF
{
  { \legacy_if_p:n { DTLbox } }
  { \bool_not_p:n { \l__dataplot_side_axes_bool } }
  { ! \fp_compare_p:nNn { \l__dataplot_extended_min_y_fp } = { \c_zero_fp } }
}
{
  \cs_set_eq:NN \__dataplot_draw_box_ticks_lower_x:n \use:n
}
{
  \cs_set_eq:NN \__dataplot_draw_box_ticks_lower_x:n \use_none:n
}
\bool_lazy_all:nTF
{
  { \legacy_if_p:n { DTLbox } }
  { \bool_not_p:n { \l__dataplot_side_axes_bool } }
  { ! \fp_compare_p:nNn { \l__dataplot_extended_min_x_fp } = { \c_zero_fp } }
}
{
  \cs_set_eq:NN \__dataplot_draw_box_ticks_lower_y:n \use:n
}
{
  \cs_set_eq:NN \__dataplot_draw_box_ticks_lower_y:n \use_none:n
}

```

Determine scaling factors and offsets.

```

  \dataplot_calc_transform:

```

If x tics specified, construct a list of x tic points if not already specified.

```

  \__dataplot_calc_x_tics:

```

If y tics specified, construct a list of y tic points if not already specified.

```

  \__dataplot_calc_y_tics:

```

Do the picture.

```

  \__dataplot_do_plot:
}
}

```

Action 'plot':

```

\cs_new:cn { __datatool_action_plot : }
{
  \group_begin:

```

This will be the primary return value.

```

  \int_zero:N \l__dataplot_stream_index_int
  \tl_clear:N \l__dataplot_content_tl

```

Initialise command to encapsulate plot code. Any errors should change this to do nothing.

```
\cs_set_eq:NN \__dataplot_do_plot:n \use:n
```

Parse options if provided.

```
\clist_if_empty:NF \l__datatool_action_options_clist
{
  \keys_set:nV { datatool / plot }
  \l__datatool_action_options_clist
}

```

The 'name' action setting may be a comma-separated list of database names. These will already be available in a sequence, so just copy it.

```
\seq_set_eq:NN
  \l__dataplot_dbnames_seq \l__datatool_action_names_seq
```

Check that all the databases exist.

```
\seq_map_inline:Nn \l__dataplot_dbnames_seq
{
  \DTLifdbexists { ##1 } { }
  {
    \__datatool_action_error:nn
    {
      Database ~ `##1' ~ doesn't ~ exist
    }
    {
      Check ~ you ~ have ~ spelt ~ the ~ database ~ name ~
      correctly ~ in ~
      \token_to_str:N \DTLaction [name=
      { \seq_use:N \l__datatool_action_names_seq { , } } ]
      { \l__datatool_action_tl } ~ or ~ check ~ the ~ default-
name ~
      option ~ in ~ \token_to_str:N \DTLsetup
    }
  }
  \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n
}
}
\__dataplot_do_plot:n
{

```

Convert the minor gap dimension to user co-ordinates:

```
\fp_set:Nn \l__dataplot_min_minor_gap_fp
{ \DTLminminortickgap / 65536 }
```

Save the plot marks comma-separated list as a sequence:

```
\__dataplot_set_style_from_clist:NN
  \l__dataplot_mark_seq \DTLplotmarks
```

Save the plot lines comma-separated list as a sequence:

```
\__dataplot_set_style_from_clist:NN
  \l__dataplot_line_seq \DTLplotlines
```

Save the plot mark colours comma-separated list as a sequence:

```
\__dataplot_set_style_from_clist:NN  
\l__dataplot_mark_colors_seq \DTLplotmarkcolors
```

Save the plot line colours comma-separated list as a sequence:

```
\__dataplot_set_style_from_clist:NN  
\l__dataplot_line_colors_seq \DTLplotlinecolors
```

Clear the legend token list:

```
\tl_clear:N \l__dataplot_legend_tl
```

Check the user has supplied at least one x variable:

```
\clist_if_empty:NT \l__dataplot_x_keys_clist  
{  
  \__datatool_action_error:nn  
  {  
    Missing ~ x ~ setting  
  }  
  {  
    The ~ `x' ~ setting ~ needs ~ to ~ be ~ set ~ to ~  
    the ~ column ~ key ~ to ~ be ~ used ~ for ~  
    the ~ plot ~ x ~ values, ~ either ~ in ~  
    \token_to_str:N  
    \DTLaction [ options={x={...}}, ~ ... ]  
    { \l__datatool_action_tl } ~ or ~ in ~  
    \token_to_str:N \DTLsetup { plot = { x= { ... } } }  
  }  
  \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n  
}
```

Check the user has supplied at least one y variable:

```
\seq_if_empty:NTF \l__dataplot_y_keys_seq  
{  
  \__datatool_action_error:nn  
  {  
    Missing ~ y ~ setting  
  }  
  {  
    The ~ `y' ~ setting ~ needs ~ to ~ be ~ set ~ to ~  
    the ~ column ~ key ~ to ~ be ~ used ~ for ~  
    the ~ plot ~ y ~ values, ~ either ~ in ~  
    \token_to_str:N  
    \DTLaction [ options={y={...}}, ~ ... ]  
    { \l__datatool_action_tl } ~ or ~ in ~  
    \token_to_str:N \DTLsetup { plot = { y= { ... } } }  
  }  
  \cs_set_eq:NN \__dataplot_do_plot:n \use_none:n  
}  
{
```

Check that there aren't more x than y variables:

Primary return property and end group.

```
\tl_put_left:Nx \l__dataplot_content_tl
{
  \exp_not:N \group_end:
  \exp_not:N \tl_set:Nn
    \exp_not:N \l__datatool_action_return_tl
    { \int_use:N \l_dataplot_stream_index_int }
}
\l__dataplot_content_tl
}
\cs_new:Nn \__dataplot_set_style_from_clist:NN
{
  \seq_set_from_clist:NN #1 #2
```

The sequence must contain at least one item:

```
\seq_if_empty:NT #1
{
  \seq_put_right:Nn #1 { }
}
}
```

`\dtl@getbounds` Extract bounds function removed in version 3.0. See `__dataplot_update_bounds:nn`

```
\__dataplot_construct_tick_list:NNNN(min-fp)<max-fp>(min-gap-fp)<seq>
```

```
\cs_new:Nn \__dataplot_construct_tick_list:NNNN
{
  \fp_compare:nTF { #1 < \c_zero_fp < #2 }
  {
```

Tick list straddles the origin.

```
\fp_set:Nn \l__dataplot_width_fp { - ( #1 ) }
\__dataplot_default_gap:NNN
  \l__dataplot_neg_gap_fp \l__dataplot_width_fp #3
\__dataplot_default_gap:NNN
  \l__dataplot_pos_gap_fp #2 #3
\fp_set:Nn \l__dataplot_gap_fp
  { max ( \l__dataplot_neg_gap_fp, \l__dataplot_pos_gap_fp ) }
```

Don't construct a list if minimum gap is greater than plot width

```
\fp_compare:nF { \l__dataplot_gap_fp > \l__dataplot_width_fp }
{
  \__dataplot_construct_tick_list_over_zero:NNNN
    #1 #2 #4 \l__dataplot_gap_fp
}
}
}
```

Tick list doesn't straddle the origin.

```
\fp_set:Nn \l__dataplot_width_fp { #2 - #1 }
\__dataplot_default_gap:NNN
  \l__dataplot_gap_fp \l__dataplot_width_fp #3
\fp_compare:nTF { \l__dataplot_gap_fp < #3 }
{
```

Don't construct a list if minimum gap is greater than plot width

```
\fp_compare:nTF { #3 > \l__dataplot_width_fp }
{
  \seq_put_right:NV #4 #1
  \seq_put_right:NV #4 #2
}
{
  \__dataplot_construct_tick_list_with_gap:NNNN
  #1 #2 #4 #3
}
}
{
  \__dataplot_construct_tick_list_with_gap:NNNN
  #1 #2 #4 \l__dataplot_gap_fp
}
}
}
\__dataplot_default_gap:NNN <fp-var> {<extent>} {<max gap>}
\cs_new:Nn \__dataplot_default_gap:NNN
{
  \fp_set:Nn #1 { #2 / 10 }
  \fp_compare:nNnT { #1 } < { #3 }
  {
    \fp_set:Nn #1 { #2 / 5 }
    \fp_compare:nNnT { #1 } < { #3 }
    {
      \fp_set_eq:NN #1 #3
    }
  }
}
\fp_compare:nTF { #1 <= 0.1 }
{
  \fp_set:Nn #1 { 0.1 }
}
{
  \fp_compare:nTF { #1 <= 0.5 }
  {
    \fp_set:Nn #1 { 0.5 }
  }
  {
    \fp_compare:nTF { #1 <= 0.5 }
    {
      \fp_set:Nn #1 { 0.5 }
    }
  }
}
```



```

\fp_compare:nNnT
  { #1 - #2 } < { 0.1 * #3 }
  {
    \seq_put_right:NV #4 #2
  }
}

```

__dataplot_construct_tick_list_with_gap:NNNN
 $\langle min-fp \rangle \langle max-fp \rangle \langle seq \rangle \langle gap-fp \rangle$

Constructs a list of tick points between $\langle min \rangle$ and $\langle max \rangle$ and store in $\langle list \rangle$ (a control sequence) using the gap given by $\langle gap \rangle$ where the gap is given in user co-ordinates.

```

\cs_new:Nn \__dataplot_construct_tick_list_with_gap:NNNN
{
  \fp_set:Nn \l__datatool_tmpa_fp
    { #4 * ( floor ( #1 / #4 ) + 1 ) }
  \fp_compare:nNnT
    { #1 - \l__datatool_tmpa_fp } < { 0.5 * #4 }
    {
      \seq_put_right:NV #3 #1
    }
  \fp_while_do:nn { #1 < \l__datatool_tmpa_fp < #2 }
  {
    \seq_put_right:NV #3 \l__datatool_tmpa_fp
    \fp_add:Nn \l__datatool_tmpa_fp { #4 }
  }
  \fp_compare:nNnT
    { \l__datatool_tmpa_fp - #2 } < { 0.5 * #4 }
    {
      \seq_put_right:NV #3 #2
    }
}

```

constructticklistwithgap Version 3.0: replaced \dtl@constructticklistwithgap with __dataplot_construct_tick_list_w

__dataplot_construct_tick_list_over_zero:NNNN
 $\langle min-fp \rangle \langle max-fp \rangle \langle seq \rangle \langle gap-fp \rangle$

Constructs a list of tick points between $\langle min \rangle$ and $\langle max \rangle$ and store in $\langle list \rangle$ (a control sequence) using the gap given by $\langle gap \rangle$ where the tick list straddles zero.

```

\cs_new:Nn \__dataplot_construct_tick_list_over_zero:NNNN
{
  \fp_compare:nNnF { #4 } < { \c_dataplot_smallest_gap_fp }
  {
    \seq_put_right:NV #3 \c_zero_fp
    \fp_set_eq:NN \l__datatool_tmpa_fp #4
    \fp_while_do:nn { \c_zero_fp < \l__datatool_tmpa_fp < #2 }
  }
}

```

```

{
  \seq_put_right:NV #3 \l__datatool_tmpa_fp
  \fp_add:Nn \l__datatool_tmpa_fp { #4 }
}
\dataplot_add_end_tick:NNNN
  \l__datatool_tmpa_fp #2 #4 #3
\fp_compare:nF { #1 = \c_zero_fp }
{
  \fp_set:Nn \l__datatool_tmpa_fp { - ( #4 ) }
  \fp_while_do:nn { #1 < \l__datatool_tmpa_fp < \c_zero_fp }
  {
    \seq_put_left:NV #3 \l__datatool_tmpa_fp
    \fp_sub:Nn \l__datatool_tmpa_fp { #4 }
  }
  \fp_compare:nNnT
  { #1 - \l__datatool_tmpa_fp } < { 0.5 * #4 }
  {
    \seq_put_left:NV #3 #1
  }
}
}
}
}

```

Construct minor list. Syntax: $\langle major\ tic\ seq \rangle \langle min\ fp \rangle \langle max\ fp \rangle \langle scale\ fp \rangle \langle minor\ tic\ seq \rangle$

```

\cs_new:Nn \__dataplot_construct_minor_ticks:NNNNN
{

```

Calculate minor gap, which will be stored in $\l__dataplot_gap_fp$

```

\int_compare:nNnTF
{ \seq_count:N #1 } > { 3 }
{
  \tl_set:Nx \l__dataplot_x_fp
  { \seq_item:Nn #1 { 2 } }
  \tl_set:Nx \l__dataplot_y_fp
  { \seq_item:Nn #1 { 3 } }
  \__dataplot_calc_minor_gap:NNN
  \l__dataplot_x_fp \l__dataplot_y_fp
  #4
}
{
  \int_compare:nNnTF
  { \seq_count:N #1 } > { \c_one_int }
  {
    \tl_set:Nx \l__dataplot_x_fp
    { \seq_item:Nn #1 { 1 } }
    \tl_set:Nx \l__dataplot_y_fp
    { \seq_item:Nn #1 { 2 } }
    \__dataplot_calc_minor_gap:NNN
    \l__dataplot_x_fp \l__dataplot_y_fp
  }
}

```

```

        #4
    }
    {
        \__dataplot_calc_minor_gap:NNN
        #2 #3 #4
    }
}
Previous tick
\fp_set_eq:NN \l__dataplot_x_fp #2
\seq_map_indexed_inline:Nn #1
{
Current major tick
\tl_set:Nn \l__dataplot_y_fp { ##2 }
\int_compare:nNnT { ##1 } > { \c_one_int }
{
Construct minor ticks between them:
\int_compare:nNnTF { ##1 } = { 2 }
{
    \__dataplot_construct_reverse_tick_list:NNNN
    \l__dataplot_x_fp
    \l__dataplot_y_fp
    #5
    \l__dataplot_gap_fp
}
{
    \__dataplot_construct_tick_list_with_gap_excl:NNNN
    \l__dataplot_x_fp
    \l__dataplot_y_fp
    #5
    \l__dataplot_gap_fp
}
}
Previous major tick for next iteration:
\fp_set_eq:NN \l__dataplot_x_fp \l__dataplot_y_fp
}
Final ticks
\fp_set_eq:NN \l__dataplot_y_fp #3
\fp_compare:nNnT
{ \l__dataplot_min_minor_gap_fp }
<
{ \l__dataplot_y_fp - \l__dataplot_x_fp }
{
    \__dataplot_construct_tick_list_with_gap_excl:NNNN
    \l__dataplot_x_fp
    \l__dataplot_y_fp
    #5
    \l__dataplot_gap_fp
}

```

```

    }
  }
  Calculate minor gap and stores the result in \l__dataplot_gap_fp
\cs_new:Nn \__dataplot_calc_minor_gap:NNN
{
  \fp_set:Nn \l__dataplot_width_fp
  {
    ( #2 - #1 ) * #3
  }
  \fp_set:Nn \l__dataplot_gap_fp
  { \l__dataplot_width_fp / 10 }
  \fp_compare:nT
  { \l__dataplot_gap_fp < \l__dataplot_min_minor_gap_fp }
  {
    \fp_set:Nn \l__dataplot_gap_fp
    { \l__dataplot_width_fp / 4 }
    \fp_compare:nT
    { \l__dataplot_gap_fp < \l__dataplot_min_minor_gap_fp }
    {
      \fp_set:Nn \l__dataplot_gap_fp
      { \l__dataplot_width_fp / 2 }
      \fp_compare:nT
      { \l__dataplot_gap_fp < \l__dataplot_min_minor_gap_fp }
      {
        \fp_set_eq:NN \l__dataplot_gap_fp \l__dataplot_width_fp
      }
    }
  }
}
\fp_set:Nn \l__dataplot_gap_fp
{ \l__dataplot_gap_fp / #3 }
}

```

`__constructticklistwithgapz` Version 3.0: replaced `\dtl@constructticklistwithgapz` with `__dataplot_construct_tick_list_with_gapz`
 $\langle min-fp \rangle \langle max-fp \rangle \langle seq \rangle \langle gap-fp \rangle$

`__constructminorticklist` Version 3.0: removed

`\dtl@constructminorticklist` $\{\langle min \rangle\}\{\langle max \rangle\}\{\langle scale factor \rangle\}\{\langle list \rangle\}$

Constructs a list of minor tick points between $\langle min \rangle$ and $\langle max \rangle$ and append to $\langle list \rangle$ (a control sequence.)

`__dataplot_construct_tick_list_with_gap_excl`:NNNN
 $\langle min-fp \rangle \langle max-fp \rangle \langle seq \rangle \langle gap-fp \rangle$

Constructs a list of tick points between $\langle min \rangle$ and $\langle max \rangle$ and appends to $\langle seq \rangle$ using the gap given by $\langle gap \rangle$ where the gap is given in user co-ordinates. The end points are not included in the list.

```
\cs_new:Nn \__dataplot_construct_tick_list_with_gap_excl:NNNN
{
  \fp_compare:nTF
    { #1 < \c_zero_fp < #2 }
    {
      \__dataplot_construct_tick_list_over_zero:NNNN
      #1 #2 #3 #4
    }
    {
      \fp_compare:nNnF { #4 } < { \c_dataplot_smallest_gap_fp }
      {
        \fp_set:Nn \l__datatool_tmpa_fp { #1 + #4 }
        \fp_while_do:nn { #1 < \l__datatool_tmpa_fp < #2 }
        {
          \seq_put_right:NV #3 \l__datatool_tmpa_fp
          \fp_add:Nn \l__datatool_tmpa_fp { #4 }
        }
      }
    }
}
}
```

Syntax: $\langle min-fp \rangle \langle max-fp \rangle \langle seq \rangle \langle gap-fp \rangle$

```
\cs_new:Nn \__dataplot_construct_reverse_tick_list:NNNN
{
  \fp_compare:nNnF { #4 } < { \c_dataplot_smallest_gap_fp }
  {
    \fp_set:Nn \l__datatool_tmpa_fp { #2 - #4 }
    \fp_while_do:nn { #1 < \l__datatool_tmpa_fp < #2 }
    {
      \seq_put_left:NV #3 \l__datatool_tmpa_fp
      \fp_sub:Nn \l__datatool_tmpa_fp { #4 }
    }
  }
}
```

```
\__dataplot_construct_tick_list_with_gap_incl:NNNN
\langle min-fp \rangle \langle max-fp \rangle \langle seq \rangle \langle gap-fp \rangle
```

Constructs a list of tick points between $\langle min \rangle$ and $\langle max \rangle$ and appends to $\langle seq \rangle$ using the gap given by $\langle gap \rangle$ where the gap is given in user co-ordinates. The end points are included in the list if the gap is large enough.

```
\cs_new:Nn \__dataplot_construct_tick_list_with_gap_incl:NNNN
{
  \fp_compare:nTF
    { #1 < \c_zero_fp < #2 }
    {
```



```

        #2
        \pgfpathmoveto{\pgfpoint{-10pt}{0pt}}
        \pgfpathlineto{\pgfpoint{10pt}{0pt}}
        \pgfusepath{stroke}
    \end{pgfscope}
  }
}
\tl_if_empty:nF { #1 }
{
  \tl_if_eq:nnF { #1 } { \relax }
  {
    \tl_put_right:Nn \l_datatool_tmpc_tl { #1 }
  }
}
\tl_if_empty:NF \l_datatool_tmpc_tl
{
  \tl_put_right:Nn \l_dataplot_legend_tl
  { \begin { pgfpicture } }
  \tl_put_right:NV \l_dataplot_legend_tl \l_datatool_tmpc_tl
  \tl_put_right:Nn \l_dataplot_legend_tl
  { \end { pgfpicture } }
  \tl_put_right:Nn \l_dataplot_legend_tl { & #3 }
}
}
}

```

```

\dataplot_get_default_legend:Nnnnn
<tl-var>{<database index>}{<database name>}{<x key>}{<y
key>}

```

Get the default legend label (if legend labels not set). The $\langle tl-var \rangle$ is the token list variable in which to store the legend label. The current x key index can be accessed with $\backslash\l_dataplot_x_key_int$ and the current y key index can be accessed with $\backslash\l_dataplot_y_key_int$.

```

\cs_new:Nn \dataplot_get_default_legend:Nnnnn
{
  \int_compare:nNnTF
  { \dataplot_x_key_count: } > { \c_one_int }
  {
    \tl_put_right:Nx #1
    {
      \exp_not:N \DTLplotlegendxy
      [ #2 ] { #3 }
      [ \int_use:N \l_dataplot_x_key_int ] { #4 }
      [ \int_use:N \l_dataplot_y_key_int ] { #5 }
    }
  }
}

```

```

\int_compare:nNnT
{ \dataplot_y_key_count: } > { \c_one_int }
{
  \tl_put_right:Nx #1
  {
    \exp_not:N \DTLplotlegendy
    [ #2 ] { #3 }
    [ \int_use:N \l_dataplot_y_key_int ] { #5 }
  }
}
}
\if_empty:NTF #1
{
  \tl_set:Nx #1
  {
    \exp_not:N \DTLplotlegendname [ #2 ] { #3 }
  }
}
{
  \int_compare:nNnT
  { \dataplot_db_count: } > { \c_one_int }
  {
    \tl_put_left:Nx #1
    {
      \exp_not:N \DTLplotlegendname [ #2 ] { #3 }
      \exp_not:N \DTLplotlegendnamesep
    }
  }
}
}
}

```

In the following commands, $\langle db\ index \rangle$ is the index of the database name in the list supplied to `\DTLplot`, $\langle x\ index \rangle$ is the index of the $\langle x\ key \rangle$ in the x list, and $\langle y\ index \rangle$ the index of the $\langle y\ key \rangle$ in the y list. This is not the same as the column index (which can be obtained with `\dtlcolumnindex{\langle db-name \rangle}{\langle key \rangle}`).

```

\DTLplotlegendxy[\langle db\ index \rangle]{\langle db-name \rangle}[\langle x
index \rangle]{\langle x\ key \rangle}[\langle y\ index \rangle]{\langle y\ key \rangle}

```

`\DTLplotlegendxy`

x / y label in legend.

```

\NewDocumentCommand \DTLplotlegendxy { O{0} m O{0} m O{0} m }
{
  \DTLplotlegendx [ #1 ] { #2 } [ #3 ] { #4 }
  \DTLplotlegendxysep
  \DTLplotlegendy [ #1 ] { #2 } [ #5 ] { #6 }
}

```

`\DTLplotlegendxysep` Separator between x and y labels in legend.

```

\newcommand \DTLplotlegendxysep
{
  \c_space_tl / \c_space_tl
}

```

\DTLplotlegendnamesep Separator after name in legend.

```

\newcommand \DTLplotlegendnamesep { ~ }

```

```

\DTLplotlegendxy[<db index>]{<db-name>}

```

\DTLplotlegendname

Database label in legend.

```

\NewDocumentCommand \DTLplotlegendname { O{0} m }
{
  \prop_get:NnNTF \l_dataplot_legend_names_prop
    { #2 } \l_dataplot_legend_name_tl
    { \l_dataplot_legend_name_tl }
    { #2 }
}

```

\DTLplotlegendsetname Allow the user to supply a database name to legend text mapping.

```

\prop_new:N \l_dataplot_legend_names_prop
\tl_new:N \l_dataplot_legend_name_tl
\NewDocumentCommand \DTLplotlegendsetname { m m }
{
  \prop_put:Nnn \l_dataplot_legend_names_prop { #1 } { #2 }
}

```

```

\DTLplotlegendx[<db index>]{<db-name>}[<x index>]
{<x-key>}

```

\DTLplotlegendx

x label in legend.

```

\NewDocumentCommand \DTLplotlegendx { O{0} m O{0} m }
{

```

If a mapping has been supplied for the *x* key, use that.

```

  \prop_get:NnNTF \l_dataplot_legend_xlabels_prop
    { #4 } \l_dataplot_legend_xlabel_tl
    { \l_dataplot_legend_xlabel_tl }
    {
      \DTLaction
        [ name = { #2 }, key = { #4 } ]
        { column ~ data }
      \DTLuse { header }
    }
}

```

`\DTLplotlegendsetxlabel` Allow the user to supply alternative text for the x label to legend text mapping.

```
\prop_new:N \l_dataplot_legend_xlabel_prop
\tl_new:N \l_dataplot_legend_xlabel_tl
\NewDocumentCommand \DTLplotlegendsetxlabel { m m }
{
  \prop_put:Nnn \l_dataplot_legend_xlabel_prop { #1 } { #2 }
}
```

```
\DTLplotlegendy[<db index>]{<db-name>}[<y index>]
{<y-key>}
```

`\DTLplotlegendy`

```
\NewDocumentCommand \DTLplotlegendy { O{0} m O{0} m }
{
```

If a mapping has been supplied for the y key, use that.

```
\prop_get:NnNTF
  \l_dataplot_legend_ylabels_prop
  { #4 }
  \l_dataplot_legend_ylabel_tl
  {
    \l_dataplot_legend_ylabel_tl
  }
  {
    \DTLaction
      [ name = { #2 }, key = { #4 } ]
      { column ~ data }
    \DTLuse { header }
  }
}
```

`\DTLplotlegendsetylabel` Allow the user to supply alternative text for the y label to legend text mapping.

```
\prop_new:N \l_dataplot_legend_ylabel_prop
\tl_new:N \l_dataplot_legend_ylabel_tl
\NewDocumentCommand \DTLplotlegendsetylabel { m m }
{
  \prop_put:Nnn \l_dataplot_legend_ylabel_prop { #1 } { #2 }
}
```

The following commands may be used in the above definition to access additional information. Get the total number of databases:

```
\cs_new:Nn \dataplot_db_count:
{
  \seq_count:N \l__dataplot_dbnames_seq
}
```

Get the total number of x keys provided. NB this needs to count the original clist not the sequence which has items popped from it.

```

\cs_new:Nn \dataplot_x_key_count:
{
  \clist_count:N \l__dataplot_x_keys_clist
}
Get the total number of y keys provided:
\cs_new:Nn \dataplot_y_key_count:
{
  \seq_count:N \l__dataplot_y_keys_seq
}
\ExplSyntaxOff

```

30 person.sty

30.1 Package Declaration

Package identification:

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```

\DeclareRelease{v2.32}{2019-09-27}{person-2019-09-27.sty}
\DeclareCurrentRelease{v3.4}{2025-04-03}

```

Declare package:

```
\ProvidesPackage{person}[2025/04/03 v3.4 (NLCT)]
```

No longer requires the `ifthen` package. However, `ifthen` is automatically loaded by `datatool-base`, so this will have no noticeable effect. This package only really requires `datatool-base` not `datatool`. Provide an option to omit loading `datatool`.

```
\@person@datatoolsty
```

```
\newcommand\@person@datatoolsty{datatool}
```

Define shortcut commands.

```
\ExplSyntaxOn
```

```
\cs_new:Nn \__person_define_shortcuts:
```

```

{
  \newcommand \they { \peoplepronoun }
  \newcommand \They { \Peoplepronoun }
  \newcommand \them { \peopleobjpronoun }
  \newcommand \Them { \Peopleobjpronoun }
  \newcommand \their { \peoplepossadj }
  \newcommand \Their { \Peoplepossadj }
  \newcommand \theirs { \peopleposspronoun }
  \newcommand \Theirs { \Peopleposspronoun }
  \newcommand \you { \peoplepronounii }
  \newcommand \You { \Peoplepronounii }
  \newcommand \thee { \peopleobjpronounii }
  \newcommand \Thee { \Peopleobjpronounii }
  \newcommand \your { \peoplepossadjii }
}

```

```

\newcommand \Your { \Peoplepossadjii }
\newcommand \yours { \peopleposspronounii }
\newcommand \Yours { \Peopleposspronounii }
\newcommand \siblings { \peoplesibling }
\newcommand \Siblings { \Peoplesibling }
\newcommand \children { \peoplechild }
\newcommand \Children { \Peoplechild }
\newcommand \parents { \peopleparent }
\newcommand \Parents { \Peopleparent }
\cs_set:Nn \__person_define_shortcuts: { }
}

```

This will allow `datatool-base` and (if also required) `datatool` options to be passed to `person`:

```

\keys_define:nn { datatool }
{
  base-only .code:n =
  {
    \tl_set:Nn \@person@datatoolsty {datatool-base}
  } ,
  base-only .value_forbidden:n = true ,
  datatool .code:n =
  {
    \tl_set:Nn \@person@datatoolsty {datatool}
  } ,
  datatool .value_forbidden:n = true ,
  shortcuts .code:n = { \__person_define_shortcuts: } ,
  shortcuts .value_forbidden:n = true
}
\ExplSyntaxOff
  Process options:
\IfPackageLoadedTF{\@person@datatoolsty}
{
  \ProcessKeyOptions[datatool]
}
{
  \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{\@person@datatoolsty}}
  \ProcessOptions
}
\RequirePackage{\@person@datatoolsty}
\ExplSyntaxOn

```

Remove the package option keys so they can't be used with `\DTLsetup`.

```

\keys_define:nn { datatool }
{
  base-only .undefine: ,
  datatool .undefine: ,
  shortcuts .undefine: ,
}

```

Default behaviour is to locally define people. This allows the throwaway anon label to be used within a scoped context.

```
\bool_new:N \l__person_local_bool
\bool_set_true:N \l__person_local_bool

  Define options specific to person commands.
\keys_define:nn { datatool/person }
{
  local .bool_set:N = \l__person_local_bool ,
  global .bool_set_inverse:N = \l__person_local_bool ,
  shortcuts .code:n = { \__person_define_shortcuts: } ,
  shortcuts .value_forbidden:n = true
}
```

Allow these keys to be set in `\DTLsetup{person={...}}`

```
\keys_define:nn { datatool }
{
  person .code:n = { \keys_set:nn { datatool/person } { #1 } }
}
```

30.2 Defining People

`people` Keep count of the number of people who have been defined. This really should have been an internal variable, but retained for backward compatibility. The `people` label sequence can now simply be counted. (NB `\thepeople` was documented prior to v3.0.)

```
\newcounter{people}
```

`\PersonTotalCount`

```
\newcommand* \PersonTotalCount
{ \int_use:c { c@people } }
```

`\PersonMaleCount` Keep count of the number of male people who have been defined:

```
\int_new:N \l__person_male_int
\newcommand* \PersonMaleCount
{ \int_use:N \l__person_male_int }
```

`\PersonFemaleCount` Keep count of the number of female people who have been defined:

```
\int_new:N \l__person_female_int
\newcommand* \PersonFemaleCount
{ \int_use:N \l__person_female_int }
```

`\PersonNonBinaryCount` Keep count of the number of non-binary people who have been defined:

```
\int_new:N \l__person_nonbinary_int
\newcommand* \PersonNonBinaryCount
{ \int_use:N \l__person_nonbinary_int }
```

`\PersonUnknownCount` Keep count of the number of people who have been defined with the gender set to unknown:

```
\int_new:N \l__person_unknown_int
\newcommand* \PersonUnknownGenderCount
{ \int_use:N \l__person_unknown_int }
```

The label scratch variable is a public one to allow the label to be referenced in the `\newperson` hooks.

```
\tl_new:N \l__person_label_tl
```

Scratch variables.

```
\tl_new:N \l__person_full_name_tl
\tl_new:N \l__person_forenames_tl
\tl_new:N \l__person_name_tl
\tl_new:N \l__person_gender_tl
\tl_new:N \l__person_title_tl
\tl_new:N \l__person_surname_tl
```

`person` Version 3.0: Temporary counter `person` removed.

Define deprecated command. The deprecated command is provided rather than defined to help avoid conflict. Syntax: `<old cmd><new cmd>`

```
\cs_new:Nn \__person_define_deprecated_cmd:NN
{
  \providecommand #1
  {
    \PackageWarning { person }
    {
      \token_to_str:N #1 \c_space_tl ~ deprecated ~
      and ~ may ~ be ~ removed ~ in ~ future. ~ Use ~
      \token_to_str:N #2 \c_space_tl ~
      instead
    }
    #2
  }
}
```

`\@people@list` Keep a list of labels for each person who has been defined. Version 3.0: replaced `\@people@list` with:

```
\seq_new:N \l__person_people_seq
```

Internal constant gender identifiers. These are used to form token list variable names. The gender supplied when defining a person may be any of the defined labels, but it will be converted to the applicable constant value for internal use.

`\@male@label` Version 3.0: changed `\@male@label` to:

```
\tl_const:Nn \c_person_male_label_tl { male }
```

`\@female@label` Version 3.0: changed `\@female@label` to:

```
\tl_const:Nn \c_person_female_label_tl { female }
```

Non-binary:

```
\tl_const:Nn \c_person_nonbinary_label_tl { nonbinary }
```

Special case where the gender is unknown. This will usually be treated the same as non-binary.

```
\tl_const:Nn \c_person_unknown_label_tl { unknown }
```

Do something depending on whether none, one or multiple people defined.

```
\cs_new:Nn \__person_case:nnn
```

```
{  
  \int_case:nnF { \seq_count:N \l__person_people_seq }  
  {  
    { \c_zero_int } { #1 }  
    { \c_one_int } { #2 }  
  }  
  { #3 }  
}
```

Set person label scratch variable:

```
\cs_new:Nn \person_set_label:n
```

```
{  
  \__person_set_label:Nn \l_person_label_tl { #1 }  
}
```

Supply token list variable:

```
\cs_new:Nn \__person_set_label:Nn
```

```
{  
  \tl_set:Nx #1  
  { \text_purify:n { \tl_trim_spaces:n { #2 } } }  
}
```

~~\@get@firstperson~~ Version 3.0 removed ~~\@get@firstperson~~

~~\@@get@firstperson~~ Version 3.0 removed ~~\@@get@firstperson~~

~~\malelabels~~ List of labels that can be used to indicate that a person is male (when defining a person using ~~\newperson~~). Version 3.0: replaced ~~\malelabels~~ with an internal clist variable to reduce the possibility of a command name clash.

```
\clist_new:N \g_person_male_label_clist
```

~~\PersonSetMaleLabels~~

```
\NewDocumentCommand \PersonSetMaleLabels { m }
```

```
{  
  \clist_gset:Ne \g_person_male_label_clist { #1 }  
}
```

Initialise:

```
\PersonSetMaleLabels {Male,MALE,M,m}
```

`\PersonAddMaleLabel` Adds a label to the list of male labels.

```

\NewDocumentCommand \PersonAddMaleLabel { m }
{
  \clist_gput_right:Ne \g_person_male_label_clist { #1 }
}

```

`\addmalelabel` Old command.

```

\__person_define_deprecated_cmd:NN
\addmalelabel \PersonAddMaleLabel

```

`\femalelabels` List of labels that can be used to indicate that a person is female (when defining a person using `\newperson`). Version 3.0: replaced `\femalelabels` with an internal `clist` variable to reduce the possibility of a command name clash.

```

\clist_new:N \g_person_female_label_clist

```

`\PersonSetFemaleLabels`

```

\NewDocumentCommand \PersonSetFemaleLabels { m }
{
  \clist_gset:Ne \g_person_female_label_clist { #1 }
}

```

Initialise:

```

\PersonSetFemaleLabels {Female,FEMALE,F,f}

```

`\addfemalelabel` Adds a label to the list of female labels.

```

\__person_define_deprecated_cmd:NN
\addfemalelabel \PersonAddFemaleLabel

```

`\PersonAddFemaleLabel` Adds a label to the list of female labels.

```

\NewDocumentCommand \PersonAddFemaleLabel { m }
{
  \clist_gput_right:Ne \g_person_female_label_clist { #1 }
}

```

List of labels that can be used to indicate that a person is non-binary (when defining a person using `\newperson`).

```

\clist_new:N \g_person_nonbinary_label_clist

```

`\PersonSetNonBinaryLabels`

```

\NewDocumentCommand \PersonSetNonBinaryLabels { m }
{
  \clist_gset:Ne \g_person_nonbinary_label_clist { #1 }
}

```

Initialise:

```

\PersonSetNonBinaryLabels
{
  non-binary, Nonbinary, Non-Binary, NONBINARY,
  NON-BINARY, N, n
}

```

`\PersonAddNonBinaryLabel` Adds a label to the list of non-binary labels.

```

\NewDocumentCommand \PersonAddNonBinaryLabel { m }
{
  \clist_gput_right:Ne \g_person_nonbinary_label_clist { #1 }
}

```

`\PersonIfMaleLabel` Determines if first argument is contained in the list of male labels. (One level expansion is performed on the first object in first argument.) This always first checks the constant `\c_person_male_label_tl` so that it doesn't need to be included in the male labels list. If true does second argument, otherwise does third argument.

```

\NewDocumentCommand \PersonIfMaleLabel { m m m }
{
  \exp_args:NNo \tl_if_eq:NnTF \c_person_male_label_tl { #1 }
  { #2 }
  {
    \clist_if_in:NoTF \g_person_male_label_clist { #1 } { #2 } { #3 }
  }
}

```

`\ifmalelabel` Version 3.0: deprecated.

```

\__person_define_deprecated_cmd:NN
\ifmalelabel \PersonIfMaleLabel

```

`\PersonIfFemaleLabel` Determines if first argument is contained in the list of female labels. (One level expansion is performed on the first object in first argument.) This always first checks the constant `\c_person_female_label_tl` so that it doesn't need to be included in the `\g_person_female_label_clist` list. If true does second argument, otherwise does third argument.

```

\NewDocumentCommand \PersonIfFemaleLabel { m m m }
{
  \exp_args:NNo \tl_if_eq:NnTF \c_person_female_label_tl { #1 }
  { #2 }
  {
    \clist_if_in:NoTF \g_person_female_label_clist { #1 } { #2 } { #3 }
  }
}

```

`\iffemalelabel` Version 3.0: deprecated.

```

\__person_define_deprecated_cmd:NN
\iffemalelabel \PersonIfFemaleLabel

```

`\PersonIfNonBinaryLabel` Determines if first argument is contained in the list of non-binary gender labels. (One level expansion is performed on the first object in first argument.) This always first checks the constant `\c_person_nonbinary_label_tl` so that it doesn't need to be included in the `\g_person_nonbinary_label_clist` list. If true, does second argument, otherwise does third argument.

```

\NewDocumentCommand \PersonIfNonBinaryLabel { m m m }
{

```

```

\exp_args:NNo \tl_if_eq:NnTF
  \c_person_nonbinary_label_tl { #1 }
  { #2 }
  {
    \clist_if_in:NoTF \g_person_nonbinary_label_clist
      { #1 } { #2 } { #3 }
  }
}

```

`\newperson` Define a new person. The optional argument specifies a label with which to refer to that person. If omitted, `anon` is used. If more than one person is defined, the optional argument will be required to specify a unique label. The mandatory arguments are the person's full name, their familiar name and their gender.

Hook at the start of `\newperson`

```

\tl_new:N \g__person_new_init_tl
\cs_new:Nn \person_new_appto_start:n
{
  \tl_gput_right:N \g__person_new_init_tl { #1 }
}

```

Hook at the end of `\newperson`

```

\tl_new:N \g__person_new_finish_tl
\cs_new:Nn \person_new_appto_end:n
{
  \tl_gput_right:N \g__person_new_finish_tl { #1 }
}

```

Version 3.0 added a starred form which uses a key=value interface.

```

\NewDocumentCommand{\newperson}{ s O{anon} }
{
  \person_set_label:n { #2 }
  \tl_clear:N \l__person_full_name_tl
  \tl_clear:N \l__person_forenames_tl
  \tl_clear:N \l__person_name_tl
  \tl_clear:N \l__person_gender_tl
  \tl_clear:N \l__person_title_tl
  \tl_clear:N \l__person_surname_tl
  \g__person_new_init_tl
  \IfBooleanTF { #1 }
  { \__person_new:n }
  { \__person_new:nnn }
}

\cs_new:Nn \__person_new:nnn
{
  \person_if_exist:nTF { \l__person_label_tl }
  {
    \PackageError { person }
    {
      Person ~ ` \l__person_label_tl ' ~ has ~ already ~ been ~ defined
    }
  }
}

```

```

    }
    {
      Each ~ defined ~ person ~ must ~ have ~ a ~ unique ~ label
    }
  }
  {
    \tl_if_empty:NTF \l_person_label_tl
    {
      \PackageError { person }
      { Empty ~ person ~ label ~ not ~ permitted}
      {
        You ~ need ~ to ~ supply ~ a ~ non-empty ~
        label ~ to ~ identify ~ the ~ person
      }
    }
    {
      \tl_set:Ne \l__person_full_name_tl { \tl_trim_spaces:n { #1 } }
      \tl_set:Ne \l__person_name_tl { \tl_trim_spaces:n { #2 } }
      \datatool_if_null_or_empty:nTF { #3 }
      {
        \tl_set_eq:NN \l__person_gender_tl \c_person_unknown_label_tl
      }
      {
        \tl_set:Ne \l__person_gender_tl { \tl_trim_spaces:n { #3 } }
      }
    }
    \__person_new:
  }
}
}

```

Starred form has key=value interface. First define keys.

```

\keys_define:nn { datatool/person }
{
  fullname .tl_set:N = \l__person_full_name_tl ,
  expand-once-fullname .code:n =
  { \tl_set:No \l__person_full_name_tl { #1 } } ,
  expand-fullname .tl_set_x:N = \l__person_full_name_tl ,
  forenames .tl_set:N = \l__person_forenames_tl ,
  expand-once-forenames .code:n =
  { \tl_set:No \l__person_forenames_tl { #1 } } ,
  expand-forenames .tl_set_x:N = \l__person_forenames_tl ,
  name .tl_set:N = \l__person_name_tl ,
  expand-once-name .code:n =
  { \tl_set:No \l__person_name_tl { #1 } } ,
  expand-name .tl_set_x:N = \l__person_name_tl ,
  gender .code:n =
  {
    \datatool_if_null_or_empty:nTF { #1 }
    {
      \tl_set_eq:NN \l__person_gender_tl \c_person_unknown_label_tl
    }
  }
}

```

```

    }
    { \tl_set:Nc \l__person_gender_tl { #1 } }
  },
  title .tl_set:N = \l__person_title_tl ,
  expand-once-title .code:n =
    { \tl_set:Nc \l__person_title_tl { #1 } },
  expand-title .tl_set_x:N = \l__person_title_tl ,
  surname .tl_set:N = \l__person_surname_tl ,
  expand-once-surname .code:n =
    { \tl_set:Nc \l__person_surname_tl { #1 } },
  expand-surname .tl_set_x:N = \l__person_surname_tl ,
}
\cs_new:Nn \__person_new:n
{
  \person_if_exist:nTF { \l__person_label_tl }
  {
    \PackageError { person }
    {
      Person ~ ` \l__person_label_tl ' ~ has ~ already ~ been ~ defined
    }
    {
      Each ~ defined ~ person ~ must ~ have ~ a ~ unique ~ label
    }
  }
  {
    \tl_if_empty:NTF \l__person_label_tl
    {
      \PackageError { person }
      { Empty ~ person ~ label ~ not ~ permitted }
      {
        You ~ need ~ to ~ supply ~ a ~ non-empty ~
        label ~ to ~ identify ~ the ~ person
      }
    }
    {
      \keys_set:nn { datatool/person } { #1 }
      \__person_new:
    }
  }
}
\cs_new:Nn \__person_new:
{
  \bool_lazy_or:nnTF
  { \tl_if_empty_p:N \l__person_gender_tl }
  { \tl_if_eq_p:NN \l__person_gender_tl \c_person_unknown_label_tl }
  {

```

Unknown mostly behaves like non-binary but doesn't increment the nonbinary counter.

```
\bool_if:NTF \l__person_local_bool
```

```

{
  \tl_set:cV
  { person@ \l_person_label_tl @gender }
  \c_person_unknown_label_tl
}
{
  \tl_gset:cV
  { person@ \l_person_label_tl @gender }
  \c_person_unknown_label_tl
}
}
{
\exp_args:NV \PersonIfMaleLabel \l__person_gender_tl
{
  \bool_if:NTF \l__person_local_bool
  {
    \tl_set:cV
    { person@ \l_person_label_tl @gender }
    \c_person_male_label_tl
    \int_incr:N \l__person_male_int
  }
  {
    \tl_gset:cV
    { person@ \l_person_label_tl @gender }
    \c_person_male_label_tl
    \int_gincr:N \l__person_male_int
  }
}
}
{
\exp_args:NV \PersonIfFemaleLabel \l__person_gender_tl
{
  \bool_if:NTF \l__person_local_bool
  {
    \tl_set:cV
    { person@ \l_person_label_tl @gender }
    \c_person_female_label_tl
    \int_incr:N \l__person_female_int
  }
  {
    \tl_gset:cV
    { person@ \l_person_label_tl @gender }
    \c_person_female_label_tl
    \int_gincr:N \l__person_female_int
  }
}
}
{
\exp_args:NV \PersonIfNonBinaryLabel \l__person_gender_tl
{
  \bool_if:NTF \l__person_local_bool

```

```

{
  \tl_set:cV
  { person@ \l_person_label_tl @gender }
  \c_person_nonbinary_label_tl
  \int_incr:N \l__person_nonbinary_int
}
{
  \tl_gset:cV
  { person@ \l_person_label_tl @gender }
  \c_person_nonbinary_label_tl
  \int_gincr:N \l__person_nonbinary_int
}
}
{
  \tl_if_eq:NN \l__person_gender_tl \c_person_unknown_label_tl
  {
    \bool_if:NTF \l__person_local_bool
    {
      \tl_set:cV
      { person@ \l_person_label_tl @gender }
      \c_person_unknown_label_tl
      \int_incr:N \l__person_unknown_int
    }
    {
      \tl_gset:cV
      { person@ \l_person_label_tl @gender }
      \c_person_unknown_label_tl
      \int_gincr:N \l__person_unknown_int
    }
  }
}
{
  \PackageError { person }
  {
    Unknown ~ gender ~ ` \l__person_gender_tl ' ~
    for ~ person ~ ` \l_person_label_tl '
  }
  {
    Known ~ gender ~ identifiers ~ are: ~
    \clist_use:Nn \g_person_male_label_clist { , ~ } ~
    or ~ \clist_use:Nn \g_person_female_label_clist { , ~ } ~
    or ~ \clist_use:Nn \g_person_nonbinary_label_clist { , ~ }
    or ~ \c_person_unknown_label_tl
  }
}
\bool_if:NTF \l__person_local_bool
{
  \tl_set:cV
  { person@ \l_person_label_tl @gender }
  \c_person_unknown_label_tl
  \int_incr:N \l__person_unknown_int
}
}

```



```

\tl_if_empty:NTF \l__person_surname_tl
{
  \tl_set_eq:NN
  \l__person_full_name_tl
  \l__person_forenames_tl
}
{
  \tl_set:Nx \l__person_full_name_tl
  {
    \exp_not:V \l__person_forenames_tl
    \c_space_tl
    \exp_not:V \l__person_surname_tl
  }
}
}
}
\tl_if_empty:NT \l__person_forenames_tl
{
  \tl_set_eq:NN
  \l__person_forenames_tl
  \l__person_name_tl
}
\bool_if:NTF \l__person_local_bool
{
  \tl_set_eq:cN
  { person@ \l__person_label_tl @name }
  \l__person_name_tl
  \tl_set_eq:cN
  { person@ \l__person_label_tl @surname }
  \l__person_surname_tl
  \tl_set_eq:cN
  { person@ \l__person_label_tl @title }
  \l__person_title_tl
  \tl_set_eq:cN
  { person@ \l__person_label_tl @fullname }
  \l__person_full_name_tl
  \tl_set_eq:cN
  { person@ \l__person_label_tl @forenames }
  \l__person_forenames_tl
  \seq_put_right:NV \l__person_people_seq \l__person_label_tl
  \int_incr:N \c@people
}
{
  \tl_gset_eq:cN
  { person@ \l__person_label_tl @name }
  \l__person_name_tl
  \tl_gset_eq:cN
  { person@ \l__person_label_tl @surname }
  \l__person_surname_tl
  \tl_gset_eq:cN

```

```

        { person@ \l_person_label_tl @title }
        \l_person_title_tl
    \tl_gset_eq:cn
        { person@ \l_person_label_tl @fullname }
        \l_person_full_name_tl
    \tl_gset_eq:cn
        { person@ \l_person_label_tl @forenames }
        \l_person_forenames_tl
    \seq_gput_right:NV \l__person_people_seq \l_person_label_tl
    \int_gincr:N \c@people
    }
    \g__person_new_finish_tl
}

Syntax: {<label>}{<attribute name>}{<value>}
\cs_new:Nn \person_set_attribute:nnn
{
    \bool_if:NTF \l__person_local_bool
    {
        \tl_set_eq:cn { person@ #1 @ #2 } { #3 }
    }
    {
        \tl_gset_eq:cn { person@ #1 @ #2 } { #3 }
    }
}
\cs_generate_variant:Nn \person_set_attribute:nnn { nnV }
Syntax: {<person-label>}{<attribute>}
\cs_new:Nn \person_get_attribute:nn
{
    \tl_use:c { person@ #1 @ #2 }
}
Syntax: <tl var> {<person-label>}{<attribute>}
\cs_new:Nn \person_get_attribute:Nnn
{
    \tl_seq_eq:Nc #1 { person@ #2 @ #3 }
}
Syntax: {<person-label>}{<attribute>}
\cs_new:Nn \person_unset_attribute:nn
{
    \bool_if:NTF \l__person_local_bool
    {
        \csundef { person@ #1 @ #2 }
    }
    {
        \csgundef { person@ #1 @ #2 }
    }
}
}

```

30.3 Remove People

`\removeperson` Removes person identified by their label from the list.

```
\NewDocumentCommand \removeperson { O{anon} }
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \__person_remove:x { \l_person_label_tl }
  }
}
```

Internal commands don't check for existence.

```
\cs_new:Nn \__person_remove:
{
  \bool_if:NTF \l__person_local_bool
  {
    \seq_remove_all:NV \l__person_people_seq \l_person_label_tl
    \int_decr:N \c@people
  }
}
```

If the gender is unknown there won't be an associated counter.

```
\int_if_exist:cT
{ \l_person_ \csuse{ person@ \l_person_label_tl @gender } _int }
{
  \int_decr:c
  { \l_person_ \csuse { person@ \l_person_label_tl @gender } _int }
}
```

Undefine associated control sequences:

```
\csundef { person@ \l_person_label_tl @name }
\csundef { person@ \l_person_label_tl @fullname }
\csundef { person@ \l_person_label_tl @forenames }
\csundef { person@ \l_person_label_tl @gender }
\csundef { person@ \l_person_label_tl @title }
\csundef { person@ \l_person_label_tl @surname }
}
```

Globally remove label from list of people.

```
\seq_gremove_all:NV \l__person_people_seq \l_person_label_tl
```

Decrement number of people:

```
\int_gdecr:N \c@people
```

Decrement gender counter if it exists:

```
\int_if_exist:cT
{ \l_person_ \csuse{ person@ \l_person_label_tl @gender } _int }
{
  \int_gdecr:c
  { \l_person_ \csuse { person@ \l_person_label_tl @gender } _int }
}
```

Undefine associated control sequences:

```
\csgundef { person@ \l_person_label_tl @name }
\csgundef { person@ \l_person_label_tl @fullname }
\csgundef { person@ \l_person_label_tl @forenames }
\csgundef { person@ \l_person_label_tl @gender }
\csgundef { person@ \l_person_label_tl @title }
\csgundef { person@ \l_person_label_tl @surname }
}
\g__person_remove_tl
}
\cs_new:Nn \__person_remove:n
{
  \person_set_label:n { #1 }
  \__person_remove:
}
\cs_generate_variant:Nn \__person_remove:n { x }
```

Hook for remove person:

```
\tl_new:N \g__person_remove_tl
\cs_new:Nn \person_remove_appto:n
{
  \tl_gput_right:N \g__person_remove_tl { #1 }
}
```

`\removepeople` Removes the people listed.

```
\NewDocumentCommand \removepeople { m }
{
  \clist_map_function:nN { #1 } \__person_remove:n
}
```

`\removeallpeople` Removes everyone.

```
\NewDocumentCommand \removeallpeople { }
{
  \bool_if:NTF \l__person_local_bool
  {
    \seq_map_inline:Nn \l__person_people_seq
    {
      \person_set_label:n { ##1 }
      \csundef{person@ \l_person_label_tl @name}
      \csundef{person@ \l_person_label_tl @fullname}
      \csundef{person@ \l_person_label_tl @forenames}
      \csundef{person@ \l_person_label_tl @gender}
      \csundef{person@ \l_person_label_tl @title}
      \csundef{person@ \l_person_label_tl @surname}
      \g__person_remove_tl
    }
  }
  \int_zero:c { c@people }
  \int_zero:N \l__person_male_int
  \int_zero:N \l__person_female_int
  \int_zero:N \l__person_nonbinary_int
}
```

```

\seq_clear:N \l__person_people_seq
}
{
\seq_map_inline:Nn \l__person_people_seq
{
\person_set_label:n { ##1 }
\csgundef{person@ \l__person_label_tl @name}
\csgundef{person@ \l__person_label_tl @fullname}
\csgundef{person@ \l__person_label_tl @forenames}
\csgundef{person@ \l__person_label_tl @gender}
\csgundef{person@ \l__person_label_tl @title}
\csgundef{person@ \l__person_label_tl @surname}
\g__person_remove_tl
}
\int_gzero:c { c@people }
\int_gzero:N \l__person_male_int
\int_gzero:N \l__person_female_int
\int_gzero:N \l__person_nonbinary_int
\seq_gclear:N \l__person_people_seq
}
}

```

30.4 Conditionals and Loops

`\ifpersonexists` If person whose label is given by the first argument exists, then do the second argument otherwise do third argument.

```

\newcommand{\ifpersonexists}[3]{
\exp_args:Ne \person_if_exist:nTF
{ \tl_trim_spaces:n { #1 } }
{ #2 } { #3 }
}

\prg_new_conditional:Npnn \person_if_exist:n #1 { p, T, F, TF }
{
\tl_if_exist:cTF { person@ #1 @name}
{ \prg_return_true: }
{ \prg_return_false: }
}

\cs_new:Nn \person_if_exist_or_err:nT
{
\person_if_exist:nTF
{ #1 } { #2 }
{
\PackageError { person }
{
Person ~ ` #1 ' ~ doesn't ~ exist
}
{
Check ~ that ~ you ~ have ~ correctly ~ spelt ~ the ~ label
}
}
}

```

```

    }
  }
}

```

Case-command. Syntax: $\langle gender\ tl\text{-}var \rangle \{ \langle invalid \rangle \} \{ \langle male \rangle \} \{ \langle female \rangle \} \{ \langle non\text{-}binary \rangle \} \{ \langle unknown \rangle \}$

```

\cs_new:Nn \person_gender_case:Nnnnnn
{
  \tl_if_eq:NNTF #1 \c_person_male_label_tl
  { #3 }
  {
    \tl_if_eq:NNTF #1 \c_person_female_label_tl
    { #4 }
    {
      \tl_if_eq:NNTF #1 \c_person_nonbinary_label_tl
      { #5 }
      {
        \tl_if_eq:NNTF #1 \c_person_unknown_label_tl
        { #6 } { #2 }
      }
    }
  }
}

```

As above but label supplied as a token list.

```

\cs_new:Nn \person_gender_case:nnnnnn
{
  \tl_if_eq:NnTF \c_person_male_label_tl { #1 }
  { #3 }
  {
    \tl_if_eq:NnTF \c_person_female_label_tl { #1 }
    { #4 }
    {
      \tl_if_eq:NnTF \c_person_nonbinary_label_tl { #1 }
      { #5 }
      {
        \tl_if_eq:NnTF \c_person_unknown_label_tl { #1 }
        { #6 } { #2 }
      }
    }
  }
}
\cs_generate_variant:Nn \person_gender_case:nnnnnn
{ xnnnnn }

```

Similar but issue an error for invalid case and treat as unknown:

```

\cs_new:Nn \person_gender_case:Nnnnnn
{
  \person_gender_case:Nnnnnn #1
  {
    \PackageError { person }

```

```

    {
      Unrecognised ~ internal ~ gender ~ label ~ `#1'. ~
      Treating ~ as ~ ` \c_person_unknown_label_tl '
    }
    {
      Internal ~ gender ~ labels ~ must ~ be ~ one ~ of ~
      the ~ following: ` \c_person_male_label_tl ', ~
      ` \c_person_female_label_tl ', ~
      ` \c_person_nonbinary_label_tl ', ~
      ` \c_person_unknown_label_tl '
    }
  #5
}
{ #2 } { #3 } { #4 } { #5 }
}
Gender label provided as a token list:
\cs_new:Nn \person_gender_case:nnnnn
{
  \person_gender_case:nnnnn { #1 }
  {
    \PackageError { person }
    {
      Unrecognised ~ internal ~ gender ~ label ~ `#1'. ~
      Treating ~ as ~ ` \c_person_unknown_label_tl '
    }
    {
      Internal ~ gender ~ labels ~ must ~ be ~ one ~ of ~
      the ~ following: ` \c_person_male_label_tl ', ~
      ` \c_person_female_label_tl ', ~
      ` \c_person_nonbinary_label_tl ', ~
      ` \c_person_unknown_label_tl '
    }
  #5
}
{ #2 } { #3 } { #4 } { #5 }
}
\cs_generate_variant:Nn \person_gender_case:nnnnn
{ xnnnn }
Just need to know if the label is valid:
\cs_new:Nn \person_do_if_valid_gender:nT
{
  \person_gender_case:nnnnn { #1 }
  {
    \PackageError { person }
    {
      Unrecognised ~ internal ~ gender ~ label ~ `#1'
    }
    {
      Internal ~ gender ~ labels ~ must ~ be ~ one ~ of ~

```

```

        the ~ following: ` \c_person_male_label_tl ', ~
        ` \c_person_female_label_tl ', ~
        ` \c_person_nonbinary_label_tl ', ~
        ` \c_person_unknown_label_tl '
    }
}
{ #2 } { #2 } { #2 } { #2 }
}
\cs_generate_variant:Nn \person_do_if_valid_gender:nT
{ xT }
Test if all defined people the same gender. Syntax: {<all male>}{<all female>}{<all
non-binary>}{<other>}
\cs_new:Nn \person_all_gender_case:nnnn
{
  \int_compare:nNnTF
    { \c@people } = { \l__person_male_int }
  { #1 }
  {
    \int_compare:nNnTF
      { \c@people } = { \l__person_female_int }
    { #2 }
    {
      \int_compare:nNnTF
        { \c@people } = { \l__person_nonbinary_int }
        { #3 } { #4 }
      }
    }
  }
}

```

`\PersonIfMale` If the person given by the label in the first argument is male, do the second argument, otherwise do the third argument.

```

\NewDocumentCommand \PersonIfMale { m m m }
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \tl_if_eq:cNTF
      { person@ \l_person_label_tl @gender }
      \c_person_male_label_tl
      {#2} {#3}
  }
}

```

`\ifmale` If the person given by the label in the first argument is male, do the second argument, otherwise do the third argument.

```

\__person_define_deprecated_cmd:NN
\ifmale \PersonIfMale

```

`\PersonIfAllMale` If all people listed in first argument are male, do the second argument otherwise do the third argument. If the first argument is omitted, all defined people are checked.

```

\NewDocumentCommand \PersonIfAllMale { o m m }
{
  \IfNoValueTF { #1 }
  {
    \int_compare:nNnTF
      { \c@people } = { \l__person_male_int }
      { #2 } { #3 }
  }
  {
    \cs_set_eq:NN \__person_do:TF \cs_use_i:nn
    \clist_map_inline:nn { #1 }
    {
      \tl_if_eq:cNF
        { person@ \text_purify:n { ##1 } @gender}
        \c_person_male_label_tl
      {
        \cs_set_eq:NN \__person_do:TF \cs_use_ii:nn
        \clist_map_break:
      }
    }
  }
  \__person_do:TF { #2 } { #3 }
}

```

`\ifallmale`

```

\__person_define_deprecated_cmd:NN
\ifallmale \PersonIfAllMale

```

`\PersonIfFemale` If the person given by the label in the first argument is female, do the second argument, otherwise do the third argument.

```

\NewDocumentCommand \PersonIfFemale { m m m }
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \tl_if_eq:cNTF
      { person@ \l_person_label_tl @gender }
      \c_person_female_label_tl
      {#2} {#3}
  }
}

```

`\iffemale` If the person given by the label in the first argument is female, do the second argument, otherwise do the third argument.

```

\__person_define_deprecated_cmd:NN
\iffemale \PersonIfFemale

```

`\PersonIfAllFemale` If all people listed in first argument are female, do the second argument otherwise do the third argument.

```

\NewDocumentCommand \PersonIfAllFemale { o m m }
{
  \IfNoValueTF { #1 }
  {
    \int_compare:nNnTF
      { \c@people } = { \l__person_female_int }
      { #2 } { #3 }
  }
  {
    \cs_set_eq:NN \__person_do:TF \cs_use_i:nn
    \clist_map_inline:nn { #1 }
    {
      \tl_if_eq:cNF
        { person@ \text_purify:n { ##1 } @gender}
        \c_person_female_label_tl
      {
        \cs_set_eq:NN \__person_do:TF \cs_use_ii:nn
        \clist_map_break:
      }
    }
  }
  \__person_do:TF { #2 } { #3 }
}

```

`\ifallfemale` If all people listed in first argument are female, do the second argument otherwise do the third argument.

```

\__person_define_deprecated_cmd:NN
\ifallfemale \PersonIfAllFemale

```

`\PersonIfNonBinary` If the person given by the label in the first argument is non-binary, do the second argument, otherwise do the third argument. NB this does false for unknown.

```

\NewDocumentCommand \PersonIfNonBinary { m m m }
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \tl_if_eq:cNTF
      { person@ \l_person_label_tl @gender }
      \c_person_nonbinary_label_tl
      { #2 } { #3 }
  }
}

```

`\PersonIfAllNonBinary` If all people listed in first argument are nonbinary, do the second argument otherwise do the third argument. NB this does false for unknown.

```

\NewDocumentCommand \PersonIfAllNonBinary { o m m }
{

```

```

\IfNoValueTF { #1 }
{
  \int_compare:nNnTF
    { \c@people } = { \l__person_nonbinary_int }
    { #2 } { #3 }
}
{
  \cs_set_eq:NN \__person_do:TF \cs_use_i:nn
  \clist_map_inline:nn { #1 }
  {
    \tl_if_eq:cNF
      { person@ \text_purify:n { ##1 } @gender}
      \c_person_nonbinary_label_tl
    {
      \cs_set_eq:NN \__person_do:TF \cs_use_ii:nn
      \clist_map_break:
    }
  }
  \__person_do:TF { #2 } { #3 }
}
}

```

\PersonIfUnknownGender If the person given by the label in the first argument has the gender set to unknown, do the second argument, otherwise do the third argument.

```

\NewDocumentCommand \PersonIfUnknownGender { m m m }
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \tl_if_eq:cNTF
      { person@ \l_person_label_tl @gender }
      \c_person_unknown_label_tl
      { #2 } { #3 }
  }
}

```

PersonIfAllUnknownGender If all people listed in first argument have the gender set to unknown, do the second argument otherwise do the third argument.

```

\NewDocumentCommand \PersonIfAllUnknownGender { o m m }
{
  \IfNoValueTF { #1 }
  {
    \int_compare:nNnTF
      { \c@people } = { \l__person_unknown_int }
      { #2 } { #3 }
  }
  {
    \cs_set_eq:NN \__person_do:TF \cs_use_i:nn
    \clist_map_inline:nn { #1 }

```

```

    {
      \tl_if_eq:cNF
      { person@ \text_purify:n { ##1 } @gender}
      \c_person_unknown_label_tl
      {
        \cs_set_eq:NN \__person_do:TF \cs_use_ii:nn
        \clist_map_break:
      }
    }
  }
  \__person_do:TF { #2 } { #3 }
}
}

```

`\foreachpersonbreak` Break out of loops.

```

\newcommand{\foreachpersonbreak}
{
  \PackageError { person }
  {
    \token_to_str:N \foreachpersonbreak \c_space_tl ~
    can't ~ be ~ used ~ outside ~ of
    \token_to_str:N \forallpeople \c_space_tl ~
    or \token_to_str:N \foreachperson
  }
  { }
}

```

`\foreachperson(<name cs>,<full name cs>,<gender cs>,<label cs>)\in{<list>}\do{<body>}`

`\foreachperson`

Iterates through list of people the `\in{<list>}` is optional. If omitted, the list of all defined people is used.

```

\newcommand \foreachperson { \__person_foreach:wn }

\cs_new:Npn \__person_foreach:wn ( #1 , #2 , #3 , #4 ) #5
{
  \tl_if_eq:nnTF { #5 } { \in }
  {
    \__person_foreach:NNNNnn #1 #2 #3 #4
  }
  {
    \renewcommand \foreachpersonbreak { \seq_break: }
    \seq_map_inline:Nn \l__person_people_seq
    {
      \__person_foreach_fn:NNNNnn #1 #2 #3 #4 { ##1 } { #5 }
    }
  }
}

```

List of labels provided:

```
\cs_new:Nn \__person_foreach:NNNNnn
{
  \renewcommand \foreachpersonbreak { \clist_break: }
  \clist_map_inline:nn { #5 }
  {
    \__person_foreach_fn:NNNNxn #1 #2 #3 #4
    { \text_purify:n { \tl_trim_spaces:n { ##1 } } } { #6 }
  }
}
```

Loop function. Syntax: $\langle name-tl-var \rangle \langle full-name-tl-var \rangle \langle gender-tl-var \rangle \langle label-tl-var \rangle$
 $\{ \langle label \rangle \} \{ \langle body \rangle \}$

```
\cs_new:Nn \__person_foreach_fn:NNNNnn
{
  \person_if_exist_or_err:nT { #5 }
  {
    \tl_set:Nn #4 { #5 }
    \tl_set_eq:Nc #1 { person@ #5 @name }
    \tl_set_eq:Nc #2 { person@ #5 @fullname }
    \tl_set:Nx #3 { \__person_language:nn { #5 } { gender } }
    #6
  }
}
\cs_generate_variant:Nn \__person_foreach_fn:NNNNnn
{ NNNNxn }
```

\@foreachperson Version 3.0: removed \@foreachperson

\forallpeople

```
\forallpeople[ $\langle list \rangle$ ]{ $\langle label-cs \rangle$ }{ $\langle body \rangle$ }
```

```
\NewDocumentCommand \forallpeople { o m +m }
{
  \IfValueTF { #1 }
  {
    \renewcommand \foreachpersonbreak { \clist_break: }
    \clist_map_inline:nn { #1 }
    {
      \__person_set_label:Nn #2 { ##1 }
      \person_if_exist_or_err:nT { #2 }
      { #3 }
    }
  }
  {
    \renewcommand \foreachpersonbreak { \seq_break: }
    \seq_map_inline:Nn \l__person_people_seq
    {
      \tl_set:Nn #2 { ##1 }
    }
  }
}
```

The person should exist unless something unexpected has occurred.

```

\person_if_exist_or_err:nT { #2 }
  { #3 }
}
}

```

30.5 Predefined Words

These commands should be redefined if you are writing in another language, but note that these are structured according to English grammar.

Version 3.0 has renamed some commands to help avoid conflict. The old command names are retained for backward-compatibility but may be removed in a later version.

`\PersonSetLocalisation{<gender>}{<type>}{<value>}`

`\PersonSetLocalisation`

These are now token list variables in the form `\g__person_<gender>_<type>_tl` and can be set with the following command. NB the gender label must be one of the internal labels (“male”, “female”, “nonbinary” or “unknown”).

```

\NewDocumentCommand \PersonSetLocalisation
  { m m m }
{
\person_do_if_valid_gender:nT { #1 }
  {
\tl_gset:cn { g__person_ #1 _ #2 _tl } { #3 }
}
}

```

Define new localisation token list variable:

```

\cs_new:Nn \person_new_localisation:nnn
{
\person_do_if_valid_gender:nT { #1 }
  {
\tl_new:c { g__person_ #1 _ #2 _tl }
\tl_gset:cn { g__person_ #1 _ #2 _tl } { #3 }
}
}

```

Get localisation token list variable.

```

\cs_new:Nn \person_get_localisation:nn
{
\tl_if_exist:cTF { g__person_ #1 _ #2 _tl }
  { \tl_use:c { g__person_ #1 _ #2 _tl } }
  {
\tl_if_exist:cTF { g__person_unknown_ #2 _tl }
  {
\tl_use:c { g__person_unknown_ #2 _tl }
}
}
}

```

```

}
{
  \tl_if_exist:cTF { g__person_nonbinary_ #2 _tl }
  {
    \tl_use:c { g__person_nonbinary_ #2 _tl }
  }
  {
    ??
    \NoCaseChange
    {
      \PackageWarning { person }
      {
        Unknown ~ localisation ~ combination: ~
        gender = ` #1 ' ~ and ~ type = ` #2 '
      }
    }
  }
}
}
}
}
\cs_generate_variant:Nn \person_get_localisation:nn { vn, Vn }

```

30.5.1 Third person pronouns (subject)

```

\cs_new:Nn \__person_deprecated_lang_cs:Nnnn
{
  \tl_if_exist:NTF #1
  {
    \person_new_localisation:nnn { #2 } { #3 } { #4 }
  }
  {
    \newcommand* #1 { #4 }
    \person_new_localisation:nnn { #2 } { #3 } { #1 }
  }
}

```

`\malepronoun` Old pre 3.0 command. This may be removed in future.

```

\__person_deprecated_lang_cs:Nnnn
\malepronoun
{ male } { pronoun } { he }

```

`\femalepronoun` Old pre 3.0 command. This may be removed in future.

```

\__person_deprecated_lang_cs:Nnnn
\femalepronoun
{ female } { pronoun } { she }

```

Non-binary pronoun:

```

\person_new_localisation:nnn { nonbinary } { pronoun } { they }

```

`\pluralpronoun` Old pre 3.0 command. This may be removed in future.

```
  \__person_deprecated_lang_cs:Nnnn  
  \pluralpronoun  
  { unknown } { pluralpronoun } { they }
```

Pronouns (object).

`\maleobjpronoun` Old pre 3.0 command. This may be removed in future.

```
  \__person_deprecated_lang_cs:Nnnn  
  \maleobjpronoun  
  { male } { objpronoun } { him }
```

`\femaleobjpronoun` Old pre 3.0 command. This may be removed in future.

```
  \__person_deprecated_lang_cs:Nnnn  
  \femaleobjpronoun  
  { female } { objpronoun } { her }
```

```
  \person_new_localisation:nnn  
  { nonbinary } { objpronoun } { them }
```

`\pluralobjpronoun` Old pre 3.0 command. This may be removed in future.

```
  \__person_deprecated_lang_cs:Nnnn  
  \pluralobjpronoun  
  { unknown } { pluralobjpronoun } { them }
```

Pronouns (possessive adjective).

`\malepossadj` Old pre 3.0 command. This may be removed in future.

```
  \__person_deprecated_lang_cs:Nnnn  
  \malepossadj  
  { male } { possadj } { his }
```

`\femalepossadj` Old pre 3.0 command. This may be removed in future.

```
  \__person_deprecated_lang_cs:Nnnn  
  \femalepossadj  
  { female } { possadj } { her }
```

```
  \person_new_localisation:nnn  
  { nonbinary } { possadj } { their }
```

`\pluralpossadj` Old pre 3.0 command. This may be removed in future.

```
  \__person_deprecated_lang_cs:Nnnn  
  \pluralpossadj  
  { unknown } { pluralpossadj } { their }
```

Pronouns (possessive pronoun).

`\maleposspronoun` Old pre 3.0 command. This may be removed in future.

```
  \__person_deprecated_lang_cs:Nnnn  
  \maleposspronoun  
  { male } { posspronoun } { his }
```

`\femaleposspronoun` Old pre 3.0 command. This may be removed in future.

```
__person_deprecated_lang_cs:Nnnn
femaleposspronoun
{ female } { posspronoun } { hers }

person_new_localisation:nnn
{ nonbinary } { posspronoun } { theirs }
```

`\pluralposspronoun` Old pre 3.0 command. This may be removed in future.

```
__person_deprecated_lang_cs:Nnnn
pluralposspronoun
{ unknown } { pluralposspronoun } { theirs }
```

30.5.2 Second person

These are the same for all genders in English, but version 3.0 now provides support in the event of other languages.

```
person_new_localisation:nnn { unknown } { pronoun2 } { you }
person_new_localisation:nnn { unknown } { pluralpronoun2 } { you }
```

Objective pronoun.

```
person_new_localisation:nnn
{ unknown } { objpronoun2 } { you }
person_new_localisation:nnn
{ unknown } { pluralobjpronoun2 } { you }
```

Possessive adjective.

```
person_new_localisation:nnn
{ unknown } { possadj2 } { your }
person_new_localisation:nnn
{ unknown } { pluralpossadj2 } { your }
```

Possessive pronoun.

```
person_new_localisation:nnn
{ unknown } { posspronoun2 } { yours }
person_new_localisation:nnn
{ unknown } { pluralposspronoun2 } { yours }
```

30.5.3 Relationship

`\malechild` Old pre 3.0 command. This may be removed in future.

```
__person_deprecated_lang_cs:Nnnn
malechild
{ male } { child } { son }
```

`\femalechild` Old pre 3.0 command. This may be removed in future.

```
__person_deprecated_lang_cs:Nnnn
femalechild
{ female } { child } { daughter }
```

```

\person_new_localisation:nnn
  { nonbinary } { child } { child }

\pluralchild Old pre 3.0 command. This may be removed in future.
  \__person_deprecated_lang_cs:Nnnn
  \pluralchild
  { unknown } { pluralchild } { children }

\malechildren Old pre 3.0 command. This may be removed in future.
  \__person_deprecated_lang_cs:Nnnn
  \malechildren
  { male } { pluralchild } { sons }

\femalechildren Old pre 3.0 command. This may be removed in future.
  \__person_deprecated_lang_cs:Nnnn
  \femalechildren
  { female } { pluralchild } { daughters }

  \person_new_localisation:nnn
  { nonbinary } { pluralchild } { children }

\maleparent Old pre 3.0 command. This may be removed in future.
  \__person_deprecated_lang_cs:Nnnn
  \maleparent
  { male } { parent } { father }

\femaleparent Old pre 3.0 command. This may be removed in future.
  \__person_deprecated_lang_cs:Nnnn
  \femaleparent
  { female } { parent } { mother }

  \person_new_localisation:nnn
  { nonbinary } { parent } { parent }

\pluralparent Old pre 3.0 command. This may be removed in future.
  \__person_deprecated_lang_cs:Nnnn
  \pluralparent
  { unknown } { pluralparent } { parents }

\malesibling Old pre 3.0 command. This may be removed in future.
  \__person_deprecated_lang_cs:Nnnn
  \malesibling
  { male } { sibling } { brother }

\femalesibling Old pre 3.0 command. This may be removed in future.
  \__person_deprecated_lang_cs:Nnnn
  \femalesibling
  { female } { sibling } { sister }

```

```
\person_new_localisation:nnn
  { nonbinary } { sibling } { sibling }
```

`\pluralsibling` Old pre 3.0 command. This may be removed in future.

```
__person_deprecated_lang_cs:Nnnn
\pluralsibling
  { unknown } { pluralsibling } { siblings }
```

`\malesiblings` Old pre 3.0 command. This may be removed in future.

```
__person_deprecated_lang_cs:Nnnn
\malesiblings
  { male } { pluralsibling } { brothers }
```

`\femalesiblings` Old pre 3.0 command. This may be removed in future.

```
__person_deprecated_lang_cs:Nnnn
\femalesiblings
  { female } { pluralsibling } { sisters }

\person_new_localisation:nnn
  { nonbinary } { pluralsibling } { siblings }
```

30.5.4 Other

`\andname` Version 3.0: removed definition of `\andname` (datatool-base now provides `\DTLandname`)

`\malename` Old pre 3.0 command. This may be removed in future.

```
__person_deprecated_lang_cs:Nnnn
\malename
  { male } { gender } { male }
```

`\femalename` Old pre 3.0 command. This may be removed in future.

```
__person_deprecated_lang_cs:Nnnn
\femalename
  { female } { gender } { female }

\person_new_localisation:nnn
  { nonbinary } { gender } { non-binary }

\person_new_localisation:nnn
  { unknown } { gender } { unknown }
```

There are no plural versions of `gender`.

30.6 Displaying Information (Name and Title)

`\personsep` Separator to use between people (but not the between the last two).

```
\newcommand*{\personsep}{\DTLlistformatsep}
```

`\personlastsep` Separator to use between last two people if the list contains more than two people.

```
\newcommand*{\personlastsep}{
  \DTLlistformatoxford
  \DTLlistformatlastsep
}
```

`\twopeoplesep` Separator to use when list only contains two people.

```
\newcommand*{\twopeoplesep}{\DTLlistformatlastsep}
```

List of people. The provided function should encapsulate the person label.

```
\cs_new:Nn \person_display_list:N
{
  \int_case:nnF { \seq_count:N \l__person_people_seq }
  {
    { \c_zero_int }
    {
      \PackageWarning { person }
      { No ~ people ~ defined }
    }
    { \c_one_int }
    {
      \exp_args:Nx #1
      { \seq_item:Nn \l__person_people_seq { \c_one_int } }
    }
    { 2 }
    {
      \exp_args:Nx #1
      { \seq_item:Nn \l__person_people_seq { \c_one_int } }
      \twopeoplesep
      \exp_args:Nx #1
      { \seq_item:Nn \l__person_people_seq { 2 } }
    }
  }
}
\seq_map_indexed_inline:Nn \l__person_people_seq
{
  \int_case:nnF { ##1 }
  {
    { \seq_count:N \l__person_people_seq }
    { \personlastsep }
    { \c_one_int } { }
  }
  { \personsep }
  #1 { ##2 }
}
}
```

`\personfullname` The person's full name can be displayed using `\personfullname[⟨label⟩]`, where

$\langle label \rangle$ is the unique label used when defining that person. If $\langle label \rangle$ is omitted, `anon` is used.

```
\NewDocumentCommand \personfullname { O{anon} }
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \__person_full_name:n { \l_person_label_tl }
  }
}

\cs_new:Nn \__person_full_name:n
{
  \tl_use:c { person@ #1 @fullname }
}
\cs_generate_variant:Nn \__person_full_name:n { x }
```

`\peoplefullname` List all defined people's full names.

```
\NewDocumentCommand \peoplefullname { }
{
  \person_display_list:N \__person_full_name:n
}
}
```

`\personforenames` The person's forenames can be displayed using `\personforenames[$\langle label \rangle$]`, where $\langle label \rangle$ is the unique label used when defining that person. If $\langle label \rangle$ is omitted, `anon` is used.

```
\NewDocumentCommand \personforenames { O{anon} }
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \__person_forenames:n { \l_person_label_tl }
  }
}

\cs_new:Nn \__person_forenames:n
{
  \tl_use:c { person@ #1 @forenames }
}
\cs_generate_variant:Nn \__person_forenames:n { x }
```

`\peopleforenames` List all defined people's full names.

```
\NewDocumentCommand \peopleforenames { }
{
  \person_display_list:N \__person_forenames:n
}
}
```

`\personname` As `\personfullname`, but for the person's familiar or first name.

```
\NewDocumentCommand \personname { O{anon} }
```

```

{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \__person_name:n { \l_person_label_tl }
  }
}

\cs_new:Nn \__person_name:n
{
  \tl_use:c { person@ #1 @name }
}
\cs_generate_variant:Nn \__person_name:n { x }

```

`\peoplename` List all defined people's familiar names.

```

\NewDocumentCommand \peoplename { }
{
  \person_display_list:N \__person_name:n
}

```

`\personsurname` As `\personforenames`, but for the person's surname.

```

\NewDocumentCommand \personsurname { 0{anon} }
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \__person_surname:n { \l_person_label_tl }
  }
}

\cs_new:Nn \__person_surname:n
{
  \tl_use:c { person@ #1 @surname }
}
\cs_generate_variant:Nn \__person_surname:n { x }

```

`\peoplesurname` List all defined people's surnames.

```

\NewDocumentCommand \peoplesurname { }
{
  \person_display_list:N \__person_surname:n
}

```

`\persontitlesurname` The person's title and surname or full name can be displayed using `\persontitlesurname` [`<label>`], where `<label>` is the unique label used when defining that person. If `<label>` is omitted, `anon` is used.

```

\NewDocumentCommand \persontitlesurname { 0{anon} }
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {

```

```

    \__person_title_surname:n { \l_person_label_tl }
  }
}
\cs_new:Nn \__person_title_surname:n
{
  \tl_if_empty:cTF { person@ #1 @surname }
  { \__person_full_name:n { #1 } }
  {
    \tl_if_empty:cTF { person@#1@title }
    { \__person_full_name:n { #1 } }
    {
      \tl_use:c { person@ #1 @title }
      \persontitlesurnamesep
      \tl_use:c { person@ #1 @surname}
    }
  }
}

```

\persontitlesurnamesep

```

\ExplSyntaxOff
\newcommand{\persontitlesurnamesep}{\ }
\ExplSyntaxOn

```

\peopletitlesurname List all defined people's title and surname or full names. This iterates through all labels in \@people@list.

```

\NewDocumentCommand \peopletitlesurname { }
{
  \person_display_list:N \__person_title_surname:n
}

```

30.7 Displaying Language-Sensitive Information

Display language text for a given person identified by their label.

```

\cs_new:Nn \__person_language:nn
{
  \person_get_localisation:vn
  { person@ #1 @gender } { #2 }
}
\cs_generate_variant:Nn \__person_language:nn { xn }

```

Sentence case:

```

\cs_new:Nn \__person_Language:nn
{
  \text_titlecase_first:n
  {
    \__person_language:nn { #1 } { #2 }
  }
}
\cs_generate_variant:Nn \__person_Language:nn { xn }

```

Common function for higher level user commands. No case-change:

```
\cs_new:Nn \person_language_text:nn
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \__person_language:nn { \l_person_label_tl } { #2 }
  }
}
```

Sentence case:

```
\cs_new:Nn \person_Language_text:nn
{
  \person_set_label:n { #1 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \__person_Language:nn { \l_person_label_tl } { #2 }
  }
}
```

Plural, unless only one person defined. The argument is the language tag.

```
\cs_new:Nn \person_language_all_text:n
{
  \__person_case:nnn
  {
    \PackageWarning { person } { No ~ people ~ defined }
    \person_get_localisation:nn { unknown } { plural#1 }
  }
  {
    \exp_args:Nx \person_language_text:nn
    { \seq_item:Nn \l__person_people_seq { 1 } } { #1 }
  }
  {
    \person_all_gender_case:nnnn
    {
      \person_get_localisation:nn { male } { plural#1 }
    }
    {
      \person_get_localisation:nn { female } { plural#1 }
    }
    {
      \person_get_localisation:nn { nonbinary } { plural#1 }
    }
    {
      \person_get_localisation:nn { unknown } { plural#1 }
    }
  }
}
```

Sentence case:

```
\cs_new:Nn \person_Language_all_text:n
```

```

{
  \__person_case:nnn
  {
    \PackageWarning { person } { No ~ people ~ defined }
    \text_titlecase_first:n
    {
      \person_get_localisation:nn { unknown } { plural#1 }
    }
  }
  {
    \exp_args:Nx \person_Language_text:nn
    { \seq_item:Nn \l__person_people_seq { 1 } } { #1 }
  }
  {
    \person_all_gender_case:nnnn
    {
      \text_titlecase_first:n
      {
        \person_get_localisation:nn { male } { plural#1 }
      }
    }
    {
      \text_titlecase_first:n
      {
        \person_get_localisation:nn { female } { plural#1 }
      }
    }
    {
      \text_titlecase_first:n
      {
        \person_get_localisation:nn { nonbinary } { plural#1 }
      }
    }
    {
      \text_titlecase_first:n
      {
        \person_get_localisation:nn { unknown } { plural#1 }
      }
    }
  }
}

```

30.7.1 Third-Person Reference

`\personpronoun` Display the pronoun according to the person's gender.

```

\NewDocumentCommand \personpronoun { 0{anon} }
{
  \person_language_text:nn { #1 } { pronoun }
}

```

`\Personpronoun` As above, but make the first letter uppercase.
`\NewDocumentCommand \Personpronoun { 0{anon} }`
`{`
`\person_Language_text:nn { #1 } { pronoun }`
`}`

`\peoplepronoun` Pronoun for all defined people.
`\NewDocumentCommand \peoplepronoun { }`
`{`
`\person_language_all_text:n { pronoun }`
`}`

`\Peoplepronoun` As above, but first letter in upper case.
`\NewDocumentCommand \Peoplepronoun { }`
`{`
`\person_Language_all_text:n { pronoun }`
`}`

`\personobjpronoun` Display the objective pronoun according to the person's gender.
`\NewDocumentCommand \personobjpronoun { 0{anon} }`
`{`
`\person_language_text:nn { #1 } { objpronoun }`
`}`

`\Personobjpronoun` As above, but make the first letter uppercase.
`\NewDocumentCommand \Personobjpronoun { 0{anon} }`
`{`
`\person_Language_text:nn { #1 } { objpronoun }`
`}`

`\peopleobjpronoun` Objective pronoun for all defined people.
`\NewDocumentCommand \peopleobjpronoun { }`
`{`
`\person_language_all_text:n { objpronoun }`
`}`

`\Peopleobjpronoun` As above, but first letter in upper case
`\NewDocumentCommand \Peopleobjpronoun { }`
`{`
`\person_Language_all_text:n { objpronoun }`
`}`

`\personpossadj` Display the possessive adjective according to the person's gender.
`\NewDocumentCommand \personpossadj { 0{anon} }`
`{`
`\person_language_text:nn { #1 } { possadj }`
`}`

`\Personpossadj` As above, but make the first letter uppercase.
`\NewDocumentCommand \Personpossadj { 0{anon} }`
`{`
`\person_Language_text:nn { #1 } { possadj }`
`}`

`\peoplepossadj` Possessive adjective for all defined people.
`\NewDocumentCommand \peoplepossadj { }`
`{`
`\person_language_all_text:n { possadj }`
`}`

`\Peoplepossadj` As above, but first letter in upper case.
`\NewDocumentCommand \Peoplepossadj { }`
`{`
`\person_Language_all_text:n { possadj }`
`}`

`\personposspronoun` Display possessive pronoun according to the person's gender.
`\NewDocumentCommand \personposspronoun { 0{anon} }`
`{`
`\person_language_text:nn { #1 } { posspronoun }`
`}`

`\Personposspronoun` As above, but make the first letter uppercase.
`\NewDocumentCommand \Personposspronoun { 0{anon} }`
`{`
`\person_Language_text:nn { #1 } { posspronoun }`
`}`

`\peopleposspronoun` Possessive pronoun for all defined people.
`\NewDocumentCommand \peopleposspronoun { }`
`{`
`\person_language_all_text:n { posspronoun }`
`}`

`\Peopleposspronoun` As above, but first letter in upper case
`\NewDocumentCommand \Peopleposspronoun { }`
`{`
`\person_Language_all_text:n { posspronoun }`
`}`

30.7.2 Second-Person Reference

`\personpronounii` Display the pronoun according to the person's gender.
`\NewDocumentCommand \personpronounii { 0{anon} }`
`{`
`\person_language_text:nn { #1 } { pronoun2 }`
`}`

`\Personpronounii` As above, but make the first letter uppercase.
`\NewDocumentCommand \Personpronounii { 0{anon} }`
`{`
`\person_Language_text:nn { #1 } { pronoun2 }`
`}`

`\peoplepronounii` Pronoun for all defined people.
`\NewDocumentCommand \peoplepronounii { }`
`{`
`\person_language_all_text:n { pronoun2 }`
`}`

`\Peoplepronounii` As above, but first letter in upper case.
`\NewDocumentCommand \Peoplepronounii { }`
`{`
`\person_Language_all_text:n { pronoun2 }`
`}`

`\personobjpronounii` Display the objective pronoun according to the person's gender.
`\NewDocumentCommand \personobjpronounii { 0{anon} }`
`{`
`\person_language_text:nn { #1 } { objpronoun2 }`
`}`

`\Personobjpronounii` As above, but make the first letter uppercase.
`\NewDocumentCommand \Personobjpronounii { 0{anon} }`
`{`
`\person_Language_text:nn { #1 } { objpronoun2 }`
`}`

`\peopleobjpronounii` Objective pronoun for all defined people.
`\NewDocumentCommand \peopleobjpronounii { }`
`{`
`\person_language_all_text:n { objpronoun2 }`
`}`

`\Peopleobjpronounii` As above, but first letter in upper case
`\NewDocumentCommand \Peopleobjpronounii { }`
`{`
`\person_Language_all_text:n { objpronoun2 }`
`}`

`\personpossadjii` Display the possessive adjective according to the person's gender.
`\NewDocumentCommand \personpossadjii { 0{anon} }`
`{`
`\person_language_text:nn { #1 } { possadj2 }`
`}`

`\Personpossadjii` As above, but make the first letter uppercase.
`\NewDocumentCommand \Personpossadjii { 0{anon} }`
`{`
`\person_Language_text:nn { #1 } { possadj2 }`
`}`

`\peoplepossadjii` Possessive adjective for all defined people.
`\NewDocumentCommand \peoplepossadjii { }`
`{`
`\person_language_all_text:n { possadj2 }`
`}`

`\Peoplepossadjii` As above, but first letter in upper case.
`\NewDocumentCommand \Peoplepossadjii { }`
`{`
`\person_Language_all_text:n { possadj2 }`
`}`

`\personposspronounii` Display possessive pronoun according to the person's gender.
`\NewDocumentCommand \personposspronounii { 0{anon} }`
`{`
`\person_language_text:nn { #1 } { posspronoun2 }`
`}`

`\Personposspronounii` As above, but make the first letter uppercase.
`\NewDocumentCommand \Personposspronounii { 0{anon} }`
`{`
`\person_Language_text:nn { #1 } { posspronoun2 }`
`}`

`\peopleposspronounii` Possessive pronoun for all defined people.
`\NewDocumentCommand \peopleposspronounii { }`
`{`
`\person_language_all_text:n { posspronoun2 }`
`}`

`\Peopleposspronounii` As above, but first letter in upper case
`\NewDocumentCommand \Peopleposspronounii { }`
`{`
`\person_Language_all_text:n { posspronoun2 }`
`}`

30.7.3 Relationship Reference

`\personchild` Display this person's relationship to their parent.
`\NewDocumentCommand \personchild { 0{anon} }`
`{`
`\person_language_text:nn { #1 } { child }`
`}`

`\Personchild` As above, but make first letter uppercase.
`\NewDocumentCommand \Personchild { 0{anon} }`
`{`
`\person_Language_text:nn { #1 } { child }`
`}`

`\peoplechild` Child relationship for all. (That is, all defined people have the same parents.)
`\NewDocumentCommand \peoplechild { }`
`{`
`\person_language_all_text:n { child }`
`}`

`\Peoplechild` As above but first letter is made uppercase.
`\NewDocumentCommand \Peoplechild { }`
`{`
`\person_Language_all_text:n { child }`
`}`

`\personparent` Display this person's relationship to their child (father / mother / parent).
`\NewDocumentCommand \personparent { 0{anon} }`
`{`
`\person_language_text:nn { #1 } { parent }`
`}`

`\Personparent` As above, but make the first letter uppercase.
`\NewDocumentCommand \Personparent { 0{anon} }`
`{`
`\person_Language_text:nn { #1 } { parent }`
`}`

`\peopleparent` The parental term for all defined people.
`\NewDocumentCommand \peopleparent { }`
`{`
`\person_language_all_text:n { parent }`
`}`

`\Peopleparent` As above, but make first letter uppercase.
`\NewDocumentCommand \Peopleparent { }`
`{`
`\person_Language_all_text:n { parent }`
`}`

`\personsibling` Display this person's relationship to their siblings.
`\NewDocumentCommand \personsibling { 0{anon} }`
`{`
`\person_language_text:nn { #1 } { sibling }`
`}`

`\Person sibling` As above but make first letter uppercase.

```

\NewDocumentCommand \Person sibling { O{anon} }
{
  \person_Language_text:nn { #1 } { sibling }
}

```

`\people sibling` Sibling term for all defined people.

```

\NewDocumentCommand \people sibling { }
{
  \person_language_all_text:n { sibling }
}

```

`\Peoplesibling`

```

\NewDocumentCommand \Peoplesibling { }
{
  \person_Language_all_text:n { sibling }
}

```

30.8 Extracting Information

`\person gender` Displays the given person's gender using localisation.

```

\NewDocumentCommand \person gender { m }
{
  \person_language_text:nn { #1 } { gender }
}

```

`\Person gender` As above but converts the first letter to uppercase.

```

\NewDocumentCommand \Person gender { m }
{
  \person_Language_text:nn { #1 } { gender }
}

```

`\getperson gender` Gets person's gender name (language-sensitive) and stores in first argument which must be a control sequence.

```

\NewDocumentCommand \getperson gender { m m }
{
  \person_set_label:n { #2 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \tl_set:Ne #1
    { \__person_language:nn { \l_person_label_tl } { gender } }
  }
}

```

`\getperson gender label` Gets person's internal gender label and stores in first argument which must be a control sequence.

```

\NewDocumentCommand \getperson gender label { m m }
{

```

```

\person_set_label:n { #2 }
\person_if_exist_or_err:nT { \l_person_label_tl }
{
  \tl_set:Nx #1
  { person@ \l_person_label_tl @gender }
}
}

```

`\getpersonname` Gets person's name and stores in first argument which must be a control sequence.

```

\NewDocumentCommand \getpersonname { m m }
{
  \person_set_label:n { #2 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \tl_set_eq:Nc #1
    { person@ \l_person_label_tl @name }
  }
}

```

`\getpersonforenames` Gets person's forenames and stores in first argument which must be a control sequence.

```

\NewDocumentCommand \getpersonforenames { m m }
{
  \person_set_label:n { #2 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \tl_set_eq:Nc #1
    { person@ \l_person_label_tl @forenames }
  }
}

```

`\getpersonfullname` Gets person's full name and stores in first argument which must be a control sequence.

```

\NewDocumentCommand \getpersonfullname { m m }
{
  \person_set_label:n { #2 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \tl_set_eq:Nc #1
    { person@ \l_person_label_tl @fullname }
  }
}

```

`\getpersonsurname` Gets person's surname and stores in first argument which must be a control sequence.

```

\NewDocumentCommand \getpersonsurname { m m }
{
  \person_set_label:n { #2 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {

```

```

    \tl_set_eq:Nc #1
    { person@ \l_person_label_tl @surname }
  }
}

```

`\getpersontitle` Gets person's title and stores in first argument which must be a control sequence.

```

\NewDocumentCommand \getpersontitle { m m }
{
  \person_set_label:n { #2 }
  \person_if_exist_or_err:nT { \l_person_label_tl }
  {
    \tl_set_eq:Nc #1
    { person@ \l_person_label_tl @title }
  }
}
\ExplSyntaxOff

```

30.9 Localisation Support

`\RequirePersonDialect`

```

\newcommand*{\RequirePersonDialect}[1]{%
  \TrackLangRequireDialect{person}{#1}%
}

\datatool@load@locales{%
  \AnyTrackedLanguages
  {%
    \ForEachTrackedDialect{\@dtl@thisdialect}%
    {%
      \RequirePersonDialect{\@dtl@thisdialect}%
    }%
  }%
  {}%
}

```

30.10 Rollback v2.32 (databar-2019-09-27.sty)

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{databar}[2019/09/27 v2.32 (NLCT)]
\RequirePackage{xkeyval}
\RequirePackage{dataplot}[=v2.32]
\newif\ifDTLcolorbarchart
\DTLcolorbarcharttrue
\DeclareOption{color}{\DTLcolorbarcharttrue}
\DeclareOption{gray}{\DTLcolorbarchartfalse}
\newcommand*{\DTLbarXlabelalign}{left,rotate=-90}
\newcommand*{\DTLbarYticklabelalign}{right}
\define@boolkey{databar}[DTL]{verticalbars}[true]{%

```

```

\ifDTLverticalbars
\def\DTLbarXlabelalign{left,rotate=-90}%
\def\DTLbarYticklabelalign{right}
\else
\def\DTLbarXlabelalign{right}%
\def\DTLbarYticklabelalign{center}
\fi}
\DTLverticalbarstrue
\DeclareOption{vertical}{\DTLverticalbarstrue
\def\DTLbarXlabelalign{left,rotate=-90}%
\def\DTLbarYticklabelalign{right}
}
\DeclareOption{horizontal}{\DTLverticalbarsfalse
\def\DTLbarXlabelalign{right}%
\def\DTLbarYticklabelalign{center}
}
\ProcessOptions
\RequirePackage{datatool}[=v2.32]
\RequirePackage{tikz}
\newlength\DTLbarchartlength
\DTLbarchartlength=3in
\newlength\DTLbarwidth
\DTLbarwidth=1cm
\newlength\DTLbarlabeloffset
\setlength\DTLbarlabeloffset{10pt}
\newcommand*\DTLBarXAxisStyle{-}
\newcommand*\DTLBarYAxisStyle{-}
\newcounter{DTLbarroundvar}
\setcounter{DTLbarroundvar}{1}
\newcommand*\DTLbardisplayYticklabel}[1]{#1}
\newcommand*\DTLdisplaylowerbarlabel}[1]{#1}
\newcommand*\DTLdisplaylowermultibarlabel}[1]{#1}
\newcommand*\DTLdisplayupperbarlabel}[1]{#1}
\newcommand*\DTLdisplayuppermultibarlabel}[1]{#1}
\newcommand*\DTLbaratbegintikz{}
\newcommand*\DTLbaratendtikz{}
\newif\ifDTLbarxaxis
\newif\ifDTLbaryaxis
\newif\ifDTLbarytics
\newcount\@dtl@barcount
\newcommand*\DTLsetbarcolor}[2]{%
\expandafter\def\csname dtlbar@segcol\romannumeral#1\endcsname{#2}%
}
\newcommand*\DTLgetbarcolor}[1]{%
\csname dtlbar@segcol\romannumeral#1\endcsname}
\newcommand*\DTLdobarcolor}[1]{%
\expandafter\color\expandafter
{\csname dtlbar@segcol\romannumeral#1\endcsname}}
\newcommand*\DTLdocurrentbarcolor}{%
\ifnum\dtlforeachlevel=0\relax

```

```

\PackageError{databar}{Can't use
\string\DTLdocurrentbarcolor\space outside
\string\DTLbarchart}{}%
\else
\expandafter\DTLdobarcolor\expandafter{%
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname}%
\fi}
\newcommand*\DTLbaroutlinecolor}{black}
\newlength\DTLbaroutlinewidth
\DTLbaroutlinewidth=0pt
\ifDTLcolorbarchart
\DTLsetbarcolor{1}{red}
\DTLsetbarcolor{2}{green}
\DTLsetbarcolor{3}{blue}
\DTLsetbarcolor{4}{yellow}
\DTLsetbarcolor{5}{magenta}
\DTLsetbarcolor{6}{cyan}
\DTLsetbarcolor{7}{orange}
\DTLsetbarcolor{8}{white}
\else
\DTLsetbarcolor{1}{black!15}
\DTLsetbarcolor{2}{black!25}
\DTLsetbarcolor{3}{black!35}
\DTLsetbarcolor{4}{black!45}
\DTLsetbarcolor{5}{black!55}
\DTLsetbarcolor{6}{black!65}
\DTLsetbarcolor{7}{black!75}
\DTLsetbarcolor{8}{black!85}
\fi
\newcommand*\DTLeverybarhook}{}
\define@key{databar}{max}{\def\DTLbarmax{#1}}
\define@key{databar}{length}{\DTLbarchartlength=#1\relax
}
\define@key{databar}{maxdepth}{%
\ifnum#1>0\relax
\PackageError{databar}{depth must be zero or negative}{}%
\else
\def\DTLnegextent{#1}%
\fi}
\define@choicekey{databar}{axes}[\var\nr]{both,x,y,none}{%
\ifcase\nr\relax
% both
\DTLbarxaxistrue
\DTLbaryaxistrue
\DTLbaryticstrue
\or
% x only
\DTLbarxaxistrue
\DTLbaryaxisfalse
\DTLbaryticsfalse

```

```

\or
% y only
\DTLbarxaxisfalse
\DTLbaryaxistrue
\DTLbaryticstrue
\or
% neither
\DTLbarxaxisfalse
\DTLbaryaxisfalse
\DTLbaryticsfalse
\fi
}
\define@key{databar}{variable}{%
\def\DTLbarvariable{#1}%
}
\define@key{databar}{variables}{%
\def\dtlbar@variables{#1}%
}
\define@key{databar}{barwidth}{\set length{\DTLbarwidth}{#1}}
\define@key{databar}{bar label}{%
\def\dtl@bar label{#1}}
\def\dtl@bar label{}
\define@key{databar}{multibar labels}{%
\def\dtl@multibar labels{#1}}
\def\dtl@multibar labels{}
\define@key{databar}{groupgap}{\def\dtlbar@groupgap{#1}}
\def\dtlbar@groupgap{1}
\define@key{databar}{upperbar label}{%
\def\dtl@upperbar label{#1}}
\def\dtl@upperbar label{}
\define@key{databar}{uppermultibar labels}{%
\def\dtl@uppermultibar labels{#1}}
\def\dtl@uppermultibar labels{}
\define@key{databar}{yticpoints}{%
\def\dtlbar@ytic list{#1}\DTLbaryticstrue\DTLbaryaxistrue}
\let\dtlbar@ytic list=\relax
\define@key{databar}{yticgap}{%
\def\dtlbar@ytic gap{#1}\DTLbaryticstrue\DTLbaryaxistrue}
\let\dtlbar@ytic gap=\relax
\define@key{databar}{ytic labels}{%
\def\dtlbar@ytic labels{#1}\DTLbaryticstrue\DTLbaryaxistrue}
\let\dtlbar@ytic labels=\relax
\define@key{databar}{ylabel}{%
\def\dtlbar@ylabel{#1}}
\let\dtlbar@ylabel=\relax
\newcommand*{\DTLbarchart}[4][\boolean{true}]{%
%
\undef\DTLbarvariable
\undef\DTLbarmax
\undef\DTLnegextent

```

```

\disable@keys{databar}{variables,multibarlabels,%
  uppermultibarlabels,groupgap}%
\setkeys{databar}{#2}%
\ifundef{\DTLbarvariable}%
{%
  \PackageError{databar}%
  {\string\DTLbarchart\space missing variable}%
  {You haven't use the "variable" key}%
}%
\ifundef{\DTLbarmax}%
{%
  \@sDTLforeach[#1]{#3}{#4}{%
    \expandafter\DTLconverttodecimal\expandafter
    {\DTLbarvariable}{\dtl@barvar}%
    \ifundef{\DTLbarmax}%
    {%
      \let\DTLbarmax=\dtl@barvar
    }%
    {%
      \let\dtl@old=\DTLbarmax
      \dtlmax{\DTLbarmax}{\dtl@old}{\dtl@barvar}%
    }%
  }%
  \ifx\dtlbar@yticgap\relax
  \else
    \let\dtl@thistick=\dtlbar@yticgap
    \whiledo{\DTLisFPopenbetween{\dtl@thistick}{0}{\DTLbarmax}}%
    {%
      \dtladd{\dtl@thistick}{\dtl@thistick}{\dtlbar@yticgap}%
    }%
    \let\DTLbarmax=\dtl@thistick
  \fi
}%
}%
\ifundef{\DTLnegextent}%
{%
  \def\DTLnegextent{0}%
  \@sDTLforeach[#1]{#3}{#4}{%
    \expandafter\DTLconverttodecimal\expandafter
    {\DTLbarvariable}{\dtl@barvar}%
    \let\dtl@old=\DTLnegextent
    \DTLmin{\DTLnegextent}{\dtl@old}{\dtl@barvar}%
  }%
  \ifx\dtlbar@yticgap\relax
  \else
    \ifthenelse{\DTLisFPgt{\DTLnegextent}{0}}%
    {%
      \edef\dtl@thistick{0}%
      \whiledo{\DTLisFPclosedbetween{\dtl@thistick}{\DTLnegextent}{0}}{%

```

```

        \dtlsub{\dtl@thistick}{\dtl@thistick}{\dtlbar@yticgap}%
    }%
    \let\DTLnegextent=\dtl@thistick
    }{}%
\fi
}%
{}%
\@dtl@tmpcount=\DTLbarchartlength
\dtlsub{\dtl@extent}{\DTLbarmax}{\DTLnegextent}%
\dtldiv{\dtl@unit}{\number\@dtl@tmpcount}{\dtl@extent}%
\setlength{\dtl@yticlabelwidth}{0pt}%
\ifDTLbarytics
\ifx\dtlbar@yticlist\relax
\ifx\dtlbar@yticgap\relax
\@dtl@tmpcount=\DTLmintickgap
\divide\@dtl@tmpcount by 65536\relax
\dtldiv{\dtl@mingap}{\number\@dtl@tmpcount}{\dtl@unit}%
\dtl@constructticklist\DTLnegextent\DTLbarmax
\dtl@mingap\dtlbar@yticlist
\else
\dtl@constructticklistwithgapz
\DTLnegextent\DTLbarmax\dtlbar@yticlist\dtlbar@yticgap
\fi
\fi
\ifx\dtlbar@ylabel\relax
\else
\ifx\dtlbar@yticlabels\relax
\@for\dtl@thislabel:=\dtlbar@yticlist\do{%
\dtlround{\dtl@thislabel}{\dtl@thislabel}
{\c@DTLbarroundvar}%
\ifDTLverticalbars
\settowidth{\dtl@tmplength}{%
\DTLbardisplayYticklabel{\dtl@thislabel}}%
\else
\settoheight{\dtl@tmplength}{%
\DTLbardisplayYticklabel{\dtl@thislabel}}%
\edef\@dtl@h{\the\dtl@tmplength}%
\settodepth{\dtl@tmplength}{%
\DTLbardisplayYticklabel{\dtl@thislabel}}%
\addtolength{\dtl@tmplength}{\@dtl@h}%
\addtolength{\dtl@tmplength}{\baselineskip}%
\fi
\ifdim\dtl@tmplength>\dtl@yticlabelwidth
\setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
\fi
}%
\else
\@for\dtl@thislabel:=\dtlbar@yticlabels\do{%
\ifDTLverticalbars
\settowidth{\dtl@tmplength}{%

```

```

        \DTLbardisplayYticklabel{\dtl@thislabel}}%
\else
  \settoheight{\dtl@tmplength}{%
    \DTLbardisplayYticklabel{\dtl@thislabel}}%
  \edef\@dtl@h{\the\dtl@tmplength}%
  \settodepth{\dtl@tmplength}{%
    \DTLbardisplayYticklabel{\dtl@thislabel}}%
  \addtolength{\dtl@tmplength}{\@dtl@h}%
  \addtolength{\dtl@tmplength}{\baselineskip}%
\fi
\ifdim\dtl@tmplength>\dtl@yticlabelwidth
  \setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
\fi
}%
\fi
\fi
\fi
\edef\DTLbarchartwidth{\expandafter\number\csname dtlrows@#3\endcsname}
\begin{tikzpicture}
\ifDTLverticalbars
  \pgfsetyvec{\pgfpoint{0pt}{\dtl@unit sp}}%
  \pgfsetxvec{\pgfpoint{\DTLbarwidth}{0pt}}%
\else
  \pgfsetxvec{\pgfpoint{\dtl@unit sp}{0pt}}%
  \pgfsetyvec{\pgfpoint{0pt}{\DTLbarwidth}}%
\fi
\DTLbaratbegintikz
\def\@dtl@start{0}%
\@sDTLforeach[#1]{#3}{#4}{%
\expandafter\let\expandafter\@dtl@bar
  \csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname%
\expandafter\DTLconverttodecimal\expandafter
  {\DTLbarvariable}{\dtl@variable}%
\begin{scope}
  \DTLdocurrentbarcolor
  \ifDTLverticalbars
    \fill (\@dtl@start,0) -- (\@dtl@start,\dtl@variable)
      -- (\@dtl@bar,\dtl@variable) -- (\@dtl@bar,0) -- cycle;
  \else
    \fill (0,\@dtl@start) -- (\dtl@variable,\@dtl@start)
      -- (\dtl@variable,\@dtl@bar) -- (0,\@dtl@bar) -- cycle;
  \fi
\end{scope}
\begin{scope}
\ifdim\DTLbaroutlinewidth>0pt
  \expandafter\color\expandafter{\DTLbaroutlinecolor}
  \ifDTLverticalbars
    \draw (\@dtl@start,0) -- (\@dtl@start,\dtl@variable)
      -- (\@dtl@bar,\dtl@variable) -- (\@dtl@bar,0) -- cycle;
  \else

```

```

\draw (0,\@dtl@start) -- (\dtl@variable,\@dtl@start)
-- (\dtl@variable,\@dtl@bar) -- (0,\@dtl@bar) -- cycle;
\fi
\fi
\end{scope}
\ifDTLverticalbars
\edef\dtl@textopt{%
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{\@dtl@start.5}{0}}
{\noexpand\pgfpoint{0pt}{-\noexpand\DTLbarlabeloffset}}},
\DTLbarXlabelalign
}%
\edef\DTLstarttpt{\noexpand\pgfpointxy{\@dtl@start.5}{0}}%
\else
\edef\dtl@textopt{%
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{0}{\@dtl@start.5}}
{\noexpand\pgfpoint{-\noexpand\DTLbarlabeloffset}{0pt}}},
\DTLbarXlabelalign
}%
\edef\DTLstarttpt{\noexpand\pgfpointxy{0}{\@dtl@start.5}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
\DTLdisplaylowerbarlabel{\dtl@barlabel}}
\ifDTLverticalbars
\expandafter\DTLifnumlt\expandafter{\DTLbarvariable}{0}%
{
\edef\dtl@textopt{%
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{\@dtl@start.5}{\dtl@variable}}
{\noexpand\pgfpoint{0pt}{-\noexpand\DTLbarlabeloffset}}}}
}%
}%
\edef\dtl@textopt{%
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{\@dtl@start.5}{\dtl@variable}}
{\noexpand\pgfpoint{0pt}{\noexpand\DTLbarlabeloffset}}}}
}%
}
\edef\DTLendpt{\noexpand\pgfpointxy{\@dtl@start.5}{\dtl@variable}}%
\else
\expandafter\DTLifnumlt\expandafter{\DTLbarvariable}{0}%
{
\edef\dtl@textopt{right,
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{\dtl@variable}{\@dtl@start.5}}
{\noexpand\pgfpoint{-\noexpand\DTLbarlabeloffset}{0pt}}}}
}%
}%
\edef\dtl@textopt{left,

```

```

        at={\noexpand\pgfpointadd
            {\noexpand\pgfpointxy{\dtl@variable}{\@dtl@start.5}}
            {\noexpand\pgfpoint{\noexpand\DTLbarlabeloffset}{0pt}}}
    }%
}
\edef\DTLendpt{\noexpand\pgfpointxy{\dtl@variable}{\@dtl@start.5}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
    \DTLdisplayupperbarlabel{\dtl@upperbarlabel}}
\def\DTLmidpt{\pgfpointlineattime{0.5}{\DTLstartpt}{\DTLendpt}}%
\DTLeverybarhook
\edef\@dtl@start{\number\@dtl@bar}%
}%
\ifDTLbarxaxis
\ifDTLverticalbars
\expandafter\draw\expandafter[\DTLBarXAxisStyle]
(0,0) -- (\DTLbarchartwidth,0);
\else
\expandafter\draw\expandafter[\DTLBarXAxisStyle]
(0,0) -- (0,\DTLbarchartwidth);
\fi
\fi
\ifDTLbaryaxis
\ifDTLverticalbars
\expandafter\draw\expandafter[\DTLBarYAxisStyle]
(0,\DTLnegextent) -- (0,\DTLbarmax);
\else
\expandafter\draw\expandafter[\DTLBarYAxisStyle]
(\DTLnegextent,0) -- (\DTLbarmax,0);
\fi
\fi
\fi
\ifx\dtlbar@yticlist\relax
\else
\@for\dtl@thistick:=\dtlbar@yticlist\do{%
\ifDTLverticalbars
\pgfpathmoveto{\pgfpointxy{0}{\dtl@thistick}}
\pgfpathlineto{
\pgfpointadd{\pgfpointxy{0}{\dtl@thistick}}
{\pgfpoint{-\DTLticklength}{0pt}}}
\else
\pgfpathmoveto{\pgfpointxy{\dtl@thistick}{0}}
\pgfpathlineto{
\pgfpointadd{\pgfpointxy{\dtl@thistick}{0}}
{\pgfpoint{0pt}{-\DTLticklength}}}
\fi
\pgfusepath{stroke}
\ifx\dtlbar@yticlabels\relax
\dtlround{\dtl@thislabel}{\dtl@thistick}
{\c@DTLbarroundvar}%
\else

```

```

\dtl@chopfirst\dtlbar@yticlabels\dtl@thislabel\dtl@rest
\let\dtlbar@yticlabels=\dtl@rest
\fi
\ifDTLverticalbars
\edef\dtl@textopt{\DTLbarYticklabelalign,%
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{0}{\dtl@thistick}}
{\noexpand\pgfpoint{-\noexpand\DTLticklabeloffset}{0pt}},
}}%
\else
\edef\dtl@textopt{\DTLbarYticklabelalign,
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{\dtl@thistick}{0}}
{\noexpand\pgfpoint{0pt}{-\noexpand\DTLticklabeloffset}}
}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
\DTLbardisplayYticklabel{\dtl@thislabel}}
}%
\fi
\ifx\dtlbar@ylabel\relax
\else
\addtolength{\dtl@yticlabelwidth}{\baselineskip}%
\setlength{\dtl@tmplength}{0.5\DTLbarchartlength}
\ifDTLverticalbars
\pgftext[bottom,center,at={\pgfpointadd
{\pgfpointxy{0}{\DTLnegextent}}%
{\pgfpoint{-\dtl@yticlabelwidth}{\dtl@tmplength}}},
rotate=90]{%
\dtlbar@ylabel}
\else
\pgftext[bottom,center,at={\pgfpointadd
{\pgfpointxy{\DTLnegextent}{0}}%
{\pgfpoint{\dtl@tmplength}{-\dtl@yticlabelwidth}}}]{%
\dtlbar@ylabel}
\fi
\fi
\DTLbaratendtikz
\end{tikzpicture}
}%
}
\newcommand*{\DTLmultibarchart}[4][\boolean{true}]{%
{\let\dtlbar@variables=\relax
\let\DTLbarmax=\relax
\let\DTLnegextent=\relax
\disable@keys{databar}{variable,upperbarlabel}%
\setkeys{databar}{#2}%
\ifx\dtlbar@variables\relax
\PackageError{databar}{\string\DTLmultibarchart\space missing variables setting}{%

```

```

\else
  \ifx\DTLbarmax\relax
    \@sDTLforeach[#1]{#3}{#4}{%
      \@for\DTLbarvariable:=\dtlbar@variables\do{%
        \expandafter\DTLconverttodecimal\expandafter
          {\DTLbarvariable}{\dtl@barvar}%
        \ifx\DTLbarmax\relax
          \let\DTLbarmax=\dtl@barvar
        \else
          \let\dtl@old=\DTLbarmax
          \dtlmax{\DTLbarmax}{\dtl@old}{\dtl@barvar}%
        \fi
      }%
    }%
  \ifx\dtlbar@yticgap\relax
  \else
    \let\dtl@thistick=\dtlbar@yticgap%
    \whiledo{\DTLisFPopenbetween{\dtl@thistick}{0}{\DTLbarmax}}{%
      \dtladd{\dtl@thistick}{\dtl@thistick}{\dtlbar@yticgap}%
    }%
    \let\DTLbarmax=\dtl@thistick
  \fi
\fi
\ifx\DTLnegextent\relax
\def\DTLnegextent{0}%
\@sDTLforeach[#1]{#3}{#4}{%
  \@for\DTLbarvariable:=\dtlbar@variables\do{%
    \expandafter\DTLconverttodecimal\expandafter
      {\DTLbarvariable}{\dtl@barvar}%
    \let\dtl@old=\DTLnegextent
    \DTLmin{\DTLnegextent}{\dtl@old}{\dtl@barvar}%
  }%
}%
\ifx\dtlbar@yticgap\relax
\else
  \ifthenelse{\DTLisFPgt{\DTLnegextent}{0}}{%
    \edef\dtl@thistick{0}%
    \whiledo{\DTLisFPclosedbetween{\dtl@thistick}{\DTLnegextent}{0}}{%
      \dtlsub{\dtl@thistick}{\dtl@thistick}{\dtlbar@yticgap}%
    }%
    \let\DTLnegextent=\dtl@thistick
  }{%
  }%
\fi
\fi
\@dtl@tmpcount=\DTLbarchartlength
\dtlsub{\dtl@extent}{\DTLbarmax}{\DTLnegextent}%
\dtldiv{\dtl@unit}{\number\@dtl@tmpcount}{\dtl@extent}%
\setlength{\dtl@yticlabelwidth}{0pt}%
\ifDTLbarytics
  \ifx\dtlbar@yticlist\relax

```

```

\ifx\dtlbar@yticgap\relax
  \@dtl@tmpcount=\DTLmintickgap
  \divide\@dtl@tmpcount by 65536\relax
  \dtldiv{\dtl@mingap}{\number\@dtl@tmpcount}{\dtl@unit}%
  \dtl@constructticklist\DTLnegextent\DTLbarmax
  \dtl@mingap\dtlbar@yticlist
\else
  \dtl@constructticklistwithgapz
  \DTLnegextent\DTLbarmax\dtlbar@yticlist\dtlbar@yticgap
\fi
\fi
\ifx\dtlbar@ylabel\relax
\else
  \ifx\dtlbar@yticlabels\relax
    \@for\dtl@thislabel:=\dtlbar@yticlist\do{%
      \dtlround{\dtl@thislabel}{\dtl@thislabel}
      {\c@DTLbarroundvar}%
      \ifDTLverticalbars
        \settowidth{\dtl@tmplength}{%
          \DTLbardisplayYticklabel{\dtl@thislabel}}%
      \else
        \settoheight{\dtl@tmplength}{%
          \DTLbardisplayYticklabel{\dtl@thislabel}}%
        \edef\@dtl@h{\the\dtl@tmplength}%
        \settodepth{\dtl@tmplength}{%
          \DTLbardisplayYticklabel{\dtl@thislabel}}%
        \addtolength{\dtl@tmplength}{\@dtl@h}%
        \addtolength{\dtl@tmplength}{\baselineskip}%
      \fi
      \ifdim\dtl@tmplength>\dtl@yticlabelwidth
        \setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
      \fi
    }%
  \else
    \@for\dtl@thislabel:=\dtlbar@yticlabels\do{%
      \ifDTLverticalbars
        \settowidth{\dtl@tmplength}{%
          \DTLbardisplayYticklabel{\dtl@thislabel}}%
      \else
        \settoheight{\dtl@tmplength}{%
          \DTLbardisplayYticklabel{\dtl@thislabel}}%
        \edef\@dtl@h{\the\dtl@tmplength}%
        \settodepth{\dtl@tmplength}{%
          \DTLbardisplayYticklabel{\dtl@thislabel}}%
        \addtolength{\dtl@tmplength}{\@dtl@h}%
        \addtolength{\dtl@tmplength}{\baselineskip}%
      \fi
      \ifdim\dtl@tmplength>\dtl@yticlabelwidth
        \setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
      \fi
    }%
  \fi

```

```

    }%
    \fi
  \fi
\fi
\dtl@xticlabelheight=0pt\relax
\@dtl@tmpcount=0\relax
\@for\dtl@thislabel:=\dtl@multibarlabels\do{%
  \advance\@dtl@tmpcount by 1\relax
  \settoheight{\dtl@tmplength}{\tikz\expandafter\pgftext\expandafter
    [\DTLbarXlabelalign]{\DTLdisplaylowerbarlabel{\dtl@thislabel}};}%
  \edef\@dtl@h{\the\dtl@tmplength}%
  \settodepth{\dtl@tmplength}{\tikz\expandafter\pgftext\expandafter
    [\DTLbarXlabelalign]{\DTLdisplaylowerbarlabel{\dtl@thislabel}};}%
  \addtolength{\dtl@tmplength}{\@dtl@h}%
  \addtolength{\dtl@tmplength}{\baselineskip}%
  \ifdim\dtl@tmplength>\dtl@xticlabelheight
    \setlength{\dtl@xticlabelheight}{\dtl@tmplength}%
  \fi
}
\@dtl@tmpcount=0\relax
\@for\dtl@this:=\dtlbar@variables\do{%
  \advance\@dtl@tmpcount by 1\relax
}%
\edef\DTLbargroupwidth{\number\@dtl@tmpcount}%
\edef\dtl@n{\expandafter\number\csname dtlrows@#3\endcsname}
\dtl@mul{\dtl@tmpi}{\dtl@n}{\DTLbargroupwidth}
\dtl@sub{\dtl@tmpii}{\dtl@n}{1}%
\dtl@mul{\dtl@tmpii}{\dtl@tmpii}{\dtlbar@groupgap}%
\dtl@ladd{\DTLbarchartwidth}{\dtl@tmpi}{\dtl@tmpii}
\begin{tikzpicture}
\ifDTLverticalbars
  \pgfsetyvec{\pgfpoint{0pt}{\dtl@unit sp}}%
  \pgfsetxvec{\pgfpoint{\DTLbarwidth}{0pt}}%
\else
  \pgfsetxvec{\pgfpoint{\dtl@unit sp}{0pt}}%
  \pgfsetyvec{\pgfpoint{0pt}{\DTLbarwidth}}%
\fi
\DTLbaratbegintikz
\def\@dtl@start{0}%
\@sDTLforeach[#1]{#3}{#4}{%
\@dtl@barcount = 1\relax
\let\dtl@multibar@labels=\dtl@multibarlabels
\let\dtl@uppermultibar@labels=\dtl@uppermultibarlabels
\dtl@mul{\dtl@multimidpt}{\DTLbargroupwidth}{0.5}%
\dtl@ladd{\dtl@multimidpt}{\dtl@multimidpt}{\@dtl@start}%
\@for\DTLbarvariable:=\dtlbar@variables\do{%
\dtl@ladd{\@dtl@endpt}{\@dtl@start}{1}%
\expandafter\DTLconverttodecimal\expandafter
  {\DTLbarvariable}{\dtl@variable}%
\dtl@chopfirst\dtl@multibar@labels\dtl@thisbarlabel\dtl@rest

```

```

\let\dtl@multibar@labels=\dtl@rest
\dtl@chopfirst\dtl@uppermultibar@labels\dtl@thisupperbarlabel\dtl@rest
\let\dtl@uppermultibar@labels=\dtl@rest
\begin{scope}
\expandafter\color\expandafter{\DTLgetbarcolor{\@dtl@barcount}}%
\ifDTLverticalbars
\fill (\@dtl@start,0) -- (\@dtl@start,\dtl@variable)
-- (\@dtl@endpt,\dtl@variable) -- (\@dtl@endpt,0) -- cycle;
\else
\fill (0,\@dtl@start) -- (\dtl@variable,\@dtl@start)
-- (\dtl@variable,\@dtl@endpt) -- (0,\@dtl@endpt) -- cycle;
\fi
\end{scope}
\begin{scope}
\ifdim\DTLbaroutlinewidth>0pt
\expandafter\color\expandafter{\DTLbaroutlinecolor}
\ifDTLverticalbars
\draw (\@dtl@start,0) -- (\@dtl@start,\dtl@variable)
-- (\@dtl@endpt,\dtl@variable) -- (\@dtl@endpt,0) -- cycle;
\else
\draw (0,\@dtl@start) -- (\dtl@variable,\@dtl@start)
-- (\dtl@variable,\@dtl@endpt) -- (0,\@dtl@endpt) -- cycle;
\fi
\fi
\end{scope}
\dtladd{\@dtl@midpt}{\@dtl@start}{0.5}%
\ifDTLverticalbars
\edef\dtl@textopt{%
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{\@dtl@midpt}{0}}
{\noexpand\pgfpoint{0pt}{-\noexpand\DTLbarlabeloffset}}},
\DTLbarXlabelalign
}%
\edef\DTLstartpt{\noexpand\pgfpointxy{\@dtl@midpt}{0}}%
\else
\edef\dtl@textopt{%
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{0}{\@dtl@midpt}}
{\noexpand\pgfpoint{-\noexpand\DTLbarlabeloffset}{0pt}}},
\DTLbarXlabelalign
}%
\edef\DTLstartpt{\noexpand\pgfpointxy{0}{\@dtl@midpt}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
\DTLdisplaylowermultibarlabel{\dtl@thisbarlabel}}
\ifDTLverticalbars
\expandafter\DTLifnumlt\expandafter{\DTLbarvariable}{0}
{
\edef\dtl@textopt{%
at={\noexpand\pgfpointadd

```

```

        {\noexpand\pgfpointxy{\@dtl@midpt}{\dtl@variable}}
        {\noexpand\pgfpoint{0pt}{-\noexpand\DTLbar labeloffset}}}}
    }%
  }{%
    \edef\dtl@textopt{%
      at={\noexpand\pgfpointadd
        {\noexpand\pgfpointxy{\@dtl@midpt}{\dtl@variable}}
        {\noexpand\pgfpoint{0pt}{-\noexpand\DTLbar labeloffset}}}}
    }%
  }
  \edef\DTLendpt{\noexpand\pgfpointxy{\@dtl@midpt}{\dtl@variable}}%
\else
\expandafter\DTLifnumlt\expandafter{\DTLbarvariable}{0}
{
  \edef\dtl@textopt{right,
    at={\noexpand\pgfpointadd
      {\noexpand\pgfpointxy{\dtl@variable}{\@dtl@midpt}}
      {\noexpand\pgfpoint{-\noexpand\DTLbar labeloffset}{0pt}}}}
  }%
} {%
  \edef\dtl@textopt{left,
    at={\noexpand\pgfpointadd
      {\noexpand\pgfpointxy{\dtl@variable}{\@dtl@midpt}}
      {\noexpand\pgfpoint{\noexpand\DTLbar labeloffset}{0pt}}}}
  }%
}
\edef\DTLendpt{\noexpand\pgfpointxy{\dtl@variable}{\@dtl@midpt}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
  \DTLdisplayuppermultibarlabel{\dtl@thisupperbarlabel}}
\def\DTLmidpt{\pgfpointlineatime{0.5}{\DTLstartpt}{\DTLendpt}}%
\DTLeverybarhook
\dtladd{\@dtl@start}{\@dtl@start}{1}%
\advance\@dtl@barcount by 1\relax
}%
\setlength{\dtl@tmplength}{\DTLbar labeloffset}%
\addtolength{\dtl@tmplength}{\dtl@xticlabelheight}%
\ifDTLverticalbars
  \edef\dtl@textopt{%
    at={\noexpand\pgfpointadd
      {\noexpand\pgfpointxy{\dtl@multimidpt}{0}}
      {\noexpand\pgfpoint{0pt}{-\noexpand\dtl@tmplength}}},
    \DTLbarXlabelalign
  }%
\else
  \edef\dtl@textopt{%
    at={\noexpand\pgfpointadd
      {\noexpand\pgfpointxy{0}{\dtl@multimidpt}}
      {\noexpand\pgfpoint{-\noexpand\dtl@tmplength}{0pt}}},
    \DTLbarXlabelalign
  }%

```

```

    }%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
  \DTLdisplaylowerbarlabel{\dtl@barlabel}}
\dtladd{\@dtl@start}{\@dtl@start}{\dtlbar@groupgap}%
}
\ifDTLbarxaxis
  \ifDTLverticalbars
    \expandafter\draw\expandafter[\DTLBarXAxisStyle]
      (0,0) -- (\DTLbarchartwidth,0);
  \else
    \expandafter\draw\expandafter[\DTLBarXAxisStyle]
      (0,0) -- (0,\DTLbarchartwidth);
  \fi
\fi
\ifDTLbaryaxis
  \ifDTLverticalbars
    \expandafter\draw\expandafter[\DTLBarYAxisStyle]
      (0,\DTLnegextent) -- (0,\DTLbarmax);
  \else
    \expandafter\draw\expandafter[\DTLBarYAxisStyle]
      (\DTLnegextent,0) -- (\DTLbarmax,0);
  \fi
\fi
\ifx\dtlbar@yticlist\relax
\else
  \@for\dtl@thistick:=\dtlbar@yticlist\do{%
    \ifDTLverticalbars
      \pgfpathmoveto{\pgfpointxy{0}{\dtl@thistick}}
      \pgfpathlineto{
        \pgfpointadd{\pgfpointxy{0}{\dtl@thistick}}
          {\pgfpoint{-\DTLticklength}{0pt}}}
    \else
      \pgfpathmoveto{\pgfpointxy{\dtl@thistick}{0}}
      \pgfpathlineto{
        \pgfpointadd{\pgfpointxy{\dtl@thistick}{0}}
          {\pgfpoint{0pt}{-\DTLticklength}}}
    \fi
    \pgfusepath{stroke}
    \ifx\dtlbar@yticlabels\relax
      \dtlround{\dtl@thislabel}{\dtl@thistick}
      {\c@DTLbarroundvar}%
    \else
      \dtl@chopfirst\dtlbar@yticlabels\dtl@thislabel\dtl@rest
      \let\dtlbar@yticlabels=\dtl@rest
    \fi
    \ifDTLverticalbars
      \edef\dtl@textopt{\DTLbarYticklabelalign,%
        at={\noexpand\pgfpointadd
          {\noexpand\pgfpointxy{0}{\dtl@thistick}}

```

```

        {\noexpand\pgfpoint{-\noexpand\DTLticklabeloffset}{0pt}},
    }}%
\else
\edef\dtl@textopt{\DTLbarYticklabelalign,
at={\noexpand\pgfpointadd
{\noexpand\pgfpointxy{\dtl@thistick}{0}}
{\noexpand\pgfpoint{0pt}{-\noexpand\DTLticklabeloffset}}}
}}%
\fi
\expandafter\pgftext\expandafter[\dtl@textopt]{%
\DTLbardisplayYticklabel{\dtl@thislabel}}
}%
\fi
\ifx\dtlbar@ylabel\relax
\else
\addtolength{\dtl@yticlabelwidth}{\baselineskip}%
\setlength{\dtl@tmplength}{0.5\DTLbarchartlength}
\ifDTLverticalbars
\pgftext[bottom,center,at={\pgfpointadd
{\pgfpointxy{0}{\DTLnegextent}}%
{\pgfpoint{-\dtl@yticlabelwidth}{\dtl@tmplength}}},
rotate=90]{%
\dtlbar@ylabel}
\else
\pgftext[bottom,center,at={\pgfpointadd
{\pgfpointxy{\DTLnegextent}{0}}%
{\pgfpoint{\dtl@tmplength}{-\dtl@yticlabelwidth}}}]{%
\dtlbar@ylabel}
\fi
\fi
\DTLbaratendtikz
\end{tikzpicture}
\fi
}}

```

30.11 Rollback v2.32 (databib-2019-09-27.sty)

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{databib}[2019/09/27 v2.32 (NLCT)]
\RequirePackage{datatool}[v2.32]
\newcommand*{\dtlbib@style}{plain}
\define@choicekey{databib.sty}{style}{plain,abbrv,alpha}{%
\def\dtlbib@style{#1}}
\ProcessOptionsX
\newcommand*{\DTLloadbbl}[3][\jobname.bbl]{%
\bibliographystyle{databib}%
\if@filesw
\immediate\write\@auxout{\string\bibdata{#3}}%
\fi
\DTLnewdb{#2}%

```

```

\edef\DTLBIBdbname{#2}%
\@input@{#1}
\newcommand*\DTLnewbibrow{\@DTLnewrow{\DTLBIBdbname}}
\newcommand*\DTLnewbibitem}[2]{%
  \@DTLnewbentry{\DTLBIBdbname}{#1}{#2}}
\providecommand*\andname{and}
\providecommand*\ofname{of}
\providecommand*\inname{in}
\providecommand*\etalname{et al.}
\providecommand*\editorname{editor}
\providecommand*\editorsname{editors}
\providecommand*\volumename{volume}
\providecommand*\numbername{number}
\providecommand*\pagesname{pages}
\providecommand*\pagename{page}
\providecommand*\editionname{edition}
\providecommand*\techreportname{Technical report}
\providecommand*\mscthesishname{Master's thesis}
\providecommand*\phdthesishname{PhD thesis}
\newcommand*\DTLbibliography}[2][\boolean{true}]{%
  \begin{DTLthebibliography}[#1]{#2}%
    \DTLforeachbibentry[#1]{#2}{%
      \DTLbibitem \DTLformatbibentry \DTLendbibitem
    }%
  \end{DTLthebibliography}%
}
\newcommand*\DTLformatbibentry}{%
  \@ifundefined{DTLformat\DBIBentrytype}%
  {%
    \PackageError{datbib}{Don't know how to format bibliography
      entries of type `DBIBentrytype'}{}}%
  {%
    \dtl@message{[DBIBCitekey]}%
    \DTLstartsentencefalse\DTLmidsentencefalse\DTLperiodfalse
    \csname DTLformat\DBIBentrytype\endcsname
  }%
}
\newcommand*\gDTLformatbibentry}{%
  \@ifundefined{DTLformat\DBIBentrytype}%
  {%
    \PackageError{datbib}{Don't know how to format bibliography
      entries of type `DBIBentrytype'}{}}%
  {%
    \dtl@message{[DBIBCitekey]}%
    \global\DTLstartsentencefalse
    \global\DTLmidsentencefalse
    \global\DTLperiodfalse
    \csname DTLformat\DBIBentrytype\endcsname
  }%
}

```

```

    }%
  }
\newcommand*{\DTLformatthisbibentry}[2]{%
  \edef\DBIBname{#1}%
  \edef\DBIBcitekey{#2}%
  \edtlgetrowforvalue{#1}{\dtlcolumnindex{#1}{CiteKey}}{\DBIBcitekey}%
  \dtl@gathervalues{#1}{\dtlcurrentrow}%
  \letcs{\DBIBentrytype}{@dtl@key@EntryType}%
  \DTLformatbibentry
}
\newcommand*{\DTLendbibitem}{}
\newlength\dtl@widest
\newcommand*{\DTLcomputewidestbibentry}[4]{%
\dtl@widest=0pt\relax
\let#4=\@empty
\DTLforeachbibentry[#1]{#2}{%
\settowidth{\dtl@tmplength}{#3}%
\ifdim\dtl@tmplength>\dtl@widest\relax
\dtl@widest=\dtl@tmplength
\protected@edef#4{#3}%
\fi
}%
}
\newcommand*{\DTLforeachbibentry}{%
\@ifstar\@sDTLforeachbibentry\@DTLforeachbibentry
\newcommand*{\@DTLforeachbibentry}[3][\boolean{true}]{%
  \edef\DBIBname{#2}%
  \setcounter{DTLbibrow}{0}%
  \@DTLforeach{#2}{\DBIBcitekey=CiteKey,\DBIBentrytype=EntryType}%
  {%
    \dtl@gathervalues{#2}{\dtlcurrentrow}%
    \ifthenelse{#1}{\refstepcounter{DTLbibrow}#3}{}%
  }%
}
}
\newcommand*{\@sDTLforeachbibentry}[3][\boolean{true}]{%
  \edef\DBIBname{#2}%
  \setcounter{DTLbibrow}{0}%
  \@sDTLforeach{#2}{\DBIBcitekey=CiteKey,\DBIBentrytype=EntryType}%
  {%
    \dtl@gathervalues{#2}{\dtlcurrentrow}%
    \ifthenelse{#1}{\refstepcounter{DTLbibrow}#3}{}%
  }%
}
}
\newcommand{\gDTLforeachbibentry}{%
\@ifstar\@sgDTLforeachbibentry\@gDTLforeachbibentry
\newcommand*{\@gDTLforeachbibentry}[3][\boolean{true}]{%
  \xdef\DBIBname{#2}%
  \global\c@DTLbibrow = 0\relax
  \@DTLforeach{#2}{\DBIBcitekey=CiteKey,\DBIBentrytype=EntryType}%
  {%

```

```

\dtl@g@gathervalues{#2}{\dtlcurrentrow}%
\ifthenelse{#1}%
{%
  \refstepcounter{DTLbibrow}%
  \global\c@DTLbibrow=\c@DTLbibrow
  #3%
}%
}%
}
\newcommand*{\@sgDTLforeachbibentry}[3][\boolean{true}]{%
  \xdef\DBIBname{#2}%
  \global\c@DTLbibrow = 0\relax
  \@sDTLforeach{#2}{\DBIBCitekey=CiteKey,\DBIBentrytype=EntryType}%
  {%
    \dtl@g@gathervalues{#2}{\dtlcurrentrow}%
    \ifthenelse{#1}%
    {%
      \refstepcounter{DTLbibrow}%
      \global\c@DTLbibrow=\c@DTLbibrow
      #3%
    }%
    {}%
  }%
}
\newcounter{DTLbibrow}
\def\theHDTLbibrow{\theHDTLrow.bib.\arabic{DTLbibrow}}%
\newcommand*{\DTLbibfield}[1]{\csname @dtl@key@#1\endcsname}
\newcommand*{\DTLbibfieldlet}[2]{%
  \letcs{#1}{@dtl@key@#2}%
}
\newcommand*{\DTLifbibfieldexists}[3]{%
  \@ifundefined{@dtl@key@#1}{#3}{%
  \expandafter\DTLifnull\csname @dtl@key@#1\endcsname
  {#3}{#2}}%
}
\newcommand*{\DTLifanybibfieldexists}[3]{%
  \@for\dtl@thisfield:=#1\do{%
  \@ifundefined{@dtl@key@\dtl@thisfield}{}{%
  \expandafter\DTLifnull\csname @dtl@key@\dtl@thisfield\endcsname
  }{}%
  \@endfortrue}}}%
\if@endfor
#2%
\else
#3%
\fi
\@endforfalse
}
\newif\ifDTLperiod
\newcommand*{\DTLcheckendsperiod}[1]{%

```

```

\dtl@checkendsperiod#1\@nil\relax}
\def\dtl@checkendsperiod#1#2{%
\def\@dtl@argi{#1}\def\@dtl@argii{#2}%
\def\@dtl@period{.}%
\ifx\@dtl@argi\@nnil
  \global\DTLperiodfalse
  \let\@dtl@donext=\relax
\else
  \ifx\@dtl@argii\@nnil
    \ifx\@dtl@argi\@dtl@period
      \global\DTLperiodtrue
    \else
      \global\DTLperiodfalse
    \fi
    \let\@dtl@donext=\@gobble
  \else
    \let\@dtl@donext=\dtl@checkendsperiod
  \fi
\fi
\@dtl@donext{#2}%
}
\newcommand*{\DTLcheckbibfieldendsperiod}[1]{%
\protected@edef\@dtl@tmp{\DTLbibfield{#1}}%
\expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}}
\newif\ifDTLmidsentence
\newif\ifDTLstartsentence
\newcommand*{\DTLaddperiod}{\DTLmidsentencefalse\DTLperiodfalse
\DTLstartsentencetrue
\ifDTLperiod\else.\fi}
\newcommand*{\DTLaddcomma}{, \DTLmidsentencetrue
\DTLperiodfalse\DTLstartsentencefalse}
\newcommand*{\DTLstartsencespace}{%
\ifDTLstartsentence\spacefactor=\sfcode`.\relax\space
\fi\DTLstartsentencefalse}
\newcommand*{\DTLtwoand}{\ \andname\ }
\newcommand*{\DTLlandlast}{, \andname\ }
\newcommand*{\DTLlandnotlast}{, }
\newcount\@dtl@authorcount
\newcounter{DTLmaxauthors}
\setcounter{DTLmaxauthors}{10}
\newcommand*{\DTLformatauthorlist}{%
\DTLifbibfieldexists{Author}{%
\DTLstartsencespace
\@dtl@authorcount=0\relax
\@for\@dtl@author:=\@dtl@key@Author\do{%
\advance\@dtl@authorcount by 1\relax}%
\@dtl@tmpcount=0\relax
\ifnum\@dtl@authorcount>\c@DTLmaxauthors
{%
\@for\@dtl@author:=\@dtl@key@Author\do{%

```

```

\advance\@dtl@tmpcount by 1\relax
\ifnum\@dtl@tmpcount=1\relax
  \expandafter\DTLformatauthor\@dtl@author
\else
  \ifnum\@dtl@tmpcount>\c@DTLmaxauthors
    \DTLandnotlast \etalname
    \expandafter\DTLcheckendsperiod\expandafter{\etalname}%
    \@endfortrue
  \else
    \DTLandnotlast \expandafter\DTLformatauthor\@dtl@author
  \fi
\fi
}%
\else
  \@for\@dtl@author:=\@dtl@key@Author\do{%
\advance\@dtl@tmpcount by 1\relax
\ifnum\@dtl@tmpcount=1\relax
  \expandafter\DTLformatauthor\@dtl@author
\else
  \ifnum\@dtl@tmpcount=\@dtl@authorcount
    \ifnum\@dtl@authorcount=2\relax
      \DTLtwoand
    \else
      \DTLandlast
    \fi
    \expandafter\DTLformatauthor\@dtl@author
  \else
    \DTLandnotlast \expandafter\DTLformatauthor\@dtl@author
  \fi
\fi
}%
\fi
}}}%
}
\newcounter{DTLmaxeditors}
\setcounter{DTLmaxeditors}{10}
\newcommand*\DTLformateditorlist{%
\DTLifbibfieldexists{Editor}{%
\DTLstartsencespace
\@dtl@authorcount=0\relax
\@for\@dtl@author:=\@dtl@key@Editor\do{%
\advance\@dtl@authorcount by 1\relax}%
\@dtl@tmpcount=0\relax
\ifnum\@dtl@authorcount>\c@DTLmaxeditors
{%
\@for\@dtl@author:=\@dtl@key@Editor\do{%
\advance\@dtl@tmpcount by 1\relax
\ifnum\@dtl@tmpcount=1\relax
  \expandafter\DTLformateditor\@dtl@author

```

```

\else
  \ifnum\@dtl@tmpcount>\c@DTLmaxeditors
    \DTLandnotlast \etalname
    \expandafter\DTLcheckendsperiod\expandafter{\etalname}%
    \@endfortrue
  \else
    \DTLandnotlast \expandafter\DTLformatteditor\@dtl@author
  \fi
\fi
}%
}%
\else
\@for\@dtl@author:=\@dtl@key@Editor\do{%
  \advance\@dtl@tmpcount by 1\relax
  \ifnum\@dtl@tmpcount=1\relax
    \expandafter\DTLformatteditor\@dtl@author
  \else
    \ifnum\@dtl@tmpcount=\@dtl@authorcount
      \ifnum\@dtl@authorcount=2\relax
        \DTLtwoand
      \else
        \DTLandlast
      \fi
      \expandafter\DTLformatteditor\@dtl@author
    \else
      \DTLandnotlast \expandafter\DTLformatteditor\@dtl@author
    \fi
  \fi
}%
\fi
/
\ifnum\@dtl@authorcount=1\relax
  \editorname
  \expandafter\DTLcheckendsperiod\expandafter{\editorname}%
\else
  \editorsname
  \expandafter\DTLcheckendsperiod\expandafter{\editorsname}%
\fi
}{}%
}
\newcommand*\DTLformatsurnameonly}[4]{%
\DTLstartsencespace
\def\@dtl@tmp{#1}%
\ifx\@dtl@tmp\@empty\else#1~\fi
#2%
\def\@dtl@tmp{#3}%
\ifx\@dtl@tmp\@empty
  \DTLcheckendsperiod{#2}%
\else
  , #3%

```

```

\DTLcheckendsperiod{#3}%
\fi
}
\newcommand*{\DTLformatforenames}[1]{%
\DTLstartsentencespace
#1%
\DTLcheckendsperiod{#1}}
\newcommand*{\DTLformatabbrvforenames}[1]{%
\DTLstartsentencespace
\DTLstoreinitials{#1}\@dtl@tmp\@dtl@tmp
\expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}}
\newcommand*{\DTLformatvon}[1]{%
\DTLstartsentencespace
\def\@dtl@tmp{#1}%
\ifx\@dtl@tmp\@empty
\else
#1~%
\fi
}
\newcommand*{\DTLformatsurname}[1]{%
\DTLstartsentencespace
#1\DTLcheckendsperiod{#1}}
\newcommand*{\DTLformatjr}[1]{%
\DTLstartsentencespace
\def\@dtl@tmp{#1}%
\ifx\@dtl@tmp\@empty
\else
, #1\DTLcheckendsperiod{#1}%
\fi
}
\newcommand*{\DTLformatcrossrefeditor}{%
\DTLifbibfieldexists{Editor}{%
\DTLstartsentencespace
\@dtl@authorcount=0\relax
\@for\@dtl@author:=\@dtl@key@Editor\do{%
\advance\@dtl@authorcount by 1\relax}%
{\@dtl@tmpcount=0\relax
\@for\@dtl@author:=\@dtl@key@Editor\do{%
\ifnum\@dtl@authorcount=1\relax
\expandafter\DTLformatsurnameonly\@dtl@author
\else
\advance\@dtl@tmpcount by 1\relax
\ifnum\@dtl@tmpcount=1\relax
\expandafter\DTLformatsurnameonly\@dtl@author
\else
\ifnum\@dtl@authorcount=2\relax
\ \andname\ \expandafter\DTLformatsurnameonly\@dtl@author
\else
\ \etalname
\expandafter\DTLcheckendsperiod\expandafter{\etalname}

```

```

        \fi
        \@endfortrue
    \fi
\fi
}}%
}{}%
}
\newcommand*{\DTLformatvolnumpages}{%
\DTLifbibfieldexists{Volume}{%
\DTLstartsencespace
\DTLbibfield{Volume}\DTLperiodfalse}{}%
\DTLifbibfieldexists{Number}{%
\DTLstartsencespace
(\DTLbibfield{Number})\DTLperiodfalse}{}%
\DTLifbibfieldexists{Pages}{%
\DTLifanybibfieldexists{Volume,Number}{:}{%
\DTLstartsencespace
\protected@edef\@dtl@pages{0\DTLbibfield{Pages}}%
\DTLifnumerical{\@dtl@pages}{\pagename}{\pagesname}~}%
\DTLbibfield{Pages}\DTLperiodfalse}{}%
}
\newcommand*{\DTLformatbvvolume}{%
\DTLifbibfieldexists{Volume}{%
\ifDTLmidsentence
    \volumename
\else
    \DTLstartsencespace
    \expandafter\MakeUppercase\volumename
\fi
~\DTLbibfield{Volume}%
\DTLifbibfieldexists{Series}{\ \ofname\
{\em\DTLbibfield{Series}}\DTLcheckbibfieldendsperiod{Series}}{%
\DTLcheckbibfieldendsperiod{Volume}}%
}{}%
\newcommand*{\DTLformatchapterpages}{%
\DTLifbibfieldexists{Chapter}{%
\DTLifbibfieldexists{Type}{%
\DTLstartsencespace
\DTLbibfield{Type}}{%
\DTLstartsencespace
\chaptername}~\DTLbibfield{Chapter}%
\DTLifbibfieldexists{Pages}{\DTLaddcomma}{%
\DTLcheckbibfieldendsperiod{Chapter}}}{}%
\DTLstartsencespace
\DTLformatpages}
\newcommand*{\DTLformatpages}{%
\DTLifbibfieldexists{Pages}{%
\DTLstartsencespace
\protected@edef\@dtl@pages{0\DTLbibfield{Pages}}%
\DTLifnumerical{\@dtl@pages}{\pagename}{\pagesname}~%

```

```

\DTLbibfield{Pages}\DTLcheckbibfieldendsperiod{Pages}}{ }%
}
\newcommand*{\DTLformatnumberseries}{%
\DTLifbibfieldexists{Volume}}{ }%
\DTLifbibfieldexists{Number}}{ }%
\ifDTLmidsentence
  \numbername
\else
  \DTLstartsencespace
  \expandafter\MakeUppercase\numbername
\fi~\DTLbibfield{Number}%
\DTLifbibfieldexists{Series}{\ \inname\ \DTLbibfield{Series}%
\DTLcheckbibfieldendsperiod{Series}}{ }%
\DTLcheckbibfieldendsperiod{Number}}{ }%
}{ }%
\DTLifbibfieldexists{Series}}{ }%
\DTLstartsencespace
\DTLbibfield{Series}%
\DTLcheckbibfieldendsperiod{Series}}{ }{ }%
}{ }%
}
\newcommand*{\DTLformatbookcrossref}{%
\DTLifbibfieldexists{Volume}}{ }%
\ifDTLmidsentence
  \volumename
\else
  \DTLstartsencespace
  \expandafter\MakeUppercase\volumename
\fi
~\DTLbibfield{Volume}\ \ofname\
}{ }%
\ifDTLmidsentence
  \inname
\else
  \DTLstartsencespace
  \expandafter\MakeUppercase\inname
\fi\ }%
\DTLifbibfieldexists{Editor}}{\DTLformatcrossrefeditor}}{ }%
\DTLifbibfieldexists{Key}}{ }%
\DTLbibfield{Key}}{ }%
\DTLifbibfieldexists{Series}}{ }%
{\em\DTLbibfield{Series}}{ }{ }%
}{ }%
}{ }%
~\DTLpcite{\DTLbibfield{CrossRef}}{ }%
}
\newcommand*{\DTLformatincollproccrossref}{%
\DTLifbibfieldexists{Editor}}{ }%
\ifDTLmidsentence
  \inname

```

```

\else
  \DTLstartsentencespace
  \expandafter\MakeUppercase\inname
\fi\
\DTLformatcrossrefeditor
}{%
\DTLifbibfieldexists{Key}{%
\ifDTLmidsentence
  \inname
\else
  \DTLstartsentencespace
  \expandafter\MakeUppercase\inname
\fi\ \DTLbibfield{Key}%
}{%
\DTLifbibfieldexists{BookTitle}{%
\ifDTLmidsentence
  \inname
\else
  \DTLstartsentencespace
  \expandafter\MakeUppercase\inname
\fi\ \DTLformatbooktitle{\DTLbibfield{BookTitle}}}{%
}}%
~\DTLpcite{\DTLbibfield{CrossRef}}%
}
\newcommand*\DTLformatinedbooktitle{%
\DTLifbibfieldexists{BookTitle}{%
\ifDTLmidsentence
  \inname
\else
  \DTLstartsentencespace
  \expandafter\MakeUppercase\inname
\fi\
\DTLifbibfieldexists{Editor}{%
\DTLformateditorlist\DTLladdcomma \DTLformatbooktitle{\DTLbibfield{BookTitle}}%
\DTLcheckbibfieldendsperiod{BookTitle}%
}{\DTLformatbooktitle{\DTLbibfield{BookTitle}}%
\DTLcheckbibfieldendsperiod{BookTitle}%
}}{}}
\newcommand*\DTLformatdate{%
\DTLifbibfieldexists{Year}{%
\DTLifbibfieldexists{Month}{%
\protected@edef\@dtl@tmp{\DTLbibfield{Month}}%
\ifDTLmidsentence
  \@dtl@tmp
\else
  \DTLstartsentencespace
  \expandafter\MakeUppercase\@dtl@tmp
\fi\
\DTLmidsentencefalse}{%
\DTLstartsentencespace

```

```

\DTLbibfield{Year}}{%
\DTLifbibfieldexists{Month}}{%
\protected@edef\@dtl@tmp{\DTLbibfield{Month}}%
\ifDTLmidsentence
  \@dtl@tmp
\else
  \DTLstartsencespace
  \expandafter\MakeUppercase\@dtl@tmp
\fi
\DTLcheckbibfieldendsperiod{Month}%
}}}}
\newcommand*\DTLformatarticlecrossref}{%
\DTLifbibfieldexists{Key}}{%
\ifDTLmidsentence
  \inname
\else
  \DTLstartsencespace
  \expandafter\MakeUppercase\inname
\fi
\ {\em\DTLbibfield{Key}}}{%
\DTLifbibfieldexists{Journal}}{%
\ifDTLmidsentence
  \inname
\else
  \DTLstartsencespace
  \expandafter\MakeUppercase\inname
\fi
\ {\em\DTLbibfield{Journal}}}{%
~\DTLpcite{\DTLbibfield{CrossRef}}%
}
\newrobustcmd*\DTLpcite}[1]{%
  \protected@edef\@dtl@tmp{#1}%
  \cite{\@dtl@tmp}%
}
\newcommand*\DTLbibfieldexists}[1]{%
\TE@throw\noexpand\dtl@testbibfieldexists{#1}%
\noexpand\if@dtl@condition}
\newcommand*\dtl@testbibfieldexists}[1]{%
\DTLifbibfieldexists{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}
\newcommand*\DTLbibfielddiseq}[2]{%
\TE@throw\noexpand\dtl@testbibfielddiseq{#1}{#2}%
\noexpand\if@dtl@condition}
\newcommand*\dtl@testbibfielddiseq}[2]{%
\DTLifbibfieldexists{#1}}%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\toks\expandafter{\@dtl@tmp}%
\@dtl@toks{#2}%
\edef\@dtl@docompare{\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}}%
{\the\toks@}{\the\@dtl@toks}}%

```

```

\@dtl@docompare
\ifnum\@dtl@tmpcount=0\relax
  \@dtl@conditiontrue
\else
  \@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}
\newcommand*\DTLbibfieldislt}[2]{%
\TE@throw\noexpand\dtl@testbibfieldislt{#1}{#2}%
\noexpand\if@dtl@condition}
\newcommand*\dtl@testbibfieldislt}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\toks@\expandafter{\@dtl@tmp}%
\@dtl@toks{#2}%
\edef\@dtl@docompare{\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}%
{\the\toks@}{\the\@dtl@toks}}%
\@dtl@docompare
\ifnum\@dtl@tmpcount=-1\relax
  \@dtl@conditiontrue
\else
  \@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}
\newcommand*\DTLbibfieldisle}[2]{%
\TE@throw\noexpand\dtl@testbibfieldisle{#1}{#2}%
\noexpand\if@dtl@condition}
\newcommand*\dtl@testbibfieldisle}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\toks@\expandafter{\@dtl@tmp}%
\@dtl@toks{#2}%
\edef\@dtl@docompare{\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}%
{\the\toks@}{\the\@dtl@toks}}%
\@dtl@docompare
\ifnum\@dtl@tmpcount<1\relax
  \@dtl@conditiontrue
\else
  \@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}
\newcommand*\DTLbibfieldisgt}[2]{%

```

```

\TE@throw\noexpand\dtl@testbibfieldisgt{#1}{#2}%
\noexpand\if@dtl@condition}
\newcommand*{\dtl@testbibfieldisgt}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\toks@\expandafter{\@dtl@tmp}%
\@dtl@toks{#2}%
\edef\@dtl@docompare{\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}%
{\the\toks@}{\the\@dtl@toks}}%
\@dtl@docompare
\ifnum\@dtl@tmpcount=1\relax
\@dtl@conditiontrue
\else
\@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}
\newcommand*{\DTLbibfieldisge}[2]{%
\TE@throw\noexpand\dtl@testbibfieldisge{#1}{#2}%
\noexpand\if@dtl@condition}
\newcommand*{\dtl@testbibfieldisge}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\toks@\expandafter{\@dtl@tmp}%
\@dtl@toks{#2}%
\edef\@dtl@docompare{\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}%
{\the\toks@}{\the\@dtl@toks}}%
\@dtl@docompare
\ifnum\@dtl@tmpcount>-1\relax
\@dtl@conditiontrue
\else
\@dtl@conditionfalse
\fi
}{%
\@dtl@conditionfalse}%
}
\newcommand*{\DTLbibfieldcontains}[2]{%
\TE@throw\noexpand\dtl@testbibfieldcontains{#1}{#2}%
\noexpand\if@dtl@condition}
\newcommand*{\dtl@testbibfieldcontains}[2]{%
\DTLifbibfieldexists{#1}{%
\expandafter\let\expandafter\@dtl@tmp\expandafter
=\csname @dtl@key@#1\endcsname
\expandafter\dtl@testifsubstring\expandafter{\@dtl@tmp}{#2}%
}{\@dtl@conditionfalse}}
\newenvironment{DTLthebibliography}[2][\boolean{true}]{%
\@dtl@tmpcount=0\relax

```

```

\@sDTLforeach[#1]{#2}{\advance\@dtl@tmpcount by 1\relax}%
\begin{thebibliography}{\number\@dtl@tmpcount}
}{\end{thebibliography}}
\newcommand*\DTLmonthname[1]{%
\dtl@monthname{#1}}
\newcommand*\dtl@monthname[1]{%
\ifcase#1%
\or January%
\or February%
\or March%
\or April%
\or May%
\or June%
\or July%
\or August%
\or September%
\or October%
\or November%
\or December%
\fi}
\newcommand*\dtl@abbrvmonthname[1]{%
\ifcase#1%
\or Jan.%
\or Feb.%
\or Mar.%
\or Apr.%
\or May%
\or June%
\or July%
\or Aug.%
\or Sept.%
\or Oct.%
\or Nov.%
\or Dec.%
\fi}
\newcommand*\DTLbibitem{\bibitem{DBIBCitekey}}
\newcommand*\DTLmbibitem[1]{\bibitem{#1@DBIBCitekey}}
\newcommand*\DTLcumbibitem[3]{%
#1%
\if@filesw
\immediate\write\@auxout{\string\bibcite{#3}{#2}}%
\fi
\ignorespaces
}
\newcommand*\DTLformatauthor[4]{%
\DTLformatforenames{#4}
\DTLformatvon{#1}%
\DTLformatsurname{#2}%
\DTLformatjr{#3}}
\newcommand*\DTLformateditor[4]{%

```

```

\DTLformatforenames{#4}
\DTLformatvon{#1}%
\DTLformatsurname{#2}%
\DTLformatjr{#3}}
\newcommand*{\DTLformatedition}[1]{#1 \editionname}
\newcommand{\DTLformatarticle}{}
\newcommand{\DTLformatbook}{}
\newcommand{\DTLformatbooklet}{}
\newcommand{\DTLformatinbook}{}
\newcommand{\DTLformatincollection}{}
\newcommand{\DTLformatinproceedings}{}
\newcommand{\DTLformatmanual}{}
\newcommand{\DTLformatmastersthesis}{}
\newcommand{\DTLformatmisc}{}
\newcommand{\DTLformatphdthesis}{}
\newcommand{\DTLformatproceedings}{}
\newcommand{\DTLformattechreport}{}
\newcommand{\DTLformatunpublished}{}
\newcommand*{\DTLacmcs}{ACM Computing Surveys}
\newcommand*{\DTLacta}{Acta Informatica}
\newcommand*{\DTLcacm}{Communications of the ACM}
\newcommand*{\DTLibmjrd}{IBM Journal of Research and Development}
\newcommand*{\DTLibmsj}{IBM Systems Journal}
\newcommand*{\DTLIEEESE}{IEEE Transactions on Software Engineering}
\newcommand*{\DTLIEEEetc}{IEEE Transactions on Computers}
\newcommand*{\DTLIEEEetcad}{IEEE Transactions on Computer-Aided Design
of Integrated Circuits}
\newcommand*{\DTLipl}{Information Processing Letters}
\newcommand*{\DTLjacm}{Journal of the ACM}
\newcommand*{\DTLjcss}{Journal of Computer and System Sciences}
\newcommand*{\DTLscp}{Science of Computer Programming}
\newcommand*{\DTLsicomp}{SIAM Journal on Computing}
\newcommand*{\DTLtocs}{ACM Transactions on Computer Systems}
\newcommand*{\DTLtods}{ACM Transactions on Database Systems}
\newcommand*{\DTLtog}{ACM Transactions on Graphics}
\newcommand*{\DTLtoms}{ACM Transactions on Mathematical Software}
\newcommand*{\DTLtoois}{ACM Transactions on Office Information
Systems}
\newcommand*{\DTLtoplas}{ACM Transactions on Programming Languages
and Systems}
\newcommand*{\DTLtcs}{Theoretical Computer Science}
\newcommand{\dtl@bst@plain}{%
  \renewenvironment{DTLthebibliography}[2][\boolean{true}]{%
    \@dtl@tmpcount=0\relax
    \@sDTLforeach[##1][##2]{}{\advance\@dtl@tmpcount by 1\relax}%
    \begin{thebibliography}{\number\@dtl@tmpcount}%
    }{\end{thebibliography}}%
  }
\renewcommand*{\DTLbibitem}{\bibitem{\DBIBCitekey}}%
\renewcommand*{\DTLmbibitem}[1]{\bibitem{##1@DBIBCitekey}}%
\renewcommand*{\DTLformatauthor}[4]{%

```

```

\DTLformatforenames{##4}
\DTLformatvon{##1}%
\DTLformatsurname{##2}%
\DTLformatjr{##3}
\renewcommand*{\DTLformateditor}[4]{%
\DTLformatforenames{##4}
\DTLformatvon{##1}%
\DTLformatsurname{##2}%
\DTLformatjr{##3}}
\renewcommand*{\DTLformatedition}[1]{##1 \editionname}%
\let\DTLmonthname\dtl@monthname
\renewcommand*{\DTLacmcs}{ACM Computing Surveys}
\renewcommand*{\DTLacta}{Acta Informatica}
\renewcommand*{\DTLcacm}{Communications of the ACM}
\renewcommand*{\DTLibmjrd}{IBM Journal of Research and Development}
\renewcommand*{\DTLibmsj}{IBM Systems Journal}
\renewcommand*{\DTLIEEEese}{IEEE Transactions on Software Engineering}
\renewcommand*{\DTLIEEEetc}{IEEE Transactions on Computers}
\renewcommand*{\DTLIEEEetcad}{IEEE Transactions on Computer-Aided Design
of Integrated Circuits}
\renewcommand*{\DTLipl}{Information Processing Letters}
\renewcommand*{\DTLjacm}{Journal of the ACM}
\renewcommand*{\DTLjcss}{Journal of Computer and System Sciences}
\renewcommand*{\DTLscp}{Science of Computer Programming}
\renewcommand*{\DTLsicomp}{SIAM Journal on Computing}
\renewcommand*{\DTLtocs}{ACM Transactions on Computer Systems}
\renewcommand*{\DTLtods}{ACM Transactions on Database Systems}
\renewcommand*{\DTLtog}{ACM Transactions on Graphics}
\renewcommand*{\DTLtoms}{ACM Transactions on Mathematical Software}
\renewcommand*{\DTLtoois}{ACM Transactions on Office Information
Systems}
\renewcommand*{\DTLtoplas}{ACM Transactions on Programming Languages
and Systems}
\renewcommand*{\DTLtcs}{Theoretical Computer Science}
\renewcommand*{\DTLformatarticle}{%
\DTLformatauthorlist
\DTLifbibfieldexists{Author}{\DTLaddperiod}}}%
\DTLifbibfieldexists{Title}{%
\DTLstartsentencespace\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}}}%
\DTLifbibfieldexists{CrossRef}{%
\DTLformatarticlecrossref
\DTLifbibfieldexists{Pages}{\DTLaddcomma}}}%
\DTLformatpages
\DTLaddperiod
}{% no cross ref field
\DTLifbibfieldexists{Journal}{\DTLstartsentencespace
\em\DTLbibfield{Journal}}%
\DTLcheckbibfieldendsperiod{Journal}%

```

```

\DTLifanybibfieldexists{Number,Volume,Pages,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}{%
\DTLformatvolnumpages
\DTLifanybibfieldexists{Volume,Number,Pages}{%
\DTLifanybibfieldexists{Year,Month}{\DTLaddcomma}{%
\DTLaddperiod}%
\DTLmidsentencefalse}{}%
\DTLformatdate
\DTLifanybibfieldexists{Year,Month}{\DTLaddperiod}}{%
}%
\DTLifbibfieldexists{Note}{\DTLstartsencespace\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}{%
}
\renewcommand*{\DTLformatbook}{%
\DTLifbibfieldexists{Author}%
{%
\DTLformatauthorlist\DTLaddperiod
}%
{%
\DTLformateditorlist
\DTLifbibfieldexists{Editor}%
{%
\DTLaddperiod
}%
}%
}%
\DTLifbibfieldexists{Title}%
{%
\DTLstartsencespace
\DTLformatbooktitle{\DTLbibfield{Title}}%
\DTLcheckbibfieldendsperiod{Title}%
}%
}%
\DTLifbibfieldexists{CrossRef}%
{%
\DTLifbibfieldexists{Title}{\DTLaddperiod}}{%
\DTLformatbookcrossref
\DTLifanybibfieldexists{Edition,Month,Year}%
{\DTLaddcomma}%
{\DTLaddperiod}%
}%
{%
\DTLifbibfieldexists{Title}%
{%
\DTLifbibfieldexists{Volume}{\DTLaddcomma}{\DTLaddperiod}%
}%
}%
\DTLformatbvolume
\DTLformatnumberseries

```

```

\DTLifanybibfieldexists{Number, Series, Volume}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Publisher}%
{%
  \DTLstartsencespace
  \DTLbibfield{Publisher}%
  \DTLcheckbibfieldendsperiod{Publisher}%
  \DTLifbibfieldexists{Address}%
  {\DTLaddcomma}%
  {%
    \DTLifanybibfieldexists{Month, Year}%
    {\DTLaddcomma}%
    {\DTLaddperiod}%
  }%
}%
{}%
\DTLifbibfieldexists{Address}%
{%
  \DTLstartsencespace
  \DTLbibfield{Address}%
  \DTLcheckbibfieldendsperiod{Address}%
  \DTLifanybibfieldexists{Month, Year}{\DTLaddcomma}{\DTLaddperiod}%
}%
{}%
}%
\DTLifbibfieldexists{Edition}%
{%
  \protected@edef\@dtl@tmp{\DTLformatedition{\DTLbibfield{Edition}}}%
  \ifDTLmidsentence
    \@dtl@tmp
  \else
    \DTLstartsencespace\expandafter\MakeUppercase\@dtl@tmp
  \fi
  \expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}%
  \DTLifanybibfieldexists{Month, Year}{\DTLaddcomma}{\DTLaddperiod}%
}%
{}%
\DTLformatdate
\DTLifanybibfieldexists{Year, Month}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Note}%
{%
  \DTLstartsencespace
  \DTLbibfield{Note}%
  \DTLcheckbibfieldendsperiod{Note}%
  \DTLaddperiod
}%
{}%
}%
\renewcommand*{\DTLformatbooklet}{%
\DTLifbibfieldexists{Author}{%
\DTLformatauthorlist\DTLaddperiod}{}%

```

```

\DTLifbibfieldexists{Title}{\DTLstartsentencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}}}%
\DTLifbibfieldexists{HowPublished}{%
\DTLstartsentencespace\DTLbibfield{HowPublished}%
\DTLcheckbibfieldendsperiod{HowPublished}%
\DTLifanybibfieldexists{Address,Month,Year}{\DTLaddcomma
}{\DTLaddperiod}}}%
\DTLifbibfieldexists{Address}{\DTLstartsentencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{\DTLaddperiod}}}%
\DTLformatdate
\DTLifanybibfieldexists{Year,Month}{\DTLaddperiod}}}%
\DTLifbibfieldexists{Note}{\DTLstartsentencespace\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}}%
}%
\renewcommand*{\DTLformatinbook}{%
\DTLifbibfieldexists{Author}{%
\DTLformatauthorlist\DTLaddperiod}}%
\DTLifbibfieldexists{Editor}{\DTLformateditorlist\DTLaddperiod}}}%
\DTLifbibfieldexists{Title}{%
\DTLstartsentencespace
{\em\DTLbibfield{Title}}%
\DTLcheckbibfieldendsperiod{Title}%
}}}%
\DTLifbibfieldexists{CrossRef}{%
\DTLifbibfieldexists{Title}{%
\DTLifbibfieldexists{Chapter}{\DTLaddcomma}{\DTLaddperiod}}}%
\DTLformatchapterpages
\DTLifanybibfieldexists{Chapter,Pages}{\DTLaddperiod}}}%
\DTLformatbookcrossref
}% no cross ref
\DTLifbibfieldexists{Title}{%
\DTLifanybibfieldexists{Chapter,Volume}{\DTLaddcomma
}{\DTLaddperiod}}}%
\DTLformatbvolum
\DTLifanybibfieldexists{Volume,Series}{%
\DTLifanybibfieldexists{Chapter,Pages}{%
\DTLaddcomma}{\DTLaddperiod}}}%
\DTLformatchapterpages
\DTLifanybibfieldexists{Chapter,Pages}{\DTLaddperiod}}}%
\DTLifbibfieldexists{Publisher}{%
\DTLstartsentencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLifbibfieldexists{Address}{\DTLaddcomma}}}%
\DTLifbibfieldexists{Address}{%

```

```

\DTLstartsentencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}}{}%
}%
\DTLifanybibfieldexists{Edition,Month,Year}{\DTLaddcomma
}{\DTLaddperiod}%
\DTLifbibfieldexists{Edition}{}%
\protected@edef\@dtl@tmp{\DTLformatedition{\DTLbibfield{Edition}}}%
\ifDTLmidsentence
  \@dtl@tmp
\else
  \DTLstartsentencespace
  \expandafter\MakeUppercase\@dtl@tmp
\fi
\expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma
}{\DTLaddperiod}%
}}{}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}{}%
\DTLifbibfieldexists{Note}{}%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}{}%
}%
\renewcommand*{\DTLformatincollection}{}%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}}{}%
\DTLifbibfieldexists{Title}{}%
\DTLstartsentencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}}{}%
\DTLifbibfieldexists{CrossRef}{}%
\DTLformatincolprocrossref
\DTLifanybibfieldexists{Chapter,Pages}{\DTLaddcomma}}{}%
\DTLformatchapterpages\DTLaddperiod
}% no cross ref entry
\DTLformatinedbooktitle
\DTLifbibfieldexists{BookTitle}{}%
\DTLifanybibfieldexists{Volume,Series,Chapter,Pages,Number}{}%
\DTLaddcomma}{\DTLaddperiod}}{}%
\DTLformatbvolume
\DTLifbibfieldexists{Volume}{}%
\DTLifanybibfieldexists{Number,Series,Chapter,Pages}{}%
\DTLaddcomma}{\DTLaddperiod}}{}%
\DTLformatnumberseries
\DTLifanybibfieldexists{Number,Series}{}%
\DTLifanybibfieldexists{Chapter,Pages}{\DTLaddcomma
}{\DTLaddperiod}}{}%

```

```

\DTLformatchapterpages
\DTLifanybibfieldexists{Chapter,Pages}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Publisher}{}%
\DTLstartsencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLifanybibfieldexists{Address, Edition, Month, Year}{}%
\DTLaddcomma}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Address}{}%
\DTLstartsencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Edition, Month, Year}{}%
\DTLaddcomma}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Edition}{}%
\protected@edef\@dtl@tmp{\DTLformattedition{\DTLbibfield{Edition}}}%
\ifDTLmidsentence
  \@dtl@tmp
\else
  \DTLstartsencespace
  \expandafter\MakeUppercase\@dtl@tmp
\fi
\expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}%
\DTLifanybibfieldexists{Month, Year}{\DTLaddcomma
}{\DTLaddperiod}%
}{}%
\DTLformatdate
\DTLifanybibfieldexists{Month, Year}{\DTLaddperiod}{}%
}%
\DTLifbibfieldexists{Note}{}%
\DTLstartsencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}{}%
}%
\renewcommand*{\DTLformatinproceedings}{}%
\DTLifbibfieldexists{Author}{\DTLformatauthor list
\DTLaddperiod}{}%
\DTLifbibfieldexists{Title}{}%
\DTLstartsencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}{}%
\DTLifbibfieldexists{CrossRef}{}%
\DTLformatincolprocrossref
\DTLifbibfieldexists{Pages}{\DTLaddcomma}{}%
\DTLaddperiod}%
\DTLformatpages
\DTLifbibfieldexists{Pages}{\DTLaddperiod}{}%
}{}% no cross ref

```

\DTLformatinedbooktitle
\DTLifbibfieldexists{BookTitle}{%
\DTLifanybibfieldexists{Volume, Series, Pages, Number, Address, %
Month, Year}{%
\DTLaddcomma}{\DTLaddperiod}}{%
\DTLformatbvvolume
\DTLifbibfieldexists{Volume}{%
\DTLifanybibfieldexists{Number, Series, Pages, Address, Month, Year}{%
\DTLaddcomma}{\DTLaddperiod}}{%
\DTLformatnumberseries
\DTLifanybibfieldexists{Number, Series}{%
\DTLifanybibfieldexists{Pages, Address, Month, Year}{%
\DTLaddcomma}{\DTLaddperiod}}{%
\DTLformatpages
\DTLifbibfieldexists{Pages}{%
\DTLifanybibfieldexists{Address, Month, Year}{%
\DTLaddcomma}{\DTLaddperiod}}{%
\DTLifbibfieldexists{Address}{%
\DTLstartsencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Month, Year}{\DTLaddcomma}{%
\DTLaddperiod}%
\DTLformatdate
\DTLifanybibfieldexists{Month, Year}{\DTLaddperiod}}{%
\DTLifbibfieldexists{Organization}{%
\DTLstartsencespace
\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLifbibfieldexists{Publisher}{\DTLaddcomma}{%
\DTLaddperiod}}{%
\DTLifbibfieldexists{Publisher}{%
\DTLstartsencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLaddperiod}}{%
}%
\DTLifanybibfieldexists{Publisher, Organization}{%
\DTLaddperiod}}{%
\DTLifbibfieldexists{Organization}{%
\DTLstartsencespace
\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLifanybibfieldexists{Publisher, Month, Year}{%
\DTLaddcomma}}{%
\DTLifbibfieldexists{Publisher}{%
\DTLstartsencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLifanybibfieldexists{Month, Year}{\DTLaddcomma}{%

```

\DTLaddperiod}}{}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}{}%
}%
}%
\DTLifbibfieldexists{Note}{%
\DTLstartsencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}{}%
}%
\renewcommand*{\DTLformatmanual}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist
\DTLaddperiod}{%
\DTLifbibfieldexists{Organization}{%
\DTLstartsencespace
\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLifbibfieldexists{Address}{\DTLaddcomma \DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
}}{}%
\DTLaddperiod}}{}%
}%
\DTLifbibfieldexists{Title}{%
\DTLstartsencespace
{\em\DTLbibfield{Title}}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLifbibfieldexists{Author}{%
\DTLifanybibfieldexists{Organization,Address}{%
\DTLaddperiod}{\DTLaddcomma}}{}%
\DTLifanybibfieldexists{Organization,Address,Edition,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}}{}%
\DTLifbibfieldexists{Author}{%
\DTLifbibfieldexists{Organization}{%
\DTLstartsencespace
\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLifanybibfieldexists{Address,Edition,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}}{}%
\DTLifbibfieldexists{Address}{%
\DTLstartsencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Edition,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}}{}%
}}{}%
\DTLifbibfieldexists{Organization}{}}{}%
\DTLifbibfieldexists{Address}{%
\DTLstartsencespace
\DTLbibfield{Address}%

```

```

\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Edition,Month,Year}{\DTLaddcomma}{%
\DTLaddperiod}}{}}%
}%
\DTLifbibfieldexists{Edition}{%
\protected@edef\@dtl@tmp{\DTLformattedition{\DTLbibfield{Edition}}}%
\ifDTLmidsentence
\@dtl@tmp
\else
\DTLstartsencespace
\expandafter\MakeUppercase\@dtl@tmp
\fi
\expandafter\DTLcheckendsperiod\expandafter{\@dtl@tmp}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{%
\DTLaddperiod}}{}}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}{}}%
\DTLifbibfieldexists{Note}{%
\DTLstartsencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}{}}%
}%
\renewcommand*\DTLformatmastersthesis}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}}{}}%
\DTLifbibfieldexists{Title}{%
\DTLstartsencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}}{}}%
\DTLifbibfieldexists{Type}{%
\DTLstartsencespace
\DTLbibfield{Type}%
\DTLcheckbibfieldendsperiod{Type}%
\DTLifanybibfieldexists{School,Address,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}{}}%
\DTLifbibfieldexists{School}{%
\DTLstartsencespace
\DTLbibfield{School}%
\DTLcheckbibfieldendsperiod{School}%
\DTLifanybibfieldexists{Address,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}{}}%
\DTLifbibfieldexists{Address}{%
\DTLstartsencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}{}}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}{}}%

```

```

\DTLifbibfieldexists{Note}{%
\DTLstartsencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}{}%
}%
\renewcommand*{\DTLformatmisc}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}{}%
\DTLifbibfieldexists{Title}{%
\DTLstartsencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLifbibfieldexists{HowPublished}{\DTLaddperiod}{%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{%
\DTLaddperiod}%
}%
\DTLmidsentencefalse}{}%
\DTLifbibfieldexists{HowPublished}{%
\DTLstartsencespace
\DTLbibfield{HowPublished}%
\DTLcheckbibfieldendsperiod{HowPublished}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{%
\DTLaddperiod}{}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}{}%
\DTLifbibfieldexists{Note}{%
\DTLstartsencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}{}%
}%
\renewcommand*{\DTLformatphdthesis}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}{}%
\DTLifbibfieldexists{Title}{%
\DTLstartsencespace
{\em\DTLbibfield{Title}}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}{}%
\DTLifbibfieldexists{Type}{%
\DTLstartsencespace
\DTLbibfield{Type}%
\DTLcheckbibfieldendsperiod{Type}%
\DTLifanybibfieldexists{School,Address,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}{%
\DTLifbibfieldexists{School}{%
\DTLstartsencespace
\DTLbibfield{School}%
\DTLcheckbibfieldendsperiod{School}%
\DTLifanybibfieldexists{Address,Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}}{%

```

```

\DTLifbibfieldexists{Address}{%
\DTLstartsencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Month,Year}{%
\DTLaddcomma}{\DTLaddperiod}}{%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}{%
\DTLifbibfieldexists{Note}{%
\DTLstartsencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}{%
}%
\renewcommand*{\DTLformatproceedings}{%
\DTLifbibfieldexists{Editor}{%
\DTLformateditorlist\DTLaddperiod}{%
\DTLifbibfieldexists{Organization}{%
\DTLstartsencespace
\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLaddperiod}}{%
\DTLifbibfieldexists{Title}{%
\DTLstartsencespace
{\em\DTLbibfield{Title}}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLifanybibfieldexists{Volume,Number,Address,Editor,Publisher,%
Month,Year}{\DTLaddcomma}{\DTLaddperiod}}%
}}{%
\DTLformatbvolum
\DTLifbibfieldexists{Volume}{%
\DTLifanybibfieldexists{Number,Address,Editor,Publisher,%
Month,Year}{\DTLaddcomma}{\DTLaddperiod}}}%
\DTLformatnumberseries
\DTLifbibfieldexists{Number}{%
\DTLifanybibfieldexists{Address,Editor,Publisher,%
Month,Year}{\DTLaddcomma}{\DTLaddperiod}}}%
\DTLifbibfieldexists{Address}{%
\DTLstartsencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{\DTLaddperiod}}%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}{%
\DTLifbibfieldexists{Editor}{\DTLifbibfieldexists{Organization}{%
\DTLstartsencespace
\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLifbibfieldexists{Publisher}{%
\DTLaddcomma}{\DTLaddperiod}}}}}%

```

```

\DTLifbibfieldexists{Publisher}{%
\DTLstartsencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLaddperiod
}}%
}{% no address
\DTLifbibfieldexists{Editor}{%
\DTLifbibfieldexists{Organization}{%
\DTLstartsencespace
\DTLbibfield{Organization}%
\DTLcheckbibfieldendsperiod{Organization}%
\DTLifanybibfieldexists{Publisher, Month, Year}{%
\DTLaddcomma}{\DTLaddperiod}}}%
}}%
\DTLifbibfieldexists{Publisher}{%
\DTLstartsencespace
\DTLbibfield{Publisher}%
\DTLcheckbibfieldendsperiod{Publisher}%
\DTLifanybibfieldexists{Month, Year}{\DTLaddcomma}{\DTLaddperiod}}}%
\DTLformatdate
\DTLifanybibfieldexists{Month, Year}{\DTLaddperiod}}}%
}%
\DTLifbibfieldexists{Note}{%
\DTLstartsencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}}%
}%
\renewcommand*{\DTLformattechreport}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}}}%
\DTLifbibfieldexists{Title}{%
\DTLstartsencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}}}%
\DTLifbibfieldexists{Type}{%
\DTLstartsencespace
\DTLbibfield{Type}%
\DTLcheckbibfieldendsperiod{Type}%
\DTLifbibfieldexists{Number}{~}}}%
\DTLifbibfieldexists{Number}{%
\DTLstartsencespace
\DTLbibfield{Number}%
\DTLcheckbibfieldendsperiod{Number}%
}}%
\DTLifanybibfieldexists{Type, Number}{%
\DTLifanybibfieldexists{Institution, Address, Month, Year}{\DTLaddcomma
}{\DTLaddperiod}}}%
\DTLifbibfieldexists{Institution}{%

```

```

\DTLstartsentencespace
\DTLbibfield{Institution}%
\DTLcheckbibfieldendsperiod{Institution}%
\DTLifanybibfieldexists{Address,Month,Year}{\DTLaddcomma
}{\DTLaddperiod}}{%
\DTLifbibfieldexists{Address}{%
\DTLstartsentencespace
\DTLbibfield{Address}%
\DTLcheckbibfieldendsperiod{Address}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma
}{\DTLaddperiod}}{%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}{%
\DTLifbibfieldexists{Note}{%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLaddperiod}}{%
}%
\renewcommand*{\DTLformatunpublished}{%
\DTLifbibfieldexists{Author}{\DTLformatauthorlist\DTLaddperiod}}{%
\DTLifbibfieldexists{Title}{%
\DTLstartsentencespace
\DTLbibfield{Title}%
\DTLcheckbibfieldendsperiod{Title}%
\DTLaddperiod}}{%
\DTLifbibfieldexists{Note}{%
\DTLstartsentencespace
\DTLbibfield{Note}%
\DTLcheckbibfieldendsperiod{Note}%
\DTLifanybibfieldexists{Month,Year}{\DTLaddcomma}{\DTLaddperiod}}{%
\DTLformatdate
\DTLifanybibfieldexists{Month,Year}{\DTLaddperiod}}{%
}%
}
\newcommand*{\DTLformatbooktitle}[1]{\emph{#1}}
\newcommand{\dtlbst@abbrv}{%
\dtlbst@plain
\renewcommand*{\DTLformatauthor}[4]{%
\DTLformatabbrvforenames{##4}
\DTLformatvon{##1}%
\DTLformatsurname{##2}%
\DTLformatjr{##3}}
\renewcommand*{\DTLformateditor}[4]{%
\DTLformatabbrvforenames{##4}
\DTLformatvon{##1}%
\DTLformatsurname{##2}%
\DTLformatjr{##3}}
\let\DTLmonthname\dtl@abbrvmonthname
\renewcommand*{\DTLacms}{ACM Comput.\ Surv.}

```

```

\renewcommand*{\DTLacta}{Acta Inf.}
\renewcommand*{\DTLcacm}{Commun.\ ACM}
\renewcommand*{\DTLibmjrd}{IBM J.\ Res.\ Dev.}
\renewcommand*{\DTLibmsj}{IBM Syst.-J.}
\renewcommand*{\DTLIEEE}{IEEE Trans. Softw.\ Eng.}
\renewcommand*{\DTLIEEEetc}{IEEE Trans.\ Comput.}
\renewcommand*{\DTLIEEEetcad}{IEEE Trans.\ Comput.-Aided Design
Integrated Circuits}
\renewcommand*{\DTLipl}{Inf.\ Process.\ Lett.}
\renewcommand*{\DTLjacm}{J.-ACM}
\renewcommand*{\DTLjcss}{J.-Comput.\ Syst.\ Sci.}
\renewcommand*{\DTLscpp}{Sci.\ Comput.\ Programming}
\renewcommand*{\DTLsicomp}{SIAM J.-Comput.}
\renewcommand*{\DTLtocs}{ACM Trans.\ Comput.\ Syst.}
\renewcommand*{\DTLtods}{ACM Trans.\ Database Syst.}
\renewcommand*{\DTLtog}{ACM Trans.\ Gr.}
\renewcommand*{\DTLtoms}{ACM Trans.\ Math. Softw.}
\renewcommand*{\DTLtoois}{ACM Trans. Office Inf.\ Syst.}
\renewcommand*{\DTLtoplas}{ACM Trans.\ Prog. Lang.\ Syst.}
\renewcommand*{\DTLtcs}{Theoretical Comput.\ Sci.}
}
\newcommand{\dtlbst@alpha}{%
\dtlbst@plain
\renewenvironment{DTLthebibliography}[2][\boolean{true}]{%
\dtl@createalphabiblabels{##1}{##2}%
\begin{thebibliography}{\@dtl@widestlabel}%
}{\end{thebibliography}}%
\renewcommand*{\DTLbibitem}{%
\expandafter\bibitem\expandafter
[\csname dtl@biblabel@DBIBCitekey\endcsname]{\DBIBCitekey}}%
\renewcommand*{\DTLmbibitem}[1]{%
\expandafter\bibitem\expandafter
[\csname dtl@biblabel@DBIBCitekey\endcsname]{##1@DBIBCitekey}}%
}
\newcommand*{\dtl@createalphabiblabels}[2]{%
\dtl@message{Creating bib labels}%
\begin{group}
\gdef\@dtl@widestlabel{}%
\dtl@widest=0pt\relax
\DTLforeachbibentry[#1]{#2}{%
\dtl@message{\DBIBCitekey}%
\DTLifbibfieldexists{Author}{%
\dtl@listgetalphalabel{\@dtl@thislabel}{\@dtl@key@Author}%
}}%
\DTLifbibfieldexists{Editor}{%
\dtl@listgetalphalabel{\@dtl@thislabel}{\@dtl@key@Editor}%
}}%
\DTLifbibfieldexists{Key}{%
\expandafter\dtl@get@firstthree\expandafter
{\@dtl@key@Key}{\@dtl@thislabel}%
}

```

```

    }{%
      \DTLifbibfieldexists{Organization}{%
        \expandafter\dtl@get@firstthree\expandafter
          {\@dtl@key@Organization}{\@dtl@thislabel}%
      }{%
        \expandafter\dtl@get@firstthree\expandafter
          {\DBIBentrytype}{\@dtl@thislabel}%
      }%
    }%
  }%
\DTLifbibfieldexists{Year}{\DTLifbibfieldexists{CrossRef}}{%
\DTLgetvalueforkey{\@dtl@key@Year}{Year}{#2}{CiteKey}{%
\@dtl@key@CrossRef}}}%
\DTLifbibfieldexists{Year}{%
\expandafter\dtl@get@yearsuffix\expandafter{\@dtl@key@Year}%
\expandafter\toks@\expandafter{\@dtl@thislabel}%
\expandafter\@dtl@toks@\expandafter{\@dtl@year}%
\edef\@dtl@thislabel{\the\toks@\the\@dtl@toks}%
}%
\let\@dtl@s@thislabel=\@dtl@thislabel
\@onelevel@sanitize\@dtl@s@thislabel
\@ifundefined{c@biblabel@\@dtl@s@thislabel}{%
\newcounter{biblabel@\@dtl@s@thislabel}%
\setcounter{biblabel@\@dtl@s@thislabel}{1}%
\expandafter\edef\csname @dtl@bibfirst@\@dtl@s@thislabel\endcsname{%
\DBIBcitekey}%
\expandafter\global
\expandafter\let\csname dtl@biblabel@\DBIBcitekey\endcsname=
\@dtl@thislabel
}%
\expandafter\ifnum\csname c@biblabel@\@dtl@s@thislabel\endcsname=1\relax
\expandafter\let\expandafter\@dtl@tmp
\csname @dtl@bibfirst@\@dtl@s@thislabel\endcsname
\expandafter\protected@xdef\csname dtl@biblabel@\@dtl@tmp\endcsname{%
\@dtl@thislabel a}%
\fi
\stepcounter{biblabel@\@dtl@s@thislabel}%
\expandafter\protected@xdef\csname dtl@biblabel@\DBIBcitekey\endcsname{%
\@dtl@thislabel\alph{biblabel@\@dtl@s@thislabel}}%
}%
\settowidth{\dtl@tmplength}{%
\csname dtl@biblabel@\DBIBcitekey\endcsname}%
\ifdim\dtl@tmplength>\dtl@widest
\dtl@widest=\dtl@tmplength
\expandafter\global\expandafter\let\expandafter\@dtl@widestlabel
\expandafter=\csname dtl@biblabel@\DBIBcitekey\endcsname
\fi
}%
\endgroup
}
\newcommand*{\dtl@listgetalpha label}[2]{%

```



```

\expandafter\string\csname dtl@aux@\@dtl@af\endcsname\space
already exists}{}}}}
\@onlypreamble{\DTLmultibibs}
\newcommand*{\DTLcite}{\@ifnextchar[{\@tempwattrue \dtl@citex
}{\@tempwafalse \dtl@citex[]}}
\def\dtl@citex[#1]#2#3{%
\leavevmode\let\@citea\@empty
\@cite{\@for\@citeb:=#3\do{\@citea
\def\@citea{\penalty \@m \ }%
\edef\@citeb{\expandafter\@firstofone\@citeb\@empty}%
\if@filesw
\@ifundefined{dtl@aux@#2}{%
\PackageError{datbib}{multibib `#2' not defined}{%
You need to define `#2' in \string\DTLmutlibibs}%
}{%
\expandafter\immediate
\expandafter\write\csname dtl@aux@#2\endcsname{%
\string\citation{\@citeb}}%
}%
\fi
\@ifundefined{b@#2@\@citeb}{%
\hbox{\reset@font\bfseries ?}%
\G@refundefinedtrue
\@latex@warning{Citation `\@citeb ' on page \thepage \space
undefined}}%
}{%
\@cite@ofmt{\csname b@#2@\@citeb \endcsname }%
}%
}}{#1}%
}
\newcommand*{\DTLnocite}[2]{%
\@ifundefined{dtl@aux@#1}{%
\PackageError{datbib}{multibib `#1' not defined}{%
You need to define `#1' in \string\DTLmutlibibs}%
}{%
\@bsphack
\ifx\@onlypreamble\document
\@for\@citeb:=#2\do{%
\edef\@citeb{\expandafter\@firstofone\@citeb}%
\if@filesw
\expandafter\immediate
\expandafter\write\csname dtl@aux@#1\endcsname{%
\string\citation{\@citeb}}%
\fi
\@ifundefined{b@#1@\@citeb}{%
\G@refundefinedtrue
\@latex@warning{Citation `\@citeb ' undefined}}}{%
}%
\else
\@latex@error{Cannot be used in preamble}\@eha

```

```

\fi
\@esphack
}%
}
\newcommand*\DTLloadmdbl}[3]{%
\@ifundefined{dtl@aux@#1}{%
\PackageError{datbib}{multibib `#1' not defined}{%
You need to define `#1' in \string\DTLmutlibibs}%
}%
\if@filesw
\expandafter\immediate\expandafter
\write\csname dtl@aux@#1\endcsname{\string\bibstyle{datbib}}%
\expandafter\immediate\expandafter
\write\csname dtl@aux@#1\endcsname{\string\bibdata{#3}}%
\fi
\DTLnewdb{#2}%
\edef\DTLBIBdbname{#2}%
\@input@{#1.bbl}%
}%
}
\newcommand*\DTLmbibliography}[3][\boolean{true}]{%
\begin{DTLthebibliography}[#1]{#3}%
\DTLforeachbibentry[#1]{#3}{%
\DTLmbibitem{#2} \DTLformatbibentry \DTLendbibitem
}%
\end{DTLthebibliography}%
}

```

30.12 Rollback v2.32 (datagidx-2019-09-27.sty)

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datagidx}[2019/09/27 v2.32 (NLCT)]
\RequirePackage{datatool}[=v2.32]
\RequirePackage{etoolbox}
\RequirePackage{xkeyval}
\RequirePackage{mfirstuc}
\RequirePackage{xfor}
\RequirePackage{multicol}
\RequirePackage{textcase}
\RequirePackage{afterpage}
\newcommand*\datagidx@columns}{2}
\newcommand*\DTLgidxSetColumns}[1]{%
\DTLifint{#1}%
{%
\def\datagidx@columns{#1}%
}%
{%
\PackageError{datagidx}%
{Number of columns must be an integer}%
{%

```

```

        You have requested `#1' columns, which can't be parsed as a
        number%
    }%
}%
}
\newcounter{DTLgidxChildCount}
\def\theHDTLgidxChildCount{\Label.\arabic{DTLgidxChildCount}}
\newcommand*{\DTLgidxChildCountLabel}{\theDTLgidxChildCount} }
\newcommand*{\DTLgidxChildStyle}[1]{#1}
\newcommand*{\datagidx@setchildstyle}[1]{%
    \ifcase#1\relax
        \renewcommand*{\DTLgidxChildStyle}[1]{##1}%
    \or
        \renewcommand*{\DTLgidxChildStyle}[1]{%
            \DTLgidxChildCountLabel
        }%
    \fi
}
\newcommand{\datagidx@foreachchild}{%
    \datagidx@sort@foreachchild
}
\newcommand*{\datagidx@setchildsort}[1]{%
    \ifcase#1\relax
        \renewcommand*{\datagidx@foreachchild}{%
            \datagidx@sort@foreachchild
        }%
    \or
        \renewcommand*{\datagidx@foreachchild}{%
            \datagidx@unsort@foreachchild
        }%
    \fi
}
\newcommand*{\DTLgidxPostName}{ }
\newcommand*{\DTLgidxPostChildName}{\DTLgidxPostName}
\newcommand*{\DTLgidxNameCase}[1]{#1}
\newcommand*{\datagidx@setnamecase}[1]{%
    \ifcase#1\relax
        \renewcommand*{\DTLgidxNameCase}[1]{##1}%
    \or
        \let\DTLgidxNameCase\MakeTextUppercase
    \or
        \let\DTLgidxNameCase\MakeTextLowercase
    \or
        \let\DTLgidxNameCase\xmakefirstuc
    \or
        \let\DTLgidxNameCase\xcapitalisewords
    \fi
}
\newcommand*{\DTLgidxNameFont}[1]{\textnormal{#1}}
\newcommand*{\DTLgidxPostDescription}{}

```

```

\newcommand*\datagidx@setpostdesc}[1]{%
  \ifcase#1\relax
    \renewcommand*\DTLgidxPostDescription}{}%
  \or
    \renewcommand*\DTLgidxPostDescription}{.}%
  \fi
}
\newcommand*\DTLgidxPreLocation{\enspace}
\newcommand*\datagidx@setprelocation}[1]{%
  \ifcase#1\relax
    \renewcommand*\DTLgidxPreLocation}{}%
  \or
    \renewcommand*\DTLgidxPreLocation{\enspace}%
  \or
    \renewcommand*\DTLgidxPreLocation}{ }%
  \or
    \renewcommand*\DTLgidxPreLocation}{\dotfill}%
  \or
    \renewcommand*\DTLgidxPreLocation}{\hfill}%
  \fi
}
\newcommand*\DTLgidxLocation{\dtldolocationlist}
\newcommand*\datagidx@setlocation}[1]{%
  \ifcase#1\relax
    \renewcommand*\DTLgidxLocation}{}%
  \or
    \renewcommand*\DTLgidxLocation{\dtldolocationlist}%
  \or
    \renewcommand*\DTLgidxLocation{\dtldofirstlocation}%
  \fi
}
\newcommand*\DTLgidxSee{%
  \DTLifnull{\See}%
  {}%
  {%
    \DTLgidxPreLocation
    \DTLgidxFormatSee{\seename}{\See}%
  }%
}
\newcommand*\DTLgidxSeeAlso{%
  \DTLifnull{\SeeAlso}%
  {}%
  {%
    \DTLgidxFormatSeeAlso{\seealso}{\SeeAlso}%
  }%
}
\newcommand*\DTLgidxChildrenSeeAlso{%
  \DTLgidxChildren
  \DTLgidxSeeAlso
}

```

```

\newcommand*\datagidx@setsee}[1]{%
  \ifcase#1\relax
    \renewcommand*\DTLgidxSee{%
      \DTLifnull{\See}{}%
      {%
        , \DTLgidxFormatSee{\seename}{\See}%
      }%
    }%
  \or
    \renewcommand*\DTLgidxSee{%
      \DTLifnull{\See}{%
        {%
          \space(\DTLgidxFormatSee{\seename}{\See})%
        }%
      }%
    }%
  \or
    \renewcommand*\DTLgidxSee{%
      \DTLifnull{\See}{}%
      {%
        . \DTLgidxFormatSee{\xmakefirstuc{\seename}}{\See}%
      }%
    }%
  \or
    \renewcommand*\DTLgidxSee{%
      \DTLifnull{\See}{%
        {%
          \space\DTLgidxFormatSee{\seename}{\See}%
        }%
      }%
    }%
  \or
    \renewcommand*\DTLgidxSee{%
      \DTLifnull{\See}{%
        {%
          \DTLgidxFormatSee{\seename}{\See}%
        }%
      }%
    }%
  \or
    \renewcommand*\DTLgidxSee{%
      \DTLifnull{\See}{%
        {%
          ; \DTLgidxFormatSee{\seename}{\See}%
        }%
      }%
    }%
  \or
    \renewcommand*\DTLgidxSee{%
      \DTLifnull{\See}{%
        {%
          \DTLgidxPreLocation\DTLgidxFormatSee{\seename}{\See}%
        }%
      }%
    }%
}

```

```

\fi
}
\newcommand*{\DTLgidxSymDescSep}{\space}
\newlength\datagidxsymbolwidth
\newlength\datagidxlocationwidth
\newcommand{\DTLgidxFormatDesc}[1]{#1}
\newcommand*{\DTLgidxSymbolDescription}{%
  \DTLgidxSymbolDescLeft
  \DTLgidxSymbolDescRight
}
\newcommand*{\DTLgidxSymbolDescLeft}{%
  \ifdefempty{\Symbol}{}{(\Symbol)\DTLgidxSymDescSep}%
}
\newcommand*{\DTLgidxSymbolDescRight}{%
  \ifdefempty{\Description}{}%
  {%
    \DTLgidxFormatDesc{\Description}\DTLgidxPostDescription
  }%
}
\newif\if@datagidxsymbolleft
\@datagidxsymbollefttrue
\newcommand*{\datagidx@formatsymdesc}[1]{%
  \ifcase#1\relax
    \renewcommand*{\DTLgidxSymbolDescLeft}{%
      \ifdefempty{\Symbol}{}{\Symbol}%
    }%
    \renewcommand*{\DTLgidxSymbolDescRight}{}%
  \or
    \renewcommand*{\DTLgidxSymbolDescLeft}{%
      \ifdefempty{\Description}{}%
      {%
        \DTLgidxFormatDesc{\Description}\DTLgidxPostDescription
      }%
    }%
    \renewcommand*{\DTLgidxSymbolDescRight}{}%
  \or
    \renewcommand*{\DTLgidxSymbolDescLeft}{%
      \ifdefempty{\Symbol}{}{(\Symbol)\DTLgidxSymDescSep}%
    }%
    \renewcommand*{\DTLgidxSymbolDescRight}{%
      \ifdefempty{\Description}{}%
      {%
        \DTLgidxFormatDesc{\Description}\DTLgidxPostDescription
      }%
    }%
  \or
    \renewcommand*{\DTLgidxSymbolDescLeft}{%

```

```

        \ifdefempty{\Description}{}%
        {%
        \DTLgidxFormatDesc{\Description}%
        \DTLgidxPostDescription\DTLgidxSymDescSep
        }%
    }%
    \renewcommand*{\DTLgidxSymbolDescRight}{%
        \ifdefempty{\Symbol}{\Symbol}%
    }%
    \@datagidxsymbolleftfalse
\or
    \renewcommand*{\DTLgidxSymbolDescLeft}{%
        \ifdefempty{\Symbol}{\Symbol\DTLgidxSymDescSep}%
    }%
    \renewcommand*{\DTLgidxSymbolDescRight}{%
        \ifdefempty{\Description}{}%
        {%
        \DTLgidxFormatDesc{\Description}%
        \DTLgidxPostDescription
        }%
    }%
    \@datagidxsymbollefttrue
\or
    \renewcommand*{\DTLgidxSymbolDescLeft}{%
        \ifdefempty{\Description}{}%
        {%
        \DTLgidxFormatDesc{\Description}%
        \DTLgidxPostDescription\DTLgidxSymDescSep
        }%
    }%
    \renewcommand*{\DTLgidxSymbolDescRight}{%
        \ifdefempty{\Symbol}{\Symbol}%
    }%
    \@datagidxsymbolleftfalse
\fi
}
\newcommand*{\DTLgidxSetCompositor}[1]{%
    \undef\datagidx@docompllist
    \DeclareListParser{\datagidx@docompllist}{#1}%
    \def\datagidx@compositor{#1}%
}
\DTLgidxSetCompositor{.}
\newcommand*{\datagidx@do@sort}{\datagidx@sort}
\newcommand*{\datagidx@optimize@sort}{%
    \ifdef\datagidx@do@optimize@sort
    {%
        \datagidx@sort
    }%
    {%
        \protected@write\@auxout{}{%

```

```

        \string\gdef\string\datagidx@do@optimize@sort}{%
    }%
    \global\let\@datagidx@dorerun@warn@sort\@data@rerun@warn@sort
}
}
\newif\if@datagidx@warn
\@datagidx@warntrue
\newcommand*\@datagidx@dorerun@warn{}
\AtEndDocument{\if@datagidx@warn\@datagidx@dorerun@warn\fi}
\newcommand*\@datagidx@dorerun@warn@sort{}
\AtEndDocument{\if@datagidx@warn\@datagidx@dorerun@warn@sort\fi}
\newcommand*\@data@rerun@warn@sort{%
    \PackageWarningNoLine{datagidx}{Rerun required to sort the
    index/glossary databases}%
}
\newcommand*\@data@rerun@warn{%
    \PackageWarningNoLine{datagidx}{Rerun required to ensure the
    index/glossary location lists are up-to-date}%
}
\newcommand*\@datagidx@do@highopt@optimize}{%
    \renewcommand*\@datagidx@do@sort}{%
        \ifcsdef{datagidx@do@highopt@sort@\DTLgidxCurrentdb}%
        {%
            \csuse{datagidx@do@highopt@sort@\DTLgidxCurrentdb}%
        }%
        {%
        }%
        \bgroup
        \def\dtl@saverawdbhook{%
            \let\db@col@id@w\@datagidx@db@col@id@w
            \def\DTLgidxName{\string\DTLgidxName\space}%
            \def\DTLgidxMac{\string\DTLgidxMac\space}%
            \def\DTLgidxRank{\string\DTLgidxRank\space}%
            \def\DTLgidxParen{\string\DTLgidxParen\space}%
            \def\DTLgidxParticle{\string\DTLgidxParticle\space}%
            \def\DTLgidxOffice{\string\DTLgidxOffice\space}%
            \def\DTLgidxSaint{\string\DTLgidxSaint\space}%
            \def\DTLgidxPlace{\string\DTLgidxPlace\space}%
            \def\DTLgidxIgnore{\string\DTLgidxIgnore\space}%
            \def\DTLgidxNameNum{\string\DTLgidxNameNum\space}%
            \def\DTLgidxSubject{\string\DTLgidxSubject\space}%
        }%
        \DTLsaverawdb{\DTLgidxCurrentdb}{\datagidxhighoptfilename\DTLgidxCurrentdb}%
        \egroup
    }%
    \def\newgidx{\datagidx@highopt@newgidx}%
    \def\newterm{\datagidx@highopt@newterm}%
}
\def\@datagidx@db@col@id@w#1\db@col@id@end@\db@col@elt@w#2\db@col@elt@end@\db@col@id@w#3
    \expandafter\@gobble\string\%^^^J

```

```

\string\db@col@id@w\space #1%
\expandafter\@gobble\string\%^J
\string\db@col@id@end@\space
\expandafter\@gobble\string\%^J
\string\db@col@elt@w\space
\expandafter\ifnum\csname dtl@ci@\DTLgidxCurrenldb @Used\endcsname=#1\space
0%
\else
\expandafter\ifnum\csname dtl@ci@\DTLgidxCurrenldb @Location\endcsname=#1\space
\else
\expandafter\ifnum\csname dtl@ci@\DTLgidxCurrenldb @CurrentLocation\endcsname=#1\space
\else
\expandafter\ifnum\csname dtl@ci@\DTLgidxCurrenldb @Sort\endcsname=#1\space
\protect#2%
\else
#2%
\fi
\fi
\fi
\fi
\fi
\expandafter\@gobble\string\%^J
\string\db@col@elt@end@\space
\expandafter\@gobble\string\%^J
\string\db@col@id@w\space #3%
\expandafter\@gobble\string\%^J
\string\db@col@id@end@\space
}
\newcommand*{\datagidx@do@highopt@update}[1]{}
\newcommand*{\datagidxhighoptfilename}[1]{\jobname-#1.gidx}
\define@choicekey{datagidx.sty}{optimize}[\val\nr]%
{off, low, high}[high]%
{%
\ifcase\nr\relax
\renewcommand*{\datagidx@do@sort}{\datagidx@sort}
\or
\renewcommand*{\datagidx@do@sort}{\datagidx@optimize@sort}
\or
\datagidx@do@highopt@optimize
\fi
}
\define@choicekey{datagidx.sty}{nowarn}[\val\nr]{true, false}[true]%
{%
\ifcase\nr\relax
\@datagidx@warnfalse
\or
\@datagidx@warntrue
\fi
}
\define@choicekey{datatool.sty}{utf8}{true, false}[true]{%
\setbool{@dtl@utf8}{#1}%

```

```

}
\define@key{datagidx.sty}{columns}%
{%
  \DTLgidxSetColumns{#1}%
}
\define@choicekey{datagidx.sty}{child}[\val\nr]%
{named,noname}%
{%
  \datagidx@setchildstyle\nr
}
\define@choicekey{datagidx.sty}{namecase}[\val\nr]%
{nochange,uc,lc,firstuc,capitalise}%
{%
  \datagidx@setnamecase\nr
}
\define@key{datagidx.sty}{namefont}%
{%
  \renewcommand*{\DTLgidxNameFont}[1]{\fontfamily{#1}}%
}
\define@key{datagidx.sty}{postname}%
{%
  \renewcommand*{\DTLgidxPostName}{#1}%
}
\define@choicekey{datagidx.sty}{postdesc}[\val\nr]%
{none,dot}%
{%
  \datagidx@setpostdesc\nr
}
\define@choicekey{datagidx.sty}{prelocation}[\val\nr]%
{none,enspace,space,dotfill,hfill}%
{%
  \datagidx@setprelocation\nr
}
\define@choicekey{datagidx.sty}{location}[\val\nr]%
{hide,list,first}%
{\datagidx@setlocation\nr}
\define@choicekey{datagidx.sty}{see}[\val\nr]%
{comma,brackets,dot,space,nosep,semicolon,location}%
{\datagidx@setsee\nr}
\define@choicekey{datagidx.sty}{symboldesc}[\val\nr]%
{symbol,desc,(symbol) desc,desc (symbol),symbol desc,desc symbol}%
{\datagidx@formatsymdesc\nr}
\define@key{datagidx.sty}{compositor}%
{%
  \DTLgidxSetCompositor{#1}%
}%
\DeclareOptionX{final}{%
  \let\datagidxshowifdraft\@gobble
}
\let\datagidxshowifdraft\@gobble

```

```

\DeclareOptionX{draft}{%
  \let\datagidxshowifdraft\@firstofone
}
\define@choicekey{datagidx.sty}{verbose}[\val\nr]{%
  {true,false}[true]%
  {%
    \csuse{dtlverbose\val}%
  }
}
\ProcessOptionsX
\DTLnewdb{datagidx}
\providecommand*\seename{see}
\providecommand*\seealsoname{see also}
\newcommand*\DTLgidxSeeTagFont[1]{\emph{#1}}
\newcommand*\DTLgidxFormatSee[2]{%
  \DTLgidxSeeTagFont{#1} \DTLgidxSeeList{#2}%
}
\newcommand*\DTLgidxFormatSeeAlso[2]{%
  \datagidxdoseealso
  {%
    \DTLgidxSeeTagFont{#1} \DTLgidxSeeList{#2}%
  }%
}
\newcommand*\datagidxdoseealso[1]{%
  \datagidxseealsostart
  #1%
  \datagidxseealsoend
}
\newcommand*\DTLgidxSeeList[1]{%
  \def\datagidx@sep{}%
  \@for\dtl@thislabel:=#1\do
  {%
    \ifx\@xfor@nextelement\@nnil
      \ifdefempty{\datagidx@sep}%
      {%
        }%
      {%
        \DTLidxSeeLastSep
      }%
    \else
      \datagidx@sep
      \let\datagidx@sep\DTLidxSeeSep
    \fi
    \DTLidxFormatSeeItem{\dtl@thislabel}%
  }%
}
\newcommand*\DTLidxFormatSeeItem[1]{%
  \DTLgidxFetchEntry{\datagidx@value}{#1}{Name}%
  \datagidxlink{#1}%
  {%
    \datagidx@value
  }%
}

```

```

    }%
}
\newcommand*\DTLidxSeeSep}{, }
\newcommand*\DTLidxSeeLastSep}{ \& }
\newcommand*\DTLgidxDoSeeOrLocation}{%
  \DTLifnull\See
  {%
    \ifdefempty\Location
    {%
    }%
    {%
      \DTLgidxPreLocation
      \DTLgidxLocation
    }%
  }%
  {%
    \DTLgidxSee
  }%
}
\newcommand*\datagidx@sortchildren}{%
  \def\datagidx@sortedlist{}%
  \@for\Label:=\Children\do
  {%
    \edef\do@getrow{%
      \noexpand\dtlgetrowforvalue
      {\DTLgidxCurrentdb}%
      {\dtlcolumnindex{\DTLgidxCurrentdb}{Label}}%
      {\Label}%
    }%
    \do@getrow
    \ifdefempty\datagidx@sortedlist
    {%
      \edef\datagidx@newsortedlist{{\number\dtlrownum}{\Label}}%
    }%
    {%
      \def\datagidx@newsortedlist{}%
      \@for\@datagidx@thisval:=\datagidx@sortedlist\do
      {%
        \edef\datagidx@thisidx{\expandafter\@firstoftwo\@datagidx@thisval}%
        \ifnum\datagidx@thisidx>\dtlrownum\relax
          \ifdefempty\datagidx@newsortedlist
          {%
            \eappto\datagidx@newsortedlist
            {%
              {\number\dtlrownum}{\Label},\@datagidx@thisval
            }%
          }%
        }%
        {%
          \eappto\datagidx@newsortedlist
          {%

```

```

        ,{\number\dtlrownum}{\Label}, \@datagidx@thisval
    }%
  }%
  \@endfortrue
\else
\ifdefempty\datagidx@newsortedlist
{%
  \edef\datagidx@newsortedlist{%
    \@datagidx@thisval
  }%
}%
{%
\ea\pto\datagidx@newsortedlist
{%
  , \@datagidx@thisval
}%
}%
\fi
}%
\if@endfor
\ifdefempty\@forremainder
{%
}%
{%
  \ea\pto\datagidx@newsortedlist{, \@forremainder}%
}%
\else
\ifdefempty\datagidx@newsortedlist
{%
  \edef\datagidx@newsortedlist{{\number\dtlrownum}{\Label}}%
}%
{%
  \ea\pto\datagidx@newsortedlist{, {\number\dtlrownum}{\Label}}%
}%
\fi
\let\datagidx@sortedlist\datagidx@newsortedlist
\@endforfalse
}%
}
\newcommand{\datagidx@sort@foreachchild}[1]{%
  \datagidx@sortchildren
  \@for\@datagidx@thisval:=\datagidx@sortedlist\do
  {%
    \edef\Label{\expandafter\@secondoftwo\@datagidx@thisval}%
    #1%
  }%
}
\newcommand{\datagidx@unsort@foreachchild}[1]{%
  \@for\Label:=\Children\do

```

```

    {%
      #1%
    }%
  }
  \newcommand*{\DTLgidxChildren}{%
    \bgroup
      \DTLifnull\Children
        {}%
      {%
        \advance\datagidx@level by 1\relax
        \datagidxchildstart
        \let\Parent\Label
        \datagidx@foreachchild
        {%
          \edef\do@getrow{%
            \noexpand\dtlgetrowforvalue
              {\DTLgidxCurrentdb}%
              {\dtlcolumnindex{\DTLgidxCurrentdb}{Label}}%
              {\Label}%
          }%
          \do@getrow
          \dtlgetentryfromcurrentrow
            {\Location}%
            {\dtlcolumnindex{\DTLgidxCurrentdb}{Location}}%
          \dtlgetentryfromcurrentrow
            {\See}%
            {\dtlcolumnindex{\DTLgidxCurrentdb}{See}}%
          \dtlgetentryfromcurrentrow
            {\SeeAlso}%
            {\dtlcolumnindex{\DTLgidxCurrentdb}{SeeAlso}}%
          \DTLifnull\Location
            {%
              \DTLifnull\See
                {}%
              \DTLifnull\SeeAlso
                {}%
            }%
            \datagidx@displaychild
          }%
        }%
        {%
          \datagidx@displaychild
        }%
      }%
      {%
        \datagidx@displaychild
      }%
    }%
  \datagidxchildend
}%

```

```

\egroup
}
\newcommand*{\datagidxgetchildfields}{%
  \dtlgetentryfromcurrentrow
  {\Name}%
  {\dtlcolumnindex{\DTLgidxCurrentdb}{Name}}%
  \dtlgetentryfromcurrentrow
  {\Description}%
  {\dtlcolumnindex{\DTLgidxCurrentdb}{Description}}%
  \dtlgetentryfromcurrentrow
  {\Symbol}%
  {\dtlcolumnindex{\DTLgidxCurrentdb}{Symbol}}%
  \dtlgetentryfromcurrentrow
  {\Long}%
  {\dtlcolumnindex{\DTLgidxCurrentdb}{Long}}%
  \dtlgetentryfromcurrentrow
  {\Short}%
  {\dtlcolumnindex{\DTLgidxCurrentdb}{Short}}%
  \dtlgetentryfromcurrentrow
  {\Text}%
  {\dtlcolumnindex{\DTLgidxCurrentdb}{Text}}%
  \dtlgetentryfromcurrentrow
  {\Plural}%
  {\dtlcolumnindex{\DTLgidxCurrentdb}{Plural}}%
  \dtlgetentryfromcurrentrow
  {\Short}%
  {\dtlcolumnindex{\DTLgidxCurrentdb}{Used}}%
  \dtlgetentryfromcurrentrow
  {\Children}%
  {\dtlcolumnindex{\DTLgidxCurrentdb}{Child}}%
}
\newcommand*{\datagidx@displaychild}{%
  \datagidxgetchildfields
  \datagidxchilditem
}
\ifdef{\chapter}
{%
  \newcommand*{\datagidx@heading}{\chapter*}
}%
{%
  \newcommand*{\datagidx@heading}{\section*}
}
\let\DTLgidxNoHeading@gobble
\newcommand*{\datagidx@postheading}{}
\newcommand*{\datagidx@multicols}{multicols}
\newcommand*{\datagidx@sort}{%
  \dtlsort{Sort,FirstId}{\DTLgidxCurrentdb}{\dtlwordindexcompare}%
}
\providecommand{\@idxitem}{\par\hangindent 40\p@}
\newcommand*{\datagidxstart}%

```

```

{%
  \bgroup
  \setlength{\parindent}{0pt}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \let\item\@idxitem
}
\newcommand*\@datagidxend{\egroup}
\newcommand*\@datagidxtarget}[2]{%
  \ifdef\hypertarget
  {%
    \bgroup
    \let\glsadd@gobble
    \settoheight\dimen@{#2}%
    \raisebox{\dimen@}{\hypertarget{#1}{}}%
    \egroup
  }%
  {%
  }%
  #2%
}
\newcommand*\@datagidxtarget{\@datagidxtarget}
\newcommand*\@datagidxlink}[2]{%
  \ifdef\hyperlink
  {%
    \hyperlink{#1}{#2}%
  }%
  {%
    #2%
  }%
}
\newcommand*\@datagidxlink{\@datagidxlink}
\newcommand*\DTLgidxEnableHyper{%
  \let\datagidxtarget\@datagidxtarget
  \let\datagidxlink\@datagidxlink
}
\newcommand*\DTLgidxDisableHyper{%
  \let\datagidxtarget\@secondoftwo
  \let\datagidxlink\@secondoftwo
}
\newcommand*\@datagidxgroupsep{}
\newcommand*\@datagidxgroupheader{}
\newcommand*\@datagidxitem{}%
\newcommand*\@datagidxchildstart{}
\newcommand*\@datagidxchildend{}
\newcommand*\@datagidxchilditem{}%
\newcommand*\@datagidxseealsostart{}
\newcommand*\@datagidxseealsoend{}
\newcommand*\@datagidx@doifsymlocwidth}[3]{%
  \setlength{\dtl@tmplength}{\linewidth}%
  \addtolength{\dtl@tmplength}{-#1}%
}

```

```

\settowidth{\dimen@}{#2}%
\addtolength{\dtl@tmplength}{-\dimen@}%
\addtolength{\dtl@tmplength}{-\datagidxsymbolwidth}%
\addtolength{\dtl@tmplength}{-\datagidxlocationwidth}%
\settowidth{\dimen@}{\DTLgidxPreLocation}%
\addtolength{\dtl@tmplength}{-\dimen@}%
\settowidth{\dimen@}{\DTLgidxSymDescSep}%
\addtolength{\dtl@tmplength}{-\dimen@}%
\if@datagidxsymbolleft
  \begin{minipage}[t]{\datagidxsymbolwidth}%
    \datagidxsymalign
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescLeft
  \end{minipage}%
  \DTLgidxSymDescSep
  \begin{minipage}[t]{\dtl@tmplength}%
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescRight
  \end{minipage}%
\else
  \begin{minipage}[t]{\dtl@tmplength}%
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescRight
  \end{minipage}%
  \DTLgidxSymDescSep
  \begin{minipage}[t]{\datagidxsymbolwidth}%
    \datagidxsymalign
    \let\DTLgidxSymDescSep\@empty
    \DTLgidxSymbolDescLeft
  \end{minipage}%
\fi
\DTLgidxPreLocation
\begin{minipage}[t]{\datagidxlocationwidth}%
  \datagidxlocalign
  \let\DTLgidxPreLocation\@empty
  #3%
\end{minipage}%
}
\newcommand*{\datagidx@doiflocwidth}[3]{%
  \setlength{\dtl@tmplength}{\linewidth}%
  \addtolength{\dtl@tmplength}{-#1}%
  \settowidth{\dimen@}{#2}%
  \addtolength{\dtl@tmplength}{-\dimen@}%
  \addtolength{\dtl@tmplength}{-\datagidxlocationwidth}%
  \settowidth{\dimen@}{\DTLgidxPreLocation}%
  \addtolength{\dtl@tmplength}{-\dimen@}%
  \begin{minipage}[t]{\dtl@tmplength}%
    \DTLgidxSymbolDescription
  \end{minipage}%
  \DTLgidxPreLocation

```

```

\begin{minipage}[t]{\datagidxlocationwidth}%
  \datagidxlocalign
  \let\DTLgidxPreLocation\@empty
  #3%
\end{minipage}%
}
\newcommand*{\datagidx@doifsymwidth}[3]{%
  \setlength{\dtl@tmplength}{\linewidth}%
  \addtolength{\dtl@tmplength}{-#1}%
  \settowidth{\dimen@}{#2}%
  \addtolength{\dtl@tmplength}{-\dimen@}%
  \addtolength{\dtl@tmplength}{-\datagidxsymbolwidth}%
  \settowidth{\dimen@}{\DTLgidxSymDescSep}%
  \addtolength{\dtl@tmplength}{-\dimen@}%
  \if@datagidxsymbolleft
    \begin{minipage}[t]{\datagidxsymbolwidth}%
      \datagidxsymalign
      \let\DTLgidxSymDescSep\@empty
      \DTLgidxSymbolDescLeft
    \end{minipage}%
    \DTLgidxSymDescSep
    \begin{minipage}[t]{\dtl@tmplength}%
      \let\DTLgidxSymDescSep\@empty
      \DTLgidxSymbolDescRight
      #3%
    \end{minipage}%
  \else
    \begin{minipage}[t]{\dtl@tmplength}%
      \let\DTLgidxSymDescSep\@empty
      \DTLgidxSymbolDescRight
    \end{minipage}%
    \DTLgidxSymDescSep
    \begin{minipage}[t]{\datagidxsymbolwidth}%
      \datagidxsymalign
      \let\DTLgidxSymDescSep\@empty
      \DTLgidxSymbolDescLeft
      #3%
    \end{minipage}%
  \fi
}
\newcommand*{\datagidxlocalign}{\raggedleft}
\newcommand*{\datagidxsymalign}{\centering}
\newcommand*{\datagidxsetstyle}[1]{%
  \ifcsdef{datagidx@style@#1}%
  {%
    \csuse{datagidx@style@#1}%
  }%
  {%
    \PackageError{datagidx}{Unknown style `#1'}{ }%
  }%
}

```

```

}
\newcommand*{\datagidx@style@index}{%
\renewcommand*{\datagidxstart}%
{%
\bgroup
\setlength{\parindent}{0pt}%
\setlength{\parskip}{0pt plus 0.3pt}%
\raggedright
\let\item\@idxitem
\ifdim\datagidxsymbolwidth>0pt\relax
\ifdim\datagidxlocationwidth>0pt\relax
\def\datagidx@item@body{%
\datagidx@doifsymlocwidth{0pt}%
{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
{%
\DTLgidxDoSeeOrLocation
}%
}%
\else
\def\datagidx@item@body{%
\datagidx@doiflocwidth{0pt}%
{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
{%
\DTLgidxDoSeeOrLocation
}%
}%
\fi
\else
\ifdim\datagidxlocationwidth>0pt\relax
\def\datagidx@item@body{%
\datagidx@doiflocwidth{0pt}%
{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
{%
\DTLgidxDoSeeOrLocation
}%
}%
\else
\def\datagidx@item@body{%
\DTLgidxSymbolDescription
\DTLgidxDoSeeOrLocation
}%
\fi
\fi
}%
\renewcommand*{\datagidxend}{\egroup}%
\renewcommand*{\datagidxgroupsep}{\ifdatagidxshowgroups\indexspace\fi}%
\renewcommand{\datagidxgroupheader}{%
\ifdatagidxshowgroups
\item
\makebox[\linewidth]%

```

```

        {%
          \textbf{\DTLgidxGroupHeaderTitle{\datagidxcurrentgroup}}%
        }%
        \DTLpar\nobreak\@afterheading
    \fi
}%
\renewcommand*{\datagidxitem}{%
  \ifdefempty\datagidxprevgroup
  {%
    \datagidxgroupheader
  }%
  {%
    \ifdefequal\datagidxcurrentgroup\datagidxprevgroup
    {%
      }%
    }%
    {%
      \datagidxgroupsep
      \datagidxgroupheader
    }%
  }%
  \item
  \datagidxtarget{\Label}%
  {%
    \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
  }%
  \DTLgidxPostName
  \datagidx@item@body
  \DTLgidxChildrenSeeAlso
}%
\renewcommand*{\datagidxchildstart}{%
  {%
    \bgroup
    \setlength{\parindent}{0pt}%
    \setlength{\parskip}{0pt plus 0.3pt}%
    \let\item\@idxitem
  }%
\renewcommand*{\datagidxchildend}{\egroup}%
\renewcommand*{\datagidxchilditem}{%
  \setlength{\dimen@}{\datagidxindent}%
  \multiply\dimen@ by \datagidx@level\relax
  \@idxitem\hspace*{\dimen@}%
  \refstepcounter{DTLgidxChildCount}%
  \datagidxtarget{\Label}%
  {%
    \DTLgidxChildStyle
  }%
  \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
  \DTLgidxPostChildName
  }%
}%

```

```

\DTLgidxSymbolDescription
\DTLgidxDoSeeOrLocation
\DTLgidxChildrenSeeAlso
}%
\renewcommand*{\datagidxseealsostart}{%
{%
  \bgroup
  \setlength{\parindent}{0pt}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \setlength{\dimen@}{\datagidxindent}%
  \advance\datagidx@level by 1\relax
  \multiply\dimen@ by \datagidx@level\relax
  \@idxitem\hspace*{\dimen@}%
}%
\renewcommand{\datagidxseealsoend}{\egroup}%
}
\datagidx@style@index
\newcommand*{\datagidx@style@indexalign}{%
\renewcommand*{\datagidxstart}{%
{%
  \bgroup
  \setlength{\parindent}{0pt}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \setlength{\datagidxnamewidth}{0pt}%
  \DTLforeach*{\DTLgidxCurrentdb}{%
    {\Name=Name,\Location=Location,\See=See,\SeeAlso=SeeAlso,%
    \Parent=Parent}%
  {%
    \DTLifnull{\Parent}%
    {%
      \datagidx@doifdisplayed
      {%
        \settoheight{\dimen@}{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
        \ifdim\dimen@>\datagidxnamewidth\relax
          \datagidxnamewidth=\dimen@\relax
        \fi
      }%
    }%
  }%
  }%
  \settoheight{\dimen@}{\DTLgidxPostName}%
  \addtolength{\datagidxnamewidth}{\dimen@}%
  \setlength{\datagidxdescwidth}{\linewidth}%
  \addtolength{\datagidxdescwidth}{-\datagidxnamewidth}%
  \ifdim\datagidxsymbolwidth>0pt\relax
    \addtolength{\datagidxdescwidth}{-\datagidxsymbolwidth}%
    \settoheight{\dimen@}{\DTLgidxSymDescSep}%
    \addtolength{\datagidxdescwidth}{-\dimen@}%
  \fi
  \ifdim\datagidxlocationwidth>0pt\relax

```

```

\addtolength{\datagidxdescwidth}{-\datagidxlocationwidth}%
\settowidth{\dimen@}{\DTLgidxPreLocation}%
\addtolength{\datagidxdescwidth}{-\dimen@}%
\fi
\ifdim\datagidxsymbolwidth>0pt\relax
\ifdim\datagidxlocationwidth>0pt\relax
\if@datagidxsymbolleft
\def\datagidx@item@body{%
\begin{minipage}[t]{\datagidxsymbolwidth}%
\datagidxsymalign
\let\DTLgidxSymDescSep\@empty
\DTLgidxSymbolDescLeft
\end{minipage}%
\DTLgidxSymDescSep
\begin{minipage}[t]{\datagidxdescwidth}%
\let\DTLgidxSymDescSep\@empty
\setlength{\parskip}{0pt plus 0.3pt}%
\DTLgidxSymbolDescRight
\end{minipage}%
\DTLgidxPreLocation
\begin{minipage}[t]{\datagidxlocationwidth}%
\datagidxlocalign
\let\DTLgidxPreLocation\@empty
\DTLgidxDoSeeOrLocation
\end{minipage}%
}%
\else
\def\datagidx@item@body{%
\begin{minipage}[t]{\datagidxdescwidth}%
\let\DTLgidxSymDescSep\@empty
\DTLgidxSymbolDescLeft
\end{minipage}%
\DTLgidxSymDescSep
\begin{minipage}[t]{\datagidxsymbolwidth}%
\datagidxsymalign
\let\DTLgidxSymDescSep\@empty
\setlength{\parskip}{0pt plus 0.3pt}%
\DTLgidxSymbolDescRight
\end{minipage}%
\DTLgidxPreLocation
\begin{minipage}[t]{\datagidxlocationwidth}%
\datagidxlocalign
\let\DTLgidxPreLocation\@empty
\DTLgidxDoSeeOrLocation
\end{minipage}%
}%
\fi
\else
\if@datagidxsymbolleft
\def\datagidx@item@body{%

```

```

\begin{minipage}[t]{\datagidxsymbolwidth}%
  \datagidxsymalign
  \let\DTLgidxSymDescSep\@empty
  \DTLgidxSymbolDescLeft
\end{minipage}%
\DTLgidxSymDescSep
\begin{minipage}[t]{\datagidxdescwidth}%
  \let\DTLgidxSymDescSep\@empty
  \setlength{\parskip}{0pt plus 0.3pt}%
  \DTLgidxSymbolDescRight
  \DTLgidxDoSeeOrLocation
\end{minipage}%
}%
\else
\def\datagidx@item@body{%
\begin{minipage}[t]{\datagidxdescwidth}%
  \let\DTLgidxSymDescSep\@empty
  \DTLgidxSymbolDescLeft
\end{minipage}%
\DTLgidxSymDescSep
\begin{minipage}[t]{\datagidxsymbolwidth}%
  \datagidxsymalign
  \let\DTLgidxSymDescSep\@empty
  \setlength{\parskip}{0pt plus 0.3pt}%
  \DTLgidxSymbolDescRight
  \DTLgidxDoSeeOrLocation
\end{minipage}%
}%
\fi
\fi
\else
\ifdim\datagidxlocationwidth>0pt\relax
\def\datagidx@item@body{%
\begin{minipage}[t]{\datagidxdescwidth}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \DTLgidxSymbolDescription
\end{minipage}%
\DTLgidxPreLocation
\begin{minipage}[t]{\datagidxlocationwidth}%
\datagidxlocalign
  \let\DTLgidxPreLocation\@empty
  \DTLgidxDoSeeOrLocation
}%
\else
\def\datagidx@item@body{%
\begin{minipage}[t]{\datagidxdescwidth}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \DTLgidxSymbolDescription
  \DTLgidxDoSeeOrLocation
\end{minipage}%

```

```

    }%
  \fi
\fi
}%
\renewcommand*{\datagidxend}{\egroup}%
\renewcommand*{\datagidxgroupsep}{}%
\renewcommand*{\datagidxgroupheader}{}%
\renewcommand*{\datagidxitem}{%
  \ifdefempty\datagidxprevgroup
  {%
    \datagidxgroupheader
  }%
  {%
    \ifdefequal\datagidxcurrentgroup\datagidxprevgroup
    {%
      }%
    }%
    {%
      \datagidxgroupsep
      \datagidxgroupheader
    }%
  }%
  \hangindent0pt\relax
  \parindent0pt\relax
  \makebox[\datagidxnamewidth][l]%
  {%
    \datagidxtarget{\Label}%
    {%
      \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
      \DTLgidxPostName
    }%
  }%
  \datagidx@item@body
  \par
  \DTLgidxChildrenSeeAlso
  \par
}%
\renewcommand*{\datagidxchildstart}%
{%
  \bgroup
  \setlength{\dimen@}{\datagidxindent}%
  \multiply\dimen@ by \datagidx@level\relax
  \setlength{\dtl@tmplength}{\linewidth}%
  \addtolength{\dtl@tmplength}{-\dimen@}%
  \setlength{\parindent}{0pt}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \edef\item{\noexpand\parshape=1 \the\dimen@ \the\dtl@tmplength}%
  \setlength{\datagidxnamewidth}{0pt}%
  \DTLforeach*{\DTLgidxCurrentdb}%
  {\Name=Name,\Location=Location,\See=See,\SeeAlso=SeeAlso,%
  \Parent=Parent}%

```

```

{%
  \DTLifnull{\Parent}%
  {%
    \datagidx@doifdisplayed
    {%
      \settowidth{\dimen@}%
      {%
        \DTLgidxChildStyle
        {%
          \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
        }%
      }%
      \ifdim\dimen@>\datagidxnamewidth\relax
        \datagidxnamewidth=\dimen@\relax
      \fi
    }%
  }%
  {}%
}%
\settowidth{\dimen@}{\DTLgidxChildStyle\DTLgidxPostChildName}%
\addtolength{\datagidxnamewidth}{\dimen@}%
\setlength{\datagidxdescwidth}{\dtl@tmplength}%
\addtolength{\datagidxdescwidth}{-\datagidxnamewidth}%
}%
\renewcommand{\datagidxchildend}{\egroup}%
\renewcommand*{\datagidxchilditem}{%
  \item
  \refstepcounter{DTLgidxChildCount}%
  \makebox[\datagidxnamewidth][l]%
  {%
    \datagidxtarget{\Label}%
    {%
      \DTLgidxChildStyle
      {%
        \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
        \DTLgidxPostChildName
      }%
    }%
  }%
}%
\begin{minipage}[t]{\datagidxdescwidth}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \DTLgidxSymbolDescription
  \DTLgidxDoSeeOrLocation
  \DTLgidxChildrenSeeAlso
\end{minipage}%
\par
}%
}
\newlength\datagidxindent
\setlength\datagidxindent{10\p@}

```

```

\newlength\datagidxnamewidth
\newlength\datagidxdescwidth
\newcommand*{\datagidx@style@align}{%
  \renewcommand*{\datagidxstart}%
  {%
    \bgroup
    \setlength{\parindent}{0pt}%
    \setlength{\parskip}{0pt plus 0.3pt}%
    \setlength{\datagidxnamewidth}{0pt}%
    \DTLforeach*{\DTLgidxCurrentdb}%
      {\Name=Name, \Location=Location, \See=See, \SeeAlso=SeeAlso, %
       \Parent=Parent}%
    {%
      \DTLifnull{\Parent}%
      {%
        \datagidx@doifdisplayed
        {%
          \settowidth{\dimen@}{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
          \ifdim\dimen@>\datagidxnamewidth\relax
            \datagidxnamewidth=\dimen@\relax
          \fi
        }%
      }%
    }%
  }%
  \settowidth{\dimen@}{\DTLgidxPostName}%
  \addtolength{\datagidxnamewidth}{\dimen@}%
  \setlength{\datagidxdescwidth}{\linewidth}%
  \addtolength{\datagidxdescwidth}{-\datagidxnamewidth}%
  \ifdim\datagidxsymbolwidth>0pt\relax
    \addtolength{\datagidxdescwidth}{-\datagidxsymbolwidth}%
    \settowidth{\dimen@}{\DTLgidxSymDescSep}%
    \addtolength{\datagidxdescwidth}{-\dimen@}%
  \fi
  \ifdim\datagidxlocationwidth>0pt\relax
    \addtolength{\datagidxdescwidth}{-\datagidxlocationwidth}%
    \settowidth{\dimen@}{\DTLgidxPreLocation}%
    \addtolength{\datagidxdescwidth}{-\dimen@}%
  \fi
  \ifdim\datagidxsymbolwidth>0pt\relax
    \ifdim\datagidxlocationwidth>0pt\relax
      \if@datagidxsymbolleft
        \def\datagidx@item@body{%
          \begin{minipage}[t]{\datagidxsymbolwidth}%
            \datagidxsymalign
            \let\DTLgidxSymDescSep\@empty
            \DTLgidxSymbolDescLeft
          \end{minipage}%
          \DTLgidxSymDescSep
          \begin{minipage}[t]{\datagidxdescwidth}%

```

```

        \let\DTLgidxSymDescSep\@empty
        \setlength{\parskip}{0pt plus 0.3pt}%
        \DTLgidxSymbolDescRight
    \end{minipage}%
    \DTLgidxPreLocation
    \begin{minipage}[t]{\datagidxlocationwidth}%
        \datagidxlocalign
        \let\DTLgidxPreLocation\@empty
        \DTLgidxDoSeeOrLocation
        \DTLgidxChildrenSeeAlso
    \end{minipage}%
}%
\else
\def\datagidx@item@body{%
    \begin{minipage}[t]{\datagidxdescwidth}%
        \let\DTLgidxSymDescSep\@empty
        \DTLgidxSymbolDescLeft
    \end{minipage}%
    \DTLgidxSymDescSep
    \begin{minipage}[t]{\datagidxsymbolwidth}%
        \datagidxsymalign
        \let\DTLgidxSymDescSep\@empty
        \setlength{\parskip}{0pt plus 0.3pt}%
        \DTLgidxSymbolDescRight
    \end{minipage}%
    \DTLgidxPreLocation
    \begin{minipage}[t]{\datagidxlocationwidth}%
        \datagidxlocalign
        \let\DTLgidxPreLocation\@empty
        \DTLgidxDoSeeOrLocation
        \DTLgidxChildrenSeeAlso
    \end{minipage}%
}%
\fi
\else
\if@datagidxsymbolleft
\def\datagidx@item@body{%
    \begin{minipage}[t]{\datagidxsymbolwidth}%
        \datagidxsymalign
        \let\DTLgidxSymDescSep\@empty
        \DTLgidxSymbolDescLeft
    \end{minipage}%
    \DTLgidxSymDescSep
    \begin{minipage}[t]{\datagidxdescwidth}%
        \let\DTLgidxSymDescSep\@empty
        \setlength{\parskip}{0pt plus 0.3pt}%
        \DTLgidxSymbolDescRight
        \DTLgidxDoSeeOrLocation
        \DTLgidxChildrenSeeAlso
    \end{minipage}%
}

```

```

    }%
  \else
    \def\datagidx@item@body{%
      \begin{minipage}[t]{\datagidxdescwidth}%
        \let\DTLgidxSymDescSep\@empty
        \DTLgidxSymbolDescLeft
      \end{minipage}%
      \DTLgidxSymDescSep
      \begin{minipage}[t]{\datagidxsymbolwidth}%
        \datagidxsymalign
        \let\DTLgidxSymDescSep\@empty
        \setlength{\parskip}{0pt plus 0.3pt}%
        \DTLgidxSymbolDescRight
        \DTLgidxDoSeeOrLocation
        \DTLgidxChildrenSeeAlso
      \end{minipage}%
    }%
  \fi
\fi
\else
  \ifdim\datagidxlocationwidth>0pt\relax
    \def\datagidx@item@body{%
      \begin{minipage}[t]{\datagidxdescwidth}%
        \setlength{\parskip}{0pt plus 0.3pt}%
        \DTLgidxSymbolDescription
      \end{minipage}%
      \DTLgidxPreLocation
      \begin{minipage}[t]{\datagidxlocationwidth}%
        \datagidxlocalign
        \let\DTLgidxPreLocation\@empty
        \DTLgidxDoSeeOrLocation
        \DTLgidxChildrenSeeAlso
      \end{minipage}%
    }%
  \else
    \def\datagidx@item@body{%
      \begin{minipage}[t]{\datagidxdescwidth}%
        \setlength{\parskip}{0pt plus 0.3pt}%
        \DTLgidxSymbolDescription
        \DTLgidxDoSeeOrLocation
        \DTLgidxChildrenSeeAlso
      \end{minipage}%
    }%
  \fi
\fi
}
\renewcommand*{\datagidxend}{\egroup}%
\renewcommand*{\datagidxgroupsep}{\ifdatagidxshowgroups\indexspace\fi}%
\renewcommand{\datagidxgroupheader}{%
  \ifdatagidxshowgroups

```

```

\item
\makebox[\linewidth]%
{%
\textbf{\DTLgidxGroupHeaderTitle{\datagidxcurrentgroup}}%
}%
\DTLpar\nobreak\@afterheading
\fi
}%
\renewcommand*{\datagidxitem}{%
\ifdefempty\datagidxprevgroup
{%
\datagidxgroupheader
}%
{%
\ifdefequal\datagidxcurrentgroup\datagidxprevgroup
{%
}%
{%
\datagidxgroupsep
\datagidxgroupheader
}%
}%
\hangindent\opt\relax
\parindent\opt\relax
\makebox[\datagidxnamewidth][l]%
{%
\datagidxtarget{\Label}%
{%
\DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
\DTLgidxPostName
}%
}%
\datagidx@item@body
\par
}%
\renewcommand*{\datagidxchildstart}%
{%
\bgroup
\setlength{\parindent}{\opt}%
\setlength{\parskip}{\opt plus 0.3pt}%
\setlength{\datagidxnamewidth}{\opt}%
\DTLforeach*{\DTLgidxCurrentdb}%
{\Name=Name,\Location=Location,\See=See,\SeeAlso=SeeAlso,%
\Parent=Parent}%
{%
\DTLifnull{\Parent}%
{%
\datagidx@doifdisplayed
{%
\settowidth{\dimen@}%

```

```

        {%
          \DTLgidxChildStyle
          {%
            \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
          }%
        }%
        \ifdim\dimen@>\datagidxnamewidth\relax
          \datagidxnamewidth=\dimen@\relax
        \fi
      }%
    }%
  {}%
}%
\settowidth{\dimen@}{\DTLgidxChildStyle\DTLgidxPostChildName}%
\addtolength{\datagidxnamewidth}{\dimen@}%
\setlength{\datagidxdescwidth}{\linewidth}%
\addtolength{\datagidxdescwidth}{-\datagidxnamewidth}%
}%
\renewcommand{\datagidxchildend}{\egroup}%
\renewcommand*{\datagidxchilditem}{%
  \hangindent0pt\relax
  \parindent0pt\relax
  \refstepcounter{DTLgidxChildCount}%
  \makebox[\datagidxnamewidth][l]%
  {%
    \datagidxtarget{\Label}%
    {%
      \DTLgidxChildStyle
      {%
        \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
        \DTLgidxPostChildName
      }%
    }%
  }%
  \begin{minipage}[t]{\datagidxdescwidth}%
    \setlength{\parskip}{0pt plus 0.3pt}%
    \DTLgidxSymbolDescription
    \DTLgidxDoSeeOrLocation
    \DTLgidxChildrenSeeAlso
  \end{minipage}%
  \par
}%
}
\newcommand*{\datagidx@style@gloss}{%
\renewcommand*{\datagidxstart}{%
  {%
    \bgroup
    \setlength{\parindent}{0pt}%
    \setlength{\parskip}{0pt plus 0.3pt}%
    \setlength{\datagidxnamewidth}{0pt}%
  }
}

```

```

\DTLforeach*{\DTLgidxCurrenldb}%
  {\Name=Name,\Location=Location,\See=See,\SeeAlso=SeeAlso,%
  \Parent=Parent}%
  {%
    \DTLifnull{\Parent}%
    {%
      \datagidx@doifdisplayed
      {%
        \settowidth{\dimen@}{\DTLgidxNameFont{\DTLgidxNameCase{\Name}}}%
        \ifdim\dimen@>\datagidxnamewidth\relax
          \datagidxnamewidth=\dimen@\relax
        \fi
      }%
    }%
  }%
  \settowidth{\dimen@}{\DTLgidxPostName}%
  \addtolength{\datagidxnamewidth}{\dimen@}%
  \setlength{\datagidxdescwidth}{\linewidth}%
  \addtolength{\datagidxdescwidth}{-\datagidxnamewidth}%
}%
\renewcommand*{\datagidxend}{\egroup}%
\renewcommand*{\datagidxgroupsep}{\ifdatagidxshowgroups\indexspace\fi}%
\renewcommand{\datagidxgroupheader}{%
  \ifdatagidxshowgroups
    \item
    \makebox[\linewidth]%
    {%
      \textbf{\DTLgidxGroupHeaderTitle{\datagidxcurrentgroup}}%
    }%
    \DTLpar\nobreak\@afterheading
  \fi
}%
\renewcommand*{\datagidxitem}{%
  \ifdefempty\datagidxprevgroup
  {%
    \datagidxgroupheader
  }%
  {%
    \ifdequal\datagidxcurrentgroup\datagidxprevgroup
    {%
      }%
    }%
    \datagidxgroupsep
    \datagidxgroupheader
  }%
}%
\hangindent0pt\relax
\parindent0pt\relax
\makebox[\datagidxnamewidth][l]%

```

```

{%
  \datagidxtarget{\Label}%
  {%
    \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
    \DTLgidxPostName
  }%
}%
\begin{minipage}[t]{\datagidxdescwidth}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \@tempswatrue
  \ifdefempty{\Description}%
  {%
    \ifdefempty{\Symbol}%
    {%
      \ifdefempty{\Location}{\@tempswafalse}{}%
    }%
  }%
  {}%
}%
\if@tempswa
  \DTLgidxSymbolDescription
  \DTLgidxDoSeeOrLocation
\else
  \mbox{}%
\fi
\DTLgidxChildrenSeeAlso
\end{minipage}%
\par
}%
\renewcommand*{\datagidxchildstart}%
{%
  \bgroup
  \def\datagidx@childsep{}%
  \setcounter{DTLgidxChildCount}{0}%
}%
\renewcommand{\datagidxchildend}{\DTLgidxPostChild\egroup}%
\renewcommand*{\datagidxchilditem}{%
  \datagidx@childsep
  \refstepcounter{DTLgidxChildCount}%
  \datagidxtarget{\Label}%
  {%
    \DTLgidxChildStyle
    {%
      \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
      \DTLgidxPostChildName
    }%
  }%
  \DTLgidxSymbolDescription
  \DTLgidxDoSeeOrLocation
  \DTLgidxChildrenSeeAlso

```

```

\let\datagidx@childsep\DTLgidxChildSep
}%
}
\newcommand*\DTLgidxChildSep}{ }
\newcommand*\DTLgidxPostChild}{}
\ifdef\chapter
{%
\newcommand\DTLgidxDictHead{%
\chapter{\DTLgidxGroupHeaderTitle{\datagidxcurrentgroup}}%
}%
}%
{%
\newcommand\DTLgidxDictHead{%
\section{\DTLgidxGroupHeaderTitle{\datagidxcurrentgroup}}%
}%
}
\newcommand*\DTLgidxCategoryNameFont}[1]{#1}
\newcommand*\DTLgidxCategorySep}{\space}
\newcommand*\DTLgidxSubCategorySep}{\space}
\newcommand*\datagidxdictindent}{1em}
\newcommand*\DTLgidxDictPostItem}{\par}
\newcommand*\datagidx@style@dict}{%
\renewcommand*\datagidxstart}%
{%
\bgroup
\setlength{\parindent}{0pt}%
\setlength{\parskip}{0pt plus 0.3pt}%
\dimen@=\linewidth
\advance\dimen@ by -\datagidxdictindent\relax
\dtl@tmplength=\datagidxdictindent\relax
\def\datagidxdictparshape{%
\noexpand\parshape=2 0pt \the\linewidth\space
\the\dtl@tmplength\space \the\dimen@\relax
}%
\datagidx@level=1\relax
\raggedright
}%
\renewcommand*\datagidxend}{\egroup}%
\renewcommand*\datagidxgroupsep}{}%
\renewcommand{\datagidxgroupheader}{%
\ifdatagidxshowgroups
\datagidxend
\datagidx@end
\DTLgidxDictHead
\datagidx@prestart
\datagidxstart
\fi
}%
\renewcommand*\datagidxitem}{%
\ifdefempty\datagidxprevgroup

```

```

{%
  \datagidxgroupheader
}%
{%
  \ifdefequal\datagidxcurrentgroup\datagidxprevgroup
  {%
    }%
  {%
    \datagidxgroupsep
    \datagidxgroupheader
  }%
}%
\datagidxdictparshape
\datagidxtarget{\Label}%
{%
  \DTLgidxNameFont{\DTLgidxNameCase{\Name}}%
}%
\DTLgidxPostName
\let\datagidx@catsep\@empty
\let\datagidx@subcatsep\@empty
\DTLgidxSymbolDescription
\DTLgidxChildrenSeeAlso
\DTLgidxDictPostItem
}%
\renewcommand*{\datagidxchildstart}%
{%
  \bgroup
}%
\renewcommand*{\datagidxchildend}{\egroup}%
\renewcommand*{\datagidxchilditem}{%
  \ifnum\datagidx@level=2\relax
    \datagidx@catsep
    \let\datagidx@catsep\DTLgidxCategorySep
    \let\datagidx@subcatsep\@empty
    \datagidxtarget{\Label}%
    {%
      \DTLgidxChildStyle
      {%
        \DTLgidxCategoryNameFont{\DTLgidxNameCase{\Name}}%
        \DTLgidxPostChildName
      }%
    }%
  }%
  \setcounter{DTLgidxChildCount}{0}%
\else
  \datagidx@subcatsep
  \let\datagidx@subcatsep\DTLgidxSubCategorySep
  \refstepcounter{DTLgidxChildCount}%
  \DTLgidxChildCountLabel
  \DTLgidxPostChildName
\fi

```

```

\DTLgidxSymbolDescription
\DTLgidxDoSeeOrLocation
\DTLgidxChildrenSeeAlso
}%
\renewcommand*\datagidxseealsostart{%
{%
  \bgroup
  \setlength{\parindent}{0pt}%
  \setlength{\parskip}{0pt plus 0.3pt}%
  \setlength{\dimen@}{\datagidxindent}%
  \advance\datagidx@level by 1\relax
  \multiply\dimen@ by \datagidx@level\relax
  \@idxitem\hspace*{\dimen@}%
}%
\renewcommand{\datagidxseealsoend}{\egroup}%
}
\newcommand*\dtldofirstlocation{%
  \@for\dtl@thisloc:=\Location\do{%
    \ifdefempty\dtl@thisloc
    {%
    {%
      \expandafter\datagidx@getlocation\dtl@thisloc
      \datagidxlink{\datagidx@current@target}%
      {%
        \datagidx@formatlocation
        \datagidx@current@format\datagidx@current@locationstring
      }%
    }%
    \@endfortrue
  }%
}%
}
\newcommand*\datagidx@formatlocation}[2]{%
  \ifdefempty{#1}%
  {#2}%
  {%
  \ifcsdef{#1}%
  {%
    \csuse{#1}{#2}%
  }%
  {%
    \PackageWarning{datagidx}{Unknown format `#1'%}
    #2%
  }%
}%
}
\newcommand*\dtldolocationlist{%
  \DTLifnull{\Location}%
  {}%
  {%
    \def\datagidx@prev@location{-1}%

```

```

\def\datagidx@prev@locationstring{%
\def\datagidx@prev@format{%
\def\datagidx@prev@locationformat{%
\def\datagidx@prev@prefix{%
\def\datagidx@prev@target{%
\def\datagidx@location@sep{%
\def\datagidx@location@start{-1}%
\expandafter\forcsvlist\expandafter\datagidx@parse@location
\expandafter{\Location}%
\do@prevlocation % tidy up loose ends
}%
}
\newif\if@dtl@sequential
\newcommand*\datagidx@getlocdo[1]{%
\ifdefempty\datagidx@current@location
{%
}%
\ifdefempty\datagidx@current@prefix{%
\datagidx@current@location\datagidx@compositor
}%
}%
\def\datagidx@current@location{#1}%
}
\def\datagidx@getlocation[#1]#2#3{%
\def\datagidx@current@locationstring{#2}%
\bgroup
\datagidx@escape@location@format
\def\datagidx@current@locationformat{#2}%
\datagidx@clear@location@format
\def\datagidx@current@location{#2}%
\egroup
\let\datagidx@list\datagidx@current@location
\def\datagidx@current@prefix{%
\def\datagidx@current@location{%
\let\do\datagidx@getlocdo
\expandafter\datagidx@docomplis
\expandafter{\datagidx@list}%
\def\datagidx@current@format{#1}%
\def\datagidx@current@target{#3}%
}
\newcommand*\datagidx@parse@location}[1]{%
\datagidx@getlocation#1\relax
\ifdefequal{\datagidx@prev@locationstring}{\datagidx@current@locationstring}%
{%
\ifdefequal{\datagidx@prev@format}{\datagidx@current@format}%
{%
}%
}%
\ifdefempty{\datagidx@current@format}%
{%
}
}

```

```

}%
{%
  \ifdefempty{\datagidx@prev@format}%
  {%
    \let\datagidx@prev@format\datagidx@current@format
  }%
  {%
    \PackageWarning{datagidx}%
    {%
      Conflicting location formats '\datagidx@prev@format' and
      '\datagidx@current@format' for location '\datagidx@current@location'%
    }%
  }%
}%
}%
}%
}%
\@datagidx@parse@location
}%
}
\newcommand*{\@datagidx@parse@location}{%
  \@dtl@sequentialtrue
  \ifdefequal{\datagidx@prev@format}{\datagidx@current@format}%
  {%
    \ifdefequal{\datagidx@prev@locationformat}{\datagidx@current@locationformat}%
    {%
      \ifdefequal{\datagidx@prev@prefix}{\datagidx@current@prefix}%
      {%
        }%
      }%
      {%
        \@dtl@sequentialfalse
      }%
    }%
  }%
  {%
    \@dtl@sequentialfalse
  }%
}%
\@dtl@sequentialfalse
}%
\if@dtl@sequential
  \ifnumequal{\datagidx@prev@location+1}{\datagidx@current@location}%
  {%
    \ifdefequal
      \datagidx@current@locationformat
      \datagidx@prev@locationformat
    {%
      \@dtl@sequentialtrue
    }%
  }%
  {%

```

```

        \@dtl@sequentialfalse
    }%
}%
{%
    \@dtl@sequentialfalse
}%
\fi
\if@dtl@sequential
    \ifnumequal{\datagidx@location@start}{-1}%
    {%
        \let\datagidx@location@start\datagidx@prev@location
        \let\datagidx@location@startval\datagidx@prev@locationstring
        \let\datagidx@location@format\datagidx@prev@format
        \let\datagidx@location@target\datagidx@prev@target
    }%
    {%
    }%
\else
    \do@prevlocation
\fi
\let\datagidx@prev@location\datagidx@current@location
\let\datagidx@prev@format\datagidx@current@format
\let\datagidx@prev@prefix\datagidx@current@prefix
\let\datagidx@prev@locationformat\datagidx@current@locationformat
\let\datagidx@prev@locationstring\datagidx@current@locationstring
\let\datagidx@prev@target\datagidx@current@target
}
\newcommand*{\DTLgidxLocationSep}{, }
\newcommand*{\DTLgidxLocationF}[2]{%
    #1\DTLgidxLocationSep#2%
}
\newcommand*{\DTLgidxLocationFF}[2]{%
    #1- -#2%
}
\newcommand*{\do@prevlocation}{%
    \ifnumequal{\datagidx@location@start}{-1}%
    {%
        \ifdefempty{\datagidx@prev@locationstring}%
        {}%
        {%
            \datagidx@location@sep
            \datagidxlink{\datagidx@prev@target}%
            {%
                \datagidx@formatlocation
                \datagidx@prev@format\datagidx@prev@locationstring
            }%
            \def\datagidx@location@sep{\DTLgidxLocationSep}%
        }%
    }%
}%

```

```

\datagidx@location@sep
\do@locrange
\def\datagidx@location@sep{\DTLgidxLocationSep}%
\def\datagidx@location@start{-1}%
}%
}
\newcommand*{\do@locrange}{%
\ifnumgreater{\datagidx@prev@location}{\datagidx@location@start+1}%
{%
\DTLgidxLocationFF
{%
\datagidxlink{\datagidx@location@target}%
{%
\datagidx@formatlocation
\datagidx@location@format\datagidx@location@startval
}%
}%
{%
\datagidxlink{\datagidx@prev@target}%
{%
\datagidx@formatlocation
\datagidx@prev@format\datagidx@prev@locationstring
}%
}%
}%
}%
\DTLgidxLocationF
{%
\datagidxlink{\datagidx@location@target}%
{%
\datagidx@formatlocation
\datagidx@location@format\datagidx@location@startval
}%
}%
{%
\datagidxlink{\datagidx@prev@target}%
{%
\datagidx@formatlocation
\datagidx@prev@format\datagidx@prev@locationstring
}%
}%
}%
}
\newcommand*{\datagidx@defaultdatabase}{}
\newcommand*{\DTLgidxSetDefaultDB}[1]{%
\renewcommand*{\datagidx@defaultdatabase}{#1}%
}
\define@key{newgloss}{heading}{\renewcommand*{\datagidx@heading}{#1}}
\define@key{newgloss}{postheading}{%
\renewcommand*{\datagidx@postheading}{#1}%
}

```

```

}
\newif\ifdatagidxbalance
\datagidxbalancetrue
\define@choicekey{newgloss}{balance}{\val\nr}{true, false}[true]{%
  \ifcase\nr\relax
    \renewcommand*{\datagidx@multicols}{multicols}%
    \datagidxbalancetrue
  \or
    \renewcommand*{\datagidx@multicols}{multicols*}%
    \datagidxbalancefalse
  \fi
}
\define@key{newgloss}{sort}{\renewcommand*{\datagidx@sort}{#1}}
\newcommand*{\datagidx@style}{index}
\define@key{newgloss}{style}{\renewcommand*{\datagidx@style}{#1}}
\newif\ifdatagidxshowgroups
\newcommand*{\datagidx@showgroups}{false}
\define@choicekey{newgloss}{showgroups}{true, false}[true]%
{%
  \renewcommand{\datagidx@showgroups}{#1}%
}%
\ifundef\newgidx
{%
  \newcommand*{\newgidx}{\datagidx@newgidx}
}%
{}
\@onlypreamble\newgidx
\newcommand*{\datagidx@highopt@newgidx}[3][]{%
  \edef\datagidx@indexfilename{\datagidxhighoptfilename{#2}}%
  \IfFileExists{\datagidx@indexfilename}%
  {%
    \input{\datagidx@indexfilename}%
    \bgroup
      \setkeys{newgloss}{#1}%
      \datagidx@newgidx@update{#2}{#3}%
    \egroup
  }%
  {%
    \datagidx@newgidx[#1]{#2}{#3}%
  }%
}
\newcommand*{\loadgidx}[3][]{%
  \input{#2}%
  \bgroup
    \setkeys{newgloss}{sort={}, #1}%
    \expandafter\datagidx@newgidx@update\expandafter
    {\dtllastloadeddb}{#3}%
  \egroup
  \edef\datagidx@defaultdatabase{\dtllastloadeddb}%
  \dtlforcolumn{\Label}{\dtllastloadeddb}{Label}%

```

```

    {%
      \csxdef{datagidxentry@\Label}{\dtllastloadeddb}%
    }%
  }
  \@onlypreamble\loadgidx
  \newcommand*{\datagidx@newgidx}[3][[]]{%
    \bgroup
      \setkeys{newgloss}{#1}%
      \ifdefempty{\datagidx@defaultdatabase}%
        {\xdef\datagidx@defaultdatabase{#2}}%
      }%
      \DTLgnewdb{#2}%
      \DTLaddcolumn{#2}{Label}%
      \DTLaddcolumn{#2}{Location}%
      \DTLaddcolumn{#2}{CurrentLocation}%
      \DTLaddcolumn{#2}{FirstId}%
      \DTLaddcolumn{#2}{Name}%
      \DTLaddcolumn{#2}{Text}%
      \DTLaddcolumn{#2}{Parent}%
      \DTLaddcolumn{#2}{Child}%
      \DTLaddcolumn{#2}{Description}%
      \DTLaddcolumn{#2}{Used}%
      \DTLaddcolumn{#2}{Symbol}%
      \DTLaddcolumn{#2}{Long}%
      \DTLaddcolumn{#2}{Short}%
      \DTLaddcolumn{#2}{See}%
      \DTLaddcolumn{#2}{SeeAlso}%
      \datagidx@newgidx@update{#2}{#3}%
    \egroup
  }
  \newcommand*{\datagidx@newgidx@update}[2]{%
    \DTLnewrow{datagidx}%
    \DTLnewdbentry{datagidx}{Glossary}{#1}%
    \DTLnewdbentry{datagidx}{Title}{#2}%
    {%
      \dtlexpandnewvalue
      \DTLnewdbentry{datagidx}{Heading}{\expandonce\datagidx@heading}%
      \DTLnewdbentry{datagidx}{PostHeading}{\expandonce\datagidx@postheading}%
      \DTLnewdbentry{datagidx}{MultiCols}{\expandonce\datagidx@multicols}%
      \DTLnewdbentry{datagidx}{Sort}{\expandonce\datagidx@sort}%
      \DTLnewdbentry{datagidx}{Style}{\expandonce\datagidx@style}%
      \DTLnewdbentry{datagidx}{ShowGroups}{\expandonce\datagidx@showgroups}%
    }%
  }
  }
  \newcommand*{\newterm@label}{}
  \define@key{newterm}{label}{\renewcommand*{\newterm@label}{#1}}
  \newcommand*{\newterm@parent}{}
  \define@key{newterm}{parent}{\renewcommand*{\newterm@parent}{#1}}
  \newcommand*{\newterm@text}{}
  \define@key{newterm}{text}{\renewcommand*{\newterm@text}{#1}}

```

```

\newcommand*\newterm@description{}
\define@key{newterm}{description}{%
  \renewcommand*\newterm@description{#1}%
}
\define@key{newterm}{plural}{\def\newterm@plural{#1}}
\newcommand*\newterm@sort{}
\define@key{newterm}{sort}{\renewcommand*\newterm@sort{#1}}
\newcommand*\newterm@symbol{}
\define@key{newterm}{symbol}{\renewcommand*\newterm@symbol{#1}}
\newcommand*\newterm@database{}
\define@key{newterm}{database}{\renewcommand*\newterm@database{#1}}
\newcommand*\newterm@long{}
\define@key{newterm}{long}{%
  \renewcommand*\newterm@long{#1}%
  \def\newterm@longplural{#1s}%
}
\newcommand*\newterm@short{}
\define@key{newterm}{short}{%
  \renewcommand*\newterm@short{#1}%
  \def\newterm@shortplural{#1s}%
}
\define@key{newterm}{longplural}{%
  \def\newterm@longplural{#1}%
}
\define@key{newterm}{shortplural}{%
  \def\newterm@shortplural{#1}%
}
\newcommand*\newterm@see{}
\define@key{newterm}{see}{%
  \renewcommand*\newterm@see{#1}%
}
\newcommand*\newterm@seealso{}
\define@key{newterm}{seealso}{%
  \renewcommand*\newterm@seealso{#1}%
}
\newcommand*\newterm@defaultshook{}
\newcommand*\newterm@extrafields{}
\newcommand*\DTLgidxAssignList{%
  \Name=Name, \Description=Description, \Used=Used, \Symbol=Symbol, %
  \Long=Long, \Short=Short, \LongPlural=LongPlural, \ShortPlural=ShortPlural, %
  \Location=Location, \See=See, \SeeAlso=SeeAlso, %
  \Text=Text, \Plural=Plural, \CurrentLocation=CurrentLocation, %
  \Label=Label, \Parent=Parent, \Children=Child, \FirstId=FirstId, \Sort=Sort%
}
\newcommand*\datagidxtermkeys{%
  name, description, symbol, long, short, see, seealso, text, plural, %
  label, parent, sort%
}
\newcommand*\@datagidx@fieldkey@Name{name}%
\newcommand*\@datagidx@fieldkey@Description{description}%

```

```

\newcommand*\@datagidx@fieldkey@Symbol{symbol}%
\newcommand*\@datagidx@fieldkey@Long{long}%
\newcommand*\@datagidx@fieldkey@Short{short}%
\newcommand*\@datagidx@fieldkey@See{see}%
\newcommand*\@datagidx@fieldkey@SeeAlso{seealso}%
\newcommand*\@datagidx@fieldkey@Text{text}%
\newcommand*\@datagidx@fieldkey@Plural{plural}%
\newcommand*\@datagidx@fieldkey@Label{label}%
\newcommand*\@datagidx@fieldkey@Parent{parent}%
\newcommand*\@datagidx@fieldkey@Sort{sort}%
\newcommand*\@newtermaddfield}[4][[]]{%
  \ifstrempy{#1}%
  {%
    \dtlforcolumn{\datagidx@thisidx}{datagidx}{Glossary}%
    {%
      \DTLaddcolumn{\datagidx@thisidx}{#2}%
    }%
  }%
  {%
    \@for\datagidx@thisidx:=#1\do
    {%
      \DTLaddcolumn{\datagidx@thisidx}{#2}%
    }%
  }%
  \expandafter\gdef\csname newterm@#3\endcsname{%
  \define@key{newterm}{#3}%
  {%
    \expandafter\def\csname newterm@#3\endcsname{##1}%
  }%
  \gappto\newterm@defaultshook
  {%
    \expandafter\protected@edef\csname newterm@#3\endcsname{#4}%
  }%
  \gappto\newterm@extrafields
  {%
    \protected@edef\datagidx@value{\csname newterm@#3\endcsname}%
    \DTLnewdbentry{\newterm@database}{#2}{\expandonce\datagidx@value}%
  }%
  \xappto\DTLgidxAssignList
  {%
    , \expandafter\noexpand\csname#2\endcsname=#2%
  }%
  \xappto\datagidxtermkeys{, #3}%
  \expandafter\xdef\csname @datagidx@fieldkey@#2\endcsname{#3}%
  \xappto\datagidxgetchildfields
  {%
    \noexpand\dtlgetentryfromcurrentrow
    {\expandafter\noexpand\csname#2\endcsname}%
    {\noexpand\dtlcolumnindex{\noexpand\DTLgidxCurrentdb}{#2}}%
  }%
}

```

```

}
\newcommand*\newtermlabelhook{}
\newcommand*\DTLgidxNoFormat}[1]{#1}
\newcommand*\DTLgidxGobble}[1]{}
\newcommand*\DTLgidxStripBackslash}[1]{%
  \expandafter@gobble\string#1%
}
\newcommand*\DTLgidxName}[2]{%
  #1\space #2%
}
\newcommand*\DTLgidxNameNum}[1]{\@Roman{#1}}
\newcommand*\datagidx@namenum}[1]{\two@digits{#1}}
\newcommand*\DTLgidxPlace}[2]{%
  #2%
}
\newcommand*\DTLgidxSubject}[2]{%
  #2%
}
\newcommand*\DTLgidxOffice}[2]{%
  #2 (#1)%
}
\newcommand*\DTLgidxIgnore}[1]{#1}
\newcommand*\DTLgidxMac}[1]{#1}
\newcommand*\datagidx@mac}[1]{Mac}
\newcommand*\DTLgidxSaint}[1]{#1}
\newcommand*\datagidx@saint}[1]{Saint}
\newcommand*\DTLgidxRank}[2]{#1~#2}
\newcommand*\datagidx@rank}[2]{#2.}
\newcommand*\DTLgidxParticle}[2]{#1~#2}
\newcommand*\datagidx@particle}[2]{#2.}
\newcommand*\datagidx@bothoftwo}[2]{#1#2}
\newcommand*\datagidx@person}[2]{#2\noexpand\datatoolpersoncomma #1}
\newcommand*\datagidx@place}[2]{#2\noexpand\datatoolplacecomma #1}
\newcommand*\datagidx@subject}[2]{#2\noexpand\datatoolsubjectcomma #1}
\newcommand*\datagidx@paren}[1]{\noexpand\datatoolparenstart #1}
\newcommand*\datagidx@invert}[2]{#2, #1}
\newcommand*\DTLgidxParen}[1]{\space(#1)}
\newcommand*\datagidxwordifygreek{%
  \def\alpha{alpha}%
  \def\beta{beta}%
  \def\gamma{gamma}%
  \def\delta{delta}%
  \def\epsilon{epsilon}%
  \def\varepsilon{epsilon}%
  \def\zeta{zeta}%
  \def\eta{eta}%
  \def\theta{theta}%
  \def\vartheta{theta}%
  \def\iota{iota}%
  \def\kappa{kappa}%
}

```

```

\def\lambda{\lambda}%
\def\mu{\mu}%
\def\nu{\nu}%
\def\xi{\xi}%
\def\pi{\pi}%
\def\varpi{\varpi}%
\def\rho{\rho}%
\def\varrho{\varrho}%
\def\sigma{\sigma}%
\def\varsigma{\varsigma}%
\def\tau{\tau}%
\def\upsilon{\upsilon}%
\def\phi{\phi}%
\def\varphi{\varphi}%
\def\chi{\chi}%
\def\psi{\psi}%
\def\omega{\omega}%
\def\Gamma{\Gamma}%
\def\Delta{\Delta}%
\def\Theta{\Theta}%
\def\Lambda{\Lambda}%
\def\Xi{\Xi}%
\def\Pi{\Pi}%
\def\Sigma{\Sigma}%
\def\Upsilon{\Upsilon}%
\def\Phi{\Phi}%
\def\Psi{\Psi}%
\def\Omega{\Omega}%
}
\newcommand{\datagidxextendedtoascii}{%
\def\AE{AE}%
\def\ae{ae}%
\def\OE{OE}%
\def\oe{oe}%
\def\AA{AA}%
\def\aa{aa}%
\def\L{L}%
\def\l{l}%
\def\O{O}%
\def\o{o}%
\def\SS{SS}%
\def\ss{ss}%
\def\th{th}%
\def\TH{TH}%
\def\dh{dh}%
\def\DH{DH}%
}
\newcommand*{\datagidxconvertchars}{%
\let~\space
\ifdef\andname

```

```

{%
  \let\&\andname
}%
{%
  \def\&{\expandafter\@gobble\string\&}%
}%
\def\_ {\string_}%
\def\$\ {\string$}%
\def\#\ {\expandafter\@gobble\string\#}%
\def\%\ {\expandafter\@gobble\string\}%
\def\{\ {\expandafter\@gobble\string\}%
\def\}\ {\expandafter\@gobble\string\}%
}
\@ifl@t@r\fmtversion{2019/10/01}
{%
  \newcommand*\datagidxstripaccents{%
    \let\add@accent@\@secondoftwo
    \let\@text@composite@x@\@secondoftwo
    \let\@tabacckludge@\@secondoftwo
    \expandafter\def\csname \encodingdefault-cmd\endcsname##1##2##3{##3}%
    \expandafter\def\csname OT1-cmd\endcsname##1##2##3{##3}%
    \expandafter\def\csname T1-cmd\endcsname##1##2##3{##3}%
    \expandafter\def\csname PD1-cmd\endcsname##1##2##3{##3}%
    \def\IeC##1{\@gobbletwo##1}%
    \let\UTFviii@two@octets\UTFviii@two@octets@combine
  }%
}
{%
  \newcommand*\datagidxstripaccents{%
    \let\add@accent@\@secondoftwo
    \let\@text@composite@x@\@secondoftwo
    \let\@tabacckludge@\@secondoftwo
    \expandafter\def\csname \encodingdefault-cmd\endcsname##1##2##3{##3}%
    \expandafter\def\csname OT1-cmd\endcsname##1##2##3{##3}%
    \expandafter\def\csname T1-cmd\endcsname##1##2##3{##3}%
    \expandafter\def\csname PD1-cmd\endcsname##1##2##3{##3}%
    \def\IeC##1{\@gobbletwo##1}%
  }%
}
\providecommand{\newterm}{\datagidx@newterm}
\@onlypreamble\newterm
\newcommand{\datagidx@setfieldvalues}[2]{%
  \def\newterm@name{#2}%
  \renewcommand*\newterm@label{#2}%
  \renewcommand*\newterm@text{#2}%
  \undef\newterm@plural
  \renewcommand*\newterm@description{#2}%
  \renewcommand*\newterm@sort{#2}%
  \renewcommand*\newterm@symbol{#2}%
  \let\newterm@database\datagidx@defaultdatabase
}

```

```

\renewcommand*{\newterm@short}{#2}%
\undef\newterm@shortplural
\renewcommand*{\newterm@long}{#2}%
\undef\newterm@longplural
\renewcommand*{\newterm@see}{}%
\renewcommand*{\newterm@seealso}{}%
\renewcommand*{\newterm@parent}{}%
\let\datagidx@orgfield\field
\def\field##1{\expandafter\noexpand\csname newterm@##1\endcsname}%
\newterm@defaultshook
\let\field\datagidx@orgfield
\setkeys{newterm}{#1}%
\bgroup
  \let\glsadd@gobble
  \let\MakeUppercase\DTLgidxNoFormat
  \let\MakeTextUppercase\DTLgidxNoFormat
  \let\MakeLowercase\DTLgidxNoFormat
  \let\MakeTextLowercase\DTLgidxNoFormat
  \let\acronymfont\DTLgidxNoFormat
  \let\textrm\DTLgidxNoFormat
  \let\texttt\DTLgidxNoFormat
  \let\textsf\DTLgidxNoFormat
  \let\textsc\DTLgidxNoFormat
  \let\textbf\DTLgidxNoFormat
  \let\textmd\DTLgidxNoFormat
  \let\textit\DTLgidxNoFormat
  \let\textsl\DTLgidxNoFormat
  \let\emph\DTLgidxNoFormat
  \let\textsuperscript\DTLgidxNoFormat
\datagidxconvertchars
  \let\ensuremath\DTLgidxNoFormat
  \let\DTLgidxParen@gobble
  \let\DTLgidxName@\secondoftwo
  \let\DTLgidxPlace\datagidx@invert
  \let\DTLgidxSubject\datagidx@invert
  \let\DTLgidxOffice@\secondoftwo
  \let\DTLgidxParticle\datagidx@bothoftwo
  \datagidxwordifygreek
  \datagidxstripaccents
  \datagidxextendedtoascii
  \newtermlabelhook
  \protected@xdef\newterm@label{\newterm@label}%
  \let\DTLgidxName\datagidx@person
  \let\DTLgidxPlace\datagidx@place
  \let\DTLgidxSubject\datagidx@subject
  \let\DTLgidxOffice\datagidx@person
  \let\DTLgidxParen\datagidx@paren
  \let\DTLgidxMac\datagidx@mac
  \let\DTLgidxSaint\datagidx@saint
  \let\DTLgidxIgnore@gobble

```

```

\let\DTLgidxRank\datagidx@rank
\let\DTLgidxParticle\datagidx@particle
\let\DTLgidxNameNum\datagidx@namenum
\protected@xdef\newterm@sort{\newterm@sort}%
\egroup
}
\newcommand*{\datagidx@add@term}[1]{%
\global\cslet{datagidxentry@\newterm@label}{\newterm@database}%
\DTLnewrow{\newterm@database}%
\DTLnewdbentry{\newterm@database}{Name}{#1}%
\DTLnewdbentry{\newterm@database}{Used}{0}%
{%
\dtlexpandnewvalue
\DTLnewdbentry{\newterm@database}{Text}{\expandonce\newterm@text}%
\DTLnewdbentry{\newterm@database}{Description}{\expandonce\newterm@description}%
\DTLnewdbentry{\newterm@database}{Label}{\expandonce\newterm@label}%
\DTLnewdbentry{\newterm@database}{Sort}{\expandonce\newterm@sort}%
\DTLnewdbentry{\newterm@database}{Symbol}{\expandonce\newterm@symbol}%
\DTLnewdbentry{\newterm@database}{Short}{\expandonce\newterm@short}%
\DTLnewdbentry{\newterm@database}{Long}{\expandonce\newterm@long}%
\ifundef\newterm@plural
{%
\DTLnewdbentry{\newterm@database}{Plural}{\expandonce\newterm@text s}%
}%
{%
\DTLnewdbentry{\newterm@database}{Plural}{\expandonce\newterm@plural}%
}%
\ifundef\newterm@shortplural
{%
\DTLnewdbentry{\newterm@database}{ShortPlural}{\expandonce\newterm@short s}%
}%
{%
\DTLnewdbentry{\newterm@database}{ShortPlural}{\expandonce\newterm@shortplural}%
}%
\ifundef\newterm@longplural
{%
\DTLnewdbentry{\newterm@database}{LongPlural}{\expandonce\newterm@long s}%
}%
{%
\DTLnewdbentry{\newterm@database}{LongPlural}{\expandonce\newterm@longplural}%
}%
\ifdefempty{\newterm@see}%
{%
\DTLnewdbentry{\newterm@database}{See}{\newterm@see}}%
\ifdefempty{\newterm@seealso}%
{%
\DTLnewdbentry{\newterm@database}{SeeAlso}{\newterm@seealso}}%
\newterm@extrafields
\ifdefempty{\newterm@parent}%
{%
}

```

```

{%
  \iftermexists{\newterm@parent}%
  {%
    \edef\newterm@parentdatabase{\csuse{datagidxentry@\newterm@parent}}%
    \ifthenelse{\equal{\newterm@parentdatabase}{\newterm@database}}
    {%
      \DTLnewbentry{\newterm@database}{Parent}{\newterm@parent}%
      \datagidx@addchild{\newterm@database}{\newterm@parent}{\newterm@label}%
    }%
    {%
      \PackageError{datagidx}%
      {%
        Parent entry '\newterm@parent' must belong to the
        same database as child entry '\newterm@label'%
      }%
      {%
        Parent entry is in database
        '\newterm@parentdatabase' and child entry is in
        database '\newterm@database'%
      }%
    }%
  }%
}
{%
  \PackageError{datagidx}%
  {%
    Can't assign parent to '\newterm@label':
    '\newterm@parent' doesn't exist%
  }%
}
}
}
\global\let\datagidxlastlabel\newterm@label
\postnewtermhook
}%
\newcommand*{\postnewtermhook}{}
\newcommand*{\newtermfield}[1]{\csuse{newterm@#1}}
\newcommand{\ifnewtermfield}[3]{%
  \ifcsdef{newterm@#1}
  {%
    \ifcseempty{newterm@#1}{#3}{#2}%
  }%
  {%
    #3%
  }%
}
}
\newcommand{\datagidx@newterm}[2][]{%
  \datagidx@setfieldvalues{#1}{#2}%
  \DTLifdbexists{\newterm@database}%
  {%

```

```

\iftermexists{\newterm@label}%
{%
  \PackageError{datagidx}{Term '\newterm@label' already
    exists in database '\newterm@database'}}{%
}%
{%
  \datagidx@add@term{#2}%
}%
}%
{%
  \PackageError{datagidx}%
  {Glossary/index data base '\newterm@database' doesn't exist}%
  {%
    You must define the glossary/index data base before you can
    add any terms to it.%
  }%
}%
}
\newcommand{\datagidx@highopt@newterm}[2][]{%
  \datagidx@setfieldvalues{#1}{#2}%
  \DTLifdbexists{\newterm@database}%
  {%
    \edef\dtl@dogetrow{%
      \noexpand\dtlgetrowindex
      {\noexpand\dtl@rowidx}%
      {\newterm@database}%
      {%
        \dtlcolumnindex{\newterm@database}{Label}%
      }%
      {\newterm@label}}%
    \dtl@dogetrow
    \ifx\dtl@rowidx\dtlnovalue
      \datagidx@add@term{#2}%
      \csdef{datagidx@do@highopt@sort@\newterm@database}{\datagidx@sort}%
    \else
      \global\cslet{datagidxentry@\newterm@label}{\newterm@database}%
      \global\let\datagidxlastlabel\newterm@label
    \fi
  }%
  {%
    \PackageError{datagidx}%
    {Glossary/index data base '\newterm@database' doesn't exist}%
    {%
      You must define the glossary/index data base before you can
      add any terms to it.%
    }%
  }%
}
\newcommand*\datagidx@addchild}[3]{%
  \edef\dtl@dogetrow{%

```



```

\dtl@dogetrow
\dtlgetentryfromcurrentrow
  {\datagidx@value}%
  {\dtlcolumnindex{\newterm@database}{Used}}%
\ifnum\datagidx@value=1\relax
  #2%
\else
  #3%
\fi
}
\newcommand*\glsreset}[1]{%
  \letcs{\newterm@database}{datagidxentry@#1}%
  \edef\do@getrow{%
    \noexpand\dtlgetrowforvalue
    {\newterm@database}%
    {\dtlcolumnindex{\newterm@database}{Label}}%
    {#1}%
  }%
  \do@getrow
  \dtlreplaceentryincurrentrow
    {0}{\dtlcolumnindex{\newterm@database}{Used}}%
  \dtlrecombine
}
\newcommand*\glsunset}[1]{%
  \letcs{\newterm@database}{datagidxentry@#1}%
  \edef\do@getrow{%
    \noexpand\dtlgetrowforvalue
    {\newterm@database}%
    {\dtlcolumnindex{\newterm@database}{Label}}%
    {#1}%
  }%
  \do@getrow
  \dtlreplaceentryincurrentrow
    {1}{\dtlcolumnindex{\newterm@database}{Used}}%
  \dtlrecombine
}
\newcommand*\glsresetall}[1]{%
  \def\datagidx@list{}%
  \dtlforcolumn{\datagidx@label}{#1}{Label}%
  {%
    \ifdefempty\datagidx@list
    {%
      \let\datagidx@list\datagidx@label
    }%
    {%
      \eappto\datagidx@list{,\datagidx@label}%
    }%
  }%
  \@for\datagidx@thislabel:=\datagidx@list\do
  {%

```

```

    \glsreset{\datagidx@thislabel}%
  }%
}
\newcommand*{\glsunsetall}[1]{%
  \def\datagidx@list{}%
  \dtlforcolumn{\datagidx@label}{#1}{Label}%
  {%
    \ifdefempty\datagidx@list
    {%
      \let\datagidx@list\datagidx@label
    }%
    {%
      \eappto\datagidx@list{,\datagidx@label}%
    }%
  }%
  \@for\datagidx@thislabel:=\datagidx@list\do
  {%
    \glsunset{\datagidx@thislabel}%
  }%
}
\newcount\datagidx@anchorcount
\newcommand*{\datagidx@formatanchor}[1]{%
  \ifnum#1<10000
  0%
  \ifnum#1<1000
  0%
  \ifnum#1<100
  0%
  \ifnum#1<10
  0%
  \fi
  \fi
  \fi
  \fi
  \number#1%
}
\newcommand*{\@datagidx@escloc}[2]{%
  \expandafter\string\csname#1\endcsname{\noexpand\number#2}%
}
\newcommand*{\datagidx@escapelocation}{%
  \def\@arabic{\@datagidx@escloc{@arabic}}%
  \def\@roman{\@datagidx@escloc{@roman}}%
  \def\@Roman{\@datagidx@escloc{@Roman}}%
  \def\@alph{\@datagidx@escloc{@alph}}%
  \def\@Alph{\@datagidx@escloc{@Alph}}%
}
\newcommand*{\datagidx@escapelocationformat}{%
  \def\@arabic##1{arabic}%
  \def\@roman##1{roman}%
  \def\@Roman##1{Roman}%
}

```

```

\def\@alph##1{alph}%
\def\@Alph##1{Alph}%
}
\newcommand*\@datagidx@clearlocationformat{%
\let\@arabic\@firstofone
\let\@roman\@firstofone
\let\@Roman\@firstofone
\let\@alph\@firstofone
\let\@Alph\@firstofone
}
\newcommand*\@DTLgidxAddLocationType}[1]{%
\gappto\@datagidx@escapelocation{%
\expandafter\def\csname#1\endcsname{\@datagidx@escloc{#1}}%
}%
\gappto\@datagidx@escapelocationformat{%
\expandafter\def\csname#1\endcsname##1{#1}%
}%
\gappto\@datagidx@clearlocationformat{%
\expandafter\let\csname#1\endcsname\@firstofone
}%
}
\@onlypreamble\@DTLgidxAddLocationType
\newcommand*\@datagidx@target}[4]{%
\global\advance\@datagidx@anchorcount by 1\relax
\edef\@datagidx@target{datagidx.\@datagidx@formatanchor\@datagidx@anchorcount}%
\ifstrempy{#3}
{%
\@datagidx@write@usedentry{#1}{}%
}%
{%
\begin{group}
\@datagidx@escapelocation
\def\@arabic{\noexpand\@arabic}%
\def\@roman{\noexpand\@roman}%
\def\@Roman{\noexpand\@Roman}%
\def\@alph{\noexpand\@alph}%
\def\@Alph{\noexpand\@Alph}%
\protected@edef\@datagidx@dowriteaux{%
\noexpand\@datagidx@write@usedentry{#1}%
{[#2]{#3}{\@datagidx@target}}%
}%
\@datagidx@dowriteaux
\end{group}
}%
\ifdef\hypertarget
{%
\@datagidx@showifdraft
{%
[\@datagidx@target]%
\discretionary{}{}{}%
}
}
}

```

```

    }%
    \bgroup
      \let\glsadd@gobble
      \settoheight\dimen@{#4}%
      \raisebox{\dimen@}%
      {%
        \datagidxtarget{\@datagidx@target}{}%
      }%
    \egroup
  }%
  {%
  }%
  \datagidxshowifdraft{[#1]\discretionary{}{}{}}%
  #4%
}
\DeclareRobustCommand*\glsdispenentry}[2]{%
  \DTLgidxFetchEntry{\datagidx@dispenentryval}{#1}{#2}%
  \datagidx@dispenentryval
}
\DeclareRobustCommand*\Glsdispenentry}[2]{%
  \DTLgidxFetchEntry{\datagidx@dispenentryval}{#1}{#2}%
  \xmakefirstuc\datagidx@dispenentryval
}
\newcommand*\DTLgidxFetchEntry}[3]{%
  \ifcsdef{datagidxentry@#2}%
  {%
    \letcs{\newterm@database}{datagidxentry@#2}%
    \edef\do@getrow{%
      \noexpand\dtlgetrowforvalue
      {\newterm@database}%
      {\dtlcolumnindex{\newterm@database}{Label}}%
      {#2}%
    }%
    \do@getrow
    \dtlgetentryfromcurrentrow
    {#1}%
    {\dtlcolumnindex{\newterm@database}{#3}}%
  }%
  {%
    \PackageError{datagidx}{No term `#2' defined}{}%
  }%
}
\newcommand*\datagidx@parse@formatlabel}[1]{%
  \datagidx@parse@format@label@#1\@endparse@formatlabel@
}
\newcommand*\datagidx@parse@format@label@{%
  \ifnextchar[{\datagidx@parse@formatlabel@}{\datagidx@parse@formatlabel@[ ]}%
}
\def\datagidx@parse@formatlabel@[#1]#2\@endparse@formatlabel@{%
  \def\datagidx@format{#1}%

```

```

\def\datagidx@label{#2}%
}
\newcommand*\{@datagidx@use@entry}[1]{%
\ifcsundef{datagidxentry@\datagidx@label}
{%
\PackageError{datagidx}{Entry '\datagidx@label' doesn't exist}{}%
}%
{%
\letcs{\newterm@database}{datagidxentry@\datagidx@label}%
\edef\do@getrow{%
\noexpand\dtlgetrowforvalue
{\newterm@database}%
{\dtlcolumnindex{\newterm@database}{Label}}%
{\datagidx@label}%
}%
\do@getrow
\dtlgetentryfromcurrentrow
{\datagidx@id}%
{\dtlcolumnindex{\newterm@database}{FirstId}}%
\DTLifnull\datagidx@id
{%
\count@=\datagidx@anchorcount\relax
\advance\count@ by 1\relax
\dtlappendentrytocurrentrow{FirstId}{\datagidx@formatanchor\count@}%
}%
}%
\dtlreplaceentryincurrentrow
{1}{\dtlcolumnindex{\newterm@database}{Used}}%
\dtlgetentryfromcurrentrow
{\datagidx@parent}%
{\dtlcolumnindex{\newterm@database}{Parent}}%
\dtlrecombine
\datagidx@markparent{\newterm@database}{\datagidx@parent}%
\datagidx@target{\datagidx@label}{\datagidx@format}%
{\csuse{the\DTLgidxCOUNTER}}{#1}%
}%
}
\newcommand*\{DTLgidxCOUNTER}{page}
\newcommand*\{datagidx@markparent}[2]{%
\ifx#2\dtlnovalue
\else
\datagidx@target{#2}{\}\}%
\edef\do@getrow{%
\noexpand\dtlgetrowforvalue
{#1}%
{\dtlcolumnindex{#1}{Label}}%
{#2}}%
\do@getrow
\dtlgetentryfromcurrentrow
{\datagidx@id}%

```

```

        {\dtlcolumnindex{\newterm@database}{FirstId}}%
\DTLifnull\datagidx@id
{%
  \dtlappendentrytocurrentrow{FirstId}{\datagidx@formatanchor\datagidx@anchorcount}%
}%
}%
}
  \dtlgetentryfromcurrentrow
  {\datagidx@parent}%
  {\dtlcolumnindex{#1}{Parent}}%
\dtlrecombine
  \datagidx@markparent{#1}{\datagidx@parent}%
\fi
}
\newcommand*{\datagidx@write@usedentry}[2]{%
  \datagidx@do@highopt@update{#1}%
  \protected@write{\@auxout}{}%
  {%
    \string\datagidx@usedentry{#1}{#2}%
  }%
  \protected@edef\datagidx@do@usedentry{%
    \noexpand\datagidx@xusedentry{CurrentLocation}{#1}{#2}%
  }%
  \expandafter\ifstrequal\expandafter{\DTLgidxCOUNTER}{page}%
  {%
    \expandafter\afterpage\expandafter{\datagidx@do@usedentry}%
  }%
  {
    \datagidx@do@usedentry
  }%
}
\newcommand*{\datagidx@xusedentry}[3]{%
  \protected@edef\@datagidx@do@xusedentry{%
    \noexpand\datagidx@usedentry[#1]{#2}{#3}%
  }%
  \@datagidx@do@xusedentry
}
\newcommand*{\datagidx@usedentry}[3][Location]{%
  \ifcsundef{datagidxentry@#2}%
  {%
    \PackageWarning{datagidx}{No term `#2' defined. Ignoring}%
  }%
  {%
    \letcs{\newterm@database}{datagidxentry@#2}%
    \edef\do@getrow{%
      \noexpand\dtlgetrowforvalue
      {\newterm@database}%
      {\dtlcolumnindex{\newterm@database}{Label}}%
      {#2}%
    }%
    \do@getrow
  }%
}

```

```

\dtlgetentryfromcurrentrow
  {\datagidx@loc}%
  {\dtlcolumnindex{\newterm@database}{#1}}%
\ifx\datagidx@loc\dtlnovalue
  \def\datagidx@loc{#3}%
  \dtlappendentrytocurrentrow{#1}{\expandonce\datagidx@loc}%
\else
  \ifdefempty{\datagidx@loc}%
  {%
    \def\datagidx@loc{#3}%
  }%
  {%
    \ifstrempy{#3}%
    {}%
    {%
      \appto\datagidx@loc{,#3}%
    }%
  }%
  \expandafter\dtlreplaceentryincurrentrow\expandafter
  {\datagidx@loc}%
  {\dtlcolumnindex{\newterm@database}{#1}}%
\fi
\dtlrecombine
}%
}
\newcommand*{\datagidx@save@loc}[2]{%
\bgroup
  \datagidx@escape@location
  \xdef\datagidx@tmp{#2}%
\egroup
\expandafter\xdef\csname datagidx@prev@loc@#1\endcsname{\datagidx@tmp}%
}
\newcommand*{\glsadd}[1]{%
  \NoCaseChange{\@glsadd{#1}}%
}
\DeclareRobustCommand*{\@glsadd}[1]{%
  \ifcsundef{datagidxentry@\datagidx@label}%
  {%
    \PackageError{datagidx}{Term ``\datagidx@label' doesn't exist}{}%
  }%
  {%
    \datagidx@parse@format@label{#1}%
    \datagidx@target{\datagidx@label}{\datagidx@format}%
    {\csuse{the\DTLgidxCounter}}{}%
    \letcs{\newterm@database}{datagidxentry@\datagidx@label}%
    \edef\do@getrow{%
      \noexpand\dtlgetrowforvalue
      {\newterm@database}%
      {\dtlcolumnindex{\newterm@database}{Label}}%
      {\datagidx@label}%
    }%
  }%
}

```

```

}%
\do@getrow
\dtlreplaceentryincurrentrow
  {1}{\dtlcolumnindex{\newterm@database}{Used}}%
\dtlgetentryfromcurrentrow
  {\datagidx@id}%
  {\dtlcolumnindex{\newterm@database}{FirstId}}%
\DTLifnull\datagidx@id
{%
  \dtlappendentrytocurrentrow{FirstId}{\datagidx@formatanchor\datagidx@anchorcount}%
}%
}%
\dtlrecombine
}%
}
\newcount\datagidx@count
\newcommand*\glsaddall}[1]{%
  \DTLifdbexists{#1}%
  {%
    \edef\datagidx@rowcount{\number\DTLrowcount{#1}}%
    \datagidx@count=0\relax
    \loop
      \advance\datagidx@count by 1\relax
      \dtlgetrow{#1}{\datagidx@count}%
      \dtlgetentryfromcurrentrow
        {\datagidx@label}%
        {\dtlcolumnindex{#1}{Label}}%
    \bgroup
      \undef\hypertarget
      \datagidx@target{\datagidx@label}{}{}{}%
    \egroup
    \dtlreplaceentryincurrentrow
      {1}{\dtlcolumnindex{#1}{Used}}%
    \dtlgetentryfromcurrentrow
      {\datagidx@id}%
      {\dtlcolumnindex{#1}{FirstId}}%
    \DTLifnull\datagidx@id
    {%
      \dtlappendentrytocurrentrow{FirstId}{\datagidx@formatanchor\datagidx@anchorcount}%
    }%
    }%
    \dtlrecombine
  \ifnum\datagidx@count<\datagidx@rowcount
  \repeat
  }%
  }%
  \PackageError{datagidx}{Database `#1' doesn't exist}{}%
  }%
}
\DeclareRobustCommand*\glslink}[2]{%

```

```

\datagidx@parse@format label{#1}%
\datagidxlink{\datagidx@label}%
{%
  \@datagidx@use@entry{#2}%
}%
}
\DeclareRobustCommand*\useentry}[2]{%
  \datagidx@parse@format label{#1}%
  \DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
  \datagidxlink{\datagidx@label}%
  {%
    \@datagidx@use@entry{\datagidx@value}%
  }%
}
\DeclareRobustCommand*\Useentry}[2]{%
  \datagidx@parse@format label{#1}%
  \DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
  \datagidxlink{\datagidx@label}%
  {%
    \@datagidx@use@entry{\xmakefirstuc{\datagidx@value}}%
  }%
}
\DeclareRobustCommand*\USEEntry}[2]{%
  \datagidx@parse@format label{#1}%
  \DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
  \datagidxlink{\datagidx@label}%
  {%
    \@datagidx@use@entry{\MakeTextUppercase{\datagidx@value}}%
  }%
}
\DeclareRobustCommand*\useentrynl}[2]{%
  \datagidx@parse@format label{#1}%
  \DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
  \@datagidx@use@entry{\datagidx@value}%
}
\DeclareRobustCommand*\Useentrynl}[2]{%
  \datagidx@parse@format label{#1}%
  \DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
  \@datagidx@use@entry{\xmakefirstuc{\datagidx@value}}%
}
\DeclareRobustCommand*\USEEntrynl}[2]{%
  \datagidx@parse@format label{#1}%
  \DTLgidxFetchEntry{\datagidx@value}{\datagidx@label}{#2}%
  \@datagidx@use@entry{\MakeTextUppercase{\datagidx@value}}%
}
\DeclareRobustCommand*\gls}[1]{\useentry{#1}{Text}}
\DeclareRobustCommand*\glspl}[1]{\useentry{#1}{Plural}}
\DeclareRobustCommand*\Gls}[1]{\Useentry{#1}{Text}}
\DeclareRobustCommand*\Glspl}[1]{\Useentry{#1}{Plural}}
\DeclareRobustCommand*\glsnl}[1]{\useentrynl{#1}{Text}}

```

```

\DeclareRobustCommand*\glsplnl}[1]{\useentryn{#1}{Plural}}
\DeclareRobustCommand*\Glsnl}[1]{\Useentryn{#1}{Text}}
\DeclareRobustCommand*\Glsplnl}[1]{\Useentryn{#1}{Plural}}
\DeclareRobustCommand*\gls sym}[1]{\useentry{#1}{Symbol}}
\DeclareRobustCommand*\Gls sym}[1]{\Useentry{#1}{Symbol}}
\newcommand*\DTLgidxFormatAcr}[3]{%
  \DTLgidxAcrStyle{\glsdispenry{#1}{#2}}{\useentry{#1}{#3}}%
}
\newcommand*\DTLgidxFormatAcrUC}[3]{%
  \DTLgidxAcrStyle{\Glsdispenry{#1}{#2}}{\useentry{#1}{#3}}%
}
\DeclareRobustCommand*\acr}[1]{%
  \ifentryused{#1}%
  {\useentry{#1}{Short}}%
  {\DTLgidxFormatAcr{#1}{Long}{Short}}%
}
\DeclareRobustCommand*\acrpl}[1]{%
  \ifentryused{#1}%
  {\useentry{#1}{ShortPlural}}%
  {\DTLgidxFormatAcr{#1}{LongPlural}{ShortPlural}}%
}
\DeclareRobustCommand*\Acr}[1]{%
  \ifentryused{#1}%
  {\Useentry{#1}{Short}}%
  {\DTLgidxFormatAcrUC{#1}{Long}{Short}}%
}
\DeclareRobustCommand*\Acrpl}[1]{%
  \ifentryused{#1}%
  {\Useentry{#1}{ShortPlural}}%
  {\DTLgidxFormatAcrUC{#1}{LongPlural}{ShortPlural}}%
}
\define@key{printterms}{database}{\renewcommand*\newterm@database}{#1}}
\define@choicekey{printterms}{postdesc}[\val\nr]%
{none,dot}%
{%
  \datagidx@setpostdesc\nr
}
\define@choicekey{printterms}{prelocation}[\val\nr]%
{none,enspace,space,dotfill,hfill}%
{%
  \datagidx@setprelocation\nr
}
\define@choicekey{printterms}{location}[\val\nr]%
{hide,list,first}%
{\datagidx@setlocation\nr}
\define@choicekey{printterms}{symbol desc}[\val\nr]%
{symbol,desc,(symbol) desc,desc (symbol),symbol desc,desc symbol}%
{\datagidx@formatsymdesc\nr}
\define@key{printterms}{columns}%
{%

```

```

\DTLgidxSetColumns{#1}%
}
\define@choicekey{printterms}{namecase}[\val\nr]%
{nochange,uc,lc,firstuc,capitalise}%
{%
\datagidx@setnamecase\nr
}
\define@key{printterms}{namefont}%
{%
\renewcommand*\DTLgidxNameFont}[1][{#1{##1}}]%
}
\define@key{printterms}{postname}
{%
\renewcommand*\DTLgidxPostName}{#1}%
}
\define@choicekey{printterms}{see}[\val\nr]%
{comma,brackets,dot,space,nosep,semicolon,location}%
{\datagidx@setsee\nr}
\define@choicekey{printterms}{child}[\val\nr]%
{named,noname}%
{%
\datagidx@setchildstyle\nr
}
\define@key{printterms}{symbolwidth}%
{%
\setlength{\datagidxsymbolwidth}{#1}%
}
\define@key{printterms}{locationwidth}%
{%
\setlength{\datagidxlocationwidth}{#1}%
}
\define@choicekey{printterms}{childsort}[\val\nr]%
{true,false}[true]%
{%
\datagidx@setchildsort\nr
}
\define@choicekey{printterms}{showgroups}{true,false}[true]{%
\appto\newterm@styles{showgroups={#1},}%
}
\define@key{printterms}{style}{\appto\newterm@styles{style={#1},}}
\define@key{printterms}{heading}{\appto\newterm@styles{heading={#1},}}
\define@key{printterms}{postheading}{%
\appto\newterm@styles{postheading={#1},}%
}
\define@key{printterms}{sort}{\appto\newterm@styles{sort={#1},}}
\define@choicekey{printterms}{balance}[\val\nr]{true,false}[true]{%
\ifcase\nr\relax
\appto\newterm@styles{balance=true,}%
\or
\appto\newterm@styles{balance=false,}%
}

```

```

\fi
}
\newcommand*{\printterms@condition}{\boolean{true}}
\define@key{printterms}{condition}{\renewcommand*{\printterms@condition}{#1}}
\newcommand{\printtermsstartpar}{\par}
\newcommand*{\printterms@setupmulticol}{%
\ifdefempty\datagidx@postheading
{%
\edef\datagidx@prestart{%
\noexpand\datagidx@heading{\noexpand\datagidx@title}%
\noexpand\begin{\datagidx@multicols}{\datagidx@columns}%
}%
}%
{%
\edef\datagidx@prestart{%
\noexpand\datagidx@heading{\noexpand\datagidx@title}%
\noexpand\begin{\datagidx@multicols}{\datagidx@columns}%
[\noexpand\datagidx@postheading]%
}%
}%
\edef\datagidx@postend{%
\noexpand\end{\datagidx@multicols}%
}%
}
}
\newcommand*{\printterms@setuptwocol}{%
\def\datagidx@prestart{%
\twocolumn[\datagidx@heading{\datagidx@title}%
\datagidx@postheading]}%
\if@twocolumn
\def\datagidx@postend{}%
\else
\def\datagidx@postend{\printtermsrestoreonecolumn}%
\fi
}
}
\newcommand{\printtermsrestoreonecolumn}{\onecolumn}
\newcommand{\printterms}[1][1]{%
\bgroup
\let\newterm@database\datagidx@defaultdatabase
\let\newterm@styles\@empty
\setkeys{printterms}{#1}%
\DTLifdbexists{\newterm@database}%
{%
\edef\DTLgidxCurrentdb{\newterm@database}%
\edef\do@getrow{\noexpand\dtlgetrowforvalue
{datagidx}%
{\dtlcolumnindex{datagidx}{Glossary}}%
{\newterm@database}%
}%
\do@getrow
\dtlgetentryfromcurrentrow

```

```

{\datagidx@title}%
{\dtlcolumnindex{datagidx}{Title}}%
\dtlgetentryfromcurrentrow
{\datagidx@heading}%
{\dtlcolumnindex{datagidx}{Heading}}%
\dtlgetentryfromcurrentrow
{\datagidx@postheading}%
{\dtlcolumnindex{datagidx}{PostHeading}}%
\dtlgetentryfromcurrentrow
{\datagidx@multicols}%
{\dtlcolumnindex{datagidx}{MultiCols}}%
\dtlgetentryfromcurrentrow
{\datagidx@sort}%
{\dtlcolumnindex{datagidx}{Sort}}%
\dtlgetentryfromcurrentrow
{\datagidx@style}%
{\dtlcolumnindex{datagidx}{Style}}%
\dtlgetentryfromcurrentrow
{\datagidx@showgroups}%
{\dtlcolumnindex{datagidx}{ShowGroups}}%
\edef\dtl@do@setkeys{\noexpand\setkeys{newgloss}{\expandonce\newterm@styles}}%
\dtl@do@setkeys
\ifnum\datagidx@columns>1\relax
  \ifnum\datagidx@columns=2\relax
    \ifdatagidxbalance
      \printterms@setupmulticol
    \else
      \printterms@setuptwocol
    \fi
  \else
    \printterms@setupmulticol
  \fi
\else
  \def\datagidx@prestart{}%
  \def\datagidx@postend{}%
\fi
\let\@dtl@dbname\DTLgidxCurrentdb
\csuse{datagidxshowgroups\datagidx@showgroups}%
\datagidxsetstyle{\datagidx@style}%
\def\datagidx@labellist{}%
\ifnum\datagidx@columns=1\relax
  \datagidx@heading{\datagidx@title}%
  \datagidx@postheading
\fi
\datagidx@do@sort
\datagidx@prestart
\printtermsstartpar
\datagidxstart
\let\DTLgidxName\datagidx@invert
\let\DTLgidxPlace\datagidx@invert

```

```

\let\DTLgidxSubject\datagidx@invert
\let\DTLgidxOffice\datagidx@invert
\DTLgidxForeachEntry
  {%
    \datagidxitem
  }%
\datagidxend
\datagidx@postend
}%
{%
\PackageError{datagidx}%
{Glossary/index data base '\newterm@database' doesn't exist}%
{%
  You must define the glossary/index data base before you can
  use it.%
}%
}%
\egroup
}
\def\datagidx@getgroup#1#2\datagidx@endgetgroup{%
\dtl@setcharcode{#1}{\count@}%
\dtlifintclosedbetween{\count@}{48}{57}%
{%
\gdef\datagidxcurrentgroup{Numbers}%
}%
{%
\dtlifintclosedbetween{\count@}{97}{122}%
{%
\advance\count@ by -96\relax
\def\datagidxcurrentgroup{\@Alph\count@}%
}%
{%
\dtlifintclosedbetween{\count@}{65}{90}%
{%
\gdef\datagidxcurrentgroup{#1}%
}%
{%
\gdef\datagidxcurrentgroup{Symbols}%
}%
}%
}
}
\newcommand*{\DTLgidxGroupHeaderTitle}[1]{%
\ifcsdef{datagidx#1name}
{%
\csuse{datagidx#1name}%
}%
{%
#1%
}%
}

```

```

}
\newcommand{\DTLgidxForeachEntry}[1]{%
  \def\datagidxprevgroup{%
    \edef\datagidx@doforeachentry{%
      \noexpand\DTLforeach*[\expandonce\printterms@condition]{\DTLgidxCurrenldb}%
      {\expandonce\DTLgidxAssignList}
    }%
    \datagidx@doforeachentry
  }%
  \DTLifnull{\Parent}%
  {%
    \DTLifnull\Location
    {%
      \DTLifnull\CurrentLocation
      {%
        }%
      }%
      {%
        \global\let\@datagidx@dorerun@warn\@data@rerun@warn
      }%
    }%
    {%
      \ifcsdef{datagidx@prev@loc@\Label}%
      {%
        \dtlgidx@checklocationchange
      }%
      {%
        \global\let\@datagidx@dorerun@warn\@data@rerun@warn
      }%
    }%
    \datagidx@doifdisplayed
    {%
      \edef\datagidx@dowrite{%
        \noexpand\protected@write\noexpand\@auxout{%
          {%
            \string\datagidx@save@loc{\Label}{\CurrentLocation}%
          }%
        }%
      }%
      \datagidx@dowrite
      \datagidx@level=1\relax
      \expandafter\datagidx@getgroup\Sort{\datagidx@endgetgroup
      #1%
      \global\let\datagidxprevgroup\datagidxcurrentgroup
    }%
  }%
  }%
  }%
}
\newcommand*{\dtlgidx@checklocationchange}{%
  \protected@edef\@prev@location{%
    \csname datagidx@prev@loc@\Label\endcsname}%

```

```

\@onelevel@sanitize\@prev@location
\protected@edef\@cur@location{\CurrentLocation}%
\@onelevel@sanitize\@cur@location
\ifdefequal{\@prev@location}{\@cur@location}%
{}%
{%
\global\let\@datagidx@dorerun@warn\@data@rerun@warn
}%
}
\newcommand{\datagidx@doifdisplayed}[1]{%
\DTLifnull{\Location}%
{%
\DTLifnull{\See}
{%
\DTLifnull{\SeeAlso}{}%
{}%
#1%
}%
}%
{%
\@for\dtl@thislabel:=\See\do
{%
\iftermexists{\dtl@thislabel}%
{%
\ifentryused{\dtl@thislabel}%
{%
#1%
\@endfortrue
}%
}%
}%
}%
}%
}%
#1%
}%
}%
\newcount\datagidx@level

```

30.13 Rollback v2.32 (datapie-2019-09-27.sty)

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datapie}[2019/09/27 v2.32 (NLCT)]
\RequirePackage{xkeyval}
\newif\ifDTLcolorpiechart
\DTLcolorpiecharttrue
\DeclareOption{color}{\DTLcolorpiecharttrue}

```

```

\DeclareOption{gray}{\DTLcolorpiechartfalse}
\define@boolkey{datapie}[DTL]{rotateinner}[true]{}
\define@boolkey{datapie}[DTL]{rotateouter}[true]{}
\DTLrotateinnerfalse
\DTLrotateouterfalse
\DeclareOption{rotateinner}{\DTLrotateinnertrue}
\DeclareOption{norotateinner}{\DTLrotateinnerfalse}
\DeclareOption{rotateouter}{\DTLrotateoutertrue}
\DeclareOption{norotateouter}{\DTLrotateouterfalse}
\ProcessOptions
\RequirePackage{datatool}[v2.32]
\RequirePackage{tikz}
\newlength\DTLradius
\DTLradius=2cm
\newcommand*\DTLinnerratio{0.5}
\newcommand*\DTLouterratio{1.25}
\newcommand*\DTLcutawayratio{0.2}
\newcommand*\DTLstartangle{0}
\newlength\dtl@inneroffset
\dtl@inneroffset=\DTLinnerratio\DTLradius
\newlength\dtl@outeroffset
\dtl@outeroffset=\DTLouterratio\DTLradius
\newlength\dtl@cutawayoffset
\dtl@cutawayoffset=\DTLcutawayratio\DTLradius
\newcommand*\dtl@piecutaways{}
\def\dtl@innerlabel{\DTLpievariable}%
\def\dtl@outerlabel{}%
\newcounter{DTLpieroundvar}
\setcounter{DTLpieroundvar}{1}
\newcommand*\DTLdisplayinnerlabel[1]{#1}
\newcommand*\DTLdisplayouterlabel[1]{#1}
\newcommand*\DTLpiepercent}{%
\ifnum\dtlforeachlevel=0\relax
\PackageError{datapie}{Can't use
\string\DTLpiepercent\space outside
\string\DTLpiechart}{}%
\else
\csname dtl@piepercent@\romannumeral\@dtl@seg\endcsname
\fi}
\newcommand*\DTLpieatbegintikz{}
\newcommand*\DTLpieatendtikz{}
\newcommand*\DTLsetpiesegmentcolor}[2]{%
\expandafter\def\csname dtlpie@segcol\romannumeral#1\endcsname{#2}%
}
\newcommand*\DTLgetpiesegmentcolor}[1]{%
\csname dtlpie@segcol\romannumeral#1\endcsname}
\newcommand*\DTLdopiesegmentcolor}[1]{%
\expandafter\color\expandafter
{\csname dtlpie@segcol\romannumeral#1\endcsname}}
\newcommand*\DTLdocurrentpiesegmentcolor}{%

```

```

\ifnum\dtlforeachlevel=0\relax
  \PackageError{datapie}{Can't use
    \string\DTLdocurrentpiesegmentcolor\space outside
    \string\DTLpiechart}{}%
\else
  \expandafter\DTLdopiesegmentcolor\expandafter{%
    \csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname}%
\fi}
\newcommand*\DTLpieoutlinecolor}{black}
\newlength\DTLpieoutlinewidth
\DTLpieoutlinewidth=0pt
\ifDTLcolorpiechart
  \DTLsetpiesegmentcolor{1}{red}
  \DTLsetpiesegmentcolor{2}{green}
  \DTLsetpiesegmentcolor{3}{blue}
  \DTLsetpiesegmentcolor{4}{yellow}
  \DTLsetpiesegmentcolor{5}{magenta}
  \DTLsetpiesegmentcolor{6}{cyan}
  \DTLsetpiesegmentcolor{7}{orange}
  \DTLsetpiesegmentcolor{8}{white}
\else
  \DTLsetpiesegmentcolor{1}{black!15}
  \DTLsetpiesegmentcolor{2}{black!25}
  \DTLsetpiesegmentcolor{3}{black!35}
  \DTLsetpiesegmentcolor{4}{black!45}
  \DTLsetpiesegmentcolor{5}{black!55}
  \DTLsetpiesegmentcolor{6}{black!65}
  \DTLsetpiesegmentcolor{7}{black!75}
  \DTLsetpiesegmentcolor{8}{black!85}
\fi
\define@key{datapie}{start}{\def\DTLstartangle{#1}}
\define@key{datapie}{radius}{\DTLradius=#1\relax
\dtl@inneroffset=\DTLinnerratio\DTLradius
\dtl@outeroffset=\DTLouterratio\DTLradius
\dtl@cutawayoffset=\DTLcutawayratio\DTLradius}
\define@key{datapie}{innerratio}{%
\def\DTLinnerratio{#1}%
\dtl@inneroffset=\DTLinnerratio\DTLradius}
\define@key{datapie}{outerratio}{%
\def\DTLouterratio{#1}%
\dtl@outeroffset=\DTLouterratio\DTLradius}
\define@key{datapie}{cutawayratio}{%
\def\DTLcutawayratio{#1}%
\dtl@cutawayoffset=\DTLcutawayratio\DTLradius}
\define@key{datapie}{inneroffset}{%
\dtl@inneroffset=#1}
\define@key{datapie}{outeroffset}{%
\dtl@outeroffset=#1}
\define@key{datapie}{cutawayoffset}{%
\dtl@cutawayoffset=#1}

```

```

\define@key{datapie}{cutaway}{%
\renewcommand*{\dtl@piecutaways}{#1}}
\define@key{datapie}{variable}{%
\def\DTLpievariable{#1}}
\define@key{datapie}{inner label}{%
\def\dtl@inner label{#1}}
\define@key{datapie}{outer label}{%
\def\dtl@outer label{#1}}
\newcommand*{\DTLpiechart}[4][\boolean{true}]{%
\bggroup
\let\DTLpievariable=\relax
\setkeys{datapie}{#2}%
\ifx\DTLpievariable\relax
\PackageError{datapie}%
{\string\DTLpiechart\space missing variable}{}%
\else
\def\dtl@total{0}%
\@sDTLforeach[#1]{#3}{#4}{%
\let\dtl@oldtotal=\dtl@total
\expandafter\DTLconverttodecimal\expandafter
{\DTLpievariable}{\dtl@variable}%
\dtladd{\dtl@total}{\dtl@variable}{\dtl@total}%
}%
\expandafter\DTLconverttodecimal\expandafter
{\DTLstartangle}{\@dtl@start}%
\@sDTLforeach[#1]{#3}{#4}{%
\expandafter\DTLconverttodecimal\expandafter
{\DTLpievariable}{\dtl@variable}%
\dtl@computeangles
{\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname}%
{\dtl@variable}%
\expandafter\@dtl@seg\expandafter=
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname%
\dtl mul{\dtl@tmp}{\dtl@variable}{100}%
\let\dtl@old=\dtl@tmp
\dtl div{\dtl@tmp}{\dtl@old}{\dtl@total}%
\expandafter\dtl round
\csname dtl@piepercent@\romannumeral\@dtl@seg\endcsname\dtl@tmp
\c@DTLpieroundvar
}%
\@for\dtl@row:=\dtl@piecutaways\do{%
\expandafter\@dtl@set@off\dtl@row-\relax
}%
\let\dtl@start=\DTLstartangle
\begin{tikzpicture}
\DTLpieatbegintikz
\@sDTLforeach[#1]{#3}{#4}%
{%
\expandafter\@dtl@seg\expandafter=
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname%

```

```

\edef\dtl@start{%
  \csname dtl@sang@\romannumeral\@dtl@seg\endcsname}%
\edef\dtl@extent{%
  \csname dtl@angle@\romannumeral\@dtl@seg\endcsname}%
\dtladd{\dtl@endangle}{\dtl@start}{\dtl@extent}%
\edef\dtl@angle{%
  \csname dtl@cut@angle@\romannumeral\@dtl@seg\endcsname}%
\let\dtl@old=\dtl@angle
\dtl@truncatedecimal\dtl@angle
\ifnum\dtl@angle>180\relax
  \dtlsub{\dtl@angle}{\dtl@old}{360}%
  \dtl@truncatedecimal\dtl@angle
\fi
\edef\dtl@cutlen{%
  \csname dtl@cut@len@\romannumeral\@dtl@seg\endcsname
}%
\edef\@dtl@shift{(\dtl@angle:\dtl@cutlen)}%
\dtlmul{\dtl@angle}{\dtl@extent}{0.5}%
\dtladd{\dtl@midangle}{\dtl@angle}{\dtl@start}%
\begin{scope}[shift={\@dtl@shift}]%
\fill[color=\DTLgetpiesegmentcolor\@dtl@seg] (0,0) --
(\dtl@start:\DTLradius)
arc (\dtl@start:\dtl@endangle:\DTLradius) -- cycle;
\ifdim\DTLpieoutlinewidth>0pt\relax
  \draw[color=\DTLpieoutlinecolor,%
    line width=\DTLpieoutlinewidth]
    (0,0) -- (\dtl@start:\DTLradius)
    arc (\dtl@start:\dtl@endangle:\DTLradius) -- cycle;
\fi
\dtl@truncatedecimal\dtl@midangle
\ifDTLrotateinner
  \dtlifnumopenbetween{\dtl@midangle}{90}{270}%
  {%
    \let\@dtl@next\@firstoftwo
  }%
  {%
    \dtlifnumlt{\dtl@midangle}{-90}%
    {\let\@dtl@next\@firstoftwo}%
    {\let\@dtl@next\@secondoftwo}%
  }%
  \@dtl@next
  {%
    \dtlsub{\dtl@labelangle}{\dtl@midangle}{180}%
    \dtl@truncatedecimal\dtl@labelangle
    \edef\dtl@innernodeopt{anchor=east,rotate=\dtl@labelangle}%
  }%
  {%
    \edef\dtl@innernodeopt{anchor=west,rotate=\dtl@midangle}%
  }%
\else

```

```

\edef\dtl@innernodeopt{anchor=center}%
\fi
\ifDTLrotateouter
\dtlifnumopenbetween{\dtl@midangle}{90}{270}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumlt{\dtl@midangle}{-90}%
{\let\@dtl@next\@firstoftwo}%
{\let\@dtl@next\@secondoftwo}%
}%
\@dtl@next
{%
\dtlsub{\dtl@labelangle}{\dtl@midangle}{180}%
\dtl@truncatedecimal\dtl@labelangle
\edef\dtl@outernodeopt{anchor=east,rotate=\dtl@labelangle}%
}%
{%
\edef\dtl@outernodeopt{anchor=west,rotate=\dtl@midangle}%
}%
\else
\dtlifnumeq{\dtl@midangle}{45}
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumgt{\dtl@midangle}{315}
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumopenbetween{\dtl@midangle}{-45}{45}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\let\@dtl@next\@secondoftwo
}%
}%
}%
\@dtl@next
{%
\edef\dtl@outernodeopt{anchor=west}%
}%
{%
\dtlifnumopenbetween{\dtl@midangle}{45}{135}%
{%
\let\@dtl@next\@firstoftwo
}%
}%

```

```

{%
\dtlifnumeq{\dtl@midangle}{135}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\let\@dtl@next\@secondoftwo
}%
}%
\@dtl@next
{%
\edef\dtl@outernodeopt{anchor=south}%
}%
{%
\dtlifnumopenbetween{\dtl@midangle}{135}{225}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumeq{\dtl@midangle}{225}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumeq{\dtl@midangle}{-135}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\dtlifnumlt{\dtl@midangle}{-135}%
{%
\let\@dtl@next\@firstoftwo
}%
{%
\let\@dtl@next\@secondoftwo
}%
}%
}%
\@dtl@next
{%
\edef\dtl@outernodeopt{anchor=east}%
}%
{%
\edef\dtl@outernodeopt{anchor=north}%
}%
}%
\fi
\edef\@dtl@do label{%

```

```

        \noexpand\draw (\dtl@midangle:\the\dtl@inneroffset)
            node[\dtl@innernodeopt]{%
        \noexpand\DTLdisplayinnerlabel{\noexpand\dtl@innerlabel}};
    }%
    \@dtl@dolabel
    \edef\@dtl@dolabel{%
        \noexpand\draw (\dtl@midangle:\the\dtl@outeroffset)
            node[\dtl@outernodeopt]{%
        \noexpand\DTLdisplayouterlabel{\noexpand\dtl@outerlabel}};
    }%
    \@dtl@dolabel
    \end{scope}%
}
\DTLpieatendtikz
\end{tikzpicture}%
\fi
\egroup
}
\newcommand*{\dtl@computeangles}[2]{%
    \dtlifnumgt{\@dtl@start}{180}%
    {%
        \let\dtl@old=\@dtl@start
        \dtlsub{\@dtl@start}{\dtl@old}{360}%
    }%
    {}%
    \dtlifnumlt{\@dtl@start}{-180}%
    {%
        \let\dtl@old=\@dtl@start
        \dtladd{\@dtl@start}{\dtl@old}{360}%
    }%
    {}%
    \expandafter\edef\csname dtl@sang@\romannumeral#1\endcsname{%
        \@dtl@start}%
    \dtlmlu{\dtl@angle}{360}{#2}%
    \let\dtl@old=\dtl@angle
    \dtldiv{\dtl@angle}{\dtl@old}{\dtl@total}%
    \expandafter\let\csname dtl@angle@\romannumeral#1\endcsname=\dtl@angle
    \let\dtl@old=\@dtl@start
    \dtladd{\@dtl@start}{\dtl@old}{\dtl@angle}%
    \expandafter\def\csname dtl@cut@angle@\romannumeral#1\endcsname{0}%
    \expandafter\def\csname dtl@cut@len@\romannumeral#1\endcsname{0cm}%
}
\def\@dtl@set@off#1-#2\relax{%
    \ifstrempy{#2}%
    {%
        \@@dtl@set@off{#1}%
    }%
    {%
        \@@dtl@set@offr#1-#2\relax
    }%
}

```

```

}
\newcommand*{\@@dtl@set@off}[1]{%
  \edef\dtl@old{\csname dtl@angle@\romannumeral#1\endcsname}%
  \dtlmul{\dtl@angle}{\dtl@old}{0.5}%
  \let\dtl@old=\dtl@angle
  \edef\dtl@sang{\csname dtl@sang@\romannumeral#1\endcsname}%
  \dtladd{\dtl@angle}{\dtl@old}{\dtl@sang}%
  \expandafter\edef\csname dtl@cut@angle@\romannumeral#1\endcsname{%
    \dtl@angle}%
  \expandafter\edef\csname dtl@cut@len@\romannumeral#1\endcsname{%
    \the\dtl@cutawayoffset}%
}
\newcount\@dtl@seg
\def\@@dtl@set@offr#1-#2-\relax{%
  \ifnum#1>#2\relax
    \PackageError{dataplot}{Segment ranges must go in ascending order}{%
      Try #2-#1 instead of #1-#2}%
  \else
    \def\dtl@angle{0}%
    \@dtl@seg=#1\relax
    \whiledo{\not\(\@dtl@seg > #2\)}{%
      \let\dtl@old=\dtl@angle
      \edef\dtl@segang{\csname dtl@angle@\romannumeral\@dtl@seg\endcsname}%
      \dtladd{\dtl@angle}{\dtl@old}{\dtl@segang}%
      \advance\@dtl@seg by 1\relax
    }%
    \let\dtl@old=\dtl@angle
    \dtlmul{\dtl@angle}{\dtl@old}{0.5}%
    \edef\dtl@sang{\csname dtl@sang@\romannumeral#1\endcsname}%
    \let\dtl@old=\dtl@angle
    \dtladd{\dtl@angle}{\dtl@old}{\dtl@sang}%
    \@dtl@seg=#1\relax
    \whiledo{\not\(\@dtl@seg > #2\)}{%
      \expandafter
        \let\csname dtl@cut@angle@\romannumeral\@dtl@seg\endcsname
          =\dtl@angle
      \expandafter
        \edef\csname dtl@cut@len@\romannumeral\@dtl@seg\endcsname{%
          \the\dtl@cutawayoffset}
      \advance\@dtl@seg by 1\relax
    }%
  \fi
}

```

30.14 Rollback v2.32 (dataplot-2019-09-27.sty)

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{dataplot}[2019/09/27 v2.32 (NLCT)]
\RequirePackage{xkeyval}
\RequirePackage{tikz}

```

```

\RequirePackage{datatool}[=v2.32]
\usetikzlibrary{plotmarks}
\usetikzlibrary{plohandlers}
\usetikzlibrary{calc}
\newcommand*{\DTLplotstream}[4][\boolean{true}]{%
  \@sDTLforeach[#1]{#2}{\dtl@x=#3,\dtl@y=#4}{%
    \DTLconverttodecimal{\dtl@x}{\dtl@decx}%
    \DTLconverttodecimal{\dtl@y}{\dtl@decy}%
    \pgfplotstreampoint{\pgfpointxy{\dtl@decx}{\dtl@decy}}%
  }%
}
\newcommand*{\DTLplotmarks}{%
  \pgfuseplotmark{o},%
  \pgfuseplotmark{x},%
  \pgfuseplotmark{+},%
  \pgfuseplotmark{square},%
  \pgfuseplotmark{triangle},%
  \pgfuseplotmark{diamond},%
  \pgfuseplotmark{pentagon},%
  \pgfuseplotmark{asterisk},%
  \pgfuseplotmark{star}%
}
\newcommand*{\DTLplotmarkcolors}{%
  red,%
  green,%
  blue,%
  yellow,%
  magenta,%
  cyan,%
  orange,%
  black,%
  gray}
\newcommand*{\DTLplotlines}{%
  \pgfsetdash{{0pt},% solid line
  \pgfsetdash{{10pt}{5pt}}{0pt},%
  \pgfsetdash{{5pt}{5pt}}{0pt},%
  \pgfsetdash{{1pt}{5pt}}{0pt},%
  \pgfsetdash{{5pt}{5pt}{1pt}{5pt}}{0pt},%
  \pgfsetdash{{1pt}{3pt}}{0pt},%
}
\newcommand*{\DTLplotlinecolors}{%
  red,%
  green,%
  blue,%
  yellow,%
  magenta,%
  cyan,%
  orange,%
  black,%
  gray}

```

```

\newlength\DTLplotwidth
\setlength\DTLplotwidth{4in}
\newlength\DTLplotheight
\setlength\DTLplotheight{4in}
\newlength\DTLticklength
\setlength\DTLticklength{5pt}
\newlength\DTLminorticklength
\setlength\DTLminorticklength{2pt}
\newlength\DTLticklabeloffset
\setlength\DTLticklabeloffset{8pt}
\newlength\dtl@xticlabelheight
\newlength\dtl@yticlabelwidth
\newlength\DTLmintickgap
\setlength\DTLmintickgap{20pt}
\newlength\DTLminminortickgap
\setlength\DTLminminortickgap{5pt}
\newcounter{DTLplotroundXvar}
\setcounter{DTLplotroundXvar}{2}
\newcounter{DTLplotroundYvar}
\setcounter{DTLplotroundYvar}{2}
\newif\ifDTLxaxis
\DTLxaxistrue
\newcommand*\DTLXAxisStyle{-}
\newif\ifDTLyaxis
\DTLyaxistrue
\newcommand*\DTLYAxisStyle{-}
\newcommand*\DTLmajorgridstyle{color=gray,-}
\newcommand*\DTLminorgridstyle{color=gray,loosely dotted}
\newif\ifDTLxticsin
\DTLxticsintrue
\newif\ifDTLyticsin
\DTLyticsintrue
\newcount\dtl@legendsetting
\newlength\DTLlegendxoffset
\setlength\DTLlegendxoffset{10pt}
\newlength\DTLlegandyoffset
\setlength\DTLlegandyoffset{10pt}
\newcommand*\DTLformatlegend[1]{%
\setlength{\fboxrule}{1.1pt}%
\fcolorbox{black}{white}{#1}}
\newif\ifDTLshowmarkers
\DTLshowmarkerstrue
\newif\ifDTLshowlines
\DTLshowlinesfalse
\newcommand*\DTLplotatbegintikz{}
\newcommand*\@dtlplotohandlermark[1]{%
\pgfplotohandlermark
{%
\pgfmathparse{1/\dtl@scale@x}%
\pgftransformxscale{\pgfmathresult}%

```

```

    \pgfmathparse{1/\dtl@scale@y}%
    \pgftransformyscale{\pgfmathresult}%
    #1%
  }%
}
\newcommand*{\dtlplothandlermark}[1]{%
  \PackageWarning{dataplot}{\string\dtlplothandlermark\space
    found outside \string\DTLplot}%
  \pgfplothandlermark{#1}%
}
\newcommand*{\DTLplotatendtikz}{}
\define@key{dataplot}{x}{%
\def\dtl@xkey{#1}}
\define@key{dataplot}{y}{%
\def\dtl@ykey{#1}}
\define@key{dataplot}{markcolors}{%
\def\DTLplotmarkcolors{#1}}
\define@key{dataplot}{linecolors}{%
\def\DTLplotlinecolors{#1}}
\define@key{dataplot}{colors}{%
\def\DTLplotmarkcolors{#1}%
\def\DTLplotlinecolors{#1}}
\define@key{dataplot}{marks}{%
\def\DTLplotmarks{#1}}
\define@key{dataplot}{lines}{%
\def\DTLplotlines{#1}}
\define@key{dataplot}{width}{%
\setlength\DTLplotwidth{#1}}
\define@key{dataplot}{height}{%
\setlength\DTLplotheight{#1}}
\define@choicekey{dataplot}{style}[\val\nr]{both, lines, markers}{%
\ifcase\nr\relax
  \DTLshowlinestrue
  \DTLshowmarkerstrue
\or
  \DTLshowlinestrue
  \DTLshowmarkersfalse
\or
  \DTLshowmarkerstrue
  \DTLshowlinesfalse
\fi}
\define@choicekey{dataplot}{axes}[\val\nr]{both, x, y, none}[both]{%
\ifcase\nr\relax
  % both
  \DTLxaxistrue
  \DTLxticstrue
  \DTLyaxistrue
  \DTLyticstrue
\or % x
  \DTLxaxistrue

```

```

\DTLxticstrue
\DTLyaxisfalse
\DTLyticsfalse
\or % y
\DTLxaxisfalse
\DTLxticsfalse
\DTLyaxistrue
\DTLyticstrue
\or % none
\DTLxaxisfalse
\DTLxticsfalse
\DTLyaxisfalse
\DTLyticsfalse
\fi
}
\define@boolkey{dataplot}[DTL]{box}[true]{}
\DTLboxfalse
\define@boolkey{dataplot}[DTL]{xtics}[true]{}
\DTLxticstrue
\define@boolkey{dataplot}[DTL]{ytics}[true]{}
\DTLyticstrue
\define@boolkey{dataplot}[DTL]{xminortics}[true]{}%
\ifDTLxminortics \DTLxticstrue\fi
\DTLxminorticsfalse
\define@boolkey{dataplot}[DTL]{yminortics}[true]{}%
\ifDTLyminortics \DTLyticstrue\fi
\DTLyminorticsfalse
\define@boolkey{dataplot}[DTL]{grid}[true]{}
\define@choickey{dataplot}{xticdir}[\val\nr]{in,out}{}%
\ifcase\nr\relax
\DTLxticsintrue
\or
\DTLxticsinfalse
\fi
}
\define@choickey{dataplot}{yticdir}[\val\nr]{in,out}{}%
\ifcase\nr\relax
\DTLyticsintrue
\or
\DTLyticsinfalse
\fi
}
\define@choickey{dataplot}{ticdir}[\val\nr]{in,out}{}%
\ifcase\nr\relax
\DTLxticsintrue
\DTLyticsintrue
\or
\DTLxticsinfalse
\DTLyticsinfalse
\fi

```

```

}
\define@key{dataplot}{bounds}{%
\def\dtl@bounds{#1}}
\let\dtl@bounds=\relax
\define@key{dataplot}{minx}{%
\def\dtl@minx{#1}}
\let\dtl@minx=\relax
\define@key{dataplot}{maxx}{%
\def\dtl@maxx{#1}}
\let\dtl@maxx=\relax
\define@key{dataplot}{miny}{%
\def\dtl@miny{#1}}
\let\dtl@miny=\relax
\define@key{dataplot}{maxy}{%
\def\dtl@maxy{#1}}
\let\dtl@maxy=\relax
\define@key{dataplot}{xticpoints}{%
\def\dtl@xticlist{#1}\DTLxticstrue\DTLxaxistrue}
\let\dtl@xticlist=\relax
\define@key{dataplot}{yticpoints}{%
\def\dtl@yticlist{#1}\DTLyticstrue\DTLyaxistrue}
\let\dtl@yticlist=\relax
\define@key{dataplot}{xticgap}{\def\dtl@xticgap{#1}%
\DTLxticstrue\DTLxaxistrue}
\let\dtl@xticgap=\relax
\define@key{dataplot}{yticgap}{\def\dtl@yticgap{#1}%
\DTLyticstrue\DTLyaxistrue}
\let\dtl@yticgap=\relax
\define@key{dataplot}{xticlabels}{%
\def\dtl@xticlabels{#1}\DTLxticstrue\DTLxaxistrue}
\let\dtl@xticlabels=\relax
\define@key{dataplot}{yticlabels}{%
\def\dtl@yticlabels{#1}\DTLyticstrue\DTLyaxistrue}
\let\dtl@yticlabels=\relax
\define@key{dataplot}{xlabel}{%
\def\dtl@xlabel{#1}}
\let\dtl@xlabel=\relax
\define@key{dataplot}{ylabel}{%
\def\dtl@ylabel{#1}}
\let\dtl@ylabel=\relax
\define@choicekey{dataplot}{legend}[\val\nr]{none,north,northeast,%
east,southeast,south,southwest,west,northwest}[northeast]{%
\dtl@legendsetting=\nr\relax
}
\define@key{dataplot}{legendlabels}{\def\dtl@legendlabels{#1}}
\newcommand*\DTLplot[3][\boolean{true}]{%
\bgroup
\let\dtl@xkey=\relax
\let\dtl@ykey=\relax
\let\dtl@legendlabels=\relax

```

```

\setkeys{dataplot}{#3}%
\let\dtl@plotmarklist=\DTLplotmarks
\let\dtl@plotlinelist=\DTLplotlines
\let\dtl@plotmarkcolorlist=\DTLplotmarkcolors
\let\dtl@plotlinecolorlist=\DTLplotlinecolors
\def\dtl@legend{ }%
\ifx\dtl@legendlabels\relax
  \edef\dtl@legendlabels{#2}%
\fi
\ifx\dtl@xkey\relax
  \PackageError{dataplot}{Missing x setting for
    \string\DTLplot}{ }%
\else
  \ifx\dtl@ykey\relax
    \PackageError{dataplot}{Missing y setting for
      \string\DTLplot}{ }%
  \else
    \ifx\dtl@bounds\relax
      \DTLcomputebounds[#1]{#2}{\dtl@xkey}{\dtl@ykey}
        {\DTLminX}{\DTLminY}{\DTLmaxX}{\DTLmaxY}%
      \ifx\dtl@minx\relax
        \else
          \let\DTLminX=\dtl@minx
        \fi
      \ifx\dtl@maxx\relax
        \else
          \let\DTLmaxX=\dtl@maxx
        \fi
      \ifx\dtl@miny\relax
        \else
          \let\DTLminY=\dtl@miny
        \fi
      \ifx\dtl@maxy\relax
        \else
          \let\DTLmaxY=\dtl@maxy
        \fi
    \else
      \expandafter\dtl@getbounds\dtl@bounds\@nil
    \fi
    \@dtl@tmpcount=\DTLplotwidth
    \divide\@dtl@tmpcount by 65536\relax
    \dtlsub{\dtl@dx}{\DTLmaxX}{\DTLminX}%
    \dtldiv{\dtl@scale@x}{\number\@dtl@tmpcount}{\dtl@dx}%
    \dtlmlul{\dtl@offset@x}{-\dtl@scale@x}{\DTLminX}%
    \@dtl@tmpcount=\DTLplotheight
    \divide\@dtl@tmpcount by 65536\relax
    \dtlsub{\dtl@dy}{\DTLmaxY}{\DTLminY}%
    \dtldiv{\dtl@scale@y}{\number\@dtl@tmpcount}{\dtl@dy}%
    \dtlmlul{\dtl@offset@y}{-\dtl@scale@y}{\DTLminY}%
  \ifDTLxtics

```

```

\ifx\dtl@xticlist\relax
  \ifx\dtl@xticgap\relax
    \dtlsub{\dtl@mingap}{\number\DTLmintickgap}{\dtl@offset@x}%
    \dtldiv{\dtl@mingap}{\dtl@mingap}{\dtl@scale@x}%
    \dtldiv{\dtl@mingap}{\dtl@mingap}{65536}%
    \dtl@constructticklist\DTLminX\DTLmaxX
    \dtl@mingap\dtl@xticlist
  \else
    \DTLifFPopenbetween{0}{\DTLminX}{\DTLmaxX}{%
      \dtl@constructticklistwithgapz
      \DTLminX\DTLmaxX\dtl@xticlist\dtl@xticgap}{%
      \dtl@constructticklistwithgap
      \DTLminX\DTLmaxX\dtl@xticlist\dtl@xticgap}%
    \fi
  \fi
\let\dtl@xminorticlist\@empty
\ifDTLxminortics
  \let\dtl@prevtick=\relax
  \@for\dtl@nexttick:=\dtl@xticlist\do{%
    \ifx\dtl@prevtick\relax
      \else
        \dtl@constructminorticklist
        \dtl@prevtick\dtl@nexttick\dtl@scale@x\dtl@xminorticlist
      \fi
      \let\dtl@prevtick=\dtl@nexttick
    }%
  \fi
\ifx\dtl@xticlabels\relax
  \settoheight{\dtl@xticlabelheight}{\dtl@xticlist}%
\else
  \settoheight{\dtl@xticlabelheight}{\dtl@xticlabels}%
\fi
\else
  \setlength{\dtl@xticlabelheight}{0pt}%
\fi
\setlength{\dtl@yticlabelwidth}{0pt}%
\ifDTLytics
  \ifx\dtl@yticlist\relax
    \ifx\dtl@yticgap\relax
      \dtlsub{\dtl@mingap}{\number\DTLmintickgap}{\dtl@offset@y}%
      \dtldiv{\dtl@mingap}{\dtl@mingap}{\dtl@scale@y}%
      \dtldiv{\dtl@mingap}{\dtl@mingap}{65536}%
      \dtl@constructticklist\DTLminY\DTLmaxY
      \dtl@mingap\dtl@yticlist
    \else
      \DTLifFPopenbetween{0}{\DTLminY}{\DTLmaxY}{%
        \dtl@constructticklistwithgapz
        \DTLminY\DTLmaxY\dtl@yticlist\dtl@yticgap}{%
        \dtl@constructticklistwithgap
        \DTLminY\DTLmaxY\dtl@yticlist\dtl@yticgap}%
      \fi
    \fi
  \fi

```

```

\fi
\fi
\let\dtl@yminorticlist\@empty
\ifDTLyminortics
\let\dtl@prevtick=\relax
\@for\dtl@nexttick:=\dtl@yticlist\do{%
\ifx\dtl@prevtick\relax
\else
\dtl@constructminorticklist
\dtl@prevtick\dtl@nexttick\dtl@scale@y\dtl@yminorticlist
\fi
\let\dtl@prevtick=\dtl@nexttick
}%
\fi
\ifx\dtl@ylabel\relax
\else
\ifx\dtl@yticlabels\relax
\@for\dtl@thislabel:=\dtl@yticlist\do{%
\dtl@round{\dtl@thislabel}{\dtl@thislabel}
{\c@DTLplotroundYvar}%
\settowidth{\dtl@tmplength}{\dtl@thislabel}%
\ifdim\dtl@tmplength>\dtl@yticlabelwidth
\setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
\fi
}%
\else
\@for\dtl@thislabel:=\dtl@yticlabels\do{%
\settowidth{\dtl@tmplength}{\dtl@thislabel}%
\ifdim\dtl@tmplength>\dtl@yticlabelwidth
\setlength{\dtl@yticlabelwidth}{\dtl@tmplength}%
\fi
}%
\fi
\fi
\fi
\begin{tikzpicture}
\pgfsetxvec{\pgfpoint{1pt}{0pt}}%
\pgfsetyvec{\pgfpoint{0pt}{1pt}}%
\begin{scope}
\pgftransformcm{\dtl@scale@x}{0}{0}{\dtl@scale@y}%
{\pgfpoint{\dtl@offset@x pt}{\dtl@offset@y pt}}%
\let\dtl@lothandlermark\@dtl@lothandlermark
\DTLplotatbegintikz
\ifDTLbox
\draw (\DTLminX,\DTLminY) -- (\DTLmaxX,\DTLminY) --
(\DTLmaxX,\DTLmaxY) -- (\DTLminX,\DTLmaxY) --
cycle;
\else
\ifDTLxaxis
\expandafter\draw\expandafter[\DTLXAxisStyle]

```

```

        (\DTLminX,\DTLminY) -- (\DTLmaxX,\DTLminY);
\fi
\ifDTLyaxis
  \expandafter\draw\expandafter[\DTLYAxisStyle]
    (\DTLminX,\DTLminY) -- (\DTLminX,\DTLmaxY);
\fi
\fi
\ifDTLgrid
  \ifDTLxminortics
    \@for\dtl@thistick:=\dtl@xminorticlist\do{%
      \expandafter\draw\expandafter[\DTLminorgridstyle]
        (\dtl@thistick,\DTLminY) -- (\dtl@thistick,\DTLmaxY);
    }%
  \fi
  \ifDTLyminortics
    \@for\dtl@thistick:=\dtl@yminorticlist\do{%
      \expandafter\draw\expandafter[\DTLminorgridstyle]
        (\DTLminX,\dtl@thistick) -- (\DTLmaxX,\dtl@thistick);
    }%
  \fi
  \@for\dtl@thistick:=\dtl@xticlist\do{%
    \expandafter\draw\expandafter[\DTLmajorgridstyle]
      (\dtl@thistick,\DTLminY) -- (\dtl@thistick,\DTLmaxY);
  }%
  \@for\dtl@thistick:=\dtl@yticlist\do{%
    \expandafter\draw\expandafter[\DTLmajorgridstyle]
      (\DTLminX,\dtl@thistick) -- (\DTLmaxX,\dtl@thistick);
  }%
\fi
\ifDTLxtics
  \dtlsub{\dtl@ticklength}{\number\DTLticklength}{-\dtl@offset@y}%
  \dtldiv{\dtl@ticklength}{\dtl@ticklength}{\dtl@scale@y}%
  \dtldiv{\dtl@ticklength}{\dtl@ticklength}{65536}%
  \addtolength\dtl@xticlabelheight{\DTLticklabeloffset}%
  \dtlsub{\dtl@ticlabeloffset}{\number\dtl@xticlabelheight}{-
\dtl@offset@y}%
  \dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{\dtl@scale@y}%
  \dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{65536}%
  \@for\dtl@thistick:=\dtl@xticlist\do{%
    \let\dtl@thisticklabel\dtl@thistick
    \ifx\dtl@xticlabels\relax
      \dtlround{\dtl@thislabel}{\dtl@thistick}
      {\c@DTLplotroundXvar}%
    \else
      \dtl@chopfirst\dtl@xticlabels\dtl@thislabel\dtl@rest
      \let\dtl@xticlabels=\dtl@rest
    \fi
  \fi
  \ifDTLxticsin
    \draw (\dtl@thistick,\DTLminY) -- ++(0,\dtl@ticklength);
    \draw (\dtl@thistick,\DTLminY)

```

```

        ++ (0, -\dtl@ticlabeloffset) node {\dtl@thislabel};
\else
  \draw (\dtl@thistick, \DTLminY) -- ++(0, -\dtl@ticklength)
    ++ (0, -\dtl@ticlabeloffset) node {\dtl@thislabel};
\fi
\ifDTLbox
  \ifDTLxticsin
    \draw (\dtl@thistick, \DTLmaxY) -- ++(0, -\dtl@ticklength);
  \else
    \draw (\dtl@thistick, \DTLmaxY) -- ++(0, \dtl@ticklength);
  \fi
\fi
}%
\fi
\ifx\dtl@xlabel\relax
\else
  \dtladd{\dtl@x}{\number\baselineskip}{\dtl@offset@y}%
  \dtldiv{\dtl@x}{\dtl@x}{\dtl@scale@y}%
  \dtldiv{\dtl@x}{\dtl@x}{65536}%
  \dtladd{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{\dtl@x}%
  \dtlml{\dtl@x}{\dtl@dx}{0.5}%
  \draw (\DTLminX, \DTLminY) ++(\dtl@x, -\dtl@ticlabeloffset)
    node[anchor=north] {\dtl@xlabel};
\fi
\ifDTLxminortics
  \dtlsub{\dtl@ticklength}{\number\DTLminorticklength}{-
\dtl@offset@y}%
  \dtldiv{\dtl@ticklength}{\dtl@ticklength}{\dtl@scale@y}%
  \dtldiv{\dtl@ticklength}{\dtl@ticklength}{65536}%
  \@for\dtl@thistick:=\dtl@xminorticlist\do{%
    \ifDTLxticsin
      \draw (\dtl@thistick, \DTLminY) -- ++(0, \dtl@ticklength);
      \draw (\dtl@thistick, \DTLminY)
        ++ (0, -\dtl@ticlabeloffset) node[anchor=north] {\dtl@thislabel};
    \else
      \draw (\dtl@thistick, \DTLminY) -- ++(0, -\dtl@ticklength)
        ++ (0, -\dtl@ticlabeloffset) node[anchor=north] {\dtl@thislabel};
    \fi
  }
\ifDTLbox
  \ifDTLxticsin
    \draw (\dtl@thistick, \DTLmaxY) -- ++(0, -\dtl@ticklength);
  \else
    \draw (\dtl@thistick, \DTLmaxY) -- ++(0, \dtl@ticklength);
  \fi
\fi
}%
\fi
\ifDTLytics
  \dtlsub{\dtl@ticklength}{\number\DTLticklength}{-\dtl@offset@x}%
  \dtldiv{\dtl@ticklength}{\dtl@ticklength}{\dtl@scale@x}%

```

```

\dtldiv{\dtl@ticklength}{\dtl@ticklength}{65536}%
\dtladd{\dtl@ticlabeloffset}{\number\DTLticlabeloffset}{0}%
\dtlsub{\dtl@ticlabeloffset}{\number\DTLticlabeloffset}{-
\dtl@offset@x}%
\dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{\dtl@scale@x}%
\dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{65536}%
\@for\dtl@thistick:=\dtl@yticlist\do{%
\let\dtl@thisticklabel\dtl@thistick
\ifx\dtl@yticlabels\relax
\dtlround{\dtl@thislabel}{\dtl@thistick}
{\c@DTLplotroundXvar}%
\else
\dtl@chopfirst\dtl@yticlabels\dtl@thislabel\dtl@rest
\let\dtl@yticlabels=\dtl@rest
\fi
\ifDTLyticsin
\draw (\DTLminX,\dtl@thistick) -- ++(\dtl@ticklength,0);
\draw (\DTLminX,\dtl@thistick)
++ (-\dtl@ticlabeloffset,0) node[anchor=east] {\dtl@thislabel};
\else
\draw (\DTLminX,\dtl@thistick) -- ++(-\dtl@ticklength,0)
++ (-\dtl@ticlabeloffset,0) node[anchor=east] {\dtl@thislabel};
\fi
\ifDTLbox
\ifDTLyticsin
\draw (\DTLmaxX,\dtl@thistick) -- ++(-\dtl@ticklength,0);
\else
\draw (\DTLmaxX,\dtl@thistick) -- ++(\dtl@ticklength,0);
\fi
\fi
}%
\fi
\ifx\dtl@ylabel\relax
\else
\setlength{\dtl@tmplength}{\baselineskip}%
\addtolength{\dtl@tmplength}{\dtl@yticlabelwidth}%
\addtolength{\dtl@tmplength}{\DTLticlabeloffset}%
\dtlsub{\dtl@ticlabeloffset}{\number\dtl@tmplength}{-\dtl@offset@x}%
\dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{\dtl@scale@x}%
\dtldiv{\dtl@ticlabeloffset}{\dtl@ticlabeloffset}{65536}%
\dtlmul{\dtl@y}{\dtl@dy}{0.5}%
\draw (\DTLminX,\DTLminY) ++(-\dtl@ticlabeloffset,\dtl@y)
node[rotate=90,anchor=south] {\dtl@ylabel};
\fi
\ifDTLyminortics
\dtlsub{\dtl@ticklength}{\number\DTLminorticklength}{-
\dtl@offset@x}%
\dtldiv{\dtl@ticklength}{\dtl@ticklength}{\dtl@scale@x}%
\dtldiv{\dtl@ticklength}{\dtl@ticklength}{65536}%
\@for\dtl@thistick:=\dtl@yminorticlist\do{%

```

```

\ifDTLyticsin
  \draw (\DTLminX,\dtl@thistick) -- ++(\dtl@ticklength,0);
\else
  \draw (\DTLminX,\dtl@thistick) -- ++(-\dtl@ticklength,0);
\fi
\ifDTLbox
  \ifDTLyticsin
    \draw (\DTLmaxX,\dtl@thistick) -- ++(-\dtl@ticklength,0);
  \else
    \draw (\DTLmaxX,\dtl@thistick) -- ++(\dtl@ticklength,0);
  \fi
\fi
}%
\fi
\end{scope}
\@for\dtl@thisdb:=#2\do{%
  \ifx\dtl@plotmarkcolorlist\@empty
    \let\dtl@plotmarkcolorlist=\DTLplotmarkcolors
  \fi
  \dtl@chopfirst\dtl@plotmarkcolorlist\dtl@thisplotmarkcolor
  \dtl@remainder
  \let\dtl@plotmarkcolorlist=\dtl@remainder
  \ifDTLshowmarkers
    \ifx\dtl@plotmarklist\@empty
      \let\dtl@plotmarklist=\DTLplotmarks
    \fi
    \dtl@chopfirst\dtl@plotmarklist\dtl@thisplotmark
    \dtl@remainder
    \let\dtl@plotmarklist=\dtl@remainder
    \ifx\dtl@thisplotmark\relax
      \let\dtl@mark=\relax
    \else
      \expandafter\toks@\expandafter{\dtl@thisplotmark}%
      \ifx\dtl@thisplotmarkcolor\@empty
        \edef\dtl@mark{\the\toks@}%
      \else
        \edef\dtl@mark{%
          \noexpand\color{\dtl@thisplotmarkcolor}%
          \the\toks@}%
      \fi
    \fi
  \else
    \let\dtl@mark=\relax
  \fi
  \ifx\dtl@plotlinecolorlist\@empty
    \let\dtl@plotlinecolorlist=\DTLplotlinecolors
  \fi
  \dtl@chopfirst\dtl@plotlinecolorlist\dtl@thisplotlinecolor
  \dtl@remainder
  \let\dtl@plotlinecolorlist=\dtl@remainder

```

```

\ifDTLshowlines
  \ifx\dtl@plotlinelist\@empty
    \let\dtl@plotlinelist=\DTLplotlines
  \fi
  \dtl@chopfirst\dtl@plotlinelist\dtl@thisplotline
  \dtl@remainder
  \let\dtl@plotlinelist=\dtl@remainder
  \expandafter\ifx\dtl@thisplotline\relax
  \let\dtl@linestyle=\relax
\else
  \expandafter\toks@\expandafter{\dtl@thisplotline}%
  \ifx\dtl@thisplotlinecolor\@empty
    \edef\dtl@linestyle{\the\toks@}%
  \else
    \edef\dtl@linestyle{%
      \noexpand\color{\dtl@thisplotlinecolor}%
      \the\toks@}%
  \fi
\fi
\let\dtl@linestyle=\relax
\fi
\ifnum\dtl@legendsetting>0\relax
  \dtl@chopfirst\dtl@legendlabels\dtl@thislabel\dtl@rest
  \let\dtl@legendlabels=\dtl@rest
  \expandafter\toks@\expandafter{\dtl@mark}%
  \expandafter\@dtl@toks\expandafter{\dtl@linestyle}%
  \edef\dtl@addtolegend{\noexpand\DTLaddtoplotlegend
    {\the\toks@}{\the\@dtl@toks}{\dtl@thislabel}}%
  \dtl@addtolegend
\fi
\def\dtl@stream{\pgfplotstreamstart}%
\@sDTLforeach[#1]{\dtl@thisdb}{\dtl@x=\dtl@xkey,%
  \dtl@y=\dtl@ykey}{%
  \DTLconverttodecimal{\dtl@x}{\dtl@decx}%
  \DTLconverttodecimal{\dtl@y}{\dtl@decy}%
  \ifthenelse{%
    \DTLisclosedbetween{\dtl@x}{\DTLminX}{\DTLmaxX}%
    \and
    \DTLisclosedbetween{\dtl@y}{\DTLminY}{\DTLmaxY}}%
  {%
    \expandafter\toks@\expandafter{\dtl@stream}%
    \dtl@mul{\dtl@decx}{\dtl@decx}{\dtl@scale@x}%
    \dtl@add{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
    \dtl@round{\dtl@decx}{\dtl@decx}{1}%
    \dtl@mul{\dtl@decy}{\dtl@decy}{\dtl@scale@y}%
    \dtl@add{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
    \dtl@round{\dtl@decy}{\dtl@decy}{1}%
    \edef\dtl@stream{\the\toks@

```

```

\noexpand\pgfplotstreampoint
  {\noexpand\pgfpointxy{\dtl@decx}{\dtl@decy}}}%
}{}}%
}%
\expandafter\toks@\expandafter{\dtl@stream}%
\edef\dtl@stream{\the\toks@\noexpand\pgfplotstreamend}%
\ifx\dtl@linestyle\relax
\else
  \begin{scope}
    \dtl@linestyle
    \pgfplotshandlerlineto
    \dtl@stream
    \pgfusepath{stroke}
  \end{scope}
\fi
\ifx\dtl@mark\relax
\else
  \begin{scope}
    \pgfplotshandlermark{\dtl@mark}%
    \dtl@stream
    \pgfusepath{stroke}
  \end{scope}
\fi
}%
\ifcase\dtl@legendsetting
% none
\or % north
  \dtl mul{\dtl@decx}{\dtl@dx}{0.5}%
  \dtl ladd{\dtl@decx}{\DTLminX}{\dtl@decx}%
  \dtl mul{\dtl@decx}{\dtl@decx}{\dtl@scale@x}%
  \dtl ladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
  \dtl mul{\dtl@decy}{\DTLmaxY}{\dtl@scale@y}%
  \dtl ladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
  \draw (\dtl@decx,\dtl@decy) ++(0,-\DTLlegendyoffset)
    node[anchor=north]
    {\DTLformatlegend
     {\begin{tabular}{c l}\dtl@legend\end{tabular}}}%
  };
\or % north east
  \dtl mul{\dtl@decx}{\DTLmaxX}{\dtl@scale@x}%
  \dtl ladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
  \dtl mul{\dtl@decy}{\DTLmaxY}{\dtl@scale@y}%
  \dtl ladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
  \draw (\dtl@decx,\dtl@decy) ++(-\DTLlegendxoffset,-\DTLlegendyoffset)
    node[anchor=north east]
    {\DTLformatlegend
     {\begin{tabular}{c l}\dtl@legend\end{tabular}}}%
  };
\or % east
  \dtl mul{\dtl@decy}{\dtl@dy}{0.5}%

```

```

\dtladd{\dtl@decy}{\DTLminY}{\dtl@decy}%
\dtlmlul{\dtl@decy}{\dtl@decy}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\dtlmlul{\dtl@decx}{\DTLmaxX}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\draw (\dtl@decx,\dtl@decy) ++(-\DTLlegendxoffset,0)
  node[anchor=east]
  {\DTLformatlegend
  {\begin{tabular}{c}\dtl@legend\end{tabular}}}%
};
\or % south east
\dtlmlul{\dtl@decx}{\DTLmaxX}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\dtlmlul{\dtl@decy}{\DTLminY}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\draw (\dtl@decx,\dtl@decy) ++(-\DTLlegendxoffset,\DTLlegendyoffset)
  node[anchor=south east]
  {\DTLformatlegend
  {\begin{tabular}{c}\dtl@legend\end{tabular}}}%
};
\or % south
\dtlmlul{\dtl@decx}{\dtl@dx}{0.5}%
\dtladd{\dtl@decx}{\DTLminX}{\dtl@decx}%
\dtlmlul{\dtl@decx}{\dtl@decx}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\dtlmlul{\dtl@decy}{\DTLminY}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\draw (\dtl@decx,\dtl@decy) ++(0,\DTLlegendyoffset)
  node[anchor=south]
  {\DTLformatlegend
  {\begin{tabular}{c}\dtl@legend\end{tabular}}}%
};
\or % south west
\dtlmlul{\dtl@decx}{\DTLminX}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\dtlmlul{\dtl@decy}{\DTLminY}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\draw (\dtl@decx,\dtl@decy) ++(\DTLlegendxoffset,\DTLlegendyoffset)
  node[anchor=south west]
  {\DTLformatlegend
  {\begin{tabular}{c}\dtl@legend\end{tabular}}}%
};
\or % west
\dtlmlul{\dtl@decy}{\dtl@dy}{0.5}%
\dtladd{\dtl@decy}{\DTLminY}{\dtl@decy}%
\dtlmlul{\dtl@decy}{\dtl@decy}{\dtl@scale@y}%
\dtladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\dtlmlul{\dtl@decx}{\DTLminX}{\dtl@scale@x}%
\dtladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\draw (\dtl@decx,\dtl@decy) ++(\DTLlegendxoffset,0)

```

```

        node[anchor=west]
        {\DTLformatlegend
        {\begin{tabular}{cl}\dtl@legend\end{tabular}}}%
    };
\or % north west
\dtl mul{\dtl@decx}{\DTLminX}{\dtl@scale@x}%
\dtl ladd{\dtl@decx}{\dtl@decx}{\dtl@offset@x}%
\dtl mul{\dtl@decy}{\DTLmaxY}{\dtl@scale@y}%
\dtl ladd{\dtl@decy}{\dtl@decy}{\dtl@offset@y}%
\draw (\dtl@decx,\dtl@decy) ++(\DTLlegendxoffset,-\DTLlegandyoffset)
node[anchor=north west]
{\DTLformatlegend
{\begin{tabular}{cl}\dtl@legend\end{tabular}}}%
};
\fi
\pgftransformcm{\dtl@scale@x}{0}{0}{\dtl@scale@y}%
{\pgfpoint{\dtl@offset@x pt}{\dtl@offset@y pt}}%
\let\dtlplotahandlermark\dtlplotahandlermark
\DTLplotatendtikz
\end{tikzpicture}
\fi
\fi
\egroup
}
\def\dtl@getbounds#1,#2,#3,#4@nil{%
\def\DTLminX{#1}%
\def\DTLminY{#2}%
\def\DTLmaxX{#3}%
\def\DTLmaxY{#4}%
\dtl ifnumgt{\DTLminX}{\DTLmaxX}
{%
\PackageError{dataplot}{Min X > Max X in bounds #1,#2,#3,#4}{%
The bounds must be specified as minX,minY,maxX,maxY}%
}}%
\dtl ifnumgt{\DTLminY}{\DTLmaxY}
{%
\PackageError{dataplot}{Min Y > Max Y in bounds #1,#2,#3,#4}{%
The bounds must be specified as minX,minY,maxX,maxY}%
}}%
}
\newcommand*{\dtl@constructticklist}[4]{%
\DTLifFPopenbetween{0}{#1}{#2}%
{%
\dtl sub{\@dtl@width}{0}{#1}%
\dtl div{\@dtl@neggap}{\@dtl@width}{10}%
\dtl ifnumlt{\@dtl@neggap}{#3}%
{%
\edef\@dtl@neggap{#3}%
}%
}%
}%
}

```

```

\dtldiv{\@dtl@posgap}{#2}{10}%
\dtlifnumlt{\@dtl@posgap}{#3}%
{%
  \edef\@dtl@posgap{#3}%
}%
{}%
\dtlmax{\@dtl@gap}{\@dtl@neggap}{\@dtl@posgap}%
\dtlifnumgt{\@dtl@gap}{\@dtl@width}%
{}%
{%
  \dtl@constructticklistwithgapz{#1}{#2}{#4}{\@dtl@gap}%
}%
{}%
\dtlsub{\@dtl@width}{#2}{#1}%
\dtldiv{\@dtl@gap}{\@dtl@width}{10}%
\dtlifnumlt{\@dtl@gap}{#3}%
{%
  \dtlifnumgt{#3}{\@dtl@width}%
  {%
    \def#4{#1,#2}%
  }%
  {}%
  \dtl@constructticklistwithgap{#1}{#2}{#4}{#3}%
}
}%
{}%
\dtl@constructticklistwithgap{#1}{#2}{#4}{\@dtl@gap}%
}%
}
\newcommand*\@dtl@constructticklistwithgap[4]{%
\edef\@dtl@thistick{#1}%
\edef#3{#1}%
\dtladd{\@dtl@thistick}{\@dtl@thistick}{#4}%
\whiledo{\DTLisFPopenbetween{\@dtl@thistick}{#1}{#2}}{%
  \expandafter\toks@\expandafter{\@dtl@thistick}%
  \edef#3{#3,\the\toks@}%
  \dtladd{\@dtl@thistick}{\@dtl@thistick}{#4}%
}%
\expandafter\toks@\expandafter{#2}%
\edef#3{#3,\the\toks@}%
}
\newcommand*\@dtl@constructticklistwithgapz[4]{%
\edef\@dtl@thistick{0}%
\edef#3{0}%
\dtladd{\@dtl@thistick}{\@dtl@thistick}{#4}%
\whiledo{\DTLisFPopenbetween{\@dtl@thistick}{0}{#2}}{%
  {}%
  \expandafter\toks@\expandafter{\@dtl@thistick}%
}

```

```

\edef#3{#3,\the\toks@}%
\dtladd{\@dtl@thistick}{\@dtl@thistick}{#4}%
}%
\expandafter\toks@\expandafter{#2}%
\edef#3{#3,\the\toks@}%
\dtlifnumeq{#1}{0}%
}%
{%
\edef\@dtl@thistick{0}%
\dtlsub{\@dtl@thistick}{\@dtl@thistick}{#4}%
\whiledo{\DTLisFPopenbetween{\@dtl@thistick}{#1}{0}}%
{%
\expandafter\toks@\expandafter{\@dtl@thistick}%
\edef#3{\the\toks@,#3}%
\dtlsub{\@dtl@thistick}{\@dtl@thistick}{#4}%
}%
\expandafter\toks@\expandafter{#1}%
\edef#3{\the\toks@,#3}%
}%
}
}
\newcommand*{\dtl@constructminorticklist}[4]{%
\dtlsub{\@dtl@width}{#2}{#1}%
\dtlmlul{\@dtl@width}{\@dtl@width}{#3}%
\dtldiv{\@dtl@gap}{\@dtl@width}{10}%
\setlength\dtl@tmplength{\@dtl@gap sp}%
\ifdim\dtl@tmplength<\DTLminminortickgap
\dtldiv{\@dtl@gap}{\@dtl@width}{4}%
\setlength\dtl@tmplength{\@dtl@gap sp}%
\ifdim\dtl@tmplength<\DTLminminortickgap
\dtldiv{\@dtl@gap}{\@dtl@width}{2}%
\setlength\dtl@tmplength{\@dtl@gap sp}%
\ifdim\dtl@tmplength<\DTLminminortickgap
\let\@dtl@gap=\@dtl@width
\fi
\fi
\fi
\dtldiv{\@dtl@gap}{\@dtl@gap}{#3}%
\dtl@constructticklistwithgapex{#1}{#2}{\dtl@tmp}{\@dtl@gap}%
\ifx#4\@empty
\let#4=\dtl@tmp
\else
\expandafter\toks@\expandafter{#4}%
\edef#4{#4,\dtl@tmp}%
\fi
}
}
\newcommand*{\dtl@constructticklistwithgapex}[4]{%
\edef\@dtl@thistick{#1}%
\let#3=\@empty
\dtladd{\@dtl@thistick}{\@dtl@thistick}{#4}%
\whiledo{\DTLisFPopenbetween{\@dtl@thistick}{#1}{#2}}{%

```

```

\expandafter\toks@\expandafter{\@dtl@thistick}%
\ifx#3\@empty
  \edef#3{\the\toks@}%
\else
  \edef#3{#3,\the\toks@}%
\fi
\dtladd{\@dtl@thistick}{\@dtl@thistick}{#4}%
}%
}
\newcommand*\DTLaddtoplotlegend}[3]{%
\def\dtl@legendline{}%
\ifx\relax#2\relax
\else
  \toks@{#2%
  \pgfpathmoveto{\pgfpoint{-10pt}{0pt}}%
  \pgfpathlineto{\pgfpoint{10pt}{0pt}}%
  \pgfusepath{stroke}}%
  \edef\dtl@legendline{\the\toks@}%
\fi
\ifx\relax#1\relax
\else
  \toks@{#1}%
  \expandafter\@dtl@toks\expandafter{\dtl@legendline}%
  \edef\dtl@legendline{\the\@dtl@toks\the\toks@}%
\fi
\expandafter\toks@\expandafter{\dtl@legendline}%
\ifx\dtl@legend\@empty
  \xdef\dtl@legend{\noexpand\tikz\the\toks@; \noexpand& #3}%
\else
  \expandafter\@dtl@toks\expandafter{\dtl@legend}%
  \xdef\dtl@legend{\the\@dtl@toks\noexpand\\%
  \noexpand\tikz\the\toks@; \noexpand& #3}%
\fi
}

```

30.15 Rollback v2.32 (datatool-2019-09-27.sty)

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datatool}[2019/09/27 v2.32 (NLCT)]
\RequirePackage{xkeyval}
\RequirePackage{ifthen}
\RequirePackage{xfor}
\RequirePackage{substr}
\RequirePackage{etoolbox}
\newcommand*\@dtl@separator}{,}
\newcommand*\DTLsetseparator}[1]{%
  \renewcommand*\@dtl@separator}{#1}%
  \@dtl@construct@lopoffs
}
\begingroup

```

```

\catcode`\^^I12
\gdef\DTLsettabseparator{%
  \catcode`\^^I12
  \DTLsetseparator{^^I}%
}
\gdef\DTLmaketabspace{%
  \catcode`\^^I10\relax
}
\endgroup
\begingroup
\catcode`\"12\relax
\gdef\@dtl@delimiter{"}
\endgroup
\newcommand*\DTLsetdelimiter[1]{%
  \renewcommand*\@dtl@delimiter}{#1}%
  \@dtl@construct@lopoffs
}
\edef\@dtl@construct@lopoff#1#2{%
  \noexpand\long
  \noexpand\def\noexpand\@dtl@lopoff#1##1##2\noexpand\to##3##4{%
    \noexpand\ifx##1\noexpand\relax
      \noexpand\ifstrempy{##1}%
        {\noexpand\@dtl@qlopoff#1}{##2\noexpand\to##3##4\relax}%
        {%
          \noexpand\dtl@ifsingle{##1}%
          {\noexpand\@dtl@qlopoff#1##1##2\noexpand\to##3##4\relax}%
          {\noexpand\@dtl@qlopoff#1{##1}##2\noexpand\to##3##4\relax}%
        }%
      \noexpand\else
        \noexpand\ifstrempy{##1}%
        {\noexpand\@dtl@lop@ff#1}{##2\noexpand\to##3##4\relax}%
        {%
          \noexpand\dtl@ifsingle{##1}%
          {\noexpand\@dtl@lop@ff#1##1##2\noexpand\to##3##4\relax}%
          {\noexpand\@dtl@lop@ff#1{##1}##2\noexpand\to##3##4\relax}%
        }%
      \noexpand\fi
    }%
  }
}
\edef\@dtl@construct@qlopoff#1#2{%
  \noexpand\long
  \noexpand\def\noexpand\@dtl@qlopoff#1#2##1#2##1##2\noexpand\to##3##4{%
    \noexpand\def##4{##1}%
    \noexpand\DTLsubstituteall{##4}{#2#2}{#2}%
    \noexpand\edef\noexpand\@dtl@dossubs{%
      \noexpand\noexpand\noexpand\DTLsubstituteall{\noexpand\noexpand##4}%
      {\noexpand\expandafter\noexpand\noexpand\noexpand\cename#2\noexpand\endcename#2}%
      {\noexpand\expandafter\noexpand\noexpand\noexpand\cename#2\noexpand\endcename}%
    }%
    \noexpand\@dtl@dossubs
  }
}

```

```

        \noexpand\def##3{#1##2}%
    }%
}
\edef\@dtl@construct@lop@ff#1{%
    \noexpand\long
        \noexpand\def\noexpand\@dtl@lop@ff#1##1#1##2\noexpand\to##3##4{%
            \noexpand\def##4{##1}%
            \noexpand\def##3{#1##2}%
        }%
    }
}
\newcommand{\@dtl@construct@lopoffs}{%
    \edef\@dtl@chars{\@dtl@separator}\@dtl@delimiter}}%
    \expandafter\@dtl@construct@lopoff\@dtl@chars
    \expandafter\@dtl@construct@qlopoff\@dtl@chars
    \expandafter\@dtl@construct@lop@ff\expandafter{\@dtl@separator}%
}
\define@key{datatool.sty}{separator}{%
    \DTLsetseparator{#1}%
}
\define@key{datatool.sty}{delimiter}{%
    \DTLsetdelimiter{#1}%
}
\define@boolkey{datatool.sty}[dtl]{verbose}[true]{}
\define@choicekey{datatool.sty}{math}[\val\nr]{fp,pgfmath}{%
    \renewcommand*\@dtl@mathprocessor{#1}%
}
\providecommand*\@dtl@mathprocessor{fp}
\newcommand*\@dtl@set@options{}
\define@choicekey{datatool.sty}{utf8}{true,false}[true]{%
    \renewcommand*\@dtl@set@options{\setbool{\@dtl@utf8}{#1}}%
}
\ProcessOptionsX
\@dtl@construct@lopoffs
\RequirePackage{datatool-base}[v2.32]
\@dtl@set@options
\DeclareRobustCommand{\DTLpar}{\par}
\newcommand*\@DTLnewdb[1]{%
    \DTLifdbexists{#1}%
    {%
        \PackageError{datatool}{Database `#1' already exists}{}%
    }%
    {%
        \dtl@message{Creating database `#1'}%
        \expandafter\newtoks\csname dtldb@#1\endcsname
        \expandafter\newtoks\csname dtlkeys@#1\endcsname{}%
        \expandafter\newcount\csname dtlrows@#1\endcsname
        \expandafter\newcount\csname dtlcols@#1\endcsname
    }%
}
\newcommand*\@DTLcleardb[1]{%

```

```

\DTLifdbexists{#1}%
{%
  \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
  {%
    \expandafter\let\csname dtl@ci@#1@\@dtl@key\endcsname\undefined
  }%
  \csname dtldb@#1\endcsname{ }%
  \csname dtlkeys@#1\endcsname{ }%
  \csname dtlrows@#1\endcsname=0\relax
  \csname dtlcols@#1\endcsname=0\relax
}%
{%
  \PackageError{Can't clear database `#1':
    database doesn't exist}{ }{ }%
}%
}
\newcommand*\DTLdeletedb}[1]{%
  \DTLifdbexists{#1}%
  {%
    \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
    {%
      \expandafter\let\csname dtl@ci@#1@\@dtl@key\endcsname\undefined
    }%
    \expandafter\let\csname dtldb@#1\endcsname\undefined
    \expandafter\let\csname dtlkeys@#1\endcsname\undefined
    \expandafter\let\csname dtlrows@#1\endcsname\undefined
    \expandafter\let\csname dtlcols@#1\endcsname\undefined
  }%
  {%
    \PackageError{Can't delete database `#1':
      database doesn't exist}{ }{ }%
  }%
}%
}
\newcommand*\DTLgnewdb}[1]{%
  \DTLifdbexists{#1}%
  {%
    \PackageError{datatool}{Database `#1' already exists}{ }%
  }%
  {%
    \dtl@message{Creating database `#1'}%
    \expandafter\global\expandafter\newtoks\csname dtldb@#1\endcsname
    \expandafter\global\expandafter\newtoks\csname dtlkeys@#1\endcsname{ }%
    \expandafter\global\expandafter\newcount\csname dtlrows@#1\endcsname
    \expandafter\global\expandafter\newcount\csname dtlcols@#1\endcsname
  }%
}%
}
\newcommand*\DTLgdeletedb}[1]{%
  \DTLifdbexists{#1}%
  {%
    \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do

```

```

    {%
      \expandafter\global\expandafter\let\csname dtl@ci@#1@\@dtl@key\endcsname\undefined
    }%
    \expandafter\global\expandafter\let\csname dtldb@#1\endcsname\undefined
    \expandafter\global\expandafter\let\csname dtlkeys@#1\endcsname\undefined
    \expandafter\global\expandafter\let\csname dtlrows@#1\endcsname\undefined
    \expandafter\global\expandafter\let\csname dtlcols@#1\endcsname\undefined
  }%
  {%
    \PackageError{Can't delete database `#1':
      database doesn't exist}{}}{%
  }%
}
\newcommand*\DTLgcleardb}[1]{%
  \DTLifdbexists{#1}%
  {%
    \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
    {%
      \expandafter\global\expandafter\let\csname dtl@ci@#1@\@dtl@key\endcsname\undefined
    }%
    \expandafter\global\csname dtldb@#1\endcsname{}%
    \expandafter\global\csname dtlkeys@#1\endcsname{}%
    \expandafter\global\csname dtlrows@#1\endcsname=0\relax
    \expandafter\global\csname dtlcols@#1\endcsname=0\relax
  }%
  {%
    \PackageError{Can't clear database `#1':
      database doesn't exist}{}}{%
  }%
}
\newcommand*\DTLrowcount}[1]{%
  \expandafter\number\csname dtlrows@#1\endcsname
}
\newcommand*\DTLcolumncount}[1]{%
  \expandafter\number\csname dtlcols@#1\endcsname
}
\newcommand{\DTLifdbempty}[3]{%
  \DTLifdbexists{#1}%
  {\@DTLifdbempty{#1}{#2}{#3}}%
  {\PackageError{Can't check if database `#1' is empty:
    database doesn't exist}{}}}%
}
\newcommand{\@DTLifdbempty}[3]{%
  \expandafter\ifnum\csname dtlrows@#1\endcsname=0\relax
  #2%
  \else
  #3%
  \fi
}
\newcommand*\DTLnewrow}{%

```

```

    \@ifstar\@sDTLnewrow\@DTLnewrow
  }
  \newcommand*\@DTLnewrow}[1]{%
\DTLifdbexists{#1}%
  {\@sDTLnewrow{#1}}%
  {\PackageError{datatool}{Can't add new row to database `#1':
    database doesn't exist}{}}%
  }
  \newcommand*\@sDTLnewrow}[1]{%
    \global\advance\csname dtlrows@#1\endcsname by 1\relax
    \@dtl@toks@gput@right@cx{dtldb@#1}{%
      \noexpand\db@row@elt@w%
        \noexpand\db@row@id@w \number\csname dtlrows@#1\endcsname
        \noexpand\db@row@id@end@%
        \noexpand\db@row@id@w \number\csname dtlrows@#1\endcsname
        \noexpand\db@row@id@end@%
        \noexpand\db@row@elt@end@%
      }%
    \@dtl@message{New row added to database `#1'}%
  }
  \newcount\dtlcolumnnum
  \newcount\dtlrownum
  \newcommand*\@DTLifhaskey{\@ifstar\@sDTLifhaskey\@DTLifhaskey}
  \newcommand{\@DTLifhaskey}[4]{%
    \DTLifdbexists{#1}%
    {%
      \@sDTLifhaskey{#1}{#2}{#3}{#4}%
    }%
    {%
      \PackageError{datatool}{Database `#1' doesn't exist}{}}%
  }%
  }
  \newcommand{\@sDTLifhaskey}[4]{%
    \@ifundefined{dtl@ci@#1@#2}%
    {%
      #4%
    }%
    {%
      #3%
    }%
  }%
  }
  \newcommand*\@DTLgetcolumnindex{%
    \@ifstar\@sdtl@getcolumnindex\@dtl@getcolumnindex
  }
  \newcommand*\@dtl@getcolumnindex}[3]{%
    \DTLifdbexists{#2}%
    {%
      \@sDTLifhaskey{#2}{#3}%
    }%
    {\@sdtl@getcolumnindex{#1}{#2}{#3}%
  }

```

```

    }%
    {%
        \PackageError{datatool}{Database `#2' doesn't contain
            key `#3'}{ }%
    }%
}
}
{%
    \PackageError{datatool}{Database `#2' doesn't exist}{ }%
}
}
}
\newcommand*{\@sdtl@getcolumnindex}[3]{%
    \expandafter\let\expandafter#1\csname dtl@ci@#2@#3\endcsname
}
}
\newcommand*{\dtlcolumnindex}[2]{%
    \csname dtl@ci@#1@#2\endcsname
}
}
\newcommand*{\DTLgetkeyforcolumn}{%
    \@ifstar\@sdtlgetkeyforcolumn\@dtlgetkeyforcolumn}
\newcommand*{\@dtlgetkeyforcolumn}[3]{%
    \DTLifdbexists{#2}%
    {%
        \ifnum#3<1\relax
            \PackageError{datatool}{Invalid column index \number#3}{%
                Column indices start at 1}%
        \else
            \expandafter\ifnum\csname dtlcols@#2\endcsname<#3\relax
                \PackageError{datatool}{Index \number#3\space out of
                    range for database `#2'}{Database `#2' only has
                    \expandafter\number\csname dtlcols@#2\endcsname\space
                    columns}%
            \else
                \@sdtlgetkeyforcolumn{#1}{#2}{#3}%
            \fi
        \fi
    }%
}
}
\newcommand*{\@sdtlgetkeyforcolumn}[3]{%
    \edef\@dtl@dogetkeyforcolumn{\noexpand\@dtl@getkeyforcolumn
        {\noexpand#1}{#2}{\number#3}}%
    \@dtl@dogetkeyforcolumn
}
}
\newcommand*{\@dtl@getkeyforcolumn}[3]{%
    \def\@dtl@get@keyforcolumn##1% before stuff
        \db@plist@elt@w% start of block
        \db@col@id@w #3\db@col@id@end@% index
        \db@key@id@w ##2\db@key@id@end@% key
        \db@type@id@w ##3\db@type@id@end@% data type
}
}

```

```

        \db@header@id@w ##4\db@header@id@end@% header
        \db@col@id@w #3\db@col@id@end@% index
        \db@plist@elt@end@% end of block
        ##5\q@nil{\def#1{##2}}%
\edef\@dtl@tmp{\expandafter\the\csname dtlkeys@#2\endcsname}%
\expandafter\@dtl@get@keyforcolumn\@dtl@tmp
        \db@plist@elt@w% start of block
        \db@col@id@w #3\db@col@id@end@ %index
        \db@key@id@w \@nil\db@key@id@end@% key
        \db@type@id@w \db@type@id@end@% data type
        \db@header@id@w \db@header@id@end@% header
        \db@col@id@w #3\db@col@id@end@% index
        \db@plist@elt@end@% end of block
        \q@nil
    }
\def\DTLunsettype{}
\def\DTLstringtype{0}
\def\DTLinttype{1}
\def\DTLrealtype{2}
\def\DTLcurrencytype{3}
\newcommand*\@DTLgetdatatype}{%
    \@ifstar\@sdtlgetdatatype\@dtlgetdatatype
}
\newcommand*\@dtlgetdatatype}[3]{%
    \DTLifdbexists{#2}%
    {%
        \@sDTLifhaskey{#2}{#3}%
        {%
            \@sdtlgetdatatype{#1}{#2}{#3}%
        }%
        {%
            \PackageError{datatool}{Key `#3' undefined in database `#2'}{}}%
        }%
    }%
    {%
        \PackageError{datatool}{Database `#2' doesn't exist}{}}%
    }%
}
\newcommand*\@sdtlgetdatatype}[3]{%
    \edef\@dtl@dogetdata{\noexpand\@dtl@getdatatype{\noexpand#1}%
        {\expandafter\the\csname dtlkeys@#2\endcsname}%
        {\dtlcolumnindex{#2}{#3}}}%
    \@dtl@dogetdata
}
\newcommand*\@dtl@getdatatype}[3]{%
    \def\@dtl@get@keydata##1% stuff before
        \db@plist@elt@w% start of key block
        \db@col@id@w #3\db@col@id@end@% column index
        \db@key@id@w ##2\db@key@id@end@% key id
        \db@type@id@w ##3\db@type@id@end@% data type

```

```

        \db@header@id@w ##4\db@header@id@end@% header
        \db@col@id@w #3\db@col@id@end@% column index
        \db@plist@elt@end@% end of key block
        ##5% stuff afterwards
        \q@nil{\def#1{##3}}%
    \@dtl@get@keydata#2\q@nil
}
\newcommand*{\@dtl@getprops}[7]{%
    \def\@dtl@get@keydata##1% stuff before
        \db@plist@elt@w% start of key block
        \db@col@id@w #7\db@col@id@end@% column index
        \db@key@id@w ##2\db@key@id@end@% key id
        \db@type@id@w ##3\db@type@id@end@% data type
        \db@header@id@w ##4\db@header@id@end@% header
        \db@col@id@w #7\db@col@id@end@% column index
        \db@plist@elt@end@% end of key block
        ##5% stuff afterwards
        \q@nil{%
            \def#1{##2}% key
            \def#2{##3}% data type
            #3={##4}% header
            #4={##1}% before stuff
            #5={##5}% after stuff
        }%
    \@dtl@get@keydata#6\q@nil
}
\newtoks\@dtl@before
\newtoks\@dtl@after
\newtoks\@dtl@colhead
\newcommand*{\DTLaddcolumn}{%
    \@ifstar\@sDTLaddcolumn\@DTLaddcolumn
}
\newcommand{\@DTLaddcolumn}[2]{%
    \DTLifdbexists{#1}%
    {\@dtl@updatekeys{#1}{#2}{}}%
    {\PackageError{datatool}{Can't add new column to database `#1':
        database doesn't exist}{}}%
}
\newcommand{\s@DTLaddcolumn}[2]{%
    \@dtl@updatekeys{#1}{#2}{}}%
}
\newcommand*{\@dtl@updatekeys}[3]{%
    \@sDTLifhaskey{#1}{#2}%
    {%
        \expandafter\dtlcolumnnum\expandafter
        =\dtlcolumnindex{#1}{#2}\relax
        \edef\@dtl@dogetprops{\noexpand\@dtl@getprops
            {\noexpand\@dtl@key}{\noexpand\@dtl@type}%
            {\noexpand\@dtl@colhead}{\noexpand\@dtl@before}%
            {\noexpand\@dtl@after}{\the\csname dtlkeys@#1\endcsname}%
        }%
    }%
}

```

```

        {\number\dtlcolumnnum}}%
\@dtl@dogetprops
\ifstrempy{#3}%
{%
}%
{%
\let\@dtl@oldtype\@dtl@type
\@dtl@checknumerical{#3}%
\ifdefempty{\@dtl@type}%
{%
\edef\@dtl@type{\number\@dtl@datatype}%
}%
{%
\ifcase\@dtl@datatype % string
\def\@dtl@type{0}%
\or % int
\or % real
\ifnum\@dtl@type=1\relax
\def\@dtl@type{2}%
\fi
\or % currency
\ifnum\@dtl@type>0\relax
\def\@dtl@type{3}%
\fi
\fi
}%
\ifx\@dtl@oldtype\@dtl@type
\else
\@dtl@toks@gconcat@middle@cx{dtlkeys@#1}%
{\@dtl@before}%
{%
\noexpand\db@plist@elt@w% start of key block
\noexpand\db@col@id@w \the\dtlcolumnnum
\noexpand\db@col@id@end@% column index
\noexpand\db@key@id@w #2\noexpand\db@key@id@end@% key id
\noexpand\db@type@id@w \@dtl@type
\noexpand\db@type@id@end@% data type
\noexpand\db@header@id@w \the\@dtl@colhead
\noexpand\db@header@id@end@% header
\noexpand\db@col@id@w \the\dtlcolumnnum
\noexpand\db@col@id@end@% column index
\noexpand\db@plist@elt@end@% end of key block
}%
{\@dtl@after}%
\fi
}%
}%
{%
\expandafter\global\expandafter\advance
\csname dtlcols@#1\endcsname by 1\relax

```

```

\dtlcolumnnum=\csname dtlcols@#1\endcsname\relax
\expandafter\xdef\csname dtl@ci@#1@#2\endcsname{%
  \number\dtlcolumnnum}%
\ifstrempy{#2}%
{%
  \edef\@dtl@type{}% don't know data type yet
}%
{%
  \@dtl@checknumerical{#3}%
  \edef\@dtl@type{\number\@dtl@datatype}%
}%
\@dtl@toks@gput@right@cx{dtlkeys@#1}%
{%
  \noexpand\db@plist@elt@w
  \noexpand\db@col@id@w \the\dtlcolumnnum
  \noexpand\db@col@id@end@
  \noexpand\db@key@id@w #2\noexpand\db@key@id@end@
  \noexpand\db@type@id@w \@dtl@type
  \noexpand\db@type@id@end@
  \noexpand\db@header@id@w #2\noexpand\db@header@id@end@
  \noexpand\db@col@id@w \the\dtlcolumnnum
  \noexpand\db@col@id@end@
  \noexpand\db@plist@elt@end@
}%
}%
}
\newcommand*{\DTLsetheader}{\@ifstar\@sDTLsetheader\@DTLsetheader}
\newcommand*{\@DTLsetheader}[3]{%
  \DTLifdbexists{#1}%
  {%
    \@sDTLifhaskey{#1}{#2}%
    {%
      \@sDTLsetheader{#1}{#2}{#3}%
    }%
  }%
  {\PackageError{datatool}{Database `#1' doesn't contain key
`#2'}{}}%
}%
}%
\PackageError{datatool}{Database `#1' doesn't exist}{}}%
}%
}
\newcommand*{\@sDTLsetheader}[3]{%
  \expandafter\dtlcolumnnum\expandafter
  =\dtlcolumnindex{#1}{#2}\relax
  \@dtl@setheaderforindex{#1}{\dtlcolumnnum}{#3}%
}
\newcommand*{\@dtl@setheaderforindex}[3]{%
  \edef\@dtl@dogetprops{\noexpand\@dtl@getprops

```

```

{\noexpand\dtl@key}{\noexpand\dtl@type}%
{\noexpand\dtl@colhead}{\noexpand\dtl@before}%
{\noexpand\dtl@after}{\the\csname dtlkeys@#1\endcsname}%
{\number#2}}%
\@dtl@dogetprops
\@dtl@colhead={#3}%
\edef\@dtl@colnum{\number#2}\relax
\@dtl@toks@gconcat@middle@cx{dtlkeys@#1}%
{\@dtl@before}%
{%
  \noexpand\db@plist@elt@w% start of block
  \noexpand\db@col@id@w \@dtl@colnum
  \noexpand\db@col@id@end@% index
  \noexpand\db@key@id@w \@dtl@key\noexpand\db@key@id@end@% key
  \noexpand\db@type@id@w \@dtl@type
  \noexpand\db@type@id@end@% data type
  \noexpand\db@header@id@w \the\@dtl@colhead
  \noexpand\db@header@id@end@% header
  \noexpand\db@col@id@w \@dtl@colnum
  \noexpand\db@col@id@end@% index
  \noexpand\db@plist@elt@end@% end of block
}%
{\@dtl@after}%
}
\newcommand*{\dtlexpandnewvalue}{%
  \def\@dtl@setnewvalue##1{\protected@edef\@dtl@tmp{##1}%
  \expandafter\@dtl@toks\expandafter{\@dtl@tmp}}%
}
\newcommand*{\dtlnoexpandnewvalue}{%
  \def\@dtl@setnewvalue##1{\@dtl@toks{##1}}%
}
\dtlnoexpandnewvalue
\newcommand{\DTLnewdbentry}{%
  \@ifstar\@sDTLnewdbentry\@DTLnewdbentry
}
\newcommand{\@DTLnewdbentry}[3]{%
  \DTLifdbexists{#1}%
  {\@sDTLnewdbentry{#1}{#2}{#3}}%
  {\PackageError{datatool}{Can't add new entry to database `#1':
  database doesn't exist}{}}%
}
\newcommand*{\@sDTLnewdbentry}[3]{%
  \@dtl@updatekeys{#1}{#2}{#3}%
  \expandafter\dtlcolumnnum\expandafter
  =\dtlcolumnindex{#1}{#2}\relax
  \edef\dtl@dogetrow{\noexpand\dtlgetrow{#1}%
  {\number\csname dtlrows@#1\endcsname}}%
  \dtl@dogetrow
  \edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
  {\noexpand\dtl@entry}{\number\dtlcolumnnum}%
}

```

```

}%
\dtl@dogetentry
\ifx\dtl@entry\dtlnovalue
  \@dtl@setnewvalue{#3}%
  \@dtl@toks@gconcat@middle@cx{dtldb@#1}%
  {\dtlbeforerow}%
  {%
    \noexpand\db@row@elt@w%
    \noexpand\db@row@id@w \number\csname dtlrows@#1\endcsname
    \noexpand\db@row@id@end@%
    \the\dtlcurrentrow
    \noexpand\db@col@id@w \number\dtlcolumnnum
    \noexpand\db@col@id@end@%
    \noexpand\db@col@elt@w \the\@dtl@toks
    \noexpand\db@col@elt@end@%
    \noexpand\db@col@id@w \number\dtlcolumnnum
    \noexpand\db@col@id@end@%
    \noexpand\db@row@id@w \number\csname dtlrows@#1\endcsname
    \noexpand\db@row@id@end@%
    \noexpand\db@row@elt@end@%
  }%
  {\dtlafterrow}%
  \dtl@message{Added #2\space -> #3\space to database `#1'}%
\else
  \PackageError{datatool}{Can't add entry with ID `#2' to
current row of database `#1'}{There is already an entry with
this ID in the current row}%
\fi
}
}
\newcommand{\DTLifdbexists}[3]{%
  \@ifundefined{dtldb@#1}{#3}{#2}}
\newcommand*\DTLassign}[3]{%
  \DTLifdbexists{#1}
  {%
    \dtlgetrow{#1}{#2}%
    \@dtl@assign{#3}{#1}%
  }%
}%
{%
  \PackageError{datatool}{Database `#1' doesn't exist}{}%
}%
}
\newcommand*\DTLassignfirstmatch}[4]{%
  \dtl@assignfirstmatch{#3}{#1}{#2}{#4}%
}
\newcommand*\xDTLassignfirstmatch}[4]{%
  \protected@edef\@dtl@asg@value{\expandonce{#3}}%
  \expandafter\dtl@assignfirstmatch\expandafter
  {\@dtl@asg@value}{#1}{#2}{#4}%
}

```

```

}
\newcommand*{\dtl@assignfirstmatch}[4]{%
  \DTLifdbexists{#2}%
  {%
    \dtlgetrowindex{\dtl@asg@rowidx}{#2}{\dtlcolumnindex{#2}{#3}}{#1}%
    \ifx\dtl@asg@rowidx\dtlnovalue
      \PackageError{datatool}{No match found for
        \string\DTLassignfirstmatch{#2}{#3}{#1}{#4}}{%
    \else
      \dtlgetrow{#2}{\dtl@asg@rowidx}%
      \@dtl@assign{#4}{#2}%
    \fi
  }%
}%
\PackageError{datatool}{Data base `#2' doesn't exist}{}%
}
\newcommand*{\@dtl@assign}[2]{%
  \ifstrempy{#1}{}%
  {%
    \@dtl@assigncmd#1,\@nil\@{#2}%
  }%
}
\def\@dtl@assigncmd#1#2=#3,#4\@#5{%
  \edef\@dtl@dbname{#5}%
  \@sDTLifhaskey{#5}{#3}%
  {%
    \edef\@dtl@dogetentry{%
      \noexpand\dtlgetentryfromcurrentrow
      {\noexpand#1}{\dtlcolumnindex{#5}{#3}}}%
    \@dtl@dogetentry
    \ifdefequal{#1}{\dtlnovalue}%
    {%
      \@@dtl@setnull{#1}{#3}%
    }%
  }%
  {}%
  \global\let#1=#1\relax
}%
\PackageError{datatool}{Can't assign \string#1\space: there
  is no key `#3' in data base `#5'}{}%
\global\let#1\DTLstringnull
}%
\def\dtl@tmp{#4}%
\ifx\@nnil\dtl@tmp
  \let\@dtl@next\@dtl@assigncmdnoop
\else
  \let\@dtl@next\@dtl@assigncmd

```

```

\fi
\@dtl@next#4\@{#5}%
}
\def\@dtl@assigncmdnoop#1\@{#2}{
\newcommand*\@dtl@setnull}[2]{%
\@sDTLifhaskey{\@dtl@dbname}{#2}%
{%
\@dtl@setnull{#1}{#2}%
}%
}%
\global\let#1=\DTLstringnull
}%
}
\newcommand*\@dtl@setnull}[2]{%
\@sdtlgetdatatype{\@dtl@type}{\@dtl@dbname}{#2}%
\ifnum0\@dtl@type=0\relax
\global\let#1=\DTLstringnull
\else
\global\let#1=\DTLnumbernull
\fi
}
\newcommand*\DTLstringnull{\@dtlstringnull}
\newcommand*\@dtlstringnull{NULL}
\newcommand*\DTLnumbernull{\@dtlnumbernull}
\newcommand*\@dtlnumbernull{0}
\newcommand*\DTLifnull}[3]{%
\ifx#1\dtlnovalue
#2%
\else
\ifx#1\DTLstringnull
#2%
\else
\ifx#1\DTLnumbernull
#2%
\else
#3%
\fi
\fi
\fi
}
\newcommand*\DTLifnullloempty}[3]{%
\ifdefempty{#1}{#2}{\DTLifnull{#1}{#2}{#3}}%
}
\def\@dtlnovalue{Undefined Value}
\def\dtlnovalue{\@dtlnovalue}
\newcommand*\DTLgetkeydata{%
\@ifstar\@sdtlgetkeydata\@dtlgetkeydata
}
\newcommand*\@dtlgetkeydata}[5]{%
\DTLifdbexists{#2}%

```

```

{%
  \@sDTLifhaskey{#2}{#1}%
  {%
    \@sdtlgetkeydata{#1}{#2}{#3}{#4}{#5}%
  }%
  {%
    \PackageError{datatool}{Key `#1' not defined in database
      `#2'}{ }%
  }%
}
{%
  \PackageError{datatool}{Database `#2' doesn't exist}{ }%
}
}
\newcommand*{\@sdtlgetkeydata}[5]{%
  \@sdtlgetcolumnindex{#3}{#2}{#1}%
  \edef\@dtl@dogetkeydata{\noexpand\@dtl@getprops
    {\noexpand\@dtl@key}{\noexpand#4}{\noexpand\@dtl@colhead}%
    {\noexpand\@dtl@before}{\noexpand\@dtl@after}%
    {\expandafter\the\csname dtlkeys@#2\endcsname}%
    {#3}}%
  \@dtl@dogetkeydata
  \edef#5{\the\@dtl@toks}%
}
\newcommand{\@dtl@gathervalues}[3][key]{%
  \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#2}\do
  {%
    \dtlgetentryfromrow{\@dtl@tmp}{\@dtl@col}{#3}%
    \ifx\@dtl@tmp\dtlnovalue
      \@dtl@setnull{\@dtl@tmp}{\@dtl@key}%
    \fi
    \expandafter\let\csname @dtl@#1@\@dtl@key\endcsname\@dtl@tmp
  }%
}
\newcommand{\@dtl@g@gathervalues}[3][key]{%
  \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#2}\do
  {%
    \dtlgetentryfromrow{\@dtl@tmp}{\@dtl@col}{#3}%
    \ifx\@dtl@tmp\dtlnovalue
      \@dtl@setnull{\@dtl@tmp}{\@dtl@key}%
    \fi
    \expandafter\global
    \expandafter\let\csname @dtl@#1@\@dtl@key\endcsname\@dtl@tmp
  }%
}
\newtoks\dtlcurrentrow
\newtoks\dtlbeforerow
\newtoks\dtlafterrow

\newcommand*{\dtlgetrow}[2]{%

```

```

\dtlrownum=#2\relax
\edef\dtldbname{#1}%
\expandafter\toks@\expandafter=\csname dtldb@#1\endcsname
\edef\@dtl@dogetrow{\noexpand\@dtlgetrow{\the\toks@}{\number#2}}%
\@dtl@dogetrow
}
\newcommand{\edtgetrowforvalue}[3]{%
\protected@edef\@dtl@dogetrowforvalue{%
\noexpand\dtlgetrowforvalue{#1}{#2}{#3}}%
\@dtl@dogetrowforvalue
}
\newcommand{\DTLfetch}[4]{%
\edtgetrowforvalue{#1}{\dtlcolumnindex{#1}{#2}}{#3}%
\dtlgetentryfromcurrentrow{\dtlcurrentvalue}{\dtlcolumnindex{#1}{#4}}%
\dtlcurrentvalue
}
\newcommand*\@dtlgetrowforvalue}[3]{%
\dtlgetrowindex{\dtl@rowidx}{#1}{#2}{#3}%
\ifx\dtl@rowidx\dtlnovalue
\PackageError{datatool}{No row found in database `#1' for
column `#2' matching `#3'}{}%
\else
\dtlrownum=\dtl@rowidx\relax
\edef\dtldbname{#1}%
\expandafter\toks@\expandafter=\csname dtldb@#1\endcsname
\edef\@dtl@dogetrow{\noexpand\@dtlgetrow{\the\toks@}{\dtl@rowidx}}%
\@dtl@dogetrow
\fi
}
\newcommand*\@dtlgetrow}[2]{%
\def\@dtl@getrow##1% before stuff
\@db@row@elt@w% start of the row
\@db@row@id@w #2\@db@row@id@end@% row id
##2%
\@db@row@id@w #2\@db@row@id@end@% row id
\@db@row@elt@end@% end of the row
##3% after stuff
\q@nil{\dtlbeforerow={##1}\dtlcurrentrow={##2}\dtlafterrow={##3}}%
\@dtl@getrow#1\q@nil
}
\newcommand*\@dtlrecombine}{%
\@dtl@toks@gconcat@middle@cx{dtldb@\dtldbname}%
{\dtlbeforerow}%
{%
\noexpand\@db@row@elt@w
\noexpand\@db@row@id@w
\number\dtlrownum
\noexpand\@db@row@id@end@
\the\dtlcurrentrow
\noexpand\@db@row@id@w
}

```

```

        \number\dtlrownum
        \noexpand\db@row@id@end@
        \noexpand\db@row@elt@end@
    }%
    {\dtlafterrow}%
}
\newcommand{\dtlrecombineomitcurrent}{%
    \dtl@decrementrows{\dtlafterrow}{\dtlrownum}
    \csname dtldb@\dtldbname\endcsname=\dtlbeforerow
    \@dtl@toks@gput@right@c{x{\dtldb@\dtldbname}}{\the\dtlafterrow}%
    \dtl@message{Removed row \number\dtlrownum\space in database
        \dtldbname'}%
}
\newcommand*{\dtlsplitrow}[4]{%
    \def\@dtlsplitrow##1%before stuff
        \db@col@id@w #2\db@col@id@end@% column id
        ##2% unwanted stuff
        \db@col@id@w #2\db@col@id@end@% column id
        ##3% after stuff
        \q@nil{\def#3{##1}\def#4{##3}}%
    \@dtlsplitrow#1\q@nil
}
\newcommand*{\dtlreplaceentryincurrentrow}[2]{%
    \edef\@dtl@do@splitrow{\noexpand\dtlsplitrow
        {\the\dtlcurrentrow}%
        {\number#2}%
        {\noexpand\@dtl@before@cs}%
        {\noexpand\@dtl@after@cs}}%
    \@dtl@do@splitrow
    \toks@{#1}%
    \edef\@dtl@stuff{%
        \expandonce\@dtl@before@cs
        \noexpand\db@col@id@w \number#2\noexpand
        \noexpand\db@col@id@end@% column id
        \noexpand\db@col@elt@w
        \the\toks@
        \noexpand\db@col@elt@end@
        \noexpand\db@col@id@w \number#2\noexpand
        \noexpand\db@col@id@end@% column id
        \expandonce\@dtl@after@cs
    }%
    \expandafter\dtlcurrentrow\expandafter{\@dtl@stuff}%
    \@sdtlgetkeyforcolumn{\@dtl@key}{\dtldbname}{#2}%
    \@dtl@updatekeys{\dtldbname}{\@dtl@key}{#1}%
    \dtl@message{Updated \@dtl@key\space -> #1\space in database
        \dtldbname'}%
}
\newcommand*{\dtlremoveentryincurrentrow}[1]{%
    \edef\@dtl@do@splitrow{\noexpand\dtlsplitrow
        {\the\dtlcurrentrow}%

```

```

{\number#1}%
{\noexpand\@dtl@before@cs}%
{\noexpand\@dtl@after@cs}}%
\@dtl@do@splitrow
\edef\@dtl@stuff{%
  \expandonce\@dtl@before@cs
  \expandonce\@dtl@after@cs
}%
\expandafter\dtlcurrentrow\expandafter{\@dtl@stuff}%
\dtl@message{Removed entry from column \number#1\space\space in database
  '\dtldbname'}%
}
\newcommand*\dtlswapentriesincurrentrow}[2]{%
  \dtlgetentryfromcurrentrow{\@dtl@entryI}{#1}%
  \dtlgetentryfromcurrentrow{\@dtl@entryII}{#2}%
  \expandafter\dtlreplaceentryincurrentrow\expandafter
  {\@dtl@entryII}{#1}%
  \expandafter\dtlreplaceentryincurrentrow\expandafter
  {\@dtl@entryI}{#2}%
}
\newcommand*\dtlgetentryfromcurrentrow}[2]{%
  \dtlgetentryfromrow{#1}{#2}{\dtlcurrentrow}%
}
\newcommand*\dtlgetentryfromrow}[3]{%
  \edef\@dtl@do@getentry{\noexpand\dtl@getentryfromrow
    {\noexpand#1}{\number#2}{\the#3}}%
  \@dtl@do@getentry
}
\newcommand*\dtl@getentryfromrow}[3]{%
  \def\dtl@dogetentry##1% before stuff
    \db@col@id@w #2\db@col@id@end@% Column id
    \db@col@elt@w ##2\db@col@elt@end@% Value
    \db@col@id@w #2\db@col@id@end@% Column id
    ##3% Remaining stuff
    \q@nil{\def#1{##2}}%
  \dtl@dogetentry#3%
    \db@col@id@w #2\db@col@id@end@%
    \db@col@elt@w \@dtlnovalue\db@col@elt@end@%
    \db@col@id@w #2\db@col@id@end@%
    \q@nil
}
\newcommand*\dtlappendentrytocurrentrow}[2]{%
  \@dtl@updatekeys{\dtldbname}{#1}{#2}%
  \expandafter\dtlcolumnnum\expandafter
  =\dtlcolumnindex{\dtldbname}{#1}\relax
  \edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
    {\noexpand\dtl@entry}{\number\dtlcolumnnum}%
  }%
  \dtl@dogetentry
  \ifx\dtl@entry\dtlnovalue

```

```

\protected@edef\@dtl@tmp{#2}%
\expandafter\@dtl@toks\expandafter{\@dtl@tmp}%
\@dtl@toks@gput@right@cx{dtlcurrentrow}%
{%
  \noexpand\db@col@id@w
  \number\dtlcolumnnum
  \noexpand\db@col@id@end@
  \noexpand\db@col@elt@w
  \the\@dtl@toks
  \noexpand\db@col@elt@end@
  \noexpand\db@col@id@w
  \number\dtlcolumnnum
  \noexpand\db@col@id@end@
}%
\dtl@message{Appended #1\space -> #2\space to database
'\dtldbname'}%
\else
\PackageError{datatool}{Can't append entry to row:
there is already an entry for key `#1' in this row}{}%
\fi
}
\newcommand*{\dtlupdateentryincurrentrow}[2]{%
\@dtl@updatekeys{\dtldbname}{#1}{#2}%
\expandafter\dtlcolumnnum\expandafter
=\dtlcolumnindex{\dtldbname}{#1}\relax
\edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
{\noexpand\dtl@entry}{\number\dtlcolumnnum}%
}%
\dtl@dogetentry
\ifx\dtl@entry\dtlnovalue
\protected@edef\@dtl@tmp{#2}%
\expandafter\@dtl@toks\expandafter{\@dtl@tmp}%
\@dtl@toks@gput@right@cx{dtlcurrentrow}%
{%
  \noexpand\db@col@id@w
  \number\dtlcolumnnum
  \noexpand\db@col@id@end@
  \noexpand\db@col@elt@w
  \the\@dtl@toks
  \noexpand\db@col@elt@end@
  \noexpand\db@col@id@w
  \number\dtlcolumnnum
  \noexpand\db@col@id@end@
}%
\dtl@message{Appended #1\space -> #2\space to database
'\dtldbname'}%
\else
\toks@{#2}%
\edef\do@dtlreplaceincurrentrow{%
  \noexpand\dtlreplaceentryincurrentrow{\the\toks@}{\number\dtlcolumnnum}%
}

```

```

    }%
    \do@dtlreplaceincurrentrow
  \fi
}
\newcommand*\DTLgetvalue}[4]{%
  \edef\dtl@dogetvalue{\noexpand\dtl@getvalue{\noexpand#1}{#2}%
    {\number#3}{\number#4}}%
  \dtl@dogetvalue
}
\newcommand*\dtl@getvalue}[4]{%
  \def\@dtl@getvalue ##1% stuff before row <r>
    \db@row@id@w #3\db@row@id@end@% row <r> id
    ##2% stuff in row <r> before column <c>
    \db@col@id@w #4\db@col@id@end@% column <c> id
    \db@col@elt@w ##3\db@col@elt@end@% value
    ##4% stuff after value
    \q@nil{\def#1{##3}}%
  \toks@=\csname dtldb@#2\endcsname
  \expandafter\@dtl@getvalue\the\toks@% contents of data base
    \db@row@id@w #3\db@row@id@end@%
    \db@col@id@w #4\db@col@id@end@%
    \db@col@elt@w \@dtlnovalue\db@col@elt@end@% undefined value
    \q@nil
  \ifx#1\dtlnovalue
    \PackageError{datatool}{There is no element at (row=#3,\space
      column=#4) in database `#2'}`}%
  \fi
}
\newcommand*\DTLgetlocation}[4]{%
  \def\@dtl@getlocation##1% stuff before value
    \db@col@elt@w #4\db@col@elt@end@% value
    \db@col@id@w ##2\db@col@id@end@% column id
    ##3% stuff after this column
    \db@row@id@w ##4\db@row@id@end@% row id
    ##5% stuff after row
    \q@nil{\def#1{##4}\def#2{##2}}%
  \toks@=\csname dtldb@#3\endcsname
  \expandafter\@dtl@getlocation\the\toks@% contents of data base
    \db@col@elt@w #4\db@col@elt@end@% value
    \db@col@id@w \@dtlnovalue\db@col@id@end@% undefined column id
    \db@row@id@w \@dtlnovalue\db@row@id@end@% undefined row id
    \q@nil
  \ifx#1\dtlnovalue
    \PackageError{datatool}{There is no element `#4' in database `#3'}`}%
  \fi
}
\newcommand*\DTLgetrowindex}[4]{%
  \toks@{#4}%
  \edef\dtl@dogetrowindex{\noexpand\dtl@getrowindex{\noexpand#1}{#2}{\number#3}{\the\toks@}}
  \dtl@dogetrowindex

```

```

\ifx#1\dtlnovalue
  \PackageError{datatool}{There is no element `#4' for column
    \number#3\space in database `#2'}{ }%
\fi
}
\newcommand*\dtlgetrowindex[4]{%
  \toks@{#4}%
  \edef\dtl@dogetrowindex{\noexpand\@dtlgetrowindex{\noexpand#1}{#2}{\number#3}{\the\toks@}
  \dtl@dogetrowindex
}
\newcommand*\xdtlgetrowindex[4]{%
  \protected@edef\dtl@dogetrowindex{\noexpand\@dtlgetrowindex{\noexpand#1}{#2}{\number#3}
  \dtl@dogetrowindex
}
\newcommand*\@dtlgetrowindex[4]{%
  \def\@dtlgetrowindex##1% stuff before value
    \db@col@elt@w #4\db@col@elt@end@% value
    \db@col@id@w #3\db@col@id@end@% column id
    ##2% stuff after this column
    \db@row@id@w ##3\db@row@id@end@% row id
    ##4% stuff after row
    \q@nil{\def#1{##3}}%
  \toks@=\csname dtldb@#2\endcsname
  \expandafter\@dtlgetrowindex\the\toks@% contents of data base
    \db@col@elt@w #4\db@col@elt@end@% value
    \db@col@id@w #3\db@col@id@end@% column id
    \db@row@id@w \@dtlnovalue\db@row@id@end@% undefined row id
    \q@nil
}
\long\def\@dtlforeachrow(#1,#2)\in#3\do#4{%
  \edef\dtl@tmp{\expandafter\the\csname dtldb@#3\endcsname}%
  \expandafter\@dtlforeachrow\dtl@tmp
    \db@row@elt@w%
    \db@row@id@w \@nil\db@row@id@end@%
    \db@row@id@w \@nil\db@row@id@end@%
    \db@row@elt@end@%
    \@{#1}{#2}{#4}\q@nil
}
\long\def\@dtlforeachrow\db@row@elt@w%
  \db@row@id@w #1\db@row@id@end@%
  #2\db@row@id@w #3\db@row@id@end@%
  \db@row@elt@end@#4\@@#5#6#7\q@nil{%
  \gdef#5{#1}%
  \gdef\@dtl@loopbody{#7}%
  \global\advance\@dtl@foreach@level by 1\relax
  \ifx#5\@nnil
    \expandafter\global\expandafter
      \let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
        =\@dtl@foreachnoop

```

```

\else
  \gdef#6{#2}%
  \expandafter\let
    \csname @dtl@break@the\@dtl@foreach@level\endcsname
    \dtlbreak
  \gdef\dtlbreak{\expandafter\global\expandafter
    \let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
    =\@dtl@foreachnoop}%
  \expandafter\global\expandafter
    \let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
    =\@dtl@foreachrow
  \@dtl@loopbody
  \expandafter\let\expandafter\dtlbreak
    \csname @dtl@break@the\@dtl@foreach@level\endcsname
\fi
\expandafter\let\expandafter\@dtl@foreachnext
  \csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
\global\advance\@dtl@foreach@level by -1\relax
\@dtl@foreachnext#4\@@{#5}{#6}{#7}\q@nil
}
\long\def\@dtl@foreachnoop#1\@@#2\q@nil{}
\long\def\dtlforeachkey(#1,#2,#3,#4)\in#5\do#6{%
  \gdef\@dtl@loopbody{#6}%
  \edef\@dtl@keys{\expandafter\the\csname dtlkeys@#5\endcsname}%
  \expandafter\@dtl@foreachkey\@dtl@keys
    \db@plist@elt@w%
    \db@col@id@w -1\db@col@id@end@%
    \db@key@id@w \db@key@id@end@%
    \db@type@id@w \db@type@id@end@%
    \db@header@id@w \db@header@id@end@%
    \db@col@id@w -1\db@col@id@end@%
    \db@plist@elt@end@%
    \@@{\@dtl@updatefkcs{#1}{#2}{#3}{#4}}\q@nil
}
\newcommand*\@dtl@updatefkcs}[8]{%
  \gdef#1{#5}%
  \gdef#2{#6}%
  \gdef#3{#7}%
  \gdef#4{#8}%
}
\long\def\@dtl@foreachkey\db@plist@elt@w%
\db@col@id@w #1\db@col@id@end@%
\db@key@id@w #2\db@key@id@end@%
\db@type@id@w #3\db@type@id@end@%
\db@header@id@w #4\db@header@id@end@%
\db@col@id@w #5\db@col@id@end@%
\db@plist@elt@end@#6\@@#7\q@nil{%
  \ifnum#1=-1\relax
    \let\@dtl@foreachnext\@dtl@foreachnoop
  \else

```

```

#7{#2}{#1}{#3}{#4}%
\global\advance\@dtl@foreach@level by 1\relax
\expandafter\let
  \csname @dtl@break@the\@dtl@foreach@level\endcsname
  \dtlbreak
\gdef\dtlbreak{\expandafter\global\expandafter
  \let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
  =\@dtl@foreachnoop}%
\expandafter\global\expandafter
  \let\csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
  =\@dtl@foreachkey
\@dtl@loopbody
\expandafter\let\expandafter\@dtl@foreachnext
  \csname @dtl@foreachnext\the\@dtl@foreach@level\endcsname
\expandafter\let\expandafter\dtlbreak
  \csname @dtl@break@the\@dtl@foreach@level\endcsname
\global\advance\@dtl@foreach@level by -1\relax
\fi
\@dtl@foreachnext#6\@{#7}\q@nil
}
\newcommand*\@dtlforcolumn{\@ifstar\@sdtlforcolumn\@dtlforcolumn}
\newcommand{\@dtlforcolumn}[4]{%
  \DTLifdbexists{#2}%
  {%
    \@DTLifhaskey{#2}{#3}%
    {%
      \@sdtlforcolumn{#1}{#2}{#3}{#4}%
    }%
    {%
      \PackageError{datatool}{Database `#2' doesn't contain
        key `#3'}{ }%
    }%
  }%
  {%
    \PackageError{datatool}{Database `#2' doesn't exist}{ }%
  }%
}
\newcommand{\@sdtlforcolumn}[4]{%
  \toks@{#4}%
  \edef\@dtl@doforcol{\noexpand\dtlforcolumn{\noexpand#1}%
    {\expandafter\the\csname dtldb@#2\endcsname}%
    {\dtlcolumnindex{#2}{#3}}{\the\toks@}}%
  }%
  \@dtl@doforcol%
}
\newcommand*\@dtlforcolumnidx{%
  \@ifstar\@sdtlforcolumnidx\@dtlforcolumnidx
}
\newcommand{\@dtlforcolumnidx}[4]{%
  \DTLifdbexists{#2}%

```

```

{%
  \expandafter\ifnum\csname dtlcols@#2\endcsname<#3\relax
  \PackageError{datatool}{Column index \number#3\space out of
    bounds for database `#2'}{Database `#2' only has
    \expandafter\number\csname dtlcols@#2\endcsname\space
    columns}%
  \else
  \ifnum#3<1\relax
  \PackageError{datatool}{Column index \number#3\space out of
    bounds for database `#2'}{Indices start from 1}%
  \else
  \@sdttlforcolumnidx{#1}{#2}{#3}{#4}%
  \fi
  \fi
}%
{%
  \PackageError{datatool}{Database `#2' doesn't exist}{}%
}%
}
\newcommand{\@sdttlforcolumnidx}[4]{%
  \toks@{#4}%
  \edef\@dtl@doforcol{\noexpand\dtl@forcolumn{\noexpand#1}%
    {\expandafter\the\csname dtldb@#2\endcsname}%
    {\number#3}{\the\toks@}}%
  }%
  \@dtl@doforcol
}
\newcommand{\dtl@forcolumn}[4]{%
  \let\@dtl@oldbreak\dtlbreak
  \def\dtlbreak{\let\@dtl@forcolnext=\@dtl@forcolnoop}%
  \def\@dtl@forcolumn##1% before stuff
  \db@col@id@w #3\db@col@id@end@% column index
  \db@col@elt@w ##2\db@col@elt@end@% entry
  \db@col@id@w #3\db@col@id@end@% column index
  ##3% after stuff
  \q@nil{%
    \def#1{##2}% assign value to <cs>
    \ifx#1\@nnil
      \let\@dtl@forcolnext=\@dtl@forcolnoop
    \else
      #4%
      \let\@dtl@forcolnext=\@dtl@forcolumn
    \fi
    \@dtl@forcolnext##3\q@nil
  }%
  \@dtl@forcolumn#2%
  \db@col@id@w #3\db@col@id@end@%
  \db@col@elt@w \@nil\db@col@elt@end@%
  \db@col@id@w #3\db@col@id@end@\q@nil
  \let\dtlbreak\@dtl@oldbreak

```

```

}
\def\@dtl@forcolnoop#1\q@nil{}

\newcount\dtlforeachlevel
\newcounter{DTLrowi}
\newcounter{DTLrowii}
\newcounter{DTLrowiii}
\newcounter{DTLrow}
\def\theHDTLrow{\arabic{DTLrow}}
\def\theHDTLrowi{\theHDTLrow.\arabic{DTLrowi}}
\def\theHDTLrowii{\theHDTLrowi.\arabic{DTLrowii}}
\def\theHDTLrowiii{\theHDTLrowii.\arabic{DTLrowiii}}
\newcount\dtl@rowi
\newcount\dtl@rowii
\newcount\dtl@rowiii
\newtoks\@dtl@curi
\newtoks\@dtl@previ
\newtoks\@dtl@nexti
\newtoks\@dtl@curii
\newtoks\@dtl@previi
\newtoks\@dtl@nextii
\newtoks\@dtl@curiii
\newtoks\@dtl@previii
\newtoks\@dtl@nextiii
\newcommand*\DTLsaveastrowcount}[1]{%
\ifnum\dtlforeachlevel>2\relax
  \def#1{0}%
\else
  \ifnum\dtlforeachlevel<0\relax
    \def#1{0}%
  \else
    \@dtl@tmpcount=\dtlforeachlevel
    \advance\@dtl@tmpcount by 1\relax
    \edef#1{\expandafter\number
      \csname c@DTLrow\romannumeral\@dtl@tmpcount\endcsname}%
    \fi
  \fi}
\newenvironment{DTLenvforeach}[3][\boolean{true}]%
{%
  \def\@dtlenvforeach@args{[#1]{#2}{#3}}%
  \long@collect@body\@do@dtlenvforeach
}%
{}
\newcommand{\@do@dtlenvforeach}[1]{%
  \expandafter\@DTLforeach\@dtlenvforeach@args{#1}%
}
\newenvironment{DTLenvforeach*}[3][\boolean{true}]%
{%
  \def\s@dtlenvforeach@args{[#1]{#2}{#3}}%
  \long@collect@body\@do@sdtlenvforeach
}

```

```

}%
{}
\newcommand{\@do@sdtlenvforeach}[1]{%
  \expandafter\@sDTLforeach\s@dtlenvforeach@args{#1}%
}
\newcommand*{\DTLforeach}{\@ifstar\@sDTLforeach\@DTLforeach}
\newcommand{\@DTLforeach}[4][\boolean{true}]{%
  \DTLifdbexists{#2}%
  {%
    \refstepcounter{DTLrow}%
    \global\c@DTLrow=\c@DTLrow\relax
    \xdef\@dtl@dbname{#2}%
    \global\advance\dtlforeachlevel by 1\relax
    \ifnum\dtlforeachlevel>3\relax
      \PackageError{datatool}{\string\DTLforeach\space nested too
        deeply}{Only 3 levels are allowed}%
    \else
      \@DTLifdbempty{#2}%
      {}%
      {%
        \expandafter\global
          \csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
            = 0\relax
        \expandafter\global\expandafter\let%
          \csname @dtl@iffirstrow\the\dtlforeachlevel\endcsname
            \DTLiffirstrow
        \gdef\DTLiffirstrow##1##2{%
          \expandafter\ifnum
            \csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
              =1 %space intended
            ##1%
          \else
            ##2%
          \fi}%
        \expandafter\global\expandafter\let%
          \csname @dtl@iflastrow\the\dtlforeachlevel\endcsname
            \DTLiflastrow
        \gdef\DTLiflastrow##1##2{%
          \expandafter\ifnum
            \csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
              =\csname dtlrows@#2\endcsname
            ##1%
          \else
            ##2%
          \fi}%
        \expandafter\global\expandafter\let%
          \csname @dtl@ifodddrow\the\dtlforeachlevel\endcsname
            \DTLifodddrow
        \gdef\DTLifodddrow##1##2{%
          \expandafter\ifodd

```

```

\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
##1%
\else
##2%
\fi}%
\expandafter\global\expandafter\let
\csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname
=@dtl@dbname
\expandafter\global\expandafter\let
\csname @dtl@ro@\romannumeral\dtlforeachlevel\endcsname
= \relax
\dtlgorint
\csname dtl@row\romannumeral\dtlforeachlevel\endcsname
=1\to\csname dtlrows@#2\endcsname\step1\do
{%
\@dtl@tmpcount=
\csname dtl@row\romannumeral\dtlforeachlevel\endcsname
\edef\dtl@dogetrow{\noexpand\dtlgetrow{#2}%
{\number\@dtl@tmpcount}}%
\dtl@dogetrow
\expandafter\global
\csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
= \dtlcurrentrow
\expandafter\global
\csname @dtl@prev\romannumeral\dtlforeachlevel\endcsname
= \dtlbeforerow
\expandafter\global
\csname @dtl@next\romannumeral\dtlforeachlevel\endcsname
= \dtlafterrow
\ifblank{#3}{\@dtl@assign{#3}{#2}}%
\ifthenelse{#1}%
{%
\refstepcounter{DTLrow\romannumeral\dtlforeachlevel}%
\expandafter\edef\expandafter\DTLcurrentindex%
\expandafter{%
\arabic{DTLrow\romannumeral\dtlforeachlevel}}%
#4%
\edef\@dtl@tmp{\expandafter\the
\csname @dtl@cur\romannumeral
\dtlforeachlevel\endcsname}%
\ifx\@dtl@tmp\@nnil
\expandafter\dtl@decrementrows\expandafter
{\csname @dtl@prev\romannumeral
\dtlforeachlevel\endcsname
}{\csname dtl@row\romannumeral
\dtlforeachlevel\endcsname}%
\expandafter\dtl@decrementrows\expandafter
{\csname @dtl@next\romannumeral
\dtlforeachlevel\endcsname
}{\csname dtl@row\romannumeral

```

```

        \dtlforeachlevel\endcsname}%
\edef\@dtl@tmp{%
  \expandafter\the
    \csname @dtl@prev\romannumeral
      \dtlforeachlevel\endcsname
    \expandafter\the
      \csname @dtl@next\romannumeral
        \dtlforeachlevel\endcsname
    }%
\expandafter\global\expandafter
  \csname dtldb@#2\endcsname\expandafter{\@dtl@tmp}%
\expandafter\global\expandafter
  \advance\csname dtlrows@#2\endcsname by -1\relax
\expandafter\global\expandafter
  \advance\csname dtl@row\romannumeral
    \dtlforeachlevel\endcsname by -1\relax
\else
  \@dtl@before=\csname @dtl@prev\romannumeral
    \dtlforeachlevel\endcsname
  \@dtl@after=\csname @dtl@next\romannumeral
    \dtlforeachlevel\endcsname
  \@dtl@toks@gconcat@middle@cx{dtldb@#2}%
  {\@dtl@before}%
  {%
    \noexpand\db@row@elt@w%
    \noexpand\db@row@id@w \expandafter\number
      \csname dtl@row\romannumeral
        \dtlforeachlevel\endcsname
    \noexpand\db@row@id@end@%
    \expandafter\the
      \csname @dtl@cur\romannumeral
        \dtlforeachlevel\endcsname
    \noexpand\db@row@id@w \expandafter\number
      \csname dtl@row\romannumeral
        \dtlforeachlevel\endcsname
    \noexpand\db@row@id@end@%
    \noexpand\db@row@elt@end@%
  }%
  {\@dtl@after}%
\fi
}%
}%
}%
\expandafter\global\expandafter\let\expandafter\DTLiffirstrow
  \csname @dtl@iffirstrow\the\dtlforeachlevel\endcsname
\expandafter\global\expandafter\let\expandafter\DTLiflastrow
  \csname @dtl@iflastrow\the\dtlforeachlevel\endcsname
\expandafter\global\expandafter\let\expandafter\DTLifoddrow
  \csname @dtl@ifoddrow\the\dtlforeachlevel\endcsname
}%

```

```

\fi
\global\advance\dtlforeachlevel by -1\relax
}%
{%
\PackageError{datatool}{Database `#2' doesn't exist}{}%
}%
}
\newcommand{\@sDTLforeach}[4][\boolean{true}]{%
\DTLifdbexists{#2}%
{%
\refstepcounter{DTLrow}%
\global\c@DTLrow=\c@DTLrow
\edef\@dtl@dbname{#2}%
\global\advance\dtlforeachlevel by 1\relax
\ifnum\dtlforeachlevel>3\relax
\PackageError{datatool}{\string\DTLforeach\space nested too
deeply}{Only 3 levels are allowed}%
\else
\@DTLifdbempty{#2}%
{}%
{%
\expandafter\global
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
= 0\relax
\expandafter\global\expandafter\let%
\csname @dtl@iffirstrow\the\dtlforeachlevel\endcsname
\DTLiffirstrow
\gdef\DTLiffirstrow##1##2{%
\expandafter\ifnum
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
=1 % space intended
##1%
\else
##2%
\fi}%
\expandafter\global\expandafter\let%
\csname @dtl@iflastrow\the\dtlforeachlevel\endcsname
\DTLiflastrow
\gdef\DTLiflastrow##1##2{%
\expandafter\ifnum
\csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
=\csname dtlrows@#2\endcsname
##1%
\else
##2%
\fi}%
\expandafter\global\expandafter\let%
\csname @dtl@ifoddrow\the\dtlforeachlevel\endcsname
\DTLifoddrow
\gdef\DTLifoddrow##1##2{%

```

```

\expandafter\ifodd
  \csname c@DTLrow\romannumeral\dtlforeachlevel\endcsname
  ##1%
\else
  ##2%
\fi}%
\expandafter\gdef\csname @dtl@dbname@\romannumeral
\dtlforeachlevel\endcsname{#2}%
\expandafter\global\expandafter\let
\csname @dtl@ro@\romannumeral\dtlforeachlevel\endcsname
= 1\relax
\@dtlforeachrow(\dtl@thisidx,\dtl@thisrow)\in{#2}\do%
{%
\csname dtl@row\romannumeral\dtlforeachlevel\endcsname
= \dtl@thisidx\relax
\expandafter\global
\csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
= \expandafter{\dtl@thisrow}%
\ifblank{#3}{%
}%
\dtlcurrentrow=\expandafter{\dtl@thisrow}%
\@dtl@assign{#3}{#2}%
}%
\ifthenelse{#1}%
{%
\refstepcounter{DTLrow\romannumeral\dtlforeachlevel}%
\expandafter\edef\expandafter\DTLcurrentindex%
\expandafter{%
\arabic{DTLrow\romannumeral\dtlforeachlevel}}%
#4%
}%
}%
}%
\expandafter\global\expandafter\let\expandafter\DTLiffirstrow
\csname @dtl@iffirstrow\the\dtlforeachlevel\endcsname
\expandafter\global\expandafter\let\expandafter\DTLiflastrow
\csname @dtl@iflastrow\the\dtlforeachlevel\endcsname
\expandafter\global\expandafter\let\expandafter\DTLifoddrow
\csname @dtl@ifoddrow\the\dtlforeachlevel\endcsname
}%
\fi
\global\advance\dtlforeachlevel by -1\relax
}%
{%
\PackageError{datatool}{Database `#2' doesn't exist}{%
}%
}
}
\newcommand*{\@dtlifreadonly}[2]{%
\expandafter\ifx
\csname @dtl@ro@\romannumeral\dtlforeachlevel\endcsname1\relax

```

```

    #1%
  \else
    #2%
  \fi
}
\newcommand*{\DTLappendtorow}[2]{%
  \ifnum\dtlforeachlevel=0\relax
    \PackageError{datatool}{\string\DTLappendrow\space can only be
      used inside \string\DTLforeach}{}%
  \else
    \expandafter\let\expandafter\@dtl@thisdb
    \csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname
    \@dtlifreadonly
    {%
      \PackageError{datatool}{\string\DTLappendtorow\space can't
        be used inside \DTLforeach*}{The starred version of
        \string\DTLforeach\space is read only}%
    }%
    {%
      \dtlrownum=
      \csname dtl@row\romannumeral\dtlforeachlevel\endcsname\relax
      \@dtl@updatekeys{\@dtl@thisdb}{#1}{#2}%
      \expandafter\dtlcolumnnum\expandafter
      =\dtlcolumnindex{\@dtl@thisdb}{#1}\relax
      \dtlcurrentrow =
      \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
      \edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
        {\noexpand\dtl@entry}{\number\dtlcolumnnum}}%
      }%
      \dtl@dogetentry
      \ifx\dtl@entry\dtlnovalue
        \protected@edef\@dtl@tmp{#2}%
        \expandafter\@dtl@toks\expandafter{\@dtl@tmp}%
        \@dtl@toks@gput@right@cx{\@dtl@cur\romannumeral\dtlforeachlevel}%
        {%
          \noexpand\db@col@id@w \number\dtlcolumnnum
          \noexpand\db@col@id@end@
          \noexpand\db@col@elt@w \the\@dtl@toks
          \noexpand\db@col@elt@end@
          \noexpand\db@col@id@w \number\dtlcolumnnum
          \noexpand\db@col@id@end@
        }%
        \dtl@message{Appended #1\space -> #2\space to database
          \@dtl@thisdb'}%
      \else
        \PackageError{datatool}{Can't append entry to row:
          there is already an entry for key `#1' in this row}{}%
      \fi
    }%
  \fi
}
\fi

```

```

}
\newcommand*{\DTLremoveentryfromrow}[1]{%
  \ifnum\dtlforeachlevel=0\relax
    \PackageError{datatool}{\string\DTLremoveentryfromrow\space
      can only be used inside \string\DTLforeach}}{%
  \else
    \expandafter\let\expandafter\@dtl@thisdb
      \csname @dtl@dbname@romannumeral\dtlforeachlevel\endcsname
    \@dtlifreadonly
    {%
      \PackageError{datatool}{\string\DTLremoveentryfromrow\space
        can't be used inside \string\DTLforeach*}{The starred
        version of \string\DTLforeach\space is read only}%
    }%
    {%
      \dtlrownum=
      \csname dtl@row\romannumeral\dtlforeachlevel\endcsname\relax
      \@DTLifhaskey{\@dtl@thisdb}{#1}%
      {%
        \@dtl@getcolumnindex{\thiscol}{\@dtl@thisdb}{#1}\relax
        \dtlcolumnnum=\thiscol\relax
        \dtlcurrentrow =
        \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
        \edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
          {\noexpand\dtl@entry}{\number\dtlcolumnnum}}%
        }%
        \dtl@dogetentry
        \ifx\dtl@entry\dtlnovalue
          \PackageError{datatool}{Can't remove entry given by `#1'
            from current row in database ` \@dtl@thisdb': no such
            entry}{The current row doesn't contain an entry for
            key `#1'}%
        \else
          \edef\@dtl@dosplitrow{%
            \noexpand\dtlsplitrow{\the\dtlcurrentrow}%
            {\number\dtlcolumnnum}{\noexpand\dtl@pre}%
            {\noexpand\dtl@post}}%
          }%
          \@dtl@dosplitrow
          \expandafter\@dtl@toks\expandafter{\dtl@pre}%
          \expandafter\toks@\expandafter{\dtl@post}%
          \edef\@dtl@tmp{\the\@dtl@toks \the\toks@}%
          \dtlcurrentrow=\expandafter{\@dtl@tmp}%
          \expandafter\global
          \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
            = \dtlcurrentrow
          \dtl@message{Removed entry given by #1\space from current
            row of database ` \@dtl@thisdb'}%
        \fi
      }%
    }%
  }%
}

```

```

    {%
      \PackageError{datatool}{Can't remove entry given by
        `#1' - no such key exists}{}%
    }%
  }%
\fi
}
\newcommand*{\DTLreplaceentryforrow}[2]{%
  \ifnum\dtlforeachlevel=0\relax
    \PackageError{datatool}{\string\DTLreplaceentryforrow\space
      can only be used inside \string\DTLforeach}{}%
  \else
    \expandafter\let\expandafter\@dtl@thisdb
      \csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname
    \@dtlifreadonly
    {%
      \PackageError{datatool}{\string\DTLreplaceentryforrow\space
        can't be used inside \string\DTLforeach*}{The starred version
          of \string\DTLforeach\space is read only}%
    }%
    {%
      \dtlrownum=
      \csname dtl@row\romannumeral\dtlforeachlevel\endcsname\relax
      \@DTLifhaskey{\@dtl@thisdb}{#1}%
      {%
        \@dtl@getcolumnindex{\thiscol}{\@dtl@thisdb}{#1}\relax
        \dtlcolumnnum=\thiscol\relax
        \dtlcurrentrow =
          \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
        \edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
          {\noexpand\dtl@entry}{\number\dtlcolumnnum}}%
      }%
      \dtl@dogetentry
      \ifx\dtl@entry\dtlnovalue
        \PackageError{datatool}{Can't replace entry given by `#1'
          from current row in database ``\@dtl@thisdb': no such
          entry}{The current row doesn't contain an entry for
            key `#1'}%
      \else
        \edef\@dtl@dospplitrow{%
          \noexpand\dtlsplitrow{\the\dtlcurrentrow}%
            {\number\dtlcolumnnum}{\noexpand\dtl@pre}%
            {\noexpand\dtl@post}%
        }%
        \@dtl@dospplitrow
        \protected@edef\@dtl@tmp{#2}%
        \expandafter\@dtl@toks\expandafter{\@dtl@tmp}% new value
        \expandafter\@dtl@before\expandafter{\dtl@pre}%
        \expandafter\@dtl@after\expandafter{\dtl@post}%
        \@dtl@toks@gconcat@middle@cx
      \fi
    }%
  \fi
}

```

```

        {\dtl@cur\romannumeral\dtlforeachlevel}%
        {\@dtl@before}%
        {%
            \noexpand\db@col@id@w \number\dtlcolumnnum
            \noexpand\db@col@id@end@%
            \noexpand\db@col@elt@w \the\@dtl@toks
            \noexpand\db@col@elt@end@%
            \noexpand\db@col@id@w \number\dtlcolumnnum
            \noexpand\db@col@id@end@%
        }%
        {\@dtl@after}%
        \dtl@message{Updated #1\space -> #2\space in database
        \@dtl@thisdb'}%
    \fi
}%
{%
    \PackageError{datatool}{Can't replace key `#1' - no such
    key in database \@dtl@thisdb'}{}%
}%
}%
\fi
}
\newcommand*\DTLremovecurrentrow{%
    \ifnum\dtlforeachlevel=0\relax
        \PackageError{datatool}{\string\DTLremovecurrentrow\space can
        only be used inside \string\DTLforeach}{}%
    \else
        \expandafter\let\expandafter\@dtl@thisdb
        \csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname
        \@dtlifreadonly
        {%
            \PackageError{datatool}{\string\DTLreplaceentryforrow\space
            can't be used inside \string\DTLforeach*}{The starred version
            of \string\DTLforeach\space is read only}%
        }%
        {%
            \expandafter\global
            \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
            ={\@nil}%
        }%
    \fi
}
\newcommand{\DTLaddentryforrow}[5]{%
    \DTLifdbexists{#1}%
    {%
        \def\@dtl@notdone{\PackageError{datatool}{Unable to add entry
        given by key `#4': condition not met for any row in database
        `#1'}{}}%
        \DTLforeach[#3]{#1}{#2}%
        {%

```

```

        \DTLappendtorow{#4}{#5}%
        \let\@dtl@notdone\relax
        \dtlbreak
    }%
    \@dtl@notdone
}%
{%
    \PackageError{datatool}{Unable to add entry given by key `#4':
        database `#1' doesn't exist}{}%
}%
}
\newcommand*\DTLforeachkeyinrow}[2]{%
    \ifnum\dtlforeachlevel=0\relax
        \PackageError{datatool}{\string\DTLforeachkeyinrow\space can only
            be used inside \string\DTLforeach}{}%
    \else
        \expandafter\let\expandafter\@dtl@thisdb
            \csname @dtl@dbname@\romannumeral\dtlforeachlevel\endcsname
        \dtlforeachkey(\dtlkey,\dtlcol,\dtltype,\dtlheader)\in
            \@dtl@thisdb\do{%
            \dtlcurrentrow =
                \csname @dtl@cur\romannumeral\dtlforeachlevel\endcsname
            \edef\dtl@dogetentry{\noexpand\dtlgetentryfromcurrentrow
                {\noexpand#1}{\dtlcol}}%
            \dtl@dogetentry
            \ifx#1\dtlnovalue
                \ifnum0\dtltype=0\relax
                    \let#1=\@dtlstringnull
                \else
                    \let#1=\@dtlnumbernull
                \fi
            \fi
            \global\let#1#1%
            \def\@dtl@loop@body{#2}%
            \@dtl@loop@body
        }%
    \fi
}
\newcommand{\DTLiffirstrow}[2]{%
    \PackageError{datatool}{\string\DTLiffirstrow\space can only
        be used inside \string\DTLforeach}{}%
}
\newcommand{\DTLiflastrow}[2]{%
    \PackageError{datatool}{\string\DTLiflastrow\space can only
        be used inside \string\DTLforeach}{}%
}
\newcommand{\DTLifoddrow}[2]{%
    \PackageError{datatool}{\string\DTLifoddrow\space can only
        be used inside \string\DTLforeach}{}%
}
}

```

```

\newcommand*\dtlbetweencols{}
\newcommand*\dtlbeforecols{}
\newcommand*\dtlaftercols{}
\newcommand*\dtlstringalign{l}
\newcommand*\dtlintalign{r}
\newcommand*\dtlrealalign{r}
\newcommand*\dtlcurrencyalign{r}
\newcommand*\dtladdalign[4]{%
  \ifnum#3=1\relax
    \protected@edef#1{\dtlbeforecols}%
  \else
    \protected@edef#1{#1\dtlbetweencols}%
  \fi
  \ifstrempy{#2}%
  {%
    \protected@edef#1{#1c}%
  }%
  {%
    \ifcase#2\relax
      \protected@edef#1{#1\dtlstringalign}%
    \or
      \protected@edef#1{#1\dtlintalign}%
    \or
      \protected@edef#1{#1\dtlrealalign}%
    \or
      \protected@edef#1{#1\dtlcurrencyalign}%
    \else
      \protected@edef#1{#1c}%
      \PackageError{datatool}{Unknown data type `#2'}{}%
    \fi
  }%
  \ifnum#3=#4\relax
    \protected@edef#1{#1\dtlaftercols}%
  \fi
}
\newcommand*\dtlheaderformat[1]{\null\hfil\textbf{#1}\hfil\null}
\newcommand*\dtlstringformat[1]{#1}
\newcommand*\dtlintformat[1]{#1}
\newcommand*\dtlrealformat[1]{#1}
\newcommand*\dtlcurrencyformat[1]{#1}
\newcommand*\dtldisplaystarttab{}
\newcommand*\dtldisplayendtab{}
\newcommand*\dtldisplayafterhead{}
\newcommand*\dtldisplayvalign{c}
\newcommand*\dtldisplaystartrow{}
\newcommand*\dtldisplaycr{\tabularnewline}

\newcommand*\DTLdisplaydb[2][]{%
  \def\@dtl@doamp{\gdef\@dtl@doamp{&}}%
  \def\@dtl@resetdoamp{\gdef\@dtl@doamp{\gdef\@dtl@doamp{&}}}%

```

```

\edef\@dtl@maxcols{\expandafter\number
  \csname dtlcols@#2\endcsname}%
\DTLnumitemsinlist{#1}{\@dtl@tmp}%
\dtlsub{\@dtl@maxcols}{\@dtl@maxcols}{\@dtl@tmp}%
\dtlclip{\@dtl@maxcols}{\@dtl@maxcols}%
\def\@dtl@tabargs{ }%
\dtlforeachkey(\@dtl@key, \@dtl@idx, \@dtl@type, \@dtl@head)%
  \in{#2}\do
  {%
    \expandafter\DTLifinlist\expandafter{\@dtl@key}{#1}%
    }%
    {%
      \dtladdalign\@dtl@tabargs\@dtl@type\@dtl@idx\@dtl@maxcols
    }%
  }%
\edef\@dtl@dobegintab{\noexpand\begin{tabular}[\dtl@displayvalign]{\@dtl@tabargs}}%
\@dtl@dobegintab
\dtl@displaystarttab
\@dtl@resetdoamp
\dtlforeachkey(\@dtl@key, \@dtl@idx, \@dtl@type, \@dtl@head)%
  \in{#2}\do
  {%
    \expandafter\DTLifinlist\expandafter{\@dtl@key}{#1}%
    }%
    {%
      \@dtl@doamp
      \dtlheaderformat{\@dtl@head}%
    }%
  }%
\\%
\dtl@displayafterhead
\@dtl@resetdoamp
\@sDTLforeach{#2}{ }{%
  \DTLiffirstrow{ }\dtl@displaycr\dtl@displaystartrow}%
  \@dtl@resetdoamp
  \DTLforeachkeyinrow{\@dtl@val}%
  {%
    \expandafter\DTLifinlist\expandafter{\dtl@key}{#1}%
    }%
    {%
      \global\let\@dtl@val\@dtl@val
      \@dtl@doamp
      \@dtl@datatype=0\dtl@type\relax
      \ifcase\@dtl@datatype
        \dtlstringformat\@dtl@val
      \or
        \dtlintformat\@dtl@val
      \or
        \dtlrealformat\@dtl@val
      \or
    }%
  }%

```

```

\dtlcurrencyformat\@dtl@val
\else
\@dtl@val
\fi
}%
}%
\dtldisplayendtab
\end{tabular}%
}
\define@key{displaylong}{caption}{\def\@dtl@cap{#1}}
\define@key{displaylong}{contcaption}{\def\@dtl@contcap{#1}}
\define@key{displaylong}{shortcaption}{\def\@dtl@shortcap{#1}}
\define@key{displaylong}{label}{\def\@dtl@label{#1}}
\define@key{displaylong}{foot}{\def\@dtl@foot{#1}}
\define@key{displaylong}{lastfoot}{\def\@dtl@lastfoot{#1}}
\define@key{displaylong}{omit}{\def\@dtl@omitlist{#1}}
\newcommand*\@dtl@resetdostartrow{%
\gdef\@dtl@dostartrow{%
\gdef\@dtl@dostartrow{\dtldisplaycr\dtldisplaystartrow}}%
}
\newcommand*\DTLdisplaylongdb}[2][]{%
\def\@dtl@cap{\@nil}%
\def\@dtl@contcap{\@nil}%
\def\@dtl@label{\@nil}%
\def\@dtl@shortcap{\@dtl@cap}%
\def\@dtl@foot{\@nil}%
\def\@dtl@lastfoot{\@nil}%
\def\@dtl@omitlist{}%
\setkeys{displaylong}{#1}%
\def\@dtl@doamp{\gdef\@dtl@doamp{&}}%
\def\@dtl@resetdoamp{\gdef\@dtl@doamp{\gdef\@dtl@doamp{&}}}%
\@dtl@resetdostartrow
\edef\@dtl@maxcols{\expandafter\number
\csname dtlcols@#2\endcsname}%
\DTLnumitemsinlist{\@dtl@omitlist}{\@dtl@tmp}%
\dtlsub{\@dtl@maxcols}{\@dtl@maxcols}{\@dtl@tmp}%
\dtlclip{\@dtl@maxcols}{\@dtl@maxcols}%
\def\@dtl@tabargs{}%
\dtlforeachkey(\@dtl@key,\@dtl@idx,\@dtl@type,\@dtl@head)%
\in{#2}\do
{%
\expandafter\DTLifinlist\expandafter{\@dtl@key}{\@dtl@omitlist}%
}%
{%
\dtladdalign\@dtl@tabargs\@dtl@type\@dtl@idx\@dtl@maxcols
}%
}%
\edef\@dtl@dobegintab{\noexpand\begin{longtable}{\@dtl@tabargs}}%
\@dtl@dobegintab

```

```

\ifx\@dtl@foot\@nnil
\else
  \@dtl@foot\endfoot
\fi
\ifx\@dtl@lastfoot\@nnil
\else
  \@dtl@lastfoot\endlastfoot
\fi
\ifx\@dtl@cap\@nnil
  \@dtl@resetdoamp
  \dtldisplaystarttab
  \dtlforeachkey(\@dtl@key,\@dtl@idx,\@dtl@type,\@dtl@head)%
    \in{#2}\do
    {%
      \expandafter\DTLifinlist\expandafter{\@dtl@key}{\@dtl@omitlist}%
    }%
    {%
      \@dtl@doamp{\dtlheaderformat{\@dtl@head}}%
    }%
  }%
  \@dtl@resetdoamp
  \@dtl@resetdostartrow
  \endhead\dtldisplayafterhead
\else
  \caption[\@dtl@shortcap]{\@dtl@cap}%
  \ifx\@dtl@label\@nnil
  \else
    \label{\@dtl@label}%
  \fi
  \dtldisplaycr
\dtldisplaystarttab
  \@dtl@resetdoamp
  \dtlforeachkey(\@dtl@key,\@dtl@idx,\@dtl@type,\@dtl@head)%
    \in{#2}\do
    {%
      \expandafter\DTLifinlist\expandafter{\@dtl@key}{\@dtl@omitlist}%
    }%
    {%
      \@dtl@doamp{\dtlheaderformat{\@dtl@head}}%
    }%
  }%
  \@dtl@resetdoamp
  \dtldisplaycr\dtldisplayafterhead
  \endfirsthead
  \ifx\@dtl@contcap\@nnil
    \caption{\@dtl@cap}%
  \else
    \caption{\@dtl@contcap}%
  \fi
  \dtldisplaycr\dtldisplaystarttab

```

```

\@dtl@resetdoamp
\dtlforeachkey(\@dtl@key,\@dtl@idx,\@dtl@type,\@dtl@head)%
\in{#2}\do
{%
\expandafter\DTLifinlist\expandafter{\@dtl@key}{\@dtl@omitlist}%
}%
{%
\@dtl@doamp{\dtlheaderformat{\@dtl@head}}%
}%
}%
\@dtl@resetdoamp
\@dtl@resetdostartrow
\dtldisplaycr\dtldisplayafterhead
\endhead
\fi
\@sDTLforeach{#2}{}%
\@dtl@dostartrow
\@dtl@resetdoamp
\DTLforeachkeyinrow{\@dtl@val}%
{%
\global\let\@dtl@val\@dtl@val
\expandafter\DTLifinlist\expandafter{\dtlkey}{\@dtl@omitlist}%
}%
{%
\@dtl@doamp
\@dtl@datatype=0\dtltype\relax
\ifcase\@dtl@datatype
\dtlstringformat\@dtl@val
\or
\dtlintformat\@dtl@val
\or
\dtlrealformat\@dtl@val
\or
\dtlcurrencyformat\@dtl@val
\fi
}%
}%
\dtldisplayendtab
\end{longtable}%
}
\newcommand*{\dtlswaprows}[3]{%
\ifnum#2=#3\relax
\else
\ifnum#2<#3\relax
\edef\@dtl@rowAidx{\number#2}%
\edef\@dtl@rowBidx{\number#3}%
\else
\edef\@dtl@rowAidx{\number#3}%
\edef\@dtl@rowBidx{\number#2}%

```

```

\fi
\edef\@dtl@dosplit{\noexpand\dtlgetrow{#1}{\@dtl@rowAidx}}%
\@dtl@dosplit
\expandafter\def\expandafter\@dtl@firstpart\expandafter
  {\the\dtlbeforerow}%
\@dtl@toksA=\dtlcurrentrow
\edef\@dtl@dosplit{\noexpand\@dtlgetrow
  {\the\dtlafterrow}{\@dtl@rowBidx}}%
\@dtl@dosplit
\expandafter\def\expandafter\@dtl@secondpart\expandafter
  {\the\dtlbeforerow}%
\@dtl@toksB=\dtlcurrentrow
\expandafter\def\expandafter\@dtl@thirdpart\expandafter
  {\the\dtlafterrow}%
\toks@=\expandafter{\@dtl@firstpart}%
\@dtl@toks=\expandafter{\@dtl@secondpart}%
\edef\@dtl@tmp{\the\toks@
  \noexpand\db@row@elt@w%
  \noexpand\db@row@id@w \@dtl@rowAidx\noexpand\db@row@id@end@%
  \the\@dtl@toksB
  \noexpand\db@row@id@w \@dtl@rowAidx\noexpand\db@row@id@end@%
  \noexpand\db@row@elt@end@%
  \the\@dtl@toks}%
\toks@=\expandafter{\@dtl@tmp}%
\@dtl@toks=\expandafter{\@dtl@thirdpart}%
\edef\@dtl@tmp{\the\toks@
  \noexpand\db@row@elt@w%
  \noexpand\db@row@id@w \@dtl@rowBidx\noexpand\db@row@id@end@%
  \the\@dtl@toksA
  \noexpand\db@row@id@w \@dtl@rowBidx\noexpand\db@row@id@end@%
  \noexpand\db@row@elt@end@%
  \the\@dtl@toks}%
\expandafter\global\csname dtldb@#1\endcsname=\expandafter
  {\@dtl@tmp}%
\fi
}
\newcommand*{\dtl@decrementrows}[2]{%
  \def\@dtl@newlist{}%
  \edef\@dtl@min{\number#2}%
  \expandafter\@dtl@decrementrows\the#1%
  \db@row@elt@w%
  \db@row@id@w \@nil\db@row@id@end@%
  \db@row@id@w \@nil\db@row@id@end@%
  \db@row@elt@end@%
  \@nil
  #1=\expandafter{\@dtl@newlist}%
}
\def\@dtl@decrementrows\db@row@elt@w\db@row@id@w #1\db@row@id@end@%
#2\db@row@id@w #3\db@row@id@end@\db@row@elt@end@#4\@nil{%
  \def\@dtl@thisrow{#1}%

```

```

\ifx\@dtl@thisrow\@nnil
  \let\@dtl@donextdec=\@dtl@gobbletonil
\else
  \ifnum\@dtl@thisrow>\@dtl@min
    \@dtl@tmpcount=\@dtl@thisrow\relax
    \advance\@dtl@tmpcount by -1\relax
    \toks@{#2}%
    \@dtl@toks=\expandafter{\@dtl@newlist}%
    \edef\@dtl@newlist{\the\@dtl@toks
      \noexpand\db@row@elt@w% row header
      \noexpand\db@row@id@w \number\@dtl@tmpcount
      \noexpand\db@row@id@end@% row id
      \the\toks@ % row contents
      \noexpand\db@row@id@w \number\@dtl@tmpcount
      \noexpand\db@row@id@end@% row id
      \noexpand\db@row@elt@end@% row end
    }%
  \else
    \toks@{#2}%
    \@dtl@toks=\expandafter{\@dtl@newlist}%
    \edef\@dtl@newlist{\the\@dtl@toks
      \noexpand\db@row@elt@w% row header
      \noexpand\db@row@id@w #1%
      \noexpand\db@row@id@end@% row id
      \the\toks@ % row contents
      \noexpand\db@row@id@w #3%
      \noexpand\db@row@id@end@% row id
      \noexpand\db@row@elt@end@% row end
    }%
  \fi
  \let\@dtl@donextdec=\@dtl@decrementrows
\fi
\@dtl@donextdec#4\@nil
}
\newcommand*{\DTLremove row}[2]{%
  \DTLifdbexists{#1}%
  {%
    \ifnum#2>0\relax
      \expandafter\ifnum\csname dtlrows@#1\endcsname<#2\relax
        \expandafter\ifnum\csname dtlrows@#1\endcsname=1\relax
          \PackageError{datatool}{Can't remove row ``\number#2' from
            database `#1': no such row}{Database `#1' only has
              1 row}%
        \else
          \PackageError{datatool}{Can't remove row ``\number#2' from
            database `#1': no such row}{Database `#1' only has
              \expandafter\number\csname dtlrows@#1\endcsname\space
              rows}%
        \fi
      \else
        \fi
    }%
  \else
    \fi
  }%
}

```

```

        \@DTLremove{row}{#1}{#2}%
    \fi
\else
    \PackageError{datatool}{Can't remove row \number#2: index
        out of bounds}{Row indices start at 1}%
\fi
}%
{%
    \PackageError{datatool}{Can't remove row: database `#1' doesn't
        exist}{}%
}%
}
\newcommand*{\@DTLremove}{2}{%
    \edef\dtl@dogetrow{\noexpand\dtlgetrow{#1}{\number#2}}%
    \dtl@dogetrow
    \expandafter\dtl@decrementrows\expandafter
        {\dtlbefore{row}{#2}}%
    \expandafter\dtl@decrementrows\expandafter
        {\dtlafter{row}{#2}}%
    \edef\dtl@tmp{\the\dtlbefore{row} \the\dtlafter{row}}%
    \expandafter\global\csname dtldb@#1\endcsname
        =\expandafter{\dtl@tmp}%
    \expandafter\global\expandafter\advance
        \csname dtlrows@#1\endcsname by -1\relax
}
\newcommand*{\DTLsumforkeys}[1][\boolean{true}]{and
\DTLisnumerical{\DTLthisval}}{%
    \def\@dtl@cond{#1}%
    \@dtlsumforkeys
}
\newcommand*{\@dtlsumforkeys}[4][[]]{%
    \def#4{0}%
    \@for\@dtl@db@name:=#2\do{%
        \@sDTLforeach{\@dtl@db@name}{%
            {#1}% assignment list
            {%
                \@for\@dtl@key:=#3\do{%
                    \@sdtl@getcolumnindex{\@dtl@col}{\@dtl@db@name}{\@dtl@key}%
                    \dtlcurrentrow=\expandafter{\dtl@thisrow}%
                    \dtlgetentryfromrow{\DTLthisval}{\@dtl@col}{\dtlcurrentrow}%
                    \expandafter\ifthenelse\expandafter{\@dtl@cond}{%
                        {\DTLadd{#4}{#4}{\DTLthisval}}}{%
                    }%
                }%
            }%
        }%
    }%
}
\newcommand*{\DTLsumcolumn}[3]{%
    \def#3{0}%
    \DTLifdbexists{#1}%
    {%

```

```

\@sDTLifhaskey{#1}{#2}%
{%
  \@sdtlforcolumn{\DTLthisval}{#1}{#2}%
  {%
    \DTLadd{#3}{#3}{\DTLthisval}%
  }%
}%
{%
  \PackageError{datatool}{Key `#2' doesn't
    exist in database `#1'}{}}%
}%
{%
  \PackageError{datatool}{Data base `#1' doesn't
    exist}{}}%
}%
}
\newcommand*\@DTLmeanforkeys}[1][\boolean{true}\and
\DTLisnumerical{\DTLthisval}]{%
  \def\@dtl@cond{#1}%
  \@dtlmeanforkeys
}
\newcount\@dtl@elements
\newcommand*\@dtlmeanforkeys}[4][[]]{%
  \def#4{0}%
  \@dtl@elements=0\relax
  \@for\@dtl@db@name:=#2\do{%
    \@sDTLforeach{\@dtl@db@name}%
    {#1}% assignment list
    {%
      \@for\@dtl@key:=#3\do{%
        \@sdtl@getcolumnindex{\@dtl@col}{\@dtl@db@name}{\@dtl@key}%
        \dtlcurrentrow=\expandafter{\dtl@thisrow}%
        \dtlgetentryfromrow{\DTLthisval}{\@dtl@col}{\dtlcurrentrow}%
        \expandafter\ifthenelse\expandafter{\@dtl@cond}%
        {%
          \DTLadd{#4}{#4}{\DTLthisval}%
          \advance\@dtl@elements by 1\relax
        }{}}%
      }%
    }%
  }%
  \ifnum\@dtl@elements=0\relax
    \PackageError{datatool}{Unable to evaluate mean: no data}{}}%
  \else
    \edef\@dtl@n{\number\@dtl@elements}%
    \DTLdiv{#4}{#4}{\@dtl@n}%
  \fi
}
\newcommand*\@DTLmeanforcolumn}[3]{%

```

```

\def#3{0}%
\@dtl@elements=0\relax
\DTLifdbexists{#1}%
{%
  \@sDTLifhaskey{#1}{#2}%
  {%
    \@sdtlforcolumn{\DTLthisval}{#1}{#2}%
    {%
      \DTLadd{#3}{#3}{\DTLthisval}%
      \advance\@dtl@elements by 1\relax
    }%
    \ifnum\@dtl@elements=0\relax
      \PackageError{datatool}{Can't compute mean for
        column `#2' in database `#1': no data}{}%
    \else
      \edef\@dtl@n{\number\@dtl@elements}%
      \DTLdiv{#3}{#3}{\@dtl@n}%
    \fi
  }%
  {%
    \PackageError{datatool}{Key `#2' doesn't
      exist in database `#1'}{}%
  }%
  {%
    \PackageError{datatool}{Data base `#1' doesn't
      exist}{}%
  }%
}
\newcommand*\DTLvarianceforkeys[1][\boolean{true}\and
\DTLisnumerical{\DTLthisval}]{%
  \def\@dtl@cond{#1}%
  \@dtlvarianceforkeys
}
\newcommand*\@dtlvarianceforkeys[4][]{%
\@dtl@meanforkeys[#1]{#2}{#3}{\dtl@mean}%
\def#4{0}%
\@dtl@elements=0\relax
\@for\@dtl@db@name:=#2\do{%
  \@sDTLforeach{\@dtl@db@name}%
  {#1}% assignment list
  {%
    \@for\@dtl@key:=#3\do{%
      \@sdtl@getcolumnindex{\@dtl@col}{\@dtl@db@name}{\@dtl@key}%
      \dtlcurrentrow=\expandafter{\dtl@thisrow}%
      \dtlgetentryfromrow{\DTLthisval}{\@dtl@col}{\dtlcurrentrow}%
      \expandafter\ifthenelse\expandafter{\@dtl@cond}%
      {%
        \DTLsub{\dtl@diff}{\DTLthisval}{\dtl@mean}%
        \DTLmul{\dtl@diff}{\dtl@diff}{\dtl@diff}%
      }%
    }%
  }%
}

```

```

        \DTLadd{#4}{#4}{\dtl@diff}%
        \advance\@dtl@elements by 1\relax
    }{}%
  }%
}%
\ifnum\@dtl@elements=0\relax
  \PackageError{datatool}{Unable to evaluate variance: no data}{}%
\else
  \edef\@dtl@n{\number\@dtl@elements}%
  \DTLdiv{#4}{#4}{\@dtl@n}%
\fi
}
\newcommand*\DTLvianceforcolumn}[3]{%
  \DTLmeanforcolumn{#1}{#2}{\dtl@mean}%
  \def#3{0}%
  \@dtl@elements=0\relax
  \DTLifdbexists{#1}%
  {%
    \@sDTLifhaskey{#1}{#2}%
    {%
      \@sdtlforcolumn{\DTLthisval}{#1}{#2}%
      {%
        \DTLsub{\dtl@diff}{\DTLthisval}{\dtl@mean}%
        \DTLmul{\dtl@diff}{\dtl@diff}{\dtl@diff}%
        \DTLadd{#3}{#3}{\dtl@diff}%
        \advance\@dtl@elements by 1\relax
      }%
      \ifnum\@dtl@elements=0\relax
        \PackageError{datatool}{Can't compute variance for
          column `#2' in database `#1': no data}{}%
      \else
        \edef\@dtl@n{\number\@dtl@elements}%
        \DTLdiv{#3}{#3}{\@dtl@n}%
      \fi
    }%
    {%
      \PackageError{datatool}{Key `#2' doesn't
        exist in database `#1'}{}%
    }%
  }%
  \PackageError{datatool}{Data base `#1' doesn't
    exist}{}%
}
}
\newcommand*\DTLsdforkeys}[1][\boolean{true}\and
\DTLisnumerical{\DTLthisval}]{}%
\def\@dtl@cond{#1}%
\@dtl@sdforkeys

```

```

}
\newcommand*\@dtlsdforkeys}[4][[]]{%
  \@dtlvarianceforkeys{#1}{#2}{#3}{#4}%
  \DTLsqrt{#4}{#4}%
}
\newcommand*\DTLsdforcolumn}[3]{%
  \DTLvarianceforcolumn{#1}{#2}{#3}%
  \DTLsqrt{#3}{#3}%
}
\newcommand*\DTLminforkeys}[1][\boolean{true}]\and
\DTLisnumerical{\DTLthisval}]{%
  \def\@dtl@cond{#1}%
  \@dtlminforkeys
}
\newcommand*\@dtlminforkeys}[4][[]]{%
  \def#4{%
    \@for\@dtl@db@name:=#2\do{%
      \@sDTLforeach{\@dtl@db@name}%
        {#1}% assignment list
        {%
          \@for\@dtl@key:=#3\do{%
            \@sdtl@getcolumnindex{\@dtl@col}{\@dtl@db@name}{\@dtl@key}%
            \dtlcurrentrow=\expandafter{\dtl@thisrow}%
            \dtlgetentryfromrow{\DTLthisval}{\@dtl@col}{\dtlcurrentrow}%
            \expandafter\ifthenelse\expandafter{\@dtl@cond}%
            {%
              \ifdefempty{#4}%
                {%
                  \let#4\DTLthisval
                }%
              {%
                \DTLmin{#4}{#4}{\DTLthisval}%
              }%
            }{%
          }%
        }%
      }%
    }%
  }%
}
\newcommand*\DTLminforcolumn}[3]{%
  \def#3{%
    \DTLifdbexists{#1}%
    {%
      \@sDTLifhaskey{#1}{#2}%
      {%
        \@sdtlforcolumn{\DTLthisval}{#1}{#2}%
        {%
          \ifdefempty{#3}%
            {%
              \let#3\DTLthisval
            }%
          }%
        }%
      }%
    }%
  }%
}

```

```

        {%
        \DTLmin{#3}{#3}{\DTLthisval}%
        }%
    }%
    {%
    \PackageError{datatool}{Key `#2' doesn't
    exist in database `#1'}{ }%
    }%
    }%
    {%
    \PackageError{datatool}{Data base `#1' doesn't
    exist}{ }%
    }%
}
\newcommand*\DTLmaxforkeys}[1][\boolean{true}]\and
\DTLisnumerical{\DTLthisval}]%
\def\@dtl@cond{#1}%
\@dtlmaxforkeys
}
\newcommand*\@dtlmaxforkeys}[4][ ]{%
\def#4{ }%
\@for\@dtl@db@name:=#2\do{%
\@sDTLforeach{\@dtl@db@name}%
{#1}% assignment list
{%
\@for\@dtl@key:=#3\do{%
\@sdtl@getcolumnindex{\@dtl@col}{\@dtl@db@name}{\@dtl@key}%
\dtlcurrentrow=\expandafter{\dtl@thisrow}%
\dtlgetentryfromrow{\DTLthisval}{\@dtl@col}{\dtlcurrentrow}%
\expandafter\ifthenelse\expandafter{\@dtl@cond}%
{%
\ifdefempty{#4}%
{%
\let#4\DTLthisval
}%
{%
\DTLmax{#4}{#4}{\DTLthisval}%
}%
}{}%
}%
}%
}
}
}
\newcommand*\DTLmaxforcolumn}[3]{%
\def#3{ }%
\DTLifdbexists{#1}%
{%
\@sDTLifhaskey{#1}{#2}%
{%

```

```

\@sdtlforcolumn{\DTLthisval}{#1}{#2}%
{%
  \ifdefempty{#3}%
  {%
    \let#3\DTLthisval
  }%
  {%
    \DTLmax{#3}{#3}{\DTLthisval}%
  }%
}%
}%
{%
  \PackageError{datatool}{Key `#2' doesn't
    exist in database `#1'}{ }%
}%
}%
{%
  \PackageError{datatool}{Data base `#1' doesn't
    exist}{ }%
}%
}
\newcommand*\DTLcomputebounds}[8][\boolean{true}]{%
\let#5=\relax
\let#6=\relax
\let#7=\relax
\let#8=\relax
\@fordtl@thisdb:=#2\do{%
  \@sDTLforeach[#1]{\dtl@thisdb}{\DTLthisX=#3,\DTLthisY=#4}{%
    \expandafter\DTLconverttodecimal\expandafter{\DTLthisX}{\dtl@decx}%
    \expandafter\DTLconverttodecimal\expandafter{\DTLthisY}{\dtl@decy}%
    \ifx#5\relax
      \let#5=\dtl@decx
      \let#6=\dtl@decy
      \let#7=\dtl@decx
      \let#8=\dtl@decy
    \else
      \dtlmin{#5}{#5}{\dtl@decx}%
      \dtlmin{#6}{#6}{\dtl@decy}%
      \dtlmax{#7}{#7}{\dtl@decx}%
      \dtlmax{#8}{#8}{\dtl@decy}%
    \fi
  }%
}%
}
\newcommand*\DTLgetvalueforkey}[5]{%
  \DTLgetrowforkey{\@dtl@row}{#3}{#4}{#5}%
  \@sdtl@getcolumnindex{\@dtl@col}{#3}{#2}%
  {%
    \dtlcurrentrow=\expandafter{\@dtl@row}%
    \edef\@dtl@dogetval{\noexpand\dtlgetentryfromcurrentrow

```

```

        {\noexpand\dtl@val}{\dtl@col}}%
\dtl@dogetval
\global\let#1=\dtl@val
}%
}
\newcommand*\DTLgetrowforkey}[4]{%
\global\let#1=\@empty
\@sDTLforeach{#2}{\dtl@refvalue=#3}{%
\DTLifnull{\dtl@refvalue}%
}%
{%
\ifthenelse{\equal{\dtl@refvalue}{#4}}%
{%
\xdef#1{\the\dtlcurrentrow}%
\dtlbreak
}%
}%
}%
}
\newtoks\dtl@list
\newcommand*\DTLsort{\@ifstar\@sDTLsort\DTLsort}
\newcommand{\@sDTLsort}[3][]{%
\dtlsort[#1]{#2}{#3}{\dtlcompare}%
}
\newcommand*\@sDTLsort}[3][]{%
\dtlsort[#1]{#2}{#3}{\dtlcompare}%
}
\newcommand{\dtlsort}[4][]{%
\DTLifdbexists{#3}%
{%
\ifnum\DTLrowcount{#3}>100\relax
\typeout{Sorting `#3' - this may take a while.}%
\fi
\edef\dtl@replacementkeys{#1}%
\def\dtl@sortorder{}%
\@for\dtl@level:=#2\do
{%
\expandafter\dtl@getsortdirection\dtl@level=\relax
\DTLifhaskey{#3}{\dtl@key}%
{%
\ifdefempty\dtl@sortorder
{\let\dtl@sortorder=\dtl@level}%
{\eappto\dtl@sortorder{,\dtl@level}}%
}%
}%
\PackageError{datatool}%
{%
Can't sort on `\dtl@level'.
No such key `\dtl@key' in database `#3'%
}
}
}
}

```

```

    }{}%
  }%
}%
\ifdefempty\@dtl@sortorder
{%
  \PackageWarning{datatool}{No keys provided to sort database `#3'}%
}%
{%
  \let\@dtl@comparecs=#4%
  \dtl@sortdata{#3}%
}%
}%
}%
\PackageError{datatool}{Database `#3' doesn't exist}{}%
}%
}
\newtoks\@dtl@rowa
\newtoks\@dtl@rowb
\newcommand*\@dtl@sortdata}[1]{%
  \def\@dtl@sortedlist{}%
  \edef\@dtl@dbname{#1}%
  \@dtlforeachrow(\@dtl@rowAnum,\@dtl@rowAcontents)\in\@dtl@dbname\do{%
    \@dtl@rowa=\expandafter{\@dtl@rowAcontents}%
    \def\@dtl@newlist{}%
    \@dtl@insertdonefalse
    \dtlrownum=0\relax
    \expandafter\@dtl@foreachrow\@dtl@sortedlist
      \db@row@elt@w%
      \db@row@id@w \@nil\db@row@id@end@%
      \db@row@id@w \@nil\db@row@id@end@%
      \db@row@elt@end@%
      \@@{\@dtl@rowBnum}{\@dtl@rowBcontents}%
      {%
        \@dtl@rowb=\expandafter{\@dtl@rowBcontents}%
        \dtlrownum=\@dtl@rowBnum
        \if@dtl@insertdone
          \advance\dtlrownum by 1\relax
        \else
          \@dtl@sortcriteria{\@dtl@rowa}{\@dtl@rowb}%
          \ifnum\dtl@sortresult<0\relax
            \toks@=\expandafter{\@dtl@newlist}%
            \edef\@dtl@newlist{%
              \the\toks@
              \noexpand\db@row@elt@w%
              \noexpand\db@row@id@w \number\dtlrownum
              \noexpand\db@row@id@end@%
              \the\@dtl@rowa
              \noexpand\db@row@id@w \number\dtlrownum
              \noexpand\db@row@id@end@%
              \noexpand\db@row@elt@end@%
            }
          \fi
        \fi
      }
    }
  }

```

```

    }%
    \advance\dtlrownum by 1\relax
    \@dtl@insertdone true
  \fi
\fi
\toks@=\expandafter{\@dtl@newlist}%
\edef\@dtl@newlist{\the\toks@
\noexpand\db@row@elt@w%
\noexpand\db@row@id@w \number\dtlrownum
\noexpand\db@row@id@end@%
\the\@dtl@rowb
\noexpand\db@row@id@w \number\dtlrownum
\noexpand\db@row@id@end@%
\noexpand\db@row@elt@end@%
}%
}\q@nil
\if@dtl@insertdone
\else
\advance\dtlrownum by 1\relax
\toks@=\expandafter{\@dtl@newlist}%
\edef\@dtl@newlist{\the\toks@
\noexpand\db@row@elt@w%
\noexpand\db@row@id@w \number\dtlrownum
\noexpand\db@row@id@end@%
\the\@dtl@rowa
\noexpand\db@row@id@w \number\dtlrownum
\noexpand\db@row@id@end@%
\noexpand\db@row@elt@end@%
}%
\fi
\let\@dtl@sortedlist=\@dtl@newlist
}%
\expandafter\global\csname dtldb@#1\endcsname=\expandafter
{\@dtl@sortedlist}%
}
\newcommand{\@dtl@sortcriteria}[2]{%
\@for\@dtl@level:=\@dtl@sortorder\do
{%
\expandafter\@dtl@getsortdirection\@dtl@level=\relax
\let\@dtl@keya=\@dtl@key
\let\@dtl@keyb=\@dtl@key
\@sdtl@getcolumnindex{\@dtl@col}{\@dtl@dbname}{\@dtl@key}%
\dtlgetentryfromrow{\@dtl@a}{\@dtl@col}{#1}%
\dtlgetentryfromrow{\@dtl@b}{\@dtl@col}{#2}%
\ifx\@dtl@a\dtlnovalue
\@dtl@setnull{\@dtl@a}{\@dtl@key}%
\fi
\ifx\@dtl@b\dtlnovalue
\@dtl@setnull{\@dtl@b}{\@dtl@key}%
\fi
}
}

```

```

\DTLifnull{\@dtl@a}%
{%
  \for\@dtl@keya:=\@dtl@replacementkeys\do{%
    \sdtl@getcolumnindex{\@dtl@col}{\@dtl@dbname}{\@dtl@keya}%
    \dtlgetentryfromrow{\@dtl@a}{\@dtl@col}{#1}%
    \ifx\@dtl@a\dtlnovalue
      \@dtl@setnull{\@dtl@a}{\@dtl@key}%
    \fi
    \DTLifnull{\@dtl@a}{\@endfortrue}%
  }%
  \ifx\@dtl@keya\@nnil
    \let\@dtl@keya\@dtl@key
    \@dtl@setnull{\@dtl@a}{\@dtl@key}%
  \fi
}%
}%
\DTLifnull{\@dtl@b}%
{%
  \for\@dtl@keyb:=\@dtl@replacementkeys\do{%
    \sdtl@getcolumnindex{\@dtl@col}{\@dtl@dbname}{\@dtl@keyb}%
    \dtlgetentryfromrow{\@dtl@b}{\@dtl@col}{#2}%
    \ifx\@dtl@b\dtlnovalue
      \@dtl@setnull{\@dtl@b}{\@dtl@key}%
    \fi
    \DTLifnull{\@dtl@b}{\@endfortrue}%
  }%
  \ifx\@dtl@keyb\@nnil
    \let\@dtl@keyb\@dtl@key
    \@dtl@setnull{\@dtl@b}{\@dtl@key}%
  \fi
}%
}%
\@dtl@toksA=\expandafter{\@dtl@a}%
\@dtl@toksB=\expandafter{\@dtl@b}%
\edef\@dtl@docompare{\noexpand\dtl@compare@
  {\@dtl@keya}{\@dtl@keyb}%
  {\noexpand\@dtl@toksA}{\noexpand\@dtl@toksB}}%
\@dtl@docompare
\ifnum\dtl@sortresult=0\relax
  \@endforfalse
\else
  \@endfortrue
\fi
}%
\multiply\dtl@sortresult by -\@dtl@sortdirection\relax
}
\def\@dtl@getsortdirection#1=#2\relax{%
  \def\@dtl@key{#1}%
  \def\@dtl@sortdirection{#2}%
  \ifdefempty{\@dtl@sortdirection}%

```

```

{%
  \def\@dtl@sortdirection{-1}%
}%
{%
  \@dtl@get@sortdirection#2%
  \def\@dtl@dir{ascending}%
  \ifx\@dtl@sortdirection\@dtl@dir
    \def\@dtl@sortdirection{-1}%
  \else
    \def\@dtl@dir{descending}%
    \ifx\@dtl@sortdirection\@dtl@dir
      \def\@dtl@sortdirection{1}%
    \else
      \PackageError{datatool}{Invalid sort direction
        \@dtl@sortdirection'}{The sort direction can only be
        one of `ascending' or `descending'}%
      \def\@dtl@sortdirection{-1}%
    \fi
  \fi
}%
}
\def\@dtl@get@sortdirection#1={\def\@dtl@sortdirection{#1}}
\newtoks\@dtl@toksA
\newtoks\@dtl@toksB
\newcommand{\dtl@compare}[3]{%
  \dtl@compare@{#1}{#1}{#2}{#3}%
}
\newcommand{\dtl@compare@}[4]{%
  \DTLgetdatatype{\@dtl@typeA}{\@dtl@dbname}{#1}%
  \ifx\@dtl@typeA\DTLunsettype
    \let\@dtl@typeA\DTLstringtype
  \fi
  \DTLgetdatatype{\@dtl@typeB}{\@dtl@dbname}{#2}%
  \ifx\@dtl@typeB\DTLunsettype
    \let\@dtl@typeB\DTLstringtype
  \fi
  \@dtl@tmpcount=\@dtl@typeA\relax
  \multiply\@dtl@tmpcount by \@dtl@typeB\relax
  \ifnum\@dtl@tmpcount=0\relax
    \edef\@dtl@tmpcmp{%
      \noexpand\dtl@comparecs{\noexpand\dtl@sortresult}%
      {\the#3}{\the#4}%
    }%
    \@dtl@tmpcmp
    \ifdtlverbose
      \edef\@dtl@a{\the#3}%
      \edef\@dtl@b{\the#4}%
    \fi
  \else
    \edef\@dtl@a{\the#3}%

```

```

\edef\@dtl@b{\the#4}%
\DTLifnumlt{\@dtl@a}{\@dtl@b}%
{%
  \dtl@sortresult=-1\relax
}%
{%
  \DTLifnumgt{\@dtl@a}{\@dtl@b}%
  {%
    \dtl@sortresult=1\relax
  }%
  {%
    \dtl@sortresult=0\relax
  }%
}%
\fi
\ifdtlverbose
  \@onelevel@sanitize\@dtl@a
  \@onelevel@sanitize\@dtl@b
  \dtl@message{\@dtl@a' <=> \@dtl@b' = \number\dtl@sortresult}%
\fi
}
\newwrite\@dtl@write
\newcommand*{\DTLsavedb}[2]{%
  \DTLifdbexists{#1}%
  {%
    \openout\@dtl@write=#2\relax
    \def\@dtl@header{}%
    \dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)%
      \in{#1}\do
    {%
      \IfSubStringInString{\@dtl@separator}{\@dtl@key}%
      {%
        \ifdefempty{\@dtl@header}%
        {%
          \protected@edef\@dtl@header{%
            \@dtl@delimiter\@dtl@key\@dtl@delimiter}%
          }%
        {%
          \toks@=\expandafter{\@dtl@header}%
          \protected@edef\@dtl@header{%
            \the\toks@\@dtl@separator
            \@dtl@delimiter\@dtl@key\@dtl@delimiter}%
          }%
        }%
      }%
    }%
  }%
  \ifdefempty{\@dtl@header}%
  {%
    \protected@edef\@dtl@header{\@dtl@key}%
  }%
  {%

```

```

\ toks@=\ expandafter{\ @dtl@header}%
\ protected@edef\ @dtl@header{\ the\ toks@
\ @dtl@separator\ @dtl@key}%
}%
}%
}%
\ protected@write\ @dtl@write{\ @dtl@header}%
\ @sDTLforeach{#1}{}%
{%
\ def\ @dtl@row{%
\ DTLforeachkeyinrow{\ @dtl@val}%
{%
\ IfSubStringInString{\ @dtl@separator}\ @dtl@val}%
{%
\ ifdefempty{\ @dtl@row}%
{%
\ protected@edef\ @dtl@row{%
\ @dtl@delimiter\ @dtl@val\ @dtl@delimiter}%
}%
}%
\ toks@=\ expandafter{\ @dtl@row}%
\ protected@edef\ @dtl@row{\ the\ toks@\ @dtl@separator
\ @dtl@delimiter\ @dtl@val\ @dtl@delimiter}%
}%
}%
{%
\ ifdefempty{\ @dtl@row}%
{%
\ protected@edef\ @dtl@row{\ @dtl@val}%
}%
}%
\ toks@=\ expandafter{\ @dtl@row}%
\ protected@edef\ @dtl@row{\ the\ toks@\ @dtl@separator
\ @dtl@val}%
}%
}%
\ protected@write\ @dtl@write{\ @dtl@row}%
}%
\ closeout\ @dtl@write
}%
}%
\ PackageError{datatool}{Can't save database `#1': no such
database}{}%
}%
}
\ newcommand*\ @DTLsavepdb[2]{%
\ DTLifdbexists{#1}%
{%
\ openout\ @dtl@write=#2\ relax

```

```

\protected@write\@dtl@write{}{\string\DTLnewdb{#1}}%
\@sDTLforeach{#1}{}%
{%
  \protected@write\@dtl@write{}{\string\DTLnewrow*{#1}}%
  \DTLforeachkeyinrow{\@dtl@val}%
  {%
    \DTLifnull{\@dtl@val}%
    {\def\@dtl@val{}}%
    {}%
    \protected@write\@dtl@write{}{%
      \string\DTLnewdbentry*{#1}{\dtlkey}{\@dtl@val}}%
  }%
}%
\dtlforeachkey(\@dtl@k,\@dtl@c,\@dtl@t,\@dtl@h)\in{#1}\do
{%
  \@onelevel@sanitize\@dtl@h
  \protected@write\@dtl@write{}{%
    \string\DTLsetheader*{#1}{\@dtl@k}{\@dtl@h}}%
}%
\protected@write{\@dtl@write}{\string\def\string\dtllastloadeddb{#1}}%
\closeout\@dtl@write
}%
}%
\PackageError{datatool}{Can't save database `#1': no such
database}{}%
}%
}
\newcommand*\@dtl@saverawdbhook{}
\newcommand*\DTLsaverawdb}[2]{%
  \DTLifdbexists{#1}%
  {%
    \openout\@dtl@write=#2\relax
    \protected@write{\@dtl@write}{%
      \string\DTLifdbexists{#1}\expandafter\@gobble\string\%^AJ%
      {%
        \string\PackageError{datatool}{Database `#1' ^AJalready exists}{}%
        \expandafter\@gobble\string\%^AJ%
        \string\aftergroup\string\endinput
      }%
      {%
        }\expandafter\@gobble\string\%^
      }%
    }%
  }%
  {%
    \def\db@row@elt@w{\expandafter\@gobble\string\%^AJ\string\db@row@elt@w\space}%
    \def\db@row@elt@end{\expandafter\@gobble\string\%^AJ\string\db@row@elt@end\space}%
    \def\db@row@id@w{\expandafter\@gobble\string\%^AJ\string\db@row@id@w\space}%
    \def\db@row@id@end{\expandafter\@gobble\string\%^AJ\string\db@row@id@end\space}%
    \def\db@col@elt@w{\expandafter\@gobble\string\%^AJ\string\db@col@elt@w\space}%
    \def\db@col@elt@end{\expandafter\@gobble\string\%^AJ\string\db@col@elt@end\space}%
    \def\db@col@id@w{\expandafter\@gobble\string\%^AJ\string\db@col@id@w\space}%
  }%
}

```

```

\def\db@col@id@end@{\expandafter\@gobble\string\%^J\string\db@col@id@end@\space}%
\def\db@plist@elt@w{\expandafter\@gobble\string\%^J\string\db@plist@elt@w\space}%
\def\db@plist@elt@end@{\expandafter\@gobble\string\%^J\string\db@plist@elt@end@\space}%
\def\db@key@id@w{\expandafter\@gobble\string\%^J\string\db@key@id@w\space}%
\def\db@key@id@end@{\expandafter\@gobble\string\%^J\string\db@key@id@end@\space}%
\def\db@type@id@w{\expandafter\@gobble\string\%^J\string\db@type@id@w\space}%
\def\db@type@id@end@{\expandafter\@gobble\string\%^J\string\db@type@id@end@\space}%
\def\db@header@id@w{\expandafter\@gobble\string\%^J\string\db@header@id@w\space}%
\def\db@header@id@end@{\expandafter\@gobble\string\%^J\string\db@header@id@end@\space}%
\protected@write{\@dtl@write}{\string\bgroup\string\makeatletter}%
\protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database^^J`#1'}}%
\expandafter\@gobble\string\%^J\string\dtl@message{Reconstructing database^^J`#1'}}%
\protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database^^J`#1'}}%
\string\expandafter
\string\global\string\expandafter^^J\string\newtoks
\string\csname\space dtlkeys@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database^^J`#1'}}%
\string\expandafter
\string\global^^J
\string\csname\space dtlkeys@#1\string\endcsname
=\expandafter\@gobble\string\{ \expandafter\@gobble\string\}%
\expandafter\protected@xdef\csname dtl@rawwritedbkeys@#1\endcsname{\the\csname dtlkeys@#1\endcsname}%
\protected@write{\@dtl@write}{\csname dtl@rawwritedbkeys@#1\endcsname}%
\protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database^^J`#1'}}%
{\expandafter\@gobble\string\}\expandafter\@gobble\string\}%
\dtl@saverawdbhook
\protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database^^J`#1'}}%
\string\expandafter\string\global
\string\expandafter^^J\string\newtoks
\string\csname\space dtldb@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database^^J`#1'}}%
\string\global^^J\string\csname\space dtldb@#1\string\endcsname
=\expandafter\@gobble\string\{ \expandafter\@gobble\string\}%
\expandafter\protected@xdef\csname dtl@rawwritedb@#1\endcsname{\the\csname dtldb@#1\endcsname}%
\protected@write{\@dtl@write}{\csname dtl@rawwritedb@#1\endcsname}%
\protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database^^J`#1'}}%
\protected@write{\@dtl@write}{\string\expandafter\string\global^^J
\string\expandafter\string\newcount
\string\csname\space dtlrows@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database^^J`#1'}}%
\string\csname\space dtlrows@#1\string\endcsname
=\expandafter\number\csname dtlrows@#1\endcsname\string\relax}%
\protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database^^J`#1'}}%
\string\expandafter\string\newcount
\string\csname\space dtlcols@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database^^J`#1'}}%
\string\csname\space dtlcols@#1\string\endcsname

```

```

        =\expandafter\number\csname dtlcols@#1\endcsname\string\relax}%
\dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
{%
  \edef\dtl@tmp{%
    \string\expandafter^^J
    \string\gdef
    \string\csname\space dtl@ci@#1@\@dtl@key\string\endcsname
    {\csname dtl@ci@#1@\@dtl@key\endcsname}\expandafter\@gobble\string\%
  }%
  \expandafter\write\expandafter\@dtl@write\expandafter{\dtl@tmp}%
}%
\protected@write{\@dtl@write}{\string\group}%
}%
\protected@write{\@dtl@write}{\string\def\string\dtllastloadeddb{#1}}%
\closeout\@dtl@write
}%
{%
  \PackageError{datatool}{Can't save database `#1': no such
  database}{}%
}%
}
\newcommand*{\DTLprotectedsaveawdb}[2]{%
  \DTLifdbexists{#1}%
  {%
    \openout\@dtl@write=#2\relax
    \protected@write{\@dtl@write}{\string\DTLifdbexists{#1}\expandafter\@gobble\string\%^^^J%
    {%
      \string\PackageError{datatool}{Database `#1' ^^Jalready exists}{}%
      \expandafter\@gobble\string\%^^^J%
      \string\aftergroup\string\endinput
    }%
    {%
      }\expandafter\@gobble\string\%
    }%
  }%
  {%
    \protected@write{\@dtl@write}{\string\bgroup\string\makeatletter}%
    \protected@write{\@dtl@write}{\string\dtl@message{Reconstructing database
    ^^J`#1'}\expandafter\@gobble\string\%}%
    \protected@write{\@dtl@write}{\string\expandafter
    \string\global\string\expandafter^^J\string\newtoks
    \string\csname\space dtlkeys@#1\string\endcsname}%
    \protected@write{\@dtl@write}{\string\expandafter
    \string\global^^J
    \string\csname\space dtlkeys@#1\string\endcsname
    =\expandafter\@gobble\string\{\expandafter\@gobble\string\%}%
    \edef\dtl@rawwrite@keys{\the\csname dtlkeys@#1\endcsname}%
    \@onelevel@sanitize\dtl@rawwrite@keys
  }%
}

```

```

\expandafter\write\expandafter\@dtl@write\expandafter
  {\dtl@rawwrite@keys\expandafter\@gobble\string\}}%
\protected@write{\@dtl@write}{\string\expandafter\string\global
\string\expandafter^^J\string\newtoks
\string\csname\space dtldb@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\expandafter
\string\global^^J\string\csname\space dtldb@#1\string\endcsname
=\expandafter\@gobble\string\{\expandafter\@gobble\string\}%
\edef\dtl@rawwrite@db{\the\csname dtldb@#1\endcsname}%
\@onelevel@sanitize\dtl@rawwrite@db
\expandafter\write\expandafter\@dtl@write\expandafter
  {\dtl@rawwrite@db\expandafter\@gobble\string\}}%
\protected@write{\@dtl@write}{\string\expandafter\string\global^^J
\string\expandafter\string\newcount
\string\csname\space dtlrows@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\expandafter\string\global^^J
\string\csname\space dtlrows@#1\string\endcsname
=\expandafter\number\csname dtlrows@#1\endcsname\string\relax}%
\protected@write{\@dtl@write}{\string\expandafter\string\global^^J
\string\expandafter\string\newcount
\string\csname\space dtlcols@#1\string\endcsname}%
\protected@write{\@dtl@write}{\string\expandafter\string\global^^J
\string\csname\space dtlcols@#1\string\endcsname
=\expandafter\number\csname dtlcols@#1\endcsname\string\relax}%
\dtlforeachkey(\@dtl@key,\@dtl@col,\@dtl@type,\@dtl@head)\in{#1}\do
{%
\edef\dtl@tmp{%
\string\expandafter^^J
\string\gdef
\string\csname\space dtl@ci@#1@\@dtl@key\string\endcsname
{\csname dtl@ci@#1@\@dtl@key\endcsname}\expandafter\@gobble\string\%
}%
\expandafter\write\expandafter\@dtl@write\expandafter{\dtl@tmp}%
}%
\protected@write{\@dtl@write}{\string\egroup}%
}%
\protected@write{\@dtl@write}{\string\def\string\dtlloaddb{#1}}%
\closeout\@dtl@write
}%
}%
\PackageError{datatool}{Can't save database `#1': no such
database}{}%
}%
}
\newcommand*\DTLloaddbtex}[2]{%
\IfFileExists{#2}%
{%
\input{#2}%

```

```

\ifdef#1%
{%
  \PackageError{datatool}{Command \string#1\space is already defined}%
  {}}%
}%
{%
  \let#1\dtllastloadeddb
}%
}%
\PackageError{datatool}{File `#2' doesn't exist.}{}%
}%
}
\newread\@dtl@read
\newcount\dtl@entrycr
\define@boolkey{loaddb}[dtl]{noheader}[true]{}
\define@boolkey{loaddb}[dtl]{autokeys}[true]{}
\dtlautokeysfalse
\define@key{loaddb}{keys}{%
  \dtl@entrycr=0\relax
  \@for\@dtl@key:=#1\do
  {%
    \advance\dtl@entrycr by 1\relax
    \expandafter
      \edef\csname @dtl@inky@\romannumeral\dtl@entrycr\endcsname{%
        \@dtl@key}%
  }%
}
\define@key{loaddb}{headers}{%
  \dtl@entrycr=0\relax
  \@for\@dtl@head:=#1\do
  {%
    \advance\dtl@entrycr by 1\relax
    \toks@=\expandafter{\@dtl@head}%
    \expandafter
      \edef\csname @dtl@inhd@\romannumeral\dtl@entrycr\endcsname{%
        \the\toks@}%
  }%
}
\newcount{\dtl@omitlines}
\define@key{loaddb}{omitlines}{\dtl@omitlines=#1\relax}
\newcommand*\dtldefaultkey{Column}
\newcommand*\@dtl@readline[2]{%
  \begingroup
  \catcode\endlinechar=\active%
  \global\read#1 to #2%
  \endgroup%
  \ifx#2\empty%
  \else%
    \expandafter\@dtl@stripeol#2%

```

```

        \let#2\@dtl@strippedline%
    \fi%
}
\beginingroup
\catcode\endlinechar=\active%
\gdef\@dtl@stripeol#1
{\gdef\@dtl@strippedline{#1}}
\endgroup
\newcommand*\@dtl@readrawline}[2]{%
    \@dtl@rawread#1 to #2%
    \@dtl@domappings\@dtl@line
}
\newif\ifDTLnewdbonload
\DTLnewdbonloadtrue
\newcommand*\@DTLloaddb}{%
    \let\@dtl@doreadline\@dtl@readline
    \@dtlloaddb
}
\newcommand*\@dtlloaddb}[3][]{%
    \IfFileExists{#3}{%
        \beginingroup
            \catcode`\\"12\relax
            \dtlnoheaderfalse
            \setkeys{loaddb}{#1}%
            \openin\@dtl@read=#3%
            \dtl@message{Reading `#3'}%
            \loop
            \ifnum \dtl@omitlines > \z@
                \advance\dtl@omitlines by \m@ne
                \read\@dtl@read to \@dtl@line
            \repeat
            \ifDTLnewdbonload
                \DTLnewdb{#2}%
            \fi
            \ifeof\@dtl@read
                \PackageWarning{datatool}{File `#3' has no data}%
            \else
                \ifdtlnoheader
                \else
                    \loop
                    \@dtl@conditionfalse
                    \ifeof\@dtl@read
                    \else
                        \@dtl@doreadline\@dtl@read\@dtl@line
                        \ifdefempty{\@dtl@line}%
                        {%
                            \@dtl@conditiontrue
                        }%
                    }%
                }%
            }%
        }%
    }%
}

```

```

\fi
\if@dtl@condition
\repeat
\protected@edef\@dtl@lin@{%
  \@dtl@separator\@dtl@line\@dtl@separator}%
\dtl@entrycr=0\relax
\loop
\expandafter\@dtl@lopoff\@dtl@lin@\to\@dtl@lin@\@dtl@key
\advance\dtl@entrycr by 1\relax
\ifdtlautokeys
  \csedef{\@dtl@inky@\romannumeral\dtl@entrycr}%
    {\dtldefaultkey\number\dtl@entrycr}%
\else
  \ifdefempty{\@dtl@key}%
    {%
      \edef\@dtl@key{\dtldefaultkey\number\dtl@entrycr}%
    }%
  {}%
\fi
\expandafter\@dtl@toks\expandafter{\@dtl@key}%
\@ifundefined{\@dtl@inky@\romannumeral\dtl@entrycr}%
{%
  \expandafter
  \edef\csname @dtl@inky@\romannumeral
    \dtl@entrycr\endcsname{\the\@dtl@toks}%
}%
{%
  \@ifundefined{\@dtl@inhd@\romannumeral\dtl@entrycr}%
  {%
    \expandafter
    \edef\csname @dtl@inhd@\romannumeral
      \dtl@entrycr\endcsname{\the\@dtl@toks}%
  }%
  {}%
}%
\ifx\@dtl@lin@\@dtl@separator
  \@dtl@conditionfalse
\else
  \@dtl@conditiontrue
\fi
\if@dtl@condition
\repeat
\fi
\ifeof\@dtl@read
  \ifdtlnoheader
    \PackageWarning{datatool}{No data in `#3'}%
  \else
    \PackageWarning{datatool}{Only header row found in `#3'}%
  \fi
\else

```

```

\@dtl@conditiontrue
\loop
\@dtl@doreadline\@dtl@read\@dtl@line
\ifdefempty{\@dtl@line}%
{%
}%
{%
\@sDTLnewrow{#2}%
\expandafter\@dtl@toks\expandafter{\@dtl@line}%
\edef\@dtl@lin@\@dtl@separator\the\@dtl@toks
\@dtl@separator}%
\dtl@entrycr=0\relax
}%
\@dtl@conditiontrue
\loop
\expandafter\@dtl@lopoff\@dtl@lin@\to
\@dtl@lin@\@dtl@thisentry
\advance\dtl@entrycr by 1\relax
\@ifundefined{\@dtl@inky@\romannumeral\dtl@entrycr}%
{%
\edef\@dtl@thiskey{\dtldefaultkey
\number\dtl@entrycr}%
\expandafter\let
\csname @dtl@inky@\romannumeral
\dtl@entrycr\endcsname\@dtl@thiskey
}%
}%
\edef\@dtl@thiskey{%
\csname @dtl@inky@\romannumeral
\dtl@entrycr\endcsname}%
}%
\expandafter\@dtl@toks\expandafter{\@dtl@thisentry}%
\edef\@do@dtlnewentry{\noexpand\@sDTLnewdbentry
{#2}{\@dtl@thiskey}{\the\@dtl@toks}}%
\@do@dtlnewentry
\ifx\@dtl@lin@\@dtl@separator
\@dtl@conditionfalse
\fi
\if@dtl@condition
\repeat
}%
}%
\ifeof\@dtl@read \@dtl@conditionfalse\fi
\if@dtl@condition
\repeat
\fi
\fi
\closein\@dtl@read
\edef\@dtl@maxcols{\expandafter
\number\csname dtlcols@#2\endcsname}%

```

```

\dtlgforint\dtl@entrycr=1\to\@dtl@maxcols\step1\do
{%
  \@ifundefined{@dtl@inhd@\romannumeral\dtl@entrycr}%
  {}%
  {%
    \expandafter\let\expandafter\@dtl@head
    \csname @dtl@inhd@\romannumeral\dtl@entrycr\endcsname
    \@dtl@toks=\expandafter{\@dtl@head}%
    \edef\@dtl@dosetheader{\noexpand\@dtl@setheaderforindex
      {#2}{\number\dtl@entrycr}{\the\@dtl@toks}}%
    \@dtl@dosetheader
  }%
}%
\endgroup
}{%
  \PackageError{datatool}{Can't load database `#2' (file `#3'
  doesn't exist)}{}%
}%
}
\newcommand*\DTLloadrawdb{%
  \let\@dtl@doreadline\@dtl@readrawline
  \@dtl@loaddb
}
\begingroup
\catcode`\%=\active
\catcode`\$=\active
\catcode`\&=\active
\catcode`\~=\active
\catcode`\_=\active
\catcode`\^=\active
\catcode`\#=\active
\catcode`?=6\relax
\catcode`<=1\relax
\catcode`>=2\relax
\catcode`\{=\active
\catcode`\}= \active
\gdef\@dtl@rawread?1to?2<\relax
<<\catcode`\%=\active
\catcode`\$=\active
\catcode`\&=\active
\catcode`\~=\active
\catcode`\_=\active
\catcode`\^=\active
\catcode`\#=\active
\catcode`\{=\active
\catcode`\}= \active
\def%<\noexpand\%>\relax
\def$<\noexpand\$>\relax
\def&<\&>\relax
\def#<\#>\relax

```

```

\def~<\noexpand\textasciitilde>\relax
\def_<\noexpand\_>\relax
\def^<\noexpand\textasciicircum>\relax
\@dtl@activatebraces
\@dtl@doreadraw?1?2>>>
\gdef\@dtl@doreadraw?1?2<\relax
\begingroup\catcode\endlinechar=\active\global\read?1 to \dtl@tmp\endgroup
\expandafter\@dtl@stripeo\dtl@tmp
\let\dtl@tmp\@dtl@strippedline
\protected@xdef?2<\dtl@tmp>\relax
>
\endgroup
\begingroup
\catcode`\{=\active
\catcode`\}=\active
\catcode`<=1\relax
\catcode`>=2\relax
\gdef\@dtl@activatebraces<%
\catcode`\{=\active
\catcode`\}=\active
\def{<\noexpand\{>%
\def}<\noexpand\}>%
>%
\endgroup
\newcommand*{\DTLrawmap}[2]{%
\expandafter\@dtl@toks\expandafter{\@dtl@rawmappings}%
\ifdefempty{\@dtl@rawmappings}%
{%
\def\@dtl@rawmappings{#{1}#{2}}%
}%
{%
\def\@dtl@tmp{#{1}#{2}}%
\protected@edef\@dtl@rawmappings{\the\@dtl@toks,\@dtl@tmp}%
}%
}
\newcommand*{\@dtl@rawmappings}{}
\newcommand*{\dtl@domappings}[1]{%
\@for\@dtl@map:=\@dtl@rawmappings\do{%
\expandafter\DTLsubstituteall\expandafter#1\@dtl@map
}%
}
\newcommand*{\dtlshowdb}[1]{%
\expandafter\showthe\csname dtldb@#1\endcsname
}
\newcommand*{\dtlshowdbkeys}[1]{%
\expandafter\showthe\csname dtlkeys@#1\endcsname
}
\newcommand*{\dtlshowtype}[2]{%
DTLgetdatatype{\@dtl@type}{#1}#{2}\show\@dtl@type
}

```

30.16 Rollback v2.32 (datatool-base-2019-09-27.sty)

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datatool-base}[2019/09/27 v2.32 (NLCT)]
\RequirePackage{etoolbox}
\RequirePackage{amsmath}
\RequirePackage{xkeyval}
\RequirePackage{xfor}
\RequirePackage{ifthen}
\RequirePackage{substr}[2009/10/20]
\ifundef{\ifdtlverbose}
{
  \define@boolkey{datatool-base.sty}[dtl]{verbose}[true]{}
}%
{}
\define@choicekey{datatool-base.sty}{math}[\val\nr]{fp,pgfmath}{%
  \renewcommand*\@dtl@mathprocessor{#1}%
}
\define@boolkey{datatool-base.sty}[@dtl@]{utf8}[true]{}
\ifdef\UTFviii@two@octets
{\booltrue{@dtl@utf8}}%
{\boolfalse{@dtl@utf8}}
\newcommand*\dtlenableUTFviii{\booltrue{@dtl@utf8}}
\newcommand*\dtldisableUTFviii{\boolfalse{@dtl@utf8}}
\providecommand*\@dtl@mathprocessor{fp}
\ProcessOptionsX
\RequirePackage{datatool-\@dtl@mathprocessor}[=v2.32]
\newcommand*\dtl@message}[1]{%
  \ifdtlverbose\typeout{#1}\fi
}
\newtoks\@dtl@toks
\newcount\@dtl@tmpcount
\newlength\dtl@tmplength
\newcommand{\dtl@ifsingle}[3]{%
  \def\@dtl@arg{#1}%
  \ifdefempty{\@dtl@arg}%
  {%
    #3%
  }%
  {%
    \@dtl@ifsingle#1\@nil{#2}{#3}%
  }%
}
\def\@dtl@ifsingle#1#2\@nil#3#4{%
  \def\dtl@sg@arg{#2}%
  \ifdefempty{\dtl@sg@arg}%
  {%
    #3%
  }%
  {%

```

```

#4%
}%
}
\newcommand{\dtl@ifsingleorUTFviii}[3]{%
\ifbool{@dtl@utf8}
{%
\def\@dtl@arg{#1}%
\ifdefempty{\@dtl@arg}%
{%
#3%
}%
}%
\expandafter\dtl@if@two@octets#1\relax\relax\dtl@end@if@two@octets
{%
\dtl@getfirst@UTFviii#1\@nil\end@dtl@getfirst@UTFviii
\ifdefempty\dtl@rest{#2}{#3}%
}%
{%
\@dtl@ifsingle#1\@nil{#2}{#3}%
}%
}%
}%
\dtl@ifsingle{#1}{#2}{#3}%
}%
\newcommand{\dtlifintopenbetween}[5]{%
\ifnum#1>#2\relax
\ifnum#1<#3\relax
#4%
\else
#5%
\fi
\else
#5%
\fi
}
\newcommand{\dtlifintclosedbetween}[5]{%
\dtlifintopenbetween{#1}{#2}{#3}{#4}%
{%
\ifnum#1=#2\relax
#4%
\else
\ifnum#1=#3\relax
#4%
\else
#5%
\fi
\fi
}%
}

```

```

}
\long\def\long@collect@body#1{%
  \@envbody{\@xp#1\@xp{\the\@envbody}}%
  \edef\process@envbody{\the\@envbody\@nx\end{\@currenvir}}%
  \@envbody\@emptytoks \def\begin@stack{b}%
  \begingroup
  \@xp\let\csname\@currenvir\endcsname\long@collect@@body
  \edef\process@envbody{\@xp\@nx\csname\@currenvir\endcsname}%
  \process@envbody
}
\long\def\long@addto@envbody#1{%
  \toks@{#1}%
  \edef\@dtl@tmp{\the\@envbody\the\toks@}%
  \global\@envbody\@xp{\@dtl@tmp}%
}
\long\def\long@collect@@body#1\end#2{%
  \protected@edef\begin@stack{%
    \long@push@begins#1\begin\end \@xp\@gobble\begin@stack
  }%
  \ifx\@empty\begin@stack
    \endgroup
    \@checkend{#2}%
    \long@addto@envbody{#1}%
  \else
    \long@addto@envbody{#1\end{#2}}%
  \fi
  \process@envbody
}
\long\def\long@push@begins#1\begin#2{%
  \ifx\end#2\else b\@xp\long@push@begins\fi
}
\newcommand*{\DTLifinlist}[4]{%
  \def\@dtl@doifinlist##1,#1,##2\end@dtl@doifinlist{%
    \def\@before{##1}%
    \def\@after{##2}%
  }%
  \expandafter\@dtl@doifinlist\expandafter,#2,#1,\@nil
  \end@dtl@doifinlist
  \ifx\@after\@nil
    #4%
  \else
    #3%
  \fi
}
\newif\ifDTLlistskipempty
\DTLlistskipemptytrue
\newrobustcmd{\DTLlistelement}[2]{%
  \begingroup
  \@dtl@tmpcount=0\relax
  \@for\@dtl@element:=#1\do{%

```

```

\ifDTLlistskipempty
\ifdefempty{\@dtl@element}%
{%
\advance\@dtl@tmpcount by 1\relax%
\ifnum\@dtl@tmpcount=#2 \@dtl@element\@endfortrue\fi
}%
\else
\advance\@dtl@tmpcount by 1\relax%
\ifnum\@dtl@tmpcount=#2 \@dtl@element\@endfortrue\fi
\fi
}%
\if@endfor \else\@dtl@listelement@outofrange{#2}\fi
\endgroup
}
\newrobustcmd{\DTLfetchlistelement}[3]{%
\begingroup
\@dtl@tmpcount=0\relax
\@for\@dtl@element:=#1\do{%
\ifDTLlistskipempty
\ifdefempty{\@dtl@element}%
{%
\advance\@dtl@tmpcount by 1\relax%
\ifnum\@dtl@tmpcount=#2 \@endfortrue\fi
}%
\else
\advance\@dtl@tmpcount by 1\relax%
\ifnum\@dtl@tmpcount=#2 \@endfortrue\fi
\fi
}%
\if@endfor \else\def\@dtl@element{\@dtl@listelement@outofrange{#2}}\fi
\edef\x{%
\endgroup
\noexpand\def\noexpand#3{\expandonce\@dtl@element}%
}\x
}
\newcommand{\@dtl@listelement@outofrange}[1]{%
\PackageWarning{datatool-base}{List index '\number#1' out of range}%
}
\newrobustcmd{\DTLnumitemsinlist}[2]{%
\@dtl@tmpcount=0\relax
\@for\@dtl@element:=#1\do{%
\ifDTLlistskipempty
\ifdefempty{\@dtl@element}%
{%
\advance\@dtl@tmpcount by 1\relax}%
\else
\advance\@dtl@tmpcount by 1\relax
\fi
}
}

```

```

}%
\edef#2{\number\@dtl@tmpcount}%
}
\newcommand*\@dtl@choplast}[3]{%
\let#2\@empty
\let#3\@empty
\@for\@dtl@element:=#1\do{%
\ifdefempty{#3}%
{%
}%
}%
\ifdefempty{#2}%
{%
\expandafter\toks@\expandafter{#3}%
\edef#2{\the\toks@}%
}%
{%
\expandafter\toks@\expandafter{#3}%
\expandafter\@dtl@toks\expandafter{#2}%
\edef#2{\the\@dtl@toks,\the\toks@}%
}%
}%
\let#3=\@dtl@element%
}%
}
\newcommand*\@dtl@chopfirst}[3]{%
\let#2=\@empty
\let#3=\@empty
\@for\@dtl@element:=#1\do{%
\let#2=\@dtl@element
\@endfortrue
}%
\if@endfor
\let#3=\@forremainder
\fi
\@endforfalse
}
\newcommand{\@dtl@sortlist}[2]{%
\def\@dtl@sortedlist{}%
\@for\@dtl@currentrow:=#1\do{%
\expandafter\@dtl@insertinto\expandafter
{\@dtl@currentrow}{\@dtl@sortedlist}{#2}%
\@endforfalse}%
\let#1=\@dtl@sortedlist
}
\newcommand{\@dtl@insertinto}[3]{%
\def\@dtl@newsortedlist{}%
\@dtl@insertdonefalse
\@for\@dtl@srtelement:=#2\do{%
\if@dtl@insertdone

```

```

\expandafter\toks@\expandafter{\dtl@srtelement}%
\edef\@dtl@newstuff{\the\toks@}%
\else
\expandafter#3\expandafter{\dtl@srtelement}{#1}%
\ifnum\dtl@sortresult<0\relax
\expandafter\toks@\expandafter{\dtl@srtelement}%
\dtl@toks{#1}%
\edef\@dtl@newstuff{\the\@dtl@toks},{\the\toks@}%
\@dtl@insertdone
\else
\expandafter\toks@\expandafter{\dtl@srtelement}%
\edef\@dtl@newstuff{\the\toks@}%
\fi
\fi
\ifdefempty{\@dtl@newsortedlist}%
{%
\expandafter\toks@\expandafter{\@dtl@newstuff}%
\edef\@dtl@newsortedlist{\the\toks@}%
}%
{%
\expandafter\toks@\expandafter{\@dtl@newsortedlist}%
\expandafter\@dtl@toks\expandafter{\@dtl@newstuff}%
\edef\@dtl@newsortedlist{\the\toks@,\the\@dtl@toks}%
}%
\@endforfalse
}%
\ifdefempty{\@dtl@newsortedlist}%
{%
\@dtl@toks{#1}%
\edef\@dtl@newsortedlist{\the\@dtl@toks}%
}%
{%
\if@dtl@insertdone
\else
\expandafter\toks@\expandafter{\@dtl@newsortedlist}%
\@dtl@toks{#1}%
\edef\@dtl@newsortedlist{\the\toks@,\the\@dtl@toks}%
\fi
}%
\global\let#2=\@dtl@newsortedlist
}
\newcommand{\dtl@sortlist}[2]{%
\def\@dtl@sortedlist{}%
\@for\@dtl@currentrow:=#1\do{%
\expandafter\dtl@insertinto\expandafter
{\@dtl@currentrow}{\@dtl@sortedlist}{#2}%
\@endforfalse}%
\let#1=\@dtl@sortedlist
}
\newcommand{\dtl@insertinto}[3]{%

```

```

\def\@dtl@newsortedlist{%
\@dtl@insertdonefalse
\@for\dtl@srtelement:=#2\do{%
  \expandafter\DTLifSubString\expandafter{\dtl@srtelement}{,}
  {%
    \expandafter\toks@\expandafter{\dtl@srtelement}%
    \edef\dtl@srtelement{{\the\toks@}}%
  }%
  {%
  }
  \if@dtl@insertdone
    \let\@dtl@newstuff\dtl@srtelement
  \else
    \expandafter#3\expandafter\dtl@sortresult
    \expandafter{\dtl@srtelement}{#1}%
    \ifnum\dtl@sortresult>0\relax
      \DTLifSubString{#1}{,}%
      {%
        \@dtl@toks{#1}%
      }%
      {%
        \@dtl@toks{#1}%
      }%
      \expandafter\toks@\expandafter{\dtl@srtelement}%
      \edef\@dtl@newstuff{\the\@dtl@toks,\the\toks@}%
      \@dtl@insertdonetrue
    \else
      \expandafter\toks@\expandafter{\dtl@srtelement}%
      \edef\@dtl@newstuff{{\the\toks@}}%
      \let\@dtl@newstuff\dtl@srtelement
    \fi
  \fi
  \ifdefempty{\@dtl@newsortedlist}%
  {%
    \expandafter\toks@\expandafter{\@dtl@newstuff}%
    \edef\@dtl@newsortedlist{\the\toks@}%
  }%
  {%
    \expandafter\toks@\expandafter{\@dtl@newsortedlist}%
    \expandafter\@dtl@toks\expandafter{\@dtl@newstuff}%
    \edef\@dtl@newsortedlist{\the\toks@,\the\@dtl@toks}%
  }%
  \@endforfalse
}%
\ifdefempty{\@dtl@newsortedlist}%
{%
  \DTLifSubString{#1}{,}%
  {%
    \@dtl@toks{#1}%
  }%
}%

```

```

    {%
      \@dtl@toks{#1}%
    }%
    \edef\@dtl@newsortedlist{\the\@dtl@toks}%
  }%
  {%
    \if@dtl@insertdone
    \else
      \DTLifSubString{#1}{,}%
      {%
        \@dtl@toks{{#1}}%
      }%
      {%
        \@dtl@toks{#1}%
      }%
      \expandafter\toks\expandafter{\@dtl@newsortedlist}%
      \edef\@dtl@newsortedlist{\the\toks@\the\@dtl@toks}%
    \fi
  }%
  \global\let#2=\@dtl@newsortedlist
}
\newcommand*\@edtlininsertinto[3]{%
  \protected@edef\dtl@srtelement{#1}%
  \expandafter\dtlininsertinto\expandafter{\dtl@srtelement}{#2}{#3}%
}
\newif\if@dtl@insertdone
\newcount\dtl@sortresult
\newcommand*\@DTLlistformatsep}{, }
\newcommand*\@DTLlistformatoxford}{ }
\ifdef\andname
  {\newcommand*\@DTLlandname}{\andname}}
  {\newcommand*\@DTLlandname}{\&}}
\newcommand*\@DTLlistformatlastsep}{ \@DTLlandname\space}
\newcommand*\@DTLlistformatitem}[1]{#1}
\newcommand*\@dtl@formatlist@handler}[1]{%
  \@dtl@formatlist@itemsep
  \@dtl@formatlist@lastitem
  \renewcommand{\@dtl@formatlist@lastitem}{%
    \renewcommand{\@dtl@formatlist@itemsep}{%
      \@DTLlistformatsep
      \renewcommand*\@dtl@formatlist@prelastitemsep}{%
        \@DTLlistformatoxford}}}%
    \renewcommand{\@dtl@formatlist@prelastitem}{%
      \@dtl@formatlist@prelastitemsep
      \@DTLlistformatlastsep}%
    \@DTLlistformatitem{#1}%
  }%
}
\newrobustcmd*\@DTLformatlist}{%
  \@ifstar{\s@dtlformatlist}{\@dtlformatlist}%
}

```

```

}
\newcommand*{\s@dtlformatlist}[1]{%
  \def\@dtl@formatlist@itemsep{}%
  \def\@dtl@formatlist@lastitem{}%
  \def\@dtl@formatlist@prelastitem{}%
  \def\@dtl@formatlist@prelastitemsep{}%
  \@for\@dtl@formatlist@item:=#1\do{%
    \ifDTLlistskipempty
      \ifdefempty{\@dtl@formatlist@item}%
        {}%
      {\expandafter\@dtl@formatlist@handler\expandafter{\@dtl@formatlist@item}}%
    \else
      \expandafter\@dtl@formatlist@handler\expandafter{\@dtl@formatlist@item}%
    \fi
  }%
  \@dtl@formatlist@prelastitem\@dtl@formatlist@lastitem
}
\newcommand*{\@dtlformatlist}[1]{\s@dtlformatlist{#1}}
\newcommand{\@dtl@toks@gput@right@cx}[2]{%
  \def\@dtl@toks@name{#1}%
  \edef\@dtl@stuff{#2}%
  \global\csname\@dtl@toks@name\endcsname\expandafter
  \expandafter\expandafter{\expandafter\the
  \csname\expandafter\@dtl@toks@name\expandafter\endcsname\@dtl@stuff}%
}
\newcommand{\@dtl@toks@gconcat@middle@cx}[4]{%
  \def\@dtl@toks@name{#1}%
  \edef\@dtl@stuff{#3}%
  \global\csname\@dtl@toks@name\endcsname\expandafter\expandafter
  \expandafter\expandafter\expandafter
  \expandafter\expandafter{\expandafter\expandafter\expandafter
  \the\expandafter\expandafter\expandafter#2%
  \expandafter\@dtl@stuff\the#4}%
}
\newcount\@dtl@numgrpsepcount
\newcommand*{\@dtl@decimal}{.}
\newcommand*{\@dtl@numbergroupchar}{,}
\newcommand*{\DTLsetnumberchars}[2]{%
  \renewcommand*{\@dtl@numbergroupchar}{#1}%
  \renewcommand*{\@dtl@decimal}{#2}%
  \@dtl@construct@getnums
  \@dtl@construct@stripnumgrpchar{#1}%
}
\edef\@dtl@construct@getintfrac#1{%
  \noexpand\def\noexpand\@dtl@getintfrac##1#1##2\noexpand\relax{%
    \noexpand\@dtl@get@intpart{##1}%
    \noexpand\def\noexpand\@dtl@fracpart{##2}%
    \noexpand\ifdefempty{\noexpand\@dtl@fracpart}
    {%
      \noexpand\def\noexpand\@dtl@fracpart{0}%

```

```

}%
{%
  \noexpand\@dtl@getfracpart##2\noexpand\relax
  \noexpand\@dtl@choptrailingzeroes{\noexpand\@dtl@fracpart}%
}%
}%
\noexpand\def\noexpand\@dtl@getfracpart##1#1\noexpand\relax{%
  \noexpand\def\noexpand\@dtl@fracpart{##1}%
}%
\noexpand\def\noexpand\DTLconverttodecimal##1##2{%
  \noexpand\dtl@ifsingle{##1}%
  {%
    \noexpand\expandafter\noexpand\toks@\noexpand\expandafter{##1}%
    \noexpand\edef\noexpand\@dtl@tmp{\noexpand\the\noexpand\toks@}%
  }%
  {%
    \noexpand\def\noexpand\@dtl@tmp{##1}%
  }%
  \noexpand\@dtl@standardize@currency\noexpand\@dtl@tmp
  \noexpand\ifdefempty{\noexpand\@dtl@org@currency}%
  {%
  }%
  {%
    \noexpand\let\noexpand\@dtl@currency\noexpand\@dtl@org@currency
  }%
  \noexpand\expandafter
  \noexpand\@dtl@getintfrac\noexpand\@dtl@tmp#1\noexpand\relax
  \noexpand\edef##2{\noexpand\@dtl@intpart.\noexpand\@dtl@fracpart}%
}%
}
\newcommand*{\@dtl@construct@getnums}{%
  \expandafter\@dtl@construct@getintfrac\expandafter{\@dtl@decimal}%
}
\newcommand*{\@dtl@get@intpart}[1]{%
  \@dtl@tmpcount=1\relax
  \def\@dtl@intpart{#1}%
  \ifx\@dtl@intpart\@empty
    \def\@dtl@intpart{0}%
  \else
    \def\@dtl@intpart{}%
    \@dtl@get@int@part#1.\relax%
  \fi
  \ifnum\@dtl@tmpcount<0\relax
    \edef\@dtl@intpart{-\@dtl@intpart}%
  \fi
  \@dtl@strip@numgrpchar{\@dtl@intpart}%
}
\def\@dtl@get@int@part#1#2\relax{%
  \def\@dtl@argi{#1}%
  \def\@dtl@argii{#2}%
}

```

```

\ifx\protect#1\relax%
  \let\@dtl@get@nextintpart=\@dtl@get@int@part
\else
  \expandafter\ifx\@dtl@argi\${%
    \let\@dtl@get@nextintpart=\@dtl@get@int@part
  \else
    \ifx-#1%
      \multiply\@dtl@tmpcount by -1\relax
      \let\@dtl@get@nextintpart=\@dtl@get@int@part
    \else
      \if\@dtl@argi+%
        \let\@dtl@get@nextintpart=\@dtl@get@int@part
      \else
        \def\@dtl@intpart{#1}%
        \ifx.\@dtl@argii
          \let\@dtl@get@nextintpart=\@gobble
        \else
          \let\@dtl@get@nextintpart=\@dtl@get@next@intpart
        \fi
      \fi
    \fi
  \fi
  \fi
  \fi
  \@dtl@get@nextintpart#2\relax
}
\def\@dtl@get@next@intpart#1.\relax{%
  \edef\@dtl@intpart{\@dtl@intpart#1}%
}
\newcommand*\@dtl@choptrailingzeroes}[1]{%
  \def\@dtl@tmpcpz{}%
  \expandafter\@dtl@chop@trailingzeroes#1\@nil%
  \let#1=\@dtl@tmpcpz
}
\def\@dtl@chop@trailingzeroes#1#2\@nil{%
  \dtlifnumeq{#2}{0}%
  {%
    \edef\@dtl@tmpcpz{\@dtl@tmpcpz#1}%
    \let\@dtl@chopzeroesnext=\@dtl@gobbletonil
  }%
  {%
    \edef\@dtl@tmpcpz{\@dtl@tmpcpz#1}%
    \let\@dtl@chopzeroesnext=\@dtl@chop@trailingzeroes
  }%
  \@dtl@chopzeroesnext#2\@nil
}
\def\@dtl@gobbletonil#1\@nil{}
\newcommand*\@dtl@truncatedecimal}[1]{%
  \expandafter\@dtl@truncatedecimal#1.\@nil#1%
}
\def\@dtl@truncatedecimal#1.#2\@nil#3{%

```

```

\def#3{#1}%
}
\newcommand*{\@dtl@strip@numgrpchar}[1]{%
\def\@dtl@stripped{}%
\edef\@dtl@do@strip@numgrpchar{%
\noexpand\@dtl@strip@numgrpchar#1\@dtl@numbergroupchar
\noexpand\relax
}%
\@dtl@do@strip@numgrpchar
\let#1=\@dtl@stripped
}
\edef\@dtl@construct@strip@numgrpchar#1{%
\noexpand\def\noexpand\@dtl@strip@numgrpchar##1#1##2\noexpand\relax{%
\noexpand\expandafter\noexpand\toks@\noexpand\expandafter
{\noexpand\@dtl@stripped}%
\noexpand\edef\noexpand\@dtl@stripped{%
\noexpand\the\noexpand\toks@
##1%
}%
\noexpand\def\noexpand\@dtl@tmp{##2}%
\noexpand\ifx\noexpand\@dtl@tmp\noexpand\@empty
\noexpand\let\noexpand\@dtl@next=\noexpand\relax
\noexpand\else
\noexpand\let\noexpand\@dtl@next=\noexpand\@dtl@strip@numgrpchar
\noexpand\fi
\noexpand\@dtl@next##2\noexpand\relax
}%
}
\newcommand*{\DTLdecimalto locale}[2]{%
\edef\@dtl@tmpdtl{#1}%
\expandafter\@dtl@decimalto locale\@dtl@tmpdtl.\relax
\dtl@ifnumeq{\@dtl@fracpart}{0}%
{%
\edef#2{\@dtl@intpart}%
}%
{%
\edef#2{\@dtl@intpart\@dtl@decimal\@dtl@fracpart}%
}%
}
\def\@dtl@decimalto locale#1.#2\relax{%
\@dtl@decimalto localeint{#1}%
\def\@dtl@fracpart{#2}%
\ifdefempty\@dtl@fracpart
{%
\def\@dtl@fracpart{0}%
}%
{%
\@dtl@decimalto localefrac#2\relax
}%
}
}

```

```

\def\@dtl@decimal@to@localeint#1{%
  \@dtl@tmpcount=0\relax
  \@dtl@countdigits#1.\relax
  \@dtl@numgrpsepcount=\@dtl@tmpcount\relax
  \divide\@dtl@numgrpsepcount by 3\relax
  \multiply\@dtl@numgrpsepcount by 3\relax
  \advance\@dtl@numgrpsepcount by -\@dtl@tmpcount\relax
  \ifnum\@dtl@numgrpsepcount<0\relax
    \advance\@dtl@numgrpsepcount by 3\relax
  \fi
  \def\@dtl@intpart{}%
  \@dtl@decimal@to@localeint#1.\relax
}
\def\@dtl@countdigits#1#2\relax{%
  \advance\@dtl@tmpcount by 1\relax
  \ifx.#2\relax
    \let\@dtl@countnext=\@gobble
  \else
    \let\@dtl@countnext=\@dtl@countdigits
  \fi
  \@dtl@countnext#2\relax
}
\def\@dtl@decimal@to@localeint#1#2\relax{%
  \advance\@dtl@numgrpsepcount by 1\relax
  \ifx.#2\relax
    \edef\@dtl@intpart{\@dtl@intpart#1}%
    \let\@dtl@localeintnext=\@gobble
  \else
    \ifnum\@dtl@numgrpsepcount=3\relax
      \edef\@dtl@intpart{\@dtl@intpart#1\@dtl@numbergroupchar}%
      \@dtl@numgrpsepcount=0\relax
    \else
      \ifnum\@dtl@numgrpsepcount>3\relax
        \@dtl@numgrpsepcount=0\relax
      \fi
      \edef\@dtl@intpart{\@dtl@intpart#1}%
    \fi
    \let\@dtl@localeintnext=\@dtl@decimal@to@localeint
  \fi
  \@dtl@localeintnext#2\relax
}
\def\@dtl@decimal@to@localefrac#1.\relax{%
  \count@=0\relax
  \@dtl@digitcount#1\relax
  \ifnum\count@>9\relax
    \@dtl@chopexcessfrac#1000000000\@nil
  \else
    \def\@dtl@fracpart{#1}%
  \fi
}

```

```

\newcommand*{\@dtl@chopexcessfrac}[9]{%
  \def\@dtl@fracpart{#1#2#3#4#5#6#7#8#9}%
  \@dtl@gobbletonil
}
\newcommand*{\@dtl@digitcount}[1]{%
  \ifx\relax#1\relax
    \let\@dtl@digitcountnext\relax
  \else
    \advance\count@ by \@ne
    \let\@dtl@digitcountnext\@dtl@digitcount
  \fi
  \@dtl@digitcountnext
}
\newcommand*{\DTLdecimaltocurrency}[2]{%
  \edef\@dtl@tmpdtl{#1}%
  \expandafter\@dtl@decimaltolocale\@dtl@tmpdtl.\relax
  \dtl@truncatedecimal\@dtl@tmpdtl
  \@dtl@tmpcount=\@dtl@tmpdtl\relax
  \expandafter\@dtl@toks\expandafter{\@dtl@currency}%
  \dtl@ifnumeq{\@dtl@fracpart}{0}%
  {%
    \ifnum\@dtl@tmpcount<0\relax
      \@dtl@tmpcount = -\@dtl@tmpcount\relax
      \edef#2{-\the\@dtl@toks\the\@dtl@tmpcount\@dtl@decimal00}%
    \else
      \edef#2{\the\@dtl@toks\@dtl@intpart\@dtl@decimal00}%
    \fi
  }%
  {%
    \ifnum\@dtl@tmpcount<0\relax
      \@dtl@tmpcount = -\@dtl@tmpcount\relax
      \ifnum\@dtl@fracpart<10\relax
        \edef#2{%
          -\the\@dtl@toks\number\@dtl@tmpcount
          \@dtl@decimal\@dtl@fracpart0%
        }%
      \else
        \edef#2{%
          -\the\@dtl@toks\number\@dtl@tmpcount
          \@dtl@decimal\@dtl@fracpart
        }%
      \fi
    \else
      \ifnum\@dtl@fracpart<10\relax
        \edef#2{\the\@dtl@toks\@dtl@intpart\@dtl@decimal\@dtl@fracpart0}%
      \else
        \edef#2{\the\@dtl@toks\@dtl@intpart\@dtl@decimal\@dtl@fracpart}%
      \fi
    \fi
  }%
}

```

```

}
\@dtl@construct@getnums
\expandafter\@dtl@construct@stripnumgrpchar\expandafter
  {\@dtl@numbergroupchar}
\newcommand*{\@dtl@currencies}{\$, \pounds}
\newcommand*{\DTLnewcurrencysymbol}[1]{%
  \expandafter\toks@\expandafter{\@dtl@currencies}%
  \@dtl@toks{#1}%
  \edef\@dtl@currencies{\the\@dtl@toks,\the\toks@}%
}
\AtBeginDocument{%
  \@ifundefined{texteuro}{\DTLnewcurrencysymbol{\texteuro}}%
  \@ifundefined{textdollar}{\DTLnewcurrencysymbol{\textdollar}}%
  \@ifundefined{textstirling}{\DTLnewcurrencysymbol{\textstirling}}%
  \@ifundefined{textyen}{\DTLnewcurrencysymbol{\textyen}}%
  \@ifundefined{textwon}{\DTLnewcurrencysymbol{\textwon}}%
  \@ifundefined{textcurrency}{\DTLnewcurrencysymbol{\textcurrency}}%
  \@ifundefined{euro}{\DTLnewcurrencysymbol{\euro}}%
  \@ifundefined{yen}{\DTLnewcurrencysymbol{\yen}}%
}
\newcommand{\@dtl@standardize@currency}[1]{%
  \def\@dtl@org@currency{%
    \@for\@dtl@thiscurrency:=\@dtl@currencies\do{%
      \expandafter\toks@\expandafter{\@dtl@thiscurrency}%
      \edef\@dtl@dosubs{\noexpand\DTLsubstitute{\noexpand#1}%
        {\the\toks@}\noexpand\$}%
      \@dtl@dosubs
      \ifdefempty{\@dtl@replaced}%
        {%
        }%
        {%
          \let\@dtl@org@currency=\@dtl@replaced
          \@endfortrue
        }%
      }%
    }%
  }%
  \@endforfalse
}
\newcommand*{\@dtl@currency}{\$}
\newcommand*{\DTLsetdefaultcurrency}[1]{%
  \renewcommand*{\@dtl@currency}{#1}%
}
\newcommand*{\DTLadd}[3]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \DTLconverttodecimal{#3}{\@dtl@numii}%
  \dtladd{\@dtl@tmp}{\@dtl@numi}{\@dtl@numii}%
  \ifdefempty{\@dtl@replaced}%
    {%
      \DTLdecimalto locale{\@dtl@tmp}{#1}%
    }%
  {%
}

```

```

        \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
    }%
}
\newcommand*\DTLgadd}[3]{%
    \DTLadd{\@dtl@tmpii}{#2}{#3}%
    \global\let#1=\@dtl@tmpii
}
\newcommand*\DTLaddall}[2]{%
    \def\@dtl@sum{0}%
    \@for\@dtl@thisval:=#2\do{%
        \expandafter\DTLconverttodecimal\expandafter{\@dtl@thisval}{\@dtl@num}%
        \dtladd{\@dtl@sum}{\@dtl@sum}{\@dtl@num}%
    }%
    \ifdefempty{\@dtl@replaced}%
    {%
        \DTLdecimaltolocale{\@dtl@sum}{#1}%
    }%
    {%
        \DTLdecimaltocurrency{\@dtl@sum}{#1}%
    }%
}
\newcommand*\DTLgaddall}[2]{%
    \DTLaddall{\@dtl@tmpi}{#2}%
    \global\let#1=\@dtl@tmpi
}
\newcommand*\DTLsub}[3]{%
    \DTLconverttodecimal{#2}{\@dtl@numi}%
    \DTLconverttodecimal{#3}{\@dtl@numii}%
    \dtlsub{\@dtl@tmp}{\@dtl@numi}{\@dtl@numii}%
    \ifdefempty{\@dtl@replaced}%
    {%
        \DTLdecimaltolocale{\@dtl@tmp}{#1}%
    }%
    {%
        \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
    }%
}
\newcommand*\DTLgsub}[3]{%
    \DTLsub{\@dtl@tmpii}{#2}{#3}%
    \global\let#1=\@dtl@tmpii
}
\newcommand*\DTLmul}[3]{%
    \let\@dtl@thisreplaced=@empty
    \DTLconverttodecimal{#2}{\@dtl@numi}%
    \ifdefempty{\@dtl@replaced}%
    {%
    }%
    {%
        \let\@dtl@thisreplaced=@dtl@replaced
    }%
}

```

```

\DTLconverttodecimal{#3}{\@dtl@numii}%
\ifdefempty{\@dtl@replaced}%
{%
}%
{%
  \let\@dtl@thisreplaced=\@dtl@replaced
}%
\dtl@mul{\@dtl@tmp}{\@dtl@numi}{\@dtl@numii}%
\ifdefempty{\@dtl@thisreplaced}%
{%
  \DTLdecimaltoLocale{\@dtl@tmp}{#1}%
}%
{%
  \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
}%
}
\newcommand*\DTLgmul}[3]{%
  \DTLmul{\@dtl@tmpii}{#2}{#3}%
  \global\let#1=\@dtl@tmpii
}
\newcommand*\DTLdiv}[3]{%
  \let\@dtl@thisreplaced=@empty
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \ifdefempty{\@dtl@replaced}%
  {%
  }%
  {%
    \let\@dtl@thisreplaced=\@dtl@replaced
  }%
  \DTLconverttodecimal{#3}{\@dtl@numii}%
  \dtl@div{\@dtl@tmp}{\@dtl@numi}{\@dtl@numii}%
  \ifdefempty{\@dtl@thisreplaced}%
  {%
    \DTLdecimaltoLocale{\@dtl@tmp}{#1}%
  }%
  {%
    \ifdefequal{\@dtl@thisreplaced}{\@dtl@replaced}%
    {%
      \DTLdecimaltoLocale{\@dtl@tmp}{#1}%
    }%
    {%
      \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
    }%
  }%
}
}
\newcommand*\DTLgdiv}[3]{%
  \DTLdiv{\@dtl@tmpii}{#2}{#3}%
  \global\let#1=\@dtl@tmpii
}
\newcommand*\DTLabs}[2]{%

```

```

\DTLconverttodecimal{#2}{\@dtl@numi}%
\dtlabs{\@dtl@tmp}{\@dtl@numi}%
\ifdefempty{\@dtl@replaced}%
{%
  \DTLdecimaltolocale{\@dtl@tmp}{#1}%
}%
{%
  \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
}%
}
\newcommand*{\DTLgabs}[2]{%
  \DTLabs{\@dtl@tmpii}{#2}%
  \global\let#1=\@dtl@tmpii
}
\newcommand*{\DTLneg}[2]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \dtlneg{\@dtl@tmp}{\@dtl@numi}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@tmp}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
  }%
}
\newcommand*{\DTLgneg}[2]{%
  \DTLneg{\@dtl@tmpii}{#2}%
  \global\let#1=\@dtl@tmpii
}
\newcommand*{\DTLsqrt}[2]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \dtlroot{\@dtl@tmpi}{\@dtl@numi}{2}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@tmpi}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@tmpi}{#1}%
  }%
}
\newcommand*{\DTLsqrt}[2]{%
  \DTLsqrt{\@dtl@tmpii}{#2}%
  \global\let#1=\@dtl@tmpii
}
\newcommand*{\DTLmin}[3]{%
  \DTLconverttodecimal{#2}{\@dtl@numi}%
  \DTLconverttodecimal{#3}{\@dtl@numii}%
  \dtlifnumlt{\@dtl@numi}{\@dtl@numii}%
  {%
    \dtl@ifsingle{#2}%
  }%
}

```

```

        {\let#1=#2}%
        {\def#1{#2}}%
    }%
    {%
    \dtl@ifsingle{#3}%
    {\let#1=#3}%
    {\def#1{#3}}%
    }%
}
\newcommand*{\DTLgmin}[3]{%
    \DTLmin{\@dtl@tmpii}{#2}{#3}%
    \global\let#1=\@dtl@tmpii
}
\newcommand*{\DTLminall}[2]{%
    \let\@dtl@min=\@empty
    \@for\dtl@thisval:=#2\do{%
        \expandafter\DTLconverttodecimal\expandafter{\dtl@thisval}{\@dtl@num}%
        \ifdefempty{\@dtl@min}%
        {%
            \let\@dtl@min=\@dtl@num
        }%
        {%
            \dtlmin{\@dtl@min}{\@dtl@min}{\@dtl@num}%
        }%
    }%
    \ifdefempty{\@dtl@replaced}%
    {%
        \DTLdecimaltolocale{\@dtl@min}{#1}%
    }%
    {%
        \DTLdecimaltocurrency{\@dtl@min}{#1}%
    }%
}
\newcommand*{\DTLgminall}[2]{%
    \DTLminall{\@dtl@tmpi}{#2}%
    \global\let#1=\@dtl@tmpi
}
\newcommand*{\DTLmax}[3]{%
    \DTLconverttodecimal{#2}{\@dtl@numi}%
    \DTLconverttodecimal{#3}{\@dtl@numii}%
    \dtlmax{\@dtl@tmp}{\@dtl@numi}{\@dtl@numii}%
    \dtlifnumgt{\@dtl@numi}{\@dtl@numii}%
    {%
        \dtl@ifsingle{#2}%
        {\let#1=#2}%
        {\def#1{#2}}%
    }%
    {%
        \dtl@ifsingle{#3}%
        {\let#1=#3}%
    }%
}

```

```

    {\def#1{#3}}%
  }%
}
\newcommand*{\DTLgmax}[3]{%
  \DTLmax{\@dtl@tmpii}{#2}{#3}%
  \global\let#1=\@dtl@tmpii
}
\newcommand*{\DTLmaxall}[2]{%
  \let\@dtl@max=\@empty
  \@for\@dtl@thisval:=#2\do{%
    \expandafter\DTLconverttodecimal\expandafter{\@dtl@thisval}{\@dtl@num}%
    \ifdefempty{\@dtl@max}%
    {%
      \let\@dtl@max\@dtl@num
    }%
    {%
      \dtlmax{\@dtl@max}{\@dtl@max}{\@dtl@num}%
    }%
  }%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@max}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@max}{#1}%
  }%
}
\newcommand*{\DTLgmaxall}[2]{%
  \DTLmaxall{\@dtl@tmpi}{#2}%
  \global\let#1=\@dtl@tmpi
}
\newcommand*{\DTLmeanforall}[2]{%
  \def\@dtl@mean{0}%
  \def\@dtl@n{0}%
  \@for\@dtl@thisval:=#2\do{%
    \expandafter\DTLconverttodecimal\expandafter{\@dtl@thisval}{\@dtl@num}%
    \dtladd{\@dtl@mean}{\@dtl@mean}{\@dtl@num}%
    \dtladd{\@dtl@n}{\@dtl@n}{1}%
  }%
  \dtldiv{\@dtl@mean}{\@dtl@mean}{\@dtl@n}%
  \ifdefempty{\@dtl@replaced}%
  {%
    \DTLdecimaltolocale{\@dtl@mean}{#1}%
  }%
  {%
    \DTLdecimaltocurrency{\@dtl@mean}{#1}%
  }%
}
\newcommand*{\DTLgmeanforall}[2]{%
  \DTLmeanforall{\@dtl@tmpi}{#2}%
}

```

```

\global\let#1=\@dtl@tmpi
}
\newcommand*{\DTLvarianceforall}[2]{%
\def\@dtl@mean{0}%
\def\@dtl@n{0}%
\let\@dtl@decvals=\@empty
\@for\@dtl@thisval:=#2\do{%
\expandafter\DTLconverttodecimal\expandafter{\@dtl@thisval}{\@dtl@num}%
\ifdefempty{\@dtl@decvals}%
{%
\let\@dtl@decvals=\@dtl@num
}%
}%
\expandafter\toks@\expandafter{\@dtl@decvals}%
\edef\@dtl@decvals{\the\toks@,\@dtl@num}%
}%
\dtladd{\@dtl@mean}{\@dtl@mean}{\@dtl@num}%
\dtladd{\@dtl@n}{\@dtl@n}{1}%
}%
\dtldiv{\@dtl@mean}{\@dtl@mean}{\@dtl@n}%
\def\@dtl@var{0}%
\@for\@dtl@num:=\@dtl@decvals\do{%
\dtlsub{\@dtl@diff}{\@dtl@num}{\@dtl@mean}%
\dtlmul{\@dtl@diff}{\@dtl@diff}{\@dtl@diff}%
\dtladd{\@dtl@var}{\@dtl@var}{\@dtl@diff}%
}%
\dtldiv{\@dtl@var}{\@dtl@var}{\@dtl@n}%
\ifdefempty{\@dtl@replaced}%
{%
\DTLdecimaltolocale{\@dtl@var}{#1}%
}%
{%
\DTLdecimaltocurrency{\@dtl@var}{#1}%
}%
}
\newcommand*{\DTLgvarianceforall}[2]{%
\DTLvarianceforall{\@dtl@tmpi}{#2}%
\global\let#1=\@dtl@tmpi
}
\newcommand*{\DTLsdforall}[2]{%
\def\@dtl@mean{0}%
\def\@dtl@n{0}%
\let\@dtl@decvals=\@empty
\@for\@dtl@thisval:=#2\do{%
\expandafter\DTLconverttodecimal\expandafter{\@dtl@thisval}{\@dtl@num}%
\ifdefempty{\@dtl@decvals}%
{%
\let\@dtl@decvals=\@dtl@num
}%
}%
}

```

```

\expandafter\toks@\expandafter{\@dtl@decvals}%
\edef\@dtl@decvals{\the\toks@,\@dtl@num}%
}%
\dtladd{\@dtl@mean}{\@dtl@mean}{\@dtl@num}%
\dtladd{\@dtl@n}{\@dtl@n}{1}%
}%
\dtldiv{\@dtl@mean}{\@dtl@mean}{\@dtl@n}%
\def\@dtl@sd{0}%
\@for\@dtl@num:=\@dtl@decvals\do{%
\dtlsub{\@dtl@diff}{\@dtl@num}{\@dtl@mean}%
\dtlmul{\@dtl@diff}{\@dtl@diff}{\@dtl@diff}%
\dtladd{\@dtl@sd}{\@dtl@sd}{\@dtl@diff}%
}%
\dtldiv{\@dtl@sd}{\@dtl@sd}{\@dtl@n}%
\dtlroot{\@dtl@sd}{\@dtl@sd}{2}%
\ifdefempty{\@dtl@replaced}%
{%
\DTLdecimaltoLocale{\@dtl@sd}{#1}%
}%
{%
\DTLdecimaltocurrency{\@dtl@sd}{#1}%
}%
}
\newcommand*\@DTLgsdforall}[2]{%
\DTLsdforall{\@dtl@tmpi}{#2}%
\global\let#1=\@dtl@tmpi
}
\newcommand*\@DTLround}[3]{%
\DTLconverttodecimal{#2}{\@dtl@numi}%
\dtlround{\@dtl@tmp}{\@dtl@numi}{#3}%
\ifdefempty{\@dtl@replaced}%
{%
\DTLdecimaltoLocale{\@dtl@tmp}{#1}%
}%
{%
\DTLdecimaltocurrency{\@dtl@tmp}{#1}%
}%
}
\newcommand*\@DTLground}[3]{%
\DTLround{\@dtl@tmpii}{#2}{#3}%
\global\let#1=\@dtl@tmpii
}
\newcommand*\@DTLtrunc}[3]{%
\DTLconverttodecimal{#2}{\@dtl@numi}%
\dtltrunc{\@dtl@tmp}{\@dtl@numi}{#3}%
\ifdefempty{\@dtl@replaced}%
{%
\DTLdecimaltoLocale{\@dtl@tmp}{#1}%
}%
{%
}

```

```

        \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
    }%
}
\newcommand*\DTLgtrunc}[3]{%
    \DTLtrunc{\@dtl@tmpii}{#2}{#3}%
    \global\let#1=\@dtl@tmpii
}
\newcommand*\DTLclip}[2]{%
    \DTLconverttodecimal{#2}{\@dtl@numi}%
    \dtlclip{\@dtl@tmp}{\@dtl@numi}%
    \ifdefempty{\@dtl@replaced}%
    {%
        \DTLdecimaltolocale{\@dtl@tmp}{#1}%
    }%
    {%
        \DTLdecimaltocurrency{\@dtl@tmp}{#1}%
    }%
}
\newcommand*\DTLgclip}[3]{%
    \DTLclip{\@dtl@tmpii}{#2}%
    \global\let#1=\@dtl@tmpii
}
\newcommand*\DTLinitials[1]{%
    \def\dtl@initialscmd{%
        \dtl@subnobrsp{#1}{\dtl@string}%
        \DTLsubstituteall{\dtl@string}{~}{ }%
        \DTLsubstituteall{\dtl@string}{\ }{ }%
        \DTLsubstituteall{\dtl@string}{\space}{ }%
        \expandafter\dtl@initials\dtl@string{} \@nil%
        \dtl@initialscmd
    }%
}
\edef\dtl@construct@subnobrsp{%
    \noexpand\def\noexpand\@dtl@subnobrsp##1\noexpand\protect
    \expandafter\noexpand\csname nobreakspace \endcsname ##2{%
        \noexpand\toks@{##1}%
        \noexpand\expandafter\noexpand\@dtl@toks\noexpand\expandafter{%
            \noexpand\@dtl@string}%
        \noexpand\edef\noexpand\@dtl@string{\noexpand\the\noexpand\@dtl@toks
            \noexpand\the\noexpand\toks@}%
        \noexpand\def\noexpand\@dtl@tmp{##2}%
        \noexpand\ifx\noexpand\@dtl@tmp\noexpand\@nnil
            \noexpand\let\noexpand\@dtl@subnobrspnext=\noexpand\relax
        \noexpand\else
            \noexpand\toks@{ }%
            \noexpand\expandafter\noexpand\@dtl@toks\noexpand\expandafter{%
                \noexpand\@dtl@string}%
            \noexpand\edef\noexpand\@dtl@string{\noexpand\the\noexpand\@dtl@toks
                \noexpand\the\noexpand\toks@}%
            \noexpand\let\noexpand\@dtl@subnobrspnext=\noexpand\@dtl@subnobrsp
        \noexpand\fi
    }%
}

```

```

\noexpand\@dtl@subnobrspnext
}%
\noexpand\def\noexpand\dtl@subnobrsp##1##2{%
\noexpand\def\noexpand\@dtl@string{%
\noexpand\@dtl@subnobrsp ##1\noexpand\protect\expandafter\noexpand
\csname nobreakspace \endcsname \noexpand\@nil
\noexpand\let##2=\noexpand\@dtl@string
}%
}
\dtl@construct@subnobrsp
\newcommand*\DTLstoreinitials}[2]{%
\def\dtl@initialscmd{%
\dtl@subnobrsp{#1}\@dtl@string}%
\DTLsubstituteall{\@dtl@string}{~}{ }%
\DTLsubstituteall{\@dtl@string}{\ }{ }%
\DTLsubstituteall{\@dtl@string}{\space}{ }%
\expandafter\dtl@initials\@dtl@string{ } \@nil
\let#2=\dtl@initialscmd
}
\def\dtl@initials#1#2 #3{%
\dtl@ifsingle{#1}%
{%
\ifcat\noexpand#1\relax\relax
\def\@dtl@donextinitials{\@dtl@initials#2 {#3}}%
\else
\def\@dtl@donextinitials{\@dtl@initials#1#2 {#3}}%
\fi
}%
}%
\def\@dtl@donextinitials{\@dtl@initials{#1}#2 {#3}}%
}%
\@dtl@donextinitials
}
\def\@dtl@initials#1#2 #3{%
\dtl@initialshyphen#2-{\dtl@endhyp
\expandafter\@dtl@toks\expandafter{\dtl@initialscmd}%
\toks@{#1}%
\ifdefempty{\dtl@inithyphen}%
{%
}%
}%
\edef\dtl@initialscmd{\the\@dtl@toks\the\toks@}%
\expandafter\@dtl@toks\expandafter{\dtl@initialscmd}%
\expandafter\toks@\expandafter{\dtl@inithyphen}%
}%
\def\dtl@tmp{#3}%
\ifx\@nnil\dtl@tmp
\edef\dtl@initialscmd{\the\@dtl@toks\the\toks@\DTLafterinitials}%
\let\dtl@initialsnext=\@gobble
\else

```

```

\edef\dtl@initialscmd{\the\@dtl@toks\the\toks@\DTLbetweeninitials}%
\let\dtl@initialsnext=\dtl@initials
\fi
\dtl@initialsnext{#3}%
}
\def\dtl@initialshyphen#1-#2#3\dtl@endhyp{%
\def\dtl@inithyphen{#2}%
\ifdefempty{\dtl@inithyphen}%
{%
}%
}%
\edef\dtl@inithyphen{%
\DTLafterinitialbeforehyphen\DTLinitialhyphen#2}%
}%
}
\newcommand*\{DTLafterinitials}\{.}
\newcommand*\{DTLbetweeninitials}\{.}
\newcommand*\{DTLafterinitialbeforehyphen}\{.}
\newcommand*\{DTLinitialhyphen}\{-}
\newcommand*\{DTLifAllUpperCase}[3]{%
\protected@edef\dtl@tuc{#1}%
\expandafter\dtl@testifuppercase\dtl@tuc\@nil\relax
\if@dtl@condition#2\else#3\fi
}
\def\dtl@testifuppercase#1#2{%
\def\dtl@argi{#1}%
\def\dtl@argii{#2}%
\def\dtl@tc@rest{}%
\ifx\dtl@argi\@nnil
\let\dtl@testifuppernext=\@nnil
\else
\ifx#1\protect
\let\dtl@testifuppernext=\dtl@testifuppercase
\else
\ifx\uppercase#1\relax
\@dtl@conditiontrue
\def\dtl@tc@rest{}%
\let\dtl@testifuppernext=\relax
\else
\edef\dtl@tc@arg{\string#1}%
\expandafter\dtl@test@ifuppercase\dtl@tc@arg\end
\ifx\dtl@argii\@nnil
\let\dtl@testifuppernext=\@dtl@gobbletonil
\fi
\fi
\fi
\ifx\dtl@testifuppernext\relax
\edef\dtl@dotestifuppernext{%
\noexpand\dtl@testifuppercase}%

```

```

\else
\ifx\dtl@testifuppernext\@nnil
\edef\dtl@dotestifuppernext{#2}%
\else
\expandafter\toks@\expandafter{\dtl@tc@rest}%
\@dtl@toks{#2}%
\edef\dtl@dotestifuppernext{%
\noexpand\dtl@testifuppernext\the\toks@\the\@dtl@toks}%
\fi
\fi
\dtl@dotestifuppernext
}
\def\dtl@test@ifuppercase#1#2\end{%
\def\dtl@tc@rest{#2}%
\IfSubStringInString{\string\MakeUppercase}{#1#2}%
{%
\@dtl@conditiontrue
\def\dtl@tc@rest{}}%
\let\dtl@testifuppernext=\relax
}%
{%
\IfSubStringInString{\string\MakeTextUppercase}{#1#2}%
{%
\@dtl@conditiontrue
\def\dtl@tc@rest{}}%
\let\dtl@testifuppernext=\relax
}%
{%
\edef\dtl@uccode{\the\uccode`#1}%
\edef\dtl@code{\number`#1}%
\ifnum\dtl@code=\dtl@uccode\relax
\@dtl@conditiontrue
\let\dtl@testifuppernext=\dtl@testifuppercase
\else
\ifnum\dtl@uccode=0\relax
\@dtl@conditiontrue
\let\dtl@testifuppernext=\dtl@testifuppercase
\else
\@dtl@conditionfalse
\let\dtl@testifuppernext=\@dtl@gobbletonil
\fi
\fi
}%
}%
}
\newcommand*{\DTLifAllLowerCase}[3]{%
\protected@edef\dtl@tlc{#1}%
\expandafter\dtl@testiflowercase\dtl@tlc\@nil\relax
\if@dtl@condition#2\else#3\fi
}

```

```

\def\dtl@testiflowercase#1#2{%
  \def\dtl@argi{#1}%
  \def\dtl@argii{#2}%
  \ifx\dtl@argi\@nnil
    \let\dtl@testiflowernext=\@nnil
  \else
    \ifx#1\protect
      \let\dtl@testiflowernext=\dtl@testiflowercase
    \else
      \ifx\lowercase#1\relax
        \@dtl@conditiontrue
        \def\dtl@tc@rest{}%
        \let\dtl@testiflowernext=\relax
      \else
        \edef\dtl@tc@arg{\string#1}%
        \expandafter\dtl@test@iflowercase\dtl@tc@arg\end
        \ifx\dtl@argii\@nnil
          \let\dtl@testiflowernext=\@dtl@gobbletonil
        \fi
      \fi
    \fi
  \ifx\dtl@testiflowernext\relax
    \edef\dtl@dotestiflowernext{%
      \noexpand\dtl@testiflowercase}%
  \else
    \ifx\dtl@testiflowernext\@nnil
      \edef\dtl@dotestiflowernext{#2}%
    \else
      \expandafter\toks@\expandafter{\dtl@tc@rest}%
      \@dtl@toks{#2}%
      \edef\dtl@dotestiflowernext{%
        \noexpand\dtl@testiflowernext\the\toks@\the\@dtl@toks}%
    \fi
  \fi
  \dtl@dotestiflowernext
}
\def\dtl@test@iflowercase#1#2\end{%
  \def\dtl@tc@rest{#2}%
  \IfSubStringInString{\string\MakeLowercase}{#1#2}%
  {%
    \@dtl@conditiontrue
    \def\dtl@tc@rest{}%
    \let\dtl@testiflowernext=\relax
  }%
  {%
    \IfSubStringInString{\string\MakeTextLowercase}{#1#2}%
    {%
      \@dtl@conditiontrue
      \def\dtl@tc@rest{}%
    }%
  }%
}

```

```

        \let\dtl@testiflowernext=\relax
    }%
    {%
        \edef\dtl@lccode{\the\lccode`#1}%
        \edef\dtl@code{\number`#1}%
        \ifnum\dtl@code=\dtl@lccode\relax
            \dtl@conditiontrue
            \let\dtl@testiflowernext=\dtl@testiflowercase
        \else
            \ifnum\dtl@lccode=0\relax
                \dtl@conditiontrue
                \let\dtl@testiflowernext=\dtl@testiflowercase
            \else
                \dtl@conditionfalse
                \let\dtl@testiflowernext=\dtl@gobbletonil
            \fi
        \fi
    }%
}
\newcommand{\DTLsubstitute}[3]{%
    \expandafter\DTLsplitstring\expandafter
        {#1}{#2}{\dtl@beforepart}{\dtl@afterpart}%
    \ifdefempty{\dtl@replaced}%
        {%
        }%
        {%
            \def#1{%
                \expandafter\dtl@toks\expandafter{\dtl@beforepart}%
                \expandafter\toks@\expandafter{#1}%
                \protected@edef#1{\the\toks@\the\dtl@toks#3}%
                \expandafter\dtl@toks\expandafter{\dtl@afterpart}%
                \expandafter\toks@\expandafter{#1}%
                \edef#1{\the\toks@\the\dtl@toks}%
            }%
        }
    \newcommand*\DTLsplitstring}[4]{%
        \def\dtl@splitstr##1#2##2\@nil{%
            \def#3{##1}%
            \def#4{##2}%
            \ifdefempty{#4}%
                {%
                    \let\dtl@replaced=\@empty
                }%
                {%
                    \def\dtl@replaced{#2}%
                    \dtl@split@str##2\@nil
                }%
            }%
        }
    \def\dtl@split@str##1#2\@nil{\def#4{##1}}%

```

```

\dtl@splitstr#1#2\@nil
}
\newcommand{\DTLsubstituteall}[3]{%
\def\@dtl@splitsubstr{%
\let\@dtl@afterpart=#1\relax
\@dtl@dosubstitute{#2}{#3}%
\expandafter\toks@\expandafter{\@dtl@splitsubstr}%
\expandafter\@dtl@toks\expandafter{\@dtl@afterpart}%
\long\edef#1{\the\toks@\the\@dtl@toks}%
}
\def\@dtl@dosubstitute#1#2{%
\expandafter\DTLsplitstring\expandafter
{\@dtl@afterpart}{#1}{\@dtl@beforepart}{\@dtl@afterpart}%
\expandafter\toks@\expandafter{\@dtl@splitsubstr}%
\expandafter\@dtl@toks\expandafter{\@dtl@beforepart}%
\edef\@dtl@splitsubstr{\the\toks@\the\@dtl@toks}%
\ifdefempty{\@dtl@replaced}%
{%
\let\@dtl@dosubstnext=\@dtl@dosubstitutenoop
}%
}%
\expandafter\toks@\expandafter{\@dtl@splitsubstr}%
\@dtl@toks{#2}%
\edef\@dtl@splitsubstr{\the\toks@\the\@dtl@toks}%
\let\@dtl@dosubstnext=\@dtl@dosubstitute
}%
\@dtl@dosubstnext{#1}{#2}%
}
\def\@dtl@dosubstitutenoop#1#2{}
\newif\if@dtl@condition
\newcount\@dtl@datatype
\newcommand{\@dtl@checknumerical}[1]{%
\@dtl@numgrpsepfalse
\dtl@ifsingle{#1}%
{%
\expandafter\toks@\expandafter{#1}%
\edef\@dtl@tmp{\the\toks@}%
}%
}%
\def\@dtl@tmp{#1}%
}%
\ifdefempty\@dtl@tmp
{%
\@dtl@datatype=0\relax
}%
}%
\@dtl@tmpcount=0\relax
\@dtl@datatype=0\relax
\@dtl@numgrpsepcount=2\relax
\@dtl@standardize@currency\@dtl@tmp

```

```

\ifdefempty{\@dtl@org@currency}%
{%
}%
{%
  \let\@dtl@currency\@dtl@org@currency
}%
\expandafter\@dtl@checknumericalstart\@dtl@tmp\@nil\@nil
}%
\ifnum\@dtl@numgrpsepcount>-1\relax
  \if@dtl@numgrpsep
    \ifnum\@dtl@numgrpsepcount=3\relax
      \else
        \@dtl@datatype=0\relax
      \fi
    \fi
  \fi
}
\newcommand*\@dtl@protect{\protect}
\newcommand*\@dtl@minus}{-}
\newcommand*\@dtl@plus}{+}
\newcommand*\@dtl@dollar}{\$}
\def\@dtl@checknumericalstart#1#2\@nil\@nil{%
  \def\@dtl@tmp{#1}%
  \ifx\@dtl@tmp\@dtl@protect
    \@dtl@checknumericalstart#2\@nil\@nil\relax
  \else
    \ifx\@dtl@tmp\@dtl@minus
      \def\@dtl@tmp{#2}%
      \ifdefempty{\@dtl@tmp}%
        {%
          \@dtl@datatype=0\relax
        }%
      {%
        \ifnum\@dtl@datatype=0\relax
          \@dtl@datatype=1\relax
        \fi
        \@dtl@checknumericalstart#2\@nil\@nil\relax
      }%
    \else
      \ifx\@dtl@tmp\@dtl@plus
        \def\@dtl@tmp{#2}%
        \ifdefempty{\@dtl@tmp}%
          {%
            \@dtl@datatype=0\relax
          }%
        {%
          \ifnum\@dtl@datatype=0\relax
            \@dtl@datatype=1\relax
          \fi
          \@dtl@checknumericalstart#2\@nil\@nil\relax
        }%
      \fi
    \fi
  \fi
}

```

```

    }%
  \else
    \def\@dtl@tmp{#1}%
    \ifx\@dtl@tmp\@dtl@dollar
      \def\@dtl@tmp{#2}%
      \ifdefempty{\@dtl@tmp}%
        {%
          \@dtl@datatype=0\relax
        }%
      {%
        \@dtl@datatype=3\relax
        \@dtl@checknumericalstart#2\@nil\@nil\relax
      }%
    \else
      \ifdefempty{\@dtl@tmp}%
        {%
          \@dtl@datatype=0\relax
        }%
      {%
        \ifnum\@dtl@datatype=0\relax
          \@dtl@datatype=1\relax
        \fi
        \@dtl@checknumericalloop#1#2\@nil\@nil\relax
      }%
    \fi
  \fi
\fi
\fi
}
\newif\if@dtl@numgrpsep
\newcommand*{\@dtl@ifDigitOrDecimalSep}[3]{%
  \ifnum 9<1\noexpand#1\relax
    #2%
  \else
    \expandafter\ifx\@dtl@decimal#1\relax
      #2%
    \else
      #3%
    \fi
  \fi
}
\def\@dtl@checknumericalloop#1#2\@nil{%
\def\@dtl@tmp{#1}%
\ifx\@nil\@dtl@tmp\relax
\let\@dtl@chcknumnext=\@dtl@checknumericalloop%
\else
\@dtl@ifDigitOrDecimalSep{#1}{%
\let\@dtl@chcknumnext=\@dtl@checknumericalloop%
\expandafter\ifx\@dtl@decimal#1\relax
\if@dtl@numgrpsep

```

```

        \ifnum\@dtl@numgrpsepcount=3\relax
        \@dtl@numgrpsepcount=-1\relax
        \else
        \@dtl@datatype=0\relax
        \let\@dtl@chcknumnext=\@dtl@checknumericalnoop
        \fi
    \else
    \@dtl@numgrpsepcount=-1\relax
    \fi
\else
\ifnum\@dtl@numgrpsepcount=-1\relax
\else
\advance\@dtl@numgrpsepcount by 1\relax
\fi
\fi
}{%
\ifx\@dtl@numbergroupchar\@dtl@tmp\relax
\@dtl@numgrpseptrue
\ifnum\@dtl@numgrpsepcount<3\relax
\@dtl@datatype=0\relax
\let\@dtl@chcknumnext=\@dtl@checknumericalnoop
\else
\@dtl@numgrpsepcount=0\relax
\fi
\else
\@dtl@datatype=0\relax
\let\@dtl@chcknumnext=\@dtl@checknumericalnoop
\fi
}%
\ifx\@dtl@decimal\@dtl@tmp\relax
\ifnum\@dtl@datatype<3\relax
\@dtl@datatype=2\relax
\fi
\advance\@dtl@tmpcount by 1\relax
\ifnum\@dtl@tmpcount>1\relax
\@dtl@datatype=0\relax
\let\@dtl@chcknumnext=\@dtl@checknumericalnoop%
\fi
\fi
\fi
\@dtl@chcknumnext#2\@nil
}
\def\@dtl@checknumericalnoop#1\@nil#2{}
\newcommand{\DTLifnumerical}[3]{%
\@dtl@checknumerical{#1}%
\ifnum\@dtl@datatype=0\relax#3\else#2\fi
}
\newcommand{\DTLifreal}[3]{%
\@dtl@checknumerical{#1}%
\ifnum\@dtl@datatype=2\relax #2\else #3\fi
}

```

```

}
\newcommand{\DTLifint}[3]{%
  \@dtl@checknumerical{#1}%
  \ifnum\@dtl@datatype=1\relax #2\else #3\fi
}
\newcommand{\DTLifstring}[3]{%
  \@dtl@checknumerical{#1}%
  \ifnum\@dtl@datatype=0\relax #2\else #3\fi
}
\newcommand{\DTLifcurrency}[3]{%
  \@dtl@checknumerical{#1}%
  \ifnum\@dtl@datatype=3\relax #2\else #3\fi
}
\newcommand*{\DTLifcurrencyunit}[4]{%
  \@dtl@checknumerical{#1}%
  \ifnum\@dtl@datatype=3\relax
    \ifthenelse{\equal{\@dtl@org@currency}{#2}}{#3}{#4}%
  \else
    #4%
  \fi
}
\newcommand{\DTLifcasedatatype}[5]{%
  \@dtl@checknumerical{#1}%
  \ifcase\@dtl@datatype
    #2% string
  \or
    #3% integer
  \or
    #4% number
  \or
    #5% currency
  \fi
}
\newcommand*{\dtl@testbothnumerical}[2]{%
  \dtl@ifsingle{#1}{%
    \edef\@dtl@tmp{#1}}{%
    \def\@dtl@tmp{#1}}%
  \expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
  \edef\@dtl@firsttype{\number\@dtl@datatype}%
  \dtl@ifsingle{#2}{%
    \edef\@dtl@tmp{#2}}{%
    \def\@dtl@tmp{#2}}%
  \expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
  \multiply\@dtl@datatype by \@dtl@firsttype\relax
  \ifnum\@dtl@datatype>0\relax
    \@dtl@conditiontrue
  \else
    \@dtl@conditionfalse
  \fi
}
}

```

```

\newcommand*\DTLifnumlt}[4]{%
  \DTLconverttodecimal{#1}{\@dtl@numi}%
  \DTLconverttodecimal{#2}{\@dtl@numii}%
  \dtlifnumlt{\@dtl@numi}{\@dtl@numii}%
  {%
    #3%
  }%
  {%
    #4%
  }%
}
\newif\ifdtlcompareskipcs
\dtlcompareskipcsfalse
\newcommand*\dtlcompare}[3]{%
  \dtl@subnobrsp{#2}{\@dtl@argA}%
  \dtl@subnobrsp{#3}{\@dtl@argB}%
  \ifdefempty{\@dtl@argA}%
  {%
    \ifdefempty{\@dtl@argB}%
    {%
      #1=0\relax
    }%
    {%
      #1=-1\relax
    }%
  }%
  {%
    \ifdefempty{\@dtl@argB}%
    {%
      #1=1\relax
    }%
    {%
      \dtl@setwordbreaksnohyphens{\@dtl@argA}{\@dtl@wordbreak}%
      \let\@dtl@argA\dtl@string
      \dtl@setwordbreaksnohyphens{\@dtl@argB}{\@dtl@wordbreak}%
      \let\@dtl@argB\dtl@string
      \expandafter\dtl@getfirst\@dtl@argA\end@dtl@getfirst
      \let\dtl@firstA=\dtl@first
      \let\dtl@restA=\dtl@rest
      \expandafter\dtl@getfirst\@dtl@argB\end@dtl@getfirst
      \let\dtl@firstB=\dtl@first
      \let\dtl@restB=\dtl@rest
      \expandafter\dtl@ifsingleorUTFviii\expandafter{\dtl@firstA}%
      {%
        \expandafter\dtl@ifsingleorUTFviii\expandafter{\dtl@firstB}%
        {%
          \expandafter\dtl@setcharcode\expandafter{\dtl@firstA}{\dtl@codeA}%
          \expandafter\dtl@setcharcode\expandafter{\dtl@firstB}{\dtl@codeB}%
          \let\dtl@donextcompare\@firstofone
          \ifdtlcompareskipcs

```

```

\ifnum\dtl@codeA=0\relax
  \ifnum\dtl@codeB=0\relax
    \edef\dtl@donext{%
      \noexpand\dtlcompare
      {\noexpand#1}{\expandonce\dtl@restA}{\expandonce\dtl@restB}}%
    \dtl@donext
    \let\dtl@donextcompare\@gobble
  \else
    \edef\dtl@donext{%
      \noexpand\dtlcompare
      {\noexpand#1}{\expandonce\dtl@restA}{\expandonce\@dtl@argB}}%
    \dtl@donext
    \let\dtl@donextcompare\@gobble
  \fi
\else
  \ifnum\dtl@codeB=0\relax
    \edef\dtl@donext{%
      \noexpand\dtlcompare
      {\noexpand#1}{\expandonce\@dtl@argA}{\expandonce\dtl@restB}}%
    \dtl@donext
    \let\dtl@donextcompare\@gobble
  \fi
\fi
\dtl@donextcompare
{%
  \ifnum\dtl@codeA=-1\relax
    \ifnum\dtl@codeB=-1\relax
      \edef\dtl@donext{%
        \noexpand\dtlcompare
        {\noexpand#1}{\expandonce\dtl@restA}{\expandonce\dtl@restB}}%
      \dtl@donext
    \else
      \edef\dtl@donext{%
        \noexpand\dtlcompare
        {\noexpand#1}%
        {\expandonce\dtl@restA}%
        {\expandonce\dtl@firstB\expandonce\dtl@restB}}%
      \dtl@donext
    \fi
  \else
    \ifnum\dtl@codeB=-1\relax
      \edef\dtl@donext{%
        \noexpand\dtlcompare
        {\noexpand#1}%
        {\expandonce\dtl@firstA\expandonce\dtl@restA}%
        {\expandonce\dtl@restB}}%
      \dtl@donext
    \else
      \ifnum\dtl@codeA<\dtl@codeB

```

```

#1=-1\relax
\else
\ifnum\dtl@codeA>\dtl@codeB
#1=1\relax
\else
\ifdefempty{\dtl@restA}%
{%
\ifdefempty{\dtl@restB}%
{%
#1=0\relax
}%
}%
#1=-1\relax
}%
}%
{%
\ifdefempty{\dtl@restB}%
{%
#1=1\relax
}%
}%
\protected@edef\dtl@donext{%
\noexpand\dtlcompare
{\noexpand#1}{\dtl@restA}{\dtl@restB}}%
\dtl@donext
}%
}%
\fi
\fi
\fi
\fi
}%
}%
{%
\edef\dtl@donext{%
\noexpand\dtlcompare
{\noexpand#1}%
{\expandonce\dtl@firstA\expandonce\dtl@restA}%
{\expandonce\dtl@firstB\expandonce\dtl@restB}}%
\dtl@donext
}%
}%
{%
\edef\dtl@donext{%
\noexpand\dtlcompare
{\noexpand#1}%
{\expandonce\dtl@firstA\expandonce\dtl@restA}%
{\expandonce\dtl@firstB\expandonce\dtl@restB}}%
\dtl@donext
}%
}

```

```

    }%
  }%
}
\def\dtl@if@two@octets#1#2\dtl@end@if@two@octets#3#4{%
  \ifbool{@dtl@utf8}
  {%
    \ifx\UTFviii@two@octets#1\relax
      #3%
    \else
      #4%
    \fi
  }%
  {%
    #4%
  }%
}
\def\dtl@getfirst@UTFviii#1#2#3\end@dtl@getfirst@UTFviii{%
  \def\dtl@first{#1#2}%
  \ifx\@nil#3\relax
    \def\dtl@rest{}%
  \else
    \expandafter\def\expandafter\dtl@rest\expandafter{\@dtl@firsttonil#3}%
  \fi
}
\def\@dtl@firsttonil#1\@nil{#1}
\def\dtl@getfirst#1#2\end@dtl@getfirst{%
  \def\dtl@first{#1}%
  \ifdefempty{\dtl@first}%
  {%
    \def\dtl@rest{#2}%
  }%
  {%
    \ifbool{@dtl@utf8}
    {%
      \expandafter\dtl@if@two@octets#1#2\relax\dtl@end@if@two@octets
      {%
        \dtl@getfirst@UTFviii#1#2\@nil\end@dtl@getfirst@UTFviii
      }%
      {%
        \dtl@ifsingle{#1}{\def\dtl@rest{#2}}{\dtl@getfirst#1#2\end@dtl@getfirst}%
      }%
    }%
    {%
      \dtl@ifsingle{#1}{\def\dtl@rest{#2}}{\dtl@getfirst#1#2\end@dtl@getfirst}%
    }%
  }%
}
\newcount\dtl@codeA
\newcount\dtl@codeB
\newcommand*{\dtl@setcharcode}[2]{%

```

```

\ifstrempy{#1}%
{%
  #2=-1\relax
}%
{%
  \ifx\@dtl@wordbreak#1\relax
  #2=\ \relax
\else
  \ifcat\noexpand#1\relax
  #2=0\relax
\else
  \expandafter\dtl@if@two@octets#1\relax\relax\dtl@end@if@two@octets
  {%
    \dtlsetUTFviiiicharcode{#1}{#2}%
  }%
  {%
    \dtlsetcharcode{#1}{#2}%
  }%
\fi
\fi
}%
}
\newcommand*\dtlsetcharcode[2]{#2=#1\relax}
\newcommand*\dtlsetlccharcode[2]{#2=\lccode`#1\relax}
\newcommand*\dtlsetUTFviiiicharcode[2]{\dtlsetdefaultUTFviiiicharcode{#1}{#2}}
\newcommand*\dtlsetUTFviiilccharcode[2]{\dtlsetdefaultUTFviiilccharcode{#1}{#2}}
\newcommand*\dtlsetdefaultUTFviiiicharcode[2]{%
\ifboolexpr
{
  test {\ifstrequal{#1}{À}}
  or test {\ifstrequal{#1}{Á}}
  or test {\ifstrequal{#1}{Â}}
  or test {\ifstrequal{#1}{Ã}}
  or test {\ifstrequal{#1}{Ä}}
}%
{%
  #2=`A\relax
}%
{%
  \ifstrequal{#1}{Ç}%
  {%
    #2=`C\relax
  }%
  {%
    \ifboolexpr
    {
      test {\ifstrequal{#1}{È}}
      or test {\ifstrequal{#1}{É}}
      or test {\ifstrequal{#1}{Ê}}
      or test {\ifstrequal{#1}{Ë}}
    }
  }
}

```

```

}%
{%
  #2=`E\relax
}%
{%
  \ifboolexpr
  {
    test {\ifstrequal{#1}{İ}}
    or test {\ifstrequal{#1}{I}}
    or test {\ifstrequal{#1}{ı}}
    or test {\ifstrequal{#1}{i}}
  }%
  {%
    #2=`I\relax
  }%
  {%
    \ifstrequal{#1}{Ñ}%
    {%
      #2=`N\relax
    }%
    {%
      \ifboolexpr
      {
        test {\ifstrequal{#1}{Ò}}
        or test {\ifstrequal{#1}{Ó}}
        or test {\ifstrequal{#1}{ō}}
        or test {\ifstrequal{#1}{ö}}
        or test {\ifstrequal{#1}{ö}}
      }%
      {%
        #2=`O\relax
      }%
      {%
        \ifboolexpr
        {
          test {\ifstrequal{#1}{Û}}
          or test {\ifstrequal{#1}{Ü}}
          or test {\ifstrequal{#1}{ú}}
          or test {\ifstrequal{#1}{ü}}
        }%
        {%
          #2=`U\relax
        }%
        {%
          \ifstrequal{#1}{Ý}%
          {%
            #2=`Y\relax
          }%
          {%
            \ifboolexpr

```

```

{
  test {\ifstrequal{#1}{à}}
  or test {\ifstrequal{#1}{á}}
  or test {\ifstrequal{#1}{â}}
  or test {\ifstrequal{#1}{ã}}
  or test {\ifstrequal{#1}{ä}}
}%
{%
  #2=`a\relax
}%
{%
  \ifstrequal{#1}{ç}%
  {%
    #2=`c\relax
  }%
  {%
    \ifboolexpr
    {
      test {\ifstrequal{#1}{è}}
      or test {\ifstrequal{#1}{é}}
      or test {\ifstrequal{#1}{ê}}
      or test {\ifstrequal{#1}{ë}}
    }%
    {%
      #2=`e\relax
    }%
    {%
      \ifboolexpr
      {
        test {\ifstrequal{#1}{i}}
        or test {\ifstrequal{#1}{í}}
        or test {\ifstrequal{#1}{î}}
        or test {\ifstrequal{#1}{ï}}
      }%
      {%
        #2=`i\relax
      }%
      {%
        \ifstrequal{#1}{ñ}%
        {%
          #2=`n\relax
        }%
        {%
          \ifboolexpr
          {
            test {\ifstrequal{#1}{ò}}
            or test {\ifstrequal{#1}{ó}}
            or test {\ifstrequal{#1}{ô}}
            or test {\ifstrequal{#1}{õ}}
            or test {\ifstrequal{#1}{ö}}
          }
        }
      }
    }
  }
}

```



```

    or test {\ifstrequal{#1}{Ã}}
    or test {\ifstrequal{#1}{Ä}}
}%
{%
#2=`a\relax
}%
{%
\ifboolexpr
{
    test {\ifstrequal{#1}{ç}}
    or test {\ifstrequal{#1}{Ç}}
}
}%
#2=`c\relax
}%
{%
\ifboolexpr
{
    test {\ifstrequal{#1}{è}}
    or test {\ifstrequal{#1}{é}}
    or test {\ifstrequal{#1}{ê}}
    or test {\ifstrequal{#1}{ë}}
    or test {\ifstrequal{#1}{È}}
    or test {\ifstrequal{#1}{É}}
    or test {\ifstrequal{#1}{Ê}}
    or test {\ifstrequal{#1}{Ë}}
}
}%
{%
#2=`e\relax
}%
{%
\ifboolexpr
{
    test {\ifstrequal{#1}{i}}
    or test {\ifstrequal{#1}{ı}}
    or test {\ifstrequal{#1}{İ}}
    or test {\ifstrequal{#1}{İ}}
    or test {\ifstrequal{#1}{I}}
    or test {\ifstrequal{#1}{Í}}
    or test {\ifstrequal{#1}{Î}}
    or test {\ifstrequal{#1}{Ï}}
}
}%
{%
#2=`i\relax
}%
{%
\ifboolexpr
{
    test {\ifstrequal{#1}{ñ}}
    or test {\ifstrequal{#1}{Ñ}}
}
}

```

```

}
{%
  #2=`n\relax
}%
{%
  \ifboolexpr
  {
    test {\ifstrequal{#1}{ò}}
    or test {\ifstrequal{#1}{ó}}
    or test {\ifstrequal{#1}{ô}}
    or test {\ifstrequal{#1}{õ}}
    or test {\ifstrequal{#1}{ö}}
    or test {\ifstrequal{#1}{Ë}}
    or test {\ifstrequal{#1}{Ï}}
    or test {\ifstrequal{#1}{Ï}}
    or test {\ifstrequal{#1}{Ï}}
  }%
  {%
    #2=`o\relax
  }%
  {%
    \ifboolexpr
    {
      test {\ifstrequal{#1}{ù}}
      or test {\ifstrequal{#1}{ú}}
      or test {\ifstrequal{#1}{û}}
      or test {\ifstrequal{#1}{ü}}
      or test {\ifstrequal{#1}{Û}}
      or test {\ifstrequal{#1}{Ü}}
      or test {\ifstrequal{#1}{Û}}
      or test {\ifstrequal{#1}{Ü}}
    }%
    {%
      #2=`u\relax
    }%
    {%
      \ifboolexpr
      {
        test {\ifstrequal{#1}{ý}}
        or test {\ifstrequal{#1}{ÿ}}
      }%
      {%
        #2=`y\relax
      }%
      {%
        #2=96\relax
      }%
    }%
  }%
}

```



```

{%
\dtl@setwordbreaksnohyphens{\@dtl@argA}{\@dtl@wordbreak}%
\let\@dtl@argA\dtl@string
\dtl@setwordbreaksnohyphens{\@dtl@argB}{\@dtl@wordbreak}%
\let\@dtl@argB\dtl@string
\expandafter\dtl@getfirst\@dtl@argA\end@dtl@getfirst
\let\dtl@firstA=\dtl@first
\let\dtl@restA=\dtl@rest
\expandafter\dtl@getfirst\@dtl@argB\end@dtl@getfirst
\let\dtl@firstB=\dtl@first
\let\dtl@restB=\dtl@rest
\expandafter\dtl@ifsingleorUTFviii\expandafter{\dtl@firstA}%
{%
\expandafter\dtl@ifsingleorUTFviii\expandafter{\dtl@firstB}%
{%
\expandafter\dtl@setlccharcode\expandafter{\dtl@firstA}{\dtl@codeA}%
\expandafter\dtl@setlccharcode\expandafter{\dtl@firstB}{\dtl@codeB}%
\let\dtl@donextcompare\@firstofone
\ifdtlcompareskipcs
\ifnum\dtl@codeA=0\relax
\ifnum\dtl@codeB=0\relax
\edef\dtl@donext{%
\noexpand\dtl@licompare
{\noexpand#1}{\expandonce\dtl@restA}{\expandonce\dtl@restB}}%
\dtl@donext
\let\dtl@donextcompare\@gobble
\else
\edef\dtl@donext{%
\noexpand\dtl@licompare
{\noexpand#1}{\expandonce\dtl@restA}{\expandonce\@dtl@argB}}%
\dtl@donext
\let\dtl@donextcompare\@gobble
\fi
\else
\ifnum\dtl@codeB=0\relax
\edef\dtl@donext{%
\noexpand\dtl@licompare
{\noexpand#1}{\expandonce\@dtl@argA}{\expandonce\dtl@restB}}%
\dtl@donext
\let\dtl@donextcompare\@gobble
\fi
\fi
\fi
\dtl@donextcompare
{%
\ifnum\dtl@codeA=-1\relax
\ifnum\dtl@codeB=-1\relax
\edef\dtl@donext{%
\noexpand\dtl@licompare{\noexpand#1}%
{\expandonce\dtl@restA}{\expandonce\dtl@restB}}%

```

```

\dtl@donext
\else
\edef\dtl@donext{%
\noexpand\dtlcompare
{\noexpand#1}%
{\expandonce\dtl@restA}%
{\expandonce\dtl@firstB\expandonce\dtl@restB}}%
\dtl@donext
\fi
\else
\ifnum\dtl@codeB=-1\relax
\edef\dtl@donext{%
\noexpand\dtlcompare
{\noexpand#1}%
{\expandonce\dtl@firstA\expandonce\dtl@restA}%
{\expandonce\dtl@restB}}%
\dtl@donext
\else
\ifnum\dtl@codeA<\dtl@codeB
#1=-1\relax
\else
\ifnum\dtl@codeA>\dtl@codeB
#1=1\relax
\else
\ifdefempty{\dtl@restA}%
{%
\ifdefempty{\dtl@restB}%
{%
#1=0\relax
}%
}%
#1=-1\relax
}%
}%
\ifdefempty{\dtl@restB}%
{%
#1=1\relax
}%
{%
\edef\dtl@donext{%
\noexpand\dtlcompare
{\noexpand#1}%
{\expandonce\dtl@restA}%
{\expandonce\dtl@restB}}%
\dtl@donext
}%
}%
\fi
\fi

```



```

    {\@dtl@argA}{\datatoolpersoncomma}{\@dtl@beforepart}{\@dtl@afterpart}%
\ifdefempty{\@dtl@replaced}%
{%
  \expandafter\DTLsplitstring\expandafter
    {\@dtl@argA}{\datatoolplacecomma}{\@dtl@beforepart}{\@dtl@afterpart}%
\ifdefempty{\@dtl@replaced}%
{%
  \expandafter\DTLsplitstring\expandafter
    {\@dtl@argA}{\datatoolsubjectcomma}{\@dtl@beforepart}{\@dtl@afterpart}%
\ifdefempty{\@dtl@replaced}%
{%
  \expandafter\DTLsplitstring\expandafter
    {\@dtl@argA}{\datatoolparenstart}{\@dtl@beforepart}{\@dtl@afterpart}%
\ifdefempty{\@dtl@replaced}%
{%
  \def\@dtl@A@comma{0}%
  \let\@dtl@A@before\@dtl@argA
  \def\@dtl@A@after{}}%
}%
{%
  \let\@dtl@A@comma\@dtl@replaced
  \let\@dtl@A@before\@dtl@beforepart
  \let\@dtl@A@after\@dtl@afterpart
}%
}%
{%
  \let\@dtl@A@comma\@dtl@replaced
  \let\@dtl@A@before\@dtl@beforepart
  \let\@dtl@A@after\@dtl@afterpart
}%
}%
{%
  \let\@dtl@A@comma\@dtl@replaced
  \let\@dtl@A@before\@dtl@beforepart
  \let\@dtl@A@after\@dtl@afterpart
}%
}%
\expandafter\DTLsplitstring\expandafter
{\@dtl@argB}{\datatoolpersoncomma}{\@dtl@beforepart}{\@dtl@afterpart}%
\ifdefempty{\@dtl@replaced}%
{%
  \expandafter\DTLsplitstring\expandafter
    {\@dtl@argB}{\datatoolplacecomma}{\@dtl@beforepart}{\@dtl@afterpart}%
\ifdefempty{\@dtl@replaced}%
{%

```



```

\edef\dtl@donext{%
  \noexpand\dtlcompare
  {\noexpand#1}%
  {\expandonce\@dtl@A@before}%
  {\expandonce\@dtl@B@before}}%
\dtl@donext
\or
\ifnum\@dtl@A@before<\@dtl@B@before\relax
  #1=-1\relax
\else
  \ifnum\@dtl@A@before>\@dtl@B@before\relax
    #1=1\relax
  \else
    #1=0\relax
  \fi
\fi
\or
\@dtlwordindexcompare{#1}{\@dtl@A@before}{\@dtl@B@before}
  {\dtlicomparewords}{#4}%
\ifnum#1=0\relax
  \let\@org@dtl@person@comma\datatoolpersoncomma
  \let\@org@dtl@place@comma\datatoolplacecomma
  \let\@org@dtl@subject@comma\datatoolsubjectcomma
  \let\@org@dtl@paren@start\datatoolparenstart
  \def\datatoolpersoncomma{3}%
  \def\datatoolplacecomma{2}%
  \def\datatoolsubjectcomma{1}%
  \def\datatoolparenstart{-1}%
  \ifnum\@dtl@A@comma>\@dtl@B@comma\relax
    #1=-1\relax
  \else
    \ifnum\@dtl@A@comma<\@dtl@B@comma\relax
      #1=1\relax
    \else
      \@dtlwordindexcompare{#1}{\@dtl@B@before}{\@dtl@A@before}
        {\dtlcomparewords}{#4}%
      \ifnum#1=0\relax
        \@dtlwordindexcompare{#1}{\@dtl@A@after}{\@dtl@B@after}
          {\dtlicomparewords}{#4}%
        \fi
      \fi
    \fi
  \let\datatoolpersoncomma\@org@dtl@person@comma
  \let\datatoolplacecomma\@org@dtl@place@comma
  \let\datatoolsubjectcomma\@org@dtl@subject@comma
  \let\datatoolparenstart\@org@dtl@paren@start
\fi
\fi
\fi
\fi

```

```

    }%
  }%
}
\newcommand*{\datatoolpersoncomma}{, \space}
\newcommand*{\datatoolplacecomma}{, \space}
\newcommand*{\datatoolsubjectcomma}{, \space}
\newcommand*{\datatoolparenstart}{\space}
\newcommand*{\@dtlwordindexcompare}[5]{%
  \dtl@setwordbreaks{#2}{#5}%
  \let#2\dtl@string
  \dtl@setwordbreaks{#3}{}%
  \let#3\dtl@string
  \edef\@dtl@do@compare{%
    \noexpand#4{\noexpand#1}%
    {\expandonce#2}{\expandonce#3}%
  }%
  \@dtl@do@compare
}
\newcommand*{\@dtl@dict@compare}[4]{%
  \ifdefempty{#2}%
  {%
    \ifdefempty{#3}%
    {%
      #1=0\relax
    }%
    {%
      #1=-1\relax
    }%
  }%
  \ifdefempty{#3}%
  {%
    #1=1\relax
  }%
  {%
    \expandafter\dtl@grabword#2\@dtl@endgrabword\dtl@A@first\dtl@A@remain
    \expandafter\dtl@grabword#3\@dtl@endgrabword\dtl@B@first\dtl@B@remain
    \edef\@dtl@do@compare{%
      \noexpand#4{\noexpand#1}%
      {\expandonce\dtl@A@first}{\expandonce\dtl@B@first}%
    }%
    \@dtl@do@compare
    \ifnum#1=0\relax
    \@dtl@dict@compare{#1}{\dtl@A@remain}{\dtl@B@remain}{#4}%
    \fi
  }%
}
\def\dtl@grabword#1\@dtl@wordbreak#2\@dtl@endgrabword#3#4{%
  \def#3{#1}%

```

```

\def#4{#2}%
}
\newcommand{\dtlicomparewords}[3]{%
\dtlicompare{#1}{#2}{#3}%
}
\newcommand{\dtlcomparewords}[3]{%
\dtlcompare{#1}{#2}{#3}%
}
\newcommand*{\dtl@setwordbreaks}[2]{%
\expandafter\dtl@subnobrsp\expandafter{#1}{\dtl@string}%
\DTLsubstituteall{\dtl@string}{~}{#2}%
\DTLsubstituteall{\dtl@string}{\ }{#2}%
\DTLsubstituteall{\dtl@string}{\space}{#2}%
\DTLsubstituteall{\dtl@string}{-}{#2}%
\toks@{#2}%
\edef\dtl@do@setwordbreaks{%
\noexpand\dtl@setwordbreaks{\the\toks@}\expandonce\dtl@string\space\noexpand\nil}%
\def\dtl@string{}%
\dtl@do@setwordbreaks
}
\def\dtl@setwordbreaks#1#2 #3{%
\def\dtl@tmp{#3}%
\ifx\nnil\dtl@tmp
\let\dtl@setwordbreaks@next\@gobbletwo
\appto\dtl@string{#2}%
\else
\let\dtl@setwordbreaks@next\dtl@setwordbreaks
\appto\dtl@string{#2#1}%
\fi
\dtl@setwordbreaks@next{#1}#3%
}
\newcommand*{\dtl@setwordbreaksnohyphens}[2]{%
\expandafter\dtl@subnobrsp\expandafter{#1}{\dtl@string}%
\DTLsubstituteall{\dtl@string}{~}{#2}%
\DTLsubstituteall{\dtl@string}{\ }{#2}%
\DTLsubstituteall{\dtl@string}{\space}{#2}%
\toks@{#2}%
\edef\dtl@do@setwordbreaks{%
\noexpand\dtl@setwordbreaks{\the\toks@}\expandonce\dtl@string\space\noexpand\nil}%
\def\dtl@string{}%
\dtl@do@setwordbreaks
}
\newcommand*{\dtl@wordbreak}{ }
\def\dtl@ifcasechargroup#1#2\dtl@end@ifcasechargroup#3#4#5{%
\expandafter\dtl@if@two@octets#1#2\relax\relax\dtl@end@if@two@octets
}%
\dtl@getfirst@UTFviii#1#2\nil\end\dtl@getfirst@UTFviii
\expandafter\dtlsetUTFviiilccharcode\expandafter{\dtl@first}{\count@}%
\ifnum\count@<`a\relax #5\else#3\fi
}%

```

```

{%
\dtlifcasechargroup{#1}%
  {#3}%
  {%
    \DTLifint{#1#2}
    {%
      #4%
    }%
    {%
      #3%
    }%
  }%
  {#5}%
}%
}
\newcommand*{\dtlifcasechargroup}[4]{%
\count@=#1\relax
\dtlifintclosedbetween{\number\count@}{48}{57}%
{%
  #3%
}%
{%
\dtlifintclosedbetween{\number\count@}{97}{122}%
{%
  #2%
}%
{%
\dtlifintclosedbetween{\number\count@}{65}{90}%
{%
  #2%
}%
  #4%
}%
}%
}
\newcommand*{\dtlparsewords}[2]{%
\dtl@subnobrsp{#1}{\dtl@string}%
\DTLsubstituteall{\dtl@string}{~}{ }%
\DTLsubstituteall{\dtl@string}{\ }{ }%
\DTLsubstituteall{\dtl@string}{\space}{ }%
\DTLsubstituteall{\dtl@string}{-}{ }%
\let\dtl@parsewordshandler#2\relax
\edef\dtl@donext{%
\noexpand\@dtl@parse@words\expandonce\dtl@string\space\noexpand\@nil}%
\dtl@donext
}
\def\@dtl@parse@words#1 #2{%
\def\dtl@tmp{#2}%

```

```

\ifx\@nnil\dtl@tmp
  \let\parse@wordsnext=\@gobble
\else
  \let\parse@wordsnext=\@dtl@parse@words
\fi
\dlt@parsewordshandler{#1}%
\parse@wordsnext#2%
}
\newcommand*\@DTLifstringlt{\@ifstar\@sDTLifstringlt\@DTLifstringlt}
\newcommand*\@DTLifstringlt[4]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \ifnum\@dtl@tmpcount<0\relax
    #3%
  \else
    #4%
  \fi
}
\newcommand*\@sDTLifstringlt[4]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \ifnum\@dtl@tmpcount<0\relax
    #3%
  \else
    #4%
  \fi
}
\newcommand*\@DTLiflt{\@ifstar\@sDTLiflt\@DTLiflt}
\newcommand*\@DTLiflt[4]{%
  \dtl@testbothnumerical{#1}{#2}%
  \if@dtl@condition
    \DTLifnumlt{#1}{#2}{#3}{#4}%
  \else
    \@DTLifstringlt{#1}{#2}{#3}{#4}%
  \fi
}
\newcommand*\@sDTLiflt[4]{%
  \dtl@testbothnumerical{#1}{#2}%
  \if@dtl@condition
    \DTLifnumlt{#1}{#2}{#3}{#4}%
  \else
    \@sDTLifstringlt{#1}{#2}{#3}{#4}%
  \fi
}
\newcommand*\@DTLifnumgt[4]{%
  \DTLconverttodecimal{#1}{\@dtl@numi}%
  \DTLconverttodecimal{#2}{\@dtl@numii}%
  \dtlifnumgt{\@dtl@numi}{\@dtl@numii}%
}

```

```

    {%
      #3%
    }%
    {%
      #4%
    }%
  }
\newcommand*{\DTLifstringgt}{\@ifstar\@sDTLifstringgt\@DTLifstringgt}
\newcommand*{\@DTLifstringgt}[4]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \ifnum\@dtl@tmpcount>0\relax
    #3%
  \else
    #4%
  \fi
}
\newcommand*{\@sDTLifstringgt}[4]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \ifnum\@dtl@tmpcount>0\relax
    #3%
  \else
    #4%
  \fi
}
\newcommand*{\DTLifgt}{\@ifstar\@sDTLifgt\@DTLifgt}
\newcommand*{\@DTLifgt}[4]{%
  \dtl@testbothnumerical{#1}{#2}%
  \if@dtl@condition
    \DTLifnumgt{#1}{#2}{#3}{#4}%
  \else
    \@DTLifstringgt{#1}{#2}{#3}{#4}%
  \fi
}
\newcommand*{\@sDTLifgt}[4]{%
  \dtl@testbothnumerical{#1}{#2}%
  \if@dtl@condition
    \DTLifnumgt{#1}{#2}{#3}{#4}%
  \else
    \@sDTLifstringgt{#1}{#2}{#3}{#4}%
  \fi
}
\newcommand*{\DTLifnumeq}[4]{%
  \DTLconverttodecimal{#1}{\@dtl@numi}%
  \DTLconverttodecimal{#2}{\@dtl@numii}%
  \dtlifnumeq{\@dtl@numi}{\@dtl@numii}%
  {%

```

```

    #3%
  }%
  {%
    #4%
  }%
}
\newcommand*{\DTLifstringeq}{\@ifstar\@sDTLifstringeq\@DTLifstringeq}
\newcommand*{\@DTLifstringeq}[4]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \ifnum\@dtl@tmpcount=0\relax
    #3%
  \else
    #4%
  \fi
}
\newcommand*{\@sDTLifstringeq}[4]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \ifnum\@dtl@tmpcount=0\relax
    #3%
  \else
    #4%
  \fi
}
}
\newcommand*{\DTLifreq}{\@ifstar\@sDTLifreq\@DTLifreq}
\newcommand*{\@DTLifreq}[4]{%
  \dtl@testbothnumerical{#1}{#2}%
  \if@dtl@condition
    \DTLifnumeq{#1}{#2}{#3}{#4}%
  \else
    \@DTLifstringeq{#1}{#2}{#3}{#4}%
  \fi
}
\newcommand*{\@sDTLifreq}[4]{%
  \dtl@testbothnumerical{#1}{#2}%
  \if@dtl@condition
    \DTLifnumeq{#1}{#2}{#3}{#4}%
  \else
    \@sDTLifstringeq{#1}{#2}{#3}{#4}%
  \fi
}
}
\newcommand*{\DTLifSubString}[4]{%
  \protected@edef\@dtl@dotestifsubstring{\noexpand\dtl@testifsubstring
{#1}{#2}}%
  \@dtl@dotestifsubstring
  \if@dtl@condition
    #3%

```

```

\else
  #4%
\fi
}
\newcommand*{\dtl@testifsubstring}[2]{%
  \dtl@subnobrsp{#1}{\dtl@argA}%
  \dtl@subnobrsp{#2}{\dtl@argB}%
  \dtl@setwordbreaksnohyphens{\dtl@argA}{\dtl@wordbreak}%
  \let\dtl@argA\dtl@string
  \dtl@setwordbreaksnohyphens{\dtl@argB}{\dtl@wordbreak}%
  \let\dtl@argB\dtl@string
  \edef\dtl@donext{%
    \noexpand\dtl@testifsubstring{\expandonce\dtl@argA}{\expandonce\dtl@argB}}%
  \dtl@donext
}
\newcommand*{\@dtl@testifsubstring}[2]{%
  \def\dtl@subs@argA{#1}%
  \def\dtl@subs@argB{#2}%
  \ifdefempty{\dtl@subs@argB}%
  {%
    \@dtl@conditiontrue
  }%
  {%
    \ifdefempty{\dtl@subs@argA}%
    {%
      \@dtl@conditionfalse
    }%
    {%
      \@dtl@teststartswith{#1}{#2}%
      \if@dtl@condition
      \else
        \dtl@getfirst#1\end@dtl@getfirst
        \expandafter\dtl@ifsingle\expandafter{\dtl@first}%
        {%
          \expandafter\@dtl@testifsubstring\expandafter{\dtl@rest}{#2}%
        }%
        {%
          \protected@edef\dtl@donext{\noexpand\@dtl@testifsubstring
            {\expandonce\dtl@first\expandonce\dtl@rest}{\expandonce\dtl@subs@argB}}%
          \dtl@donext
        }%
      \fi
    }%
  }%
}
}
\newcommand*{\DTLifStartsWith}[4]{%
  \@dtl@conditionfalse
  \protected@edef\dtl@tmp{\noexpand\dtl@teststartswith{#1}{#2}}%
  \@dtl@tmp
  \if@dtl@condition

```

```

#3%
\else
#4%
\fi
}
\newcommand*{\dtl@teststartswith}[2]{%
\dtl@subnobrsp{#1}{\dtl@argA}%
\dtl@subnobrsp{#2}{\dtl@argB}%
\dtl@setwordbreaksnohyphens{\dtl@argA}{\dtl@wordbreak}%
\let\dtl@argA\dtl@string
\dtl@setwordbreaksnohyphens{\dtl@argB}{\dtl@wordbreak}%
\let\dtl@argB\dtl@string
\edef\dtl@donext{%
\noexpand\dtl@teststartswith{\expandonce\dtl@argA}{\expandonce\dtl@argB}}%
\dtl@donext
}

\newcommand*{\@dtl@teststartswith}[2]{%
\def\@dtl@argA{#1}%
\def\@dtl@argB{#2}%
\ifdefempty{\@dtl@argA}%
{%
\ifdefempty{\@dtl@argB}%
{%
\@dtl@conditiontrue
}%
{%
\@dtl@conditionfalse
}%
}%
}%
\ifdefempty{\@dtl@argB}%
{%
\@dtl@conditiontrue
}%
{%
\expandafter\dtl@getfirst\@dtl@argA\end@dtl@getfirst
\let\dtl@firstA=\dtl@first
\let\dtl@restA=\dtl@rest
\expandafter\dtl@getfirst\@dtl@argB\end@dtl@getfirst
\let\dtl@firstB=\dtl@first
\let\dtl@restB=\dtl@rest
\expandafter\dtl@ifsingle\expandafter{\dtl@firstA}%
{%
\expandafter\dtl@ifsingle\expandafter{\dtl@firstB}%
{%
\expandafter\dtl@setcharcode\expandafter{\dtl@firstA}{\dtl@codeA}%
\expandafter\dtl@setcharcode\expandafter{\dtl@firstB}{\dtl@codeB}%
\ifnum\dtl@codeA=-1\relax
\ifnum\dtl@codeB=-1\relax

```

```

        \protected@edef\dtl@donext{%
            \noexpand\@dtl@teststartswith{\expandonce\dtl@restA}{\expandonce\dtl@restB}}
        \dtl@donext
    \else
        \protected@edef\dtl@donext{%
            \noexpand\@dtl@teststartswith
                {\expandonce\dtl@restA}{\expandonce\dtl@firstB\expandonce\dtl@restB}}
        \dtl@donext
    \fi
\else
\ifnum\dtl@codeB=-1\relax
    \protected@edef\dtl@donext{%
        \noexpand\@dtl@teststartswith
            {\expandonce\dtl@firstA\expandonce\dtl@restA}{\expandonce\dtl@restB}}
        \dtl@donext
    \else
        \ifnum\dtl@codeA=\dtl@codeB
            \protected@edef\dtl@donext{%
                \noexpand\@dtl@teststartswith{\expandonce\dtl@restA}{\expandonce\dtl@restB}}
            \dtl@donext
        \else
            \@dtl@conditionfalse
        \fi
    \fi
\fi
\fi
}%
{%
\protected@edef\dtl@donext{%
    \noexpand\@dtl@teststartswith
        {\expandonce\dtl@firstA\expandonce\dtl@restA}%
        {\expandonce\dtl@firstB\expandonce\dtl@restB}}%
\dtl@donext
}%
}%
{%
\protected@edef\dtl@donext{%
    \noexpand\@dtl@teststartswith
        {\expandonce\dtl@firstA\expandonce\dtl@restA}%
        {\expandonce\dtl@firstB\expandonce\dtl@restB}}%
}%
}%
}
\newcommand*\DTLifnumclosedbetween}[5]{%
    \DTLconverttodecimal{#1}{\@dtl@numi}%
    \DTLconverttodecimal{#2}{\@dtl@numii}%
    \DTLconverttodecimal{#3}{\@dtl@numiii}%
    \DTLifFPclosedbetween{\@dtl@numi}{\@dtl@numii}{\@dtl@numiii}{#4}{#5}%
}
\newcommand*\DTLifstringclosedbetween}{%

```

```

    \@ifstar\@sDTLifstringclosedbetween\@DTLifstringclosedbetween
  }
\newcommand*{\@DTLifstringclosedbetween}[5]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \let\@dtl@dovalue\relax
  \ifnum\@dtl@tmpcount<0\relax
    \def\@dtl@dovalue{#5}%
  \fi
  \ifx\@dtl@dovalue\relax
    \protected@edef\@dtl@tmpcmp{%
      \noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#3}}%
    \@dtl@tmpcmp
    \ifnum\@dtl@tmpcount>0\relax
      \def\@dtl@dovalue{#5}%
    \else
      \def\@dtl@dovalue{#4}%
    \fi
  \fi
  \@dtl@dovalue
}
\newcommand*{\@sDTLifstringclosedbetween}[5]{%
  \protected@edef\@dtl@tmpcmp{%
    \noexpand\dtlicompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
  \@dtl@tmpcmp
  \let\@dtl@dovalue\relax
  \ifnum\@dtl@tmpcount<0\relax
    \def\@dtl@dovalue{#5}%
  \fi
  \ifx\@dtl@dovalue\relax
    \protected@edef\@dtl@tmpcmp{%
      \noexpand\dtlicompare{\noexpand\@dtl@tmpcount}{#1}{#3}}%
    \@dtl@tmpcmp
    \ifnum\@dtl@tmpcount>0\relax
      \def\@dtl@dovalue{#5}%
    \else
      \def\@dtl@dovalue{#4}%
    \fi
  \fi
  \@dtl@dovalue
}
\newcommand*{\DTLifclosedbetween}{%
  \@ifstar\@sDTLifclosedbetween\@DTLifclosedbetween
}
\newcommand*{\@DTLifclosedbetween}[5]{%
  \dtl@testbothnumerical{#2}{#3}%
  \if@dtl@condition
    \dtl@ifsingle{#1}{%
      \edef\@dtl@tmp{#1}}%
  \fi
}

```

```

\def\@dtl@tmp{#1}%
\expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
\ifnum\@dtl@datatype>0\relax
\DTLifnumclosedbetween{#1}{#2}{#3}{#4}{#5}%
\else
\@DTLifstringclosedbetween{#1}{#2}{#3}{#4}{#5}%
\fi
\else
\@DTLifstringclosedbetween{#1}{#2}{#3}{#4}{#5}%
\fi
}
\newcommand*\@sDTLifclosedbetween}[5]{%
\dtl@testbothnumerical{#2}{#3}%
\if@dtl@condition
\dtl@ifsingle{#1}{%
\edef\@dtl@tmp{#1}}{%
\def\@dtl@tmp{#1}}%
\expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
\ifnum\@dtl@datatype>0\relax
\DTLifnumclosedbetween{#1}{#2}{#3}{#4}{#5}%
\else
\@sDTLifstringclosedbetween{#1}{#2}{#3}{#4}{#5}%
\fi
\else
\@sDTLifstringclosedbetween{#1}{#2}{#3}{#4}{#5}%
\fi
}
\newcommand*\DTLifnumopenbetween}[5]{%
\DTLconverttodecimal{#1}{\@dtl@numi}%
\DTLconverttodecimal{#2}{\@dtl@numii}%
\DTLconverttodecimal{#3}{\@dtl@numiii}%
\DTLifFPopenbetween{\@dtl@numi}{\@dtl@numii}{\@dtl@numiii}{#4}{#5}%
}
\newcommand*\DTLifstringopenbetween}{%
\@ifstar\@sDTLifstringopenbetween\@DTLifstringopenbetween
}
\newcommand*\@DTLifstringopenbetween}[5]{%
\protected@edef\@dtl@tmpcmp{%
\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
\@dtl@tmpcmp
\let\@dtl@dovalue\relax
\ifnum\@dtl@tmpcount>0\relax
\else
\def\@dtl@dovalue{#5}%
\fi
\ifx\@dtl@dovalue\relax
\protected@edef\@dtl@tmpcmp{%
\noexpand\dtlcompare{\noexpand\@dtl@tmpcount}{#1}{#3}}%
\@dtl@tmpcmp
\ifnum\@dtl@tmpcount<0\relax

```

```

        \def\@dtl@dovalue{#4}%
    \else
        \def\@dtl@dovalue{#5}%
    \fi
\fi
\@dtl@dovalue
}
\newcommand*{\@sDTLifstringopenbetween}[5]{%
    \protected@edef\@dtl@tmpcmp{%
        \noexpand\dtlicompare{\noexpand\@dtl@tmpcount}{#1}{#2}}%
    \@dtl@tmpcmp
    \let\@dtl@dovalue\relax
    \ifnum\@dtl@tmpcount>0\relax
    \else
        \def\@dtl@dovalue{#5}%
    \fi
    \ifx\@dtl@dovalue\relax
        \protected@edef\@dtl@tmpcmp{%
            \noexpand\dtlicompare{\noexpand\@dtl@tmpcount}{#1}{#3}}%
        \@dtl@tmpcmp
        \ifnum\@dtl@tmpcount<0\relax
            \def\@dtl@dovalue{#4}%
        \else
            \def\@dtl@dovalue{#5}%
        \fi
    \fi
    \@dtl@dovalue
}
\newcommand*{\DTLifopenbetween}{%
    \@ifstar\@sDTLifopenbetween\@DTLifopenbetween
}
\newcommand*{\@DTLifopenbetween}[5]{%
    \dtl@testbothnumerical{#2}{#3}%
    \if@dtl@condition
        \dtl@ifsingle{#1}{%
            \edef\@dtl@tmp{#1}}{%
            \def\@dtl@tmp{#1}}%
        \expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
        \ifnum\@dtl@datatype>0\relax
            \DTLifnumopenbetween{#1}{#2}{#3}{#4}{#5}%
        \else
            \@DTLifstringopenbetween{#1}{#2}{#3}{#4}{#5}%
        \fi
    \else
        \@DTLifstringopenbetween{#1}{#2}{#3}{#4}{#5}%
    \fi
}
\newcommand*{\@sDTLifopenbetween}[5]{%
    \dtl@testbothnumerical{#2}{#3}%
    \if@dtl@condition

```

```

\dtl@ifsingle{#1}{%
  \edef\@dtl@tmp{#1}{%
    \def\@dtl@tmp{#1}{%
      \expandafter\@dtl@checknumerical\expandafter{\@dtl@tmp}%
      \ifnum\@dtl@datatype>0\relax
        \DTLifnumopenbetween{#1}{#2}{#3}{#4}{#5}%
      \else
        \@sDTLifstringopenbetween{#1}{#2}{#3}{#4}{#5}%
      \fi
    \else
      \@sDTLifstringopenbetween{#1}{#2}{#3}{#4}{#5}%
    \fi
  }
}
\let\DTLifFPopenbetween\dtlifnumopenbetween
\let\DTLifFPclosedbetween\dtlifnumclosedbetween
\newcommand*\@dtl@testlt}[2]{%
  \DTLiflt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\@DTLislt}[2]{%
  \TE@throw\noexpand\dtl@testlt{#1}{#2}\noexpand\if@dtl@condition
}
\newcommand*\@dtl@testiclt}[2]{%
  \@sDTLiflt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\@DTLisilt}[2]{%
  \TE@throw\noexpand\dtl@testiclt{#1}{#2}\noexpand\if@dtl@condition
}
\newcommand*\@dtl@testgt}[2]{%
  \DTLifgt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\@DTLisgt}[2]{%
  \TE@throw\noexpand\dtl@testgt{#1}{#2}\noexpand\if@dtl@condition
}
\newcommand*\@dtl@testicgt}[2]{%
  \@sDTLifgt{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\@DTLisigt}[2]{%
  \TE@throw\noexpand\dtl@testicgt{#1}{#2}\noexpand\if@dtl@condition
}
\newcommand*\@dtl@testeq}[2]{%
  \DTLifeq{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\@DTLiseq}[2]{%
  \TE@throw\noexpand\dtl@testeq{#1}{#2}\noexpand\if@dtl@condition
}
\newcommand*\@dtl@testiceq}[2]{%
  \@sDTLifeq{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\@DTLisieq}[2]{%
  \TE@throw\noexpand\dtl@testiceq{#1}{#2}\noexpand\if@dtl@condition
}

```

```

}
\newcommand*\DTLisSubString}[2]{%
  \TE@throw\noexpand\dtl@testifsubstring{#1}{#2}%
  \noexpand\if@dtl@condition
}
\newcommand*\DTLisPrefix}[2]{%
  \TE@throw\noexpand\dtl@teststartswith{#1}{#2}%
  \noexpand\if@dtl@condition
}
\newcommand*\DTLisinlist}[2]{%
  \TE@throw\noexpand\dtl@testinlist{#1}{#2}%
  \noexpand\if@dtl@condition
}
\newcommand*\dtl@testinlist}[2]{%
  \DTLifinlist{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\dtl@testnumclosedbetween}[3]{%
  \DTLifnumclosedbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\DTLisnumclosedbetween}[3]{%
  \TE@throw\noexpand\dtl@testnumclosedbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}
\newcommand*\dtl@testnumopenbetween}[3]{%
  \DTLifnumopenbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\DTLisnumopenbetween}[3]{%
  \TE@throw\noexpand\dtl@testnumopenbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}
\newcommand*\dtl@testclosedbetween}[3]{%
  \DTLifclosedbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\DTLisclosedbetween}[3]{%
  \TE@throw\noexpand\dtl@testclosedbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}
\newcommand*\dtl@testiclosedbetween}[3]{%
  \@sDTLifclosedbetween{#1}{#2}{#3}%
  {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\DTLisiclosedbetween}[3]{%
  \TE@throw\noexpand\dtl@testiclosedbetween{#1}{#2}{#3}%
  \noexpand\if@dtl@condition
}
\newcommand*\dtl@testopenbetween}[3]{%
  \DTLifopenbetween{#1}{#2}{#3}%

```

```

        {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
    }
\newcommand*\DTLisopenbetween}[3]{%
    \TE@throw\noexpand\dtl@testopenbetween{#1}{#2}{#3}%
    \noexpand\if@dtl@condition
}
\newcommand*\dtl@testiopenbetween}[3]{%
    \@sDTLifopenbetween{#1}{#2}{#3}%
    {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\DTLisiopenbetween}[3]{%
    \TE@throw\noexpand\dtl@testiopenbetween{#1}{#2}{#3}%
    \noexpand\if@dtl@condition
}
\let\DTLisFPclosedbetween\DTLisnumclosedbetween
\newcommand*\dtl@testFPopenbetween}[3]{%
    \DTLifFPopenbetween{#1}{#2}{#3}%
    {\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*\DTLisFPopenbetween}[3]{%
    \TE@throw\noexpand\dtl@testFPopenbetween{#1}{#2}{#3}%
    \noexpand\if@dtl@condition
}
\newcommand*\dtl@testFPislt}[2]{%
    \dtlifnumlt{#1}{#2}%
    {%
        \@dtl@conditiontrue
    }%
    {%
        \@dtl@conditionfalse
    }%
}
\newcommand*\DTLisFPlt}[2]{%
    \TE@throw\noexpand\dtl@testFPislt{#1}{#2}%
    \noexpand\if@dtl@condition
}
\newcommand*\dtl@testFPisgt}[2]{%
    \dtlifnumgt{#1}{#2}%
    {%
        \@dtl@conditiontrue
    }%
    {%
        \@dtl@conditionfalse
    }%
}
\newcommand*\DTLisFPgt}[2]{%
    \TE@throw\noexpand\dtl@testFPisgt{#1}{#2}%
    \noexpand\if@dtl@condition
}
\newcommand*\dtl@testFPiseq}[2]{%

```

```

\dtlifnumeq{#1}{#2}%
{%
  \@dtl@conditiontrue
}%
{%
  \@dtl@conditionfalse
}%
}
\newcommand*{\DTLisFPeq}[2]{%
  \TE@throw\noexpand\dtl@testFPiseq{#1}{#2}%
  \noexpand\if@dtl@condition
}
\newcommand*{\dtl@testFPislteq}[2]{%
  \dtlifnumlt{#1}{#2}%
  {%
    \@dtl@conditiontrue
  }%
  {%
    \@dtl@conditionfalse
  }%
  \if@dtl@condition
  \else
  \dtl@testFPiseq{#1}{#2}%
  \fi
}
\newcommand*{\DTLisFPlteq}[2]{%
  \TE@throw\noexpand\dtl@testFPislteq{#1}{#2}%
  \noexpand\if@dtl@condition
}
\newcommand*{\dtl@testFPisgteq}[2]{%
  \dtlifnumgt{#1}{#2}%
  {%
    \@dtl@conditiontrue
  }%
  {%
    \@dtl@conditionfalse
  }%
  \if@dtl@condition
  \else
  \dtl@testFPiseq{#1}{#2}%
  \fi
}
\newcommand*{\DTLisFPgteq}[2]{%
  \TE@throw\noexpand\dtl@testFPisgteq{#1}{#2}%
  \noexpand\if@dtl@condition}
\newcommand*{\dtl@teststring}[1]{%
  \DTLifstring{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}
\newcommand*{\DTLisstring}[1]{%
  \TE@throw\noexpand\dtl@teststring{#1}\noexpand\if@dtl@condition}
\newcommand*{\dtl@testnumerical}[1]{%

```

```

\DTLifnumerical{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}%
}
\newcommand*{\DTLisnumerical}[1]{%
\TE@throw\noexpand\dtl@testnumerical{#1}\noexpand\if@dtl@condition}
\newcommand*{\dtl@testint}[1]{%
\DTLifint{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}
\newcommand*{\DTLisint}[1]{%
\TE@throw\noexpand\dtl@testint{#1}\noexpand\if@dtl@condition}
\newcommand*{\dtl@testreal}[1]{%
\DTLifreal{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}
\newcommand*{\DTLisreal}[1]{%
\TE@throw\noexpand\dtl@testreal{#1}\noexpand\if@dtl@condition}
\newcommand*{\dtl@testcurrency}[1]{%
\DTLifcurrency{#1}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}
\newcommand*{\DTLiscurrency}[1]{%
\TE@throw\noexpand\dtl@testcurrency{#1}\noexpand\if@dtl@condition}
\newcommand*{\dtl@testcurrencyunit}[2]{%
\DTLifcurrencyunit{#1}{#2}{\@dtl@conditiontrue}{\@dtl@conditionfalse}}
\newcommand*{\DTLiscurrencyunit}[2]{%
\TE@throw\noexpand\dtl@testcurrencyunit{#1}{#2}%
\noexpand\if@dtl@condition}
}
\newcommand*{\dtlbreak}{%
\PackageError{datatool}{Can't break out of anything}{}%
}
\long\def\dtlforint#1=#2\to#3\step#4\do#5{%
\let\@dtl@orgbreak\dtlbreak
\def\@dtl@endloophook{}%
\def\dtlbreak{\def\@dtl@endloophook{#1=#3}}%
#1=#2\relax
\ifnum#4<0\relax
\whiledo{\(#1>#3)\TE@or\(#1=#3)\}%
{%
#5%
\@dtl@endloophook
\advance#1 by #4\relax
}%
\else
\whiledo{\(#1<#3)\TE@or\(#1=#3)\}%
{%
#5%
\@dtl@endloophook
\advance#1 by #4\relax
}%
\fi
\let\dtlbreak\@dtl@orgbreak
}
\newcount\@dtl@foreach@level
\long\def\dtlforeachint#1=#2\to#3\step#4\do#5{%
\global#1=#2\relax

```

```

\global\advance\@dtl@foreach@level by 1\relax
\expandafter\global\expandafter
  \let\csname @dtl@endhook@\the\@dtl@foreach@level\endcsname
  \relax
\expandafter\global\expandafter
  \let\csname @dtl@break@\the\@dtl@foreach@level\endcsname
  \dtlbreak
\gdef\dtlbreak{\expandafter
  \gdef\csname @dtl@endhook@\the\@dtl@foreach@level\endcsname{%
    #1=#3}}%
\ifnum#4<0\relax
  \whiledo{\(#1>#3\)\TE@or\(#1=#3\)}%
  {%
    #5%
    \csname @dtl@endhook@\the\@dtl@foreach@level\endcsname
    \global\advance#1 by #4\relax
  }%
\else
  \whiledo{\(#1<#3\)\TE@or\(#1=#3\)}%
  {%
    #5%
    \csname @dtl@endhook@\the\@dtl@foreach@level\endcsname
    \global\advance#1 by #4\relax
  }%
\fi
\expandafter\global\expandafter\let\expandafter\dtlbreak
  \csname @dtl@break@\the\@dtl@foreach@level\endcsname
\global\advance\@dtl@foreach@level by -1\relax
}
\newenvironment{dtlenvgforint}[1]%
{%
  \def\@dtlenvgforint@arg{#1}%
  \long@collect@body\@do@dtlenvgforint
}%
{}
\newcommand{\@do@dtlenvgforint}[1]{%
  \expandafter\dtlgforint\@dtlenvgforint@arg\do{#1}%
}

```

30.17 Rollback v2.32 (datatool-fp-2019-09-27.sty)

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datatool-fp}[2019/09/27 v2.32 (NLCT)]
\RequirePackage{xkeyval}
\RequirePackage{fp}
\RequirePackage{datatool-base}[=v2.32]
\define@choicekey{datatool-fp}{verbose}[\val\nr]{true,false}[true]{%
  \ifcase\nr\relax
    \FPmessagestrue
  \or

```

```

        \FPmessagesfalse
    \fi
}
\let\ifFPmessages\ifdtlverbose
\ProcessOptionsX
\providecommand*\@dtl@mathprocessor}{fp}
\newcommand*\dtlifnumeq}[4]{%
    \FPifeq{#1}{#2}%
    #3%
    \else
    #4%
    \fi
}
\let\ifdtlverbose\ifFPmessages
\newcommand*\dtlifnumlt}[4]{%
    \FPiflt{#1}{#2}%
    #3%
    \else
    #4%
    \fi
}
\newcommand*\dtlifnumgt}[4]{%
    \FPifgt{#1}{#2}%
    #3%
    \else
    #4%
    \fi
}
\newcommand*\dtlifnumopenbetween}[5]{%
    \let\@dtl@dovalue\relax
    \dtlifnumgt{#1}{#2}%
    {}%
    {%
        \def\@dtl@dovalue{#5}%
    }%
    \dtlifnumlt{#1}{#3}%
    {%
        \ifx\@dtl@dovalue\relax
            \def\@dtl@dovalue{#4}%
        \fi
    }%
    {}%
    \def\@dtl@dovalue{#5}%
}
\@dtl@dovalue
}
\newcommand*\dtlifnumclosedbetween}[5]{%
    \let\@dtl@dovalue\relax
    \dtlifnumgt{#1}{#2}%
    {}%

```

```

{%
  \dtlifnumeq{#1}{#2}%
  {%
    \def\@dtl@dovalue{#4}%
  }%
  {%
    \def\@dtl@dovalue{#5}%
  }%
}%
\dtlifnumlt{#1}{#3}%
{%
  \ifx\@dtl@dovalue\relax
    \def\@dtl@dovalue{#4}%
  \fi
}%
{%
  \dtlifnumeq{#1}{#3}%
  {%
    \def\@dtl@dovalue{#4}%
  }%
  {%
    \def\@dtl@dovalue{#5}%
  }%
}%
\@dtl@dovalue
}
\newcommand*\@dtladd}[3]{%
  \FPadd{#1}{#2}{#3}%
}
\newcommand*\@dtlsub}[3]{%
  \FPsub{#1}{#2}{#3}%
}
\newcommand*\@dtlmul}[3]{%
  \FPmul{#1}{#2}{#3}%
}
\newcommand*\@dtldiv}[3]{%
  \FPdiv{#1}{#2}{#3}%
}
\newcommand*\@dtlroot}[2]{%
  \FProot{#1}{#2}%
}
\newcommand*\@dtlround}[3]{%
  \FPround{#1}{#2}{#3}%
}
\newcommand*\@dtltrunc}[3]{%
  \FPtrunc{#1}{#2}{#3}%
}
\newcommand*\@dtlclip}[2]{%
  \FPclip{#1}{#2}%
}
}

```

```

\newcommand*\dtlmin}[3]{%
  \FPmin{#1}{#2}{#3}%
}
\newcommand*\dtlmax}[3]{%
  \FPmax{#1}{#2}{#3}%
}
\newcommand*\dtlabs}[2]{%
  \FPabs{#1}{#2}%
}
\newcommand*\dtlneg}[2]{%
  \FPneg{#1}{#2}%
}

```

30.18 Rollback v2.32 (datatool-pgfmth-2019-09-27.sty)

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{datatool-pgfmth}[2019/09/27 v2.32 (NLCT)]
\RequirePackage{xkeyval}
\RequirePackage{pgfrcs,pgfkeys,pgfmth}
\ProcessOptionsX
\providecommand*\@dtl@mathprocessor}{pgfmth}
\newcommand*\dtlifnumeq}[4]{%
  \def\@dtl@truepart{#3}%
  \def\@dtl@falsepart{#4}%
  \pgfmthifthenelse{\number0#1==\number0#2}%
    {"\noexpand\@dtl@truepart"}{"\noexpand\@dtl@falsepart"}%
  \pgfmthresult
}
\RequirePackage{datatool-base}[=v2.32]
\newcommand*\dtlifnumlt}[4]{%
  \def\@dtl@truepart{#3}%
  \def\@dtl@falsepart{#4}%
  \pgfmthifthenelse{\number0#1 < \number0#2}%
    {"\noexpand\@dtl@truepart"}{"\noexpand\@dtl@falsepart"}%
  \pgfmthresult
}
\newcommand*\dtlifnumgt}[4]{%
  \def\@dtl@truepart{#3}%
  \def\@dtl@falsepart{#4}%
  \pgfmthifthenelse{\number0#1 > \number0#2}%
    {"\noexpand\@dtl@truepart"}{"\noexpand\@dtl@falsepart"}%
  \pgfmthresult
}
\newcommand*\dtlifnumopenbetween}[5]{%
  \def\@dtl@truepart{#4}%
  \def\@dtl@falsepart{#5}%
  \pgfmthifthenelse
    {(\number0#2 < \number0#1) && (\number0#1 < \number0#3)}%
    {"\noexpand\@dtl@truepart"}{"\noexpand\@dtl@falsepart"}%
  \pgfmthresult
}

```

```

}
\newcommand*\dtlifnumclosedbetween}[5]{%
  \def\dtl@truepart{#4}%
  \def\dtl@falsepart{#5}%
  \pgfmathifthenelse
    {(\number0#2 <= \number0#1) && (\number0#1 <= \number0#3)}
    {"\noexpand\dtl@truepart"}{"\noexpand\dtl@falsepart"}%
  \pgfmathresult
}
\newcommand*\dtladd}[3]{%
  \pgfmathadd{#2}{#3}%
  \let#1\pgfmathresult
}
\newcommand*\dtlsub}[3]{%
  \pgfmathsubtract{#2}{#3}%
  \let#1\pgfmathresult
}
\newcommand*\dtlmul}[3]{%
  \pgfmathmultiply{#2}{#3}%
  \let#1\pgfmathresult
}
\newcommand*\dtldiv}[3]{%
  \pgfmathdivide{#2}{#3}%
  \let#1\pgfmathresult
}
\newcommand*\dtlroot}[2]{%
  \pgfmathsqrt{#2}%
  \let#1\pgfmathresult
}
\newcommand*\dtlround}[3]{%
  \ifnum#3=0\relax
    \pgfmathparse{int(round(#2))}%
    \let#1\pgfmathresult
  \else
    \pgfmathparse{int(10^#3)}%
    \let\dtl@tmpshift\pgfmathresult
    \pgfmathparse{int(floor(#2))}%
    \let\dtl@int@round\pgfmathresult
    \pgfmathparse{int(round((#2-\dtl@int@round) * \dtl@tmpshift))}%
    \dtl@tmpcount=0\relax
    \expandafter\dtl@countdigits\pgfmathresult.\relax
    \advance\dtl@tmpcount by -#3\relax
    \def\dtl@intpart{}%
    \def\dtl@fracpart{}%
    \expandafter\dtl@gatherintfrac\pgfmathresult\relax
    \edef\dtl@intpart{\number\numexpr\dtl@int@round
      +\number0\dtl@intpart}%
    \edef#1{\dtl@intpart.\dtl@fracpart}%
  \fi
}

```

```

\newcommand*\@dtl@gatherintfrac}[1]{%
  \ifx\relax#1\relax
  \else
    \advance\@dtl@tmpcount by -1\relax
    \ifnum\@dtl@tmpcount<0\relax
      \edef\@dtl@fracpart{\@dtl@fracpart#1}%
    \else
      \edef\@dtl@intpart{\@dtl@intpart#1}%
    \fi
    \expandafter\@dtl@gatherintfrac
  \fi
}
\newcommand*\@dtl@trunc}[3]{%
  \ifnum#3=0\relax
    \pgfmathparse{int(floor(#2))}%
    \let#1\pgfmathresult
  \else
    \pgfmathparse{int(10^#3)}%
    \let\@dtl@tmpshift\pgfmathresult
    \pgfmathparse{int(floor(#2))}%
    \let\@dtl@int@trunc\pgfmathresult
    \pgfmathparse{int(floor((#2-\@dtl@int@trunc) * \@dtl@tmpshift))}%
    \@dtl@tmpcount=0\relax
    \expandafter\@dtl@countdigits\pgfmathresult.\relax
    \advance\@dtl@tmpcount by -#3\relax
    \def\@dtl@intpart{}%
    \def\@dtl@fracpart{}%
    \expandafter\@dtl@gatherintfrac\pgfmathresult\relax
    \edef\@dtl@intpart{\number\numexpr\@dtl@int@trunc
      +\number0\@dtl@intpart}%
    \edef#1{\@dtl@intpart.\@dtl@fracpart}%
  \fi
}
\newcommand*\@dtl@clip}[2]{%
  \edef#1{#2}%
}
\newcommand*\@dtl@min}[3]{%
  \pgfmathmin{#2}{#3}%
  \let#1\pgfmathresult
}
\newcommand*\@dtl@max}[3]{%
  \pgfmathmax{#2}{#3}%
  \let#1\pgfmathresult
}
\newcommand*\@dtl@abs}[2]{%
  \pgfmathabs{#2}%
  \let#1\pgfmathresult
}
\newcommand*\@dtl@neg}[2]{%
  \pgfmathmul{-1}{#2}%

```

```

\let#1\pgfmathresult
}

```

30.19 Rollback v2.32 (person-2019-09-27.sty)

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{person}[2019/09/27 v2.32 (NLCT)]
\RequirePackage{ifthen}
\RequirePackage{datatool}[=v2.32]
\newcounter{people}
\newcounter{person}
\newcommand*\@people@list}{,}
\newcommand*\@get@firstperson}[1]{%
\expandafter\@get@firstperson\@people@list,\@nil{#1}}
\def\@get@firstperson,#1,#2\@nil#3{%
\def#3{#1}%
}
\newcommand*\@malelabels}{male, Male, MALE, M, m}
\newcommand*\@addmalelabel}[1]{%
\expandafter\@dtl@toksA\expandafter{\@malelabels}%
\expandafter\@dtl@toksB\expandafter{#1}%
\edef\@malelabels{\the\@dtl@toksA,\the\@dtl@toksB}%
}
\newcommand*\@addfemalelabel}[1]{%
\expandafter\@dtl@toksA\expandafter{\@femalelabels}%
\expandafter\@dtl@toksB\expandafter{#1}%
\edef\@femalelabels{\the\@dtl@toksA,\the\@dtl@toksB}%
}
\newcommand*\@femalelabels}{female, Female, FEMALE, F, f}
\newcommand*\@iffmalelabel}[3]{%
\expandafter\DTLifinlist\expandafter{#1}{\@malelabels}{#2}{#3}%
}
\newcommand*\@ifffemalelabel}[3]{%
\expandafter\DTLifinlist\expandafter{#1}{\@femalelabels}{#2}{#3}%
}
\newcommand*\@newperson}[4][anon]{%
\@ifundefined{person@#1@name}%
{%
\iffmalelabel{#4}%
{%
\expandafter\gdef\csname person@#1@gender\endcsname{male}%
}%
{%
\iffemalelabel{#4}%
{%
\expandafter\gdef\csname person@#1@gender\endcsname{female}%
}%
}%
\PackageError{person}{Unknown gender `#4' for person
`#1'}{Allowed gender labels are: \@malelabels\space or

```

```

        \femalelabels}%
        \@namedef{person@#1@gender}{other}%
    }%
}%
\expandafter
\protected@xdef\csname person@#1@fullname\endcsname{#2}%
\expandafter
\protected@xdef\csname person@#1@name\endcsname{#3}%
\protected@xdef\@people@list{\@people@list#1,}%
\stepcounter{people}%
}%
{%
\PackageError{person}{Person `#1' has already been defined}{}%
}%
}
\newcommand*\removeperson}[1][anon]{%
\edef\@person@label{#1}%
\expandafter\removeperson\expandafter{\@person@label}%
}
\newcommand*\@removeperson}[1]{%
\ifpersonexists{#1}%
{%
\def\@remove@person##1, #1, ##2\@nil{%
\def\@prsn@pre{##1}\def\@prsn@post{##2}}%
\expandafter\@remove@person\@people@list\@nil
\xdef\@people@list{\@prsn@pre, \@prsn@post}%
\addtocounter{people}{-1}%
\expandafter\global\expandafter
\let\csname person@#1@name\endcsname\undefined
\expandafter\global\expandafter
\let\csname person@#1@fullname\endcsname\undefined
\expandafter\global\expandafter
\let\csname person@#1@gender\endcsname\undefined
}%
{%
\PackageError{person}{Can't remove person `#1': no such
person}{}%
}%
}
\newcommand*\removepeople}[1]{%
\@for\@thisperson:=#1\do{%
\ifx\@thisperson\@empty
\else
\expandafter\removeperson\expandafter[\@thisperson]%
\fi
}%
}
\newcommand*\removeallpeople{%
\@for\@thisperson:=\@people@list\do{%
\expandafter\global\expandafter

```

```

        \let\csname person@\@thisperson @name\endcsname\undefined
        \expandafter\global\expandafter
        \let\csname person@\@thisperson @fullname\endcsname\undefined
        \expandafter\global\expandafter
        \let\csname person@\@thisperson @gender\endcsname\undefined
    }%
    \setcounter{people}{0}%
    \gdef\@people@list{,}%
}
\newcommand{\ifpersonexists}[3]{%
    \@ifundefined{person@#1@name}{#3}{#2}%
}
\newcommand{\ifmale}[3]{%
    \ifpersonexists{#1}%
    {%
        \edef\@gender{\csname person@#1@gender\endcsname}%
        \ifx\@gender\@male@label
            #2%
        \else
            #3%
        \fi
    }%
    {%
        \PackageError{person}{Person `#1' doesn't exist.}{}%
    }%
}
\def\@male@label{male}
\newcommand{\ifallmale}[3][\@people@list]{%
    \@for\@thisperson:=#1\do{%
        \ifpersonexists{\@thisperson}%
        {%
            \edef\@gender{\csname person@\@thisperson @gender\endcsname}%
            \ifx\@gender\@male@label
                \endfortrue
            \fi
        }%
        {%
            \PackageError{person}{Person `#1' doesn't exist.}{}%
        }%
    }%
}
\if@endfor
    #3%
\else
    #2%
\fi
}
\newcommand{\iffemale}[3]{%
    \ifpersonexists{#1}%
    {%

```

```

\edef\@gender{\csname person@#1@gender\endcsname}%
\ifx\@gender\@female@label
#2%
\else
#3%
\fi
}%
{%
\PackageError{person}{Person `#1' doesn't exist.}{}%
}%
}
\def\@female@label{female}
\newcommand{\ifallfemale}[3][\@people@list]{%
\@for\@thisperson:=#1\do{%
\edef\@gender{\csname person@\@thisperson @gender\endcsname}%
\ifx\@gender\@female@label
\else
\@endfortrue
\fi
}%
\if@endfor
#3%
\else
#2%
\fi
}
\def\foreachperson(#1,#2,#3,#4)#5{%
\ifx#5\in
\def\@do@foreachperson{\@foreachperson(#1,#2,#3,#4)#5}%
\else
\def\@do@foreachperson{%
\@foreachperson(#1,#2,#3,#4)\in\@people@list#5}%
\fi
\@do@foreachperson
}
\long\def\@foreachperson(#1,#2,#3,#4)\in#5\do#6{%
\@for#4:=#5\do{%
\ifx#4@empty
\else
\ifpersonexists{#4}%
{%
\expandafter
\let\expandafter#1\csname person@#4@name\endcsname
\expandafter
\let\expandafter#2\csname person@#4@fullname\endcsname
\expandafter
\let\expandafter#3\csname person@#4@gender\endcsname
\ifx#3\@male@label
\let#3\malename
\else

```

```

        \ifx#3\@female@label
        \let#3\femalename
        \fi
    \fi
    \fi
    #6%
}%
{%
\PackageError{person}{Person `#4' doesn't exist}{}%
}%
\fi
}%
}
\newcommand*\malepronoun{he}
\newcommand*\femalepronoun{she}
\newcommand*\pluralpronoun{they}
\newcommand*\maleobjpronoun{him}
\newcommand*\femaleobjpronoun{her}
\newcommand*\pluralobjpronoun{them}
\newcommand*\malepossadj{his}
\newcommand*\femalepossadj{her}
\newcommand*\pluralpossadj{their}
\newcommand*\maleposspronoun{his}
\newcommand*\femaleposspronoun{hers}
\newcommand*\pluralposspronoun{theirs}
\newcommand*\malechild{son}
\newcommand*\femalechild{daughter}
\newcommand*\pluralchild{children}
\newcommand*\malechildren{sons}
\newcommand*\femalechildren{daughters}
\newcommand*\maleparent{father}
\newcommand*\femaleparent{mother}
\newcommand*\pluralparent{parents}
\newcommand*\malesibling{brother}
\newcommand*\femalesibling{sister}
\newcommand*\pluralsibling{siblings}
\newcommand*\malesiblings{brothers}
\newcommand*\femalesiblings{sisters}
\providecommand*\andname{and}
\newcommand*\malename{male}
\newcommand*\femalename{female}
\newcommand*\personsep}{, }
\newcommand*\personlastsep}{\space\andname\space}
\newcommand*\twopeoplesep}{\space\andname\space}
\newcommand*\personfullname}[1][anon]{%
\@ifundefined{person@#1@fullname}%
{%
\PackageError{person}{Person `#1' has not been defined}{}%
}%
{%
\csname person@#1@fullname\endcsname

```

```

    }%
  }
\newcommand*{\peoplefullname}{%
  \setcounter{person}{1}%
  \@for\@thisperson:=\@people@list\do{%
    \ifthenelse{\equal{\@thisperson}{}}{%
      }%
      {%
        \personfullname[\@thisperson]%
        \stepcounter{person}%
        \ifnum\c@people=1\relax
        \else
          \ifnum\c@person=\c@people
            \ifnum\c@people=2\relax
              \twopeoplesep
            \else
              \personlastsep
            \fi
          \else
            \ifnum\c@person<\c@people
              \personsep
            \fi
          \fi
        \fi
      }%
    }%
  }
\newcommand*{\personname}[1][anon]{%
  \@ifundefined{person@#1@name}%
  {%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \csname person@#1@name\endcsname
  }%
}
\newcommand*{\peoplename}{%
  \setcounter{person}{1}%
  \@for\@thisperson:=\@people@list\do{%
    \ifthenelse{\equal{\@thisperson}{}}{%
      }%
      {%
        \personname[\@thisperson]%
        \stepcounter{person}%
        \ifnum\c@people=1\relax
        \else
          \ifnum\c@person=\c@people
            \ifnum\c@people=2\relax
              \twopeoplesep
            \else
              \else
            \fi
          \fi
        \fi
      }%
    }%
  }

```

```

        \personlastsep
      \fi
    \else
      \ifnum\c@person<\c@people
        \personsep
      \fi
    \fi
  \fi
}
}%
}
}
\newcommand*{\personpronoun}[1][anon]{%
  \@ifundefined{person@#1@gender}{%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender pronoun\endcsname
  }%
}
\newcommand*{\Personpronoun}[1][anon]{%
  \@ifundefined{person@#1@gender}{%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \expandafter\expandafter\expandafter
    \MakeUppercase\csname\@gender pronoun\endcsname
  }%
}
\newcommand*{\peoplepronoun}{%
  \ifnum\c@people>1\relax
    \pluralpronoun
  \else
    \@get@firstperson{\@thisperson}%
    \personpronoun[\@thisperson]%
  \fi
}
\newcommand*{\Peoplepronoun}{%
  \ifnum\c@people>1\relax
    \expandafter\MakeUppercase\pluralpronoun
  \else
    \@get@firstperson{\@thisperson}%
    \Personpronoun[\@thisperson]%
  \fi
}
\newcommand*{\personobjpronoun}[1][anon]{%
  \@ifundefined{person@#1@gender}{%

```

```

    {%
      \PackageError{person}{Person `#1' has not been defined}{}%
    }%
    {%
      \edef\@gender{\csname person@#1@gender\endcsname}%
      \csname\@gender objpronoun\endcsname
    }%
  }
\newcommand*\Personobjpronoun}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \expandafter\expandafter\expandafter
    \MakeUppercase\csname\@gender objpronoun\endcsname
  }%
}
\newcommand*\peopleobjpronoun}{%
  \ifnum\c@people>1\relax
    \pluralobjpronoun
  \else
    \@get@firstperson{\@thisperson}%
    \personobjpronoun[\@thisperson]%
  \fi
}
\newcommand*\Peopleobjpronoun}{%
  \ifnum\c@people>1\relax
    \expandafter\MakeUppercase\pluralobjpronoun
  \else
    \@get@firstperson{\@thisperson}%
    \Personobjpronoun[\@thisperson]%
  \fi
}
\newcommand*\personpossadj}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender possadj\endcsname
  }%
}
\newcommand*\Personpossadj}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
}

```

```

    {%
      \edef\@gender{\csname person@#1@gender\endcsname}%
      \expandafter\expandafter\expandafter
      \MakeUppercase\csname\@gender possadj\endcsname
    }%
  }
\newcommand*\peoplepossadj{%
  \ifnum\c@people>1\relax
    \pluralpossadj
  \else
    \@get@firstperson{\@thisperson}%
    \personpossadj[\@thisperson]%
  \fi
}
\newcommand*\Peoplepossadj{%
  \ifnum\c@people>1\relax
    \expandafter\MakeUppercase\pluralpossadj
  \else
    \@get@firstperson{\@thisperson}%
    \Personpossadj[\@thisperson]%
  \fi
}
\newcommand*\personposspronoun}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender posspronoun\endcsname
  }%
}
\newcommand*\Personposspronoun}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \expandafter\expandafter\expandafter
    \MakeUppercase\csname\@gender posspronoun\endcsname
  }%
}
\newcommand*\peopleposspronoun{%
  \ifnum\c@people>1\relax
    \pluralposspronoun
  \else
    \@get@firstperson{\@thisperson}%
    \personposspronoun[\@thisperson]%
  \fi
}

```

```

}
\newcommand*{\Peoplepossproun}{%
  \ifnum\c@people>1\relax
    \expandafter\MakeUppercase\pluralpossproun
  \else
    \@get@firstperson{\@thisperson}%
    \Personpossproun[\@thisperson]%
  \fi
}
\newcommand*{\personchild}[1][anon]{%
  \@ifundefined{person@#1@gender}{%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender child\endcsname
  }%
}
\newcommand*{\Personchild}[1][anon]{%
  \@ifundefined{person@#1@gender}{%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \expandafter\expandafter\expandafter\MakeUppercase
      \csname\@gender child\endcsname
  }%
}
\newcommand*{\peoplechild}{%
  \ifnum\c@people>1\relax
    \ifallmale
      {\malechildren}%
      {\ifallfemale{\femalechildren}{\pluralchild}}%
    \else
      \@get@firstperson{\@thisperson}%
      \personchild[\@thisperson]%
    \fi
}
\newcommand*{\Peoplechild}{%
  \ifnum\c@people>1\relax
    \ifallmale
      {\expandafter\MakeUppercase\malechildren}%
      {\ifallfemale
        {\expandafter\MakeUppercase\femalechildren}
        {\expandafter\MakeUppercase\pluralchild}}%
    \else
      \@get@firstperson{\@thisperson}%
      \Personchild[\@thisperson]%
    \fi
}

```

```

\fi
}
\newcommand*{\personparent}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender parent\endcsname
  }%
}
\newcommand*{\Personparent}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \expandafter\expandafter\expandafter\MakeUppercase
      \csname\@gender parent\endcsname
  }%
}
\newcommand*{\peopleparent}{%
  \ifnum\c@people>1\relax
    \pluralparent
  \else
    \@get@firstperson{\@thisperson}%
    \personparent[\@thisperson]%
  \fi
}
\newcommand*{\Peopleparent}{%
  \ifnum\c@people>1\relax
    \expandafter\MakeUppercase\pluralparent
  \else
    \@get@firstperson{\@thisperson}%
    \Personparent[\@thisperson]%
  \fi
}
\newcommand*{\personsibling}[1][anon]{%
  \@ifundefined{person@#1@gender}%
  {%
    \PackageError{person}{Person `#1' has not been defined}{}%
  }%
  {%
    \edef\@gender{\csname person@#1@gender\endcsname}%
    \csname\@gender sibling\endcsname
  }%
}
\newcommand*{\PersonSibling}[1][anon]{%

```

```

\@ifundefined{person@#1@gender}%
{%
  \PackageError{person}{Person `#1' has not been defined}{}%
}%
{%
  \edef\@gender{\csname person@#1@gender\endcsname}%
  \expandafter\expandafter\expandafter\MakeUppercase
    \csname\@gender sibling\endcsname
}%
}
\newcommand*\peoplesibling{%
  \ifnum\c@people>1\relax
    \ifallmale
      {\malesiblings}%
      {\ifallfemale{\femalesiblings}{\pluralsibling}}%
    \else
      \@get@firstperson{\@thisperson}%
      \personsibling[\@thisperson]%
    \fi
  }
\newcommand*\persongender}[1]{%
  \ifmale{#1}{\malename}{\femalename}%
}
\newcommand*\getpersongender}[2]{%
  \ifmale{#2}{\let#1\malename}{\let#1\femalename}%
}
\newcommand*\getpersonname}[2]{%
  \ifpersonexists{#2}%
  {%
    \expandafter\let\expandafter#1\csname person@#2@name\endcsname
  }%
  {%
    \PackageError{person}{Person `#2' doesn't exist}{}%
  }%
}
\newcommand*\getpersonfullname}[2]{%
  \ifpersonexists{#2}%
  {%
    \expandafter
      \let\expandafter#1\csname person@#2@fullname\endcsname
  }%
  {%
    \PackageError{person}{Person `#2' doesn't exist}{}%
  }%
}
}

```

Change History

1.01 – 2007 Aug 17	
General: uses \@sDTLforeach instead of \DTLforeach . . .	925
\DTLaddall: removed extraneous space	201
\dtlcompare: replaces \compare (no longer using compare.tex)	233
\DTLforeach: added starred version	495
\DTLgetrowforkey: new	565
\DTLgetvalueforkey: new	565
\dtlicompare: new	234
\DTLifclosedbetween: added starred version	247
\DTLifreq: added starred version	243
\DTLifrgt: added starred version	241
\DTLiflstrrow: fixed bug	511
\DTLiflft: added starred version	240
\DTLifopenbetween: added starred version	249
\DTLifStartsWith: new	245
\DTLifstringclosedbetween: added starred version	246
\DTLifstringeq: added starred version	242
\DTLifstringgt: added starred version	241
\DTLifstringlt: added starred version	239
\DTLifstringopenbetween: added starred version	248
\DTLifSubString: new	244
\DTLinitialhyphen: new	219
\DTLinitials: now uses \DTLinitialhyphen	215
now works with unbreakable space symbol	215
\DTLisiclosedbetween: new	255
\DTLisieq: new	252
\DTLisigt: new	251
\DTLisilt: new	251
\DTLisiopenbetween: new	255
\DTLisiSubString: new	252
\DTLisPrefix: new	252
\DTLisSubString: new	252
\DTLisSuffix: new	253
\DTLmaxall: removed extraneous space	204
\DTLmeanforall: removed extraneous space	205
\DTLminall: removed extraneous space	204
\DTLplotstream: uses \@sDTLforeach instead of \DTLforeach	961
\DTLremovecurrentrow: fix bug caused by missing \fi and unrequired argument	507
\DTLsdforall: fixed bug	207
removed extraneous space	207
\DTLsort: added optional argument	585
added starred version	585
\DTLsplitstring: new	220
\DTLstoreinitials: now uses \DTLinitialhyphen	215
now works with unbreakable space symbol	215
\DTLsubstituteall: fixed bug caused when certain commands occur in the string	221
\DTLvarianceforall: fixed bug	206
removed extraneous space	206
1.01 – 2007/08/22	
\DTLmultibibs: new	845
1.03 – 2009 January 27	
\DTLnewbibitem: removed check if database exists	780
\DTLnewbibrow: removed check if database exists	780
\DTLplotlines: fixed error in solid line setting	934
2.0 – 2009 February 27	
General: added etex as a required package	313
removed \@dtl@getidtype	433
removed \@dtl@ifrowcontains	433
removed \@dtl@setidtype	433
removed \@dtl@setkeys	433

removed \dtl@getentryid .	433	\dtldisplayafterhead: new .	517
removed		\DTLdisplaydb: new	524
\dtl@getentryvalue . . .	433	\dtldisplayendtab: new	517
\@DTLforeach: updated to use		\DTLdisplaylongdb: new	535
new database structure	500	\dtldisplaystartrow: new . .	517
\@DTLifdbempty: new	402	\dtldisplaystarttab: new . .	517
\@DTLremoveoverow: new	540	\DTLeverybarhook: new	864
\@dtl@after: new	415	\dtlforcolumnidx: new	491
\@dtl@assign: updated to use		\DTLforeachkeyinrow: updated	
new database structure	437	to use new database structure . .	509
\@dtl@before: new	415	\DTLgetcolumnindex: new . . .	405
\@dtl@colhead: new	415	\DTLgetdatatype: new	408
\@dtl@decrementrows: new . .	538	\dtlgetentryfromcurrentrow:	
\@dtl@getcolumnindex:		new	452
new	405, 406	\DTLgetrowforkey: update to	
\@dtl@getdatatype: new	409	use new database structure . . .	565
\@dtl@getprops: new	409	\DTLgetvalueforkey: updated	
\@dtl@list: new	585	to use new database structure . .	565
\@dtl@setnull: modified to use		\dtlheaderformat: new	515
new database structure	439	\DTLiffirstrow: modified to	
\@dtl@sortcriteria: updated		have different definition	
to take account of new database		depending on location	510
structure	591	\DTLifhaskey: new	404
\@dtl@updatekeys: new	419	\DTLiflastrow: modified to have	
\@dtlgetdatatype: new	408	different definition depending on	
\@dtlifreadonly: new	501	location	511
\@sDTLforeach: updated to use		\DTLifoddrrow: modified to have	
new database structure	501	different definition depending on	
\@sDTLnewrow: new	403	location	512
\@sdtlgetdatatype: new	409	\dtlintformat: new	516
\dtl@compare: no longer used . .	591	\DTLinttype: new	408
\dtl@compare@: updated to use		\DTLloaddb: added optional	
new database structure	591	argument	640
\dtl@decrementrows: new . . .	538	removed checks to see if the	
\dtl@gathervalues: updated to		database exists when adding to it	640
use new database structure . . .	442	\DTLmaxforcolumn: new	559
\dtl@sortdata: new	591	\DTLmaxforkeys: added second	
\dtladdalign: new	513	optional argument	557
\DTLaddentryforrow: updated		\DTLmeanforcolumn: new	546
to use new database structure . .	508	\DTLmeanforkeys: added second	
\dtl@aftercols: new	512	optional argument	544
\DTLappendtorow: updated to use		\DTLminforcolumn: new	556
new database structure	501	\DTLminforkeys: added second	
\dtl@beforecols: new	512	optional argument	554
\dtl@betweencols: new	512	\DTLnewdb: Changed way database	
\DTLcolumncount: new	402	is stored	398
\dtlcolumnindex: new	406	\dtlrealformat: new	516
\dtlcolumnnum: new	404	\DTLrealtype: new	408
\dtlcurrencyformat: new . . .	516		
\DTLcurrencytype: new	408		

\DTLremovecurrentrow: updated to use new database structure	507	2.10 – 2012-07-18	\@dtl@construct@qlpoff: Added code to replace escaped delimiters	644
\DTLremoveentryfromrow: updated to use new database structure	503		\@dtl@getkeyforcolumn: fixed bug	407
\DTLremoverow: new	539		\dtl@domappings: replaced \DTLsubstitute with \DTLsubstituteall	641
\DTLreplaceentryforrow: updated to use new database structure	505		\dtl@omitlines: new	598
\dtlrownum: new	404		\dtlappendentrytocurrentrow: new	453
\DTLsavedb: updated to use new database structure	623		\DTLassign: new	434
\DTLsavetexdb: updated to use new database structure	623		\DTLdisplaydb: added optional arg	524
\DTLsdforcolumn: new	552		\DTLdisplaylongdb: added omit option	535
\DTLsdforkeys: added second optional argument	551		\DTLifnumeq: changed \FPifeq to \dtlifnumeq	230
\dtlshowdb: updated to use new database structure	642		\DTLifnumgt: changed \FPifgt to \dtlifnumgt	230
\dtlshowdbkeys: updated to use new database structure	642		\DTLifnumlt: changed \FPiflt to \dtlifnumlt	230
\dtlshowtype: updated to use new database structure	643		\dtlrecombineomitcurrent: new	449
\DTLsort: updated to use new data structure	585		\dtlremoveentryincurrentrow: new	452
\dtlstringformat: new	516		\dtlreplaceentryincurrentrow: new	451
\DTLstringtype: new	408		\DTLsettabseparator: changed tab character to ^^I	314
\DTLsumcolumn: new	542		\DTLsubstituteall: added \long	221
\DTLsumforkeys: added second optional argument	540		\dtlswapentriesincurrentrow: new	452
\DTLunsettype: new	408		\long@addto@envbody: new ..	269
\DTLvarianceforcolumn: new	550		\long@collect@@body: new ..	270
\DTLvarianceforkeys: added second optional argument	548		\long@push@begins: new	270
2.03 – 2009 November 15		2.11 – 2012-09-25	General: remove unwanted space ..	423
\@dtl@assigncmd: modified to ignore spaces after commas ...	439		\@dtl@updatekeys: remove unwanted space	420
\@dtl@storeandupdate: value can be expanded before adding to database	431		\@dtl@getrowindex: new	462
\DTLappendtorow: value expanded before storing	502		\DTLaddcolumn: new	417
\DTLcleardb: new	399		\dtl@displayvalign: new	517
\dtlcolumnindex: renamed \dtl@columnindex to \dtlcolumnindex	406		\dtl@getrowforvalue: new ...	445
\DTLdeletedb: new	400		\DTLgetrowindex: new	461
\DTLreplaceentryforrow: expand replacement entry	507		\dtl@getrowindex: new	461
			\dtlupdateentryincurrentrow: new	455

2.12 – 2012-11-30	
General: fixed bug in	
\DTLiflastrow	496
\dtlifnumclosedbetween:	
fixed bug causing premature	
expansion	306
\dtlifnumeq: fixed bug causing	
premature expansion	305
\dtlifnumgt: fixed bug causing	
premature expansion	305
\dtlifnumlt: fixed bug causing	
premature expansion	305
\dtlifnumopenbetween: fixed	
bug causing premature expansion	306
2.13 – 2013-01-15	
General: added datagidx package . .	645
\@DTLnewrow: fixed typo in	
\PackageError	403
\@dtl@setheaderforindex:	
removed spurious space	428
\@dtlnumbernull: new	66
\@dtlstringnull: new	66
\DTLaddentryforrow: removed	
spurious space	508
\DTLforeachkeyinrow: changed	
to use \@dtlstringnull and	
\@dtlnumbernull	510
\DTLgclearadb: new	401
\DTLgdeletedb: new	400
\DTLgnewdb: new	400
\dtlparsewords: new	238
\DTLrawmap: removed spurious	
space	641
\DTLsaverawdb: new	623
\dtlsort: new	585
\ifDTLnewdbonload: new	594
2.14 – 2013-06-28	
General: added	
\postnewtermhook	739
added calc library requirement . .	929
\@dtl@updatekeys: expand	
value before testing if it's empty	420
\@dtl@width: replaced \FPSub	
etc with \dtlsub etc	1019
\datagidx@style@gloss:	
removed spurious see also line .	693
\datagidxdb: new	746
\dtl@constructminorticklist:	
replaced \FPSub with	
\dtlsub etc	1029
\dtl@constructticklist:	
replaced \FPSub with	
\dtlsub etc	1025
\dtl@constructticklistwithgap:	
replaced \FPadd with	
\dtladd	1026
\dtl@constructticklistwithgapex:	
replaced \FPadd with	
\dtladd and changed third	
argument to minimum gap width	
(in data co-ordinates)	1031
\dtl@getbounds: changed	
\FPifgt to \dtlifnumgt	1023
\DTLgidxForeachEntry: Added	
optional argument when using	
\DTLforeach	776
\DTLpar: changed to \let	319
\ifnewtermfield: new	741
\newtermfield: new	741
\postnewtermhook: new	740
2.15 – 2013-07-10	
General: added afterpage as a	
required package	659
\datagidx@write@usedentry:	
Added check for page counter .	757
\do@locrange: removed spurious	
space	706
\DTLaddtoplotlegend: Used	
\xdef instead of \edef as may	
be scoped.	1031
\dtlpllothandlermark: new . .	962
\DTLprotectedsaverawdb:	
new	623
\loadgidx: new	708
2.16 – 2013-08-16	
\@dtl@updatekeys: reverted to	
not expanding value (2.14 change	
causes an error with fragile	
commands). Fix now in	
\@dtl@checknumerical .	420
2.17 – 2013-08-29	
\DTLfetch: new	445
\edtletgetrowforvalue: new . .	445
2.18 – 2013-09-06	
\DTLpar: changed back to a robust	
command	319
2.19 – 2014-01-17	
\@datagidx@use@entry:	
renamed	
\datagidx@use@entry to	

\@datagidx@use@entry and removed redundant field argument	755	\ifmale: bug fix: replaced \@thisperson with #1	1056
\dtldisplaycr: new	518	\persongender: bug fix: replaced \ifpersonmale with \ifmale	1079
\glsaddall: Fixed bug in database reference	765	\PersonIfFemale: bug fix: replaced \@thisperson with #1	1057
2.20 – 2014-02-03		2.24 – 2016-01-12	
General: change \gdef to \xdef .	495	\@dtl@firsttonil: new	274
\@dtl@assign: Added check for empty argument	437	\dtl@getfirst@UTFviii: new	273
\DTLassignfirstmatch: new .	434	\dtl@if@two@octets: new	273
\DTLifnullorempty: new	441	\dtl@ifsingleorUTFviii: new	272
\DTLloaddbtex: new	640	\dtl:disableUTFviii: new	269
\DTLassignfirstmatch: new	435	\dtl:enableUTFviii: new	269
2.21 – 2014-03-08		\dtl:setcharcode: new	275
\@gDTLforeachbibentry: new	787	\dtl:setdefaultUTFviiiicharcode: new	276
\@sgDTLforeachbibentry: new	787	\dtl:setdefaultUTFviiiilccharcode: new	279
\datagidx@parse@location: replaced \ifstrequal with \ifdefequal	701	\dtl:setlccharcode: new	275
\dtl@g@gathervalues: new . .	443	\dtl:setUTFviiiicharcode: new	276
\dtl@gathervalues: fixed bug that ignore row tok argument . .	443	\dtl:setUTFviiiilccharcode: new	276
\DTLforeachbibentry: fixed bug in starred version	785	2.26 – 2016-07-20	
\gDTLforeachbibentry: new .	786	General: removed truncation (caused minor gap between first and last segments)	919
\gDTLformatbibentry: new . .	783	replaced \ifthen	920
2.22 – 2014-06-10		\@@dtl@set@off: replaced fp commands	927
\DTLcumbibitem: new	813	\@@dtl@set@offr: replaced fp commands	928
\DTLformatbooktitle: new . .	838	\@dtl@gatherintfrac: new . .	308
\DTLformatthisbibentry: new	784	\dtl@insertinto: fixed bug (incorrect inequality sign)	271
\DTLpcite: new	804	fixed bug (missing \dtl@sortresult)	271
\ifdtlautokeys: new	594	\dtl@ifnumclosedbetween: added \number	306
2.23 – 2015-07-11		\dtl@ifnumeq: added \number .	305
General: removed etex as a required package	313	\dtl@ifnumgt: added \number .	305
\@DTLsort: bug fix: replaced \dtlcompare with \dtlcompare	585	\dtl@ifnumlt: added \number .	305
\dtl@getfirst: changed \end to \end@dtl@getfirst . .	274	\dtl@ifnumopenbetween: added \number	306
\dtl@testinlist: new	253	\DTLpiechart: replaced fp commands	925
\DTLisinlist: new	253		
\DTLmaketabspace: restores tab catcode to 10	315		
\iffemale: bug fix: replaced \@thisperson with #1	1057		

\dtlround: fixed bug cause by	
rounding	308
fixed bug caused by rounding	
errors	308
\dtltrunc: fixed bug caused by	
rounding errors	309
new	308
2.27 – 2016-07-28	
\dtl@insertinto: undone the	
incorrect change in v2.26	271
\dtlinsertinto: new	46
\dtlsortlist: new	45
\edtlinertinto: new	47
2.28 – 2017-11-10	
General: renamed \toks@g... to	
\dtl@toks@g...	49
\@dtl@formatlist@handler:	
new	48
\@dtlformatlist: new	49
\datagidxconvertchars: new	733
\datagidxextendedtoascii:	
new	732
\DTLlandname: new	48
\DTLformatlist: new	49
\DTLlistformatitem: new	48
\DTLlistformatlastsep: new	48
\DTLlistformatoxford: new	48
\DTLlistformatsep: new	48
\ifdatagidxbalance: new	706
\printterms: added paragraph	
break at the start	774
\printterms@setupmulticol:	
new	771
\printterms@setuptwocol:	
new	772
\printtermsstartpar: new	771
\s@dtlformatlist: new	49
\xdtlgetrowindex: new	461
2.30 – 2018-04-16	
\@dtl@construct@lopoff:	
removed spurious spaces	643
2.31 – 2018-12-07	
\@dtl@listelement@outofrange:	
new	270
\DTLnumitemsinlist: made	
robust	30
\ifDTLlistskipempty: new	21
2.32 – 2019-09-27	
General: changed \ifx test to	
\ifblank	498
removed \relax	496
\datagidxstripaccents:	
added test for kernel version	733
\dtlgidx@checklocationchange:	
new	776
\ifdtlcompareskipcs: new	22
3.0 – 2025-03-03	
General: added datetime option	11
added encoding files	51
added lists option	21
added non-binary check	1046
added numeric option	8
added thinspace, apostrophe, and	
underscore number group	
commands	60
dropped	
xkeyval	313, 778, 849, 906, 929
moved lower-level null commands	
from datatool to datatool-base	65
new	273, 281–283, 291
removed afterpage as a required	
package	659
removed textcase as a required	
package	659
removed xfor as a required	
package	659
\@@dtl@set@off: replaced with	
_datapie_set_offset:n	927
\@@dtl@setoffr: replaced with	
_datapie_set_offset_range:nw	928
\@@get@firstperson:	
removed	1040
\@DTLaddcolumnwithheader:	
new	418
\@DTLforeachbibentry:	
removed	786
\@DTLgetrowindex: new	461
\@DTLifEndsWith: new	245
\@DTLifStartsWith: new	245
\@DTLifSubString: new	244
\@DTLreconstructdata: new	625
\@DTLremove row: obey global	
setting	540
\@datagidx@db@col@id@w:	
removed	655
\@dtl@assign: updated to L ^A T _E X3	437
\@dtl@assigncmd: removed	439

\@dtl@assigncmdnoop:		\@dtl@width: replaced with	
removed	439	\l_dataplot_width_fp	931
\@dtl@assigntmpseq: new ...	29	switched to l3fp	1019
\@dtl@bar: changed to		\@dtl@year: replaced with	
__databar_index_int .	875	\l_databib_year_tl ..	844
\@dtl@barcount: removed ...	855	\@dtlgetfirstchar: new	274
\@dtl@cite@write: new	845	\@dtlmaxforkeys: removed ...	559
\@dtl@currencies: removed ..	185	\@dtlmeanforkeys: removed ..	546
\@dtl@decimal: replaced	54	\@dtlminforkeys: removed ...	556
\@dtl@def@write: new	623	\@dtlnovalue: replaced with	
\@dtl@gap: replaced with		\c_nullvalue_tl	65
\l_dataplot_gap_fp ..	931	\@dtlnumbernull: moved from	
\@dtl@get@sortdirection:		datatool to datatool-base	66
removed	591	\@dtlstdforkeys: removed	552
\@dtl@getsortdirection:		\@dtlstringnull: moved from	
removed	591	datatool to datatool-base	66
\@dtl@ifsingle: removed	270	\@dtlsumforkeys: removed ...	542
\@dtl@list: removed	585	\@dtlvarianceforkeys:	
\@dtl@mathprocessor: changed		removed	550
default processor to l3fp or lua ...	2	\@female@label: replaced with	
\@dtl@neggap: replaced with		\c_person_female_label_tl	
\l_dataplot_neg_gap_fp		1039
.....	930	\@foreachperson: removed ..	1061
\@dtl@numbergroupchar:		\@gDTLforeachbibentry:	
replaced	54	removed	787
\@dtl@posgap: replaced with		\@get@firstperson: removed	1040
\l_dataplot_pos_gap_fp		\@male@label: replaced with	
.....	930	\c_person_male_label_tl	
\@dtl@rowa: removed	590	1039
\@dtl@rowb: removed	590	\@people@list: replaced with	
\@dtl@seg: replaced with		\l_person_people_seq	1039
\l_datapie_segment_int		\@person@datatoolsty: new	1036
.....	915	\@s@DTLnewdbentry: new	432
\@dtl@set@off: replaced with		\@sDTLforeachbibentry:	
__datapie_set_offset:nw		removed	786
.....	927	\@sDTLifEndsWith: new	245
\@dtl@sortcriteria: removed	591	\@sDTLifStartsWith: new ...	245
\@dtl@start: renamed		\@sDTLifSubString: new	244
\l_databar_start_fp .	851	\@sgDTLforeachbibentry:	
replaced with		removed	787
\l_datapie_start_tl .	915	macro: made robust	238
\@dtl@storeandupdate: new .	431	\@addfemalelabel: made robust	1041
\@dtl@thislabel: replaced with		\@addmalelabel: deprecated ..	1041
\l_databib_label_tl .	839	\@andname: removed	778, 1067
\@dtl@userresult: new	332	\@datagidx@add@term: replaced	
\@dtl@widestlabel: replaced		with	
with		__datagidx_add_term:n	735
\g_databib_widest_label_tl		\@datagidx@addchild: replaced	
.....	839	with \	743

\datagidx@anchorcount:	\datagidx@setfieldvalues:
replaced with	removed 734
\g__datagidx_anchor_count_int	\datagidx@setlocation:
..... 750	removed 647
\datagidx@aux@usedentry:	\datagidx@setnamecase:
new 760	removed 646
\datagidx@clearlocationformat:	\datagidx@setpostdesc:
removed 751	removed 646
\datagidx@columns: replaced	\datagidx@setprelocation:
with	removed 647
\l__datagidx_columns_int	\datagidx@setsee: removed ..
..... 645	647
\datagidx@count: removed ...	\datagidx@sort: replaced
765	\dtl sort with
\datagidx@defaultdatabase:	\DTL sort data 667
replaced with	replaced with
\l__datagidx_default_database_tl	\l__datagidx_sort_tl .
..... 706	667
\datagidx@doifsymlocwidth:	\datagidx@sort@foreachchild:
replaced with	removed 661
__datagidx_do_ifsymlocwidth:nnn	\datagidx@sortchildren:
..... 669	removed 661
\datagidx@escapelocation:	\datagidx@unsort@foreachchild:
removed 751	removed 662
\datagidx@escapelocationformat:	\datagidx@write@usedentry:
removed 751	Removed check for page counter
\datagidx@formatanchor:	757
replaced with	\datagidxdosealso: changed
__datagidx_format_anchor:n	to new document command ...
..... 750	663
\datagidx@formatlocation:	\datagidxmapdata: new
replaced with	676
__datagidx_formatlocation:nn	\datatoolasciient: new
..... 698	31
\datagidx@formatsymdesc:	\datatoolasciistart: new ..
removed 648	31
\datagidx@getgroup: removed	\datatoolctrlboundary: new
775	31
\datagidx@getlocdo: removed	\datatoolcurrencysymbolprefixfmt:
699	new 8
\datagidx@multicols:	\DataToolDateFmt: new
replaced with	12
\l__datagidx_multicols_tl	\DataToolDateTimeFmt: new .
..... 667	14
\datagidx@postheading:	\datatoolparen: new 237
replaced with	\datatoolSetCurrencySort:
\l__datagidx_post_heading_tl	new 193
..... 666	\DataToolTimeFmt: new
\datagidx@setchildsort:	12
removed 662	\DataToolTimeStampFmtSep:
\datagidx@setchildstyle:	new 14
removed 646	\DataToolTimeStampNoZoneFmt:
	new 15
	\DataToolTimeStampWithZoneFmt:
	new 15
	\DataToolTimeZoneFmt: new .
	13
	\do@prevlocation: removed ..
	704
	\dtl@angle: replaced with
	\l__datapie_angle_tl .
	915

<code>\dtl@bar label:</code> renamed	<code>\dtl@ifsingle:</code> now uses
<code>\l__databar_bar_label_tl</code>	LaTeX3 270
. 852	<code>\dtl@ifsingleorUTFviii:</code>
<code>\dtl@bounds:</code> replaced with	partially rewritten to use \LaTeX 3 272
<code>\l__dataplot_bounds_seq</code>	<code>\dtl@init@write@wrap:</code> new . 607
. 933	<code>\dtl@inner label:</code> renamed
<code>\dtl@compare:</code> removed 591	<code>\l__datatool_pie_inner_label_tl</code>
<code>\dtl@compare@:</code> removed 591 908
<code>\dtl@constructminorticklist:</code>	<code>\dtl@innernodeopt:</code> replaced
removed 1029	with
<code>\dtl@constructticklist:</code>	<code>\l__datapie_inner_node_opt_tl</code>
removed 1025 915
<code>\dtl@constructticklistwithgap:</code>	<code>\dtl@inneroffset:</code> replaced
removed 1026	with
<code>\dtl@constructticklistwithgapex:</code>	<code>\l__datapie_inner_offset_dim</code>
removed 1031 908
<code>\dtl@constructticklistwithgapz:</code>	<code>\dtl@legend:</code> replaced with
removed 1029	<code>\l__dataplot_legend_tl</code> 933
<code>\dtl@cutawayoffset:</code> replaced	<code>\dtl@legendlabels:</code> converted
with	to sequence
<code>\l__datapie_cutaway_offset_dim</code>	<code>\l__dataplot_legend_labels_seq</code>
. 908 939
<code>\dtl@cutlen:</code> replaced with	<code>\dtl@legendsetting:</code> replaced
<code>\l__datapie_cut_length_tl</code>	with
. 915	<code>\l__dataplot_legend_setting_int</code>
<code>\dtl@decx:</code> replaced with 939
<code>\l__dataplot_decimal_x_tl</code>	<code>\dtl@linestyle:</code> replaced with
. 930	<code>\l__dataplot_current_line_tl</code>
<code>\dtl@decy:</code> replaced with 932
<code>\l__dataplot_decimal_y_tl</code>	<code>\dtl@mark:</code> replaced with
. 930	<code>\l__dataplot_current_mark_tl</code>
<code>\dtl@dx:</code> replaced with 932
<code>\l__dataplot_x_extent_fp</code>	<code>\dtl@maxx:</code> replaced with
. 931	<code>\l__dataplot_max_x_tl</code> 938
<code>\dtl@dy:</code> replaced with	<code>\dtl@maxy:</code> replaced with
<code>\l__dataplot_y_extent_fp</code>	<code>\l__dataplot_max_y_tl</code> 938
. 931	<code>\dtl@midangle:</code> replaced with
<code>\dtl@endangle:</code> replaced with	<code>\l__datapie_mid_tl</code> . . . 915
<code>\l__datapie_end_tl</code> . . . 915	<code>\dtl@minx:</code> replaced with
<code>\dtl@extent:</code> renamed	<code>\l__dataplot_min_x_tl</code> 938
<code>\l__databar_extent_fp</code> 852	<code>\dtl@miny:</code> replaced with
replaced with	<code>\l__dataplot_min_y_tl</code> 938
<code>\l__datapie_extent_tl</code> 915	<code>\dtl@multibarlabels:</code> changed
<code>\dtl@get@yearsuffix:</code>	to
replaced with	<code>\l__databar_multibarlabels_seq</code>
<code>__databib_get_year_suffix:n</code> 852
. 844	<code>\dtl@offset@x:</code> replaced with
<code>\dtl@getbounds:</code> removed . . . 1023	<code>\l__dataplot_offset_x_fp</code>
<code>\dtl@getfirst:</code> deprecated . . . 274 931

\dtl@offset@y: replaced with \l__dataplot_offset_y_fp 931	\l__databar_upperbarlabel_tl 852
\dtl@outerlabel: renamed \l__datatool_pie_outer_label_tl 908	\dtl@uppermultibarlabels: changed to \l__databar_uppermultibarlabels_seq 853
\dtl@outernodeopt: replaced with \l__datapie_outer_node_opt_tl 915	\dtl@x: replaced with \l__dataplot_x_tl 930
\dtl@outeroffset: replaced with \l__datapie_outer_offset_dim 908	\dtl@xkey: replaced \dtl@xkey with \l__dataplot_x_key_tl 930
\dtl@piecutaways: replaced with \l__datapie_cutaways_clist 908	\dtl@xlabel: replaced with \l__dataplot_xlabel_tl 939
\dtl@reconstruct@data: new 622	\dtl@xminorticlist: replaced with \l__dataplot_x_minor_tic_seq 933
\dtl@scale@x: replaced with \l__dataplot_scale_x_fp 931	\dtl@xticgap: replaced with \l__dataplot_xtic_gap_tl 939
\dtl@scale@y: replaced with \l__dataplot_scale_y_fp 931	\dtl@xticlabelheight: replaced with \l__dataplot_x_tic_label_height_dim 931
\dtl@sortdata: removed 591	\dtl@xticlabels: converted to sequence \l__dataplot_xtic_labels_seq 939
\dtl@SortWordCommands: new 31	\dtl@xticlist: replaced with \l__dataplot_x_tic_seq 938
\dtl@SortWordCommands@hook: new 31	\dtl@y: replaced with \l__dataplot_y_tl 930
\dtl@stream: replaced with \l__dataplot_stream_tl 933	\dtl@ykey: replaced \dtl@ykey with \l__dataplot_y_key_tl 930
\dtl@thisplotlinecolor: replaced with \l__dataplot_current_line_color_tl 932	\dtl@ylabel: replaced with \l__dataplot_ylabel_tl 939
\dtl@thisplotmarkcolor: replaced with \l__dataplot_current_mark_color_tl 932	\dtl@yminorticlist: replaced with \l__dataplot_y_minor_tic_seq 933
\dtl@ticklength: replaced with \l__ 931	\dtl@yticgap: replaced with \l__dataplot_ytic_gap_tl 939
\dtl@ticlabeloffset: replaced with \l__dataplot_tic_label_offset_tl 932	\dtl@yticlabels: converted to sequence \l__dataplot_ytic_labels_seq 939
\dtl@unit: renamed \l__databar_unit_fp .. 852	\dtl@yticlabelwidth: replaced with
\dtl@upperbarlabel: changed to	

<code>\l_ytic_label_width_dim</code>		<code>\DTLbarXneglabelalign: new</code>	850
.....	931	<code>\DTLbarXnegupperlabelalign:</code>	
<code>\dtl@yticlist: replaced with</code>		new	850
<code>\l_dataplot_y_tic_seq</code>	938	<code>\DTLbarXupperlabelalign:</code>	
<code>\DTLabs: made robust</code>	202	new	849
<code>\DTLaction: new</code>	319	<code>\DTLbibaccessedname: new</code>	805
<code>\DTLadd: made robust</code>	200	<code>\DTLbibdatefield: new</code>	787
<code>\DTLaddall: made robust</code>	201	<code>\DTLbibdoi: new</code>	805
<code>\dtladdall: new</code>	300, 306	<code>\DTLbibdoihome: new</code>	804
<code>\DTLaddcolumn: made robust</code>	417	<code>\DTLbibdoitag: new</code>	804
<code>\DTLaddcolumnwithheader:</code>		<code>\DTLbibprints: new</code>	805
new	418	<code>\DTLbibfieldlet: made robust</code>	788
<code>\dtladdheaderalign: new</code>	515	<code>\DTLbibformatdigital: made</code>	
<code>\DTLaddperiod: bug fix: insert</code>		new	806
period before resetting		<code>\DTLbibgetlongestlabel:</code>	
conditional	790	new	781
<code>\DTLaddtopplotlegend:</code>		<code>\DTLbibliography: made robust</code>	782
switched to		switched to read-only loop	782
<code>\l_dataplot_legend_tl</code>		<code>\DTLbibliographystyle:</code>	
instead of <code>\dtl@legend</code>	1031	made robust	844
<code>\DTLaposinitialpunc: new</code>	219	<code>\DTLbibpubmed: new</code>	806
<code>\dtlappendentrytocurrentrow:</code>		<code>\DTLbibpubmedhome: new</code>	804
made robust	453	<code>\DTLbibpubmedtag: new</code>	804
use new value setting instead of		<code>\DTLbibsetlongestlabel:</code>	
always expanding	453	new	781
<code>\DTLappendtorow: made robust</code>	501	<code>\DTLbibsorntencap: new</code>	848
<code>\DTLassign: made robust</code>	434	<code>\DTLbibsorntname: new</code>	848
<code>\DTLassignfirstmatch: made</code>		<code>\DTLbibsorntnamesep: new</code>	848
robust	434	<code>\DTLbiburl: new</code>	805
<code>\DTLassignfromcurrentrow:</code>		<code>\DTLbiburldate: new</code>	805
new	436	<code>\DTLcheckendsperiod: made</code>	
<code>\DTLassignlettergroup: new</code>	40	robust	789
<code>\dtlbar@groupgap: changed to</code>		<code>\DTLclearbarcolors: new</code>	859
<code>\l_databar_groupgap_tl</code>		<code>\DTLcleardb: changed to new</code>	
.....	852	document command	399
<code>\dtlbar@variables: changed to</code>		<code>\DTLclearnegbarcolors: new</code>	859
<code>\l_databar_variables_seq</code>		<code>\DTLclip: made robust</code>	209
.....	851	<code>\dtlcolumnheader: new</code>	515
<code>\dtlbar@ylabel: renamed</code>		<code>\dtlcolumnindex: expand to 0 if</code>	
<code>\l_databar_ylabel_tl</code>	853	undefined	406
<code>\dtlbar@yticgap: renamed to</code>		<code>\DTLcomputebounds: changed to</code>	
<code>\l_databar_yticgap_tl</code>	853	new document command	561
<code>\DTLbargroupindex: new</code>	855	changed to use <code>\DTLmapdata</code>	561
<code>\DTLbargrouplabelalign:</code>		<code>\DTLcomputewidestbibentry:</code>	
new	855	made robust	784
<code>\DTLbarindex: new</code>	855	switched to read-only loop	784
<code>\DTLbarsetupperlabelalign:</code>		<code>\DTLconverttodecimal: made</code>	
new	864	robust	104
<code>\DTLBarStyle: new</code>	857	<code>\DTLcurr: new</code>	192
<code>\DTLbartotalvariables: new</code>	851	<code>\DTLcurrChar: new</code>	186

\DTLcurrCodeOrSymOrChar:	\DTLdatatypedatetimenamename:
new 8	new 64
\dtlcurrdefaultfmt: new ... 190	\DTLdatatypedecimalname:
\DTLcurrency: new 190	new 64
\DTLCurrencyCode: new 185	\DTLdatatypeintegernamename:
\dtlcurrencygroup: new 43	new 64
\DTLCurrencySymbol: new ... 185	\DTLdatatypeinvalidname:
\DTLcurrencytype: changed to	new 64
\newcommand 408	\DTLdatatypestringname:
\DTLCurrentLocaleFormatDate:	new 64
new 11	\DTLdatatypetimenamename: new . 64
\DTLCurrentLocaleFormatTime:	\DTLdatatypeunsetnamename: new 63
new 12	\dtldateformat: new 516
\DTLCurrentLocaleFormatTimeStampNoZone:	\dtldateformatgroup: new 43
new 17	\dtldateformat: new ... 516
\DTLCurrentLocaleFormatTimeStampWithZone:	\dtldateformatgroup: new 43
new 17	\DTLdatumcurrency: new 78
\DTLCurrentLocaleFormatTimeZone:	\DTLdatumtype: new 79
new 13	\DTLdatumvalue: new 78
\DTLCurrentLocaleGetGroupString:	\dtldbcolreconstruct: new . 620
new 41	\dtldbdatumreconstruct:
\DTLCurrentLocaleGetInitialLetter:	new 621
new 210	\dtldbheaderreconstruct:
\DTLCurrentLocaleIfpmTF:	new 621
new 150	\DTLdbLog: new 641
\DTLCurrentLocaleParseDate:	\DTLdbNewEntry: new 433
new 145	\DTLdbNewRow: new 433
\DTLCurrentLocaleParseTime:	\DTLdbProvideData: new 624
new 146	\dtldbconstructkeyindex:
\DTLCurrentLocaleParseTimeStamp:	new 622
new 144	\dtldbrowreconstruct: new . 620
\DTLCurrentLocaleTimeStampFmtSep:	\DTLdbSetHeader: new 434
new 14	\dtldbvaluereconstruct:
\DTLCurrentLocaleWordHandler:	new 621
new 30	\DTLdecimaltocurrency:
\DTLcurrEUR: new 193	added optional argument 106
\dtlcurrfmtsep: new 192	\DTLdefaultEURcurrencyfmt:
\dtlcurrfmtsymsep: new 191	new 192
\dtlcurrprefixfmt: new 190	\DTLDefaultLocaleWordHandler:
\DTLcurrStr: new 186	new 30
\dtlcurrsuffixfmt: new 191	\DTLdefcurrency: new 187
\DTLcurrSym: new 186	\DTLdeleteddb: changed to new
\DTLcurrXBT: new 192	document command 400
\DTLcurrXXX: new 192	\DTLdisplaybargrouplabel:
\DTLcustombibitem: made	new 857
robust 813	\DTLdisplaydb: changed to new
\DTLcustomlegend: new 936	document command 524
\DTLdatatypecurrencyname:	\DTLdisplaydbAddBegin: new 518
new 64	\DTLdisplaydbAddEnd: new .. 519
\DTLdatatypedatename: new . 64	\DTLdisplaydbAddItem: new . 532

<code>\dtldisplaydbenv: new</code>	518	<code>\DTLformatjr: made robust</code> . . .	796
<code>\DTLdisplaylongdb: made</code>		<code>\DTLformatnumberseries:</code>	
robust and reimplemented	535	made robust	799
<code>\DTLdisplaylongdbAddEnd:</code>		<code>\DTLformatpages: made robust</code>	799
new	535	<code>\DTLformatsurname: made</code>	
<code>\dtldisplaylongdbenv: new</code> .	532	robust	796
<code>\DTLdisplayTBrowidxmap:</code>		<code>\DTLformatsurnameonly:</code>	
new	518	made robust	794
<code>\DTLdiv: made robust</code>	202	<code>\DTLformatthisbibentry:</code>	
<code>DTLenvforeach: changed to</code>		made robust	784
xparse	495	<code>\DTLformatvolnumpages:</code>	
<code>DTLenvforeach*: changed to</code>		made robust	797
xparse	495	<code>\DTLformatvon: made robust</code> . .	795
<code>DTLenvmapdata: new</code>	470	<code>\DTLgabs: made robust</code>	202
<code>\DTLeverybargrouphook: new</code>	864	<code>\DTLgadd: made robust</code>	200
<code>\DTLeveryprebarhook: new</code> . .	864	<code>\DTLgaddall: made robust</code>	201
<code>\dtlfallbackaction: new</code> . . .	43	<code>\DTLgcleardb: changed to new</code>	
<code>\DTLfetch: made robust</code>	445	document command	401
<code>\DTLfetchlistelement:</code>		<code>\DTLgclip: made robust</code>	210
rewritten in \LaTeX 3	30	<code>\DTLgdeletedb: changed to new</code>	
<code>\DTLfmtcurr: new</code>	190	document command	400
<code>\DTLfmtcurrency: new</code>	190	<code>\DTLgdiv: made robust</code>	202
<code>\dtlforcolum: changed to</code>		<code>\DTLget: new</code>	330
document command	490	<code>\DTLgetcolumnindex: made</code>	
<code>\dtlforcolumnidx: changed to</code>		robust	405
document command	491	<code>\DTLgetdatatype: made robust</code>	408
<code>\DTLforeach: made robust</code>	495	<code>\DTLgetDataTypeName: new</code> . .	63
<code>\DTLforeachbibentry: made</code>		<code>\dtlgetentryfromcurrentrow:</code>	
robust	785	made robust	452
only assign <code>\DBIBCitekey</code> and		<code>\dtlgetentryfromrow: made</code>	
<code>\DBIBEntrytype</code> locally . .	785	robust	453
<code>\DTLformatarticlecrossref:</code>		<code>\DTLGetInitialLetter: new</code> .	210
made robust	803	<code>\DTLgetkeydata: made robust</code> .	441
<code>\DTLformatbibentry: made</code>		<code>\DTLgetkeyforcolumn: made</code>	
robust	783	robust	406
<code>\DTLformatbookcrossref:</code>		<code>\DTLgetlocation: made robust</code>	458
made robust	800	<code>\DTLgetnegbarcolor: new</code> . . .	861
<code>\DTLformatbvolume: made</code>		<code>\dtlgetrow: made robust</code>	444
robust	798	<code>\dtlgetrowforvalue: made</code>	
<code>\DTLformatchapterpages:</code>		robust	445
made robust	798	<code>\DTLgetrowindex: changed to</code>	
<code>\DTLformatcrossrefeditor:</code>		new document command and	
made robust	796	added starred variant	461
<code>\DTLformatdate: made robust</code> .	802	<code>\dtlgetrowindex: made robust</code>	461
<code>\DTLformatforenames: made</code>		<code>\DTLgetvalue: made robust</code> . . .	456
robust	795	<code>\dtlgidx@checklocationchange:</code>	
<code>\DTLformatincollproccrossref:</code>		removed	776
made robust	801	<code>\DTLgidxAddLocationType:</code>	
<code>\DTLformatinedbooktitle:</code>		deprecated	751
made robust	802	<code>dtlgidxchildlist:</code>	665

\DTLgidxDoSeeOrLocation:		\DTLlifeq: made robust	243
made robust	664	\DTLlifgt: made robust	241
\DTLgidxForeachEntry: made		\DTLlifhaskey: made robust	404
robust	776	\DTLlifinlist: rewritten in L ^A T _E X3	29
switched to \DTLmapdata	776	\DTLlifint: made robust	226
\DTLgidxFormatSeeAlso:		\dtlifintclosedbetween:	
changed to new document		switched to L ^A T _E X3	25
command	662	\dtlifintopenbetween:	
\DTLgidxPostLocation: new	647	switched to L ^A T _E X3	25
\DTLgidxSeeList: added group	663	\DTLliflt: made robust	240
changed to new document		\DTLlifnumclosedbetween:	
command	663	made robust	230
\DTLgidxSetColumns: mad		\dtlifnumclosedbetween:	
robust	645	made robust	299, 306
\DTLgmax: made robust	204	\DTLlifnumeq: made robust	230
\DTLgmaxall: made robust	205	\dtlifnumeq: made robust	298, 305
\DTLgmeanforall: made robust	205	\DTLlifnumerical: made robust	225
\DTLgmin: made robust	203	\DTLlifnumgt: made robust	230
\DTLgminall: made robust	204	\dtlifnumgt: made robust	298, 305
\DTLgneg: made robust	203	\DTLlifnumlt: made robust	230
\DTLground: made robust	209	\dtlifnumlt: made robust	298, 305
\DTLgsdforall: made robust	208	\DTLlifnumopenbetween: made	
\DTLgsqrt: made robust	203	robust	231
\DTLgsub: made robust	201	\dtlifnumopenbetween: made	
\DTLgtrunc: made robust	209	robust	299, 306
\DTLgvarianceforall: made		\DTLlifopenbetween: made	
robust	207	robust	249
\dtlheaderformat: removed		\DTLlifreal: made robust	226
\hfil	515	\DTLlifStartsWith: made robust	245
\DTLidxFormatSeeItem: added		\DTLlifstring: made robust	227
group	664	\DTLlifstringclosedbetween:	
changed to new document		made robust	246
command	664	\DTLlifstringeq: made robust	242
\DTLifaction: new	330	\DTLlifstringgt: made robust	241
\DTLifAllLowerCase: made		\DTLlifstringlt: made robust	239
robust	220	\DTLlifstringopenbetween:	
\DTLifAllUpperCase: made		made robust	248
robust	220	\DTLlifSubString: added starred	
\DTLifanybibfieldexists:		version	244
made robust	788	made robust	244
\DTLifcasedatatype: made		\DTLliftemporal: new	225
robust	228	\DTLlifetime: new	227
\DTLifclosedbetween: made		\DTLinbooktitlefmt: new	794
robust	247	\DTLinitialpunc: new	219
\DTLifcurrency: made robust	227	\DTLinitials: changed to new	
\DTLifcurrencyunit: made		document command	215
robust	228	\DTLinseries: new	794
\DTLifdate: new	227	\dtlininsertinto: made robust	46
\DTLifdatetime: new	226	\DTLinttype: changed to	
\DTLifEndsWith: new	245	\newcommand	408

\DTLisFPopenbetween: made synonym of	
\DTLisnumopenbetween	254
\DTLisiPrefix: new	253
\DTLisiSuffix: new	253
\DTLisnumeq: new	256
\DTLisnumgt: new	256
\DTLisnumgteq: new	257
\DTLisnumlt: new	256
\DTLisnumlteq: new	257
\DTLjournalfmt: new	794
\dtllettergroup: new	42
\DTLlistand: new	21
\DTLlistelement: rewritten in \LaTeX 3	30
\DTLloadbbbl: add check for begin document hook	779
allow empty name to indicate default	780
made robust	779
\DTLloadmdbl: made robust	847
\DTLmanualtitlefmt: new	794
\DTLmapdata: new	467
\DTLmapdatabreak: new	470
\DTLmapget: new	481
\DTLmapgetvalues: new	484
\DTLmaprow: new	480
\DTLmaprowbreak: new	481
\DTLmax: made robust	204
\DTLmaxall: made robust	204
\dtlmaxall: new	295, 302, 310
\DTLmaxforcolumn: changed to new document command	559
changed to use \DTLmapdata	559
\DTLmaxforkeys: changed to new document command	557
changed to use \DTLmapdata	557
\DTLmbibliography: made robust	847
\DTLmeanforall: made robust	205
\dtlmeanforall: new	302, 310
\DTLmeanforcolumn: changed to new document command	546
switched to using \DTLmapdata	546
\DTLmeanforkeys: changed to new document command	544
changed to use \DTLmapdata	544
\DTLmin: made robust	203
\DTLminall: made robust	204
\dtlminall: new	294, 301, 309
\DTLminforcolumn: changed to new document command	556
changed to use \DTLmapdata	556
\DTLminforkeys: changed to new document command	554
changed to use \DTLmapdata	554
\DTLmul: made robust	201
\DTLmultibibs: made robust	845
\DTLneg: made robust	202
\DTLnewbibitem: made robust	780
\DTLnewbibliteraitem: new	780
\DTLnewbibrow: made robust	780
\DTLnewcurrencysymbol: changed to document command	54
\DTLnewdb: changed to new document command	398
\DTLnewdbentry: switch to new document command	431
\DTLnewrow: made robust	403
\dtlnonlettergroup: new	43
\dtlnovalue: moved from datatool to datatool-base	66
\dtlnumbergroup: new	43
\DTLnumbernull: moved from datatool to datatool-base	66
\DTLnumcompare: new	231
\dtlnumericformat: new	516
\DTLnumitemsinlist: rewritten in \LaTeX 3	30
\DTLofseries: new	794
\DTLofseriesfmt: new	794
\dtlpadleadingzeros: new	27
\dtlpadleadingzerosminus: new	27
\dtlpadleadingzerosplus: new	27
\DTLparse: new	86
\DTLpieatsegment: new	909
\DTLpiechart: switched to using \DTLmapdata	925
\DTLplotdisplayticklabel: new	938
\DTLplotdisplayXticklabel: new	938
\DTLplotdisplayYticklabel: new	938
\DTLplotlegendname: new	1034
\DTLplotlegendnamesep: new	1034

<code>\DTLplotlegendsetname:</code>		<code>\dtlreplaceentryincurrentrow:</code>	
new	1034	made robust	451
<code>\DTLplotlegendsetxlabel:</code>		<code>\DTLresetLanguage:</code>	new 261
new	1035	<code>\DTLresetpredefined:</code>	new .. 816
<code>\DTLplotlegendsetylabel:</code>		<code>\DTLresetpredefinedabbrv:</code>	
new	1035	new	816
<code>\DTLplotlegendx:</code>	new 1034	<code>\DTLresetRegion:</code>	new 262
<code>\DTLplotlegendxy:</code>	new 1033	<code>\DTLrmentry:</code>	new 479
<code>\DTLplotlegendxysep:</code>	new . . 1033	<code>\DTLrmrow:</code>	new 480
<code>\DTLplotlegendy:</code>	new 1035	<code>\dtlroot:</code>	bug fix: added missing
<code>\DTLpostchaptername:</code>	new .. 793	third argument 307
<code>\DTLpostnumbername:</code>	new .. 794	<code>\DTLround:</code>	made robust 209
<code>\DTLpostpagename:</code>	new 793	<code>\DTLrowincr:</code>	new 493
<code>\DTLpostvolnum:</code>	new 793	<code>\DTLrowreset:</code>	new 493
<code>\DTLpostvolumename:</code>	new .. 793	<code>\DTLsavedb:</code>	rewritten to use
<code>\DTLpostvon:</code>	new 793	<code>\DTLwrite</code> 623
<code>\DTLprecite:</code>	new 794	<code>\DTLsaverawdb:</code>	rewritten to use
<code>\DTLPreProcessCurrencyGroup:</code>		<code>\DTLwrite</code> 623
new	42	<code>\DTLsavetexdb:</code>	rewritten to use
<code>\DTLPreProcessDateGroup:</code>		<code>\DTLwrite</code> 623
new	42	<code>\DTLscinum:</code>	new 8
<code>\DTLPreProcessDateTimeGroup:</code>		<code>\DTLsdforall:</code>	made robust . . . 207
new	42	<code>\dtlsdforall:</code>	new 303, 312
<code>\DTLPreProcessDecimalGroup:</code>		<code>\DTLsdforcolumn:</code>	changed to
new	42	new document command 552
<code>\DTLPreProcessIntegerGroup:</code>		changed to use <code>\DTLmapdata</code>	. . 552
new	42	<code>\DTLsdforkeys:</code>	changed to new
<code>\DTLPreProcessLetterGroup:</code>		document command 551
new	42	changed to use <code>\DTLmapdata</code>	. . 551
<code>\DTLPreProcessNonLetterGroup:</code>		<code>\DTLsetcurrencydatum:</code>	new . . 91
new	42	<code>\DTLsetdecimaldatum:</code>	new .. 90
<code>\DTLPreProcessTimeGroup:</code>		<code>\DTLsetdefaultcurrency:</code>	
new	42	changed to document command	186
<code>\DTLproceedingstitlefmt:</code>		<code>\DTLsetdelimiter:</code>	changed to
new	794	new document command and set	
<code>\DTLprotectedsaverawdb:</code>		up reg exp 315
rewritten to use <code>\DTLwrite</code>	. 623	<code>\DTLsetentry:</code>	new 476
<code>\DTLrealtype:</code>	changed to	<code>\DTLsetfpdatum:</code>	new 90
<code>\newcommand</code> 408	<code>\DTLsetheader:</code>	made robust .. 428
<code>\dtlrecombine:</code>	made robust .. 448	<code>\DTLsetintegerdatum:</code>	new .. 90
<code>\dtlrecombineomitcurrent:</code>		<code>\DTLsetLocaleOptions:</code>	new . . 265
made robust 449	<code>\DTLsetseparator:</code>	changed to
<code>\DTLreconstructdata:</code>	new .. 624	new document command and	
<code>\DTLreconstructdatabase:</code>		<code>detokenize</code> 314
new	625	<code>\DTLsetstringdatum:</code>	new ... 92
<code>\DTLreconstructdbdata:</code>	new 625	<code>\DTLsettemporaldatum:</code>	new . . 92
<code>\DTLremoveentryfromrow:</code>		<code>\DTLsetup:</code>	new 22
made robust 503	<code>\DTLshufflelist:</code>	new 47
<code>\dtlremoveentryincurrentrow:</code>		<code>\dtlsort:</code>	rewritten in \LaTeX 3 . . . 585
made robust 452	<code>\dtlsortdatavalue:</code>	new 582

<code>\DTLsortedactual</code> : new	39	<code>\DTLunsettype</code> : changed to	
<code>\DTLsortedletter</code> : new	39	<code>\newcommand</code>	408
<code>\DTLsortedvalue</code> : new	39	<code>\dtlupdateentryincurrentrow</code> :	
<code>\DTLsortlettercasehandler</code> :		check global setting	455
new	45	made robust	455
<code>\DTLsortletterhandler</code> : new	44	<code>\DTLuse</code> : new	331
<code>\DTLsortwordcasehandler</code> :		<code>\DTLusedatum</code> : new	78
new	44	<code>\DTLvarianceforall</code> : made	
<code>\dtlSortWordCommands</code> : new .	31	robust	206
<code>\DTLsortwordhandler</code> : new . .	44	<code>\dtlvarianceforall</code> : new	302, 311
<code>\DTLsortwordlist</code> : new	32	<code>\DTLvarianceforcolumn</code> :	
<code>\dtlspecialvalue</code> : new	591	changed to new document	
<code>\dtlsplitrow</code> : made robust . . .	449	command	550
<code>\DTLsplitstring</code> : made robust	220	switched to using <code>\DTLmapdata</code>	550
<code>\DTLsqrt</code> : made robust	203	<code>\DTLvarianceforkeys</code> : changed	
<code>\DTLStoreInitialGetLetter</code> :		to new document command . . .	548
new	219	changed to use <code>\DTLmapdata</code>	548
<code>\DTLstoreinitials</code> : changed to		<code>\DTLwrite</code> : new	605
new document command	215	<code>\DTLxparse</code> : new	87
<code>\DTLstringnull</code> : moved from		<code>\DTLxsetcurrencydatum</code> : new	91
<code>datatool</code> to <code>datatool-base</code>	66	<code>\DTLxsetdecimaldatum</code> : new .	91
<code>\DTLstringtype</code> : changed to		<code>\DTLxsetintegerdatum</code> : new .	90
<code>\newcommand</code>	408	<code>\DTLxsetstringdatum</code> : new . .	93
<code>\DTLsub</code> : made robust	201	<code>\DTLxsettemporaldatum</code> : new	92
<code>\DTLsubstitute</code> : made robust .	220	<code>\DTLxsplitstring</code> : new	221
rewritten in \LaTeX 3	220	<code>\DTLyAxisLabelStyle</code> : new . .	853
<code>\DTLsubstituteall</code> : made		<code>\edtlgetrowforvalue</code> : made	
robust	221	robust	445
rewritten in \LaTeX 3	221	<code>\femalelabels</code> : replaced with	
<code>\DTLsumcolumn</code> : changed to new		<code>\g_person_female_label_clist</code>	
document command	542	1041
changed to use <code>\DTLmapdata</code>	542	<code>\forallpeople</code> : new	1061
<code>\DTLsumforkeys</code> : changed to new		<code>\gDTLformatbibentry</code> : made	
document command	540	robust	783
changed to use <code>\DTLmapdata</code>	540	<code>\getpersonforenames</code> : new .	1080
<code>\dtlswapentriesincurrentrow</code> :		<code>\getpersonfullname</code> : made	
made robust	452	robust	1080
<code>\dtlswaprows</code> : made robust . . .	536	<code>\getpersongender</code> : made	
obey global setting	538	robust	1079
<code>\DTLtemporalvalue</code> : new	111	<code>\getpersongenderlabel</code> :	
<code>\dtltxorsort</code> : new	31	new	1079
<code>\DTLtherow</code> : new	494	<code>\getpersonname</code> : made robust	1080
<code>\DTLthesistitlefmt</code> : new . . .	794	<code>\getpersonsurname</code> : new . . .	1080
<code>\dtltimeformat</code> : new	517	<code>\getpersontitle</code> : made robust	1081
<code>\dtltimegroup</code> : new	43	<code>\if@datagidx@warn</code> : replaced	
<code>\DTLtotalbargroups</code> : new . . .	851	with	
<code>\DTLtotalbars</code> : new	851	<code>\l__datagidx_warn_bool</code>	652
<code>\DTLtrunc</code> : made robust	209	<code>\if@datagidxsymbolleft</code> :	
<code>\dtlunknowntag</code> : new	746	replaced with	

<code>\l_datagidx_symbol_left_bool</code>	<code>\newterm@plural: replaced with</code>
..... 648	<code>\l_datagidx_term_plural_tl</code>
<code>\if@dtl@sequential: replaced</code> 720
with	<code>\newterm@see: replaced with</code>
<code>\l_datagidx_sequential_bool</code>	<code>\l_datagidx_term_see_tl</code>
..... 699 721
<code>\ifallfemale: deprecated</code> ... 1058	<code>\newterm@seealso: replaced</code>
<code>\ifallmale: deprecated</code> 1057	with
<code>\iffemale: deprecated</code> 1057	<code>\l_datagidx_term_seealso_tl</code>
<code>\iffemalelabel: deprecated</code> . 1042 721
<code>\ifmale: deprecated</code> 1056	<code>\newterm@short: replaced with</code>
<code>\ifmalelabel: deprecated</code> ... 1042	<code>\l_datagidx_term_short_tl</code>
<code>\loadgidx: made robust</code> 708 720
<code>\malelabels: replaced with</code>	<code>\newterm@shortplural:</code>
<code>\g_person_male_label_clist</code>	replaced with
..... 1040	<code>\l_datagidx_term_shortplural_tl</code>
<code>\newperson: added starred form</code> 1043 720
made robust 1043	<code>\newterm@sort: replaced with</code>
<code>\newterm@database: replaced</code>	<code>\l_datagidx_term_sort_tl</code>
with 720
<code>\l_datagidx_term_database_tl</code>	<code>\newterm@symbol: replaced with</code>
..... 720	<code>\l_datagidx_term_symbol_tl</code>
<code>\newterm@defaultshook:</code> 720
replaced with	<code>\newterm@text: replaced with</code>
<code>\g_datagidx_term_defaults_tl</code>	<code>\l_datagidx_term_text_tl</code>
..... 724 720
<code>\newterm@description:</code>	<code>\newtermaddfield: check for</code>
replaced with	column existence 726
<code>\l_datagidx_term_description_tl</code>	<code>\newtermsorthook: new</code> 728
..... 720	<code>\Peoplechild: added warning if</code>
<code>\newterm@extrafields:</code>	no people defined 1078
replaced with	made robust 1078
<code>\g_datagidx_extra_fields_tl</code>	switched to LaTeX3 for case
..... 724	change 1078
<code>\newterm@label: replaced with</code>	<code>\peoplechild: added warning if</code>
<code>\l_datagidx_term_label_tl</code>	no people defined 1078
..... 720	made robust 1078
<code>\newterm@long: replaced with</code>	<code>\peopleforenames: new</code> 1069
<code>\l_datagidx_term_long_tl</code>	<code>\peoplefullname: added</code>
..... 720	warning if no people 1069
<code>\newterm@longplural:</code>	made robust 1069
replaced with	<code>\peoplename: made robust</code> ... 1070
<code>\l_datagidx_term_longplural_tl</code>	<code>\Peopleobjpronoun: added</code>
..... 720	warning if no people defined . 1074
<code>\newterm@name: replaced with</code>	made robust 1074
<code>\l_datagidx_term_name_tl</code>	<code>\peopleobjpronoun: added</code>
..... 720	warning if no people defined . 1074
<code>\newterm@parent: replaced with</code>	made robust 1074
<code>\l_datagidx_term_parent_tl</code>	<code>\Peopleobjpronounii: new</code> . 1076
..... 720	<code>\peopleobjpronounii: new</code> . 1076

<code>\Peopleparent</code> : added warning if		<code>\PersonAddNonBinaryLabel</code> :	
no people defined	1078	new	1042
made robust	1078	<code>\Personchild</code> : made robust . .	1078
switched to LaTeX3 for case		switched to LaTeX3 for case	
change	1078	change	1078
<code>\peopleparent</code> : added warning if		<code>\personchild</code> : made robust . .	1077
no people defined	1078	<code>\PersonFemaleCount</code> : new . .	1038
made robust	1078	<code>\personforenames</code> : new	1069
<code>\Peoplepossadj</code> : added warning		<code>\personfullname</code> : made robust	1069
if no people defined	1075	<code>\Persongender</code> : new	1079
made robust	1075	<code>\PersonIfAllFemale</code> : new . .	1058
switched to LaTeX3 for case		<code>\PersonIfAllMale</code> : new	1057
change	1075	<code>\PersonIfAllNonBinary</code> :	
<code>\peoplepossadj</code> : added warning		new	1058
if no people defined	1075	<code>\PersonIfAllUnknownGender</code> :	
made robust	1075	new	1059
<code>\Peoplepossadjii</code> : new	1077	<code>\PersonIfFemale</code> : made robust	1057
<code>\peoplepossadjii</code> : new	1077	<code>\PersonIfFemaleLabel</code> : made	
<code>\Peopleposspronoun</code> : added		robust	1042
warning if no people defined .	1075	<code>\PersonIfMale</code> : new	1056
made robust	1075	<code>\PersonIfMaleLabel</code> : new . .	1042
switched to LaTeX3 for case		<code>\PersonIfNonBinary</code> : new . .	1058
change	1075	<code>\PersonIfNonBinaryLabel</code> :	
<code>\peopleposspronoun</code> : added		new	1042
warning if no people defined .	1075	<code>\PersonIfUnknownGender</code> :	
made robust	1075	new	1059
<code>\Peopleposspronounii</code> : new	1077	<code>\personlastsep</code> : use	
<code>\peopleposspronounii</code> : new	1077	datatool-base separators	1068
<code>\Peoplepronoun</code> : added warning		<code>\PersonMaleCount</code> : new	1038
if no people defined	1074	<code>\personname</code> : made robust . . .	1069
made robust	1074	<code>\PersonNonBinaryCount</code> :	
switched to LaTeX3 for case		new	1038
change	1074	<code>\Personobjpronoun</code> : made	
<code>\peoplepronoun</code> : added warning		robust	1074
if no people defined	1074	switched to LaTeX3 for case	
made robust	1074	change	1074
<code>\Peoplepronounii</code> : new	1076	<code>\personobjpronoun</code> : made	
<code>\peoplepronounii</code> : new	1076	robust	1074
<code>\Peoplesibling</code> : new	1079	<code>\Personobjpronounii</code> : new .	1076
<code>\peoplesibling</code> : added warning		<code>\personobjpronounii</code> : new .	1076
if no people defined	1079	<code>\Personparent</code> : made robust .	1078
made robust	1079	switched to LaTeX3 for case	
<code>\peoplesurname</code> : new	1070	change	1078
<code>\peopletitlesurname</code> : new .	1071	<code>\personparent</code> : new	1078
<code>person</code> : removed	1039	<code>\Personpossadj</code> : made robust	1075
<code>\PersonAddFemaleLabel</code> :		switched to LaTeX3 for case	
made robust	1041	change	1075
<code>\PersonAddMaleLabel</code> : made		<code>\personpossadj</code> : made robust	1074
robust	1041	<code>\Personpossadjii</code> : new	1077
		<code>\personpossadjii</code> : new	1076

<code>\Personpossproun: made</code>		<code>\l_databar_yticlabels_seq</code>	
robust	1075	853
switched to LaTeX3 for case		<code>dtlbar@yticlist: replaced with</code>	
change	1075	<code>\l_databar_yticpoints_seq</code>	
<code>\personpossproun: made</code>		853
robust	1075	<code>\twopeoplesep: use datatool-base</code>	
<code>\Personpossprounii: new</code>	1077	separators	1068
<code>\personpossprounii: new</code>	1077	<code>\xDTLassignfirstmatch:</code>	
<code>\Personproun: made robust</code>	1074	made robust	435
switched to LaTeX3 for case		<code>\xDTLinitials: new</code>	215
change	1074	3.1 – 2025-03-03	
<code>\personproun: made robust</code>	1073	<code>\DTLsortlettercasehandler:</code>	
<code>\Personprounii: new</code>	1076	changed <code>\tl_set:Nx</code> to	
<code>\personprounii: new</code>	1075	<code>\tl_set:Ne</code>	45
<code>\PersonSetFemaleLabels:</code>		<code>\DTLsortletterhandler:</code>	
new	1041	changed <code>\tl_set:Nx</code> to	
<code>\PersonSetLocalisation:</code>		<code>\tl_set:Ne</code>	44
new	1062	moved case-change	44
<code>\PersonSetMaleLabels: new</code>	1040	<code>\DTLsortwordcasehandler:</code>	
<code>\PersonSetNonBinaryLabels:</code>		changed <code>\tl_set:Nx</code> to	
new	1041	<code>\tl_set:Ne</code>	44
<code>\Personsisbling: made robust</code>	1079	<code>\DTLsortwordhandler: changed</code>	
switched to LaTeX3 for case		<code>\tl_set:Nx</code> to <code>\tl_set:Ne</code>	44
change	1079	moved case-change	44
<code>\personsisbling: made robust</code>	1078	3.1 – 2025-03-10	
<code>\personsurname: new</code>	1070	<code>\DTLmeanforall: changed</code>	
<code>\persontitlesurname: new</code> .	1070	<code>\tl_set:Nx</code> to <code>\tl_set:Ne</code>	205
<code>\persontitlesuramesep:</code>		<code>\DTLmeanforcolumn: expand</code>	
new	1071	result	547
<code>\PersonTotalCount: new</code> ...	1038	<code>\DTLmeanforkeys: expand result</code>	544
<code>\PersonUnknownCount: new</code> .	1039	<code>\DTLsdfforall: changed</code>	
<code>\removeallpeople: made</code>		<code>\tl_set:Nx</code> to <code>\tl_set:Ne</code>	208
robust	1052	<code>\DTLsdforcolumn: expand result</code>	553
<code>\removepeople: made robust</code> .	1052	<code>\DTLsdforkeys: expand result</code> .	552
<code>\removeperson: made robust</code> .	1051	<code>\DTLsumcolumn: expand result</code> .	543
moved existence check	1051	<code>\DTLsumforkeys: expand result</code>	542
<code>\RequireDatatoolDialect:</code>		<code>\DTLvarianceforall: changed</code>	
new	263	<code>\tl_set:Nx</code> to <code>\tl_set:Ne</code>	207
<code>\s@dtlformatlist: rewritten to</code>		<code>\DTLvarianceforcolumn:</code>	
(partially) use LaTeX3	49	expand result	551
<code>\seealsoname: added check for</code>		<code>\DTLvarianceforkeys: expand</code>	
<code>\alsoname</code>	662	result	549
<code>dtl@createalphabiblabels:</code>		3.3 – 2025-03-15	
switched to read-only loop ...	840	General: bug fix: multiple separators	
<code>dtlbar@yticlabels: replaced</code>		in delimited cell	639
with			

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in *roman* refer to the pages where the entry is used.

Symbols	
<code>\"</code>	1224, 1285
<code>\#</code>	31, 53, 607, 733, 1175, 1288
<code>\\$</code>	31, 52, 185, 187, 733, 1175, 1288, 1300, 1304, 1319
<code>\%</code>	31, 607, 627, 733, 781, 1137, 1138, 1175, 1280–1283, 1288
<code>\&</code>	21, 32, 48, 261, 664, 733, 1141, 1175, 1288, 1297
<code>\'</code>	51, 283
<code>\(</code>	259–261, 1204, 1356, 1357
<code>\)</code>	259–261, 1204, 1356, 1357
<code>\+</code>	122, 123, 150
<code>\,</code>	60, 166
<code>\-</code>	44, 55, 57–60, 93, 122, 123, 150–156, 213
<code>\.</code>	55, 93, 152, 154, 156, 157, 789, 791, 1101
<code>\/</code>	150–155
<code>\:</code>	150, 157
<code>\@</code>	273
<code>\@@</code>	486, 487, 489, 490, 1236, 1237, 1244–1246, 1274
<code>\@dtl@set@off</code>	927, 1203, 1204
<code>\@dtl@set@offr</code>	1203, 1204
<code>\@dtl@setnull</code>	439, 439, 1236, 1237
<code>\@dtl@setoffr</code>	928
<code>\@dtl@strip@numgrpchar</code>	1301
<code>\@get@firstperson</code>	1040, 1363
<code>\@Alph</code>	1182, 1183, 1194
<code>\@DTLaddcolumn</code>	417, 1231
<code>\@DTLaddcolumnwithheader</code>	418, 418
<code>\@DTLforeach</code>	495, 500, 785, 786, 1099, 1248, 1249
<code>\@DTLforeachbibentry</code>	786, 1099
<code>\@DTLgetrowindex</code>	461, 461
<code>\@DTLifEndsWith</code>	245, 245, 253
<code>\@DTLifStartsWith</code>	245, 245, 252
<code>\@DTLifSubString</code>	244, 244, 252
<code>\@DTLifclosedbetween</code>	247, 247, 254, 1349
<code>\@DTLifdbempty</code>	391, 402, 402, 496, 528, 1227, 1249, 1252
<code>\@DTLifeq</code>	243, 243, 251, 1345
<code>\@DTLifgt</code>	242, 242, 251, 1344
<code>\@DTLifhaskey</code>	404, 404, 490, 504, 506, 629, 1228, 1246, 1255, 1256
<code>\@DTLiflt</code>	240, 240, 250, 1343
<code>\@DTLifopenbetween</code>	249, 249, 255, 1351
<code>\@DTLifstringclosedbetween</code>	246, 246, 247, 1349, 1350
<code>\@DTLifstringeq</code>	242, 243, 244, 1345
<code>\@DTLifstringgt</code>	241, 241, 242, 1344
<code>\@DTLifstringlt</code>	239, 239, 240, 1343
<code>\@DTLifstringopenbetween</code>	248, 249, 1350, 1351
<code>\@DTLnewdbentry</code>	431, 431, 1098, 1234
<code>\@DTLnewrow</code>	403, 403, 1098, 1228
<code>\@DTLreconstructdata</code>	625, 625
<code>\@DTLremove row</code>	539, 539, 1266
<code>\@DTLsetheader</code>	428, 428, 1233
<code>\@DTLsort</code>	585, 585, 1273
<code>\@Roman</code>	729, 1173, 1182, 1183
<code>\@TrackLangAddToHook</code>	264
<code>\@after</code>	1292
<code>\@afterheading</code>	674, 688, 692, 1149, 1158, 1160
<code>\@alph</code>	1182, 1183
<code>\@arabic</code>	1182, 1183
<code>\@auxout</code>	652, 757, 780, 813, 1097, 1111, 1136, 1186, 1195
<code>\@before</code>	1292
<code>\@begindocumenthook</code>	779
<code>\@bsphack</code>	847, 1130
<code>\@checkend</code>	270, 1292
<code>\@cite</code>	846, 1130
<code>\@cite@ofmt</code>	846, 1130
<code>\@citea</code>	846, 1130
<code>\@citeb</code>	846, 847, 1130
<code>\@cur@location</code>	1196
<code>\@currenvir</code>	269, 1292
<code>\@data@rerun@warn</code>	653, 1137, 1195, 1196
<code>\@data@rerun@warn@sort</code>	652, 653, 1137
<code>\@datagidx@db@col@id@w</code>	655, 1137
<code>\@datagidx@do@xusedentry</code>	1186

\@datagidx@dorerun@warn	652, 653, 1137, 1195, 1196	\@dtl@activatebraces	1289
\@datagidx@dorerun@warn@sort	652, 653, 653, 1137	\@dtl@af	1129, 1130
\@datagidx@dowriteaux	1183	\@dtl@after	415, 420, 421, 428, 429, 442, 499, 507, 1231, 1232, 1234, 1238, 1251, 1256, 1257
\@datagidx@escloc	751, 1182, 1183	\@dtl@after@cs	1240, 1241
\@datagidx@fieldkey@Description	1171	\@dtl@afterpart	1317, 1318, 1337, 1338
\@datagidx@fieldkey@Label	1172	\@dtl@arg	1290, 1291
\@datagidx@fieldkey@Long	1172	\@dtl@argA	1323, 1324, 1333, 1334, 1336, 1337, 1346, 1347
\@datagidx@fieldkey@Name	1171	\@dtl@argB	1323, 1324, 1333, 1334, 1336–1338, 1346, 1347
\@datagidx@fieldkey@Parent	1172	\@dtl@argi	1101, 1129, 1299, 1300
\@datagidx@fieldkey@Plural	1172	\@dtl@argii	1101, 1129, 1299, 1300
\@datagidx@fieldkey@See	1172	\@dtl@argiii	1129
\@datagidx@fieldkey@SeeAlso	1172	\@dtl@asg@value	1235
\@datagidx@fieldkey@Short	1172	\@dtl@assign	434, 436, 437, 498, 1235, 1236, 1250, 1253
\@datagidx@fieldkey@Sort	1172	\@dtl@assigncmd	439, 1236
\@datagidx@fieldkey@Symbol	1172	\@dtl@assigncmdnoop	439, 1236, 1237
\@datagidx@fieldkey@Text	1172	\@dtl@assigntmpseq	29, 29, 30, 49, 198, 199, 206, 207
\@datagidx@parse@location	702, 702, 1166	\@dtl@author	1101–1104, 1128
\@datagidx@rerun@warn	653	\@dtl@authorcount	1101–1104, 1128
\@datagidx@rerun@warn@sort	653	\@dtl@b	1275–1278
\@datagidx@target	660, 1183, 1184	\@dtl@bar	875, 1087–1089
\@datagidx@thisval	1141, 1142	\@dtl@barcount	855, 1082, 1093–1095
\@datagidx@use@entry	755, 1185, 1189	\@dtl@before	415, 420, 421, 428, 429, 442, 499, 507, 1231, 1232, 1234, 1238, 1251, 1256, 1257
\@datagidx@warnfalse	1138	\@dtl@before@cs	1240, 1241
\@datagidx@warntrue	1137, 1138	\@dtl@beforepart	1317, 1318, 1337, 1338
\@datagidx@link	1145	\@dtl@c	1280
\@datagidx@symbolleftfalse	1135, 1136	\@dtl@cap	1261, 1262
\@datagidx@symbollefttrue	1135, 1136	\@dtl@chars	644, 645, 1225
\@datagidx@target	1145	\@dtl@chknumnext	1320, 1321
\@do@dtl@envforeach	1248	\@dtl@checknumerical	225, 225, 420, 422, 1232, 1233, 1318, 1321, 1322, 1350–1352
\@do@dtl@envgforint	1357	\@dtl@checknumericalloop	1320
\@do@dtl@lnewentry	1287	\@dtl@checknumericalnoop	1320, 1321
\@do@foreachperson	1366	\@dtl@checknumericalstart	1319, 1320
\@do@sdtl@envforeach	1248, 1249	\@dtl@chop@trailingzeroes	1300
\@do@endpe	667, 775	\@dtl@chopexcessfrac	1302, 1303
\@dtl@A@after	1337, 1339	\@dtl@choptrailingzeroes	1299, 1300
\@dtl@A@before	1337–1339		
\@dtl@A@chargroup	1338		
\@dtl@A@comma	1337, 1339		
\@dtl@B@after	1338, 1339		
\@dtl@B@before	1338, 1339		
\@dtl@B@chargroup	1338		
\@dtl@B@comma	1338, 1339		
\@dtl@a	1275–1278		

<code>\@dtl@chopzeroesnext</code>	1300	
<code>\@dtl@cite@write</code>	845, 846, 847	
<code>\@dtl@col</code>		420–424, 428–431, 451, 454, 455,
	. 399–401, 443, 565, 1226, 1227,		477, 541–547, 549–551, 553, 555,
	1238, 1266–1268, 1270–1273,		556, 558, 560, 562, 563, 570,
	1275, 1276, 1278, 1282, 1283		589, 633–636, 638, 1232, 1233,
<code>\@dtl@colhead</code>	415, 420, 421,	1260, 1263, 1318–1322, 1350–1352
	428, 429, 442, 1231, 1232, 1234, 1238		<code>\@dtl@db@name</code>
<code>\@dtl@colnum</code>	429, 1234	1266–1268, 1270, 1271
<code>\@dtl@comparecs</code>	1274, 1277	<code>\@dtl@dbname</code>
<code>\@dtl@cond</code>	1266–1271
<code>\@dtl@conditionfalse</code>		438, 439,
	.. 225, 226, 250–259, 807–811,		495, 497, 511, 774, 1193, 1236,
	1108–1110, 1285–1287, 1315,		1237, 1249, 1250, 1252, 1274–1277
	1317, 1322, 1346–1348, 1352–1356		<code>\@dtl@decimal</code>
<code>\@dtl@conditiontrue</code>	225,
	250–259, 807–810, 1108–1110,		54,
	1285–1287, 1314–1317,		1298, 1299, 1301, 1303, 1320, 1321
	1322, 1346, 1347, 1352–1356		<code>\@dtl@decimal@to@localeint</code>
<code>\@dtl@construct@getintfrac</code>	.		1302
	1298, 1299	<code>\@dtl@decimaltolocale</code>
<code>\@dtl@construct@getnums</code> 1301, 1303
	1298, 1299, 1304	<code>\@dtl@decimaltolocalefrac</code>
<code>\@dtl@construct@lop@ff</code>
	644, 645, 1225	1301, 1302
<code>\@dtl@construct@lopoff</code>		<code>\@dtl@decimaltolocaleint</code>
	643, 645, 1224, 1225
<code>\@dtl@construct@lopoffs</code>		1301, 1302
	644, 1223–1225	<code>\@dtl@decrementrows</code>
<code>\@dtl@construct@qlopoff</code>
	644, 645, 1224, 1225	538, 538, 1264, 1265
<code>\@dtl@construct@stripnumgrpchar</code>	1298, 1301, 1304	<code>\@dtl@decvals</code>
<code>\@dtl@contcap</code>	1261, 1262
<code>\@dtl@countdigits</code>		1310, 1311
	... 269, 308, 309, 1302, 1361, 1362		<code>\@dtl@def@write</code>
<code>\@dtl@countnext</code>	269, 1302
<code>\@dtl@curi</code>	494, 1248	623
<code>\@dtl@curii</code>	494, 1248	<code>\@dtl@delimiter</code>
<code>\@dtl@curiii</code>	494, 1248
<code>\@dtl@currencies</code>	185, 1304	315, 315,
<code>\@dtl@currency</code>	9,	609, 627, 644, 1224, 1225, 1278, 1279
	102, 108, 185, 185, 186, 189, 190,		<code>\@dtl@dict@compare</code>
	228, 325, 328, 1299, 1303, 1304, 1319	
<code>\@dtl@currentrow</code>	..	271, 1294, 1295	1340
<code>\@dtl@datatype</code>	5, 35–37,	<code>\@dtl@diff</code>
	40, 61, 70, 75, 77, 86, 87, 93,	
	94, 96, 100, 102–104, 116, 119,		1310, 1311
	147, 194–200, 206, 207, 225–229,		<code>\@dtl@digitcount</code>
	231, 363, 365–368, 375–377, 386,	
			1302, 1303
			<code>\@dtl@digitcountnext</code>
		
			1303
			<code>\@dtl@dir</code>
		
			1277
			<code>\@dtl@do@compare</code>
		
			1340
			<code>\@dtl@do@getentry</code>
		
			1241
			<code>\@dtl@do@splitrow</code>
		
			1240, 1241
			<code>\@dtl@do@stripnumgrpchar</code>
			..
			1301
			<code>\@dtl@doamp</code>
		
			1259–1263
			<code>\@dtl@dobegintab</code>
		
			1260, 1261
			<code>\@dtl@docompare</code>
			...
			1108–1110, 1276
			<code>\@dtl@doforcol</code>
		
			1246, 1247
			<code>\@dtl@dogetdata</code>
		
			409, 1230
			<code>\@dtl@dogetentry</code>
		
			1236
			<code>\@dtl@dogetkeydata</code>
		
			1238
			<code>\@dtl@dogetkeyforcolumn</code>
			407, 1229
			<code>\@dtl@dogetprops</code>
		
			1231–1234
			<code>\@dtl@dogetrow</code>
		
			1239
			<code>\@dtl@dogetrowforvalue</code>
		
			1239
			<code>\@dtl@dogetval</code>
		
			565, 1272, 1273
			<code>\@dtl@doifinlist</code>
		
			1292
			<code>\@dtl@dolabel</code>
		
			1202, 1203
			<code>\@dtl@dollar</code>
		
			1319, 1320
			<code>\@dtl@donext</code>
		
			1101, 1129, 1346
			<code>\@dtl@donextdec</code>
		
			538, 539, 1265
			<code>\@dtl@donextinitials</code>
		
			1313

<code>\@dtl@doreadline</code> .	1285, 1287, 1288	<code>\@dtl@fracpart</code>	308, 309,
<code>\@dtl@doreadraw</code>	1289		1298, 1299, 1301–1303, 1361, 1362
<code>\@dtl@dosetheader</code>	1288	<code>\@dtl@gap</code>	931, 1221, 1222
<code>\@dtl@dosplit</code>	537, 1264	<code>\@dtl@gatherintfrac</code>	
<code>\@dtl@dosplitrow</code>			308, 308, 309, 1361, 1362
	504, 506, 507, 1255, 1256	<code>\@dtl@get@int@part</code>	1299, 1300
<code>\@dtl@dostartrow</code>	1261, 1263	<code>\@dtl@get@intpart</code>	1298, 1299
<code>\@dtl@dosubs</code>	644, 1224, 1304	<code>\@dtl@get@keydata</code> .	409, 1230, 1231
<code>\@dtl@dosubstitute</code>	1318	<code>\@dtl@get@keyforcolumn</code>	
<code>\@dtl@dosubstitutenoop</code>	1318		407, 1229, 1230
<code>\@dtl@dosubstnext</code>	1318	<code>\@dtl@get@next@intpart</code>	1300
<code>\@dtl@dotestifsubstring</code> . . .	1345	<code>\@dtl@get@nextintpart</code>	1300
<code>\@dtl@dovalue</code>		<code>\@dtl@get@sortdirection</code> <u>591</u> ,	1277
	299, 300, 1349–1351, 1358, 1359	<code>\@dtl@getcolumnindex</code> . . .	405,
<code>\@dtl@element</code>	1292–1294		405, 406, 504, 506, 1228, 1255, 1256
<code>\@dtl@elements</code>	543, 1267–1269	<code>\@dtl@getdatatype</code> . .	409, 409, 1230
<code>\@dtl@endgrabword</code>	1340	<code>\@dtl@getfracpart</code>	1299
<code>\@dtl@endloophook</code> . .	259, 260, 1356	<code>\@dtl@getintfrac</code>	1298, 1299
<code>\@dtl@endpt</code>	1093, 1094	<code>\@dtl@getkeyforcolumn</code>	
<code>\@dtl@entryI</code>	452, 1241		329, 389, 390, 407, 407, 1229
<code>\@dtl@entryII</code>	452, 1241	<code>\@dtl@getlocation</code>	1243
<code>\@dtl@falsepart</code> <u>305</u> , <u>306</u> , 1360, 1361		<code>\@dtl@getprops</code> <u>409</u> , 1231, 1233, 1238	
<code>\@dtl@firstpart</code>	537, 1264	<code>\@dtl@getrow</code>	1239
<code>\@dtl@firsttonil</code> . . .	273, <u>274</u> , 1326	<code>\@dtl@getrowindex</code>	1244
<code>\@dtl@firstttype</code>	1322	<code>\@dtl@getsortdirection</code>	
<code>\@dtl@foot</code>	1261, 1262		591, 1273, 1275, 1276
<code>\@dtl@forcolnext</code>	492, 1247	<code>\@dtl@getvalue</code>	1243
<code>\@dtl@forcolnoop</code> <u>492</u> , <u>493</u> , 1247, 1248		<code>\@dtl@gobbletonil</code>	269,
<code>\@dtl@forcolumn</code>	492, 1247		538, 1265, 1300, 1303, 1314–1317
<code>\@dtl@foreach@level</code>		<code>\@dtl@h</code> . .	1086, 1087, 1092, 1093, 1280
	260, <u>260</u> , 261, 486,	<code>\@dtl@head</code>	
	487, 489, 490, 1244–1246, 1356, 1357		399–401, 443, 1226, 1227, 1238,
<code>\@dtl@foreachkey</code> <u>489</u> , <u>489</u> , 1245, 1246			1260–1263, 1278, 1282–1284, 1288
<code>\@dtl@foreachnext</code>		<code>\@dtl@header</code>	1278, 1279
	487, 489, 490, 1245, 1246	<code>\@dtl@idx</code>	1260–1263
<code>\@dtl@foreachnoop</code>		<code>\@dtl@ifDigitOrDecimalSep</code> .	1320
	486, <u>487</u> , 489, 1244–1246	<code>\@dtl@ifsingle</code>	<u>270</u> , 1290, 1291
<code>\@dtl@foreachrow</code>		<code>\@dtl@initials</code>	1313
	486, <u>486</u> , 1244, 1245, 1274	<code>\@dtl@insertdonefalse</code>	
<code>\@dtl@formatlist@handler</code> . . .			46, 271, 1274, 1294, 1296
	48, 49, 1297, 1298	<code>\@dtl@insertdonetrue</code>	
<code>\@dtl@formatlist@item</code>	1298		46, 271, 1275, 1295, 1296
<code>\@dtl@formatlist@itemsep</code> . . .		<code>\@dtl@intpart</code>	
	48, 49, 1297, 1298		308, 309, 1299–1303, 1361, 1362
<code>\@dtl@formatlist@lastitem</code> . .		<code>\@dtl@k</code>	1280
	48, 49, 1297, 1298	<code>\@dtl@key</code>	
<code>\@dtl@formatlist@prelastitem</code> . .			399–401, 420, 428, 429, 442, 443,
	48, 49, 1297, 1298		1226, 1227, 1231, 1234, 1238,
<code>\@dtl@formatlist@prelastitemsep</code> . .			1240, 1260–1263, 1266–1268,
	48, 49, 1297, 1298		

1270, 1271, 1273, 1275, 1276,
 1278, 1279, 1282–1284, 1286
 \@dtl@key@Author
 793, 840, 1101, 1102, 1126
 \@dtl@key@CrossRef 841, 1127
 \@dtl@key@Editor
 ... 793, 796, 840, 1102–1104, 1126
 \@dtl@key@EprintType 807
 \@dtl@key@Key 840, 1126
 \@dtl@key@Organization 840, 1127
 \@dtl@key@Year 841, 1127
 \@dtl@keya 1275, 1276
 \@dtl@keyb 1275, 1276
 \@dtl@keys 488, 489, 1245
 \@dtl@label 1261, 1262
 \@dtl@lastfoot 1261, 1262
 \@dtl@level 1273, 1275
 \@dtl@lin@ 1286, 1287
 \@dtl@line 1285–1287
 \@dtl@list 585, 1273
 \@dtl@listelement@outofrange
 270, 1293
 \@dtl@localeintnext 1302
 \@dtl@loop@body 510, 1258
 \@dtl@loopbody
 486–488, 490, 1244–1246
 \@dtl@lop@ff ... 643, 644, 1224, 1225
 \@dtl@lopoff .. 643, 1224, 1286, 1287
 \@dtl@map 641, 1289
 \@dtl@mathprocessor
 2, 6, 23, 76, 1225, 1290, 1358, 1360
 \@dtl@max 1309
 \@dtl@maxcols 1260, 1261, 1287, 1288
 \@dtl@mean 303, 304, 311, 312, 1309–1311
 \@dtl@midpt 1094, 1095
 \@dtl@min 538, 1264, 1265, 1308
 \@dtl@minus 1319
 \@dtl@n 1267–1269, 1309–1311
 \@dtl@neggap 930, 1220, 1221
 \@dtl@newlist
 538, 1264, 1265, 1274, 1275
 \@dtl@newsortedlist
 271, 272, 1294–1297
 \@dtl@newstuff . 271, 272, 1295, 1296
 \@dtl@next 1200–1202, 1236, 1237, 1301
 \@dtl@nexti 494, 1248
 \@dtl@nextii 494, 1248
 \@dtl@nextiii 494, 1248
 \@dtl@notdone .. 508, 509, 1257, 1258
 \@dtl@num 1305, 1308–1311
 \@dtl@numbergroupchar
 .. 54, 1298, 1301, 1302, 1304, 1321
 \@dtl@numgrpsepcount
 1298, 1302, 1318, 1319, 1321
 \@dtl@numgrpsepfalse 1318
 \@dtl@numgrpseptrue 1321
 \@dtl@numi
 ... 230, 231, 1304–1308, 1311,
 1312, 1323, 1343, 1344, 1348, 1350
 \@dtl@numii . 230, 231, 1304–1308,
 1323, 1343, 1344, 1348, 1350
 \@dtl@numiii ... 230, 231, 1348, 1350
 \@dtl@oldbreak 492, 493, 1247
 \@dtl@oldtype 420, 421, 1232
 \@dtl@omitlist 1261–1263
 \@dtl@org@currency
 1299, 1304, 1319, 1322
 \@dtl@orgbreak 259, 260, 1356
 \@dtl@pages 1105
 \@dtl@parse@words 1342, 1343
 \@dtl@period 1101
 \@dtl@plus 1319
 \@dtl@posgap 930, 1221
 \@dtl@previ 494, 1248
 \@dtl@previi 494, 1248
 \@dtl@previii 494, 1248
 \@dtl@protect 1319
 \@dtl@qlopoff 643, 644, 1224
 \@dtl@rawmappings .. 641, 641, 1289
 \@dtl@rawread 1285, 1288
 \@dtl@read 1284–1287
 \@dtl@readline 1284, 1285
 \@dtl@readrawline 1285, 1288
 \@dtl@reconstruct@data 622
 \@dtl@replaced 221,
 1304–1312, 1317, 1318, 1337, 1338
 \@dtl@replacementkeys . 1273, 1276
 \@dtl@resetdoamp 1259–1263
 \@dtl@resetdoastrow . 1261–1263
 \@dtl@row 565, 1272, 1279
 \@dtl@rowAcontents 1274
 \@dtl@rowAidx .. 536, 537, 1263, 1264
 \@dtl@rowAnum 1274
 \@dtl@rowBcontents 1274
 \@dtl@rowBidx .. 536, 537, 1263, 1264
 \@dtl@rowBnum 1274
 \@dtl@rowa 590, 1274, 1275
 \@dtl@rowb 590, 1274, 1275
 \@dtl@s@thislabel 1127
 \@dtl@sd 1311

\@dtl@secondpart 537, 1264
\@dtl@seg . 915, 1197, 1199, 1200, 1204
\@dtl@separator 314, 314,
608, 609, 627, 639, 640, 644, 645,
1223, 1225, 1278, 1279, 1286, 1287
\@dtl@sequentialfalse . 1166, 1167
\@dtl@sequentialtrue 1166
\@dtl@set@off 927, 1199, 1203
\@dtl@set@options 1225
\@dtl@setheaderforindex
..... 428, 428, 626, 1233, 1288
\@dtl@setnewvalue
..... 317, 318, 430, 630, 1234, 1235
\@dtl@setnull
.. 439, 443, 1237, 1238, 1275, 1276
\@dtl@setwordbreaks 1341
\@dtl@setwordbreaks@next .. 1341
\@dtl@shift 1200
\@dtl@shortcap 1261, 1262
\@dtl@sortcriteria 591, 1274, 1275
\@dtl@sortdirection ... 1276, 1277
\@dtl@sortedlist
..... 271, 1274, 1275, 1294, 1295
\@dtl@sortorder 1273–1275
\@dtl@splitsubstr 1318
\@dtl@standardize@currency .
..... 1299, 1304, 1318
\@dtl@start 851, 915,
1087–1089, 1093–1096, 1199, 1203
\@dtl@storeandupdate ... 431, 432
\@dtl@string 1312, 1313
\@dtl@strip@numgrpchar 1299, 1301
\@dtl@stripeol ... 1284, 1285, 1289
\@dtl@stripped 1301
\@dtl@strippedline 1285, 1289
\@dtl@stuff 1240, 1241, 1298
\@dtl@subnohrsp 1312, 1313
\@dtl@subnohrspnext ... 1312, 1313
\@dtl@subs@argA 1346
\@dtl@subs@argB 1346
\@dtl@sum 1305
\@dtl@t 1280
\@dtl@tabargs 1260, 1261
\@dtl@testifsubstring 1346
\@dtl@teststartswith .. 1346–1348
\@dtl@thirdpart 537, 1264
\@dtl@thiscurrency 1304
\@dtl@thisdb ... 501–509, 1254–1258
\@dtl@thisdialect 849, 1081
\@dtl@thisentry 1287
\@dtl@thiskey 1287
\@dtl@thislabel ... 839, 1126, 1127
\@dtl@thisreplaced 1305, 1306
\@dtl@thisrow 538, 1264, 1265
\@dtl@thistick 1221–1223
\@dtl@tmp 269,
300–304, 317, 407, 443, 502,
505, 507, 537, 538, 641, 795,
1101, 1103, 1104, 1107–1110,
1115, 1117, 1118, 1121, 1127,
1128, 1230, 1234, 1238, 1242,
1250, 1251, 1254–1256, 1260,
1261, 1264, 1289, 1292, 1299,
1301, 1304–1308, 1311, 1312,
1318–1322, 1346, 1349–1352
\@dtl@tmpcmp
..... 1277, 1343–1345, 1349–1351
\@dtl@tmpcount
..... 23, 269, 308, 309, 494,
538, 808–810, 1086, 1091–1093,
1101–1104, 1108–1112, 1128,
1210, 1248, 1250, 1265,
1277, 1290, 1292–1294, 1299,
1300, 1302, 1303, 1318, 1321,
1343–1345, 1349–1351, 1361, 1362
\@dtl@tmpcpz 1300
\@dtl@tmpdtl 1301, 1303
\@dtl@tmpi 1305, 1307–1311
\@dtl@tmpii .. 1305–1309, 1311, 1312
\@dtl@toks . 23, 271, 272, 317, 318,
430, 432, 433, 502, 504, 505, 507,
537, 538, 630, 641, 1108–1110,
1127, 1128, 1217, 1223, 1234,
1235, 1238, 1242, 1254–1257,
1264, 1265, 1286–1290,
1294–1297, 1303, 1304, 1312–1318
\@dtl@toks@gconcat@middle@cx
..... 49, 1232,
1234, 1235, 1239, 1251, 1256, 1298
\@dtl@toks@gput@right@cx 49,
1228, 1233, 1240, 1242, 1254, 1298
\@dtl@toks@name 1298
\@dtl@toksA
.. 536, 537, 1264, 1276, 1277, 1363
\@dtl@toksB
.. 536, 537, 1264, 1276, 1277, 1363
\@dtl@truepart . 305, 306, 1360, 1361
\@dtl@truncatedecimal 1300
\@dtl@type ... 399–401, 420–422,
428, 429, 440, 443, 643, 1226,

1227, 1231–1234, 1237, 1238,
 1260–1263, 1278, 1282, 1283, 1289
 \@dtl@typeA 1277
 \@dtl@typeB 1277
 \@dtl@updatefkcs ... 489, 489, 1245
 \@dtl@updatekeys 419,
 502, 1231, 1234, 1240–1242, 1254
 \@dtl@userresult 332, 332
 \@dtl@val 565,
 1260, 1261, 1263, 1273, 1279, 1280
 \@dtl@var 1310
 \@dtl@vonpart 1128
 \@dtl@widestlabel . 839, 1126, 1127
 \@dtl@width 931, 1220–1222
 \@dtl@wordbreak
 237, 1323, 1327, 1333,
 1334, 1336, 1340, 1341, 1346, 1347
 \@dtl@write 623, 623, 1278–1283
 \@dtl@year 844, 1127, 1129
 \@dtldictcompare ... 237, 237, 1336
 \@dtl@envforeach@args 1248
 \@dtl@envgforint@arg 1357
 \@dtl@forcolumn 490, 490, 1246
 \@dtl@forcolumnidx .. 491, 491, 1246
 \@dtl@foreachrow 486, 1244, 1253, 1274
 \@dtl@formatlist .. 49, 49, 1297, 1298
 \@dtl@getdatatype ... 408, 408, 1230
 \@dtl@getfirstchar 274
 \@dtl@getkeydata 441, 441, 1237
 \@dtl@getkeyforcolumn 406, 406, 1229
 \@dtl@getrow
 447, 467, 529, 537, 1239, 1264
 \@dtl@getrowindex .. 462, 1243, 1244
 \@dtl@lifereadonly
 501, 502, 503, 505, 508, 1253–1257
 \@dtl@loaddb 1285, 1288
 \@dtl@maxforkeys 559, 1271
 \@dtl@meanforkeys .. 546, 1267, 1268
 \@dtl@minforkeys 556, 1270
 \@dtl@novalue 65, 1237, 1241, 1243, 1244
 \@dtl@numberrnull 66, 66, 510, 1237, 1258
 \@dtl@plotheadlermark
 962, 973, 1206, 1212, 1220
 \@dtl@sdforkeys 552, 1269, 1270
 \@dtl@splitrow 1240
 \@dtl@stringnull 66, 66, 510, 1237, 1258
 \@dtl@sumforkeys 542, 1266
 \@dtl@varianceforkeys
 550, 1268, 1270
 \@dtl@wordindexcompare . 1339, 1340
 \@eha 847, 1130
 \@empty .. 221, 270, 565, 846, 1099,
 1103, 1104, 1128, 1130, 1146,
 1147, 1151, 1152, 1155–1157,
 1163, 1192, 1211, 1212, 1216,
 1217, 1222, 1223, 1273, 1292,
 1294, 1299, 1301, 1305, 1306,
 1308–1310, 1317, 1364, 1366
 \@emptytoks 269, 1292
 \@endforfalse 271, 272,
 1100, 1142, 1276, 1294–1296, 1304
 \@endfortrue .. 1100, 1102, 1103,
 1105, 1128, 1142, 1164, 1196,
 1276, 1293, 1294, 1304, 1365, 1366
 \@endparse@formatlabel@ 755, 1184
 \@envbody 269, 1292
 \@esphack 847, 1131
 \@female@label ... 1039, 1366, 1367
 \@firstofone 812, 846,
 847, 1130, 1140, 1183, 1323, 1334
 \@firstoftwo 1141, 1200–1202
 \@for 271, 300–304,
 641, 846, 847, 1086, 1089,
 1091–1093, 1096, 1100–1104,
 1128–1130, 1140–1142, 1164,
 1172, 1181, 1182, 1196,
 1199, 1211–1216, 1266–1268,
 1270–1273, 1275, 1276, 1284,
 1289, 1292–1296, 1298, 1304,
 1305, 1308–1311, 1364–1366, 1368
 \@foreachperson 1061, 1366
 \@forremainder 1142, 1294
 \@gDTLforeachbibentry . 787, 1099
 \@gender 1365, 1366, 1369–1374
 \@get@firstperson
 1040, 1363, 1369–1374
 \@glsadd 1187
 \@gobble 31, 32, 269,
 270, 723, 733, 1101, 1137–1139,
 1144, 1145, 1173, 1175, 1176,
 1184, 1280–1283, 1292, 1300,
 1302, 1313, 1324, 1334, 1343
 \@gobbletwo 733, 1175, 1341
 \@idxitem . 667, 667, 673, 675, 676,
 697, 1144, 1145, 1148–1150, 1164
 \@ifl@t@r 1175
 \@ifnextchar ... 755, 846, 1130, 1184
 \@ifstar
 49, 244, 245, 406, 408, 417, 428,
 441, 495, 585, 1099, 1228–1231,

1233, 1234, 1237, 1246, 1249,
 1273, 1297, 1343–1345, 1349–1351
 \@ifundefined 846, 847,
 1098, 1100, 1127, 1129–1131,
 1228, 1235, 1286–1288,
 1304, 1363, 1365, 1367–1374
 \@input@ 780, 847, 1098, 1131
 \@latex@error 847, 1130
 \@latex@warning 1130
 \@m 846, 1130
 \@male@label 1039, 1365, 1366
 \@namedef 1364
 \@ne 302–304, 493, 494, 1303
 \@nil 220,
 221, 269, 273, 274, 407, 486, 493,
 498, 508, 538, 539, 1101, 1128,
 1129, 1210, 1220, 1230, 1236,
 1244, 1247, 1257, 1261, 1264,
 1265, 1274, 1290–1292, 1300,
 1302, 1312–1315, 1317–1321,
 1326, 1341, 1342, 1363, 1364
 \@nnil 486, 492, 538,
 1101, 1129, 1140, 1236, 1244,
 1247, 1250, 1262, 1265, 1276,
 1292, 1312–1316, 1320, 1341, 1343
 \@nx 269, 1292
 \@onelevel@sanitize 592,
 1127, 1196, 1278, 1280, 1282, 1283
 \@onlypreamble 707, 708, 734, 845,
 847, 1130, 1169, 1170, 1175, 1183
 \@org@dtl@paren@start 1339
 \@org@dtl@person@comma 1339
 \@org@dtl@place@comma 1339
 \@org@dtl@subject@comma ... 1339
 \@people@list 1039, 1363–1366, 1368
 \@percentchar 294
 \@person@datatoolsty .. 1036, 1037
 \@person@label 1364
 \@prev@location 1195, 1196
 \@prsn@post 1364
 \@prsn@pre 1364
 \@remove@person 1364
 \@removeperson 1364
 \@roman 1182, 1183
 \@s@DTLnewdentry ... 368, 432, 432
 \@sDTLaddcolumn 417, 1231
 \@sDTLforeach
 495, 501, 565, 785, 786, 811, 817,
 1085, 1087, 1091, 1093, 1099,
 1100, 1111, 1112, 1199, 1205,
 1217, 1249, 1252, 1260, 1263,
 1266–1268, 1270–1273, 1279, 1280
 \@sDTLforeachbibentry . 786, 1099
 \@sDTLifEndsWith 245, 245, 253
 \@sDTLifStartsWith .. 245, 245, 253
 \@sDTLifSubString ... 244, 244, 252
 \@sDTLifclosedbetween
 ... 247, 247, 255, 1349, 1350, 1353
 \@sDTLlifeq .. 243, 244, 252, 1345, 1352
 \@sDTLifgt .. 242, 242, 251, 1344, 1352
 \@sDTLifhaskey
 .. 369, 373, 404, 405, 405, 408,
 417, 418, 420, 423, 428, 438, 439,
 441, 596, 597, 626, 1228, 1230,
 1231, 1233, 1236–1238, 1267–1271
 \@sDTLiflt .. 240, 240, 251, 1343, 1352
 \@sDTLifopenbetween
 249, 250, 255, 1351, 1354
 \@sDTLifstringclosedbetween
 246, 246, 248, 1349, 1350
 \@sDTLifstringeq 242, 243, 244, 1345
 \@sDTLifstringgt 241, 241, 242, 1344
 \@sDTLifstringlt ... 239, 240, 1343
 \@sDTLifstringopenbetween ..
 248, 248, 250, 1350–1352
 \@sDTLnewdentry
 431, 432, 434, 780, 1234, 1287
 \@sDTLnewrow
 403, 403, 433, 780, 1228, 1287
 \@sDTLsetheader
 428, 428, 434, 627, 1233
 \@sDTLsort 585, 585, 1273
 \@sdtl@getcolumnindex 369, 405,
 406, 442, 565, 1228, 1229, 1238,
 1266–1268, 1270–1272, 1275, 1276
 \@sdtlforcolumn
 .. 490, 491, 1246, 1267–1270, 1272
 \@sdtlforcolumnidx
 491, 491, 492, 1246, 1247
 \@sdtlgetdatatype
 408, 409, 440, 1230, 1237
 \@sdtlgetkeydata 441, 442, 1237, 1238
 \@sdtlgetkeyforcolumn
 406, 407, 407, 1229, 1240
 \@secondoftwo 32, 733,
 1142, 1145, 1175, 1176, 1200–1202
 \@sgDTLforeachbibentry
 787, 1099, 1100
 \@tabacckludge 733, 1175
 \@tempwafalse 846, 1130, 1161

<code>\@tempswatrue</code>	846, 1130, 1161		
<code>\@text@composite@x</code>	733, 1175		
<code>\@thisperson</code>	1364–1366, 1368–1374		
<code>\@undefined</code>	779		
<code>\@xfor@nextelement</code>	1140		
<code>\@xp</code>	269, 270, 1292		
<code>\[</code>	213		
<code>\</code>	83–86, 316, 592, 607, 1031, 1223, 1260		
<code>_</code>	31, 212, 244, 607, 642, 791, 794, 816, 817, 846, 1071, 1101, 1104–1108, 1125, 1126, 1130, 1312, 1313, 1327, 1333, 1341, 1342		
<code>\]</code>	213		
<code>\^</code>	213, 314, 315, 1224		
<code>_</code>	3–5, 7, 25, 27–29, 31–40, 43, 45–47, 49–61, 66, 69–79, 81, 86–110, 112, 113, 119–133, 135, 138–148, 187–189, 194–200, 205–210, 213, 214, 216–219, 222–231, 233–237, 239–241, 243, 245, 246, 248, 249, 263, 264, 268, 272–275, 314, 315, 321, 325–351, 353–375, 377–399, 401, 404, 409–433, 436–440, 442, 444–474, 476–485, 487, 488, 491, 495–502, 507, 508, 510–512, 518, 519, 521, 524, 525, 527, 529, 530, 532, 535–538, 540–556, 558, 560–564, 567–584, 586–598, 601–622, 624, 626–635, 637–642, 646, 648–650, 652, 654, 655, 657, 658, 661, 667–671, 673, 674, 676, 697–702, 704–712, 716, 717, 719, 721–728, 731, 733–769, 773, 776–778, 780, 781, 785, 786, 788, 789, 791, 792, 796, 797, 811, 813, 840–845, 855, 856, 858, 860–864, 869, 871, 874–887, 892, 894–905, 909, 911, 914, 916, 917, 920–923, 925–928, 940–942, 959, 962, 963, 965–975, 978, 981, 984, 986, 987, 989, 991, 995, 997, 998, 1000, 1002–1008, 1014–1017, 1019–1024, 1026–1031, 1036–1045, 1051, 1052, 1056–1061, 1063–1067, 1069–1073, 1079, 1175, 1289		
<code>\ </code>	69, 213, 239		
<code>\~</code>	212, 213, 244, 245, 607		
		Numbers	
<code>\1</code>	97, 98, 100, 105, 107, 108, 214, 215, 592, 593, 630, 639		
<code>\2</code>	97, 98, 100, 105, 107, 108, 214, 239		
<code>\3</code>	97, 98, 100, 105, 107, 108, 214		
<code>\4</code>	97, 98, 100, 105, 107, 108, 214, 215		
<code>\5</code>	97, 98, 100, 105, 107, 108, 214		
<code>\6</code>	98, 105, 107		
		A	
<code>\A</code>	55, 57–60, 93, 122, 150–157, 166–169, 210, 238, 267, 314, 315		
<code>\AA</code>	732, 1174		
<code>\aa</code>	732, 1174		
<code>\Acr</code>	771, 1190		
<code>\acr</code>	770, 771, 1190		
<code>\acronymfont</code>	721, 722, 744, 745, 1176, 1180		
<code>\Acrpl</code>	771, 1190		
<code>\acrpl</code>	770, 771, 1190		
<code>\active</code>	1284, 1285, 1288, 1289		
<code>\add@accent@</code>	733, 1175		
<code>\addfemalelabel</code>	1041, 1363		
<code>\addmalelabel</code>	1041, 1363		
<code>\addtocounter</code>	1364		
<code>\AddToHook</code>	8		
<code>\addtolength</code>	1086, 1087, 1090, 1092, 1093, 1095, 1097, 1145–1147, 1150, 1151, 1153–1155, 1159, 1160, 1213, 1215		
<code>\AddTrackedRegion</code>	267		
<code>\advance</code>	259–261, 269, 302–304, 308, 309, 486, 487, 489, 490, 494, 1093, 1095, 1101–1104, 1111, 1112, 1128, 1143, 1150, 1162, 1164, 1183, 1185, 1188, 1194, 1204, 1228, 1232, 1244–1246, 1248, 1249, 1251–1253, 1265–1269, 1274, 1275, 1284–1287, 1293, 1302, 1303, 1321, 1356, 1357, 1361, 1362		
<code>\AE</code>	732, 1174		
<code>\ae</code>	732, 1174		
<code>\aftergroup</code>	613, 1280, 1282		
<code>\afterpage</code>	1186		
<code>\alph</code>	1127		
<code>\alpha</code>	731, 1173		
<code>\alsoname</code>	662		
<code>\and</code>	1217, 1266–1271		

<code>\andname</code>	. 48, 733, 778, 1067, 1098, 1101, 1104, 1174, 1175, 1297, 1367		
<code>\AnyTrackedLanguages</code>	268, 849, 1081		
<code>\appto</code> 30, 1187, 1191, 1341		
<code>\arabic</code> 493, 498, 660, 787, 1100, 1132, 1248, 1250, 1253		
<code>\AtBeginDocument</code>	... 752, 780, 1304		
<code>\AtEndDocument</code> 653, 1137		
B			
<code>\baselineskip</code> 853, 986, 997, 1086, 1087, 1090, 1092, 1093, 1097, 1214, 1215		
<code>\begin</code> 270, 518, 533, 665, 669–672, 678–681, 683, 685–688, 690, 693, 771, 782, 811, 817, 839, 847, 884, 889, 902, 917, 919, 937, 973, 974, 1007, 1031, 1032, 1087, 1093, 1094, 1098, 1111, 1112, 1126, 1131, 1146, 1147, 1151, 1152, 1154–1157, 1159, 1161, 1192, 1199, 1200, 1212, 1218–1220, 1260, 1261, 1292		
<code>\begin@stack</code> 269, 270, 1292		
<code>\beginngroup</code> 31, 269, 314, 1126, 1223, 1224, 1284, 1285, 1288, 1289, 1292, 1293		
<code>\beta</code> 731, 1173		
<code>\bfseries</code> 846, 1130		
<code>\bgroup</code>	613, 624, 708, 709, 1137, 1143, 1145, 1148–1150, 1153, 1155, 1158, 1159, 1161–1165, 1169, 1170, 1176, 1183, 1184, 1187, 1188, 1192, 1199, 1209, 1281, 1282		
<code>\bibcite</code> 813, 1111		
<code>\bibdata</code> 780, 847, 1097, 1131		
<code>\bibitem</code> 812, 813, 817, 839, 1111, 1112, 1126		
<code>\bibliographystyle</code> 779, 1097		
<code>\bibstyle</code> 847, 1131		
<code>\bool</code>	2–11, 17–22, 25–29, 32, 34, 35, 38, 44, 45, 64–68, 72, 95, 96, 103, 116, 124, 143–146, 191, 194, 195, 210, 235, 236, 317, 318, 320, 322, 324, 326, 327, 329, 337, 361, 364, 366, 390–393, 399, 400, 403, 415, 416, 419, 421, 422, 424, 425, 427, 429, 430, 438, 440, 449, 454, 455, 466, 467, 469–472, 497, 498, 517, 519, 527, 533, 534, 540, 542–544, 547, 549, 551–553, 555, 557, 559, 560, 566, 568–571, 576, 578, 579, 582, 587–589, 592–595, 598, 599, 601–604, 627, 631, 633–639, 648–650, 652, 653, 661, 664, 665, 669, 671, 678, 679, 685, 686, 693, 699, 702, 703, 711, 744, 772, 778, 779, 848, 875, 878, 880, 889, 892, 898, 899, 932, 933, 942–945, 963, 967, 976, 977, 982–984, 987, 988, 992–994, 997–999, 1002–1004, 1007, 1017–1019, 1038, 1045–1047, 1049–1052		
<code>\boolean</code> 495, 500, 501, 782, 786, 811, 817, 839, 847, 1084, 1090, 1098–1100, 1110, 1112, 1126, 1131, 1192, 1199, 1205, 1209, 1248, 1249, 1252, 1266–1272		
<code>\boolfalse</code> 269, 1290		
<code>\booltrue</code> 269, 1290		
<code>\box</code> 24		
C			
<code>\c</code> 5, 6, 13, 26–28, 35–38, 40, 41, 53, 55, 60, 61, 63–70, 72, 75, 79–83, 86–91, 93, 94, 96–100, 102, 103, 105–124, 130–135, 139, 143, 144, 146, 147, 149–157, 178, 184, 193–195, 197, 206, 207, 210–215, 222, 226–229, 231, 234–236, 244, 316, 320–324, 326–328, 333–335, 337, 338, 342–344, 348, 349, 355, 365, 367, 369, 374, 376–378, 380, 382, 384, 386, 391, 406, 411–414, 420–423, 425–429, 433, 436–438, 444, 445, 449, 451–457, 459, 460, 462–466, 468, 473, 474, 476, 479, 481, 483, 484, 488, 496, 497, 500–503, 505–508, 510–514, 517–520, 527, 528, 530, 531, 533–535, 541, 542, 544, 546, 549–551, 553, 554, 556, 558, 560, 561, 568, 569, 571, 576, 578, 580–583, 588–590, 593, 600, 608–619, 621, 624, 628, 629, 633–638, 642, 645, 651, 673, 674, 677, 678, 680, 682, 685, 687, 689, 690, 695, 699, 700, 709, 710, 724–726, 728, 729, 731, 733–736, 738, 740, 742, 748, 751,		

754, 755, 764, 773, 774, 776, 779,
780, 791–793, 796, 797, 800–804,
809, 810, 841, 842, 844, 853–856,
858, 860–863, 868, 872–874, 876,
877, 879, 881, 886–889, 891–893,
898, 899, 901, 905, 906, 909, 910,
915, 917–922, 924, 925, 927, 930,
931, 942, 943, 946, 956–958, 963,
968, 970, 971, 982, 984, 985,
989, 990, 993–996, 1000, 1001,
1008–1013, 1018, 1019, 1023,
1025–1028, 1030–1034, 1039,
1040, 1042–1049, 1054–1060, 1068
\c@DTLbarroundvar 857,
865, 866, 887, 1086, 1089, 1092, 1096
\c@DTLbibrow 1099, 1100
\c@DTLmaxauthors .. 793, 1101, 1102
\c@DTLmaxeditors .. 793, 1102, 1103
\c@DTLpieroundvar .. 913, 916, 1199
\c@DTLplotroundXvar
..... 946, 970, 1213, 1215
\c@DTLplotroundYvar 946, 972, 1212
\c@DTLrow 1249, 1252
\c@people
1049–1051, 1056–1059, 1368–1374
\c@person 1368, 1369
\capitalisewords 744, 1180
\caption 533, 534, 1262
\catcode 273, 314,
315, 1224, 1284, 1285, 1288, 1289
\cB 210
\centering 672, 1147
\chapter 666, 694, 1144, 1162
\chaptername 798, 1105
\char 31, 52, 66, 69, 187, 627, 781
\chi 732, 1174
\Children 661,
665, 666, 725, 1037, 1141–1144, 1171
\children 1037
\citation 846, 847, 1130
\cite 804, 1108
\clist 3,
7, 38, 39, 47, 62, 265–267, 285,
288–290, 307, 310–312, 319–322,
351, 352, 361, 370, 371, 374, 382,
389, 394, 541, 545, 554, 555, 558,
561, 566, 567, 569, 570, 586, 599,
659–661, 697–699, 711, 717–719,
725, 726, 728, 734, 743, 759, 761,
762, 772, 777, 788, 789, 791, 792,
796, 797, 842, 843, 845, 848, 853,
867, 878, 883, 899, 908, 926, 929,
938, 940, 943, 951, 952, 956–958,
968, 971, 1016, 1020–1022, 1036,
1040–1043, 1047, 1052, 1057–1061
\closein 1287
\closeout 1279, 1280, 1282, 1283
\cM 239
\cO 314–316, 630
\color 862, 910,
1082, 1087, 1094, 1197, 1216, 1217
\count@ 302–304,
1185, 1194, 1302, 1303, 1341, 1342
counters:
DTLbarroundvar 857
DTLbibrow 787
DTLgidxChildCount 660
DTLmaxauthors 791
DTLmaxeditors 793
DTLpieroundvar 908
DTLplotroundXvar 935
DTLplotroundYvar 935
people 1038
person 1039
\cS 630
\cs .. 2, 3, 7, 9–13, 15–17, 20, 24–29,
32–35, 38, 39, 43, 50–52, 55–61,
63, 66, 69, 70, 73–79, 86–89, 93,
95, 99–104, 106, 107, 110, 112,
114, 115, 119, 122–140, 147–149,
157, 159–161, 163, 164, 166–172,
174–188, 190–203, 210–214, 216,
223, 224, 229, 234–237, 264–268,
273–275, 314, 321, 325–327,
329–337, 339, 341–351, 353, 355,
356, 358–362, 364, 365, 368–372,
374, 381, 382, 386, 387, 389–394,
396–398, 400–402, 409–417, 419,
423, 425, 427, 429, 430, 437,
438, 440, 444–451, 453, 457–460,
462–465, 470–474, 476, 478–485,
487, 488, 491, 495–497, 500,
510–512, 518, 519, 521, 522, 524,
525, 529, 530, 532, 535, 541, 544,
547, 549, 551, 552, 554, 558, 561,
564, 567, 569–575, 577–582, 584,
585, 587–598, 601–609, 611–613,
615–620, 625–631, 633, 635,
638–640, 646, 648–650, 652, 654,
658, 666–673, 675, 694, 698–700,

704, 708–711, 719, 721–723,
 725–729, 731, 734, 735, 739,
 740, 743–746, 750–752, 755–758,
 765, 775, 776, 778, 781, 782, 785,
 786, 788–790, 797, 805, 806, 813,
 842–844, 855, 856, 858–862, 864,
 874–880, 882–884, 886, 894, 895,
 897–902, 905, 909, 910, 914, 916,
 917, 920–923, 925–928, 937, 940,
 942, 959–963, 965–967, 969–973,
 975, 978, 981, 986, 987, 991,
 997, 998, 1002, 1008, 1014–1017,
 1019–1027, 1029, 1030, 1032,
 1035–1037, 1039, 1040, 1043,
 1045, 1050–1063, 1068–1072
 \csdef 187, 190, 1179
 \csedef 187, 419, 1286
 \csgdef 622
 \csgundef 1050, 1052, 1053
 \cslet 1177, 1179
 \csname 2, 260,
 261, 269, 400, 407, 409, 486–491,
 494, 497, 501, 502, 504–506,
 509, 539, 613–615, 622, 642–644,
 733, 846, 1082, 1083, 1087,
 1093, 1098, 1100, 1108–1110,
 1126, 1127, 1129–1131, 1138,
 1172, 1175, 1176, 1182, 1183,
 1187, 1195, 1197–1200, 1203,
 1204, 1224–1235, 1238–1240,
 1243–1258, 1260, 1261,
 1264–1266, 1275, 1281–1284,
 1286–1289, 1292, 1298,
 1312, 1313, 1357, 1363–1374
 \csundef 1050–1052
 \csuse 186, 192,
 264, 494, 654, 746, 756, 763, 774,
 1051, 1137, 1140, 1147, 1164,
 1178, 1180, 1185, 1187, 1193, 1194
 \csxdef 419, 1170
 \CurrentLocation
 ... 652, 653, 725, 1171, 1195, 1196
 \CurrentOption
 . 318, 659, 779, 850, 907, 929, 1037
 \CurrentTrackedRegion .. 263, 264
 \CurrentTrackedTag 264

D
 \d 55, 57–60,
 122, 123, 150–156, 238, 699, 844
 \databib 782, 783,
 789, 790, 820, 823, 825, 830, 842, 843
 \datagidx
 .. 667, 674, 681, 688, 692, 695, 744
 \datagidx@add@term 735, 1177, 1179
 \datagidx@addchild 743, 1178, 1179
 \datagidx@anchorcount
 .. 750, 1182, 1183, 1185, 1186, 1188
 \datagidx@aux@usedentry 757, 760
 \datagidx@bothoftwo
 721, 731, 1173, 1176
 \datagidx@catsep 696, 1163
 \datagidx@child 659, 1180
 \datagidx@childsep
 693, 694, 1161, 1162
 \datagidx@clearlocationformat
 751, 1165, 1183
 \datagidx@columns
 645, 1131, 1192, 1193
 \datagidx@compositor
 650, 1136, 1165
 \datagidx@count 765, 1188
 \datagidx@current@format ...
 698, 700–702, 704, 1164–1167
 \datagidx@current@location .
 701, 702, 704, 1165–1167
 \datagidx@current@locationformat
 702–704, 1165–1167
 \datagidx@current@locationstring
 698, 700, 701, 704, 1164, 1165, 1167
 \datagidx@current@prefix ...
 701, 702, 704, 1165–1167
 \datagidx@current@target ...
 ... 698, 701, 704, 1164, 1165, 1167
 \datagidx@defaultdatabase ..
 706, 1168–1170, 1175, 1192
 \datagidx@dispenryval 1184
 \datagidx@displaychild
 665, 666, 1143, 1144
 \datagidx@do@highopt@optimize
 654, 658, 1137, 1138
 \datagidx@do@highopt@update
 655, 757, 1138, 1186
 \datagidx@do@optimize@sort .
 652, 1136, 1137
 \datagidx@do@sort
 651, 654, 658, 774, 1136–1138, 1193
 \datagidx@do@usedentry 1186
 \datagidx@docomplist .. 1136, 1165
 \datagidx@doforeachentry .. 1195

\datagidx@doifdisplayed	\datagidx@location@format ..
. 677, 682, 704–706, 1167, 1168
684, 689, 691, 776, 776, 1150,	\datagidx@location@sep
1154, 1155, 1158, 1160, 1195, 1196 699, 705, 1165, 1167, 1168
\datagidx@doiflocwidth	\datagidx@location@start ...
. 670, 1146, 1148 700, 1165, 1167, 1168
\datagidx@doifsymlocwidth ..	\datagidx@location@startval
. 669, 1145, 1148 704–706, 1167, 1168
\datagidx@doifsymwidth 671, 1147	\datagidx@location@target ..
\datagidx@dowrite 1195 704–706, 1167, 1168
\datagidx@endgetgroup . 1194, 1195	\datagidx@mac .. 723, 730, 1173, 1176
\datagidx@escape location ...	\datagidx@markparent
. 751, 1182, 1183, 1187 756, 1185, 1186
\datagidx@escape location format	\datagidx@multicols
. 751, 1165, 1182, 1183	.. 667, 1144, 1169, 1170, 1192, 1193
\datagidx@foreachchild	\datagidx@namenum
. 661, 665, 1132, 1143 723, 729, 1173, 1177
\datagidx@format	\datagidx@newgidx
. 754, 1184, 1185, 1187 707, 709, 1169, 1170
\datagidx@format anchor	\datagidx@newgidx@update ...
.. 750, 1182, 1183, 1185, 1186, 1188 707, 708, 710, 711, 1169, 1170
\datagidx@format location ...	\datagidx@newsortedlist 1141, 1142
. 698, 1164, 1167, 1168	\datagidx@newterm
\datagidx@formatsymdesc 734, 741, 1175, 1178
. 648, 1135, 1139, 1190	\datagidx@optimize@sort
\datagidx@getgroup 775, 1194, 1195 651, 658, 1136, 1138
\datagidx@get location	\datagidx@orgfield 1176
. 700, 1164, 1165	\datagidx@paren 723, 731, 1173, 1176
\datagidx@getlocdo 699, 1165	\datagidx@parent .. 660, 1185, 1186
\datagidx@heading	\datagidx@parent database ... 660
.. 666, 1144, 1168, 1170, 1192, 1193	\datagidx@parse@format@label@
\datagidx@highopt@newgidx 755, 1184
. 654, 707, 1137, 1169	\datagidx@parse@format label
\datagidx@highopt@newterm ..	754, 763, 766–769, 1184, 1187, 1189
. 654, 742, 1137, 1179	\datagidx@parse@format label@
\datagidx@id .. 660, 1185, 1186, 1188 755, 1184
\datagidx@indexfilename 707, 1169	\datagidx@parse@location ...
\datagidx@invert 699, 701, 1165
721, 731, 775, 1173, 1176, 1193, 1194	\datagidx@particle
\datagidx@item@body 723, 730, 1173, 1177
.. 673–675, 678–682, 685–689,	\datagidx@person 723, 731, 1173, 1176
1148, 1149, 1151–1153, 1155–1158	\datagidx@place 723, 731, 1173, 1176
\datagidx@label	\datagidx@postend
. 1181, 1182, 1185, 1187–1189	695, 772, 774, 775, 1162, 1192–1194
\datagidx@labellist 1193	\datagidx@postheading
\datagidx@level 665, 675, 676, 682,	.. 666, 1144, 1168, 1170, 1192, 1193
695–697, 776, 777, 1143, 1149,	\datagidx@prestart
1150, 1153, 1162–1164, 1195, 1196 771, 1162, 1192, 1193
\datagidx@list 660, 1165, 1181, 1182	\datagidx@prev@format
\datagidx@loc 660, 1187	. 699, 701, 702, 704–706, 1165–1168

<code>\datagidx@prev@location</code>	<code>\datagidx@subcatsep</code> 696, 697, 1163
. 704, 1164, 1166–1168	<code>\datagidx@subject</code>
<code>\datagidx@prev@locationformat</code> 723, 731, 1173, 1176
. 699, 702–704, 1165–1167	<code>\datagidx@target</code>
<code>\datagidx@prev@locationstring</code> 751, 1183, 1185, 1187, 1188
699, 701, 704–706, 1165, 1167, 1168	<code>\datagidx@thisidx</code> 1141, 1172
<code>\datagidx@prev@prefix</code>	<code>\datagidx@thislabel</code> . . . 1181, 1182
. 699, 702, 704, 1165–1167	<code>\datagidx@title</code> . . . 660, 1192, 1193
<code>\datagidx@prev@target</code>	<code>\datagidx@tmp</code> 1187
. . . 699, 704–706, 1165, 1167, 1168	<code>\datagidx@unsort@foreachchild</code>
<code>\datagidx@rank</code> . 723, 730, 1173, 1177 662, 1132, 1142
<code>\datagidx@rowcount</code> 1188	<code>\datagidx@usedentry</code> 758, 758, 1186
<code>\datagidx@saint</code> 723, 730, 1173, 1176	<code>\datagidx@value</code> 1140, 1172, 1181, 1189
<code>\datagidx@save@loc</code> 763, 1187, 1195	<code>\datagidx@write@usedentry</code> . .
<code>\datagidx@sep</code> 660, 1140 752, 757, 757, 1183, 1186
<code>\datagidx@setchildsort</code>	<code>\datagidx@xusedentry</code> . . 758, 1186
. 662, 1132, 1191	<code>\datagidxbalancefalse</code> . 718, 1169
<code>\datagidx@setchildstyle</code>	<code>\datagidxbalancetrue</code> 706, 718, 1169
. 646, 1132, 1139, 1191	<code>\datagidxchildend</code> . . 665, 669,
<code>\datagidx@setfieldvalues</code>	675, 683, 690, 693, 696, 1143,
. 734, 1175, 1178, 1179	1145, 1149, 1154, 1159, 1161, 1163
<code>\datagidx@setlocation</code>	<code>\datagidxchilditem</code> . . 666, 669,
. 647, 1133, 1139, 1190	675, 683, 690, 693, 696, 1144,
<code>\datagidx@setnamecase</code>	1145, 1149, 1154, 1159, 1161, 1163
. 646, 1132, 1139, 1191	<code>\datagidxchildstart</code> . 665, 668,
<code>\datagidx@setpostdesc</code>	675, 682, 689, 693, 696, 1143,
. 646, 1133, 1139, 1190	1145, 1149, 1153, 1158, 1161, 1163
<code>\datagidx@setprelocation</code>	<code>\datagidxconvertchars</code>
. 647, 1133, 1139, 1190 721, 722, 733, 1174, 1176
<code>\datagidx@setsee</code>	<code>\datagidxcurrentgroup</code>
. 647, 1134, 1139, 1191	. . 674, 675, 681, 688, 689, 692,
<code>\datagidx@showgroups</code> . . . 706,	694, 696, 725, 776, 1149, 1153,
711, 718, 719, 774, 1169, 1170, 1193	1158, 1160, 1162, 1163, 1194, 1195
<code>\datagidx@sort</code> 667, 1136,	<code>\datagidxdb</code> 746, 1180
1138, 1144, 1169, 1170, 1179, 1193	<code>\datagidxdescwidth</code> 677–681, 683,
<code>\datagidx@sort@foreachchild</code>	684, 684, 685–688, 690, 692, 693,
. 661, 1132, 1142	1150–1152, 1154–1157, 1159–1161
<code>\datagidx@sortchildren</code>	<code>\datagidxdictindent</code> 694, 695, 1162
. 661, 1141, 1142	<code>\datagidxdictparshape</code>
<code>\datagidx@sortedlist</code> . . 1141, 1142 695, 696, 1162, 1163
<code>\datagidx@style</code>	<code>\datagidxdoseealso</code> . 663, 663, 1140
706, 711, 718, 774, 1169, 1170, 1193	<code>\datagidxend</code> 667, 674,
<code>\datagidx@style@align</code> . 684, 1155	681, 688, 692, 695, 775, 1145,
<code>\datagidx@style@dict</code> . . 695, 1162	1148, 1153, 1157, 1160, 1162, 1194
<code>\datagidx@style@gloss</code> . 691, 1159	<code>\datagidxextendedtoascii</code>
<code>\datagidx@style@index</code> 732, 1174, 1176
. 673, 1148, 1150	<code>\datagidxgetchildfields</code>
<code>\datagidx@style@indexalign</code> 665, 666, 728, 1144, 1172
. 677, 1150	<code>\datagidxgroupheader</code>
<code>\datagidx@subcapsep</code> . . . 696, 1163	. . 668, 674, 675, 681, 688, 689,

692, 695, 696, 1145, 1148, 1149, 1153, 1157, 1158, 1160, 1162, 1163	1147, 1151, 1152, 1155–1157
\datagidxgroupsep 662, 669–673, 677–680, 685–687, 712, 1135, 1146–1148, 1150–1152, 1155–1157, 1191
.. 668, 674, 675, 681, 688, 689, 692, 695, 696, 1145, 1148, 1149, 1153, 1157, 1158, 1160, 1162, 1163	\datagidxtarget 667, 668, 675, 676, 681, 683, 689, 690, 693, 696, 752, 1145, 1149, 1153, 1154, 1158, 1159, 1161, 1163, 1184
\datagidxhighoptfilename ...	\datagidxtermkeys
... 654, 655, 707, 1137, 1138, 1169 725, 725, 734, 1171, 1172
\datagidxindent 675, 676, 682, 683, 697, 1149, 1150, 1153, 1154, 1164	\datagidxwordifygreek
\datagidxitem 668, 675, 681, 689, 692, 695, 775, 1145, 1149, 1153, 1158, 1160, 1162, 1194 722, 723, 731, 1173, 1176
\datagidxlastlabel	\dataplot . 937, 941, 942, 960–962, 974, 1005, 1008, 1019, 1022, 1025, 1027, 1032, 1033, 1035, 1036
..... 739, 743, 1178, 1179	\datatool
\datagidxlink 664, 668, 668, 698, 705, 706, 766–768, 1140, 1145, 1164, 1167, 1168, 1189 2, 4, 7, 11–13, 15–17, 19, 24–28, 32, 33, 35–37, 40, 43–45, 52, 54–61, 63–68, 70–74, 76–79, 86, 88–90, 94, 98, 104, 106, 109–114, 117, 118, 123–142, 148, 149, 157–188, 190–205, 210–212, 214, 216, 225, 234, 235, 262–268, 282, 283, 286, 287, 329, 336, 375, 377, 386, 389, 390, 392, 402, 405, 429, 430, 432, 435, 438, 441, 443–446, 454, 455, 457, 458, 461, 487, 502, 504, 506, 517, 531, 532, 541–543, 545, 547, 548, 555, 556, 558, 560, 562, 563, 568, 570–575, 583, 585, 586, 589, 608, 610, 612, 630, 631, 634, 636, 637, 647, 656, 657, 661, 664, 665, 667, 669–671, 677, 678, 682–685, 689–691, 698, 710, 714–716, 726–728, 739, 740, 742, 743, 748, 752–756, 758, 760, 761, 764–769, 776, 777, 784, 788, 842, 882, 887, 916, 940, 941, 956–958, 963, 965, 966, 969, 970, 973, 1006, 1044
\datagidxlocalign	\datatool@do@load@locales ..
670, 671, 672, 679, 680, 686, 688, 1146, 1147, 1151, 1152, 1156, 1157 268, 269
\datagidxlocationwidth . 662, 669–671, 673, 674, 678–680, 685–688, 712, 1135, 1146–1148, 1150–1152, 1155–1157, 1191	\datatool@load@locales
\datagidxmapdata 2, 7, 268, 849, 1081
..... 676, 677, 682, 684, 689, 691	\datatoolasciend 31, 31, 848
\datagidxnamewidth 677, 681–684, 684, 685, 689–692, 1150, 1153–1155, 1158–1160	\datatoolasciistart ... 31, 31, 739
\datagidxnewstyle	\datatoolctrlboundary
..... 672, 673, 677, 684, 691, 695 30, 31, 31, 739
\datagidxprevgroup .. 675, 681, 689, 692, 695, 696, 776, 1149, 1153, 1158, 1160, 1162, 1163, 1195	\datatoolcurrencysymbolprefixfmt
\datagidxseealsoend 663, 669, 676, 697, 1140, 1145, 1150, 1164 8, 10, 186
\datagidxseealsoend ... 663, 669, 676, 697, 1140, 1145, 1150, 1164	
\datagidxsetstyle	
..... 672, 676, 774, 1147, 1193	
\datagidxshowifdraft	
.. 658, 752, 1139, 1140, 1183, 1184	
\datagidxstart 667, 673, 677, 684, 691, 695, 774, 1144, 1148, 1150, 1155, 1159, 1162, 1193	
\datagidxstripaccents	
..... 733, 1175, 1176	
\datagidxsymalign ... 669–672, 672, 678–680, 685–687, 1146,	

\DataToolDateFmt 12, 14, 18–20, 112, 120, 133
\DataToolDateTimeFmt	. 14, 119, 132
\datatoolparen 31, 237
\datatoolparenstart 31, 237, 731, 1173, 1337–1340
\datatoolpersoncomma 31, 237, 731, 848, 1173, 1337, 1339, 1340
\datatoolplacecomma 31, 237, 731, 1173, 1337, 1339, 1340
\datatoolSetCurrencySort	32, 193
\datatoolsubjectcomma 31, 237, 731, 1173, 1337–1340
\DataToolTimeFmt 12, 14, 18–20, 113, 121, 133
\DataToolTimeStampFmtSep 14, 16, 19
\DataToolTimeStampNoZoneFmt 15, 15, 19, 20
\DataToolTimeStampWithZoneFmt 15, 15, 19, 20
\DataToolTimeZoneFmt	13, 14, 18–20
\db@col@elt@end@ 398, 453, 457–460, 462–466, 480, 481, 492, 493, 564, 617, 620, 1137, 1138, 1235, 1240–1244, 1247, 1254, 1257, 1280
\db@col@elt@w	398, 453, 457–460, 462–466, 480, 481, 492, 493, 564, 617, 620, 1137, 1138, 1235, 1240–1244, 1247, 1254, 1257, 1280
\db@col@id@end@ 396, 398, 407, 409–415, 450, 453, 457–460, 462–466, 476, 479–481, 487–489, 492, 493, 564, 617, 618, 620–622, 1137, 1138, 1229–1235, 1240–1245, 1247, 1254, 1257, 1281
\db@col@id@w 396, 398, 407, 409–415, 450, 453, 457–460, 462–466, 476, 479–481, 487–489, 492, 493, 564, 617, 618, 620–622, 1137, 1138, 1229–1235, 1240–1245, 1247, 1254, 1257, 1280
\db@header@id@end@ 396, 407, 409–415, 487–489, 618, 620, 622, 1230–1234, 1245, 1281
\db@header@id@w 396, 407, 409–415, 487–489, 618, 620, 622, 1230–1234, 1245, 1281
\db@key@id@end@ 396, 407, 409–415, 487–489, 618, 620, 622, 1229–1234, 1245, 1281
\db@key@id@w 396, 407, 409–415, 487–489, 618, 620, 622, 1229–1234, 1245, 1281
\db@plist@elt@end@ 397, 407, 409–415, 487–489, 618, 620, 622, 1230–1234, 1245, 1281
\db@plist@elt@w 396, 407, 409–414, 487–489, 618, 620, 621, 1229–1234, 1245, 1281
\db@row@elt@end@ 397, 447, 448, 467, 470, 486, 538, 617, 620, 1228, 1235, 1239, 1240, 1244, 1251, 1264, 1265, 1274, 1275, 1280
\db@row@elt@w 397, 447, 448, 467, 470, 486, 538, 617, 620, 1228, 1235, 1239, 1244, 1251, 1264, 1265, 1274, 1275, 1280
\db@row@id@end@ 397, 447, 448, 457–460, 462–467, 470, 486, 538, 617, 620, 1228, 1235, 1239, 1240, 1243, 1244, 1251, 1264, 1265, 1274, 1275, 1280
\db@row@id@w 397, 447, 448, 457–460, 462–467, 470, 486, 538, 617, 620, 1228, 1235, 1239, 1243, 1244, 1251, 1264, 1265, 1274, 1275, 1280
\db@type@id@end@ 396, 407, 409–415, 487–489, 618, 620, 622, 1229–1234, 1245, 1281
\db@type@id@w 396, 407, 409–415, 487–489, 618, 620, 622, 1229–1234, 1245, 1281
\DBIBCitekey 783, 784, 786, 812, 813, 817, 839–842, 1098–1100, 1111, 1112, 1126, 1127
\DBIBentrytype 783, 784, 786, 840, 1098–1100, 1127
\DBIBname 784–786, 1099, 1100
\DeclareCurrentRelease	1, 304, 313, 645, 777, 849, 906, 929, 1036
\DeclareDocumentCommand 22
\DeclareListParser 1136
\DeclareOption 318, 659, 779, 850, 907, 929, 1037, 1081, 1082, 1196, 1197
\DeclareOptionX 1139, 1140

`\DeclareRelease` 1, 304, 924, 928, 931, 955, 960, 969–971, 313, 645, 777, 849, 906, 929, 1036 973, 981, 986, 987, 991, 992, 997, 998
`\DeclareRobustCommand` `\dimen@` 1145–1147, 1149–1151, 1153–1155, 1184, 1187–1190, 1225 1158–1160, 1162, 1164, 1184
`\def` 31, 32, 49, 220, `\directlua` 2, 291–297
221, 259, 260, 269–271, 273, 274, `\disable@keys` 1085, 1090
299, 300, 302–305, 308, 309, 317, `\discretionary` . 752, 753, 1183, 1184
407, 409, 420, 486–489, 492–494, `\divide` 1086, 1092, 1210, 1302
508, 510, 537, 538, 607, 611, 615, `\dlt@parsewordshandler` 1343
620, 624, 641, 643, 644, 654, 660, `\do` 259–261, 271, 300–304, 399–401, 443, 486, 488, 497, 509, 608, 610–612, 615, 616, 641, 846, 847, 1086, 1089, 1091–1093, 1096, 1100–1104, 1128–1130, 1140–1142, 1164, 1165, 1172, 1181, 1182, 1196, 1199, 1211–1216, 1226, 1227, 1238, 1244, 1245, 1250, 1253, 1258, 1260–1263, 1266–1268, 1270–1276, 1278, 1280, 1282–1284, 1288, 1289, 1292–1296, 1298, 1304, 1305, 1308–1311, 1356, 1357, 1364–1366, 1368
705, 731–733, 735, 755, 787, 846, `\do@dtlreplaceincurrentrow` 1242, 1243
1082–1085, 1087, 1089, 1091, `\do@getrow`
1093, 1095, 1097, 1100, 1101, . 1141, 1143, 1181, 1184–1188, 1192
1103, 1104, 1128–1132, 1136, `\do@locrange` 705, 705, 1168
1137, 1140, 1141, 1148, 1151, `\do@prevlocation` .. 704, 1165, 1167
1152, 1155–1157, 1161, 1164, `\do@update` 1180
1165, 1167, 1168, 1171–1176, `\document` 847, 1130
1181–1185, 1187, 1192–1195, `\dotfill` 656, 714, 1133
1197–1199, 1203, 1204, 1207, `\draw` .. 894, 920, 923, 924, 975–977, 979, 980, 982–995, 997–1001, 1014, 1087–1089, 1094, 1096, 1200, 1203, 1212–1216, 1218–1220
1209, 1210, 1217, 1220, `\dtl@A@first` 1340
1221, 1223–1225, 1229–1232, `\dtl@A@remain` 1340
1234, 1236, 1237, 1239–1241, `\dtl@abbrvmonthname`
1243–1245, 1247, 1248, 812, 838, 1111, 1125
1257–1261, 1264, 1266–1271, `\dtl@addtolegend` 1217
1273, 1274, 1276–1283, `\dtl@angle` 915, 1200, 1203, 1204
1288–1296, 1298–1305, `\dtl@argi` 1314, 1316
1308–1322, 1326, 1337–1342, `\dtl@argii` 1314, 1316
1346, 1347, 1349–1352, 1356–1366 `\dtl@asg@rowidx` 435, 436, 1236
`\define@boolkey` `\dtl@assignfirstmatch`
1081, 1197, 1208, 1225, 1284, 1290 435, 435, 1235, 1236
`\define@choicekey` 1083, `\dtl@authorcount` 791
1097, 1138–1140, 1169, 1190,
1191, 1207–1209, 1225, 1290, 1357
`\define@key` ... 1083, 1084, 1139,
1168–1172, 1190–1192, 1198,
1199, 1207, 1209, 1225, 1261, 1284
`\Delta` 732, 1174
`\delta` 731, 1173
`\Description` . 648–650, 666, 693,
725, 1135, 1136, 1144, 1161, 1171
`\detokenize` 43, 262, 781
`\DH` 732, 1174
`\dh` 732, 1174
`\dim` 24, 62, 667,
669–671, 673–678, 680, 682–685,
687, 689–692, 695, 697, 784, 840,
842, 851–854, 857, 869–871, 883,
884, 888, 889, 892, 893, 895–897,
903, 905, 906, 908, 912, 913, 919,

\dtl@B@first 1340
\dtl@B@remain 1340
\dtl@barlabel . 852, 1084, 1088, 1096
\dtl@barvar 1085, 1091
\dtl@bounds 933, 1209, 1210
\dtl@checkendsperiod 1101
\dtl@chopfirst 1090, 1093,
1094, 1096, 1213, 1215–1217, 1294
\dtl@choplast 1294
\dtl@citex 846, 846, 1130
\dtl@code 1315, 1317
\dtl@codeA 270,
1323–1326, 1334, 1335, 1347, 1348
\dtl@codeB 270,
1323–1326, 1334, 1335, 1347, 1348
\dtl@compare 591, 1277
\dtl@compare@ 591, 1276, 1277
\dtl@computeangles 1199, 1203
\dtl@construct@subnobrsp ...
..... 1312, 1313
\dtl@constructminorticklist
..... 1029, 1211, 1212, 1222
\dtl@constructticklist
..... 1025, 1086, 1092, 1211, 1220
\dtl@constructticklistwithgap
..... 1026, 1211, 1221
\dtl@constructticklistwithgapex
..... 1031, 1222
\dtl@constructticklistwithgapz
..... 1029, 1086, 1092, 1211, 1221
\dtl@createalphabiblabels ..
..... 839, 839, 840, 1126
\dtl@cutawayoffset
..... 908, 1197, 1198, 1204
\dtl@cutlen 915, 1200
\dtl@db@col@reconstruct 624
\dtl@db@datum@reconstruct ..
..... 624, 625
\dtl@db@header@reconstruct . 624
\dtl@db@reconstruct@keyindex
..... 625
\dtl@db@row@reconstruct 624
\dtl@db@value@reconstruct ..
..... 624, 625
\dtl@decrementrows 449,
498, 538, 540, 1240, 1250, 1264, 1266
\dtl@decx . 930, 1205, 1217–1220, 1272
\dtl@decy . 930, 1205, 1217–1220, 1272
\dtl@diff 1268, 1269
\dtl@do@setkeys 1193
\dtl@do@setwordbreaks 1341
\dtl@dogetentry 509, 1234,
1235, 1241, 1242, 1254–1256, 1258
\dtl@dogetrow
. 540, 1179–1181, 1234, 1250, 1266
\dtl@dogetrowindex 1243, 1244
\dtl@dogetvalue 1243
\dtl@domappings 630, 641, 1285, 1289
\dtl@donext 1324, 1325,
1334–1336, 1339, 1342, 1346–1348
\dtl@donextcompare 1323, 1324, 1334
\dtl@dotestiflowernext 1316
\dtl@dotestifuppernext 1314, 1315
\dtl@dx ... 931, 1210, 1214, 1218, 1219
\dtl@dy ... 931, 1210, 1215, 1218, 1219
\dtl@end@if@two@octets
. 273, 1291, 1326, 1327, 1333, 1341
\dtl@end@if@casechargroup ...
..... 1338, 1341
\dtl@endangle 915, 1200
\dtl@endhyp 1313, 1314
\dtl@entry
.. 432, 454, 455, 502, 504, 506,
1234, 1235, 1241, 1242, 1254–1256
\dtl@entrycr 1284, 1286–1288
\dtl@extent 852, 915, 1086, 1091, 1200
\dtl@first 273, 274,
1323, 1326, 1334, 1341, 1346, 1347
\dtl@firstA
1323–1325, 1334–1336, 1347, 1348
\dtl@firstB
1323–1325, 1334–1336, 1347, 1348
\dtl@forcolum . 491, 492, 1246, 1247
\dtl@g@gathervalues
..... 443, 787, 1100, 1238
\dtl@gathervalues
..... 442, 784, 786, 1099, 1238
\dtl@get@firstthree 844, 1126–1128
\dtl@get@yearsuffix 844, 1127, 1129
\dtl@getauthorinitial . 843, 1128
\dtl@getbounds ... 1023, 1210, 1220
\dtl@getentryfromrow ... 375,
376, 386, 453, 483, 880, 902, 1241
\dtl@getfirst
. 274, 1323, 1326, 1334, 1346, 1347
\dtl@getfirst@UTFviii
..... 273, 1291, 1326, 1341
\dtl@getfirstthree 1128, 1129
\dtl@getsinglealphalabel .. 1128
\dtl@getvalue 457, 1243

\dtl@getyearsuffix 1129
\dtl@grabword 1340
\dtl@if@two@octets
. 273, 1291, 1326, 1327, 1333, 1341
\dtl@ifcasechargroup .. 1338, 1341
\dtl@ifsingle
270, 643, 1129, 1224, 1290, 1291,
1299, 1307, 1308, 1313, 1318,
1322, 1326, 1346, 1347, 1349–1352
\dtl@ifsingleorUTFviii
..... 272, 1291, 1323, 1334
\dtl@init@write@wrap ... 607, 607
\dtl@inithyphen 1313, 1314
\dtl@initials 1312–1314
\dtl@initialscmd 1312–1314
\dtl@initialshyphen ... 1313, 1314
\dtl@initialsnext 1313, 1314
\dtl@innerlabel 908, 1197, 1199, 1203
\dtl@innernodeopt
..... 915, 1200, 1201, 1203
\dtl@inneroffset
..... 908, 1197, 1198, 1203
\dtl@insertinto 271, 271, 1294
\dtl@int@round 308, 1361
\dtl@int@trunc 309, 1362
\dtl@labelangle 1200, 1201
\dtl@lccode 1317
\dtl@legend
. 933, 1007, 1210, 1218–1220, 1223
\dtl@legendlabels
..... 939, 1209, 1210, 1217
\dtl@legendline 1223
\dtl@legendsetting
..... 939, 1206, 1209, 1217, 1218
\dtl@linestyle 932, 1217, 1218
\dtl@listgetalpha label
..... 842, 1126, 1127
\dtl@mark 932, 1216–1218
\dtl@maxx 938, 1209, 1210
\dtl@maxy 938, 1209, 1210
\dtl@mean 1268, 1269
\dtl@message
23, 267, 268, 399, 404, 433, 449,
451, 452, 454, 456, 502, 505, 507,
575, 576, 588, 594, 595, 606, 613,
625, 626, 654, 741, 783, 840, 942,
1098, 1126, 1225, 1226, 1228,
1235, 1240–1242, 1254, 1255,
1257, 1278, 1281, 1282, 1285, 1290
\dtl@midangle 915, 1200–1203
\dtl@mingap 1086, 1092, 1211
\dtl@minx 938, 1209, 1210
\dtl@miny 938, 1209, 1210
\dtl@monthname
..... 812, 812, 818, 1111, 1113
\dtl@multibar@labels .. 1093, 1094
\dtl@multibarlabels 852, 1084, 1093
\dtl@multimidpt 1093, 1095
\dtl@n 1093
\dtl@nexttick 1211, 1212
\dtl@offset@x 931,
1210–1212, 1214, 1215, 1217–1220
\dtl@offset@y
..... 931, 1210–1214, 1217–1220
\dtl@old
1085, 1091, 1199, 1200, 1203, 1204
\dtl@oldtotal 1199
\dtl@omitlines
..... 598, 604, 631, 1284, 1285
\dtl@outerlabel 908, 1197, 1199, 1203
\dtl@outernodeopt . 915, 1201–1203
\dtl@outeroffset
..... 908, 1197, 1198, 1203
\dtl@parsewordshandler 1342
\dtl@piecutaways .. 908, 1197, 1199
\dtl@plotlinecolorlist 1210, 1216
\dtl@plotlineList 1210, 1217
\dtl@plotmarkcolorlist 1210, 1216
\dtl@plotmarklist 1210, 1216
\dtl@post ... 504, 506, 507, 1255, 1256
\dtl@pre ... 504, 506, 507, 1255, 1256
\dtl@prevtick 1211, 1212
\dtl@rawwrite@db 1283
\dtl@rawwrite@keys 1282, 1283
\dtl@reconstruct@data 622, 625, 626
\dtl@refvalue 565, 1273
\dtl@remainder 1216, 1217
\dtl@rest ... 273, 274, 1090, 1093,
1094, 1096, 1213, 1215, 1217,
1291, 1323, 1326, 1334, 1346, 1347
\dtl@restA
1323–1325, 1334–1336, 1347, 1348
\dtl@restB
1323–1325, 1334–1336, 1347, 1348
\dtl@row 1199
\dtl@rowi 494, 1248
\dtl@rowidx 1179, 1239
\dtl@rowii 494, 1248
\dtl@rowiii 494, 1248
\dtl@sang 1204

<code>\dtl@saverawdbhook</code>	1137, 1280, 1281	<code>\dtl@testbothnumerical</code>
<code>\dtl@scale@x</code> 931, 1206, 1210–1212, 1214, 1215, 1217–1220	..	<u>225</u> , 240, 242–244, 247, 249, 250, 1322, 1343–1345, 1349–1351
<code>\dtl@scale@y</code> 931, 1207, 1210–1214, 1217–1220	<code>\dtl@testclosedbetween</code> 254, <u>254</u> , 1353
<code>\dtl@segang</code> 1204	<code>\dtl@testcurrency</code>	.. 258, <u>258</u> , 1356
<code>\dtl@setcharcode</code> 275, 1194, 1323, 1326, 1347	<code>\dtl@testcurrencyunit</code> 259, <u>259</u> , 1356
<code>\dtl@setlccharcode</code> 1333, 1334	<code>\dtl@testendswith</code> 253, <u>253</u>
<code>\dtl@setwordbreaks</code> 1340, 1341	<code>\dtl@testeq</code> 251, <u>251</u> , 1352
<code>\dtl@setwordbreaksnohyphens</code> 1323, 1334, 1341, 1346, 1347	<code>\dtl@testFPiseq</code> 256, <u>256</u> , 257, 1354, 1355
<code>\dtl@sg@arg</code> 1290	<code>\dtl@testFPisgt</code> 256, <u>256</u> , 1354
<code>\dtl@sortdata</code> 591, 1274	<code>\dtl@testFPisgteq</code>	.. 257, 258, 1355
<code>\dtl@sortlist</code> 270, 1294	<code>\dtl@testFPislt</code> 255, 256, 1354
<code>\dtl@sortresult</code> 35–38, 45, 46, <u>47</u> , 271, 578, 579, 588, 1274, 1276–1278, 1295–1297	<code>\dtl@testFPislteq</code>	.. 257, <u>257</u> , 1355
<code>\dtl@SortWordCommands</code> 31, <u>31</u>	<code>\dtl@testFPopenbetween</code> 1354
<code>\dtl@SortWordCommands@hook</code> 31, <u>31</u> , 32, 33, 237, 575	<code>\dtl@testgt</code> 251, <u>251</u> , 1352
<code>\dtl@split@str</code> 221, 1317	<code>\dtl@testiceq</code> 252, <u>252</u> , 1352
<code>\dtl@splitstr</code>	.. 220, 221, 1317, 1318	<code>\dtl@testicgt</code> 251, <u>251</u> , 1352
<code>\dtl@srtelement</code>	... 271, 1294–1297	<code>\dtl@testiclosedbetween</code> 255, <u>255</u> , 1353
<code>\dtl@start</code> 1199, 1200	<code>\dtl@testiclt</code> 251, <u>251</u> , 1352
<code>\dtl@stream</code> 933, 1217, 1218	<code>\dtl@testiendswith</code> 253, <u>253</u>
<code>\dtl@string</code> 1312, 1313, 1323, 1334, 1340–1342, 1346, 1347	<code>\dtl@testifisubstring</code>	.. 252, <u>252</u>
<code>\dtl@subnobrsp</code>	1312, 1313, 1323, 1333, 1336, 1341, 1342, 1346, 1347	<code>\dtl@testiflowercase</code>	... 1315–1317
<code>\dtl@tc@arg</code> 1314, 1316	<code>\dtl@testiflowernext</code>	.. 1316, 1317
<code>\dtl@tc@rest</code> 1314–1316	<code>\dtl@testifsubstring</code> 252, <u>252</u> , 811, 1110, 1345, 1346, 1353
<code>\dtl@test@iflowercase</code> 1316	<code>\dtl@testifuppercase</code>	.. 1314, 1315
<code>\dtl@test@ifuppercase</code>	. 1314, 1315	<code>\dtl@testifuppernext</code>	.. 1314, 1315
<code>\dtl@testbibfieldcontains</code> 811, <u>811</u> , 1110	<code>\dtl@testinlist</code> 253, <u>253</u> , 1353
<code>\dtl@testbibfieldexists</code> 807, <u>807</u> , 1108	<code>\dtl@testint</code> 258, <u>258</u> , 1356
<code>\dtl@testbibfieldiseq</code> 807, <u>808</u> , 1108	<code>\dtl@testiopenbetween</code> 255, <u>255</u> , 1354
<code>\dtl@testbibfieldisge</code> 810, <u>810</u> , 1110	<code>\dtl@testistartswith</code>	... 253, <u>253</u>
<code>\dtl@testbibfieldisgt</code> 809, <u>809</u> , 1110	<code>\dtl@testlt</code> 250, 251, 1352
<code>\dtl@testbibfieldisle</code> 809, <u>809</u> , 1109	<code>\dtl@testnumclosedbetween</code> 254, <u>254</u> , 1353
<code>\dtl@testbibfieldislt</code> 808, <u>808</u> , 1109	<code>\dtl@testnumerical</code> 258, <u>258</u> , 1355, 1356
		<code>\dtl@testnumopenbetween</code> 254, <u>254</u> , 1353
		<code>\dtl@testopenbetween</code> 255, <u>255</u> , 1353, 1354
		<code>\dtl@testreal</code> 258, <u>258</u> , 1356
		<code>\dtl@teststartswith</code> 252, <u>252</u> , 1346, 1347, 1353
		<code>\dtl@teststring</code> 258, <u>258</u> , 1355
		<code>\dtl@textopt</code>	. 1088–1090, 1094–1097

<code>\dtl@this</code>	1093	<code>\dtl@xkey</code> .	930, 1207, 1209, 1210, 1217
<code>\dtl@thisbarlabel</code>	1093, 1094	<code>\dtl@xlabel</code>	939, 1209, 1214
<code>\dtl@thisdb</code>	1216, 1217, 1272	<code>\dtl@xminorticlist</code>	
<code>\dtl@thisfield</code>	1100	933, 1211, 1213, 1214
<code>\dtl@thisidx</code>	1253	<code>\dtl@xticgap</code>	939, 1209, 1211
<code>\dtl@thislabel</code>	1086, 1087, 1089, 1090, 1092, 1093, 1096, 1097, 1140, 1196, 1212–1215, 1217	<code>\dtl@xticlabelheight</code> 931, 1093, 1095, 1206, 1211, 1213
<code>\dtl@thisloc</code>	1164	<code>\dtl@xticlabels</code>	939, 1209, 1211, 1213
<code>\dtl@thisplotline</code>	1217	<code>\dtl@xticlist</code> .	938, 1209, 1211, 1213
<code>\dtl@thisplotlinecolor</code>	932, 1216, 1217	<code>\dtl@y</code>	930, 1205, 1215, 1217
<code>\dtl@thisplotmark</code>	1216	<code>\dtl@ykey</code> .	930, 1207, 1209, 1210, 1217
<code>\dtl@thisplotmarkcolor</code> 932, 1216		<code>\dtl@ylabel</code> ...	939, 1209, 1212, 1215
<code>\dtl@thisrow</code>		<code>\dtl@yminorticlist</code>	
.....	1253, 1266–1268, 1270, 1271	933, 1212, 1213, 1215
<code>\dtl@thistick</code>	1085, 1086, 1089–1091, 1096, 1097, 1213–1216	<code>\dtl@yticgap</code>	939, 1209, 1211
<code>\dtl@thisticklabel</code>	1213, 1215	<code>\dtl@yticlabels</code>	939, 1209, 1212, 1215
<code>\dtl@thisupperbarlabel</code>	1094, 1095	<code>\dtl@yticlabelwidth</code> 931, 1086, 1087, 1090–1092, 1097, 1206, 1211, 1212, 1215
<code>\dtl@thisval</code>	1305, 1308–1310	<code>\dtl@yticlist</code>	
<code>\dtl@ticklength</code> ...	931, 1213–1216	938, 1209, 1211–1213, 1215
<code>\dtl@ticlabeloffset</code> 932, 1213–1215		<code>\DTLabs</code>	202, 202, 1306, 1307
<code>\dtl@tlc</code>	1315	<code>\dtlabs</code>	202, 288, 295, 302, 310, 1307, 1360, 1362
<code>\dtl@tmp</code>	486, 1199, 1222, 1236, 1244, 1266, 1282, 1283, 1289, 1313, 1341–1343	<code>\DTLacmcs</code> ..	814, 816, 1112, 1113, 1125
<code>\dtl@tmpi</code>	1093	<code>\DTLacta</code> ...	815, 816, 1112, 1113, 1126
<code>\dtl@tmpii</code>	1093	<code>\DTLaction</code>	319, 333, 336, 338, 339, 341, 345, 348, 349, 354, 355, 359, 365, 369, 371, 373, 374, 383, 387, 388, 431, 432, 652, 665, 739, 900, 1020, 1021, 1034, 1035
<code>\dtl@tmplength</code>	23, 784, 842, 970, 973, 1086, 1087, 1090, 1092, 1093, 1095, 1097, 1099, 1127, 1145–1147, 1153, 1154, 1162, 1212, 1215, 1222, 1290	<code>\DTLadd</code>	200, 200, 1266–1269, 1304, 1305
<code>\dtl@tmpshift</code> ..	308, 309, 1361, 1362	<code>\dtladd</code>	200, 201, 285, 292, 300, 306, 1085, 1091, 1093–1096, 1199, 1200, 1203, 1204, 1214, 1215, 1217–1223, 1304, 1305, 1309–1311, 1359, 1361
<code>\dtl@total</code>	1199, 1203	<code>\dtladdalign</code> ...	513, 529, 1259–1261
<code>\dtl@truncatedecimal</code>	1200, 1201, 1300, 1303	<code>\DTLaddall</code>	200, 201, 1305
<code>\dtl@tuc</code>	1314	<code>\dtladdall</code>	285, 292, 300, 306
<code>\dtl@uccode</code>	1315	<code>\DTLaddcolumn</code> .	417, 1170, 1172, 1231
<code>\dtl@unit</code> .	852, 1086, 1087, 1091–1093	<code>\DTLaddcolumnwithheader</code>	418
<code>\dtl@upperbarlabel</code>	852, 1084, 1089	<code>\DTLaddcomma</code>	
<code>\dtl@uppermultibar@labels</code> ..	1093, 1094	..	790, 799, 802, 806, 818–838, 1101, 1105, 1107, 1113–1125
<code>\dtl@uppermultibarlabels</code> ...	853, 1084, 1093	<code>\DTLaddentryforrow</code>	508, 1257
<code>\dtl@variable</code>	1087–1089, 1093–1095, 1199	<code>\dtladdheaderalign</code>	515, 529
<code>\dtl@widest</code> ...	784, 1099, 1126, 1127	<code>\DTLaddperiod</code>	
<code>\dtl@x</code>	930, 1205, 1214, 1217	... 790, 818–838, 1101, 1113–1125	

<code>\DTLaddtopplotlegend</code>	<code>\DTLbardisplayYticklabel</code> ...
..... 1005, 1031, 1217, 1223 857, 896,
<code>\DTLaftercols</code> 512, 514, 515, 521, 1259	1082, 1086, 1087, 1090, 1092, 1097
<code>\DTLafterinitialbeforehyphen</code>	<code>\DTLbargroupindex</code> 855, 875, 878, 905
..... 217, 218, 219, 842, 1128, 1314	<code>\DTLbargrouplabelalign</code>
<code>\DTLafterinitials</code> 855, 874, 904
218, 219, 219, 842, 1128, 1313, 1314	<code>\DTLbargroupwidth</code> 901, 903, 904, 1093
<code>\DTLafterrow</code>	<code>\DTLbarindex</code>
433, 443, 447–449, 498, 537, 540, 855, 885, 905
1235, 1238–1240, 1250, 1264, 1266	<code>\DTLbarlabeloffset</code>
<code>\DTLlandlast</code> 791, 792, 1101–1103 856, 857, 869–871, 874,
<code>\DTLlandname</code>	903, 1082, 1088, 1089, 1094, 1095
21, 48, 261, 1297	<code>\DTLbarmax</code>
<code>\DTLlandnotlast</code> . 791, 792, 1101–1103	.. 855, 855, 856, 881–883, 894,
<code>\DTLaposinitialpunc</code> . 217–219, 219	895, 1083–1086, 1089–1092, 1096
<code>\DTLappendentrytocurrentrow</code>	<code>\DTLbaroutlinecolor</code>
..... 453,	863, 874, 889, 890, 1083, 1087, 1094
750, 759, 760, 762, 1185–1188, 1241	<code>\DTLbaroutlinewidth</code>
<code>\DTLappendrow</code>	863, 874, 889, 890, 1083, 1087, 1094
501, 1254	<code>\DTLbarroundvar (counter)</code>
<code>\DTLappendtorow</code> 501, 509, 1254, 1258	857
<code>\DTLassign</code>	<code>\DTLbarsetupperlabelalign</code> ..
434, 1235 864, 864
<code>\DTLassignfirstmatch</code>	<code>\DTLBarStyle</code>
..... 434, 435, 1235, 1236	857, 890
<code>\DTLassignfromcurrentrow</code> ... 436	<code>\DTLbartotalvariables</code> 851, 899–901
<code>\DTLassignlettergroup</code>	<code>\DTLbarvalue</code>
..... 39, 40, 40, 585	862, 887
<code>\dtlautokeysfalse</code> .. 594, 599, 1284	<code>\DTLbarvariable</code>
<code>\dtlbar@groupgap</code>	851,
..... 852, 1084, 1093, 1096	865, 876–881, 886, 898, 1084,
<code>\dtlbar@variables</code>	1085, 1087, 1088, 1091, 1093–1095
..... 851, 1084, 1090, 1091, 1093	<code>\DTLbarwidth</code>
<code>\dtlbar@ylabel</code>	855, 866, 885,
. 853, 1084, 1086, 1090, 1092, 1097	888, 902–904, 1082, 1084, 1087, 1093
<code>\dtlbar@yticgap</code>	<code>\DTLbarxaxisfalse</code> .. 871, 872, 1084
..... 853, 1084–1086, 1091, 1092	<code>\DTLBarXAxisStyle</code>
<code>\dtlbar@yticlabels</code> 857, 872, 894, 1082, 1089, 1096
853,	<code>\DTLbarxaxistrue</code>
1084, 1086, 1089, 1090, 1092, 1096	871, 1083
<code>\dtlbar@yticlist</code>	<code>\DTLbarXlabelalign</code>
853, 849, 855, 869, 870,
1084, 1086, 1089, 1091, 1092, 1096	891, 1081, 1082, 1088, 1093–1095
<code>\DTLbaratbegintikz</code>	<code>\DTLbarXneglabelalign</code>
... 858, 885, 903, 1082, 1087, 1093 850, 869, 870, 891
<code>\DTLbaratendtikz</code>	<code>\DTLbarXnegupperlabelalign</code> .
... 858, 886, 905, 1082, 1090, 1097 850, 864, 869, 892, 893
<code>\DTLbarchart</code> 858, 875, 879, 1083–1085	<code>\DTLbarXupperlabelalign</code>
<code>\DTLbarchartlength</code> 849, 864, 868, 893
..... 853, 854, 855, 871, 883,	<code>\DTLbaryaxisfalse</code>
1082, 1083, 1086, 1090, 1091, 1097 871, 872, 1083, 1084
<code>\DTLbarchartwidth</code>	<code>\DTLBarYAxisStyle</code>
851,	... 857, 872, 894, 1082, 1089, 1096
877, 894, 901, 1087, 1089, 1093, 1096	<code>\DTLbaryaxistrue</code>
 867, 871, 872, 1083, 1084

\DTLbarYticklabelalign 850, 874,
896, 1081, 1082, 1090, 1096, 1097
\DTLbaryticsfalse 871, 872, 1083, 1084
\DTLbaryticstrue 867, 871, 872, 1083, 1084
\dtlbeforecols 512, 513, 515, 521, 1259
\dtlbeforerow 432, 443, 447–449, 497, 537, 540,
1235, 1238–1240, 1250, 1264, 1266
\dtlbetweencols 512, 513, 515, 521, 1259
\DTLbetweeninitials 216, 217, 219, 842, 1128, 1314
\dtlbib@style 778, 1097, 1129
\DTLbibaccessedname 805, 805
\DTLbibdatefield 787, 803, 806
\DTLBIBdbname 780, 781, 847, 1098, 1131
\DTLbibdoi 805, 806
\DTLbibdoihome 804, 805
\DTLbibdoitag 804, 805
\DTLbibbeprints 805, 807
\DTLbibfield 787, 787,
789, 797–804, 806, 807, 818–838,
1100, 1101, 1105–1108, 1113–1125
\DTLbibfieldcontains . . . 811, 1110
\DTLbibfieldexists 807, 1108
\DTLbibfieldiseq 807, 1108
\DTLbibfieldisge 810, 1110
\DTLbibfieldisgt 809, 1109
\DTLbibfieldisle 809, 1109
\DTLbibfieldislt 808, 1109
\DTLbibfieldlet 788, 1100
\DTLbibformatdigital 806
\DTLbibgetlongestlabel 781
\DTLbibitem 782,
812, 817, 839, 1098, 1111, 1112, 1126
\DTLbibliography 782, 1098
\DTLbibliographystyle 844, 845, 1129
\DTLbibpubmed 806, 806
\DTLbibpubmedhome 804, 806
\DTLbibpubmedtag 804, 806
DTLbibrow (counter) 787
\DTLbibsetlongestlabel 781
\DTLbibsortencap 848
\DTLbibsortname 848, 848
\DTLbibsortnamesep 848, 848
\DTLbiburl 805, 806
\DTLbiburldate 804, 806
\DTLboxfalse 937, 1208
\dtlbreak . . . 259, 259, 260, 261, 486,
487, 489, 490, 492, 493, 509, 565,
1245–1247, 1258, 1273, 1356, 1357
\dtlbst@abbrv 838, 1125
\dtlbst@alpha 839, 1126
\dtlbst@plain 817, 838, 839, 1112, 1125, 1126
\DTLcacm . . . 815, 816, 1112, 1113, 1126
\DTLcheckbibfieldendsperiod
. 789,
798–800, 802, 803, 818–838,
1101, 1105–1108, 1113–1125
\DTLcheckendsperiod 789, 789, 790, 792, 793, 795–797,
1100–1104, 1115, 1117, 1118, 1121
\DTLcite 846, 1130
\DTLclearbarcolors 859
\DTLcleardb 361, 399, 1225
\DTLclearnegbarcolors 859
\DTLclip 209, 210, 1312
\dtlclip 210, 287, 294, 301,
309, 1260, 1261, 1312, 1359, 1362
\dtlcol 509, 1258
\DTLcolorbarchartfalse 873, 1081
\DTLcolorbarcharttrue 849, 873, 1081
\DTLcolorpiechartfalse 913, 1197
\DTLcolorpiecharttrue 906, 913, 1196
\DTLcolumncount 329, 343, 354, 355, 357, 363,
372, 383, 389, 395, 402, 425, 426,
472, 580, 581, 615, 616, 642, 1227
\dtlcolumnheader 515, 529
\dtlcolumnindex 406,
409, 420, 423, 428, 432, 435,
438, 445, 454, 455, 491, 502,
586, 589, 597, 626, 661, 666, 728,
742, 743, 747–749, 751, 754–761,
763–765, 773, 774, 784, 848,
1099, 1141, 1143, 1144, 1172,
1179–1181, 1184–1188, 1192,
1193, 1229–1231, 1233, 1234,
1236, 1239, 1241, 1242, 1246, 1254
\dtlcolumnnum 365, 367, 368, 371, 372, 387,
389, 404, 419–424, 428, 431–433,
454–456, 481, 502, 504, 506, 507,

\dtldatetetimealign [513](#), [514](#)
\dtldatetetimeformat [516](#), [531](#)
\dtldatetetimegroup [41](#), [43](#), [262](#)
\DTLdatumcurrency [78](#)
\DTLdatumtoDTM [115](#)
\DTLdatumtype [78](#), [116](#), [634](#)
\DTLdatumvalue [78](#), [114](#), [115](#), [327](#),
[376](#), [377](#), [386](#), [545](#), [548](#), [562](#), [563](#), [862](#)
\dtldbcolreconstruct ... [619](#), [620](#)
\dtldbdatumreconstruct
..... [619](#), [621](#), [621](#), [625](#)
\dtldbheaderreconstruct
..... [619](#), [621](#), [624](#)
\DTLdbLog [641](#)
\dtldbname [333](#), [334](#), [371](#), [372](#), [385](#),
[389](#), [390](#), [436](#), [437](#), [444](#), [446](#), [448](#),
[449](#), [451](#), [452](#), [454–456](#), [466–470](#),
[472](#), [475](#), [483–485](#), [524–526](#),
[528](#), [529](#), [535](#), [586](#), [589](#), [1239–1242](#)
\DTLdbNewEntry [433](#), [612](#)
\DTLdbNewRow [433](#), [604](#), [611](#)
\DTLdbProvideData [611](#), [616](#), [624](#), [627](#)
\dtldbreconstructkeyindex ..
..... [616](#), [622](#), [625](#)
\dtldbrowreconstruct [618](#), [620](#), [624](#)
\DTLdbSetHeader [434](#), [612](#)
\dtldbvaluereconstruct
..... [621](#), [621](#), [625](#)
\DTLdecimaltocurrency
... [106](#), [634](#), [637](#), [1303](#), [1305–1312](#)
\DTLdecimaltodate [110](#)
\DTLdecimaltodatetetime [110](#)
\DTLdecimaltolocale
..... [104](#), [196](#), [326](#), [327](#),
[634](#), [637](#), [887](#), [969](#), [1301](#), [1304–1312](#)
\DTLdecimaltotime [111](#)
\DTLdefaultEURcurrencyfmt ..
..... [192](#), [193](#)
\dtldefaultkey ... [365](#), [373](#), [425](#),
[478](#), [594](#), [628](#), [632](#), [1284](#), [1286](#), [1287](#)
\DTLDefaultLocaleWordHandler
..... [30](#), [44](#), [45](#)
\DTLdefcurrency [9](#), [186](#)
\DTLdeletedb [360](#), [400](#), [1226](#)
\dtldisableUTFviii [269](#), [1290](#)
\DTLdisplay [20](#)
\dtldisplayafterhead [517](#), [519](#),
[521](#), [533](#), [534](#), [1259](#), [1260](#), [1262](#), [1263](#)
\DTLdisplaybargrouplabel [857](#), [904](#)
\dtldisplaycr
..... [518](#), [519](#), [530](#), [533](#), [534](#), [1259–1263](#)
\DTLdisplaydb [523](#), [1259](#)
\DTLdisplaydbAddBegin .. [518](#), [524](#)
\DTLdisplaydbAddEnd [519](#), [525](#)
\DTLdisplaydbAddItem [532](#)
\dtldisplaydbenv . [518](#), [518](#), [519](#), [522](#)
\dtldisplayendtab
... [517](#), [519](#), [535](#), [1259](#), [1261](#), [1263](#)
\DTLdisplayinner label
..... [908](#), [924](#), [1197](#), [1203](#)
\DTLdisplaylongdb [535](#), [1261](#)
\DTLdisplaylongdbAddBegin ..
..... [532](#), [536](#)
\DTLdisplaylongdbAddEnd [535](#), [536](#)
\dtldisplaylongdbenv
..... [522](#), [532](#), [533](#), [535](#)
\DTLdisplaylowerbar label ...
.. [857](#), [886](#), [1082](#), [1088](#), [1093](#), [1096](#)
\DTLdisplaylowermultibar label
..... [857](#), [905](#), [1082](#), [1094](#)
\DTLdisplayouter label
..... [909](#), [924](#), [1197](#), [1203](#)
\dtldisplaystartrow
..... [517](#), [530](#), [1259–1261](#)
\dtldisplaystarttab [517](#),
[519](#), [521](#), [533](#), [534](#), [1259](#), [1260](#), [1262](#)
\DTLdisplayTBrowidxmap [518](#)
\DTLdisplayupperbar label ...
..... [858](#), [886](#), [1082](#), [1089](#)
\DTLdisplayuppermultibar label
..... [858](#), [905](#), [1082](#), [1095](#)
\dtldisplayvalign
..... [517](#), [518](#), [522](#), [1259](#), [1260](#)
\DTLdiv [202](#), [202](#), [1267–1269](#), [1306](#)
\dtldiv [202](#), [286](#), [293](#), [300](#), [307](#), [1086](#),
[1091](#), [1092](#), [1199](#), [1203](#), [1210](#),
[1211](#), [1213–1215](#), [1220–1222](#),
[1306](#), [1309–1311](#), [1359](#), [1361](#)
\DTLdobarcolor . [861](#), [863](#), [1082](#), [1083](#)
\DTLdocurrentbarcolor
..... [862](#), [1082](#), [1083](#), [1087](#)
\DTLdocurrentpiesegmentcolor
..... [910](#), [1197](#), [1198](#)
\dtldofirstlocation
..... [656](#), [697](#), [714](#), [1133](#), [1164](#)
\dtldolocationlist
.... [647](#), [656](#), [698](#), [714](#), [1133](#), [1164](#)
\DTLdopiesegmentcolor
..... [910](#), [910](#), [911](#), [1197](#), [1198](#)

\dtlenableUTFviii 269, 1290
\DTLencapbibfield 788
\DTLendbibitem
... 782, 784, 848, 1098, 1099, 1131
\DTLendpt .. 888, 889, 1088, 1089, 1095
DTLenvforeach (env.) 495
DTLenvforeach* (env.) 495
dtlengvforint (env.) 261
dtlengvforint* (env.) 261
DTLenvmapdata (env.) 470
\DTLeverybargrouphook .. 864, 904
\DTLeverybarhook
..... 864, 894, 1083, 1089, 1095
\DTLeveryprebarhook 864, 889
\dtlexpandnewvalue
317, 318, 601, 711, 1170, 1177, 1234
\dtlfallbackaction 43
\DTLfetch 445, 1239
\DTLfetchlistelement ... 30, 1293
\DTLfmtcurr ... 95, 103, 108, 109, 190
\DTLfmtcurrency 9,
95, 102, 108, 109, 186, 190, 190, 328
\dtlforcolumn 490, 708, 726, 749,
750, 1169, 1172, 1181, 1182, 1246
\dtlforcolumnidx 491, 1246
\DTLforeach .. 495, 496, 501–503,
505–512, 1150, 1153, 1155, 1158,
1160, 1195, 1249, 1252, 1254–1258
\DTLforeachbibentry . 782, 784,
785, 840, 847, 1098, 1099, 1126, 1131
\dtlforeachkey
..... 399–401, 442, 443, 488,
509, 607, 608, 610–612, 615, 616,
1226, 1227, 1238, 1245, 1258,
1260–1263, 1278, 1280, 1282, 1283
\DTLforeachkeyinrow
. 509, 1258, 1260, 1263, 1279, 1280
\dtlforeachlevel . 493, 493, 494,
496–512, 863, 910, 911, 1082,
1083, 1087, 1197–1199, 1248–1258
\dtlforint 259, 1356
\DTLformatabbrvforenames ...
..... 795, 838, 1104, 1125
\DTLformatarticle
..... 814, 818, 1112, 1113
\DTLformatarticlecrossref ..
..... 803, 818, 1108, 1113
\DTLformatauthor 793,
813, 817, 838, 1102, 1111, 1112, 1125
\DTLformatauthorlist
792, 818, 819, 821, 822, 824, 826,
828, 830–832, 836, 837, 1101,
1113–1118, 1120–1122, 1124, 1125
\DTLformatbibentry
782, 783, 784, 848, 1098, 1099, 1131
\DTLformatbibnamelist .. 791, 793
\DTLformatbook . 814, 819, 1112, 1114
\DTLformatbookcrossref
... 800, 819, 822, 1106, 1114, 1116
\DTLformatbooklet
..... 814, 821, 1112, 1115
\DTLformatbooktitle
... 802, 819, 838, 1107, 1114, 1125
\DTLformatbvolume
.. 798, 820, 823, 824, 826, 834,
1105, 1114, 1116, 1117, 1119, 1123
\DTLformatchapterpages
... 798, 822–825, 1105, 1116–1118
\DTLformatcrossrefeditor ...
... 796, 800, 801, 1104, 1106, 1107
\DTLformatdate
802, 819, 821, 823, 825, 827, 828,
830–835, 837, 838, 1107, 1114–1125
\DTLformatedition
.. 813, 818, 820, 823, 825, 830,
1112, 1113, 1115, 1117, 1118, 1121
\DTLformateditor . 793, 813, 817,
838, 1102, 1103, 1111, 1113, 1125
\DTLformateditorlist
..... 793, 802, 819, 822,
833, 1102, 1107, 1114, 1116, 1123
\DTLformatforenames
... 795, 813, 817, 1104, 1111–1113
\DTLformatinbook 814, 822, 1112, 1116
\DTLformatincollection
..... 814, 824, 1112, 1117
\DTLformatincolprocrossref
... 801, 824, 826, 1106, 1117, 1118
\DTLformatinedbooktitle
... 802, 824, 826, 1107, 1117, 1119
\DTLformatinproceedings
..... 814, 826, 1112, 1118
\DTLformatjr 796, 813,
817, 818, 838, 1104, 1111–1113, 1125
\DTLformatlegend
.. 936, 936, 1014, 1206, 1218–1220
\DTLformatlist 49, 1297
\DTLformatmanual 814, 828, 1112, 1120

\DTLformatmastersthesis 814, 830, 1112, 1121
\DTLformatmisc . 814, 831, 1112, 1122
\DTLformatnumberseries 799, 820, 825, 826,
834, 1106, 1114, 1117, 1119, 1123
\DTLformatpages 799, 799,
818, 826, 827, 1105, 1113, 1118, 1119
\DTLformatphdthesis 814, 832, 1112, 1122
\DTLformatproceedings 814, 833, 1112, 1123
\DTLformatsurname . . . 796, 813,
817, 818, 838, 1104, 1111–1113, 1125
\DTLformatsurnameonly 794, 796, 797, 1103, 1104
\DTLformattechreport 814, 836, 1112, 1124
\DTLformatthisbibentry 784, 1099
\DTLformatunpublished 814, 837, 1112, 1125
\DTLformatvolnumpages 797, 818, 1105, 1114
\DTLformatvon 795, 813,
817, 818, 838, 1104, 1111–1113, 1125
\DTLgabs 202, 1307
\DTLgadd 200, 1305
\DTLgaddall 201, 1305
\DTLgcleardb 399, 401, 596, 1227
\DTLgclip 210, 1312
\DTLgdeletedb 400, 400, 1226
\DTLgdiv 202, 1306
\DTLget 330
\DTLgetbarcolor 860, 861, 862, 889, 1082, 1094
\DTLgetcolumnindex 405, 1228
\DTLgetdatatype 408, 643, 1230, 1277, 1289
\DTLgetDataTypeName 63
\dtlgetentryfromcurrentrow 389, 390, 432, 438, 445, 452, 452,
454, 455, 502, 504, 506, 509, 530,
565, 608, 610, 611, 665, 666, 728,
743, 748, 751, 754, 756–758, 760,
761, 765, 773, 774, 1143, 1144,
1172, 1180, 1181, 1184–1188,
1192, 1193, 1234, 1236, 1239,
1241, 1242, 1254–1256, 1258, 1272
\dtlgetentryfromrow 443, 452, 453, 1238, 1241,
1266–1268, 1270, 1271, 1275, 1276
\dtlgetfirstchar 274
\DTLGetInitialLetter . . . 210, 219
\DTLGetkeydata 441, 1237
\DTLGetkeyforcolumn . . . 406, 1229
\DTLGetlocation 458, 1243
\DTLGetnegbarcolor 861, 861, 862, 889
\DTLGetpiesegmentcolor 910, 919, 1197, 1200
\dtlgetrow 388,
393, 432, 434, 436, 443, 444, 497,
537, 540, 608, 610, 611, 1188,
1234–1236, 1238, 1250, 1264, 1266
\DTLGetrowforkey 565, 565, 1272, 1273
\dtlgetrowforvalue 445, 1141, 1143,
1180, 1181, 1184–1187, 1192, 1239
\DTLGetrowindex 461, 1243
\dtlgetrowindex 435, 461, 461, 1179, 1236, 1239, 1244
\DTLGetvalue 456, 1243
\DTLGetvalueforkey 565, 840, 1127, 1272
\dtlgforint 260, 261, 497, 1250, 1288, 1356, 1357
\dtlgidx@checklocationchange 776, 1195
\DTLgidxAcrStyle 744, 745, 770, 1180, 1190
\DTLgidxAddLocationType 751, 1183
\DTLgidxAssignList 676, 724, 728, 776, 1171, 1172, 1195
\DTLgidxCategoryNameFont 694, 697, 1162, 1163
\DTLgidxCategorySep 694, 696, 1162, 1163
DTLgidxChildCount (counter) 660
\DTLgidxChildCountLabel 646, 661, 697, 1132, 1163
dtlgidxchildlist (env.) 665
\DTLgidxChildren 647, 665, 1133, 1143
\DTLgidxChildrenSeeAlso 647, 675, 676, 682, 683,
686–688, 691, 693, 694, 696, 697,
1133, 1149, 1150, 1153, 1154,
1156, 1157, 1159, 1161, 1163, 1164
\DTLgidxChildSep . . . 694, 694, 1162

\DTLgidxChildStyle 646,
646, 676, 682, 683, 690, 693, 697,
1132, 1149, 1154, 1159, 1161, 1163
\DTLgidxCounter
.... 650, 651, 756, 763, 1185–1187
\DTLgidxCurrenldb
.. 654, 661, 665–667, 676, 728,
773, 774, 776, 1137, 1138, 1141,
1143, 1144, 1150, 1153, 1155,
1158, 1160, 1172, 1192, 1193, 1195
\DTLgidxDictHead ... 694, 695, 1162
\DTLgidxDictPostItem
..... 694, 696, 1162, 1163
\DTLgidxDisableHyper .. 668, 1145
\DTLgidxDoSeeOrLocation
..... 664, 673, 674, 676,
679–681, 683, 686–688, 691, 693,
694, 697, 1141, 1148, 1150–1152,
1154, 1156, 1157, 1159, 1161, 1164
\DTLgidxEnableHyper ... 668, 1145
\DTLgidxEndItem
..... 669, 675, 682, 689, 693, 694
\DTLgidxFetchEntry 664,
753, 753, 767–769, 1140, 1184, 1189
\DTLgidxForeachEntry
..... 775, 775, 1194, 1195
\DTLgidxFormatAcr 770, 770, 771, 1190
\DTLgidxFormatAcrUC 770, 771, 1190
\DTLgidxFormatDesc
..... 647, 648–650, 1135, 1136
\DTLgidxFormatSee ... 647, 656,
657, 662, 714–716, 1133, 1134, 1140
\DTLgidxFormatSeeAlso
..... 647, 662, 1133, 1140
\DTLgidxGobble 721, 728, 1173
\DTLgidxGroupHeaderTitle ...
..... 674, 688, 692, 694,
775, 1149, 1158, 1160, 1162, 1194
\DTLgidxIgnore
..... 723, 729, 1137, 1173, 1176
\DTLgidxLocation
.... 647, 656, 664, 714, 1133, 1141
\DTLgidxLocationF
..... 704, 706, 1167, 1168
\DTLgidxLocationFF
..... 704, 705, 1167, 1168
\DTLgidxLocationSep
..... 704, 704, 705, 1167, 1168
\DTLgidxMac 723, 729, 1137, 1173, 1176
\DTLgidxName 721,
723, 729, 775, 1137, 1173, 1176, 1193
\DTLgidxNameCase
..... 646, 655, 673–677,
681–684, 689–691, 693, 696,
697, 712, 713, 1132, 1148–1150,
1153–1155, 1158–1161, 1163
\DTLgidxNameFont 646, 655,
673–677, 681–684, 689–691, 693,
696, 713, 1132, 1139, 1148–1150,
1153–1155, 1158–1161, 1163, 1191
\DTLgidxNameNum
..... 723, 729, 1137, 1173, 1177
\DTLgidxNoFormat
..... 721, 722, 728, 1173, 1176
\DTLgidxNoHeading 666, 1144
\DTLgidxOffice 721,
723, 729, 775, 1137, 1173, 1176, 1194
\DTLgidxParen
... 721, 723, 731, 1137, 1173, 1176
\DTLgidxParticle
721, 723, 730, 1137, 1173, 1176, 1177
\DTLgidxPlace 721,
723, 729, 775, 1137, 1173, 1176, 1193
\DTLgidxPostChild
..... 693, 694, 1161, 1162
\DTLgidxPostChildName
.. 646, 676, 683, 690, 693, 697,
1132, 1149, 1154, 1159, 1161, 1163
\DTLgidxPostDescription
..... 646, 648–650,
655, 713, 1132, 1133, 1135, 1136
\DTLgidxPostLocation ... 647, 664
\DTLgidxPostName
..... 646, 646, 655, 675, 677,
682, 684, 689, 691, 693, 696, 713,
1132, 1139, 1149, 1150, 1153,
1155, 1158, 1160, 1161, 1163, 1191
\DTLgidxPreLocation
..... 646, 647, 655–657, 664,
669–671, 678–680, 685, 686, 688,
713, 714, 716, 1133, 1134, 1141,
1146, 1147, 1151, 1152, 1155–1157
\DTLgidxRank 723, 730, 1137, 1173, 1177
\DTLgidxSaint
..... 723, 730, 1137, 1173, 1176
\DTLgidxSee 647, 656,
657, 665, 714, 715, 1133, 1134, 1141
\DTLgidxSeeAlso 647, 647, 1133
\DTLgidxSeeList . 662, 663, 663, 1140

\DTLgidxSeeTagFont 662, 662, 663, 1140
\DTLgidxSetColumns
... 645, 655, 711, 1131, 1139, 1191
\DTLgidxSetCompositor
..... 650, 650, 1136, 1139
\DTLgidxSetDefaultDB .. 706, 1168
\DTLgidxStripBackslash 729, 1173
\DTLgidxSubCategorySep
..... 694, 697, 1162, 1163
\DTLgidxSubject 721,
723, 729, 775, 1137, 1173, 1176, 1194
\DTLgidxSymbolDescLeft
..... 647–650, 669–672,
678–680, 685–687, 1135, 1136,
1146, 1147, 1151, 1152, 1155–1157
\DTLgidxSymbolDescRight
..... 647–650, 670–672,
678–680, 686, 687, 1135, 1136,
1146, 1147, 1151, 1152, 1156, 1157
\DTLgidxSymbolDescription ..
..... 647, 671, 674, 676, 680,
681, 683, 688, 691, 693, 696, 697,
1135, 1146, 1148, 1150, 1152,
1154, 1157, 1159, 1161, 1163, 1164
\DTLgidxSymDescSep
..... 647, 648–650, 669–672,
678–680, 685–687, 1135, 1136,
1146, 1147, 1150–1152, 1155–1157
\DTLgmax 204, 1309
\DTLgmaxall 205, 1309
\DTLgmeanforall 205, 1309
\DTLgmin 203, 1308
\DTLgminall 204, 1308
\DTLgmul 202, 1306
\DTLgneg 203, 1307
\DTLgnewdb 400, 709, 1170, 1226
\DTLground 209, 1311
\DTLgsdforall 208, 1311
\DTLgsqrt 203, 1307
\DTLgsub 201, 1305
\DTLgtrunc 209, 1312
\DTLgvarianceforall ... 207, 1310
\dtlheader 509, 1258
\dtlheaderformat
.. 515, 516, 1259, 1260, 1262, 1263
\DTLibmjrd . 815, 816, 1112, 1113, 1126
\DTLibmsj .. 815, 816, 1112, 1113, 1126
\dtlcompare
233, 238, 585, 1273, 1333–1336,
1341, 1343–1345, 1349, 1351
\dtlcomparewords . 238, 1339, 1341
\DTLidxFormatSeeItem 663, 664, 1140
\DTLidxSeeLastSep
..... 663, 664, 1140, 1141
\DTLidxSeeSep .. 663, 664, 1140, 1141
\DTLIEEEese . 815, 816, 1112, 1113, 1126
\DTLIEEEetc . 815, 816, 1112, 1113, 1126
\DTLIEEEetcad 815, 816, 1112, 1113, 1126
\DTLlifaction 330
\DTLlifAllLowerCase 220, 1315
\DTLlifAllUpperCase 219, 1314
\DTLlifanybibfieldexists
788, 818–838, 1100, 1105, 1114–1125
\DTLlifbibfieldexists
.. 788, 789, 792, 793, 796–804,
806–811, 818–838, 840, 841,
1100–1102, 1104–1110, 1113–1127
\dtlifecyclechargroup ... 238, 1342
\DTLlifcatedatatype 228, 1322
\DTLlifclosedbetween 247, 1349, 1353
\DTLlifcurrency . 227, 258, 1322, 1356
\DTLlifcurrencyunit
..... 228, 259, 1322, 1356
\DTLlifdate 226
\DTLlifdatetime 226
\DTLlifdbempty 402, 1227
\DTLlifdbexists 333,
334, 359, 398–406, 408, 417, 418,
428, 431, 433, 434–436, 441, 467,
490, 491, 495, 508, 524, 535,
539, 546, 550, 553, 556, 559,
586, 595, 596, 606, 613, 624,
625, 741, 742, 765, 773, 1015,
1020, 1178, 1179, 1188, 1192,
1225–1231, 1233–1237, 1246,
1249, 1252, 1257, 1265, 1266,
1268–1271, 1273, 1278–1280, 1282
\DTLlifEndsWith 245
\DTLlifeq 243, 1345, 1352
\DTLliffirstrow 496, 500,
510, 1249, 1251–1253, 1258, 1260
\DTLlifFPclosedbetween
..... 230, 250, 1348, 1352
\DTLlifFPopenbetween 231,
250, 1211, 1220, 1350, 1352, 1354
\DTLlifgt 241, 1344, 1352
\DTLlifhasj 404, 1228, 1273

<code>\DTLifinlist</code>	29 ,	<code>\DTLifstringclosedbetween</code> ..	
	253 , 1260–1263 , 1292 , 1353 , 1363	 245 , 1348
<code>\DTLifint</code>		<code>\DTLifstringeq</code>	242 , 1345
	226 , 258 , 699 , 1131 , 1322 , 1342 , 1356	<code>\DTLifstringgt</code>	43 , 241 , 1344
<code>\dtlifintclosedbetween</code>		<code>\DTLifstringlt</code>	239 , 1343
	25 , 1194 , 1291 , 1342	<code>\DTLifstringopenbetween</code>	248 , 1350
<code>\dtlifintopenbetween</code> ...	25 , 1291	<code>\DTLifSubString</code>	
<code>\DTLiflastrow</code>	496 ,	 244 , 1128 , 1296 , 1297 , 1345
	500 , 511 , 1249 , 1251–1253 , 1258	<code>\DTLiftemporal</code>	225
<code>\DTLiflt</code>	240 , 1343 , 1352	<code>\DTLiftime</code>	227
<code>\DTLifnull</code>	440 ,	<code>\DTLiftimestamp</code>	226
	565 , 777 , 1100 , 1133 , 1134 , 1141 ,	<code>\DTLinbooktitlefmt</code>	794 , 822
	1143 , 1150 , 1154 , 1155 , 1158 ,	<code>\DTLinitialhyphen</code>	
	1160 , 1164 , 1185 , 1186 , 1188 ,	 217 , 218 , 219 , 842 , 1128 , 1314
	1195 , 1196 , 1237 , 1273 , 1276 , 1280	<code>\DTLinitialpunc</code>	216–218 , 219
<code>\DTLifnulllorempty</code>	441 , 1237	<code>\DTLinitials</code>	215 , 215 , 1312
<code>\DTLifnumclosedbetween</code>		<code>\DTLinnerratio</code>	
	... 230 , 247 , 254 , 1348 , 1350 , 1353	 908 , 908 , 912 , 913 , 1197 , 1198
<code>\dtlifnumclosedbetween</code> .	250 ,	<code>\DTLinseries</code>	794 , 799
	284 , 292 , 299 , 306 , 1352 , 1358 , 1361	<code>\dtlininsertinto</code> ...	46 , 47 , 1295 , 1297
<code>\DTLifnumeq</code> .	230 , 243 , 244 , 1344 , 1345	<code>\dtlintalign</code>	512 , 513 , 521 , 1259
<code>\dtlifnumeq</code>		<code>\dtlintformat</code>	
	.. 230 , 256 , 284 , 291 , 298 , 299 ,	 516 , 531 , 1259 , 1260 , 1263
	300 , 305 , 1201 , 1202 , 1222 , 1300 ,	<code>\DTLinttype</code>	408 , 1230
	1301 , 1303 , 1344 , 1355 , 1358–1360	<code>\DTLipl</code> .	815 , 816 , 817 , 1112 , 1113 , 1126
<code>\DTLifnumerical</code> 225 , 225 , 247 , 249 ,		<code>\DTLisclosedbetween</code>	254 , 1217 , 1353
	250 , 258 , 797 , 799 , 1105 , 1321 , 1356	<code>\DTLiscurrency</code>	258 , 1356
<code>\DTLifnumgt</code> 230 , 242 , 1278 , 1343 , 1344		<code>\DTLiscurrencyunit</code>	259 , 1356
<code>\dtlifnumgt</code>	230 ,	<code>\DTLiseq</code>	251 , 1352
	235 , 256 , 257 , 284 , 291 , 298 , 299 ,	<code>\DTLisFPclosedbetween</code>	
	305 , 306 , 1201 , 1203 , 1220 , 1221 ,	 254 , 1085 , 1091 , 1354
	1308 , 1343 , 1354 , 1355 , 1358 , 1360	<code>\DTLisFPeq</code>	257 , 1355
<code>\DTLifnumlt</code>	230 , 240 ,	<code>\DTLisFPgt</code>	256 , 1354
	1088 , 1094 , 1095 , 1278 , 1323 , 1343	<code>\DTLisFPgteq</code>	258 , 1355
<code>\dtlifnumlt</code>	230 ,	<code>\DTLisFPlt</code>	256 , 1085 , 1091 , 1354
	235 , 255 , 257 , 284 , 291 , 298 , 299 ,	<code>\DTLisFPlteq</code>	257 , 1355
	305 , 306 , 1200–1203 , 1220 , 1221 ,	<code>\DTLisFPopenbetween</code>	
	1307 , 1323 , 1354 , 1355 , 1358–1360	 254 , 1085 , 1091 , 1221 , 1222 , 1354
<code>\DTLifnumopenbetween</code>		<code>\DTLisgt</code>	251 , 1352
 231 , 249 , 250 , 254 , 1350–1353	<code>\DTLisiclosedbetween</code> ..	255 , 1353
<code>\dtlifnumopenbetween</code>		<code>\DTLisieq</code>	252 , 1352
 250 , 284 , 292 , 299 ,	<code>\DTLisigt</code>	251 , 1352
	306 , 1200–1202 , 1352 , 1358 , 1360	<code>\DTLisilt</code>	251 , 1352
<code>\DTLifodddrow</code>	497 ,	<code>\DTLisinlist</code>	253 , 1353
	500 , 511 , 1249 , 1251–1253 , 1258	<code>\DTLisint</code>	258 , 1356
<code>\DTLifopenbetween</code> .	249 , 1351 , 1353	<code>\DTLisiopenbetween</code>	255 , 1354
<code>\DTLifreal</code>	226 , 258 , 1321 , 1356	<code>\DTLisiPrefix</code>	253
<code>\DTLifStartsWith</code>	244 , 1346	<code>\DTLisiSubString</code>	252
<code>\DTLifstring</code> ...	227 , 258 , 1322 , 1355	<code>\DTLisiSuffix</code>	253
		<code>\DTLislt</code>	251 , 1352

\DTLisnumclosedbetween 543, 545, 547, 554, 556, 558, 560,
..... 254, 254, 1353, 1354 561, 576, 676, 776, 875, 914, 941, 961
\DTLisnumeq 256, 257 \DTLmapatabreak 470
\DTLisnumerical 258, 1266–1271, 1356 \DTLmapget ... 481, 481, 483, 541,
\DTLisnumgt 256, 256 543, 545, 547, 555, 556, 558, 560, 941
\DTLisnumgteq 257, 258 \DTLmapgetvalues . 484, 484, 541,
\DTLisnumlt 256, 256 545, 554, 558, 562, 875, 914, 941, 961
\DTLisnumlteq 257, 257 \DTLmaprow 480, 480
\DTLisnumopenbetween 254, 254, 1353 \DTLmaprowbreak 481
\DTLisopenbetween 255, 1354 \DTLmax 204, 204, 1271, 1272, 1308, 1309
\DTLisPrefix 252, 1353 \dtlmax 204,
\DTLisreal 258, 1356 287, 295, 301, 310, 1085, 1091,
\DTLisstring 258, 1355 1221, 1272, 1308, 1309, 1360, 1362
\DTLisSubString 252, 1353 \DTLmaxall 204, 205, 1309
\DTLisSuffix 253 \dtlmaxall 288, 295, 302, 310
\DTLjacc 815, 816, 817, 1112, 1113, 1126 DTLmaxauthors (counter) 791
\DTLjcss 815, 816, 817, 1112, 1113, 1126 DTLmaxeditors (counter) 793
\DTLjournalfmt 794, 804, 818 \DTLmaxforcolumn 559, 1271
\dtlkey ... 509, 1258, 1260, 1263, 1280 \DTLmaxforkeys 557, 1271
\dtllastloadeddb \DTLmaxX 960, 963, 966, 974,
.. 611, 615, 622, 624–628, 640, 975, 1022, 1210–1213, 1215–1220
708, 1169, 1170, 1280, 1282–1284 \DTLmaxY .. 960, 963, 966, 974, 975,
\dtllastloadedeb 598 1022, 1210–1214, 1217, 1218, 1220
\DTLlegendxoffset 936, \DTLmbibitem 813,
955, 1008–1013, 1206, 1218–1220 817, 839, 848, 1111, 1112, 1126, 1131
\DTLlegendyoffset 936, \DTLmbibliography 847, 1131
955, 1008–1013, 1206, 1218–1220 \DTLmeanforall 205, 205, 1309
\dtllettergroup 40, 42, 262 \dtlmeanforall ... 288, 295, 302, 310
\dtlletterindexcompare 237, 1336 \DTLmeanforcolumn . 546, 1267, 1269
\DTLlistand 21, 48, 791 \DTLmeanforkeys 544, 1267
\DTLlistelement 30, 1292 \DTLmidpt 888, 1089, 1095
\DTLlistformatitem ... 48, 48, 1297 \DTLmidsentencefalse
\DTLlistformatlastsep 790, 803, 819,
..... 48, 48, 1068, 1297 832, 1098, 1101, 1107, 1114, 1122
\DTLlistformatoxford \DTLmidsentencetrue ... 790, 1101
..... 48, 48, 1068, 1297 \DTLmin 203, 203,
\DTLlistformatsep 48, 48, 1067, 1297 1085, 1091, 1270, 1271, 1307, 1308
\DTLlistskipemptytrue .. 22, 1292 \dtlmin 203, 204, 287,
\DTLloadbbl 779, 1097 294, 301, 309, 1272, 1308, 1360, 1362
\DTLloaddb 640, 1285 \DTLminall 204, 204, 1308
\DTLloaddbtex 640, 1283 \dtlminall 287, 294, 301, 309
\DTLloadmdbl 847, 1131 \DTLminforcolumn 556, 1270
\DTLloadrawdb 640, 1288 \DTLminforkeys 554, 1270
\DTLmajorgridstyle \DTLminminortickgap
..... 936, 946, 980, 1206, 1213 935, 1015, 1020, 1206, 1222
\DTLmaketabspc 315, 1224 \DTLminorgridstyle
\DTLmanualtitlefmt 794, 829 936, 946, 979, 1206, 1213
\dtlmapcurrentrow 564 \DTLminorticklength
\DTLmapdata 375, 382, ... 935, 987, 998, 1206, 1214, 1215
467, 470, 473, 474, 481, 484, 541,

\DTLmintickgap 884,
935, 968, 971, 1086, 1092, 1206, 1211
\DTLminX .. 960, 963, 965, 974, 975,
978, 993, 994, 999, 1022, 1210–1220
\DTLminY 960, 963,
965, 974–977, 982, 983, 988, 989,
1022, 1210–1215, 1217, 1219, 1220
\DTLmonthname
812, 812, 818, 838, 1111, 1113, 1125
\DTLmul 201, 202, 1268, 1269, 1305, 1306
\dtlmul ... 201, 285, 293, 300, 307,
1093, 1199, 1200, 1203, 1204,
1210, 1214, 1215, 1217–1220,
1222, 1306, 1310, 1311, 1359, 1361
\DTLmultibarchart .. 858, 897, 1090
\DTLmultibibs .. 845, 846, 1129, 1130
\DTLmutlibibs 1130, 1131
\DTLneg 202, 203, 1307
\dtlneg 203,
288, 295, 302, 310, 1307, 1360, 1362
\DTLnegextent
.. 856, 856, 881–883, 894, 895,
1083–1086, 1089–1092, 1096, 1097
\DTLnewbibitem 780, 781, 1098
\DTLnewbibliteralitem 780
\DTLnewbibrow 780, 1098
\DTLnewcurrencysymbol
..... 52, 54, 187, 190, 1304
\DTLnewdb 398, 400,
432, 596, 610, 624, 660, 780, 847,
1097, 1131, 1140, 1225, 1280, 1285
\DTLnewdbentry 368, 431, 610, 711,
1170, 1172, 1177, 1178, 1234, 1280
\DTLnewdbonloadtrue ... 594, 1285
\DTLnewrow 403, 403,
431, 610, 711, 1170, 1177, 1227, 1280
\DTLnocite 846, 1130
\dtlnoexpandnewvalue
..... 317, 318, 601, 1234
\dtlnoheaderfalse 1285
\dtlnonlettergroup ... 40, 43, 262
\dtlnovalue 66, 66, 67, 68, 74, 78, 79,
86, 320, 325, 330–332, 458, 459,
462–465, 483–485, 509, 570, 571,
589, 728, 753, 1179, 1180, 1185,
1187, 1235–1239, 1241–1244,
1254–1256, 1258, 1275, 1276
\dtlnumbergroup ... 40, 41, 43, 262
\DTLnumbernull
66, 66, 67, 68, 78, 198, 205, 206,
208, 336, 440, 483, 531, 532, 1237
\DTLnumcompare 231, 588
\dtlnumericformat 516, 516
\DTLnumitemsinlist
..... 30, 1260, 1261, 1293
\DTLofseries 794, 798
\DTLofseriesfmt 794, 794, 801
\DTLouterratio
..... 908, 908, 912, 913, 1197, 1198
\dtlpadleadingzeros 27
\dtlpadleadingzerosminus . 27, 27
\dtlpadleadingzerosplus .. 27, 27
\DTLpar 319,
674, 688, 692, 1149, 1158, 1160, 1225
\DTLparse 34, 86
\dtlparsewords 238, 1342
\DTLpcite 801, 802, 804, 804, 1106–1108
\DTLperiodfalse
... 790, 797, 798, 1098, 1101, 1105
\DTLperiodtrue 1101
\DTLpieatbegintikz
..... 909, 917, 1197, 1199
\DTLpieatendtikz 909, 924, 1197, 1203
\DTLpieatsegment 909, 920
\DTLpiechart 909, 924, 927, 1197–1199
\DTLpieoutlinecolor
..... 911, 914, 920, 1198, 1200
\DTLpieoutlinewidth
... 911, 914, 919, 920, 1198, 1200
\DTLpiepercent 909, 925, 1197
DTLpieroundvar (counter) 908
\DTLpievariable 907,
908, 914, 916, 925–927, 1197, 1199
\DTLplot 942, 962, 1014, 1207, 1209, 1210
\DTLplotatbegintikz
..... 962, 974, 1206, 1212
\DTLplotatendtikz
..... 963, 975, 1207, 1220
\DTLplotdisplayticklabel 938, 938
\DTLplotdisplayXticklabel ..
..... 938, 970, 983, 984
\DTLplotdisplayYticklabel ..
..... 938, 973, 993, 994
\dtlplothandlermark
..... 962, 973, 1207, 1212, 1220
\DTLplotheight
... 935, 945, 960, 1206, 1207, 1210
\DTLplotlegendname ... 1033, 1034

<code>\DTLplotlegendnamesep</code>	. 1033 , 1034	<code>\dtlrealformat</code>
<code>\DTLplotlegendsetname</code> 1034	 516 , 531 , 1259 , 1260 , 1263
<code>\DTLplotlegendsetxlabel</code>	... 1035	<code>\DTLrealttype</code> 408 , 1230
<code>\DTLplotlegendsetylabel</code>	... 1035	<code>\dtlrecombine</code> 448 ,
<code>\DTLplotlegendx</code> 1033 , 1034		743 , 749 , 756 , 757 , 759 , 763 , 764 ,
<code>\DTLplotlegendxy</code> 1032 , 1033		766 , 1180 , 1181 , 1185–1188 , 1239
<code>\DTLplotlegendxysep</code>	... 1033 , 1033	<code>\dtlrecombineomitcurrent</code>	...
<code>\DTLplotlegendy</code> 1033 , 1035	 449 , 1240
<code>\DTLplotlinecolors</code>	<code>\DTLreconstructdata</code> 624
 934 , 943 , 1003 , 1005 ,	<code>\DTLreconstructdatabase</code>	616 , 625
	1016 , 1021 , 1205 , 1207 , 1210 , 1216	<code>\DTLreconstructdbdata</code> 625
<code>\DTLplotlines</code>	934 , 943 , 1003 , 1004 ,	<code>\DTLremovecurrentrow</code>	.. 507 , 1257
	1016 , 1020 , 1205 , 1207 , 1210 , 1217	<code>\DTLremoveentryfromrow</code>	503 , 1255
<code>\DTLplotmarkcolors</code>	<code>\dtlremoveentryincurrentrow</code>
 934 , 943 , 1003 , 1004 ,	 451 , 1240
	1016 , 1021 , 1205 , 1207 , 1210 , 1216	<code>\DTLremoventryfromrow</code>	. 503 , 1255
<code>\DTLplotmarks</code>	933 , 943 , 1002 , 1004 ,	<code>\DTLremoverow</code> 539 , 1265
	1016 , 1020 , 1205 , 1207 , 1210 , 1216	<code>\DTLreplaceentryforrow</code>
<code>DTLplotroundXvar (counter)</code> 935	 505 , 508 , 1256 , 1257
<code>DTLplotroundYvar (counter)</code> 935	<code>\dtlreplaceentryincurrentrow</code>
<code>\DTLplotstream</code> 961 , 1205	 451 , 452 , 748 ,
<code>\DTLplotwidth</code>		749 , 755 , 759 , 761 , 762 , 764 , 765 ,
	... 934 , 945 , 960 , 1206 , 1207 , 1210		1181 , 1185 , 1187 , 1188 , 1240–1242
<code>\DTLpostchaptername</code> 793 , 798	<code>\DTLresetLanguage</code> 261 , 282
<code>\DTLpostnumbername</code>	.. 794 , 799 , 836	<code>\DTLresetpredefined</code> 816 , 818
<code>\DTLpostpagename</code> 793 , 797 , 799	<code>\DTLresetpredefinedabbrv</code>	816 , 838
<code>\DTLpostvolnum</code> 793 , 797	<code>\DTLresetRegion</code> 262
<code>\DTLpostvolumename</code>	.. 793 , 798 , 800	<code>\DTLrmentry</code> 472 , 473 , 476 , 479
<code>\DTLpostvon</code> 793 , 794 , 795	<code>\DTLrmrow</code> 472 , 473 , 480
<code>\DTLprecite</code> 794 , 801 , 802 , 804	<code>\dtlroot</code> 203 , 286 ,
<code>\DTLPreProcessCurrencyGroup</code>		293 , 301 , 307 , 1307 , 1311 , 1359 , 1361
 41 , 42	<code>\DTLrotateinnerfalse</code>	.. 906 , 1197
<code>\DTLPreProcessDateGroup</code>	.. 41 , 42	<code>\DTLrotateinnertrue</code> 1197
<code>\DTLPreProcessDateTimeGroup</code>	<code>\DTLrotateouterfalse</code>	.. 906 , 1197
 41 , 42	<code>\DTLrotateoutertrue</code> 1197
<code>\DTLPreProcessDecimalGroup</code>	.	<code>\DTLround</code> 209 , 209 , 1311
 40 , 42	<code>\dtlround</code>
<code>\DTLPreProcessIntegerGroup</code>	.		107 , 209 ,
 40 , 42		286 , 294 , 301 , 308 , 327 , 1086 ,
<code>\DTLPreProcessLetterGroup</code>	40 , 42		1089 , 1092 , 1096 , 1199 , 1212 ,
<code>\DTLPreProcessNonLetterGroup</code>		1213 , 1215 , 1217 , 1311 , 1359 , 1361
 40 , 42	<code>\DTLrowcount</code> 337 ,
<code>\DTLPreProcessTimeGroup</code>	.. 41 , 42		362 , 391 , 395 , 401 , 444 , 467 , 525 ,
<code>\DTLproceedingstitlefmt</code>	794 , 834		528 , 575 , 586 , 596 , 608 , 610 , 611 ,
<code>\DTLprotectedsaverawdb</code>	623 , 1282		614 , 616 , 642 , 765 , 1188 , 1227 , 1273
<code>\DTLradius</code> 907 , 908 ,	<code>\DTLrowincr</code> 493
	912 , 913 , 919 , 920 , 1197 , 1198 , 1200	<code>\dtlrownum</code>
<code>\DTLrawmap</code> 641 , 1289		371 , 372 , 385 , 387 , 388 , 404 , 444 ,
<code>\DTLread</code>	.. 595 , 626 , 627 , 640 , 707 , 708		446 , 448 , 449 , 467 , 470 , 502 , 504 ,
<code>\dtlrealalign</code>	... 512 , 514 , 521 , 1259		506 , 525 , 530 , 532 , 536 , 576 , 596 ,

604, 627, 633, 1141, 1142, 1228,
 1239, 1240, 1254–1256, 1274, 1275
 \DTLrowreset 493
 \DTLsavedb 623, 1278
 \DTLsaveastrowcount .. 494, 1248
 \DTLsaverawdb 623, 1137, 1280
 \DTLsaverowcount 494
 \DTLsavetexdb 623, 1279
 \DTLscinum 8, 94
 \DTLscp . 815, 816, 817, 1112, 1113, 1126
 \DTLsdforall ... 207, 208, 1310, 1311
 \dtlsdforall 290, 296, 303, 312
 \DTLsdforcolumn 552, 1270
 \DTLsdforkeys 551, 1269
 \DTLsetbarcolor
 859, 863, 873, 1082, 1083
 \dtlsetcharcode 275, 275, 1327
 \DTLsetcurrencydatum 91, 91
 \DTLsetdecimaldatum 90, 91
 \DTLsetdefaultcurrency
 186, 262, 1304
 \dtlsetdefaultUTFviiiicharcode
 276, 276, 1327
 \dtlsetdefaultUTFviiiilccharcode
 276, 279, 1327, 1330
 \DTLsetdelimiter
 315, 318, 600, 1224, 1225
 \DTLsetentry 472, 473, 476
 \DTLsetfpdatum 90
 \DTLsetheader .. 427, 611, 1233, 1280
 \DTLsetintegerdatum ... 89, 90, 589
 \dtlsetlcharcode . 275, 1327, 1333
 \DTLsetLocaleOptions 265
 \DTLsetnegbarcolor 859, 873
 \DTLsetnumberchars
 8, 57, 58, 262, 1298
 \DTLsetpiesegmentcolor
 910, 911, 913, 914, 1197, 1198
 \DTLsetseparator
 314, 315, 318, 600, 1223–1225
 \DTLsetstringdatum 92
 \DTLsettabseparator 314, 601, 1224
 \DTLsettemporaldatum 92, 92
 \DTLsetup
 22, 116, 333, 359, 709, 773, 876,
 898, 925, 929, 963, 1003, 1020, 1021
 \dtlsetUTFviiiicharcode
 275, 276, 1327
 \dtlsetUTFviiiilccharcode ...
 276, 1327, 1333, 1341
 \dtlshowdb 642, 1289
 \dtlshowdbkeys 642, 1289
 \DTLshowlinesfalse
 937, 945, 1206, 1207
 \DTLshowlinestrue 945, 1207
 \DTLshowmarkersfalse .. 945, 1207
 \DTLshowmarkerstrue
 937, 945, 1206, 1207
 \dtlshowtype 643, 1289
 \DTLshufflelist 47
 \DTLsicomp
 ... 815, 816, 817, 1112, 1113, 1126
 \DTLsort 585, 1273
 \dtlsort ... 585, 585, 590, 1144, 1273
 \DTLsortdata
 .. 394, 567, 569, 574, 576, 577, 667
 \dtlsortdatavalue 582, 583
 \DTLsortedactual 39
 \DTLsortedletter 39
 \DTLsortedvalue 39
 \DTLsortlettercasehandler .. 45
 \DTLsortletterhandler 44
 \dtlsortlist 45, 1295
 \DTLsortwordcasehandler 44
 \dtlSortWordCommands ... 31, 812
 \DTLsortwordhandler .. 44, 237, 572
 \DTLsortwordlist 32
 \dtlspecialvalue
 430, 591, 592, 709,
 736, 748, 749, 755, 759–762, 764, 765
 \dtlsplitrow 449, 450,
 476, 479, 504, 506, 1240, 1255, 1256
 \DTLsplitstring
 .. 220, 221, 1317, 1318, 1336–1338
 \DTLsqrt 203, 203, 1270, 1307
 \dtlsqrt 286, 293, 300, 307
 \DTLstartangle
 908, 913, 916, 917, 1197–1199
 \DTLstartpt 888, 1088, 1089, 1094, 1095
 \DTLstartsentencefalse
 790, 791, 1098, 1101
 \DTLstartsencespace
 789, 790, 793, 796–804,
 818–838, 1101–1108, 1113–1125
 \DTLstartsentencetrue . 790, 1101
 \DTLStoreInitialGetLetter ..
 216–219, 219
 \DTLstoreinitials 215,
 215, 795, 842, 843, 1104, 1128, 1313

`\dtlstringalign` [512](#), [513](#), [514](#), [521](#), [1259](#)
`\dtlstringformat`
... [516](#), [531](#), [532](#), [1259](#), [1260](#), [1263](#)
`\DTLstringnull` [66](#), [66](#), [67](#), [68](#), [336](#),
[438–440](#), [483](#), [531](#), [532](#), [1236](#), [1237](#)
`\DTLstringtype` [408](#), [1230](#), [1277](#)
`\DTLsub` [201](#), [201](#), [1268](#), [1269](#), [1305](#)
`\dtlsub` [201](#), [285](#),
[293](#), [300](#), [307](#), [1086](#), [1091](#), [1093](#),
[1200](#), [1201](#), [1203](#), [1210](#), [1211](#),
[1213–1215](#), [1220–1222](#), [1260](#),
[1261](#), [1305](#), [1310](#), [1311](#), [1359](#), [1361](#)
`\DTLsubstitute` [220](#), [1304](#), [1317](#)
`\DTLsubstituteall`
..... [221](#), [641](#), [644](#), [1224](#),
[1289](#), [1312](#), [1313](#), [1318](#), [1341](#), [1342](#)
`\DTLsumcolumn` [542](#), [1266](#)
`\DTLsumforkeys` [540](#), [1266](#)
`\dtlswapentriesincurrentrow`
..... [452](#), [1241](#)
`\dtlswaprows` [536](#), [1263](#)
`\DTLtcs` . [816](#), [816](#), [817](#), [1112](#), [1113](#), [1126](#)
`\DTLtemporalvalue` [111](#),
[113–115](#), [119–121](#), [132–134](#), [615](#), [619](#)
`\dtltexorsort` [31](#), [32](#), [187](#)
`DTLthebibliography (env.)` [811](#)
`\DTLtherow` [494](#)
`\DTLthesisitlefmt` [794](#), [832](#)
`\DTLthisval` [1266–1272](#)
`\DTLthisX` [562](#), [1272](#)
`\DTLthisY` [562](#), [1272](#)
`\DTLticklabeloffset`
..... [896](#), [935](#), [945](#), [981](#), [992](#),
[997](#), [1090](#), [1097](#), [1206](#), [1213](#), [1215](#)
`\DTLticklength` ... [895](#), [935](#), [981](#),
[991](#), [1089](#), [1096](#), [1206](#), [1213](#), [1214](#)
`\dtltimealign` [513](#), [514](#)
`\dtltimeformat` [517](#), [531](#)
`\dtltimegroup` [41](#), [43](#), [262](#)
`\DTLtocs` [815](#), [816](#), [817](#), [1112](#), [1113](#), [1126](#)
`\DTLtods` [815](#), [816](#), [817](#), [1112](#), [1113](#), [1126](#)
`\DTLtog` . [815](#), [816](#), [817](#), [1112](#), [1113](#), [1126](#)
`\DTLtoms` [815](#), [816](#), [817](#), [1112](#), [1113](#), [1126](#)
`\DTLtoois` [816](#), [816](#), [817](#), [1112](#), [1113](#), [1126](#)
`\DTLtoplas`
... [816](#), [816](#), [817](#), [1112](#), [1113](#), [1126](#)
`\DTLtotalbargroups` [851](#), [901](#)
`\DTLtotalbars` [851](#), [877](#), [881](#), [901](#)
`\DTLtrunc` [209](#), [209](#), [1311](#), [1312](#)
`\dtltrunc` [209](#),
[287](#), [294](#), [301](#), [308](#), [1311](#), [1359](#), [1362](#)
`\DTLtwoand` .. [791](#), [792](#), [797](#), [1101–1103](#)
`\dtltype` [509](#), [1258](#), [1260](#), [1263](#)
`\DTLundLocaleHook` [282](#)
`\dtlunknowntag` [746](#), [746](#)
`\DTLunsettype` [408](#), [1230](#), [1277](#)
`\dtlupdateentryincurrentrow`
..... [455](#), [455](#), [743](#), [1180](#), [1242](#)
`\DTLuse` [331](#), [1034](#), [1035](#)
`\DTLusedatum` [78](#)
`\DTLvarianceforall` . [205](#), [207](#), [1310](#)
`\dtlvarianceforall` [289](#), [296](#), [302](#), [311](#)
`\DTLvarianceforcolumn`
..... [550](#), [1269](#), [1270](#)
`\DTLvarianceforkeys` ... [548](#), [1268](#)
`\dtlverbosetru` [298](#)
`\DTLverticalbarsfalse`
..... [850](#), [868](#), [1082](#)
`\DTLverticalbarstrue`
..... [849](#), [850](#), [868](#), [1082](#)
`\dtlwordindexcompare`
..... [236](#), [1144](#), [1336](#)
`\DTLwrite` [605](#), [623](#), [654](#)
`\DTLxaxisfalse` [946](#), [1208](#)
`\DTLXAxisStyle`
..... [935](#), [946](#), [976](#), [1206](#), [1212](#)
`\DTLxaxistrue`
..... [935](#), [945](#), [951–954](#), [1206](#), [1207](#), [1209](#)
`\DTLxminorticsfalse`
..... [937](#), [947](#), [948](#), [1208](#)
`\DTLxminorticstrue` [947](#), [948](#)
`\DTLxparse` [87](#)
`\DTLxsetcurrencydatum` [91](#)
`\DTLxsetdecimaldatum` [91](#)
`\DTLxsetintegerdatum` [90](#)
`\DTLxsetstringdatum` [93](#)
`\DTLxsettemporaldatum` [92](#)
`\DTLxsplitstring` [221](#)
`\DTLxticsfalse` [946](#), [1208](#)
`\DTLxticsinfalse` ... [949](#), [950](#), [1208](#)
`\DTLxticsintrue`
..... [936](#), [949](#), [950](#), [1206](#), [1208](#)
`\DTLxticstrue`
..... [937](#), [945–948](#), [951–954](#), [1207–1209](#)
`\DTLyaxisfalse` [946](#), [1208](#)
`\DTLyAxisLabelStyle` [853](#), [897](#)
`\DTLYAxisStyle`
..... [936](#), [946](#), [977](#), [1206](#), [1213](#)

<code>\DTLyaxistru</code>	1170, 1177, 1183, 1184, 1187, 1188, 1194, 1203, 1220, 1282, 1283
<code>\DTLyminorticsfalse</code>	937, 948, 1208	
<code>\DTLyminorticstrue</code>	948
<code>\DTLyticsfalse</code>	946, 1208
<code>\DTLyticsinfalse</code>	... 949, 950, 1208	
<code>\DTLyticsintru</code>	
	936, 949, 950, 1206, 1208
<code>\DTLyticstrue</code>	937, 945, 946, 948, 952–954, 1207–1209
<code>\DTMdisplay</code>	15, 16, 20, 21
<code>\DTMdisplaydate</code>	11, 20
<code>\DTMdisplaytime</code>	12, 20
<code>\DTMdisplayzone</code>	13, 20
<code>\DTMnow</code>	609
<code>\DTMsavedate</code>	115
<code>\DTMsavenoparsedate</code>	117
<code>\DTMsavetime</code>	115, 116, 118
<code>\DTMsavetimestamp</code>	... 115, 117, 119	
E		
<code>\eappto</code>	1141, 1142, 1165, 1181, 1182, 1273	
<code>\edef</code>	31, 32, 269, 271, 272, 274, 292–297, 308, 309, 407, 409, 420, 486, 488, 494, 504–506, 509, 536–538, 540, 565, 643, 644, 846, 847, 1085–1099, 1108–1110, 1127, 1130, 1131, 1141–1143, 1153, 1169, 1178–1181, 1183–1188, 1192, 1193, 1195, 1200–1204, 1210, 1216–1218, 1220–1225, 1229–1234, 1236, 1238–1248, 1250, 1251, 1253–1256, 1258, 1260, 1261, 1263–1269, 1272–1278, 1282–1284, 1286–1288, 1292–1304, 1310–1318, 1322, 1324, 1325, 1334–1336, 1339–1342, 1346, 1347, 1349–1352, 1361–1366, 1369–1374
<code>\editionname</code>	
	... 782, 813, 818, 1098, 1112, 1113	
<code>\editorname</code>	... 781, 793, 1098, 1103	
<code>\editorsname</code>	... 781, 793, 1098, 1103	
<code>\edtlgetrowforvalue</code>	
	445, 445, 784, 1099, 1239
<code>\edtlinsertinto</code>	47, 1297
<code>\egroup</code>	.. 615, 625, 708, 710, 1137, 1144, 1145, 1148–1150, 1153, 1154, 1157, 1159–1165, 1169,	
<code>\else</code>	45, 46, 102, 103, 191, 224, 228, 229, 236, 240, 242–244, 247–250, 257, 259, 261, 269–273, 291, 292, 298, 301, 302, 308, 309, 407, 420, 421, 486, 489, 491–494, 501, 509, 510, 536, 538, 539, 594, 607, 612, 643, 772, 774, 780, 790, 847, 849, 850, 853–855, 863, 868–870, 885, 888, 890, 891, 893–897, 903, 906, 911, 1082, 1083, 1085–1097, 1100–1110, 1115, 1117, 1118, 1121, 1128–1130, 1138, 1140, 1142, 1146–1148, 1151, 1152, 1156, 1157, 1161, 1163, 1167, 1179–1181, 1185, 1187, 1192, 1193, 1197–1201, 1204, 1210–1218, 1222–1224, 1227, 1229, 1232, 1235–1237, 1239, 1242, 1245, 1247–1259, 1261–1263, 1265–1269, 1272, 1274–1277, 1284–1286, 1291–1293, 1295–1303, 1312–1317, 1319–1322, 1324–1327, 1333–1335, 1338, 1339, 1341, 1343–1352, 1355–1358, 1361, 1362, 1364–1366, 1368–1374	
<code>\em</code>	1105, 1106, 1108, 1113, 1116, 1120, 1122, 1123
<code>\emph</code>	662, 721, 722, 794, 838, 1125, 1140, 1176
<code>\empty</code>	301, 302, 1284
<code>\encodingdefault</code>	733, 1175
<code>\end</code>	269, 270, 519, 535, 665, 669–672, 678–681, 683, 685–688, 691, 693, 772, 782, 812, 817, 839, 848, 886, 891, 905, 924, 937, 974, 975, 1007, 1032, 1087, 1088, 1090, 1094, 1097, 1098, 1111, 1112, 1126, 1131, 1146, 1147, 1151, 1152, 1154–1157, 1159, 1161, 1192, 1203, 1216, 1218–1220, 1261, 1263, 1292, 1314–1316	
<code>\end@dtl@doifinlist</code>	1292
<code>\end@dtl@getfirst</code>	
	.. 274, 1323, 1326, 1334, 1346, 1347	
<code>\end@dtl@getfirst@UTFviii</code>	..	
	273, 1291, 1326, 1341

<code>\endcsname</code>	2, 260, 261, 269, 400, 407, 409, 486–491, 494, 497, 501, 502, 504–506, 509, 539, 613–615, 622, 642–644, 733, 846, 1082, 1083, 1087, 1093, 1098, 1100, 1108–1110, 1126, 1127, 1129–1131, 1138, 1172, 1175, 1176, 1182, 1183, 1187, 1195, 1197–1200, 1203, 1204, 1224–1235, 1238–1240, 1243–1258, 1260, 1261, 1264–1266, 1275, 1281–1284, 1286–1289, 1292, 1298, 1312, 1313, 1357, 1363–1374	305–312, 314–317, 322, 326–328, 335, 340, 347, 362, 363, 367–369, 371–373, 375, 376, 382, 388, 389, 393, 396–399, 424, 430–432, 435, 438, 449, 451, 452, 454–460, 462, 463, 465–467, 476, 478–480, 482–485, 487, 488, 497, 498, 502–504, 506, 513, 518, 519, 524–527, 529, 530, 533–536, 540, 542–544, 547, 549, 551–553, 556, 557, 559, 561, 563, 564, 568, 571, 575–579, 583, 584, 587, 588, 591, 592, 608–614, 616, 618, 619, 621, 622, 624, 626, 627, 630, 634, 637–639, 642, 663, 676, 682, 695, 699–701, 708, 709, 711, 722, 723, 735, 739, 743–745, 747, 749–752, 755, 759–762, 771, 772, 776, 781, 784–789, 792, 793, 795, 797, 799, 804–811, 817, 839, 842–844, 847, 848, 853–855, 862, 863, 877, 878, 880, 884, 886–897, 901–905, 910, 911, 920, 923, 924, 926, 927, 941, 956–958, 963–966, 969, 970, 974–980, 982–995, 997–1001, 1004–1007, 1014, 1015, 1022, 1023, 1032, 1033, 1042, 1043, 1046, 1048, 1049, 1053, 1068, 1072, 1073
<code>\endfirsthead</code>	534, 1262	
<code>\endfoot</code>	534, 1262	
<code>\endgroup</code> 31, 32, 270, 315, 1127, 1224, 1284, 1285, 1288, 1289, 1292, 1293	
<code>\endhead</code>	533, 534, 1262, 1263	
<code>\endinput</code>	613, 1280, 1282	
<code>\endlastfoot</code>	534, 1262	
<code>\endlinechar</code>	1284, 1285, 1289	
<code>\enspace</code>	646, 655, 714, 1133	
<code>\ensuremath</code>	721, 722, 1176	
environments:		
<code>DTLenvforeach</code>	495	
<code>DTLenvforeach*</code>	495	
<code>dtlenvgforint</code>	261	
<code>dtlenvgforint*</code>	261	
<code>DTLenvmapdata</code>	470	
<code>dtlgidxchildlist</code>	665	
<code>DTLthebibliography</code>	811	
<code>\epsilon</code>	731, 1173	
<code>\equal</code>	565, 1178, 1273, 1322, 1368	
<code>\eta</code>	731, 1173	
<code>\etalname</code>	781, 792, 797, 1098, 1102–1104	
<code>\EUR</code>	192	
<code>\Euro</code>	192	
<code>\euro</code>	192, 1304	
<code>\exp</code>	4, 7, 9, 10, 25, 28, 29, 32–34, 38–41, 45–48, 51, 52, 69–71, 73–79, 86, 87, 90–95, 97–101, 104–110, 112–121, 124–130, 132–134, 138, 143, 158, 159, 161–163, 165, 170, 172–176, 178, 184, 186–189, 191, 196, 198, 210–219, 221, 223–229, 234–237, 239–241, 243–246, 248, 249, 264, 275, 285, 286, 288–290,	2, 31, 32, 260, 261, 271–274, 308, 309, 317, 400, 407, 409, 428, 486–491, 494, 501, 502, 504, 505, 507, 509, 537–540, 565, 613–615, 622, 641–645, 667, 708, 733, 775, 780, 846, 847, 929, 1082, 1083, 1085, 1087–1091, 1093–1097, 1100–1110, 1115, 1117, 1118, 1121, 1126–1131, 1137, 1138, 1141, 1142, 1164, 1165, 1169, 1172, 1173, 1175, 1176, 1182, 1183, 1186, 1187, 1195, 1197–1199, 1203, 1204, 1210, 1212, 1213, 1216–1218, 1221–1227, 1229–1235, 1238–1258, 1260–1268, 1270–1276, 1278–1284, 1286–1289, 1291, 1292, 1294–1301, 1303–1305, 1308–1320, 1322, 1323, 1326, 1327, 1333, 1334,

1336–1338, 1340, 1341,
 1346, 1347, 1350–1352,
 1357, 1361–1366, 1369–1374
 \expandonce . 435, 711, 1170, 1172,
 1177, 1187, 1193, 1195, 1235,
 1240, 1241, 1293, 1324, 1325,
 1334–1336, 1339–1342, 1346–1348
 \ExplSyntaxOff 22, 30, 31, 47–49,
 54, 191, 250, 268, 270, 273–275,
 282, 283, 290, 313, 314, 318, 406,
 415, 485, 488, 491, 494, 501, 508,
 512, 539, 564, 607, 623, 640, 642,
 659, 730, 732, 777, 779, 790, 793,
 804, 814, 846, 848, 850, 851, 906,
 907, 929, 1036, 1037, 1071, 1081
 \ExplSyntaxOn 2,
 24, 31, 32, 47, 49, 54, 192, 261,
 270, 272, 274, 275, 282, 284, 305,
 314, 315, 318, 409, 415, 487, 490,
 494, 495, 501, 510, 513, 539, 566,
 607, 624, 641, 645, 659, 730, 733,
 778, 779, 791, 794, 805, 817, 847,
 850, 851, 907, 929, 1036, 1037, 1071

F
 \faBtc 192
 \faEur 192, 193
 \fboxrule 936, 1206
 \fcolorbox 936, 1206
 \femalechild 1065, 1367
 \femalechildren .. 1066, 1367, 1372
 \femalelabels 1041, 1363, 1364
 \femalename 1067, 1367, 1374
 \femaleobjpronoun 1064, 1367
 \femaleparent 1066, 1367
 \femalepossadj 1064, 1367
 \femaleposspronoun 1065, 1367
 \femalepronoun 1063, 1367
 \femalesibling 1066, 1367
 \femalesiblings .. 1067, 1367, 1374
 \fi 23, 29, 45–47, 102, 103, 191, 224,
 228–230, 236, 240, 242, 244, 247,
 248, 250, 257, 260, 261, 269–273,
 275, 291, 292, 298, 299, 301, 302,
 308, 309, 407, 420, 421, 487, 490,
 492–494, 501, 510, 536, 538, 539,
 588, 594, 608, 612, 627, 644, 667,
 674, 688, 692, 695, 772, 774, 775,
 780, 790, 791, 812, 813, 846, 847,
 849, 850, 853–855, 863, 868–871,
 884, 885, 889–891, 893–897,
 903, 904, 906, 911, 1082–1097,
 1099–1111, 1115, 1117, 1118,
 1121, 1127–1133, 1135–1138,
 1140, 1142, 1146–1163, 1167,
 1169, 1179–1182, 1186, 1187,
 1192, 1193, 1197, 1198,
 1200–1204, 1207, 1208,
 1210–1218, 1220, 1222–1224,
 1227, 1229, 1232, 1235–1239,
 1242–1259, 1261–1269,
 1272, 1273, 1275–1278,
 1285–1287, 1290–1303,
 1312–1317, 1319–1322,
 1324–1327, 1333–1336,
 1339–1341, 1343–1352,
 1355–1359, 1361, 1362, 1364–1374
 \field 735, 1176
 \file 606, 627, 640
 \fill 919, 1087, 1094, 1200
 \FirstId 725, 1171
 \fmtversion 1175
 \forallpeople 1060, 1061
 \forcsvlist 1165
 \foreachperson ... 1060, 1060, 1366
 \foreachpersonbreak 1060, 1060, 1061
 \ForEachTrackedDialect
 267, 268, 849, 1081
 \foralllistloop 239
 \fp 27, 62, 72, 77, 90, 94, 96, 98, 112,
 116, 118, 119, 121, 122, 134–136,
 138, 140, 147, 148, 205–208, 231,
 284–290, 309, 319, 374, 376–382,
 384–387, 540, 542–556, 558–563,
 851–853, 856, 861, 862, 876,
 877, 879, 881–889, 891–893, 895,
 899, 901–905, 915–923, 927, 928,
 930–932, 940, 956–958, 960, 961,
 963–969, 971, 975–1002, 1006,
 1008–1015, 1017–1020, 1023–1031
 \FPabs 302, 1360
 \FPadd 300, 302–304, 1359
 \FPclip 301, 1359
 \FPdiv 300, 302–304, 1359
 \FPifeq 298, 1358
 \FPifgt 298, 1358
 \FPiflt 298, 1358
 \FPmax 301, 302, 1360
 \FPmessagesfalse 1358
 \FPmessagestrue 1357

<code>\FPmin</code>	301, 1360	<code>\Glslink</code>	766
<code>\FPmul</code>	300, 303, 304, 1359	<code>\glslink</code>	766, 1188
<code>\FPneg</code>	302, 1360	<code>\Glsnl</code>	770, 1190
<code>\FProot</code>	301, 304, 1359	<code>\glsnl</code>	769, 770, 1189
<code>\FPround</code>	301, 1359	<code>\Gspl</code>	769, 1189
<code>\FPsub</code>	300, 303, 304, 1359	<code>\gspl</code>	769, 769, 1189
<code>\FPtrunc</code>	301, 1359	<code>\Gsplnl</code>	770, 1190
G			
<code>\g</code>	494, 591, 606, 607, 627, 628, 652, 724, 725, 727, 735, 737, 750, 752, 755, 756, 764, 766, 776, 839, 840, 842, 1040–1043, 1047, 1050, 1052, 1053	<code>\glsreset</code>	748, 749, 1181, 1182
<code>\G@refundefinedtrue</code>	846, 847, 1130	<code>\glsresetall</code>	749, 1181
<code>\Gamma</code>	732, 1174	<code>\Glsym</code>	770, 1190
<code>\gamma</code>	731, 1173	<code>\glsym</code>	770, 770, 1190
<code>\gappto</code>	31, 1172, 1183	<code>\glsunset</code>	749, 750, 1181, 1182
<code>\gdef</code>	31, 260, 314, 315, 486, 488, 489, 615, 652, 1126, 1137, 1172, 1194, 1224, 1244–1246, 1249, 1252, 1253, 1259, 1261, 1282, 1283, 1285, 1288, 1289, 1357, 1363, 1365	<code>\glsunsetall</code>	750, 1182
<code>\gDTLforeachbibentry</code>	786, 1099	<code>\group</code>	32–34, 47, 48, 69, 70, 114, 115, 118, 187, 215, 237–239, 370–372, 430, 524, 535, 540, 542–544, 546–548, 550–554, 556, 557, 559, 561, 563, 575, 577, 586, 587, 606, 627, 641, 642, 654, 663, 664, 667, 668, 673, 675–677, 682–684, 689–691, 693, 695–699, 707, 709, 711, 721–723, 739, 752, 763, 765–769, 772, 775, 781, 840, 842, 843, 875, 877, 878, 880, 898, 899, 901, 925–927, 1015, 1017, 1019, 1023
<code>\gDTLformatbibentry</code>	783, 1098	H	
<code>\getpersonforenames</code>	1080	<code>\hangindent</code>	667, 681, 689, 690, 692, 1144, 1153, 1158–1160
<code>\getpersonfullname</code>	1080, 1374	<code>\hbox</code>	24, 846, 1130
<code>\getpersongender</code>	1079, 1374	<code>\hfil</code>	1259
<code>\getpersongenderlabel</code>	1079	<code>\hfill</code>	656, 714, 1133
<code>\getpersonname</code>	1080, 1374	<code>\HierSort</code>	725, 739
<code>\getpersonsurname</code>	1080	<code>\href</code>	805, 806
<code>\getpersontitle</code>	1081	<code>\hspace</code>	675, 676, 697, 1149, 1150, 1164
<code>\global</code>	50, 260, 261, 269, 272, 486, 487, 489, 490, 505, 510, 565, 613, 614, 622, 627, 1098–1101, 1127, 1128, 1137, 1177–1179, 1183, 1195, 1196, 1226–1228, 1232, 1236–1238, 1244–1246, 1249–1253, 1255, 1257, 1258, 1260, 1263, 1264, 1266, 1273, 1275, 1281–1284, 1289, 1292, 1295, 1297, 1298, 1305–1312, 1356, 1357, 1364, 1365	<code>\hyperlink</code>	25, 668, 1145
<code>\Gls</code>	769, 1189	<code>\hypertarget</code>	25, 667, 668, 752, 765, 1145, 1183, 1188
<code>\gls</code>	769, 769, 1189	I	
<code>\glsadd</code>	721, 722, 751, 763, 1145, 1176, 1184, 1187	<code>\IeC</code>	733, 1175
<code>\glsaddall</code>	765, 1188	<code>\if</code>	224, 1300
<code>\Glsdispenry</code>	753, 770, 1184, 1190	<code>\if@datagidx@warn</code>	652, 1137
<code>\glsdispenry</code>	753, 753, 770, 1184, 1190	<code>\if@datagidxsymbolleft</code>	648, 1135, 1146, 1147, 1151, 1155, 1156
		<code>\if@dtl@condition</code>	221, 240, 242–244, 247, 249–259, 807–811,

1108–1110, 1286, 1287, 1314,
 1315, 1318, 1343–1346, 1349–1356
 \if@dtl@insertdone 46,
 47, 271, 272, 1274, 1275, 1294–1297
 \if@dtl@numgrpsep 1319, 1320
 \if@dtl@sequential 699, 1165–1167
 \if@dtl@utf8 2
 \if@endfor
 . 1100, 1142, 1293, 1294, 1365, 1366
 \if@endpe 667, 775
 \if@filesw
 780, 813, 845, 1097, 1111, 1130, 1131
 \if@tempswa 1161
 \if@twocolumn 772, 1192
 \ifallfemale . 1058, 1366, 1372, 1374
 \ifallmale ... 1057, 1365, 1372, 1374
 \ifblank 498, 1250, 1253
 \IfBlankTF 265
 \ifbool 272–275, 1291, 1326
 \IfBooleanT 470
 \IfBooleanTF . 239–243, 246–249,
 265, 403–405, 418, 431, 461,
 484, 490, 491, 524, 785, 786, 1043
 \ifboolexpr ... 276–281, 1327–1332
 \ifcase 228, 420, 812, 1083,
 1111, 1132–1135, 1138, 1169,
 1191, 1207, 1208, 1218, 1232,
 1259, 1260, 1263, 1322, 1338, 1357
 \ifcat 1313, 1327, 1333
 \ifcsdef . 192, 433, 654, 1137, 1147,
 1164, 1178, 1180, 1184, 1194, 1195
 \ifcsemtyp 1178
 \ifcsundef 642, 643, 1185–1187
 \ifdatagidxbalance
 706, 774, 1169, 1193
 \ifdatagidxshowgroups
 674, 688, 692, 695,
 706, 1148, 1157, 1160, 1162, 1169
 \ifdef 2, 48,
 652, 733, 805, 1136, 1144, 1145,
 1162, 1174, 1183, 1284, 1290, 1297
 \ifdefempty 220, 272, 420, 641, 1135,
 1136, 1140–1142, 1149, 1153,
 1158, 1160–1162, 1164–1167,
 1170, 1177, 1181, 1182, 1187,
 1192, 1232, 1237, 1270–1274,
 1276, 1278, 1279, 1285–1287,
 1289–1291, 1293–1296, 1298,
 1299, 1301, 1304–1314,
 1317–1320, 1323, 1325, 1326,
 1333, 1335–1338, 1340, 1346, 1347
 \ifdefequal 1149, 1153, 1158, 1160,
 1163, 1165, 1166, 1196, 1236, 1306
 \ifdim 1086,
 1087, 1092–1094, 1099, 1127,
 1148, 1150–1152, 1154, 1155,
 1157, 1159, 1160, 1200, 1212, 1222
 \ifdtlautokeys 594, 1286
 \ifDTLbarxaxis
 858, 894, 1082, 1089, 1096
 \ifDTLbaryaxis
 858, 894, 1082, 1089, 1096
 \ifDTLbarytics
 858, 883, 1082, 1086, 1091
 \ifDTLbox 937, 1212, 1214–1216
 \ifDTLcolorbarchart
 849, 863, 1081, 1083
 \ifDTLcolorpiechart
 906, 911, 1196, 1198
 \ifdtlcompareskipcs
 22, 236, 1323, 1334
 \ifDTLgrid 937, 1213
 \ifDTLlistskipempty
 21, 29, 1292, 1293, 1298
 \ifDTLmidsentence .. 790, 1101,
 1105–1108, 1115, 1117, 1118, 1121
 \ifDTLnewdbonload .. 594, 594, 1285
 \ifdtlnoheader
 594, 607, 612, 627, 1285, 1286
 \ifDTLperiod ... 789, 790, 1100, 1101
 \ifDTLrotateinner 906, 1200
 \ifDTLrotateouter 906, 1201
 \ifDTLshowlines ... 937, 1206, 1217
 \ifDTLshowmarkers . 937, 1206, 1216
 \ifDTLstartsentence 790, 791, 1101
 \ifdtlverbose
 . 2, 23, 588, 1277, 1278, 1290, 1358
 \ifDTLverticalbars 849,
 849, 850, 853–855, 868–870, 884,
 888, 890–892, 894–897, 902, 903,
 905, 1082, 1086–1090, 1092–1097
 \ifDTLxaxis 935, 1206, 1212
 \ifDTLxminortics
 937, 1208, 1211, 1213, 1214
 \ifDTLxtics 937, 1210, 1213
 \ifDTLxticsin . 936, 1206, 1213, 1214
 \ifDTLxticstrue 937
 \ifDTLyaxis 935, 1206, 1213

<code>\ifDTLymainortics</code>	<code>\iftermexists</code>
..... 937, 1208, 1212, 1213, 1215 652, 737, 741, 745, 753,
<code>\ifDTLytics</code>	758, 760, 763, 777, 1178–1180, 1196
..... 937, 1211, 1214	<code>\ifthenelse</code> .. 498, 541, 544, 549,
<code>\ifDTLyticsin</code> . 936, 1206, 1215, 1216	552, 554, 558, 561, 565, 719, 785,
<code>\ifDTLyticstrue</code>	787, 875, 898, 925, 962, 1015,
..... 937	1085, 1091, 1099, 1100, 1178,
<code>\ifentryused</code>	1217, 1250, 1253, 1266–1268,
..... 748, 770, 771, 777, 1180, 1190, 1196	1270, 1271, 1273, 1322, 1368
<code>\ifeof</code>	<code>\IfTrackedIsoCode</code>
..... 1285–1287 267
<code>\iffemale</code>	<code>\ifundef</code> .. 707, 1085, 1169, 1177, 1290
..... 1057, 1365	<code>\IfValueT</code> . 320, 524, 535, 541, 545,
<code>\iffemalelabel</code>	554, 558, 574, 586, 606, 627, 707,
..... 1042, 1363	709, 772, 864, 875, 898, 925, 1015
<code>\IfFileExists</code>	<code>\IfValueTF</code> 541, 544, 549, 551, 554,
..... 707, 778, 1169, 1283, 1285	558, 561, 727, 785, 861, 962, 1061
<code>\ifFPmessages</code>	<code>\ifx</code>
..... 297, 1358 269, 270, 273, 299,
<code>\ifmale</code>	301, 302, 308, 421, 486, 492, 501,
..... 1056, 1365, 1374	509, 538, 643, 779, 847, 1085,
<code>\ifmalelabel</code>	1086, 1089–1092, 1096, 1097,
..... 1042, 1363	1101, 1103, 1104, 1128–1130,
<code>\ifmmode</code>	1140, 1179, 1180, 1185, 1187,
..... 191	1199, 1210–1218, 1222–1224,
<code>\ifnewtermfield</code>	1232, 1235–1239, 1241–1244,
..... 741, 1178	1247, 1250, 1253–1256,
<code>\IfNoValueTF</code>	1258, 1262, 1265, 1272,
..... 289, 290, 296,	1275–1277, 1284, 1286, 1287,
297, 302, 303, 311, 312, 1057–1059	1292, 1299–1303, 1312–1316,
<code>\ifnum</code> 45, 46, 102, 103, 228, 229, 259,	1319–1321, 1326, 1327, 1333,
260, 271, 272, 275, 291, 292, 308,	1341, 1343, 1349–1351,
406, 407, 420, 489, 491, 493, 494,	1358, 1359, 1362, 1364–1367
509, 536, 538, 539, 1082, 1083,	<code>\ignorespaces</code>
1101–1104, 1109, 1110, 1127, 813, 1111
1128, 1138, 1141, 1163, 1181,	<code>\immediate</code>
1182, 1188, 1193, 1197, 1198,
1200, 1204, 1217, 1227, 1229,	.. 780, 813, 1097, 1111, 1129–1131
1232, 1237, 1245, 1247–1249,	<code>\in</code>
1252, 1254–1259, 1263, 1265, 399–401, 443, 486,
1267–1269, 1273, 1274, 1276,	488, 509, 608, 610–612, 615, 616,
1277, 1285, 1291, 1293,	1060, 1226, 1227, 1238, 1244,
1295, 1296, 1299, 1302, 1303,	1245, 1253, 1258, 1260–1263,
1315, 1317, 1319–1322, 1324,	1274, 1278, 1280, 1282, 1283, 1366
1325, 1333–1335, 1338–1341,	<code>\indexspace</code>
1343–1345, 1347–1352, 1356,
1357, 1361, 1362, 1368–1374	... 674, 688, 692, 1148, 1157, 1160
<code>\ifnumequal</code>	<code>\inname</code>
..... 1166, 1167
<code>\ifnumgreater</code>	781, 794, 800–804, 1098, 1106–1108
..... 1168	<code>\input</code>
<code>\ifodd</code> 1169, 1283
..... 1249, 1253	<code>\inputencodingname</code>
<code>\IfPackageLoadedTF</code> 2
..... 8,	<code>\InputIfFileExists</code>
318, 659, 779, 850, 907, 929, 1037 22, 23, 54
<code>\ifpersonexists</code>	<code>\int</code>
..... 4, 5, 12, 25–28,
..... 1053, 1364–1366, 1374	35–38, 40, 56, 61–65, 72, 75, 79,
<code>\ifstrempty</code>	81, 83, 86–89, 96, 97, 112–114,
..... 420, 643,	116–122, 124, 134–139, 147, 148,
1172, 1183, 1187, 1203, 1224,	
1232, 1233, 1236, 1259, 1327, 1333	
<code>\ifstrequal</code> 276–281, 1186, 1327–1332	
<code>\IfSubStringInString</code>	
.....	
..... 1278, 1279, 1315, 1316	

158, 159, 161, 162, 164, 165, 170,
172–175, 177, 184, 194–208, 221,
222, 226–229, 231, 234, 288–290,
310–312, 314, 319–324, 327, 329,
335–338, 340, 342–344, 346–349,
352–355, 357, 360–373, 376–380,
383, 384, 386–389, 391–393, 399,
401–403, 411–414, 417, 419–433,
440, 444–447, 449, 451–456, 461,
466–472, 474–479, 481, 483, 485,
491, 494, 496, 497, 499–507,
510–515, 517, 518, 525–530,
536, 538, 540–553, 568, 572–576,
578–584, 586, 588, 589, 596,
597, 599, 600, 604, 607–611, 621,
626–629, 631, 633–636, 638, 645,
646, 661, 663, 665, 676, 695–697,
699, 700, 703–705, 710, 738,
748, 750–752, 755, 765, 771,
774, 776, 785, 786, 791–793,
796, 797, 808–811, 817, 841–844,
848, 857–863, 865, 866, 875,
885, 886, 896, 901, 905, 910,
915–918, 920, 924, 928, 929,
939, 940, 942, 943, 946, 950,
955–958, 974, 975, 984, 985,
989, 990, 995, 996, 1000–1003,
1005, 1007, 1008, 1016,
1018, 1019, 1022, 1023, 1027,
1028, 1032, 1033, 1038–1040,
1046–1053, 1056–1059, 1068
\ior 591, 604, 627, 628
\iota 731, 1173
\iow ... 591, 606, 607, 613–619, 845, 847
\item 667, 673–675,
682, 683, 688, 692, 1145,
1148, 1149, 1153, 1154, 1158, 1160

J

\jobname 655, 779, 1097, 1138

K

\kappa 731, 1173
\keys 6–8, 17, 22, 265, 266, 318, 320,
322, 324, 370, 371, 390, 392, 466,
467, 474, 479, 482, 520, 524, 535,
566, 569, 572, 575, 599, 605, 606,
627, 655, 659, 707–709, 711, 719,
723, 725, 734, 772, 774, 778, 779,
850, 865, 875, 876, 878, 898, 900,
907, 911, 914, 925, 927, 943, 959,
1015, 1020, 1037, 1038, 1044, 1045
\keyval 321, 334, 361, 437, 484, 568, 586

L

\L 732, 1174
\l 3–11, 17–22,
24, 25, 28–30, 32–41, 44–49,
51–55, 57–63, 70, 75, 77, 86, 87,
90, 93–104, 108, 109, 112–131,
135–149, 157–188, 192–224, 228,
229, 233–241, 243–249, 261–264,
266–268, 282, 283, 285–290,
309–312, 314–349, 351–395, 399,
400, 403, 411–416, 419, 421–427,
429, 430, 432–434, 442, 444,
446, 447, 449, 451, 452, 454–456,
459, 460, 463–485, 487, 488, 513,
515, 517–521, 523–536, 540–564,
566–571, 575–579, 581–590,
592–613, 615, 616, 624, 626–640,
645, 646, 648–653, 658–661, 663,
664, 666–672, 675–679, 682–686,
689–691, 695, 697, 699–706, 708,
709, 711, 712, 717–724, 726, 727,
732, 734–744, 746–769, 771–775,
778–780, 784, 789, 791–793,
796, 797, 811, 817, 839–845,
851–906, 908–910, 912–924,
926–933, 937–946, 950–1024,
1026–1036, 1038–1040,
1043–1053, 1056–1061,
1068–1073, 1079–1081, 1174
\Label 660, 661, 665, 675,
676, 681, 683, 689, 690, 693, 696,
708, 725, 776, 1132, 1141–1143,
1149, 1153, 1154, 1158, 1159,
1161, 1163, 1169–1171, 1195
\label 25, 533, 1262
\Lambda 732, 1174
\lambda 731, 1174
\LaTeX 32
\lccode 275, 1317, 1327
\leavevmode 846, 1130
\legacy 631–633, 674, 746, 776, 783,
789, 798–804, 806, 807, 920, 921,
968, 969, 971, 972, 975–977, 979,
981, 982, 984, 985, 987, 989–992,
995, 996, 998–1001, 1003, 1004, 1019

<code>\let</code>	31, 32, 193, 221, 250, 254, 256–261, 269, 271, 272, 299, 301, 302, 306–310, 400, 420, 486, 487, 489, 490, 492, 493, 509, 510, 538, 565, 623, 624, 627, 640, 655, 665, 667, 704, 712, 713, 733, 735, 775, 812, 818, 838, 846, 1084–1087, 1090, 1091, 1093, 1094, 1096, 1099, 1101, 1108–1110, 1113, 1125, 1127–1130, 1132, 1137, 1139, 1140, 1142–1149, 1151, 1152, 1155–1157, 1162, 1163, 1165–1167, 1174–1179, 1181–1184, 1192–1196, 1199–1204, 1209–1213, 1215–1217, 1220, 1222, 1226, 1227, 1229, 1232, 1236–1238, 1244–1247, 1249–1258, 1260, 1263, 1265, 1270–1277, 1284, 1285, 1287–1289, 1292, 1294–1297, 1299–1321, 1323, 1324, 1334, 1337–1343, 1346, 1347, 1349–1352, 1354, 1356–1358, 1361–1367, 1374	<code>\makeatletter</code> 31, 613, 624, 1281, 1282
<code>\letcs</code> 1099, 1100, 1180, 1181, 1184–1187		<code>\makebox</code> . . 674, 681, 683, 688–690, 692, 1148, 1153, 1154, 1158–1160
<code>\linewidth</code> 669–671, 674, 677, 682, 685, 688, 690, 692, 695, 1145–1148, 1150, 1153, 1155, 1158–1160, 1162	<code>\makefirstuc</code> 766
<code>\loadgidx</code>	707, 1169, 1170	<code>\MakeLowercase</code> . 721, 722, 1176, 1316
<code>\Location</code>	664, 665, 676, 693, 697–699, 725, 777, 1141, 1143, 1150, 1153, 1155, 1158, 1160, 1161, 1164, 1165, 1171, 1195, 1196	<code>\MakeTextLowercase</code> 721, 722, 1132, 1176, 1316
<code>\Long</code>	666, 725, 1144, 1171	<code>\MakeTextUppercase</code> 721, 722, 1132, 1176, 1180, 1189, 1315
<code>\long</code>	259, 260, 269, 270, 486–489, 643, 644, 1224, 1225, 1244, 1245, 1292, 1318, 1356, 1366	<code>\MakeUppercase</code> 721, 722, 1105–1108, 1115, 1117, 1118, 1121, 1176, 1315, 1369–1374
<code>\long@addto@envbody</code> 269, 270, 1292		<code>\malechild</code> 1065, 1367
<code>\long@collect@@body</code> 269, 270, 1292		<code>\malechildren</code> 1066, 1367, 1372
<code>\long@collect@body</code> 269, 1248, 1292, 1357	<code>\malelabels</code> 1040, 1363
<code>\long@push@begins</code> . . 270, 270, 1292		<code>\malename</code> 1067, 1366, 1367, 1374
<code>\LongPlural</code>	725, 1171	<code>\maleobjpronoun</code> 1064, 1367
<code>\loop</code>	1188, 1285–1287	<code>\maleparent</code> 1066, 1367
<code>\lowercase</code>	1316	<code>\malepossadj</code> 1064, 1367
		<code>\maleposspronoun</code> 1064, 1367
		<code>\malepronoun</code> 1063, 1367
		<code>\malesibling</code> 1066, 1367
		<code>\malesiblings</code> 1067, 1367, 1374
		<code>\mbox</code> 693, 1161
		<code>\MessageBreak</code> 709, 773
		<code>\MFUaddmap</code> . . . 753, 766, 767, 769–771
		<code>\MFUexcl</code> . . 749, 750, 765, 766, 768, 769
		<code>\mscthesisname</code> 782, 1098
		<code>\msg</code> 79–86
		<code>\mu</code> 731, 1174
		<code>\multicolumn</code> 516
		<code>\multiply</code> 1149, 1150, 1153, 1164, 1276, 1277, 1300, 1302, 1322
		N
		<code>\Name</code> 666, 673–677, 681–684, 689–691, 693, 696, 697, 724, 1144, 1148–1150, 1153–1155, 1158–1161, 1163, 1171
		<code>\NeedsTeXFormat</code> 1, 282, 283, 291, 297, 304, 313, 645, 777, 849, 906, 929, 1036, 1081, 1097, 1131, 1196, 1204, 1223, 1290, 1357, 1360, 1363
		<code>\newacro</code> 744, 754, 764, 1180
		<code>\newcommand</code> . . 2, 8, 11–15, 17, 21, 23, 25–27, 29–31, 39–45, 47–49, 63, 64, 66, 78, 79, 106, 112, 144, 145, 147, 149, 150, 185, 186, 190–193, 202, 210, 219, 225, 233,
		M
<code>\m@ne</code>	1285	
<code>\macro</code>	238	

234, 237–259, 261–263, 268–272,
 274–276, 279, 282, 284, 291, 292,
 308, 314, 315, 317, 330, 331,
 400–409, 417–419, 428, 431–433,
 435, 437, 439, 441–443, 447, 453,
 457, 461, 462, 481, 489–492, 494,
 500, 501, 505, 507–513, 515–518,
 532, 538–540, 565, 582, 585,
 591, 594, 607, 620–625, 640–644,
 646–648, 650–655, 658, 661, 662,
 664–669, 672, 694, 697, 701, 702,
 704–707, 711, 724, 725, 728–733,
 741, 745, 746, 751, 755, 757, 758,
 760, 763, 770–772, 775, 777, 781,
 784, 787, 788, 790–794, 804–817,
 838–840, 845, 846, 848–850, 853,
 855, 857, 858, 860, 861, 863, 864,
 908–911, 933–936, 938, 962, 963,
 1031, 1034, 1036–1039, 1053,
 1060, 1063, 1067, 1068, 1071,
 1081–1084, 1090, 1097–1112,
 1125–1138, 1140–1148,
 1150, 1155, 1159, 1162,
 1164–1175, 1177–1188, 1190,
 1192, 1194–1199, 1203–1207,
 1209, 1220–1231, 1233–1249,
 1252–1259, 1261, 1263–1275,
 1277–1280, 1282–1285,
 1288–1295, 1297–1301,
 1303–1315, 1317–1323, 1326,
 1327, 1330, 1333, 1336, 1340–1374
 \newcount 23, 47, 61, 260, 270, 404,
 493, 494, 543, 598, 614, 622, 777,
 1082, 1101, 1182, 1188, 1196,
 1204, 1206, 1225, 1226, 1228,
 1248, 1267, 1281, 1283, 1284,
 1290, 1297, 1298, 1318, 1326, 1356
 \newcounter
 .. 493, 660, 787, 791, 793, 857,
 908, 935, 1038, 1082, 1100–1102,
 1127, 1132, 1197, 1206, 1248, 1363
 \NewDocumentCommand 32,
 47, 54, 57, 86, 87, 90–93, 104,
 106, 110, 111, 115, 186, 187,
 200–210, 215, 225–227, 231,
 239–243, 246–249, 265, 285–290,
 292–296, 300–303, 305–312, 314,
 315, 320, 330, 398–405, 418, 431,
 433–436, 444–446, 449, 451–453,
 455, 456, 458, 461, 467, 470, 476,
 479–481, 484, 490, 491, 493, 494,
 513, 515, 518, 519, 524, 532,
 533, 535, 540, 542, 544, 546,
 548, 550, 551, 553, 554, 556,
 557, 559, 561, 564, 574, 586, 605,
 627, 640, 641, 645, 650, 662–664,
 668, 672, 676, 698, 707–709, 726,
 741, 742, 744, 748–750, 753, 763,
 765–769, 772, 776, 779–786, 788,
 789, 791, 794–804, 806, 813,
 844, 845, 847, 859, 861, 862,
 864, 875, 898, 910, 925, 961,
 1015, 1033–1035, 1040–1043,
 1051, 1052, 1056–1059, 1061,
 1062, 1069–1071, 1073–1081
 \NewDocumentEnvironment
 261, 470, 495, 811
 \newenvironment 665, 1110, 1248, 1357
 \newgidx
 . 654, 707, 709, 740, 742, 1137, 1169
 \newif 2, 22, 47, 221, 594, 706,
 789, 790, 849, 858, 906, 935–937,
 1081, 1082, 1100, 1101, 1135,
 1137, 1165, 1169, 1196, 1206,
 1285, 1292, 1297, 1318, 1320, 1323
 \newlength 23, 662,
 683, 684, 855, 856, 863, 907, 911,
 934–936, 1082, 1083, 1099, 1135,
 1154, 1155, 1197, 1198, 1206, 1290
 \newperson 1043, 1363
 \newread 1284
 \newrobustcmd 30, 46,
 49, 104, 220, 221, 225–228, 230,
 231, 238, 244, 245, 298, 299, 319,
 332, 406, 408, 417, 428, 441, 445,
 448, 449, 461, 495, 501, 503, 536,
 664, 769–771, 1108, 1292, 1293, 1297
 \newterm 654, 734,
 734, 744, 754, 764, 1137, 1175, 1180
 \newterm@database 720,
 1171, 1172, 1175, 1177–1181,
 1184–1188, 1190, 1192, 1194
 \newterm@defaultshook
 724, 1171, 1172, 1176
 \newterm@description
 720, 1171, 1175, 1177
 \newterm@extrafields
 724, 1171, 1172, 1177
 \newterm@label 720, 1170, 1175–1179
 \newterm@long . 720, 1171, 1176, 1177

559–561, 563, 564, 572, 575, 577,
581, 586, 587, 590, 593, 595, 596,
600, 604, 606, 613, 624–627, 642,
643, 645, 650, 651, 672, 709, 728,
735, 738, 740–743, 745–747, 754,
764, 766, 773, 775, 779, 782, 845,
846, 856, 858, 865, 876, 881,
898, 899, 909, 925, 928, 950,
955–958, 965–967, 1015, 1016,
1043–1045, 1047, 1053–1055,
1060, 1083, 1085, 1090, 1098,
1129–1131, 1147, 1178, 1179,
1184, 1185, 1187, 1188, 1194,
1197–1199, 1204, 1210, 1220,
1225–1231, 1233–1236, 1238,
1239, 1242–1244, 1246, 1247,
1249, 1252–1259, 1265–1269,
1271–1274, 1277, 1279, 1280,
1282–1284, 1288, 1356, 1363–1374
\PackageInfo 7, 54, 642
\PackageWarning 7, 9, 10, 104, 117,
118, 198, 206, 208, 270, 304, 313,
334, 351–353, 361, 371, 374, 382,
383, 450, 475, 514, 524, 526, 528,
529, 535, 572, 586, 590, 594, 600,
624, 627, 664, 698, 702, 733, 751,
759, 763, 778, 846, 847, 874, 910,
914, 942, 959, 962, 1039, 1063,
1068, 1072, 1073, 1164, 1166,
1186, 1207, 1274, 1285, 1286, 1293
\PackageWarningNoLine . 653, 1137
\pagename . . . 782, 797, 799, 1098, 1105
\pageref 25
\pagesname . . 782, 797, 799, 1098, 1105
\par 319, 630, 667, 669, 682,
683, 691, 771, 1144, 1153, 1154,
1158, 1159, 1161, 1162, 1192, 1225
\Parent 665, 677, 682, 684,
689, 691, 725, 776, 1143, 1150,
1153–1155, 1158, 1160, 1171, 1195
\Parents 1037
\parents 1037
\parindent 667, 673,
675–677, 681, 682, 684, 689–692,
695, 697, 1145, 1148–1150,
1153, 1155, 1158–1160, 1162, 1164
\parse@wordnext 1343
\parshape 682, 695, 1153, 1162
\parskip 667, 673, 675–684,
686–689, 691, 693, 695, 697,
1145, 1148–1159, 1161, 1162, 1164
\PassOptionsToPackage
. 318, 659, 779, 850, 907, 929, 1037
\path 889
\pdfstrcmp 234
\penalty 846, 1130
people (counter) 1038
\Peoplechild 1037, 1078, 1372
\peoplechild 1037, 1078, 1372
\peopleforenames 1069
\peoplefullname 1069, 1368
\peoplename 1070, 1368
\Peopleobjpronoun 1036, 1074, 1370
\peopleobjpronoun 1036, 1074, 1370
\Peopleobjpronounii . . . 1036, 1076
\peopleobjpronounii . . . 1036, 1076
\Peopleparent 1037, 1078, 1373
\peopleparent 1037, 1078, 1373
\Peoplepossadj . . . 1036, 1075, 1371
\peoplepossadj . . . 1036, 1075, 1371
\Peoplepossadjii 1037, 1077
\peoplepossadjii 1036, 1077
\Peopleposspronoun 1036, 1075, 1372
\peopleposspronoun 1036, 1075, 1371
\Peopleposspronounii . . 1037, 1077
\peopleposspronounii . . 1037, 1077
\Peoplepronoun . . . 1036, 1074, 1369
\peoplepronoun . . . 1036, 1074, 1369
\Peoplepronounii 1036, 1076
\peoplepronounii 1036, 1076
\Peoplesibling 1037, 1079
\peoplesibling . . . 1037, 1079, 1374
\peoplesurname 1070
\peopletitlesurname 1071
\person 1040,
1043, 1045, 1050–1059, 1061–1081
person (counter) 1039
\PersonAddFemaleLabel . 1041, 1041
\PersonAddMaleLabel . . . 1041, 1041
\PersonAddNonBinaryLabel . . 1042
\Personchild 1078, 1372
\personchild 1077, 1372
\PersonFemaleCount 1038
\personforenames 1069
\personfullname . . . 1068, 1367, 1368
\Persongender 1079
\persongender 1079, 1374
\PersonIfAllFemale 1058, 1058
\PersonIfAllMale 1057, 1057
\PersonIfAllNonBinary 1058

<code>\PersonIfAllUnknownGender</code>	. 1059	<code>\pgfmathifthenelse</code>
<code>\PersonIfFemale</code> 1057, 1057	 305, 306, 1360, 1361
<code>\PersonIfFemaleLabel</code>	<code>\pgfmathmax</code> 310, 1362
 1042, 1042, 1046	<code>\pgfmathmin</code> 309, 1362
<code>\PersonIfMale</code> 1056, 1056	<code>\pgfmathmul</code> 1362
<code>\PersonIfMaleLabel</code>	1042, 1042, 1046	<code>\pgfmathmultiply</code>	307, 311, 312, 1361
<code>\PersonIfNonBinary</code> 1058	<code>\pgfmathneg</code> 310
<code>\PersonIfNonBinaryLabel</code>	1042, 1046	<code>\pgfmathparse</code>
<code>\PersonIfUnknownGender</code> 1059		.. 308, 309, 1206, 1207, 1361, 1362
<code>\personlastsep</code>	1068, 1068, 1367–1369	<code>\pgfmathpow</code> 307
<code>\PersonMaleCount</code> 1038	<code>\pgfmathresult</code>
<code>\personname</code> 1069, 1368		.. 305–312, 1206, 1207, 1360–1363
<code>\PersonNonBinaryCount</code> 1038	<code>\pgfmathsqrt</code> 307, 312, 1361
<code>\Personobjpronoun</code> 1074, 1370	<code>\pgfmathsubtract</code>	307, 311, 312, 1361
<code>\personobjpronoun</code>	1074, 1369, 1370	<code>\pgfpathlineto</code>
<code>\Personobjpronounii</code> 1076	 895, 1032, 1089, 1096, 1223
<code>\personobjpronounii</code> 1076	<code>\pgfpathmoveto</code>
<code>\Personparent</code> 1078, 1373	 895, 1032, 1089, 1096, 1223
<code>\personparent</code> 1078, 1373	<code>\pgfplotandlerlineto</code>	. 1007, 1218
<code>\Personpossadj</code>	... 1075, 1370, 1371	<code>\pgfplotandlermark</code>
<code>\personpossadj</code>	... 1074, 1370, 1371	 962, 1007, 1206, 1207, 1218
<code>\Personpossadjii</code> 1077	<code>\pgfplotstreamend</code> 1007, 1218
<code>\personpossadjii</code> 1076	<code>\pgfplotstreampoint</code>
<code>\Personposspronoun</code>	1075, 1371, 1372	 962, 1006, 1205, 1218
<code>\personposspronoun</code> 1075, 1371	<code>\pgfplotstreamstart</code>	... 1006, 1217
<code>\Personposspronounii</code> 1077	<code>\pgfpoint</code> 853–855,
<code>\personposspronounii</code> 1077		885, 891–893, 895, 896, 902,
<code>\Personpronoun</code> 1074, 1369		903, 961, 973, 1032, 1087–1090,
<code>\personpronoun</code> 1073, 1369		1093–1097, 1212, 1220, 1223
<code>\Personpronounii</code> 1076	<code>\pgfpointadd</code>	. 1088–1090, 1094–1097
<code>\personpronounii</code> 1075	<code>\pgfpointlineattime</code>	... 1089, 1095
<code>\personsep</code>	... 1067, 1068, 1367–1369	<code>\pgfpointxy</code>	888, 889, 895, 962, 1006,
<code>\PersonSetFemaleLabels</code> 1041		1088–1090, 1094–1097, 1205, 1218
<code>\PersonSetLocalisation</code> 1062	<code>\pgfsetdash</code> 934, 1205
<code>\PersonSetMaleLabels</code> 1040	<code>\pgfsetstrokecolor</code> 1004, 1005
<code>\PersonSetNonBinaryLabels</code>	. 1041	<code>\pgfsetxvec</code>
<code>\Personsisibling</code> 1079, 1373		885, 902, 903, 973, 1087, 1093, 1212
<code>\personsisibling</code>	... 1078, 1373, 1374	<code>\pgfsetyvec</code>
<code>\personsurname</code> 1070		885, 902, 903, 973, 1087, 1093, 1212
<code>\persontitlesurname</code> 1070	<code>\pgftext</code> 891, 892,
<code>\persontitlesurnamesep</code>		896, 897, 903, 1088–1090, 1093–1097
 1048, 1071, 1071	<code>\pgftransformcm</code>	... 961, 1212, 1220
<code>\PersonTotalCount</code> 1038	<code>\pgftransformreset</code> 962, 974
<code>\PersonUnknownCount</code> 1039	<code>\pgftransformxscale</code> 1206
<code>\PersonUnknownGenderCount</code>	. 1039	<code>\pgftransformyscale</code> 1207
<code>\pgf@pathminx</code> 897, 906	<code>\pgfusepath</code> 896,
<code>\pgf@pathminy</code> 897, 905, 906		1007, 1032, 1089, 1096, 1218, 1223
<code>\pgfmathabs</code> 310, 1362	<code>\pgfuseplotmark</code> 933, 934, 1205
<code>\pgfmathadd</code>	. 306, 307, 310–312, 1361	<code>\phdthesisname</code> 782, 1098
<code>\pgfmathdivide</code>	.. 307, 310–312, 1361	<code>\Phi</code> 732, 1174

<code>\phi</code>	732, 1174	1289, 1292, 1297, 1314, 1315,
<code>\Pi</code>	732, 1174	1317, 1325, 1343–1346, 1348–1351
<code>\pi</code>	732, 1174	<code>\protected@write</code>
<code>\Plural</code>	666, 725, 1144, 1171	757, 1136, 1186, 1195, 1279–1283
<code>\pluralchild</code>	1066, 1367, 1372	<code>\protected@xdef</code>
<code>\pluralobjpronoun</code>	1064, 1367, 1370	. 1127, 1176, 1177, 1281, 1289, 1364
<code>\pluralparent</code>	1066, 1367, 1373	<code>\providecommand</code>
<code>\pluralpossadj</code>	1064, 1367, 1371	2, 662, 667, 734,
<code>\pluralposspronoun</code>	1065, 1367, 1371, 1372	781, 782, 1039, 1098, 1140, 1144,
<code>\pluralpronoun</code>	1064, 1367, 1369	1175, 1225, 1290, 1358, 1360, 1367
<code>\pluralsibling</code>	1067, 1367, 1374	<code>\ProvidesFile</code>
<code>\postnewtermhook</code>	739, 740, 1178	282, 283, 291, 297, 304
<code>\pounds</code>	185, 193, 1304	<code>\ProvidesPackage</code>
<code>\prg</code>	4–6, 27, 28, 64–68, 70–73, 103, 141–147, 189, 211, 212, 222, 223, 266, 405, 467, 470, 481, 517, 518, 527, 564, 1053	1, 304, 313, 645, 778, 849, 906, 929, 1036, 1081, 1097, 1131, 1196, 1204, 1223, 1290, 1357, 1360, 1363
<code>\printterms</code>	709, 772, 1192	<code>\Psi</code>
<code>\printterms@condition</code>	711, 1192, 1195	732, 1174
<code>\printterms@setupmulticol</code>	771, 774, 1192, 1193	<code>\psi</code>
<code>\printterms@setuptwocol</code>	772, 774, 1192, 1193	732, 1174
<code>\printtermsrestoreonecolumn</code>	772, 772, 1192	
<code>\printtermsstartpar</code>	771, 774, 1192, 1193	
<code>\process@envbody</code>	269, 270, 1292	
<code>\ProcessKeyOptions</code>	22, 318, 659, 779, 850, 907, 1037	
<code>\ProcessOptions</code>	318, 659, 779, 850, 907, 929, 1037, 1082, 1197	
<code>\ProcessOptionsX</code>	1097, 1140, 1225, 1290, 1358, 1360	
<code>\prop</code>	54, 100, 101, 148, 149, 177, 186, 320, 325–332, 378, 380, 384, 390, 466, 468, 472, 478, 596–600, 626, 628, 629, 632, 634–636, 1034, 1035	
<code>\protect</code>	1138, 1300, 1312–1314, 1316, 1319	
<code>\protected@edef</code>	43, 270, 317, 502, 507, 592, 641, 722, 723, 757, 1099, 1101, 1105, 1107, 1108, 1115, 1117, 1118, 1121, 1172, 1183, 1186, 1195, 1196, 1234, 1235, 1239, 1242, 1244, 1254, 1256, 1259, 1278, 1279, 1286,	
<code>\q</code>	28, 34–36, 39, 40, 56, 57, 70, 76, 77, 94, 95, 100, 102, 103, 149, 216, 223, 224, 262, 263, 272–274, 320, 322, 351, 353, 356, 369, 410–415, 447, 448, 450, 453, 457–460, 462–467, 480, 481, 487, 488, 564, 578, 582, 639, 864, 869, 926–928	
<code>\q@nil</code>	407, 409, 486, 487, 489, 490, 492, 493, 1230, 1231, 1239–1241, 1243–1248, 1275	
<code>\quark</code>	70, 102, 103, 178, 219, 331, 332, 336, 344, 353, 356, 365, 370, 373, 470, 478, 481, 488, 597, 626, 628, 629, 632, 634–636, 639	
		Q
		R
		<code>\raggedleft</code>
		672, 1147
		<code>\raggedright</code>
		673, 695, 1148, 1162
		<code>\raisebox</code>
		668, 752, 1145, 1184
		<code>\read</code>
		1284, 1285, 1289
		<code>\ref</code>
		25
		<code>\refstepcounter</code>
		25, 493, 495, 498, 676, 683, 690, 693, 697, 786, 787, 1099, 1100, 1149, 1154, 1159, 1161, 1163, 1249, 1250, 1252, 1253
		<code>\regex</code>
		. 44, 45, 51, 52, 54, 55, 57–61, 63, 93, 94, 97, 98, 100, 104, 105, 107, 114, 115, 122, 143, 144, 146, 149–172, 174–176, 178–184, 210–214, 238, 244, 245, 267, 283, 314–317, 515, 592, 593, 630, 631, 639, 641, 699, 700, 722, 789, 844

`\relax` 45, 46, 235, 236, 259–261, 269,
271, 273, 275–281, 299, 302–304,
308, 309, 315, 406, 407, 420, 428,
486, 487, 489–491, 494, 501, 504,
509, 536, 538, 539, 614, 615,
622, 623, 643, 644, 681, 791,
1014, 1031, 1032, 1082–1086,
1089–1093, 1095–1097,
1099–1104, 1109–1112,
1126–1129, 1132–1135, 1138,
1141, 1143, 1148–1155,
1157–1160, 1162–1165, 1169,
1181, 1183, 1185, 1188, 1191,
1193–1195, 1197–1200, 1203,
1204, 1207–1218, 1223, 1224,
1226–1229, 1231–1234, 1236,
1237, 1239, 1241, 1242,
1244–1260, 1263, 1265–1269,
1272–1289, 1291–1293, 1295,
1296, 1298–1303, 1312–1336,
1338–1345, 1347–1352,
1356–1359, 1361, 1362, 1368–1374
`\removeallpeople` 1052, 1364
`\removepeople` 1052, 1364
`\removeperson` 1051, 1364
`\renewcommand` 8,
10, 18–20, 48, 261–263, 268,
646, 654–658, 712–715, 816–819,
821, 822, 824, 826, 828, 830–833,
836–839, 1060, 1061, 1112–1118,
1120–1126, 1132–1139,
1148–1150, 1153–1155,
1157–1164, 1168–1171, 1175,
1176, 1190–1192, 1199,
1223–1225, 1290, 1297, 1298, 1304
`\RenewDocumentCommand` .. 472, 473
`\RenewDocumentEnvironment` ..
..... 817, 839
`\renewenvironment` 1112, 1126
`\repeat` 1188, 1285–1287
`\RequireDataBibDialect` . 849, 849
`\RequireDatatoolDialect` 263, 268
`\RequirePackage` ... 1, 297, 304,
313, 318, 645, 659, 779, 850, 851,
907, 929, 1037, 1081, 1082, 1097,
1131, 1196, 1197, 1204, 1205,
1223, 1225, 1290, 1357, 1360, 1363
`\RequirePersonDialect` . 1081, 1081
`\reset@font` 846, 1130
`\rho` 732, 1174
`\romannumeral` 493, 494,
496–512, 859, 861, 863, 909–911,
916–919, 927, 928, 1082,
1083, 1087, 1197–1200, 1203,
1204, 1248–1258, 1284, 1286–1288

S

`\s` ... 60, 93, 122, 150–157, 166–169, 315
`\s@DTLaddcolumn` 417, 418, 1231
`\s@dtlenvforeach@args` . 1248, 1249
`\s@dtlformatlist` . 49, 49, 1297, 1298
`\s@DTLifstringlt` 240
`\section` 666, 694, 1144, 1162
`\See` 647, 656,
657, 664, 665, 714–716, 725, 777,
1133, 1134, 1141, 1143, 1150,
1153, 1155, 1158, 1160, 1171, 1196
`\SeeAlso` 647,
665, 725, 777, 1133, 1143, 1150,
1153, 1155, 1158, 1160, 1171, 1196
`\seelisoname` ... 647, 662, 1133, 1140
`\seename` 647, 656,
657, 662, 714–716, 1133, 1134, 1140
`\seq` 3–7, 29, 30, 32–34, 38, 40, 45–47,
49, 53, 54, 62, 100, 102, 108,
115, 121, 123–130, 135, 141–143,
145–147, 158–188, 198–200,
206–208, 319–322, 330, 334, 335,
356, 374–386, 389, 390, 394, 395,
519–521, 523, 525–527, 530, 544,
545, 547–553, 566–569, 575–579,
582, 583, 585–590, 598–600, 631,
633, 638, 639, 652, 653, 660, 661,
663, 699–701, 776, 844, 851–853,
865–867, 873, 876, 879, 880,
884, 885, 896, 898–900, 902, 904,
905, 913, 929, 932, 933, 938–941,
943, 950, 953–955, 963, 968–973,
979–981, 987, 992, 998, 1002,
1005, 1014–1016, 1020–1024,
1026–1028, 1030, 1031, 1035,
1036, 1039, 1040, 1049–1053,
1060, 1061, 1068, 1072, 1073
`\setbool` 947, 1138, 1225
`\setcounter` 493,
693, 697, 791, 793, 857, 908, 935,
1082, 1099, 1101, 1102, 1127,
1161, 1163, 1197, 1206, 1365, 1368
`\setkeys`
.. 1085, 1090, 1169, 1170, 1176,

1192, 1193, 1199, 1210, 1261, 1285
 \setlength 856, 934–936, 1082, 1084,
 1086, 1087, 1090–1093, 1095,
 1097, 1145–1162, 1164, 1191,
 1206, 1207, 1211, 1212, 1215, 1222
 \settodepth 24, 1086, 1087, 1092, 1093
 \settoheight 24, 970, 1086,
 1087, 1092, 1093, 1145, 1184, 1211
 \settowidth 24, 973, 1086, 1092,
 1099, 1127, 1146, 1147, 1150,
 1151, 1154, 1155, 1158–1160, 1212
 \sfcode 791, 1101
 \Short 666, 725, 1144, 1171
 \ShortPlural 725, 1171
 \show 643, 1289
 \showthe 642, 643, 1289
 \Siblings 1037
 \siblings 1037
 \Sigma 732, 1174
 \sigma 732, 1174
 \skip 667, 673, 675, 676, 678–681,
 683, 684, 686–689, 691, 693, 697
 \smallskip 669
 \Sort 725, 739, 1171, 1195
 \sort 35, 45, 578, 579, 588, 661
 \space 31, 48, 237, 407, 491, 492, 502,
 505, 507, 509, 539, 647, 656, 657,
 694, 714, 715, 733, 791, 805, 962,
 1083, 1085, 1090, 1101, 1130,
 1134, 1135, 1137, 1138, 1162,
 1173, 1174, 1197–1199, 1207,
 1229, 1235, 1236, 1240–1244,
 1247, 1249, 1252, 1254–1258,
 1265, 1280–1284, 1297, 1312,
 1313, 1340–1342, 1363, 1367
 \spacefactor 791, 1101
 \SS 732, 1174
 \ss 732, 1174
 \step 259, 260, 497, 1250, 1288, 1356
 \stepcounter 25, 1127, 1364, 1368
 \str 52, 62, 187–189, 224, 234–237,
 239–241, 243, 244, 246, 248, 249
 \strcmp 234
 \string 31, 32,
 54, 304, 313, 509, 607, 652, 733,
 780, 813, 846, 847, 962, 1083,
 1085, 1090, 1097, 1111, 1130,
 1131, 1137, 1138, 1173, 1175,
 1182, 1186, 1195, 1197–1199,
 1207, 1210, 1236, 1249, 1252,
 1254–1258, 1280–1284, 1314–1316
 \Symbol 648–650, 666, 693,
 725, 1135, 1136, 1144, 1161, 1171
 \sys 2, 778

T
 \t 630
 \tabularnewline 518, 1259
 \tau 732, 1174
 \TE@or 259–261, 1356, 1357
 \TE@throw 251–259,
 807–811, 1108–1110, 1352–1356
 \techreportname 782, 1098
 \TeX 32
 \Text 666, 725, 1144, 1171
 \text 10, 32, 42, 44, 45, 77, 210–212,
 220, 235, 236, 244, 245, 262, 275,
 575, 653, 655, 707, 712, 713, 722,
 734, 744, 768, 769, 789, 798–804,
 844, 1040, 1057–1061, 1071, 1073
 \textasciicircum 1289
 \textasciitilde 1289
 \textbaht 193
 \textbf 515, 674, 688, 692, 721,
 722, 1149, 1158, 1160, 1176, 1259
 \textcent 193
 \textcentoldstyle 193
 \textcolonmonetary 193
 \textcurrency 185, 192, 193, 1304
 \textdollar 185, 193, 1304
 \textdollaroldstyle 193
 \textdong 193
 \texteuro 185, 193, 1304
 \textflorin 193
 \textguarani 193
 \textit 721, 722, 1176
 \textlira 193
 \textmd 721, 722, 1176
 \textminus 191
 \textnaira 193
 \textnormal 646, 1132
 \textpeso 193
 \textrm 721, 722, 1176
 \textsc 10, 721, 722, 804, 1176
 \textsf 721, 722, 1176
 \textsl 721, 722, 1176
 \textsmaller 10
 \textsterling 193
 \textstirling 185, 1304

<code>\textsuperscript</code> . . .	721, 722, 1176	
<code>\texttt</code>	721, 722, 805, 1176	
<code>\textwon</code>	185, 193, 1304	
<code>\textyen</code>	185, 193, 1304	
<code>\TH</code>	732, 1174	
<code>\th</code>	732, 1174	
<code>\the</code>	49–51, 260, 261, 269, 271, 272, 407, 409, 433, 486–490, 496, 497, 500, 502, 504–507, 537, 538, 565, 641, 651, 1086, 1087, 1092, 1093, 1108–1110, 1127, 1128, 1153, 1162, 1203, 1204, 1216–1218, 1221–1223, 1230–1235, 1238–1247, 1249–1257, 1264–1266, 1273–1275, 1277–1279, 1281–1284, 1286–1289, 1292, 1294–1299, 1301, 1303, 1304, 1310–1318, 1341, 1357, 1363	319–322, 324–336, 338, 340, 343, 344, 346, 351, 353, 354, 356–362, 364–374, 376–380, 382, 384, 386, 388, 390, 393, 395, 399, 405, 406, 410–414, 417, 421–426, 428–430, 432, 435, 436, 438–440, 443, 444, 446–448, 450, 453, 457–460, 462–469, 471–485, 487, 488, 495, 497, 498, 501, 503, 505, 508, 513–515, 518–520, 522, 524–527, 529–535, 541–545, 547, 549–564, 567–578, 580–587, 589, 590, 592–594, 597–602, 604, 606–609, 617, 619, 621, 624, 626–641, 648–651, 653, 655, 656, 659–664, 666, 667, 669–703, 705–709, 713, 714, 717–728, 734–743, 745–747, 751–755, 757–763, 771–774, 776, 778, 780–788, 794–796, 807, 811, 839–845, 847, 848, 851–857, 859, 860, 862, 864–901, 903–905, 907, 908, 910, 912, 915–930, 932, 933, 937–941, 946, 950–954, 959, 961–966, 968–1014, 1016, 1019, 1021–1023, 1027, 1028, 1031–1035, 1037, 1039, 1040, 1042–1050, 1052–1054, 1056–1063, 1069–1071, 1079–1081
<code>\theDTLgidxChildCount</code> .	661, 1132	
<code>\Thee</code>	1036	
<code>\thee</code>	1036	
<code>\theHDTLbibrow</code>	787, 1100	
<code>\theHDTLgidxChildCount</code>	660, 1132	
<code>\theHDTLrow</code>	493, 787, 1100, 1248	
<code>\theHDTLrowi</code>	493, 1248	
<code>\theHDTLrowii</code>	493, 1248	
<code>\theHDTLrowiii</code>	493, 1248	
<code>\Their</code>	1036	<code>\to</code> 259, 260, 497, 643, 644, 1224, 1225, 1250, 1286–1288, 1356
<code>\their</code>	1036	
<code>\Theirs</code>	1036	<code>\today</code> 609
<code>\theirs</code>	1036	<code>\token</code> 114, 116, 119, 135, 321, 332–334, 336, 338, 339, 341, 345, 348, 349, 354, 355, 359, 365, 369, 371, 373, 374, 383, 387, 388, 394, 402, 403, 431, 432, 434–436, 444, 450, 455, 473–476, 479, 481, 484, 496, 501–503, 505–508, 510–512, 524, 535, 567, 569, 576, 577, 586, 590, 595, 609–619, 624, 645, 651, 709, 728, 733, 740, 742, 746, 747, 751, 754, 757, 764, 766, 773, 775, 779, 846, 847, 858, 876, 879, 898, 900, 909, 925, 927, 942, 1015, 1016, 1020, 1021, 1039, 1060
<code>\Them</code>	1036	
<code>\them</code>	1036	
<code>\thepage</code>	1130	
<code>\Theta</code>	732, 1174	
<code>\theta</code>	731, 1173	
<code>\They</code>	1036	
<code>\they</code>	1036	
<code>\thiscol</code>	504, 506, 1255, 1256	
<code>\tikz</code>	1093, 1223	
<code>\tl</code>	2–4, 6, 9–16, 20, 24, 25, 28–30, 32, 34–36, 39–41, 44–48, 52, 54, 56–60, 62, 66–79, 81, 83–110, 112–121, 124–130, 132, 133, 143, 148–150, 166–169, 177, 178, 186–212, 214–230, 235–238, 244, 245, 261–264, 266, 267, 270, 272–275, 282, 285–290, 306–312, 314–317,	<code>\toks@</code> 269, 271, 272, 504, 505, 537, 538, 1108–1110, 1127, 1128, 1216–1218, 1221–1223, 1239, 1240, 1242–1244, 1246, 1247, 1255, 1264, 1265,

1274, 1275, 1278, 1279,
 1284, 1292, 1294–1297, 1299,
 1301, 1304, 1310–1318, 1341
 \TrackIfKnownLanguage 268
 \TrackLangAddToCaptions 264, 282
 \TrackLangEncodingName
 2, 54, 610, 611, 613, 616
 \TrackLangProvidesResource . 281
 \TrackLangRequireDialect ...
 268, 849, 1081
 \TrackLangRequireDialectOmitDialectLabel... 1138–1140, 1169, 1190,
 1191, 1207–1209, 1225, 1290, 1357
 \TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion..... 1083
 264, 266, 268
 \TrackLangRequireResource ..
 263, 264
 \TrackLangShowWarningsfalse . 7
 \TrackLanguageTag 267
 \two@digits 729, 1173
 \twocolumn 772, 1192
 \TwoLetterIsoCountryCode ... 267
 \twopeoplesep 1068, 1068, 1367, 1368
 \typeout 23, 575, 1273, 1290

U

\u 52, 57–60, 97, 98, 105, 107, 108, 592, 593
 \uccode 1315
 \undef ... 1084, 1136, 1175, 1176, 1188
 \undefined
 .. 399, 400, 1226, 1227, 1364, 1365
 \UnsafeLocation 652, 653
 \uppercase 1314
 \Upsilon 732, 1174
 \upsilon 732, 1174
 \ur 52, 58–61, 150–157, 166–169, 212, 213
 \url 805
 \use ... 2, 7, 10, 11, 25, 39, 114, 115,
 190, 224, 392, 478, 484, 485, 541,
 544, 549, 552, 554, 558, 561, 570,
 573, 574, 578, 580, 601, 609, 624,
 646, 654, 655, 658, 661, 668, 698,
 709, 712, 713, 721, 722, 741, 751,
 765, 785, 788, 789, 797, 876, 878,
 879, 898, 899, 909, 920–923, 926,
 927, 965–967, 1015, 1016, 1019–1022
 \Used 666, 725, 1171
 \USEntry 767, 1189
 \Useentry ... 767, 769–771, 1189, 1190
 \useentry 767, 767, 769–771, 1189, 1190
 \USEntrynl 769, 1189

\Useentrynl 768, 770, 1189, 1190
 \useentrynl . 768, 769, 770, 1189, 1190
 \usepackage 304, 313
 \usetikzlibrary 929, 1205
 \UTFviii@two@octets
 273, 733, 1175, 1290, 1326
 \UTFviii@two@octets@combine
 733, 1175

V

\varepsilon 731, 1173
 \varphi 732, 1174
 \varpi 732, 1174
 \varrho 732, 1174
 \varsigma 732, 1174
 \vartheta 731, 1173
 \volumename
 ... 781, 798, 800, 1098, 1105, 1106

W

\wasyeuro 193
 \whiledo 259–261, 1085,
 1091, 1204, 1221, 1222, 1356, 1357
 \write 780, 813,
 1097, 1111, 1130, 1131, 1282, 1283

X

\x 60, 61, 122, 123, 314–316, 593, 630, 1293
 \xappto 1172
 \xcapitalisewords 655, 712, 713, 1132
 \xdef .. 565, 1099, 1100, 1128, 1162,
 1165, 1170, 1172, 1187, 1194,
 1223, 1233, 1249, 1252, 1273, 1364
 \xDTLassignfirstmatch . 435, 1235
 \xdtlgetrowindex 461, 1244
 \xDTLinitials 215
 \Xi 732, 1174
 \xi 732, 1174
 \xmakefirststuc
 655, 656, 712, 713, 715,
 753, 767, 769, 1132, 1134, 1184, 1189

Y

\yen 1304
 \You 1036
 \you 1036
 \Your 1037

\your	1036	93, 122, 151–157, 166–169, 213,
\Yours	1037	238, 267, 314, 315, 699, 789, 844
\yours	1037	\z@
		1285
		\zetaa
		731, 1173
		z
\Z	55, 57–60,	