
Description of the Application Group Extension

Implementation for the X11 Sample Server

Kaleb KEITHLEY, FUJITSU Limited.

Version 1.0

Copyright © 1996 X Consortium

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

The following document explains the server side of the Application Group Extension.

WindowsNT is a trademark of Microsoft, Inc. Macintosh and Apple are trademarks of Apple Computer, Inc. X Window System is a trademark of X Consortium, Inc.

Abstract

The following document explains the server side of the Application Group Extension.

Table of Contents

AppGroup Server Public Functions	1
AppGroup Server Private APIs	2
Known Problems in this release.	3

To understand this document and the accompanying source code, you should know the C language, should be familiar with X server internals, and should also have a general knowledge of the X Window System.

AppGroup Server Public Functions

The AppGroup extension adds seven new functions that are called from elsewhere in the server. They are: XagExtensionInit, XagDefaultColormap, XagRootVisual, XagLeader, XagIsControlledRoot, XagConnectionInfo, XagCallClientStateChange.

XagExtensionInit is the extension initialization function called from InitExtension in mi/miinitext.c. Note that a new resource type, RT_APPGROUP, is created, specifying the destructor function XagAppGroupFree.

`XagDefaultColormap` returns the colormap ID that was specified in the creation of the `AppGroup`. Any time `CopyFromParent` is specified for a top-level window's colormap, i.e. in a `CreateWindow` or `ChangeWindowAttributes` request, this function is called to see if there is an `AppGroup` specific colormap to use. If there is one, its ID is returned, otherwise `None` is returned.

`XagRootVisual` returns the visual ID that was specified in the creation of the `Appgroup`. Like `XagDefaultColormap`, when `CopyFromParent` is specified for a top-level window's visual in a `CreateWindow` request, this function is called to see if there is an `AppGroup` specific visual to use. If there is one, its ID is returned, otherwise 0 (zero) is returned.

`XagLeader` returns the `ClientPtr` of the client that is the `AppGroup` Leader. Normally when an application maps or configures a top-level window a `MapRequest` or `ConfigureRequest` event is delivered to the client, e.g. a window manager, that has selected `SubstructureRedirect` on the root window. However, when the application is part of an `AppGroup`, the `MapRequest` and `ConfigureRequest` events are delivered to the `AppGroup` Leader instead.

`XagIsControlledRoot` returns a boolean: `True` if the window is a top-level window of a client in an `AppGroup`, `False` otherwise. In a combined server, i.e. one that provides both UI and printing, the application may create and map windows on the "printing" screens; thus it becomes necessary to discriminate between the `AppGroup`'s root window and other root windows. If an `AppGroup` member creates and maps a [top-level] window then the window's parent [the root window] is tested to determine whether to send `MapRequest` or `ConfigureRequest` events to the `AppGroup` Leader to to some other client.

In the trivial case `XagIsControlledRoot` returns `True` if the parent window has no parent itself, i.e. it is a root window. In the case where the application is embedded, indicated by the `singleScreen` attribute being `True`, the parent's drawable ID is compared to the `AppGroup`'s root window ID, and if it is the same, `True` is returned. If neither case is true, then `False` is returned.

`XagConnectionInfo` returns an abbreviated version of the connection setup information. When an embedded `AppGroup` is created the server returns only the information about the [UI] screen that the application is embedded within in the connection setup in order to prevent the application from creating windows on other screens; thus attempting to guarantee that any window that should be embedded can be reparented into the `AppGroup` Leader's window hierarchy.

`XagCallClientStateChange` is called to invoke the extension's client state change callback additional times as necessary -- currently only once, after the auth data becomes available between `ClientStateInitial` and `ClientStateConnected`. Client state change callbacks were introduced in the `Record` extension, which specifies when the callbacks are invoked. Unfortunately the points at which they are called are not necessarily the best as far as the `AppGroup` Extension is concerned. Adding an additional state and calling all the callbacks works too, however this seemed unnecessary overkill.

AppGroup Server Private APIs

The `AppGroup` extension adds the following functions which are private to the extension: `ProcXagDispatch` and `SProcXagDispatch`, `ProcXagQueryVersion` and `SProcXagQueryVersion`, `ProcXagCreate` and `SProcXagCreate`, `ProcXagDestroy` and `SProcXagDestroy`, `ProcGetAttr` and `SProcGetAttr`, `ProcXagQuery` and `SProcXagQuery`, `ProcXagCreateAssoc` and `SProcXagCreateAssoc`, `ProcXagDestroyAssoc` and `SProcXagDestroyAssoc`, `XagResetProc`, and `XagAppGroupFree`.

The `ProcXagDispatch`, `SProcXagDispatch`, and `XagResetProc` functions should be familiar to anyone familiar with X server internals and I won't elaborate on them here. Similarly the wrapper functions: `SProcXagQueryVersion`, `SProcXagCreate`, `SProcXagDestroy`, `SProcXagGetAttr`, `SProcXagQuery`, `SProcXagCreateAssoc`, and `SProcXagDestroyAssoc`, as wrappers which handle swapping integer data into the host's byte order will not be explained in any detail.

`ProcXagQueryVersion` returns the major and minor versions of the `AppGroup` extension supported by the server.

ProcXagCreate creates an AppGroup. A new record in a linked list of AppGroups is allocated and initialized. The attributes from the request are validated and copied to the AppGroup record. If necessary an abbreviated version of the connection setup information is compiled and also stored in the AppGroup record. The first time an AppGroup is created a client-state-change callback is registered and a reference count is incremented.

ProcXagDestroy destroys an AppGroup an AppGroup by calling FreeResource specifying the AppGroup ID. This will result in the destructor function XagAppGroupFree being called. The reference count is decremented and when it reaches zero the client-state-change callback is deleted.

ProcXagGetAttr returns the AppGroup Attributes to the requesting client.

ProcXagQuery returns the AppGroup ID of an arbitrary resource to the requesting client.

ProcXagCreateAssoc creates an association between an X window ID and system-specific data. In native X this functionality is unnecessary but for various personal computers, e.g. Macintosh, OS/2, and MS-Windows it is necessary to associate an X window ID with the system's native window identifier so that when the AppGroup Leader issues a ReparentWindow request the personal computer X server can lookup the system-specific window ID and make the necessary function call(s) with it.

ProcXagDestroyAssoc destroys the association created with ProcXagCreateAssoc.

XagResetProc removes the client-state-change callback, sets the reference count to zero, and frees all the AppGroup records in the linked list by calling XagAppGroupFree.

XagAppGroupFree calls CloseDownClient for each client in an AppGroup if the AppGroup has a leader, unlinks the AppGroup record from the linked list, frees allocated memory referenced by the record, and finally frees the record itself.

Known Problems in this release.

In a combined UI/Print server the connection setup returned to an embedded application will not have information about the print screens.

The LBX proxy caches connection setup information and will return incorrect connection setup information to an embedded client.