

Oracle®

Technology Compatibility Kit User's Guide for
JavaBeans Activation Framework 1.2

Release 1.2 for Technology Licensees

July 2017

Copyright © 2009, 2017 Oracle and/or its affiliates. All rights reserved.

Primary Author: Eric Jendrock

Contributing Author: Bill Shannon

Contributor:

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface	3
Who Should Use This Book	3
Documentation Accessibility	3
Before You Read This Book	3
Typographic Conventions	4
Shell Prompts in Command Examples	4
 1 Introduction	
1.1 Compatibility Testing	1-1
1.1.1 Why Compatibility Testing is Important	1-1
1.1.2 TCK Compatibility Rules	1-1
1.1.3 TCK Overview	1-2
1.1.4 Java Community Process (JCP) Program and Compatibility Testing	1-2
1.2 About the JAF TCK 1.2	1-2
1.2.1 JAF TCK Specifications and Requirements	1-2
1.2.2 JAF TCK Components	1-2
1.2.3 JavaTest Harness	1-3
1.2.4 TCK Compatibility Test Suite	1-3
1.2.5 Exclude Lists	1-3
1.2.6 JAF TCK Configuration	1-4
1.3 Getting Started With the JAF TCK	1-4
 2 Procedure for JavaBeans Activation Framework 1.2 Certification	
2.1 Certification Overview	2-1
2.2 Compatibility Requirements	2-1
2.2.1 Definitions	2-1
2.2.2 Rules for JavaBeans Activation Framework Version 1.2 Products	2-3
2.3 JavaBeans Activation Framework Version 1.2 Test Appeals Process	2-4
2.3.1 JavaBeans Activation Framework Version 1.2 TCK Test Appeals Steps	2-5
2.3.2 Test Challenge and Response Forms	2-6
2.4 Specifications for JavaBeans Activation Framework Version 1.2	2-6
2.5 Libraries for JavaBeans Activation Framework Version 1.2	2-6
 3 Installation	
3.1 Obtaining the JAF 1.2 Reference Implementation	3-1

3.2	Installing the JAF Software	3-1
4	Setup and Configuration	
4.1	Configuration Overview	4-1
4.2	Configuring Your Environment to Run the JAF TCK	4-1
4.3	Using the JavaTest Harness Software	4-2
4.4	Using the JavaTest Harness Configuration GUI.....	4-2
4.4.1	Configuration GUI Overview	4-2
4.4.2	Starting the Configuration GUI	4-3
4.4.3	Configuring the JavaTest Harness to Run the JAF TCK Tests	4-3
4.4.4	Modifying the Default Test Configuration	4-4
5	Executing Tests	
5.1	Starting JavaTest.....	5-1
5.1.1	To Start JavaTest in GUI Mode.....	5-1
5.1.2	To Start JavaTest in Command-Line Mode	5-1
5.2	Running a Subset of the Tests.....	5-1
5.2.1	To Run a Subset of Tests in GUI Mode	5-2
5.2.2	To Run a Subset of Tests in Command-Line Mode	5-2
5.2.3	To Run a Subset of Tests in Batch Mode Based on Prior Result Status	5-2
5.3	Test Reports	5-2
5.3.1	Creating Test Reports	5-3
5.3.1.1	To Create a Test Report in GUI Mode	5-3
5.3.1.2	To Create a Test Report in Command-Line Mode	5-3
5.3.2	Viewing an Existing Test Report.....	5-3
5.3.2.1	To View an Existing Report in GUI Mode	5-3
5.3.2.2	To View an Existing Report in Command-Line Mode	5-3
6	Debugging Test Problems	
6.1	Overview.....	6-1
6.2	Test Tree	6-1
6.3	Folder Information	6-1
6.4	Test Information	6-2
6.5	Report Files.....	6-2
6.6	Configuration Failures	6-2
A	Frequently Asked Questions	
A.1	Where do I start to debug a test failure?	A-1
A.2	How do I restart a crashed test run?.....	A-1
A.3	What would cause tests be added to the exclude list?	A-1

Preface

This guide describes how to install, configure, and run the Technology Compatibility Kit (TCK) that is used to test the JavaBeans Activation Framework 1.2 (JAF) 1.2 technology.

The JAF TCK is designed as a portable, configurable automated test suite for verifying the compatibility of a licensee's implementation of the JAF 1.2 Specification (hereafter referred to as the licensee implementation). The JAF TCK uses the JavaTest harness version 2.1.5 to run the test suite.

Note: Note All references to specific Web URLs are given for the sake of your convenience in locating the resources quickly. These references are always subject to changes that are in many cases beyond the control of the authors of this guide.

Refer to the Java Licensee Engineering (<https://javapartner.oracle.com>) Web site for answers to frequently asked questions and send questions you may have to your Java Partner Engineering contact.

Who Should Use This Book

This guide is for licensees of the JAF 1.2 technology to assist them in running the test suite that verifies compatibility of their implementation of the JAF 1.2 Specification.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Before You Read This Book

Before reading this guide, you should be familiar with the JavaBeans Activation Framework 1.2 Specification. A link to the specification can be found at <http://jcp.org/en/jsr/detail?id=925>. Before you run the tests in the JAF TCK familiarize yourself with the JavaTest documentation, which can be accessed at <https://wiki.openjdk.java.net/display/CodeTools/Documentation>.

Typographic Conventions

The following table describes the typographic conventions that are used in this book.

Convention	Meaning	Example
Boldface	Boldface type indicates graphical user interface elements associated with an action, terms defined in text, or what you type, contrasted with onscreen computer output.	From the File menu, select Open Project . A cache is a copy that is stored locally. machine_name% su Password:
Monospace	Monospace type indicates the names of files and directories, commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. machine_name% you have mail.
Italic	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.	Read Chapter 6 in the <i>User's Guide</i> . Do <i>not</i> save the file. The command to remove a file is <code>rm filename</code> .

Shell Prompts in Command Examples

The following table shows the default UNIX system prompt and superuser prompt for the C shell, Bourne shell, and Korn shell.

Shell	Prompt
C shell	machine_name%
C shell for superuser	machine_name#
Bourne shell and Korn shell	\$
Bourne shell and Korn shell for superuser	#
Bash shell	shell_name-shell_version\$
Bash shell for superuser	shell_name-shell_version#

Introduction

This chapter provides an overview of the principles that apply generally to all Technology Compatibility Kits (TCKs) and describes the JavaBeans Activation Framework 1.2 (JAF) 1.2 TCK.

The chapter also includes a high level listing of what is needed to get up and running with the JAF TCK.

1.1 Compatibility Testing

Compatibility testing differs from traditional product testing in a number of ways. The focus of compatibility testing is to test those features and areas of an implementation that are likely to differ across other implementations, such as those features that:

- ⌘ Rely on hardware or operating system-specific behavior
- ⌘ Are difficult to port
- ⌘ Mask or abstract hardware or operating system behavior

Compatibility test development for a given feature relies on a complete specification and reference implementation for that feature. Compatibility testing is not primarily concerned with robustness, performance, or ease of use.

1.1.1 Why Compatibility Testing is Important

Java platform compatibility is important to different groups involved with Java technologies for different reasons:

- ⌘ Compatibility testing ensures that the Java platform does not become fragmented as it is ported to different operating systems and hardware environments.
- ⌘ Compatibility testing benefits developers working in the Java programming language, allowing them to write applications once and then to deploy them across heterogeneous computing environments without porting.
- ⌘ Compatibility testing allows application users to obtain applications from disparate sources and deploy them with confidence.
- ⌘ Conformance testing benefits Java platform implementors by ensuring a level playing field for all Java platform ports.

1.1.2 TCK Compatibility Rules

Compatibility criteria for all technology implementations are embodied in the TCK Compatibility Rules that apply to a specified technology. Each TCK tests for adherence to these

Rules as described in [Chapter 2, "Procedure for JavaBeans Activation Framework 1.2 Certification."](#)

1.1.3 TCK Overview

A TCK is a set of tools and tests used to verify that a licensee's implementation of a Java EE technology conforms to the applicable specification. All tests in the TCK are based on the written specifications for the Java platform. A TCK tests compatibility of a licensee's implementation of the technology to the applicable specification of the technology. Compatibility testing is a means of ensuring correctness, completeness, and consistency across all implementations developed by technology licensees.

The set of tests included with each TCK is called the test suite. Most tests in a TCK's test suite are self-checking, but some tests may require tester interaction. Most tests return either a Pass or Fail status. For a given platform to be certified, all of the required tests must pass. The definition of required tests may change from platform to platform.

The definition of required tests will change over time. Before your final certification test pass, be sure to download the latest Exclude List for the TCK you are using.

1.1.4 Java Community Process (JCP) Program and Compatibility Testing

The Java Community Process (JCP) program is the formalization of the open process that has been used since 1995 to develop and revise Java technology specifications in cooperation with the international Java community. The JCP program specifies that the following three major components must be included as deliverables in a final Java technology release under the direction of the responsible Expert Group:

- ⌘ Technology Specification
- ⌘ Reference Implementation
- ⌘ Technology Compatibility Kit (TCK)

For further information about the JCP program, go to Java Community Process (<http://jcp.org/en/home/index>).

1.2 About the JAF TCK 1.2

The JAF TCK 1.2 is designed as a portable, configurable, automated test suite for verifying the compatibility of a licensee's implementation of the JAF 1.2 Specification.

1.2.1 JAF TCK Specifications and Requirements

This section lists the applicable requirements and specifications.

- ⌘ **Specification Requirements:** Software requirements for a JAF implementation are described in detail in the JAF 1.2 Specification. Links to the JAF specification and other product information can be found at <http://jcp.org/en/jsr/detail?id=925>.
- ⌘ **JAF Version:** The JAF TCK 1.2 is based on the JAF Specification, Version 1.2.
- ⌘ **Reference Implementation:** The Reference Implementation (RI) for JAF 1.2 can be downloaded from the Java Licensee Engineering web site.

1.2.2 JAF TCK Components

The JAF TCK 1.2 includes the following components:

- ⌘ **JavaTest harness:** Version 2.1.5 of the JavaTest harness
- ⌘ **JAF TCK signature tests:** Check that all public APIs are supported and/or defined as specified in the JAF Version 1.2 implementation under test

1.2.3 JavaTest Harness

The JavaTest harness, which is bundled with the JAF TCK, is a set of tools designed to run and manage test suites on different Java platforms. The JavaTest harness can be described as both a Java application and a set of compatibility testing tools. It can run tests on different kinds of Java platforms and it allows the results to be browsed online within the JavaTest GUI, or offline in the HTML reports that the JavaTest harness generates.

The JavaTest harness includes the applications and tools that are used for test execution and test suite management. It supports the following features:

- ⌘ Sequencing of tests, allowing them to be loaded and executed automatically
- ⌘ Graphic user interface (GUI) for ease of use
- ⌘ Automated reporting capability to minimize manual errors
- ⌘ Failure analysis
- ⌘ Test result auditing and auditable test specification framework
- ⌘ Distributed testing environment support

To run tests using the JavaTest harness, you specify which tests in the test suite to run, how to run them, and where to put the results as described in [Chapter 4, "Setup and Configuration."](#)

1.2.4 TCK Compatibility Test Suite

The *test suite* is the collection of tests used by the JavaTest harness to test a particular technology implementation. In this case, it is the collection of tests used by the JAF TCK 1.2 to test a JAF 1.2 implementation. The tests are designed to verify that a licensee's runtime implementation of the technology complies with the appropriate specification. The individual tests correspond to assertions of the specification.

The tests that make up the TCK compatibility test suite are precompiled and indexed within the TCK test directory structure. When a test run is started, the JavaTest harness scans through the set of tests that are located under the directories that have been selected. While scanning, the JavaTest harness selects the appropriate tests according to any matches with the filters you are using and queues them up for execution.

1.2.5 Exclude Lists

Each version of a TCK includes an Exclude List contained in a `.jtx` file. This is a list of test file URLs that identify tests which do not have to be run for the specific version of the TCK being used. Whenever tests are run, the JavaTest harness automatically excludes any test on the Exclude List from being executed.

A licensee is not required to pass or run any test on the Exclude List. The Exclude List file, `<TS_HOME>/bin/ts.jtx`, is included in the JAF TCK.

Note: From time to time, updates to the Exclude List are made available on the Java Licensee Engineering (<https://javapartner.oracle.com>) Web site. You should always make sure you are using an up-to-date copy of the Exclude List before running the JAF TCK to verify your implementation.

A test might be in the Exclude List for reasons such as:

- ⌘ An error in an underlying implementation API has been discovered which does not allow the test to execute properly.
- ⌘ An error in the specification that was used as the basis of the test has been discovered.
- ⌘ An error in the test itself has been discovered.
- ⌘ The test fails due to a bug in the tools (such as the JavaTest harness, for example).

In addition, all tests are run against the reference implementations. Any tests that fail when run on a reference Java platform are put on the Exclude List. Any test that is not specification-based, or for which the specification is vague, may be excluded. Any test that is found to be implementation dependent (based on a particular thread scheduling model, based on a particular file system behavior, and so on) may be excluded.

Note: Licensees are not permitted to alter or modify Exclude Lists. Changes to an Exclude List can only be made by using the procedure described in [Section 2.3, "JavaBeans Activation Framework Version 1.2 Test Appeals Process."](#)

1.2.6 JAF TCK Configuration

You need to set several variables in your test environment, modify properties in the `<TS_HOME>/bin/jaf.jte` file, and then use the JavaTest harness to configure and run the JAF tests, as described in [Chapter 4, "Setup and Configuration."](#)

1.3 Getting Started With the JAF TCK

This section provides an general overview of what needs to be done to install, set up, test, and use the JAF TCK. These steps are explained in more detail in subsequent chapters of this guide.

1. Make sure that the following software has been correctly installed on the system hosting the JavaTest harness:
 - ⌘ **Java SE software:** Java Platform, Standard Edition 7 (Java SE 7) software
 - ⌘ **JAF software:** The implementation of the JAF 1.2 specification under testSee the documentation for each of these software applications for installation instructions.
2. Install the JAF TCK 1.2 software.
See [Chapter 3, "Installation,"](#) for additional information.
3. Set up the JAF TCK software.
See [Chapter 4, "Setup and Configuration,"](#) for details about the following steps.
 - a. Set up your shell environment.
 - b. Modify the required properties in the `<TS_HOME>/bin/jaf.jte` file.
 - c. Configure the JavaTest harness.
4. Test the JAF 1.2 implementation.
Test the JAF implementation installation by running the test suite. See [Chapter 5, "Executing Tests."](#)

Procedure for JavaBeans Activation Framework 1.2 Certification

This chapter describes the compatibility testing procedure and compatibility requirements for JavaBeans Activation Framework 1.2.

This chapter contains the following sections:

- [Certification Overview](#)
- [Compatibility Requirements](#)
- [JavaBeans Activation Framework Version 1.2 Test Appeals Process](#)
- [Specifications for JavaBeans Activation Framework Version 1.2](#)
- [Libraries for JavaBeans Activation Framework Version 1.2](#)

2.1 Certification Overview

The certification process for JavaBeans Activation Framework Version 1.2 consists of the following activities:

- Install the appropriate version of the Technology Compatibility Kit (TCK) and execute it in accordance with the instructions in this User's Guide.
- Ensure that you meet the requirements outlined in "Compatibility Requirements," below.
- Certify to the Java Partner organization that you have finished testing and that you meet all of the compatibility requirements.

2.2 Compatibility Requirements

The compatibility requirements for JavaBeans Activation Framework Version 1.2 consist of meeting the requirements set forth by the rules and associated definitions contained in this section.

2.2.1 Definitions

These definitions are for use only with these compatibility requirements and are not intended for any other purpose.

Table 2–1 Definitions

Term	Definition
API Definition Product	A Product for which the only Java class files contained in the product are those corresponding to the application programming interfaces defined by the Specifications, and which is intended only as a means for formally specifying the application programming interfaces defined by the Specifications.
Computational Resource	<p>A piece of hardware or software that may vary in quantity, existence, or version, which may be required to exist in a minimum quantity and/or at a specific or minimum revision level so as to satisfy the requirements of the Test Suite.</p> <p>Examples of computational resources that may vary in quantity are RAM and file descriptors.</p> <p>Examples of computational resources that may vary in existence (that is, may or may not exist) are graphics cards and device drivers.</p> <p>Examples of computational resources that may vary in version are operating systems and device drivers.</p>
Conformance Tests	All tests in the Test Suite for an indicated Technology Under Test, as distributed by the Maintenance Lead, excluding those tests on the Exclude List for the Technology Under Test.
Documented	Made technically accessible and made known to users, typically by means such as marketing materials, product documentation, usage messages, or developer support programs.
Exclude List	The most current list of tests, distributed by the Maintenance Lead, that are not required to be passed to certify conformance. The Maintenance Lead may add to the Exclude List for that Test Suite as needed at any time, in which case the updated Exclude List supplants any previous Exclude Lists for that Test Suite.
Libraries	<p>The class libraries, as specified through the Java Community Process (JCP), for the Technology Under Test.</p> <p>The Libraries for JavaBeans Activation Framework Version 1.2 are listed at the end of this chapter.</p>
Location Resource	<p>A location of classes or native libraries that are components of the test tools or tests, such that these classes or libraries may be required to exist in a certain location in order to satisfy the requirements of the test suite.</p> <p>For example, classes may be required to exist in directories named in a CLASSPATH variable, or native libraries may be required to exist in directories named in a PATH variable.</p>
Maintenance Lead	The Java Community Process member responsible for maintaining the Specification, reference implementation, and TCK for the Technology. Oracle is the Maintenance Lead for JavaBeans Activation Framework Version 1.2.
Operating Mode	<p>Any Documented option of a Product that can be changed by a user in order to modify the behavior of the Product.</p> <p>For example, an Operating Mode can be binary (enable/disable optimization), an enumeration (select from a list of protocols), or a range (set the maximum number of active threads).</p> <p>Note that an Operating Mode may be selected by a command line switch, an environment variable, a GUI user interface element, a configuration or control file, etc.</p>
Product	A licensee product in which the Technology Under Test is implemented or incorporated, and that is subject to compatibility testing.

Table 2–1 (Cont.) Definitions

Term	Definition
Product Configuration	A specific setting or instantiation of an Operating Mode. For example, a Product supporting an Operating Mode that permits user selection of an external encryption package may have a Product Configuration that links the Product to that encryption package.
Resource	A Computational Resource, a Location Resource, or a Security Resource.
Rules	These definitions and rules in this Compatibility Requirements section of this User's Guide.
Security Resource	A security privilege or policy necessary for the proper execution of the Test Suite. For example, the user executing the Test Suite will need the privilege to access the files and network resources necessary for use of the Product.
Specifications	The documents produced through the Java Community Process that define a particular Version of a Technology. The Specifications for the Technology Under Test are referenced later in this chapter.
Technology	Specifications and a reference implementation produced through the Java Community Process.
Technology Under Test	Specifications and the reference implementation for JavaBeans Activation Framework Version 1.2.
Test Suite	The requirements, tests, and testing tools distributed by the Maintenance Lead as applicable to a given Version of the Technology.
Version	A release of the Technology, as produced through the Java Community Process.

2.2.2 Rules for JavaBeans Activation Framework Version 1.2 Products

The following rules apply for each version of an operating system, software component, and hardware platform Documented as supporting the Product:

JAF1 The Product must be able to satisfy all applicable compatibility requirements, including passing all Conformance Tests, in every Product Configuration and in every combination of Product Configurations, except only as specifically exempted by these Rules.

For example, if a Product provides distinct Operating Modes to optimize performance, then that Product must satisfy all applicable compatibility requirements for a Product in each Product Configuration, and combination of Product Configurations, of those Operating Modes.

JAF1.1 If an Operating Mode controls a Resource necessary for the basic execution of the Test Suite, testing may always use a Product Configuration of that Operating Mode providing that Resource, even if other Product Configurations do not provide that Resource. Notwithstanding such exceptions, each Product must have at least one set of Product Configurations of such Operating Modes that is able to pass all the Conformance Tests.

For example, a Product with an Operating Mode that controls a security policy (i.e., Security Resource) which has one or more Product Configurations that cause Conformance Tests to fail may be tested using a Product Configuration that allows all Conformance Tests to pass.

JAF1.2 A Product Configuration of an Operating Mode that causes the Product to report only version, usage, or diagnostic information is exempted from these compatibility rules.

JAF1.3 An API Definition Product is exempt from all functional testing requirements defined here, except the signature tests.

JAF2 Some Conformance Tests may have properties that may be changed. Properties that can be changed are identified in the configuration interview. Properties that can be changed are identified in the JavaTest Environment (.jte) files in the lib directory of the Test Suite installation. Apart from changing such properties and other allowed modifications described in this User's Guide (if any), no source or binary code for a Conformance Test may be altered in any way without prior written permission. Any such allowed alterations to the Conformance Tests would be posted to the [Java Licensee Engineering] web site and apply to all licensees.

JAF3 The testing tools supplied as part of the Test Suite or as updated by the Maintenance Lead must be used to certify compliance.

JAF4 The Exclude List associated with the Test Suite cannot be modified.

JAF5 The Maintenance Lead can define exceptions to these Rules. Such exceptions would be made available to and apply to all licensees.

JAF6 All hardware and software component additions, deletions, and modifications to a Documented supporting hardware/software platform, that are not part of the Product but required for the Product to satisfy the compatibility requirements, must be Documented and available to users of the Product.

For example, if a patch to a particular version of a supporting operating system is required for the Product to pass the Conformance Tests, that patch must be Documented and available to users of the Product.

JAF7 The Product must contain the full set of public and protected classes and interfaces for all the Libraries. Those classes and interfaces must contain exactly the set of public and protected methods, constructors, and fields defined by the Specifications for those Libraries. No subsetting, supersetting, or modifications of the public and protected API of the Libraries are allowed except only as specifically exempted by these Rules.

JAF7.1 If a Product includes Technologies in addition to the Technology Under Test, then it must contain the full set of combined public and protected classes and interfaces. The API of the Product must contain the union of the included Technologies. No further modifications to the APIs of the included Technologies are allowed.

JAF8 Except for tests specifically required by this TCK to be recompiled (if any), the binary Conformance Tests supplied as part of the Test Suite or as updated by the Maintenance Lead must be used to certify compliance.

JAF9 The functional programmatic behavior of any binary class or interface must be that defined by the Specifications.

2.3 JavaBeans Activation Framework Version 1.2 Test Appeals Process

Oracle has a well established process for managing challenges to its Java technology Test Suites and plans to continue using a similar process in the future. Oracle, as JavaBeans Activation Framework Maintenance Lead, will authorize representatives from the Java Partner Engineering group to be the point of contact for all test challenges. Typically this will be the engineer assigned to a company as part of its JavaBeans Activation Framework TCK support.

If a test is determined to be invalid in function or if its basis in the specification is suspect, the test may be challenged by any licensee of the JavaBeans Activation Framework TCK. Each test validity issue must be covered by a separate test challenge. Test validity or invalidity will be determined based on its technical correctness such as:

- ⤵ Test has bugs (i.e., program logic errors).
- ⤵ Specification item covered by the test is ambiguous.

- ⌘ Test does not match the specification.
- ⌘ Test assumes unreasonable hardware and/or software requirements.
- ⌘ Test is biased to a particular implementation.

Challenges based upon issues unrelated to technical correctness as defined by the specification will normally be rejected.

Test challenges must be made in writing to Java Partner Engineering and include all relevant information as described in [Example 2–1, "Test Challenge Form"](#). The process used to determine the validity or invalidity of a test (or related group of tests) is described in [Section 2.3.1, "JavaBeans Activation Framework Version 1.2 TCK Test Appeals Steps."](#)

All tests found to be invalid will either be placed on the Exclude List for that version of the JavaBeans Activation Framework TCK or have an alternate test made available.

- ⌘ Tests that are placed on the Exclude List will be placed on the Exclude List within one business day after the determination of test validity. The new Exclude List will be made available to all JavaBeans Activation Framework TCK licensees on the JavaBeans Activation Framework TCK website.
- ⌘ Oracle, as Maintenance Lead has the option of creating alternative tests to address any challenge. Alternative tests (and criteria for their use) will be made available on the JavaBeans Activation Framework TCK website.

Note: Passing an alternative test is deemed equivalent to passing the original test.

2.3.1 JavaBeans Activation Framework Version 1.2 TCK Test Appeals Steps

1. **JavaBeans Activation Framework TCK licensee writes a test challenge to Java Licensee Engineering contesting the validity of one or a related set of JavaBeans Activation Framework tests.**

A detailed justification for why each test should be invalidated must be included with the challenge as described in [Example 2–1, "Test Challenge Form"](#).

2. **Java Licensee Engineering evaluates the challenge.**

If the appeal is incomplete or unclear, it is returned to the submitting licensee for correction. If all is in order, Java Licensee Engineering will check with the responsible test developers to review the purpose and validity of the test before writing a response as described in [Example 2–2, "Test Challenge Response Form"](#). Java Licensee Engineering will attempt to complete the response within 5 business days. If the challenge is similar to a previously rejected test challenge (i.e., same test and justification), Java Licensee Engineering will send the previous response to the licensee.

3. **The challenge and any supporting materials from test developers is sent to the specification engineers for evaluation.**

A decision of test validity or invalidity is normally made within 15 working days of receipt of the challenge. All decisions will be documented with an explanation of why test validity was maintained or rejected.

4. **The licensee is informed of the decision and proceeds accordingly.**

If the test challenge is approved and one or more tests are invalidated, Oracle places the tests on the Exclude List for that version of the JavaBeans Activation Framework TCK (effectively removing the test(s) from the Test Suite). All tests placed on the Exclude List

will have a bug report written to document the decision and made available to all licensees through the bug reporting database. If the test is valid but difficult to pass due to hardware or operating system limitations, Oracle may choose to provide an alternate test to use in place of the original test (all alternate tests are made available to the licensee community).

5. **If the test challenge is rejected, the licensee may choose to escalate the decision to the Executive Committee (EC), however, it is expected that the licensee would continue to work with Oracle to resolve the issue and only involve the EC as a last resort.**

2.3.2 Test Challenge and Response Forms

[Example 2–1](#) shows the test challenge information you must provide to Java Licensee Engineering to initiate a challenge, and [Example 2–2](#) shows the test challenge response format.

Example 2–1 Test Challenge Form

Test Challenger Name and Company:
Specification Name(s) and Version(s):
Test Suite Name and Version:
Exclude List Version:
Test Name:
Complaint (argument for why test is invalid):
.jtr file of the failing test:
Console log of the JavaTest harness and device with all debugging flags turned on (if applicable):
.jti or .jte file for the test run:
Startup scripts for the JavaTest harness and agent (if applicable):

Example 2–2 Test Challenge Response Form

Test Defender Name and Company:
Test Defender Role in Defense (e.g., test developer, Maintenance Lead, etc.):
Specification Name(s) and Version(s):
Test Suite Name and Version:
Test Name:
Defense (argument for why test is valid):
[Multiple challenges and corresponding responses may be listed here.]
Implications of test invalidity (e.g., other affected tests and test framework code, creation or exposure of ambiguities in spec (due to unspecified requirements), invalidation of the reference implementation, creation of serious holes in test suite):
Alternatives (e.g., are alternate test(s) appropriate?):

2.4 Specifications for JavaBeans Activation Framework Version 1.2

The Specifications for JavaBeans Activation Framework 1.2 are found on the JCP web site at <http://jcp.org/en/jsr/detail?id=925>.

2.5 Libraries for JavaBeans Activation Framework Version 1.2

The following is the list of packages that constitute the required class libraries for JavaBeans Activation Framework:

javax.activation

This chapter explains how to install the JavaBeans Activation Framework 1.2 (JAF) 1.2 software.

After installing the software according to the instructions in this chapter, proceed to [Chapter 4, "Setup and Configuration,"](#) for instructions on configuring your test environment.

3.1 Obtaining the JAF 1.2 Reference Implementation

You can obtain the JAF Reference Implementation (RI), Version 1.2 software from the Java Community Process (<http://jcp.org/en/home/index>) web site. The JAF RI software is not necessary for running the JAF TCK, but it can be useful as a test base for familiarizing yourself with the TCK before testing your own JAF implementation.

3.2 Installing the JAF Software

Before you can run the JAF TCK tests, you must install and set up the following software components:

- ⌘ Java SE 7 software
 - ⌘ JAF TCK, Version 1.2 software
 - ⌘ An implementation of the JAF 1.2 Specification
1. Install the Java SE 7 software, if it is not already installed.

Download and install the Java SE 7 software from the <http://www.oracle.com/technetwork/java/javase/downloads/index.html> Web site. Refer to the installation instructions that accompany the software for additional information.

2. Install the JAF TCK 1.2 software.

- a. Copy or download the JAF TCK software to your local system.

You can obtain the JAF TCK software from the Java Licensee Engineering (<https://javapartner.oracle.com>) Web site. The JAF TCK software is located in the Web site's Download Center area.

- b. Change to the directory in which you want to install the JAF TCK software:

```
cd install_directory
```

- c. Use the `unzip` command to extract the bundle:

```
unzip jaftck-1.2_dd-Mmm-YYYY.zip
```

where *dd* indicates the day, *Mmm* indicates the month, and *YYYY* indicates the year in which the TCK bundle was created. For example, the JAF TCK bundle name could be `jaftck-1.2_dd-Mmm-YYYY.zip`.

When the bundle is unzipped, the `jaftck` directory is created. The *install_directory*/`jaftck` directory is the test suite home, `<TS_HOME>`.

3. Install the JAF implementation to be tested.

Before testing your own JAF implementation, it is recommended that you run the JAF TCK against the JAF RI to familiarize yourself with the JAF TCK suite and JavaTest software. See [Section 3.1, "Obtaining the JAF 1.2 Reference Implementation,"](#) for more information.

Setup and Configuration

This chapter describes how to set up the JAF TCK and JavaTest harness software. Before proceeding with the instructions in this chapter, be sure to install all required software, as described in [Chapter 3, "Installation."](#)

After completing the instructions in this chapter, proceed to [Chapter 5, "Executing Tests,"](#) for instructions on running the JAF TCK.

4.1 Configuration Overview

Setting up and configuring the JAF TCK and JavaTest harness involves three general steps:

- ? [Configuring Your Environment to Run the JAF TCK](#)
- ? [Using the JavaTest Harness Software](#)
- ? [Using the JavaTest Harness Configuration GUI](#)

Note: The third general step, [Section 4.4, "Using the JavaTest Harness Configuration GUI,"](#) is not necessary if you plan on running the JavaTest harness in command-line mode. See [Section 4.3, "Using the JavaTest Harness Software,"](#) for more information about running tests in command-line mode.

The remainder of this chapter explains these steps in detail.

4.2 Configuring Your Environment to Run the JAF TCK

This section describes how to configure the JAF TCK for your environment. After configuring your environment, continue with the instructions in [Section 4.3, "Using the JavaTest Harness Software."](#)

Note: In these instructions, variables in angle brackets need to be expanded for each platform. For example, `<TS_HOME>` becomes `$TS_HOME` on Solaris/Linux and `%TS_HOME%` on Windows. In addition, the forward slashes (/) used in all of the examples need to be replaced with backslashes (\) for Windows. Finally, be sure to use the appropriate separator for your operating system when specifying multiple path entries (; on Windows, : on UNIX/Linux).

1. Set the following environment variables in your shell environment:

- a. `JAVA_HOME` to the directory in which Java SE 7 is installed
 - b. `TS_HOME` to the directory in which the JAF TCK 1.2 software is installed
 - c. `PATH` to include the `JAVA_HOME/bin` and `<TS_HOME>/tools/ant/bin` directories
2. Edit your `<TS_HOME>/lib/jaf.jte` file, setting the `LOCAL_CLASSES` property to point to the JAF RI classes/jars.
3. Edit your `<TS_HOME>/lib/jaf.jte` file, setting the `ENDORSED_DIRS` property to the location of the RI API jars for those technologies you wish to override that exist within the JDK.
4. Run the JavaTest harness in GUI or command-line mode, as described in [Section 4.3, "Using the JavaTest Harness Software."](#)

4.3 Using the JavaTest Harness Software

There are two general ways to run the JAF TCK test suite using the JavaTest harness software:

- Through the JavaTest GUI; if using this method, please continue on to [Section 4.4, "Using the JavaTest Harness Configuration GUI."](#)
- In JavaTest batch mode, from the command line in your shell environment; if using this method, please proceed directly to [Chapter 5, "Executing Tests."](#)

4.4 Using the JavaTest Harness Configuration GUI

You can use the JavaTest harness GUI to modify general test settings and to quickly get started with the default JAF TCK test environment. This section covers the following topics:

- [Configuration GUI Overview](#)
- [Starting the Configuration GUI](#)
- [Configuring the JavaTest Harness to Run the JAF TCK Tests](#)
- [Modifying the Default Test Configuration](#)

Note: It is only necessary to proceed with this section if you want to run the JavaTest harness in GUI mode. If you plan to run the JavaTest harness in command-line mode, skip the remainder of this chapter, and continue with [Chapter 5, "Executing Tests."](#)

4.4.1 Configuration GUI Overview

In order for the JavaTest harness to execute the test suite, it requires information about how your computing environment is configured. The JavaTest harness requires two types of configuration information:

- **Test environment:** This is data used by the tests. For example, the path to the Java runtime, how to start the product being tested, network resources, and other information required by the tests in order to run. This information does not change frequently and usually stays constant from test run to test run.
- **Test parameters:** This is information used by the JavaTest harness to run the tests. Test parameters are values used by the JavaTest harness that determine which tests in the test suite are run, how the tests should be run, and where the test reports are stored. This information often changes from test run to test run.

The first time you run the JavaTest harness software, you are asked to specify the test suite and work directory that you want to use. (These parameters can be changed later from within the JavaTest harness GUI.)

Once the JavaTest harness GUI is displayed, whenever you choose **Run Tests** and then **Start** to begin a test run, the JavaTest harness determines whether all of the required configuration information has been supplied:

- ⌘ If the test environment and parameters have been completely configured, the test run starts immediately.
- ⌘ If any required configuration information is missing, the configuration editor displays a series of questions asking you the necessary information. This is called the configuration interview. When you have entered the configuration data, you are asked if you wish to proceed with running the test.

4.4.2 Starting the Configuration GUI

Before you start the JavaTest harness software, you must have a valid test suite and Java SE 7 installed on your system.

The JAF TCK includes an Ant script that is used to execute the JavaTest harness from the <TS_HOME> directory. Using this Ant script to start the JavaTest harness is part of the procedure described in [Section 4.4.3, "Configuring the JavaTest Harness to Run the JAF TCK Tests."](#)

When you execute the JavaTest harness software for the first time, the JavaTest harness displays a Welcome dialog box that guides you through the initial startup configuration.

- ⌘ If it is able to open a test suite, the JavaTest harness displays a Welcome to JavaTest dialog box that guides you through the process of either opening an existing work directory or creating a new work directory as described in the JavaTest online help.
- ⌘ If the JavaTest harness is unable to open a test suite, it displays a Welcome to JavaTest dialog box that guides you through the process of opening both a test suite and a work directory as described in the JavaTest documentation.

After you specify a work directory, you can use the Test Manager to configure and run tests as described in [Section 4.4.3, "Configuring the JavaTest Harness to Run the JAF TCK Tests."](#)

4.4.3 Configuring the JavaTest Harness to Run the JAF TCK Tests

You only need to complete all these steps the first time you start the JavaTest test harness. After you complete these steps, you can either run all of the tests by completing the steps in [Section 5.1, "Starting JavaTest,"](#) or run a subset of the tests by completing the steps in [Section 5.2, "Running a Subset of the Tests."](#)

The answers you give to some of the configuration interview questions are specific to your site. For example, the name of the host on which the JavaTest harness is running. Other configuration parameters can be set however you wish. For example, where you want test report files to be stored.

1. Start the JavaTest test harness:

```
ant gui
```

The JavaTest Quick Start screen displays, and you are prompted to **Start**, **Resume**, or **Browse** the test suite.

2. Select **Start a new test run**, and then click **Next**.

You are prompted to create a new configuration or use a configuration template.

3. Select **Create a new configuration**, and then click **Next**.
You are prompted to select a test suite.
4. Accept the default suite (`<TS_HOME>/src`), and then click **Next**.
You are prompted to specify a work directory to use to store your test results.
5. Type a work directory name or use the **Browse** button to select a work directory, and then click **Next**.
You are prompted to start the configuration editor or start a test run. At this point, the JAF TCK is configured to run the default test suite.
6. Deselect the **Start the configuration editor** option, select the **Start test run** option, and then click **Finish**.
The test run is started.

4.4.4 Modifying the Default Test Configuration

The JavaTest GUI enables you to configure numerous test options. These options are divided into two general dialog box groups:

- ? **Group 1:** Available from the JavaTest **Configure/Change Configuration** submenus, the following options are displayed in a tabbed dialog box:
 - Tests to Run
 - Exclude List
 - Keywords
 - Prior Status
 - Test Environment
 - Concurrency
 - Timeout Factor
- ? **Group 2:** Available from the JavaTest **Configure/Change Configuration/Other Values** submenu, or by pressing **Ctrl+E**, the following options are displayed in a paged dialog box:
 - Environment Files
 - Test Environment
 - Specify Tests to Run
 - Specify an Exclude List

Note that there is some overlap between the functions in these two dialog boxes; for those functions use the dialog that is most convenient for you. Please refer to the JavaTest Harness documentation or the online help for complete information about these various options.

Executing Tests

The JAF TCK uses the JavaTest harness to execute the tests in the test suite. For detailed instructions that explain how to run and use JavaTest, see the *JavaTest User's Guide and Reference* in the documentation bundle.

This chapter includes the following topics:

- [Starting JavaTest](#)
- [Running a Subset of the Tests](#)
- [Test Reports](#)

Note: The instructions in this chapter assume that you have installed and configured your test environment as described in [Chapter 3, "Installation,"](#) and [Chapter 4, "Setup and Configuration,"](#) respectively.

5.1 Starting JavaTest

There are two general ways to run the JAF TCK using the JavaTest harness software:

- Through the JavaTest GUI
- From the command line in your shell environment

5.1.1 To Start JavaTest in GUI Mode

Execute the following command:

```
ant gui
```

5.1.2 To Start JavaTest in Command-Line Mode

1. Execute the `run` target to start the JavaTest run:

```
ant run
```

5.2 Running a Subset of the Tests

5.2.1 To Run a Subset of Tests in GUI Mode

1. From the JavaTest main menu, click **Configure**, then click **Change Configuration**, and then click **Tests to Run**.

The tabbed Configuration Editor dialog box is displayed.

2. Click **Specify** from the option list on the left.
3. Select the tests you want to run from the displayed test tree, and then click **Done**.

You can select entire branches of the test tree, or use **Ctrl+Click** or **Shift+Click** to select multiple tests or ranges of tests, respectively, or select just a single test.

4. Save the file, and then click **Done**.
5. Click **Run Tests**, and then click **Start** to run the tests you selected.

Alternatively, you can right-click the test you want from the test tree in the left section of the JavaTest main window, and choose **Execute These Tests** from the menu.

5.2.2 To Run a Subset of Tests in Command-Line Mode

1. Start the test run by executing the following command:

```
ant -Dtests=api/javax/activation/DataHandler run
```

The tests in <TS_HOME>/tests/api/javax/activation/DataHandler and its subdirectories are run.

5.2.3 To Run a Subset of Tests in Batch Mode Based on Prior Result Status

You can run certain tests in batch mode based on the test's prior run status by specifying the `priorStatus` system property when invoking `ant`.

Invoke `ant` with the `priorStatus` property.

The accepted values for the `priorStatus` property are any combination of the following:

```
? fail
? pass
? error
? notRun
```

For example, you could run all the JAF tests with a status of failed and error by invoking the following command:

```
ant -DpriorStatus="fail,error" run
```

Note that multiple `priorStatus` values must be separated by commas.

5.3 Test Reports

A set of report files is created for every test run. These report files can be found in the report directory you specify. After a test run is completed, the JavaTest harness writes HTML reports for the test run. You can view these files in the JavaTest ReportBrowser when running in GUI mode, or in the web browser of your choice outside the JavaTest interface.

To see all of the HTML report files, enter the URL of the `report.html` file. This file is the root file that links to all of the other HTML reports.

The JavaTest harness also creates a `summary.txt` file in the report directory that you can open in any text editor. The `summary.txt` file contains a list of all tests that were run, their test results, and their status messages.

5.3.1 Creating Test Reports

5.3.1.1 To Create a Test Report in GUI Mode

1. From the JavaTest main menu, click **Report**, then click **Create Report**.

You are prompted to specify a directory to use for your test reports.

2. Specify the directory you want to use for your reports, and then click **OK**.

Use the **Filter** list to specify whether you want to generate reports for the current configuration, all tests, or a custom set of tests.

You are asked whether you want to view the report now.

3. Click **Yes** to display the new report in the JavaTest ReportBrowser.

5.3.1.2 To Create a Test Report in Command-Line Mode

Specify where you want to create the test report.

1. To specify the report directory from the command line at runtime, use:

```
ant -Dreport.dir="report_dir"
```

Reports are written for the last test run to the directory you specify.

2. To specify the default report directory, set the `report.dir` property in `<TS_HOME>/lib/jaf.jte`.

For example, `report.dir="/home/josephine/reports"`.

3. To disable reporting, set the `report.dir` property to `"none"`, either on the command line or in `jaf.jte`.

For example:

```
ant -Dreport.dir="none"
```

5.3.2 Viewing an Existing Test Report

5.3.2.1 To View an Existing Report in GUI Mode

1. From the JavaTest main menu, click **Report**, then click **Open Report**.

You are prompted to specify the directory containing the report you want to open.

2. Select the report directory you want to open, and then click **Open**.

The selected report set is opened in the JavaTest ReportBrowser.

5.3.2.2 To View an Existing Report in Command-Line Mode

Use the Web browser of your choice to view the `report.html` file in the report directory you specified from the command line or in `jaf.jte`.

Debugging Test Problems

There are a number of reasons that tests can fail to execute properly. This chapter provides some approaches for dealing with these failures.

Note: Most of these suggestions are only relevant when running the test harness in GUI mode.

6.1 Overview

The goal of a test run is for all tests in the test suite that are not filtered out to have passing results. If the root test suite folder contains tests with errors or failing results, you must troubleshoot and correct the cause to satisfactorily complete the test run.

- ⌘ **Errors:** Tests with errors could not be executed by the JavaTest harness. These errors usually occur because the test environment is not properly configured.
- ⌘ **Failures:** Tests that fail were executed but had failing results.

The Test Manager GUI provides you with a number of tools for effectively troubleshooting a test run. See the *JavaTest User's Guide* and JavaTest online help for detailed descriptions of the tools described in this chapter.

6.2 Test Tree

Use the test tree in the JavaTest GUI to identify specific folders and tests that had errors or failing results. Color codes are used to indicate status as follows:

- ⌘ **Green:** Passed
- ⌘ **Blue:** Test Error
- ⌘ **Red:** Failed to pass test
- ⌘ **White:** Test not run
- ⌘ **Gray:** Test filtered out (not run)

6.3 Folder Information

Click a folder in the test tree in the JavaTest GUI to display its tabs.

Choose the **Error** and the **Failed** tabs to view the lists of all tests in and under a folder that were not successfully run. You can double-click a test in the lists to view its test information.

6.4 Test Information

To display information about a test in the JavaTest GUI, click its icon in the test tree or double-click its name in a folder status tab. The tab contains detailed information about the test run and, at the bottom of the window, a brief status message identifying the type of failure or error. This message may be sufficient for you to identify the cause of the error or failure.

If you need more information to identify the cause of the error or failure, use the following tabs listed in order of importance:

- ⌵ **Test Run Messages** contains a Message list and a Message section that display the messages produced during the test run.
- ⌵ **Test Run Details** contains a two-column table of name/value pairs recorded when the test was run.
- ⌵ **Configuration** contains a two-column table of the test environment name/value pairs derived from the configuration data actually used to run the test.

6.5 Report Files

Report files are another good source of troubleshooting information. You may view the individual test results of a batch run in the JavaTest Summary window, but there are also a wide range of HTML report files that you can view in the JavaTest ReportBrowser or in the external browser or your choice following a test run. See [Section 5.3, "Test Reports,"](#) for more information.

6.6 Configuration Failures

Configuration failures are easily recognized because many tests fail the same way. When all your tests begin to fail, you may want to stop the run immediately and start viewing individual test output. However, in the case of full-scale launching problems where no tests are actually processed, report files are usually not created.

Frequently Asked Questions

This appendix contains the following questions.

- [Where do I start to debug a test failure?](#)
- [How do I restart a crashed test run?](#)
- [What would cause tests be added to the exclude list?](#)

A.1 Where do I start to debug a test failure?

From the JavaTest GUI, you can view recently run tests using the Test Results Summary, by selecting the red **Failed** tab or the blue **Error** tab. See [Chapter 6, "Debugging Test Problems,"](#) for more information.

A.2 How do I restart a crashed test run?

If you need to restart a test run, you can figure out which test crashed the test suite by looking at the `harness.trace` file. The `harness.trace` file is in the report directory that you supplied to the JavaTest GUI or parameter file. Examine this trace file, then change the JavaTest GUI initial files to that location or to a directory location below that file, and restart. This will overwrite only `.jtr` files that you rerun. As long as you do not change the value of the GUI work directory, you can continue testing and then later compile a complete report to include results from all such partial runs.

A.3 What would cause tests be added to the exclude list?

The JavaTest exclude file (`*.jtx`) contains all tests that are not required to be run. The following is a list of reasons for a test to be included in the Exclude List:

- An error in a reference implementation that does not allow the test to execute properly has been discovered.
- An error in the specification that was used as the basis of the test has been discovered.
- An error in the test has been discovered.

What would cause tests be added to the exclude list?
